Features

1. Budget-friendly!

Chelonia, the budget-friendly robot, was created to suit the needs of schools, labs, and businesses on a tight budget. Chelonia is the most affordable robot in its class, It's small!

It's small too! Chelonia measures just 138mm x 178mm x 192mm (L x W x H), making it about a quarter of the size of its predecessor. Imagine carrying Chelonia in your backpack, developing and testing your programs wherever you go.

2. Diverse Sensor Integration:

The Chelonia Base Version includes a comprehensive set of sensors, such as infrared (IR) sensors for proximity detection, ultrasonic sensors for accurate distance measurement, gas sensors for environmental monitoring, inertial measurement units (IMUs) for orientation tracking, RFID tags for identification, and sound sensors for audio interaction.

3. Versatile Motor Control:

The robot is equipped with a robust motor control system, allowing users to program precise movements. Motor pins are clearly defined, making it easy to understand and experiment with forward, backward, left, and right movements.

5. Bluetooth Connectivity:

Utilize Bluetooth communication to control the Chelonia Robot remotely. Commands can be sent through a Bluetooth module, providing wireless flexibility and enabling users to experiment with different control mechanisms.

6. Educational Platform:

Tailored for educational purposes, the Chelonia Base Version is an ideal tool for students and enthusiasts to delve into the world of robotics. The robot facilitates hands-on learning, fostering a deeper understanding of robotic systems and programming.

1. Hardware Specifications

| Features | Chelonia Base version | Advanced version |
|----------------------|---|---|
| Size | | |
| Weight | | |
| Base platform | | |
| Wheels diameter | 6 cm | 7 cm |
| Microcontroller | Arduino UNO | Raspberry pi, Teensy |
| Development | | 1 31 / 3 |
| Board | | |
| Operation time | | |
| Charging time | | |
| | HC05 | HC05 |
| Bluetooth | Speed: Asynchronous: 2.1Mbps (Max) / | Speed: Asynchronous: 2.1Mbps |
| Transceiver | | (Max) / 160 kbps, Synchronous: |
| Module | Security: Authentication and encryption. | 1Mbps/1Mbps. |
| | Profiles: Bluetooth serial port. | Security: Authentication and encryption. |
| | | Profiles: Bluetooth serial port. |
| HC-SR-04 Ultrasonic | | Power Supply +5V DC |
| sensor | Working Current 15mA | Working Current 15mA |
| | Output Signal Electrical frequency signal. | Output Signal Electrical |
| | Ranging Distance 2cms – 400 cms | frequency signal. |
| | Resolution 0.3 cm | Ranging Distance 2cms – 400 |
| | | cms |
| MPU 6050 IMU | Features three-axis gyroscope and three- | Resolution 0.3 cm Features three-axis gyroscope |
| IVII O 0030 IIVIO | axis accelerometer. | and three-axis accelerometer. |
| | Communication modes: Standard iic | Communication modes: |
| | communications protocol | Standard iic communications |
| | Chip built-in 16bit ad converter with16-bit | |
| | data output. | Chip built-in 16bit ad converter |
| | Gyroscope range: 250 500 1000 2000°/s | with 16-bit data output. |
| | | Gyroscope range: 250 500 1000 2000°/s |
| BO Motor | Color Yellow | 2000 / 15 |
| Wheels(2pcs) | Diameter 65 mm | |
| | Width 26 mm | |
| | Material Rubber | |
| C | Weight 39 g | Circle Dele Deselle Thomas |
| Switch and buttons | Single Pole Double Throw switch and pushbuttons | Single Pole Double Throw switch and pushbuttons |
| 12V 2200mAh | | Brand Witty Fox |
| Rechargeable Lithium | | Voltage 11.1V |
| Battery | Battery Capacity 5200 mAh | Battery Capacity 5200 mAh |
| | Battery Type Lithium-Ion | Battery Type Lithium-Ion |
| | Dimensions 110 x 19 x 70mm | Dimensions 110 x 19 x 70mm |
| | Weight 600 grams | Weight 600 grams |

2. **Sensors**

1. MPU 6050



The MPU 6050 is a versatile motion tracking device that combines a gyroscope and accelerometer in a single integrated circuit. With its compact size and low power consumption, the MPU 6050 is an ideal choice for a wide range of applications, from wearable devices to motion-controlled gaming controllers. Its advanced motion sensing capabilities allow for precise measurement of acceleration and angular velocity in three dimensions, enabling accurate motion tracking and gesture recognition. Additionally, the MPU 6050 features onboard digital motion processing, reducing the workload on the host microcontroller and simplifying integration into existing systems. Whether you're designing a fitness tracker, stabilizing a camera, or developing a virtual reality headset, the MPU 6050 provides the performance and flexibility you need to bring your project to life. Trust in the reliability and versatility of the MPU 6050 to meet your motion sensing needs with ease and efficiency.

2. Hc-SR04 Ultrasonic Sensor



The HC-SR04 Ultrasonic Sensor is a widely used distance-measuring device that utilizes ultrasonic waves to determine the distance between the sensor and an object. This compact and affordable sensor consists of a transmitter and receiver pair, which work together to emit ultrasonic pulses and detect their reflections. By measuring the time, it takes for the ultrasonic waves to travel to the object and back, the HC-SR04 can accurately calculate the distance with high precision.

3. DHT11- Temperature & Hummidity Sensor



The DHT11 is a popular digital sensor used for measuring temperature and humidity. It features a capacitive humidity sensor and a thermistor to measure the surrounding air, providing accurate and reliable data. The DHT11 sensor operates within a temperature range of 0-50°C and a humidity range of 20-90% RH. It is widely used in environmental monitoring and control applications due to its simplicity, low cost, and ease of integration with microcontrollers like Arduino and Raspberry Pi. The sensor communicates using a single-wire protocol, making it straightforward to connect and program in various DIY projects and educational platforms.

4. IR Sensor



An Infrared (IR) sensor is an electronic device that detects and measures infrared radiation in its environment. IR sensors are commonly used for proximity detection, object detection, and distance measurement. They operate by emitting an infrared light and detecting the reflection from nearby objects. This technology is widely employed in applications such as obstacle avoidance in robotics, motion detectors in security systems, and remote-control systems. IR sensors are valued for their simplicity, low power consumption, and ability to function effectively in various lighting conditions, making them a versatile component in many electronic projects.

5. Gas Sensor



The MQ135 gas sensor is a versatile device used to detect a variety of harmful gases in the environment, including ammonia, nitrogen oxide, alcohol, benzene, smoke, and carbon dioxide. It operates by sensing changes in the conductivity of the material inside the sensor when exposed to different gas concentrations. The MQ135 is widely used in

air quality monitoring systems due to its sensitivity and reliability. It provides analog output signals that can be easily read by microcontrollers like Arduino for real-time air quality assessment. This sensor is favoured for its affordability, ease of use, and effectiveness in detecting multiple gases, making it suitable for both industrial and domestic applications.

6. HC-05 Bluetooth Module



The HC-05 Bluetooth module is a widely used wireless communication device that enables seamless serial communication between electronic devices over short distances. Operating on the Bluetooth 2.0 standard, the HC-05 module facilitates reliable and low-power data transmission between devices such as microcontrollers, smartphones, and computers. It features a simple UART interface, allowing easy integration into various projects, including robotics, home automation, and IoT applications. The HC-05 module supports both master and slave modes, making it versatile for different communication setups. With its compact size, low cost, and robust performance, the HC-05 Bluetooth module is a popular choice for adding wireless connectivity to electronic projects.

6. HC-05 Bluetooth Module



The RFID (Radio-Frequency Identification) module is a technology that allows for the wireless transmission of data between a reader and an RFID tag. RFID systems consist of three main components: the RFID reader, the RFID tag, and the antenna. The reader emits radio waves that activate the RFID tag, which then transmits its unique identification code back to the reader. RFID modules are commonly used for tracking and identification purposes in various industries, including access control, inventory management, and asset tracking. They offer advantages such as fast and contactless data transmission, high durability, and the ability to read multiple tags simultaneously. With their versatility and reliability, RFID modules play a crucial role in automating processes and improving efficiency in numerous applications.