On the microstructure and tribological properties of pulse electrodeposited Ni-B4C-TiC nano composite coating on AZ80 magnesium alloy

DP Pushpanathan, N Alagumurthi... - Surfaces and Interfaces, 2020 - Elsevier Abstract Ni-B 4 C-TiC nanocomposite coating was successfully developed on AZ80 magnesium alloy by electrocodeposition technique using square wave form of pulse current. The duty cycle and the current density were varied and the frequency of the pulse current ...

Comparative assessment on heat transfer characteristics of a Truck Radiator using variousnano-additives

..., K Velmurugan, N Alagumurthi... - autrj.com

The thermal performance of tractor radiator is compared for various nanofluids of Cu/water (metal form) and with Al2O3/water, CuO/water (metal Oxide form) nanofluids as workings fluid. The maximum thermal management of nanofluid is identified and improved ...

☆ 272 >>>

Enhancement of surface properties of AZ80A magnesium alloy by titanium carbide particle reinforcement using electro-codeposition technique

DP Pushpanathan, **N Alagumurthi**... - Materials Today ..., 2020 - Elsevier Alloys of magnesium have been the most preferred materials in the manufacturing industry due to many attractive properties, especially high strength to weight ratio. However, outdoor applications of this metal is very scarce because of their poor wear and corrosion resistance ...

☆ 99 Related articles

Material removal characteristics of Al-SiO₂ composite in WEDM.

S Kumaravel, **N Alagumurthi** - Epitoanyag-Journal of Silicate ..., 2020 - epitoanyag.org.hu Demand for particle reinforced composite materials gradually increases and that leads to the use of inexpensive particles or solid waste particles as a reinforcement phase to lower the cost of the composite. Silica sand (SiO2) is an industrial waste that contributes to the ...

☆ 切 Cited by 1 Related articles All 4 versions 🔉

Acknowledgement of reviewers 2019

..., A Kumar, A Soliemanzadeh, **N Alagumurthi**... - Springer
© Qatar University and Springer Nature Switzerland AG 2020 ... A. Subramania INDIA Abdul Shakoor QATAR Adeniji Adetayo UNITED STATES Aharon Blank ISRAEL Ahmed Esmail Shalan SPAIN Ajeet Kumar INDIA Akbar Soliemanzadeh IRAN **Alagumurthi N** INDIA Alakesh Manna ...

☆ 99

International Activities of KSSC

..., A Zona, AV Raviprakash, B Prabu, **N Alagumurthi**... - dbpia.co.kr
This list is provided to encourage your citation and download from the SCIE indexed journal,
IJOSS. - An Experimental Study on After-fracture Redundancy of Continuous Span Two-girder
Bridges: Yongmyung Park, Woomdoji Joe, Jaebong Park, Minoh Hwang, Byung H. Choi - Mechanical ...

An approach of CAD/CAM data reuse for manufacturing cost estimation

MB Letaief, M Tlija, B Louhichi - International Journal of Computer ..., 2020 - Taylor & Francis ... The constants C 0 and C 1 are determined experimentally after NC machining (Ghali et al. 2017; Kumar, **Alagumurthi**, and Ramesh 2009) ... (1) g V δ = V R M × C 0 V C M × e - C 1 δ (1) (2) g δ = C 0 e - C 1 δ (2) (3) T p P O = L - D T × R o u n d U p W P r + W - D T × R o u n d U p ... Δ 99 All 2 versions

Committees: Proceedings of International Conference on Recent Trends in Mechanical and Materials Engineering ICRTMME 2019

V Dhinakaran, G Kumaresan, R Raju - AIP Conference ..., 2020 - aip.scitation.org ... Dr. T.Ramesh, NIT Tiruchirapali Dr. V.Anandakrishnan, NIT Tiruchirapali Dr. IA .Palani, IIT Indore Dr. K.Parthiban, NIT Tiruchirapali Dr. L.Karunamoorthy, Anna University, Chennai Dr. M. Kanthababu, Anna University, Chennai Dr. N. Alagumurthi, Pondicherry Engineering ...

☆ 切り

Experimental investigation of the effects of process parameters on material removal rate using Taguchi method in external cylindrical grinding operation

NC Deresse, V Deshpande, IWR Taifa - Engineering Science and ..., 2020 - Elsevier ... [6] found the following optimum cutting conditions: WS (300 rpm), DOC (0.02 mm) and wheel speed (WHS) (1750 rpm) [6]. Alagumurthi et al ... Smaller the better, Minimise the response, A target (optimal) value of zero that are non-negative, SNR = - 10 × log ∑ X 2 / n ...

DD Cited by 3 Related articles All 4 versions

Optimization of Wire Cut EDM Process Parameters of Al/SiO₂ Composites Using Taguchi Method

N Vinayagam, SJ Muthiya - 2020 - sae.org

... 10. Kumaravel, MS, Alagumurthy, N., and Thirunavukkarasu, V., "Experimental Analysis of Wear Characteristics of MMC ... 12. Kumaravel, MS, Alagumurthi, N., and Mathiyalagan, P., "Development of Aluminium-Silica Sand Metal Matrix Composite and Its Improved Hardness ...

☆

All 2 versions