

shopping > JS dbshop.js > ...

```
1  const mysql = require("mysql");
2
3  const connection = mysql.createConnection({
4    host: "localhost",
5    user: "root",
6    password: "info123",
7    database: "shopping2"
8  });
9
10 connection.connect(function(err) {
11   if (err) {
12     console.log("Connection Failed!");
13     throw err;
14   }
15
16   console.log("Connected Successfully!");
17
18   // Insert into product table
19   const productSql = `
20     INSERT INTO product (pname, category, price)
21     VALUES
22     ('pizza', 'food', 200),
23     ('dabeli', 'food', 80),
24     ('noodles', 'food', 300)
25   `;
26
27   connection.query(productSql, function(err, result) {
```

PROBLEMS

OUTPUT

DEBUG CONSOLE

TERMINAL

PORTS

```
PS D:\SHOPPING\shopping> node dbshop.js
PS D:\SHOPPING\shopping> node dbshop.js
Connected Successfully!
3 products inserted successfully.
3 customers inserted successfully.
PS D:\SHOPPING\shopping> █
```

shopping > JS dbshop.js > ...

```
1  const mysql = require("mysql");
2
3  const connection = mysql.createConnection({
4    host: "localhost",
5    user: "root",
6    password: "info123",
7    database: "shopping2"
8  });
9
10 connection.connect(function(err) {
11   if (err) throw err;
12
13   console.log("Connected Successfully!");
14
15   connection.query("SELECT * FROM product", function(err, result) {
16     if (err) throw err;
17
18     console.log("Product Table:");
19     console.table(result);
20
21     connection.end();
22   });
23 });
```

PROBLEMS

OUTPUT

DEBUG CONSOLE

TERMINAL

PORTS

powershell - shopping ⚠ + ▾ ☐ 🗑 ... | 🔍 ✕

PS D:\SHOPPING\shopping> node dbshop.js

(index)	pname	category	price
0	'pizza'	'food'	200
1	'dabeli'	'food'	80
2	'noodles'	'food'	300
3	'pizza'	'food'	200
4	'dabeli'	'food'	80
5	'noodles'	'food'	300

EXPLORER ...

OPEN EDITORS 1 unsaved

- Welcome
- JS dbshop.js shopping
- JS index.js shopping
- { } package-lock.json...
- { } package.json shop...

> SHOPPING

> OUTLINE

```
shopping > JS dbshop.js > ...
1  const mysql = require("mysql");
2
3  const connection = mysql.createConnection({
4      host: "localhost",
5      user: "root",
6      password: "info123",
7      database: "shopping2"
8  });
9
10 connection.connect(function(err) {
11     if (err) throw err;
12
13     console.log("Connected Successfully!");
14
15     connection.query("SELECT * FROM customer", function(err, result) {
16         if (err) throw err;
17
18         console.log("Customer Table:");
19         console.table(result);
20
21         connection.end();
22     });
23 });
```

PROBLEMS OUTPUT DEBUG CONSOLE TERMINAL PORTS

powershell - shopping ⚠ + ▾ □ 🗑 ... | 🔍 ✕

PS D:\SHOPPING\shopping> node dbshop.js

(index)	cname	address
0	'chirag'	'gujarat'
1	'golu'	'up'
2	'amit'	'bihar'
3	'chirag'	'gujarat'
4	'golu'	'up'
5	'amit'	'bihar'

PS D:\SHOPPING\shopping>

OPEN EDITORS 1 unsaved

Welcome

< JS dbshop.js shopping

JS index.js shopping

{ } package-lock.json...

● { } package.json shop...

SHOPPING

OUTLINE

shopping > JS dbshop.js > ...

```
1  const mysql = require("mysql");
2
3  const connection = mysql.createConnection({
4    host: "localhost",
5    user: "root",
6    password: "info123",
7    database: "shopping2"
8  });
9
10 connection.connect(function(err) {
11   if (err) throw err;
12
13   console.log("Connected Successfully!");
14
15   connection.query("DELETE FROM product WHERE price=80", function(err, result) {
16     if (err) throw err;
17
18     console.log("Product deleted successfully.");
19     console.log(result);
20
21     connection.end();
22   });
23 });
```

PROBLEMS

OUTPUT

DEBUG CONSOLE

TERMINAL

PORTS

powershell - shopping ⚠

PS D:\SHOPPING\shopping> node dbshop.js

```
OkPacket {
  fieldCount: 0,
  affectedRows: 2,
  insertId: 0,
  serverStatus: 34,
  warningCount: 0,
  message: '',
  protocol41: true,
  changedRows: 0
}
```

○ PS D:\SHOPPING\shopping> |

```
mysql> SELECT * FROM product;
```

pname	category	price
pizza	food	200
noodles	food	300
pizza	food	200
noodles	food	300

```
4 rows in set (0.00 sec)
```

```
mysql> |
```

```
mysql> use mysql;
Database changed
mysql> CREATE DATABASE shopping2;
Query OK, 1 row affected (0.00 sec)
```

```
mysql> USE shopping2;
Database changed
```

```
mysql> SHOW DATABASES;
```

Database
information_schema
appon
apponix
mysql
performance_schema
shopping2
test

```
7 rows in set (0.00 sec)
```

```
mysql> USE shopping2;
```

```
Database changed
```

```
mysql> SHOW TABLES;
```

```
+-----+
| Tables_in_shopping2 |
+-----+
| customer            |
| product              |
+-----+
2 rows in set (0.01 sec)
```

```
mysql> DESC product;
```

```
+-----+-----+-----+-----+-----+-----+
| Field      | Type          | Null | Key | Default | Extra |
+-----+-----+-----+-----+-----+-----+
| pname      | varchar(25)   | YES  |     | NULL    |       |
| category   | varchar(25)   | YES  |     | NULL    |       |
| price      | int(11)       | YES  |     | NULL    |       |
+-----+-----+-----+-----+-----+-----+
3 rows in set (0.02 sec)
```

```
mysql> DESC customer;
```

```
+-----+-----+-----+-----+-----+-----+
| Field      | Type          | Null | Key | Default | Extra |
+-----+-----+-----+-----+-----+-----+
| cname      | varchar(25)   | YES  |     | NULL    |       |
| address    | varchar(25)   | YES  |     | NULL    |       |
+-----+-----+-----+-----+-----+-----+
2 rows in set (0.01 sec)
```

```
mysql> use shopping2;
```

```
Database changed
```

```
mysql> select * from product;
```

pname	category	price
pizza	food	200
dabeli	food	80
noodles	food	300

```
3 rows in set (0.00 sec)
```

```
mysql> select * from customer;
```

cname	address
chirag	gujarat
golu	up
amit	bihar

```
3 rows in set (0.00 sec)
```



```
mysql> SELECT * FROM customer;
```

+-----+-----+	
cname address	
+-----+-----+	
chirag gujarat	
amit bihar	
chirag gujarat	
amit bihar	
+-----+-----+	

```
4 rows in set (0.00 sec)
```

```
mysql> show databases;
+-----+
| Database |
+-----+
| information_schema |
| appon |
| apponix |
| mysql |
| performance_schema |
| test |
+-----+
6 rows in set (0.03 sec)
```

```
mysql> use mysql;
Database changed
mysql> CREATE DATABASE shopping2;
Query OK, 1 row affected (0.00 sec)
```

```
mysql> USE shopping2;
Database changed
mysql> SHOW DATABASES;
+-----+
| Database |
+-----+
| information_schema |
| appon |
| apponix |
| mysql |
| performance_schema |
| shopping2 |
| test |
+-----+
7 rows in set (0.00 sec)
```

```
mysql> USE shopping2;
Database changed
mysql> SHOW TABLES;
+-----+
```

```
mysql> CREATE DATABASE shopping2;  
Query OK, 1 row affected (0.00 sec)
```

```
mysql> USE shopping2;  
Database changed
```

```
mysql> SHOW DATABASES;
```

Database
information_schema
appon
apponix
mysql
performance_schema
shopping2
test

```
7 rows in set (0.00 sec)
```

```
mysql> USE shopping2;  
Database changed
```

```
mysql> SHOW TABLES;
```

Tables_in_shopping2
customer
product

```
2 rows in set (0.01 sec)
```

```
mysql> DESC product;
```

Field	Type	Null	Key	Default	Extra
pname	varchar(25)	YES		NULL	
category	varchar(25)	YES		NULL	
price	int(11)	YES		NULL	

```
3 rows in set (0.02 sec)
```

```
mysql> DESC customer;
```

Field	Type	Null	Key	Default	Extra
cname	varchar(25)	YES		NULL	
address	varchar(25)	YES		NULL	

```
2 rows in set (0.01 sec)
```

```
mysql> use shopping2;
```

```
Database changed
```

```
mysql> select * from product;
```

pname	category	price
pizza	food	200
dabeli	food	80
noodles	food	300

```
3 rows in set (0.00 sec)
```

```
mysql> select * from customer;
```

cname	address
chirag	gujarat
golu	up
amit	bihar

```
3 rows in set (0.00 sec)
```

```
mysql> SELECT * FROM product;
```

pname	category	price
pizza	food	200
noodles	food	300
pizza	food	200
noodles	food	300

```
4 rows in set (0.00 sec)
```

```
mysql> SELECT * FROM customer;
```

cname	address
chirag	gujarat
amit	bihar
chirag	gujarat
amit	bihar

```
4 rows in set (0.00 sec)
```