A Major Project

Report On

AI-DRIVEN NETWORK ATTACK FORECASTING AND THREAT DETECTION USING ADVANCED MACHINE LEARNING

Submitted to

Kommuri Pratap Reddy Institute of Technology (Autonomous)

(Affiliated to JNTUH, Approved by AICTE & Accredited by NAAC & NBA)

In partial fulfillment of the requirements for the award of the degree of

Bachelor of Technology

In

Computer Science and Engineering

By

G. MOUNIKA (23RA1A0583)

Y. MEGHANA REDDY (23RA1A0582)

MD. MUDASSIR (23RA1A0584)

K. SAINATH (23RA1A05C9)

Under the guidance of

Mr. B. Laxmi Pathi

M.Tech

KPRIT

Imagine. Innovate. Inspire.

DEPARTMENT OF COMPUTER SCIENCE AND ENGINEERING

KOMMURI PRATAP REDDY INSTITUTE OF TECHNOLOGY

(UGC AUTONOMOUS)

(Affiliated to JNTUH, Ghanpur (V), Ghatkesar (M), Medchal (D)-500088)

2023-2027

DEPARTMENT OF COMPUTER SCIENCE AND ENGINEERING

KOMMURI PRATAP REDDY INSTITUTE OF TECHNOLOGY

(UGC AUTONOMOUS)

(Ghanpur (V), Ghatkesar (M), Medchal (D)-500088)

(AFFILIATED TO JNTU, Hyderabad)



CERTIFICATE

This is to certify that the Major Project entitled **"AI-DRIVEN NETWORK ATTACK FORECASTING AND THREAT DETECTION USING ADVANCED MACHINE LEARNING "** being submitted by **G. MOUNIKA (23RA1A0583), Y. MEGHANA REDDY (23RA1A0582), MD. MUDASSIR (23RA1A0584), K. SAINATH (23RALA05C9)** in partial fulfillment for the award of Bachelor of Technology in Computer Science and Engineering to the Jawaharlal Nehru Technology University is a record of confined work carried out by them under my guidance and supervision.

Guide's signature
Mr. B. Laxmi Pathi
M. Tech
Asst. Professor
Dept. of CSE

Signature of the Head of the Dept.
Dr. K. VAMSHEE KRISHNA
M. Tech, Ph. D.
Professor
HOD CSE

Signature of External Examiner

Place: Ghanpur

Date:

DEPARTMENT OF COMPUTER SCIENCE AND ENGINEERING

KOMMURI PRATAP REDDY INSTITUTE OF TECHNOLOGY

(UGC AUTONOMOUS)

(Ghanpur (V), Ghatkesar (M), Medchal (D)-500088)

(AFFILIATED TO JNTU, Hyderabad)



DECLARATION

We,**G. MOUNIKA (23RA1A0583), Y. MEGHANA REDDY (23RA1A0582), MD. MUDASSIR (23RA1A0584), K. SAINATH (23RALA05C9)** hereby declare that the project stage-1 report titled **"AI-DRIVEN NETWORK ATTACK FORECASTING AND THREAT DETECTION USING ADVANCED MACHINE LEARNING "** under the guidance of Mr. B. LAXMI PATHI, Assistant Professor, Department of Computer Science and Engineering, Kommuri Pratap Reddy Institute of Technology, Ghanpur, is submitted in partial fulfillment of the requirements for the award of the degree of Bachelor of Technology in Computer Science and Engineering.

This is a record of bonafide work carried out by us and the results embodied in this project have not been reproduced or copied from any source. The results embodied in this thesis have not been submitted to any other University and Institute for the award of any Degree or Diploma.

G. MOUNIKA	**(23RA1A0583)**
Y. MEGHANA REDDY	**(23RA1A0582)**
MD. MUDASSIR	**(23RA1A0584)**
K. SAINATH	**(23RA1A05C9)**

ACKNOWLEDGEMENT

We manifest our heartier thankfulness pertaining to our contentment over **Mr. B. Laxmi Pathi**, Assistant Professor as a project guide with whose adroit concomitance the excellence has been exemplified in bringing out this project work with artistry. We express our gratitude to **Dr. K. Vamshee Krishna**, Head of the Department for the encouragement and assistance to us, which contribute to the successful completion of this project. This Acknowledgement will be incomplete without mentioning our sincere gratefulness to our honorable Chairman **Sri. Kommuri Pratap Reddy**, our CEO, Prof. C.D. Naidu and Principal who have been observing posing valiance in abundance, forwarding our individuality to acknowledge our project work tendentiously. At the outset we thank teaching and non-teaching staff of Dept. of CSE for providing us with good faculty and for their moral support throughout the course. A heartful and sincere gratitude to our beloved parents for their tremendous motivation and moral support. We also express the overall exhilaration and gratitude to all those who animated our project work and accentuated our stance.

G. MOUNIKA **(23RA1A0583)**
Y. MEGHANA REDDY **(23RA1A0582)**
MD. MUDASSIR **(23RA1A0584)**
K. SAINATH **(23RA1A05C9)**

Vision of the Institute

To emerge as a premier institute for high quality professional graduates who can contribute to economic and social developments of the Nation.

Mission of the Institute

Mission	Statement
IM1	To have holistic approach in curriculum and pedagogy through industry interface to meet the needs of Global Competency.
IM2	To develop students with knowledge, attitude, employability skills, entrepreneurship, research potential and professionally ethical citizens.
IM3	To contribute to advancement of Engineering & Technology that would help to satisfy the societal needs.
IM4	To preserve, promote cultural heritage, humanistic values and spiritual values thus helping in peace and harmony in the society.

Vision of the Department

To Provide Quality Education in Computer Science for the innovative professionals to work for the development of the nation.

Mission of the Department

DM1 Laying the path for contemporary skills in Computer Science through the basic knowledge of mathematics and fundamentals of engineering.

DM2 Provide latest tools and technology to the students as a part of learning Infrastructure.

DM3 Training the students towards employability and entrepreneurship to meet the societal needs.

DM4 Grooming the students with professional and social ethics.

Program Educational Objectives:

PEO's	STATEMENT
PEO1	The Graduate will continuously adapt to evolving technologies in Computer Science and Engineering, staying proficient in contemporary skills through lifelong learning.
PEO2	The graduate will prove an effective communicator as team member and have skills to develop products, offer services and innovation for realworld challenges.
PEO3	The Graduate will develop a conceptual knowledge of industry processes, tools and technologies, equipping them for professional excellence and adaptability in a dynamic technological landscape which contributes to the society at large, without disturbing the ecological balance.

Program Specific Outcomes (PSOs)

PSO1: Competent to apply mathematical methods along with basic sciences and engineering sciences as a multi-disciplinary approach for solving complex engineering problems with due consideration to environment and societal aspects.

PSO2: Provide solutions for real world problems by using modern tool usage with a broad range of programming languages and open source platforms in various computing domains for sustainable development in ethical manner.

PSO3: Implement industry-standard principles, practices and strategies for software development lifecycle and possess proficient skills and knowledge of software design process including system modelling and performance optimization.

AL-Driven Network Attack Forecasting ,Threat Detection From Network Traffic Data Using Advanced Machine Learning

ABSTRACT

Modern network infrastructures generate an enormous and continuously changing stream of traffic, making it difficult to recognize the early signals of a cyberattack before substantial damage occurs. This project introduces an AI-based network attack forecasting framework that shifts the focus from simply identifying malicious traffic to anticipating potential attack behavior from evolving network patterns**.** The system analyzes network-flow characteristics such as communication frequency, packet behavior, protocol patterns, connection statistics, and traffic anomalies to learn the difference between normal and suspicious network activity.

Rather than treating every abnormal connection as an isolated event, the proposed framework examines traffic patterns over time and assigns an attack likelihood and forecasting status to emerging network behavior. Machine learning models are used to classify potential threats, while an interactive monitoring interface presents predicted attack categories, risk levels, traffic trends, and relevant network indicators in an understandable form. The system can also provide an explanation of the major traffic characteristics contributing to a prediction, supporting faster investigation by security analysts.

The primary objective is to develop a proactive network security mechanism capable of identifying warning patterns before an attack becomes a significant incident. By combining traffic analytics, machine learning, temporal behavior analysis, and explainable security insights, the proposed approach aims to reduce dependence on purely reactive intrusion detection and provide an intelligent foundation for early cyber-threat forecasting.

Key Words: *Network Attack Forecasting, Network Traffic Intelligence, Cyber Threat Prediction, Machine Learning for Security, Traffic Anomaly Analysis, Proactive Intrusion Detection, Temporal Network Behavior, Explainable AI, Attack Risk Scoring, Network Security Analystics.*

INDEX

S.NO	CONTENT	PAGE NO.
1.	INTRODUCTION	1
	1.1 Overview	1
	1.2 Research Motivation	1
	1.3 Problem Defination	2
	1.4 Significance	2
	1.5 Advantages	2
	1.6 Applications	3
2.	LITERATURE SURVEY	4
3.	EXISTING SYSTEM	5
	3.1 Overview	5
	3.2 Traditional Network Traffic Monitoring	5
	3.3 Machine Learning Based Threat Detection	6
	3.4 Disadvantages of Existing System	6
4.	PROPOSED SYSTEM	7
	4.1 Overview	7
	4.2 Proposed System Architecture	7
	4.3 Working of Proposed System	8
	4.4 Advantages of Proposed System	9
	4.5 Applications	9
5.	SYSTEM ARCHITECTRE	10
	5.1 Overvview	10
	5.2 System Architecture Diagram	10
	5.3 Description of Architecture	10
	5.4 Working Flow	10

6.	MODULES	12
7.	UML DIAGRAMS	13
	7.1 Class Diagram	13
	7.2 Use Case Diagram	13
	7.3 Sequence Diagram	14
	7.4 Component Diagram	14
	7.5 Deployment Diagram	14
	7.6 Collaboration Diagram	15
	7.7 Activity Diagram	16
	7.8 Data Flow Diagram(DFD)	16
8.	REFERENCES	17
9.	BASE PAPER	18

DIAGRAMS

S NO	NAME OF THE DIAGRAMS	PAGE NO
1.	Fig. 3.1 Traditional Network Traffic Monitoring	5
	Fig. 3.2 Machine Learning Based Threat Detection	6
2.	Fig. 4.1 Proposed System Architecture	7
3.	Fig. 5.1 System Architecture	10
4.	Fig. 6.1 Module Architecture	12
5.	Fig. 7.1 Class Diagram	13
	Fig. 7.2 Use Case Diagram	13
	Fig. 7.3 Sequence Diagram	14
	Fig. 7.4 Component Diagram	14
	Fig. 7.5 Deployment Diagram	15
	Fig. 7.6 Collaboration Diagram	15
	Fig. 7.7 Activity Diagram	16
	Fig. 7.8 Data Flow Diagram(DFD)	16

1. INTRODUCTION

1.1 Overview

In today's digital world, computer networks play an important role in communication, data sharing, and information management. Organizations, businesses, and individuals depend on networks to perform their daily activities. However, the increasing use of networks has also increased the risk of cyberattacks. Attackers use different techniques to access systems, steal information, and interrupt network services.

Traditional network security systems mainly depend on predefined rules and methods to identify threats. These systems may fail to detect new and advanced attacks. Therefore, Artificial Intelligence (AI) and Machine Learning (ML) techniques are becoming important for improving network security.

The proposed project, "AI-Driven Network Attack Forecasting: Threat Detection from Network Traffic Data Using Advanced Machine Learning," focuses on identifying suspicious network activities and predicting possible cyber threats. The system analyzes network traffic data using machine learning techniques to detect unusual patterns and classify different types of network attacks.

The proposed system also calculates risk scores for detected threats and displays the results through a dashboard. It provides alerts and AI-based security recommendations to help users understand potential risks and take preventive actions. This approach improves threat monitoring, supports early detection, and helps strengthen network security.

1.2 Research Motivation

The increasing number of cyberattacks has created a major challenge for network security. Organizations need effective methods to identify suspicious activities and protect sensitive information. Traditional security methods may not detect unknown or advanced attacks effectively.

Machine Learning provides the ability to analyze large amounts of network traffic data and identify unusual patterns. This motivates the development of an intelligent system that can detect attacks, analyze network behavior, and forecast possible future threats.

1.3 Problem Definition

Traditional network security systems mainly identify attacks using predefined rules and signatures. These methods may fail to recognize new attack patterns and advanced cyber threats.

Network traffic contains large amounts of data, making manual monitoring difficult and time-consuming. Delayed threat identification can result in data loss, unauthorized access, and network disruption.

Therefore, there is a need for an intelligent system that can analyze network traffic, detect suspicious activities, classify attacks, and predict potential security threats.

1.4 Significance

AI-driven network attack forecasting improves the ability to identify suspicious network activities. Machine Learning helps analyze traffic patterns and recognize possible attacks.

Early threat detection helps reduce security risks and supports faster responses. Risk scores and dashboard alerts make it easier to understand threats. AI-based recommendations also help users take suitable security measures.

1.5 Advantages

1. **Early Threat Detection:** Identifies suspicious network activities at an early stage.
2. **Attack Classification:** Helps identify and classify different types of network attacks.
3. **Threat Forecasting:** Uses historical traffic patterns to predict possible future threats.
4. **Improved Security:** Helps reduce the risk of cyberattacks and unauthorized access.
5. **Automated Monitoring:** Analyzes network traffic automatically and reduces manual work.
6. **Risk Score Calculation:** Assigns risk scores to detected threats based on their severity.
7. **Real-Time Alerts:** Displays security alerts to inform users about suspicious activities.
8. **AI-Based Recommendations:** Provides useful suggestions to improve network security.
9. **Better Decision Making:** Helps users understand network threats through clear dashboard results.
10. **Efficient Network Monitoring:** Makes network traffic analysis easier and more effective.

1.6 Applications

1. **Banking and Financial Systems:** Helps identify suspicious network activities and protect financial information.
2. **Healthcare Networks:** Helps protect patient information and hospital network systems.
3. **Educational Institutions:** Helps monitor college networks and detect unauthorized activities.
4. **Government Organizations:** Supports the protection of important government information and network resources.
5. **Business Organizations:** Helps companies monitor network traffic and reduce security risks.

6. **Cloud Computing:** Helps identify suspicious activities in cloud-based network environments.
7. **E-Commerce Platforms:** Helps protect online transactions and customer information.
8. **Enterprise Network Security:** Helps organizations monitor network traffic and identify potential cyber threats.

2. LITERATURE SURVEY

I. Sharafaldin et al. proposed a new intrusion detection dataset called CIC-IDS2017. Their research focused on generating realistic network traffic data containing normal activities and different types of cyberattacks. This dataset is useful for training and evaluating Machine Learning models for network attack detection.

Y. Meidan et al. proposed N-BaIoT, a network-based method for detecting IoT botnet attacks using Deep Autoencoders. Their research analyzed network traffic patterns to identify abnormal activities and detect malicious behavior. This approach demonstrated the importance of Machine Learning in identifying suspicious network activities.

A. Aldweesh et al. presented a survey on Deep Learning approaches for anomaly-based intrusion detection systems. Their research discussed different Deep Learning techniques used to identify unusual network activities. They also explained various detection methods, classification techniques, and challenges in improving intrusion detection accuracy.

S. K. Kim and Z. Zhan proposed a Machine Learning-based approach for forecasting cyberattack frequency using tumbling windows. Their research focused on predicting future cyberattack trends by analyzing historical attack data. This study highlights the importance of forecasting techniques in identifying possible future cyber threats.

Ansam Khraisat et al. presented a survey of intrusion detection systems, techniques, datasets, and challenges. Their research discussed signature-based and anomaly-based detection methods. They also explained different network attack detection techniques, commonly used datasets, and challenges in identifying unknown cyberattacks.

A. L. Buczak and E. Guven presented a survey of Data Mining and Machine Learning methods for cybersecurity intrusion detection. Their research explained different Machine Learning algorithms, data mining techniques, and datasets used for detecting cyber threats. They also discussed the challenges and importance of selecting suitable algorithms for network security.

The above studies show that Machine Learning and Deep Learning techniques are useful for analyzing network traffic and detecting cyberattacks. However, identifying unknown attacks, forecasting future threats, calculating security risk scores, and providing useful recommendations remain important challenges. These studies motivate the development of an AI-driven network attack forecasting system that combines threat detection, attack classification, historical data analysis, risk assessment, and dashboard-based security recommendations.

3. EXISTING SYSTEM

3.1 Overview

The existing network security systems mainly focus on monitoring network traffic and detecting suspicious activities using traditional security methods and basic Machine Learning techniques. These systems analyze network traffic data to identify known cyberattacks and classify network activities as normal or malicious.

Traditional Intrusion Detection Systems (IDS) use predefined rules and attack signatures to identify threats. Some Machine Learning-based systems analyze previously collected network traffic datasets to detect suspicious patterns. However, existing systems mainly concentrate on detecting current or known attacks and have limited capabilities for forecasting future cyber threats.

3.2 Traditional Network Traffic Monitoring

Traditional network monitoring systems observe incoming and outgoing network traffic to identify suspicious activities.




Fig. 3.1: Traditional Network Traffic Monitoring

3.3 Machine Learning-Based Threat Detection

Some existing systems use Machine Learning algorithms to analyze network traffic datasets and classify activities as normal or malicious.



Fig. 3.2: Machine Learning-Based Threat Detection

3.4 Disadvantages of Existing System

The major disadvantages of existing network attack detection systems are:

1. Limited detection of unknown cyberattacks.
2. Dependence on predefined rules and signatures.
3. Difficulty identifying changing attack patterns.
4. Limited forecasting of future network threats.
5. Lack of proper risk score calculation.
6. Limited centralized threat visualization.
7. Lack of intelligent security recommendations.

4. PROPOSED SYSTEM


4.1 Overview

The proposed system, AI-Driven Network Attack Forecasting and Threat Detection from Network Traffic Data Using Advanced Machine Learning, aims to improve network security by identifying suspicious activities and predicting possible cyber threats. The system uses Machine Learning (ML) techniques to analyze network traffic data and identify different types of attacks.

It collects network traffic data, processes the data, and extracts important features for analysis. The trained machine learning model classifies network activities as normal or malicious. It also analyzes historical attack patterns to forecast possible future threats. The system calculates risk scores and displays alerts and security recommendations through a user-friendly dashboard.

4.2 Proposed System Architecture

The proposed system consists of different stages, starting from network traffic data collection to threat detection and visualization. Each stage performs a specific task to improve network security.



4.3 Working of Proposed System

The proposed system works through the following steps:

1. Data Collection

Network traffic data is collected from available network traffic datasets. It contains information about normal network activities and different types of attacks.

2. Data Preprocessing

The collected data is cleaned and prepared for analysis. Unnecessary values and missing data are handled to improve the quality of the input data.

3. Feature Extraction

Important features are selected from network traffic data. These features help the machine learning model understand network activities and identify suspicious patterns.

4. Machine Learning Model

The processed data is given to the trained machine learning model. The model learns patterns from the data and helps identify normal and malicious network activities.

5. Threat Detection and Attack Classification

The system analyzes network traffic and classifies it into normal or malicious activities. It also identifies the type of attack based on the learned patterns.

6. Historical Data Analysis

The system analyzes previously recorded network attack patterns to understand repeated activities and changes in network threats.

7. Attack Forecasting

Using historical attack patterns, the system helps forecast possible future network threats. This allows users to understand potential security risks.

8. Risk Score Calculation

The system calculates a risk score based on detected suspicious activities and threat information. This helps users understand the severity of possible attacks.

9. Dashboard and Alerts

The results are displayed through a user-friendly dashboard. It shows detected attacks, risk scores, and important security alerts.

10. Security Recommendations

The system provides AI-based security recommendations to help users understand possible actions to improve network protection..

4.4 Advantages of Proposed System

The major advantages of the proposed system are:

1. Improved Threat Detection: Identifies suspicious network activities using machine learning.
2. Attack Classification: Classifies network traffic into normal and malicious activities.
3. Threat Forecasting: Uses historical patterns to forecast possible future attacks.
4. Risk Analysis: Calculates risk scores to understand threat severity.
5. Reduced Manual Work: Automates network traffic analysis.
6. Easy Monitoring: Displays security information through a dashboard.
7. Security Recommendations: Provides suggestions to improve network protection.
8. Better Decision Making: Helps users understand and respond to possible network threats.

4.5 Applications

The proposed system can be used in the following areas:

1. Banking Systems: Helps monitor suspicious network activities and possible cyberattacks.
2. Educational Institutions: Helps protect college networks and computer systems.
3. Healthcare Systems: Helps monitor network security in hospitals and healthcare organizations.
4. Business Organizations: Helps identify security threats in company networks.
5. Cloud Computing: Helps monitor network traffic and identify suspicious activities in cloud environments.
6. Government Organizations: Supports monitoring and analysis of network security threats.
7. IT Companies: Helps analyze network traffic and detect possible cyberattacks.
8. Data Centers: Helps monitor network activities and identify potential security risks.

5. SYSTEM ARCHITECTURE

5.1 Overview

System architecture describes the overall structure and working flow of the proposed project. It shows how network traffic data is collected, processed, analyzed, and displayed to the user. The system uses Machine Learning techniques to detect network attacks and forecast possible threats.

5.2 System Architecture Diagram




Fig. 5.1: System Architecture

5.3 Description of Architecture

1. Network Traffic: Collects network traffic data.
2. Data Processing: Cleans and prepares the collected data.
3. Machine Learning: Analyzes traffic patterns using a trained model.
4. Threat Detection: Identifies and classifies suspicious activities.
5. Dashboard and Alerts: Displays detected threats, risk scores, and alerts.

5.4 Working Flow

The system receives network traffic data and processes it. The Machine Learning model analyzes the data to identify suspicious activities. The system then displays the detected threats and related information through a dashboard.

6. MODULES

The proposed system consists of the following modules:

1. Data Collection Module

This module collects network traffic data from available datasets. The collected data is used to analyze normal and suspicious network activities.

2. Data Preprocessing Module

This module cleans the collected data by removing missing values, handling duplicate records, and converting the data into a suitable format for machine learning.

3. Feature Extraction Module

This module identifies important features from network traffic data, such as packet size, protocol type, connection duration, and traffic patterns. These features help in detecting network attacks.

4. Threat Detection Module

This module analyzes network traffic using machine learning techniques to identify whether the traffic is normal or suspicious.

5. Attack Classification Module

This module identifies and classifies different types of network attacks based on the patterns found in the traffic data.

6. Attack Forecasting Module

This module analyzes historical network attack patterns to predict possible future threats and identify potential security risks.

7. Risk Analysis Module

This module calculates risk scores based on detected attacks and their severity. It helps users understand the level of security risk.

8. AI-Based Security Recommendation Module


This module provides security recommendations based on detected attacks and risk levels. It helps users take appropriate steps to improve network security.

9. Frontend Module

This module provides a user-friendly interface developed using HTML, CSS, and JavaScript. It displays attack detection results, forecasting details, risk scores, and security recommendations.

10. Backend Module

This module is developed using Python and Flask. It handles dataset processing, machine learning operations, attack detection, forecasting, and communication between the frontend and backend.



7. UML DIAGRAMS

7.1 Class Diagram

The class diagram represents the main classes used in the proposed system. It shows the relationships between traffic data, preprocessing, machine learning, threat detection, forecasting, and reports.




Fig: 7.1Class Diagram

7.2 Use Case Diagram

The use case diagram shows how users and administrators interact with the system. Users can upload network traffic data, detect attacks, view forecasts, and access reports.




Fig: 7.2 Use Case Diagram

7.3 Sequence Diagram

The sequence diagram explains the step-by-step interaction between the user and system. It shows how traffic data is processed and how attack detection and forecasting results are displayed.




Fig: 7.3 Sequence Diagram

7.4 Component Diagram

The component diagram represents the major components of the system. It includes the frontend, backend, preprocessing module, machine learning module, and database.




Fig: 7.4 Component Diagram

7.5 Deployment Diagram

The deployment diagram shows how the system components are deployed and connected. It represents the user interface, application server, machine learning modules, and database.




Fig: 7.5 Deployment Diagram

7.6 Collaboration Diagram

The collaboration diagram shows how different objects communicate with each other. It explains the interaction between the user, data processing, attack detection, forecasting, and reporting modules.




Fig: 7.6 Collaboration Diagram

7.7 Activity Diagram

The activity diagram represents the workflow of the proposed system. It starts with uploading network traffic data and ends with displaying attack detection results, forecasts, and security recommendations.




Fig: 7.7 Activity Diagram

7.8 Data Flow Diagram (DFD)

The DFD shows how data moves through the system. Network traffic data is uploaded, processed, analyzed using machine learning, and converted into threat detection and forecasting results.




Fig: 7.8 Data Flow Diagram (DFD)

8. REFERENCES

[1] I. Sharafaldin, A. Habibi Lashkari, and A. A. Ghorbani, "Toward Generating a New Intrusion Detection Dataset and Intrusion Traffic Characterization," *Proceedings of the 4th International Conference on Information Systems Security and Privacy (ICISSP)*, pp. 108–116, 2018. DOI: 10.5220/0006639801080116.

[2] Y. Meidan, M. Bohadana, Y. Mathov, Y. Mirsky, A. Shabtai, D. Breitenbacher, and Y. Elovici, "N-BaIoT—Network-Based Detection of IoT Botnet Attacks Using Deep Autoencoders," *IEEE Pervasive Computing*, vol. 17, no. 3, pp. 12–22, 2018. DOI: 10.1109/MPRV.2018.03367731.

[3] A. Aldweesh, A. Derhab, and A. Z. Emam, "Deep Learning Approaches for Anomaly-Based Intrusion Detection Systems: A Survey, Taxonomy, and Open Issues," *Knowledge-Based Systems*, vol. 189, Article 105124, 2020. DOI: 10.1016/j.knosys.2019.105124.

[4] S. K. Kim and Z. Zhan, "Optimizing Cyberattack Frequency Forecasting by Advanced Machine Learning Adaptation with Tumbling Windows," *Scientific Reports*, vol. 16, Article 25911, 2026. DOI: 10.1038/s41598-026-59048-y.

[5] Canadian Institute for Cybersecurity, University of New Brunswick, "CIC-IDS2017: Intrusion Detection Evaluation Dataset," 2017.

[6] Scikit-learn Developers, "Scikit-learn: Machine Learning in Python – User Guide." Official Documentation.

[7] P. Lewis et al., "Retrieval-Augmented Generation for Knowledge-Intensive NLP Tasks," *Advances in Neural Information Processing Systems (NeurIPS)*, vol. 33, pp. 9459–9474, 2020.

[8] A. Khraisat, I. Gondal, P. Vamplew, and J. Kamruzzaman, "Survey of Intrusion Detection Systems: Techniques, Datasets and Challenges," *Cybersecurity*, Volume 2, Article 20, 2019. DOI: https://doi.org/10.1186/s42400-019-0038-7

[9]A. L. Buczak and E. Guven, "A Survey of Data Mining and Machine Learning Methods for Cyber Security Intrusion Detection," *IEEE Communications Surveys & Tutorials*, Volume 18, Issue 2, pp. 1153–1176, 2016.
DOI: https://doi.org/10.1109/COMST.2015.2494502

9.BASE PAPER

IEEE TRANSACTIONS ON NETWORK AND SERVICE MANAGEMENT (BASE PAPER REFERENCE SYSTEM)

AI-Driven Network Attack Forecasting & Threat Detection From Network Traffic Data Using Advanced Machine Learning



Salvatore J. Stolfo, PhD
Fellow, IEEE | Columbia University
Dept. of Computer Science
Email: stolfo@cs.columbia.edu



Vern Paxson, PhD
Fellow, ACM | UC Berkeley / LBNL
EECS Department
Email: vern@berkeley.edu



Yussuf Ahmed, PhD
Birmingham City University
School of Computing
Email: yussuf.ahmed@bcu.ac.uk



Taufiq Asyhari, PhD
Monash University Indonesia
Data Science Department
Email: taufiq.asyhari@monash.edu

Abstract—Network attack forecasting and threat detection are traditionally implemented as reactive tasks where security telemetry is analyzed post-hoc to detect ongoing malicious events. While effective for immediate intrusion response, standalone classification offers limited predictive intelligence regarding dynamic attack trends and operational risk trajectories. This paper presents an integrated AI-driven network security framework combining supervised threat classification, temporal attack frequency forecasting, dynamic multi-factor risk scoring, and a retrieval-augmented generation (RAG) incident explanation assistant. Labeled network-flow telemetry from benchmark datasets (CIC-IDS2017, CSE-CIC-IDS2018, UNSW-NB15) is preprocessed into continuous time-series windows. We employ supervised classifiers (Random Forest, XGBoost, SVM) alongside sequence models (LSTM, GRU, SMOreg, ARIMA) to forecast attack counts over future sliding horizons. An automated risk engine combines calibrated classifier confidence, forecasted frequency growth, anomaly magnitude, and vulnerability impact scores into a continuous metric $R \in [0, 100]$. The architecture is validated across 1,048,575 network flow observations, demonstrating predictive accuracy up to 90.4% on forecasted attack events.

Index Terms—*Network Intrusion Detection, Cyberattack Forecasting, Deep Learning, Time-Series Analysis, Sequential Minimal Optimization, Retrieval-Augmented Generation (RAG), Risk Scoring.*

I. INTRODUCTION

The relentless expansion of hyper-connected enterprise networks, hybrid cloud deployment, Internet of Things (IoT) infrastructure, and high-frequency edge computing has dramatically expanded the cyberattack surface. Modern intrusion detection systems (IDS) rely heavily on supervised and unsupervised machine learning models to identify policy violations, signature anomalies, and complex malicious flow patterns **[1]**, **[2]**. However, traditional intrusion detection operates predominantly in a *reactive mode*: an alert is produced only after malicious packets traverse the monitoring boundary.

This operational delay forces Security Operations Center (SOC) analysts into a perpetual state of fire-fighting, attempting to mitigate security incidents after damage has commenced. To bridge the gap between reactive detection and proactive cyber defense, short-term temporal forecasting of network attack frequencies is essential **[5]**, **[9]**. By aggregating flow telemetry into fixed chronological windows, statistical and deep recurrent learning models can learn temporal dependencies and estimate future attack frequencies prior to peak threat bursts.


In this work, we propose a comprehensive end-to-end framework that unifies flow-level feature engineering, multiclass threat recognition, sliding window count forecasting, dynamic multi-factor risk weighting, and evidencegrounded AI decision support.

II. RELATED WORK & THEORETICAL FOUNDATIONS

Cyberattack forecasting and network threat detection have evolved through several distinct paradigms over the past two decades. Early intrusion detection frameworks relied strictly on deterministic signature matching engines such as Snort and Zeek. While highly effective at identifying known threat payloads with negligible false-alarm rates, signature matching fails against novel zero-day exploits and polymorphic malware payloads.


A. Supervised Network Intrusion Detection

The introduction of comprehensive flow-based benchmark datasets—such as CIC-IDS2017 [1], UNSW-NB15 [4], and CSE-CIC-IDS2018 [9]—catalyzed the adoption of supervised machine learning classifiers for network anomaly recognition. Sharafaldin et al. [1] established standardized flow features including flow duration, inter-arrival times (IAT), packet length variance, and TCP header flags. Tree-based ensemble models, specifically Random Forest and Extreme Gradient Boosting (XGBoost), have consistently demonstrated superior classification metrics on tabular flow data due to their resilience to feature scale disparity and nonlinear decision boundary mapping.



B. Time-Series Analysis and Attack Frequency Forecasting

Time-series modeling in cybersecurity treats security alerts not as independent events, but as chronologically ordered sequences reflecting underlying campaign trajectories [5]. Landauer et al. surveyed temporal cybersecurity analytics, highlighting that statistical auto-regressive models (ARIMA) provide transparent baselines for stationary attack count series. However, non-stationary cyber threat events exhibiting exponential bursts are better captured by deep sequence architectures. Kim and Zhan [6] demonstrated that attention-based Long Short-Term Memory (LSTM) networks trained on tumbling temporal windows significantly outperform traditional static classifiers in predicting multi-step attack volumes.



In parallel, Ahmed et al. [9] evaluated Sequential Minimal Optimization for Regression (SMOreg) alongside Linear Regression and LSTM on the CSE-CIC-IDS2018 dataset. Their experimental findings indicated that SMOreg achieved superior Mean Absolute Error (MAE) performance when predicting downstream feature parameters across 30second window intervals, demonstrating the utility of support vector regression for rapid short-horizon forecasting.

III. PROBLEM FORMULATION & MATHEMATICAL MODELING

A. Mathematical Problem Formulation

Let network traffic telemetry be represented as a chronologically ordered set of flow records $S = \{f_1, f_2, \ldots, f_N\}$, where each flow record $f_i = (x_i, \tau_i)$ consists of a d-dimensional behavioral feature vector $x_i \in \&mathbb;R^d$ and an associated capture timestamp $\tau_i \in \&mathbb;R^+$.

The primary objectives of the integrated system are split into four interconnected mathematical tasks:

Task 1: Supervised Threat Classification

$$\hat{y}_i = \arg\max_{c \in \{0,\ldots,C\}} P_\theta(y = c \mid x_i)$$

where $c=0$ represents benign traffic and $c \in \{1,\ldots,C\}$ represents specific attack classes.

Task 2: Temporal Aggregation & Windowing

$$a_t^{(c)} = \sum_i \mathbb{1}[\hat{y}_i = c \wedge \tau_i \in (t\Delta, (t+1)\Delta]]$$

where Δ denotes the aggregation window duration (e.g., Δ = 30 seconds or 1 hour).

Task 3: Attack Frequency Forecasting

$$\hat{a}_{T+h}^{(c)} = g_\phi(a_{T-k+1}^{(c)}, a_{T-k+2}^{(c)}, \ldots, a_T^{(c)})$$

where k is the historical lookback window, h is the forecast horizon, and g_ϕ is the trained sequence model.

Task 4: Dynamic Risk Score Computation

$$R_t = w_s S + w_f F_t + w_a A_t + w_c C_t, \quad \text{s.t.} \quad \sum w = 1, \quad R_t \in [0, 100]$$

B. Key Architectural Requirements

- **Chronological Separation:** Strict time-based splitting must be maintained across training, validation, and testing sets to eliminate temporal data leakage.
- **Multi-Horizon Elasticity:** The forecasting engine must support immediate short-horizon (Δ = 30s) and tactical medium-horizon (Δ = 1h) prediction windows.
- **Explainable Grounding:** Every high-risk notification generated for analysts must contain explicit source citations referencing MITRE ATT&CK tactics or vendor remediation advisories.

IV. END-TO-END SYSTEM ARCHITECTURE

The proposed framework integrates five modular operational layers into a unified pipeline, ensuring seamless data flow from raw packet ingestion to interactive analyst decision support.

Figure 1: End-to-End AI-Driven Network Threat Detection & Forecasting Pipeline



A. Data Ingestion & Transformation Module

The ingestion engine processes network traffic telemetry formatted as standard flow records (IPFIX, NetFlow v9, or CSV representations). Each flow vector contains bidirectional connection characteristics:

- **Basic Flow Identifiers:** Source IP, Destination IP, Source Port, Destination Port, Transport Protocol.
- **Temporal Characteristics:** Flow Duration, Flow Start Time, Flow End Time, Inter-Arrival Times (IAT Mean, Std, Max, Min).
  Traffic Volume Metrics: Total Forward Packets, Total Backward Packets, Total Length of Fwd Packets, Subflow Bytes.
- **TCP Flag Distribution:** FIN, SYN, RST, PSH, ACK, URG, ECE, CWR count statistics.

B. Feature Engineering & Scaling Pipeline

To prevent synthetic data leakage, feature scalers are fitted *strictly on the training partition*. Missing values are imputed using median feature statistics, and extreme outliers are clipped at the 99.9th percentile.

V. FEATURE SELECTION & MUTUAL INFORMATION

High-dimensional flow data frequently exhibits high multi-collinearity and uninformative noise features that degrade machine learning efficiency. We execute a rigorous two-stage feature selection strategy utilizing Information Gain (IG) ratio and Pearson correlation filtering.

A. Top 21 Discriminative Flow Features

Based on experimental selection on the CSE-CIC-IDS2018 benchmark [9], the top 21 flow attributes providing maximum mutual information relative to attack class targets are detailed in Table I.

Rank	Feature Name	Description	IG Score
1	Dst Port	Destination Service Port Number	0.892
2	Flow Duration	Total duration of active connection (ms)	0.865
3	Tot Fwd Pkts	Total packets transmitted in forward direction	0.841
4	Tot Bwd Pkts	Total packets transmitted in backward direction	0.838
5	TotLen Fwd Pkts	Total payload bytes in forward direction	0.812
6	Fwd Pkt Len Max	Maximum size of forward packets (bytes)	0.795
7	Bwd Pkt Len Mean	Mean payload size of backward response packets	0.781
8	Flow IAT Mean	Mean inter-arrival time between packets	0.764
9	Flow IAT Std	Standard deviation of flow inter-arrival time	0.751
10	Fwd IAT Tot	Total time between forward direction packets	0.739
Rank	**Feature Name**	**Description**	**IG Score**
11	Bwd Header Len	Total header size of backward packets	0.718
12	Fwd Pkts/s	Forward packet transmission rate per second	0.695
13	Pkt Len Min	Minimum observed packet length in connection	0.682
14	Pkt Len Var	Variance of payload length across connection	0.671
15	SYN Flag Cnt	Number of TCP packets with SYN flag set	0.655

VI. SUPERVISED MACHINE LEARNING THREAT CLASSIFICATION

The threat detection module operates on preprocessed feature vectors to perform multi-class recognition of benign and malicious network flows. We evaluate five primary classifier algorithms: Naïve Bayes, BayesNet, k-Nearest Neighbors (k-NN), Support Vector Machines (SVM), and Random Forest Ensembles.

A. Classification Objective Loss Function


For multi-class attack classification spanning C target classes, models are optimized using categorical cross-entropy loss weighted by inverse class frequency to accommodate severe label imbalance:

$$L_{CE}(\theta) = -(1 / N)\sum_{i=1}^{N} \sum_{c=0}^{C} w_c \cdot 1[y_i = c] \cdot \log P_\theta(y = c \mid x_i)$$

B. Model Architecture & Hyperparameters

- **Random Forest:** 200 decision trees, max depth of 25, Gini impurity split criterion, bootstrap sampling enabled.
- **XGBoost:** Gradient boosted decision trees, learning rate $\eta = 0.05$, max depth = 12, subsample ratio = 0.8.
- **Support Vector Machine (SVM):** Radial Basis Function (RBF) kernel, penalty parameter $C = 10.0$, kernel coefficient γ = 'scale'.

Figure 2: Flow-Level Decision Tree Feature Partitioning Topology



VII. TEMPORAL ATTACK FREQUENCY FORECASTING


While classification maps current flow vectors to static labels, the forecasting engine models temporal attack momentum. By aggregating timestamped detections into sequential time-series windows of length Δ, we construct continuous count sequences $a_t^{(c)}$.

A. Base Sequence Models

We evaluate three distinct time-series modeling paradigms:

1. **SMOreg (Support Vector Regression):** Implements Sequential Minimal Optimization for training support vector regressors using polynomial kernels. It solves the dual optimization problem with an ε-insensitive loss tube.
2. **Long Short-Term Memory (LSTM):** Deep recurrent network utilizing memory cells with input, forget, and output gates to capture long-range temporal dependencies without vanishing gradients.
3. **ARIMA / SARIMAX:** Traditional Auto-Regressive Integrated Moving Average baseline parameterized as *ARIMA(p, d, q)* where $p=2$, $d=1$, $q=1$.

Figure 3: Sequential Sliding Window & Rolling-Origin Forecasting Topology



VIII. DYNAMIC MULTI-FACTOR RISK SCORING ENGINE

Raw attack detection alerts and forecasted numerical volumes are combined into an interpretable operational risk score $R_t \in [0, 100]$. This single-metric indicator enables automated prioritization in enterprise Security Operations Centers (SOC).

A. Mathematical Risk Formulation

$$R_t = w_s \cdot S + w_f \cdot F_t + w_a \cdot A_t + w_c \cdot C_t$$

B. Threat Level Categorization

Risk Score (R_t)	Threat Band	Actionable SOC Response Protocol
0 – 24	LOW	Log telemetry; routine background monitoring.
25 – 49	MEDIUM	Flag connection in dashboard; aggregate IP metrics.
50 – 74	HIGH	Trigger analyst investigation alert; query RAG assistant.
75 – 100	CRITICAL	Automated firewall rule recommendation; isolate subnet.

IX. RETRIEVAL-AUGMENTED GENERATION (RAG) ASSISTANT

To support human security analysts in interpreting model predictions, our architecture embeds a grounded RetrievalAugmented Generation (RAG) intelligence assistant. When an alert triggers a HIGH or CRITICAL risk rating, the RAG engine generates contextual explanations citing authoritative security documentation.

Figure 4: RAG Explanatory Pipeline & Knowledge Indexing Engine



A. Dense Retrieval & Knowledge Indexing

The knowledge repository indexes curated documents, including MITRE ATT&CK technique descriptions, NIST SP 800-61 incident handling guides, and vendor mitigation advisories. Passages are chunked into 512-token segments and embedded using a domain-tuned transformer encoder.

X. EXPERIMENTAL SETUP & DATASET CHARACTERISTICS

Empirical validation was performed across three widely recognized benchmark intrusion detection datasets. Experiments were executed on an isolated computing cluster equipped with Intel Xeon Platinum processors, 128GB RAM, and NVIDIA A100 Tensor Core GPUs.

A. Dataset Description & Partitioning

- **CSE-CIC-IDS2018:** Comprehensive dataset captured from a realistic enterprise network comprising 450 client endpoints and 30 server hosts.
- **CIC-IDS2017:** Contains labeled benign baseline flows alongside contemporary multi-vector attack scenarios.
- **UNSW-NB15:** Synthetic modern attack activities generated via IXIA PerfectStorm tool.

Dataset Subset	Total Observations	Benign Ratio	Attack Ratio	Window Size (Δ)
CSE-CIC-IDS2018 (Raw)	1,048,575	64.0%	36.0%	Flow-level
Resampled Time-Series	1,084	66.0%	34.0%	30 Seconds
Training Partition	884	65.8%	34.2%	Intervals 1–884
Forecast Test Partition	200	66.5%	33.5%	Intervals 885–1084

XI. BASELINE CLASSIFICATION PERFORMANCE

Initial benchmarking evaluated baseline classification performance on raw flow-level feature vectors prior to applying temporal forecasting transformations.

Classifier	Accuracy (%)	FAR (%)	Precision (%)	Recall (%)	F-Measure (%)
BayesNet	95.5%	0.5%	96.9%	95.5%	95.8%
Naïve Bayes	98.1%	0.2%	98.4%	98.1%	98.2%
k-Nearest Neighbors (k-NN)	98.9%	0.1%	98.9%	98.9%	98.9%
Support Vector Machine (SMO)	97.7%	0.5%	97.9%	97.7%	97.8%
Random Forest	**99.2%**	**0.1%**	**99.3%**	**99.2%**	**99.3%**

XII. CLASSIFICATION OF FORECASTED EVENT FEATURES

To validate whether downstream threat detection remains accurate when operating on *predicted future features*, we passed the 200 time-series events forecasted by Linear Regression (LNRG) and Sequential Minimal Optimization for Regression (SMOreg) directly into our trained machine learning classifiers.

A. Classification Results on SMOreg Forecasts

Base Learner	Downstream Classifier	Accuracy (%)	FAR (%)	Precision (%)	Recall (%)	F-Measure (%)
SMOreg	BayesNet	87.5%	1.0%	86.6%	87.5%	86.4%
SMOreg	Naïve Bayes	87.6%	2.0%	86.7%	87.6%	86.5%
SMOreg	k-NN	89.6%	2.0%	90.0%	89.6%	88.1%
SMOreg	**SVM**	**90.4%**	**2.0%**	**91.3%**	**90.4%**	**89.0%**
SMOreg	**Random Forest**	**90.4%**	**1.0%**	**91.3%**	**90.4%**	**89.0%**

XIII. FORECAST ERROR METRICS & TIME-SERIES EVALUATION

To measure the numerical accuracy of predicted temporal features, we evaluate Mean Absolute Error (MAE) and Root Mean Square Error (RMSE) across key network flow variables.

TABLE V: Mean Absolute Error (MAE)

Target Feature	Linear Reg	SMOreg	LSTM
Tot Fwd Pkts	0.0105	**0.0038**	2.6127
Tot Bwd Pkts	0.0034	**0.0025**	0.4981
Pkt Len Min	**0.0002**	0.0008	0.0054
Fwd Seg Size Min	0.4912	**0.0182**	0.0494
Subflow Bwd Byts	**0.7180**	0.7251	31.9957

TABLE VI: Root Mean Square Error (RMSE)

Target Feature	Linear Reg	SMOreg	LSTM
Tot Fwd Pkts	0.0129	**0.0045**	2.8946
Tot Bwd Pkts	0.0039	**0.0031**	0.5842
Pkt Len Min	**0.0002**	0.0096	0.0063
Fwd Seg Size Min	**0.0198**	0.8776	0.0497
Subflow Bwd Byts	**0.8163**	1.2969	35.0395

XIV. COMPREHENSIVE DISCUSSION & THREAT MODELING

The empirical results across 1,048,575 flow records demonstrate that coupling multi-step temporal forecasting with supervised classification achieves a **90.4% predictive detection accuracy** prior to actual attack execution. However, operational deployment in enterprise environments introduces several complex challenges and adversarial considerations.

A. Adversarial Robustness & Evasion Tactics

Sophisticated attackers may execute deliberate low-and-slow traffic injection to manipulate the historical count vector $a_t^{(c)}$. By artificially dampening packet rates or introducing stochastic inter-arrival delays, adversarial actors can attempt to keep forecasted counts $a_hat_{T+h}^{(c)}$ below SOC alert thresholds. Our framework mitigates this by incorporating anomaly evidence A_t derived from non-parametric autoencoder reconstruction errors directly into the unified risk score R_t.

B. Concept Drift & Non-Stationary Telemetry

Network traffic profiles undergo continuous drift due to scheduled system backups, software updates, and shifting user behaviors. A forecasting model calibrated solely on historic count distributions may experience performance decay when confronted with unprecedented zero-day campaigns or major infrastructure changes. To counter concept drift, the sequence modeling layer implements a rolling-origin online retraining trigger whenever the observed Mean Absolute Scaled Error (MASE) exceeds a predefined threshold ($MASE > 1.5$).

Online Concept Drift Score Metric

$$D_t = (1 / k)\sum_{i=0}^{k-1} | a_{t-i} - a_hat_{t-i} | / ((1 / (N-1))\sum_{j=2}^{N} | a_j - a_{j-1} |)$$

C. Operational Privacy & Data Governance

Processing high-granularity flow logs containing IP addresses and payload metadata raises strict compliance and privacy mandates (e.g., GDPR, HIPAA). The data ingestion layer applies anonymization and zero-knowledge feature extraction, replacing explicit host identifiers with anonymized hash mappings while preserving directional connection statistics.

XV. REAL-TIME IMPLEMENTATION & COMPUTATIONAL LATENCY

To validate the feasibility of real-time SOC integration, we measured end-to-end processing latency across all system components under simulated gigabit throughput conditions (100,000 flows/sec).


A. Computational Latency Breakdown

Pipeline Component	Processing Target	Mean Latency	99th Percentile Latency
Flow Preprocessing & Scaling	Batch of 10,000 flows	4.2 ms	8.1 ms
Tree Classifier Inference (XGBoost)	Single flow vector	0.08 ms	0.15 ms
Time-Series Window Aggregation	30-second window	1.1 ms	2.3 ms
SMOreg / LSTM Forecast Generation	Horizon h = 6 intervals	12.4 ms	24.8 ms
RAG Semantic Retrieval & Prompting	High-risk trigger event	320.0 ms	580.0 ms

B. Enterprise Deployment Architecture

The complete pipeline is engineered for deployment via containerized microservices (Docker / Kubernetes), enabling elastic horizontal scaling of classification workers alongside dedicated GPU acceleration nodes for sequence forecasting and RAG vector search.

Figure 5: Enterprise Distributed Containerized Microservice Topology



XVI. CONCLUSION, FUTURE WORK & REFERENCES

This paper presented the design, mathematical formulation, and empirical evaluation of an integrated AI-driven network security framework. By uniting flow-level supervised machine learning, multi-step time-series forecasting (SMOreg, LSTM, ARIMA), dynamic multi-factor risk scoring, and a retrieval-augmented generation (RAG) incident explanation assistant, the system effectively bridges the operational gap between reactive detection and proactive risk mitigation.

Experimental validation across 1,048,575 network flow records from benchmark intrusion datasets demonstrates that downstream classifiers operating on predicted future feature states achieve up to **90.4% predictive accuracy** using Random Forest and Support Vector Machine models. Furthermore, SMOreg sequence models yielded superior Mean Absolute Error (MAE) performance when forecasting short-term traffic volume indicators.

A. Key Research Contributions

- Unified classification, time-series forecasting, risk assessment, and explainable AI in a single framework.
- Formulated a normalized multi-factor dynamic risk score $R_t \in [0, 100]$ combining threat severity, forecast trends, anomaly
- scores, and model confidence.

Empirically proved that multi-step forecasted network flow features retain sufficient discriminative signal to enable early threat classification.

B. Directions for Future Research

Future research will focus on evaluating deep transformer architectures (such as Informer and Autoformer) for multihorizon long-sequence forecasting, expanding online cross-dataset domain adaptation, and deploying live packet capture integration within software-defined networking (SDN) environments.

REFERENCES

1. I. Sharafaldin, A. H. Lashkari, and A. A. Ghorbani, "Toward generating a new intrusion detection dataset and intrusion traffic characterization," in *Proc. Int. Conf. Information Systems Security and Privacy (ICISSP)*, 2018, pp. 108–116.
2. Y. Meidan et al., "N-BaIoT—Network-based detection of IoT botnet attacks using deep autoencoders," *IEEE Pervasive Computing*, vol. 17, no. 3, pp. 12–22, 2018.
3. N. Moustafa and J. Slay, "UNSW-NB15: A comprehensive data set for network intrusion detection systems," in *Proc. MilCIS*, 2015, pp. 1–6.
4. M. Landauer et al., "A review of time-series analysis for cyber security analytics," *Int. Journal of Information Security*, vol. 24, Art. no. 3, 2025.
5. S.-K. Kim and Z. Zhan, "Optimizing cyberattack frequency forecasting by advanced machine learning adaptation with tumbling windows," *Scientific Reports*, vol. 16, Art. no. 25911, 2026.
6. P. Lewis et al., "Retrieval-augmented generation for knowledge-intensive NLP tasks," in *NeurIPS*, vol. 33, 2020, pp. 9459–9474.
7. X. Liang et al., "SafeRAG: Benchmarking security in retrieval-augmented generation of large language model," in *Proc. ACL*, 2025, pp. 4609–4631.
8. Y. Ahmed, M. A. Azad, and T. Asyhari, "Rapid forecasting of cyber events using machine learning-enabled features," *Information*, vol. 15, no. 1, Art. no. 36, 2024.