

How to setup the main Battery

1. Glue
 - 1.1. Start by the top section, glue it with the lamp on top, ladder at the back, panel at the front. Also glue the barrel
 - 1.2. Glue the section under the deck. You can glue using points outside the tube
 - 1.3. Remember to glue the block at the bottom to the block directly connecting the bearing
 - 1.4. Right click the physical bearing to assemble it
 - 1.5. Rebuild the cannon as it will become fractured when assembling
2. Reload system
 - 2.1. Glue the screw block, remember to include the drill and the energy transmitter behind
 - 2.2. Glue the white steel Armour blocks under the payload (cartridge, powder)
 - 2.3. Go to the lowest level, run ReloadGen4 on the advanced computer. Connect the red router as guided. The redrouter closer to the computer is router1
 - 2.4. Replace the wool on the redstone link with different colour wool if needed (When there are multiple battery)
 - 2.5. Grab a linked controller, test if the screw block is operating normally. The block and the screw should go up with the first click and down with the second click. The entire cannon should not be attached to the screw.
 - 2.6. Do a test reload and fire to check if everything is working
3. Computer system
 - 3.1. Set up the cannonYawPos on the cannon to transmit the cannon data
 - 3.2. Replace the wool on the redstone link(those incharge of pitch and turning the cannon) if needed
 - 3.3. Take the tweaked controller down from the control center, map certain buttons (standard: T) to the reload redstone (the one with the wooden sword on the reload computer) and map the fire redstone (the one with flint and steel on the cannon mount) to certain button (standard: left click)
 - 3.4. Set up cannonControl on the computer at the control center
4. How to aim
 - 4.1. Basic control:
 - 4.1.1. W: Scroll up
 - 4.1.2. S: Scroll down
 - 4.1.3. Up arrow: Increase pitch compensate

- 4.1.4. Down arrow: Decrease pitch compensate
- 4.1.5. Left arrow: Decrease yaw compensate, (anti-clockwise)
- 4.1.6. Right arrow: Increase yaw compensate, (clockwise)
- 4.1.7. ; : Scroll up to the manual input and press ; to reset coordinate
- 4.2. Target selection method 1: Radar Auto Select
 - 4.2.1. Scroll up and down without going to the "Input coordinate" row.
 - 4.2.2. The locked target will be marked in blue
- 4.3. Target selection method 2: Manual Coordinate Input
 - 4.3.1. Scroll up to the "input coordinate" row
 - 4.3.2. Click the computer and enter the coordinate as instructed
- 4.4. You can switch between the two modes, the inputted coordinate will be stored even if you switched modes. Press ; while selecting the manual input mode to re-enter coordinate
- 4.5. There are multiple status display on screen. For yaw and pitch, green means they are aimed, red means they are aiming. Blindspot warning will be highlighted in red if the selected target is in the blind spot of the battery. Pitch will not move if the cannon is not assembled, pay attention to the assembly status.
- 4.6. Compensation. There are yaw and pitch compensation. Those are for you to compensate for the inaccuracies after shooting and missing once. This can also be used to hit various parts of the enemy ship. The yaw compensate is a bit complicated. It is added to the target yaw directly. So it may not work correctly.

Remark: The script may highly likely not work for the stern battery, it is very lonely so i usually ignore it