

RiverWatch: Candidate B

Evaluation report | 12 September 2026 | Fictional development fixture

Draft summary. Candidate B achieved an RMSE of **0.62 metres** on RW-90. This summary was written before a scoring defect was discovered. The correction on page 3 supersedes the draft error value.

Candidate B uses the same 420 training, 90 validation and 90 held-out cases as Baseline A. Timing was measured on the same bench workstation. Exact hardware specifications were not recorded.

All cases are simulations with water at 20-24 degrees Celsius, one leak and complete sensor readings. Sampling is 10 Hz. No noisy or missing-sensor inputs were tested.

Candidate B: timing and scope

Measure	Candidate B
Mean prediction latency	260 milliseconds
95th-percentile latency	390 milliseconds
Held-out cases	90
Hardware model	Not recorded

The timing measurements were unaffected by the scoring defect. Use these timing values together with the corrected error on page 3.

There are no tests of hydrogen service, sensor failure, artificial noise or multiple simultaneous leaks. There is no field pilot or deployment.

No confidence interval or statistical-significance test is supplied. A release recommendation must also satisfy the separate RiverWatch Release Checklist.

Correction: final location error

Approved correction | 13 September 2026

The draft summary on page 1 accidentally reused a subset score. Recomputing across all 90 held-out RW-90 cases gives a final RMSE of **0.71 metres**.

The final value is 0.71 metres, replacing 0.62 metres everywhere the draft summary is quoted. The held-out cases and latency measurements are unchanged.

Result to use	Final corrected value
Candidate B RMSE	0.71 metres
Candidate B mean latency	260 milliseconds
Candidate B 95th-percentile latency	390 milliseconds

This correction changes the reported score; it does not add robustness testing, a field pilot or evidence of deployment readiness.