

# IranKhodro timeseries Analysis

Mehrab Atighi

12/20/2021

In The Name Of God

# Contents

- problem statement 4
- Downloading Data 5
- Importing Data To R 6
- PreProccesing of data 7
- Regression modeling for Data 8
- Selecting and Ploting Data 9
- plot of auto correlation function 10
- plot of partial auto correlation function 11
- Cheking The ARIMA Models with Data 12

We want to use the Timeseries Algorithms On the shares of Irankhodro Company in the Iranian stock market.  
we should chek it with all of **ARIMA** state until the second time.

# Dawnloading Data

So We went Tse website and dawnload needed Excel file.for this step we should go to the Site and after dawnloding Excel file, we should save that as **CSV** format.

# Importing Data To R

Now we want to import the Dataset in to R. so we should use `read.csv(...)` function.

```
df = read.csv(file = "F:/lessons/time series/project/Iran.Khodro  
head(df , 4)
```

```
##      X.TICKER. X.DTYYYYMMDD. X.FIRST. X.HIGH. X.LOW. X.CLOSE.  
## 1 Iran.Khodro      20211219      1965      1970      1856      1876  
## 2 Iran.Khodro      20211218      1900      1961      1890      1953  
## 3 Iran.Khodro      20211215      1890      1950      1825      1868  
## 4 Iran.Khodro      20211214      1922      1969      1917      1921  
##      X.VOL. X.OPENINT. X.PER. X.OPEN. X.LAST.  
## 1 438255155      11188      D      1953      1856  
## 2 701269890      16307      D      1868      1961  
## 3 733471286      17475      D      1921      1856  
## 4 809024025      14825      D      2017      1917
```

# PreProcessing of data

we should separate our data and we just need to Date and close value for each day. so we use `separate` function from `tidyverse` Package.

```
library(tidyverse)

## -- Attaching packages ----- tidyverse 1.3.1 --

## v ggplot2 3.3.5      v purrr  0.3.4
## v tibble  3.1.5      v dplyr  1.0.7
## v tidyr   1.1.4      v stringr 1.4.0
## v readr   2.1.1      v forcats 0.5.1

## -- Conflicts ----- tidyverse_conflicts() --
## x dplyr::filter() masks stats::filter()
## x dplyr::lag()     masks stats::lag()

df= separate(df,2,c("year","month","day"),
             sep =c(4,6),remove = TRUE)
df= df[,c(2,3,4,8)]
head(df , 4 )

##   year month day X.CLOSE.
## 1 2021    12  19    1876
## 2 2021    12  18    1953
## 3 2021    12  15    1868
## 4 2021    12  14    1921
```

# Regression modeling for Data

Now we want to make a regression model for our data and calculating the coefficients estimate.

```
response = df$X.CLOSE.[(nrow(df)-200):nrow(df)]
model_reg = lm(response ~ (time(response)))
summary(model_reg)


##
## Call:
## lm(formula = response ~ (time(response)))
##
## Residuals:
##      Min       1Q   Median       3Q      Max
## -580.36 -127.01  -15.06   186.97   442.36
##
## Coefficients:
##              Estimate Std. Error t value Pr(>|t|)
## (Intercept)   2994.4752    28.6114  104.660 < 2e-16 ***
## time(response)    1.9140     0.2456   7.792 3.58e-13 ***
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
##
## Residual standard error: 202.1 on 199 degrees of freedom
## Multiple R-squared:  0.2338, Adjusted R-squared:  0.2299
## F-statistic: 60.72 on 1 and 199 DF,  p-value: 3.578e-13
```



# Selecting and Plotting Data

Now we want to select the Two hundred days ago data to timeseries alg and plotting them from dataset.


```
plot(response,type="o" , col = "orange")  
abline(model_reg)
```



# plot of auto correlation function

Now we want to plotting the auto correlation function values of dataset.


```
acf(response, lag=50, ylab="acf")
```



# plot of partial auto correlation function

We want to plotting the partial auto correlation function values of dataset.

```
pacf(response, lag=50, ylab="pacf")
```



We can see that the pacf values from the first times is lower than a blue bound and we can say its approximatly zero.

# Checking The ARIMA Models with Data

Now we want to check all of ARIMA state until two times.

- ARIMA(0,0,1)13 - ARIMA(0,0,2)14 - ARIMA(1,0,0)15 -  
ARIMA(2,0,0)16 - ARIMA(1,0,1)17 - ARIMA(2,0,2)18 -  
ARIMA(0,1,1)19 - ARIMA(0,1,2)20 - ARIMA(1,1,0)21 -  
ARIMA(2,1,0)22 - ARIMA(1,1,1)23 - ARIMA(2,1,2)24 -  
ARIMA(0,2,1)25 - ARIMA(0,2,2)26 - ARIMA(1,2,0)27 -  
ARIMA(2,2,0)28 - ARIMA(1,2,1)29 - ARIMA(2,2,2)30

# Modeling for all states

We Want to Chek the response with ARIMA(0,0,1): attention that we need to install and library the [TSA](#) Package.

```
library(TSA)
```

```
##
## Attaching package: 'TSA'

## The following object is masked from 'package:readr':
##
##      spec

## The following objects are masked from 'package:stats':
##
##      acf, arima

## The following object is masked from 'package:utils':
##
##      tar
```

```
(M1=arima(response,order=c(0,0,1)))
```

```
##
## Call:
## arima(x = response, order = c(0, 0, 1))
##
## Coefficients:
##      ma1  intercept
##      0.8176  3186.4328
## s.e.  0.0279    17.6125
##
## sigma^2 estimated as 18957:  log likelihood = -1275.68,  aic = 2555.36
```

# Modeling for all states

We Want to Chek the response with ARIMA(0,0,1):

```
(M2=arima(response,order=c(0,0,2)))
```

```
##  
## Call:  
## arima(x = response, order = c(0, 0, 2))  
##  
## Coefficients:  
##          ma1      ma2  intercept  
##          1.1233  0.7259  3185.4451  
## s.e.    0.0705  0.0561    19.5437  
##  
## sigma^2 estimated as 9543:  log likelihood = -1207.16,  aic = 2420.33
```

# Modeling for all states

We Want to Chek the response with ARIMA(1,0,0):

```
(M3=arima(response,order=c(1,0,0)))
```

```
##  
## Call:  
## arima(x = response, order = c(1, 0, 0))  
##  
## Coefficients:  
##          ar1  intercept  
##      0.9668  3122.7292  
## s.e.  0.0174   117.7902  
##  
## sigma^2 estimated as 3740:  log likelihood = -1113.38,  aic = 2230.76
```

# Modeling for all states

We Want to Chek the response with ARIMA(2,0,0):

```
(M4=arima(response,order=c(2,0,0)))
```

```
##  
## Call:  
## arima(x = response, order = c(2, 0, 0))  
##  
## Coefficients:  
##          ar1          ar2  intercept  
##          1.0912   -0.1293   3138.0426  
## s.e.    0.0697    0.0702    103.6656  
##  
## sigma^2 estimated as 3678:  log likelihood = -1111.7,  aic = 2229.4
```



# Modeling for all states

We Want to Chek the response with ARIMA(1,0,1):

```
(M5=arima(response,order=c(1,0,1)))
```

```
##  
## Call:  
## arima(x = response, order = c(1, 0, 1))  
##  
## Coefficients:  
##          ar1      ma1  intercept  
##          0.9579  0.1309  3135.8185  
## s.e.    0.0205  0.0690   105.7904  
##  
## sigma^2 estimated as 3678:  log likelihood = -1111.7,  aic = 2229.4
```

# Modeling for all states

We Want to Chek the response with ARIMA(2,0,2):

```
(M6=arima(response,order=c(2,0,2)))
```

```
##  
## Call:  
## arima(x = response, order = c(2, 0, 2))  
##  
## Coefficients:  
##          ar1      ar2      ma1      ma2  intercept  
##          0.1107  0.8053  0.9984  0.1828  3139.8876  
## s.e.    0.3945  0.3855  0.3855  0.0750   102.1744  
##  
## sigma^2 estimated as 3633:  log likelihood = -1110.48,  aic = 2230.96
```

# Modeling for all states

We Want to Chek the response with ARIMA(0,1,1):

```
(M7=arima(response,order=c(0,1,1)))
```

```
##  
## Call:  
## arima(x = response, order = c(0, 1, 1))  
##  
## Coefficients:  
##          ma1  
##       0.1130  
## s.e.  0.0687  
##  
## sigma^2 estimated as 3755:  log likelihood = -1106.87,  aic = 2215.73
```

# Modeling for all states

We Want to Chek the response with ARIMA(0,1,2):

```
(M8=arima(response,order=c(0,1,2)))
```

```
##  
## Call:  
## arima(x = response, order = c(0, 1, 2))  
##  
## Coefficients:  
##          ma1      ma2  
##      0.1134  0.0008  
## s.e.  0.0772  0.0781  
##  
## sigma^2 estimated as 3755:  log likelihood = -1106.87,  aic = 2217.73
```

# Modeling for all states

We Want to Chek the response with ARIMA(1,1,0):

```
(M9=arima(response,order=c(1,1,0)))
```

```
##  
## Call:  
## arima(x = response, order = c(1, 1, 0))  
##  
## Coefficients:  
##          ar1  
##      0.1095  
## s.e.  0.0701  
##  
## sigma^2 estimated as 3757:  log likelihood = -1106.93,  aic = 2215.86
```

# Modeling for all states

We Want to Chek the response with ARIMA(2,1,0):

```
(M10=arima(response,order=c(2,1,0)))
```

```
##  
## Call:  
## arima(x = response, order = c(2, 1, 0))  
##  
## Coefficients:  
##          ar1          ar2  
##      0.1151  -0.0520  
## s.e.  0.0705   0.0704  
##  
## sigma^2 estimated as 3747:  log likelihood = -1106.66,  aic = 2217.32
```

# Modeling for all states

We Want to Chek the response with ARIMA(1,1,1):

```
(M11=arima(response,order=c(1,1,1)))
```

```
##  
## Call:  
## arima(x = response, order = c(1, 1, 1))  
##  
## Coefficients:  
##          ar1      ma1  
##      0.0017  0.1115  
## s.e.  0.3128  0.3048  
##  
## sigma^2 estimated as 3755:  log likelihood = -1106.87,  aic = 2217.73
```

# Modeling for all states

We Want to Chek the response with ARIMA(2,1,2):

```
(M12=arima(response,order=c(2,1,2)))
```

```
##  
## Call:  
## arima(x = response, order = c(2, 1, 2))  
##  
## Coefficients:  
##          ar1      ar2      ma1      ma2  
##      -0.2487  -0.580   0.3940   0.6228  
## s.e.    0.5984   0.367   0.6184   0.2602  
##  
## sigma^2 estimated as 3682:  log likelihood = -1104.94,  aic = 2217.88
```



# Modeling for all states

We Want to Chek the response with ARIMA(0,2,1):

```
(M13=arima(response,order=c(0,2,1)))
```

```
##  
## Call:  
## arima(x = response, order = c(0, 2, 1))  
##  
## Coefficients:  
##             ma1  
##          -0.9892  
## s.e.      0.0271  
##  
## sigma^2 estimated as 3848:  log likelihood = -1105.69,  aic = 2213.39
```

# Modeling for all states

We Want to Chek the response with ARIMA(0,2,2):

```
(M14=arima(response,order=c(0,2,2)))
```

```
##  
## Call:  
## arima(x = response, order = c(0, 2, 2))  
##  
## Coefficients:  
##          ma1      ma2  
##       -0.8829  -0.117  
## s.e.    0.0984   0.069  
##  
## sigma^2 estimated as 3773:  log likelihood = -1104.35,  aic = 2212.7
```

# Modeling for all states

We Want to Chek the response with ARIMA(1,2,0):

```
(M15=arima(response,order=c(1,2,0)))
```

```
##  
## Call:  
## arima(x = response, order = c(1, 2, 0))  
##  
## Coefficients:  
##          ar1  
##        -0.4145  
## s.e.      0.0643  
##  
## sigma^2 estimated as 5621:  log likelihood = -1141.57,  aic = 2285.14
```

# Modeling for all states

We Want to Chek the response with ARIMA(2,2,0):

```
(M16=arima(response,order=c(2,2,0)))
```

```
##  
## Call:  
## arima(x = response, order = c(2, 2, 0))  
##  
## Coefficients:  
##          ar1      ar2  
##      -0.5036  -0.2131  
## s.e.   0.0691   0.0690  
##  
## sigma^2 estimated as 5361:  log likelihood = -1136.91,  aic = 2277.82
```

# Modeling for all states

We Want to Chek the response with ARIMA(1,2,1):

```
(M17=arima(response,order=c(1,2,1)))
```

```
##  
## Call:  
## arima(x = response, order = c(1, 2, 1))  
##  
## Coefficients:  
##          ar1          ma1  
##      0.1148   -0.9999  
## s.e.  0.0705    0.0526  
##  
## sigma^2 estimated as 3775:  log likelihood = -1104.41,  aic = 2212.81
```

# Modeling for all states

We Want to Chek the response with ARIMA(2,2,2):

```
(M18=arima(response,order=c(2,2,2)))
```

```
##
## Call:
## arima(x = response, order = c(2, 2, 2))
##
## Coefficients:
##          ar1          ar2          ma1          ma2
##          0.8334   -0.1872   -1.7110    0.7228
## s.e.   0.2024    0.0727    0.1964    0.1941
##
## sigma^2 estimated as 3740:  log likelihood = -1102.49,  aic = 2212.98
```

# Final AIC Comparing

Now we want to compare all models AIC .

```
(AIC=c(M1$aic,M2$aic,M3$aic,M4$aic,M5$aic,M6$aic,  
M7$aic,M8$aic,M9$aic,M10$aic,M11$aic,M12$aic,  
M13$aic,M14$aic,M15$aic,M16$aic,M17$aic,M18$aic))
```

```
## [1] 2555.358 2420.329 2230.761 2229.399 2229.397 2230.9  
## [9] 2215.865 2217.320 2217.734 2217.876 2213.387 2212.7  
## [17] 2212.813 2212.978
```

```
min(AIC)
```

```
## [1] 2212.702
```

```
which.min(AIC)
```

```
## [1] 14
```

So we can say that the M14 or ARIMA(0,2,2) is the best fit for our dataset.

# Final predict Visual

```
plot(response,type="o" , col = "orange")  
with(df , lines(x = time(response) , y = fitted(M14)))
```

