



Machine Learning Exercise (SS 22)

Assignment 1: k-nearest neighbors

Mojtaba Nayyeri

Mojtaba.Nayyeri@ipvs.uni-stuttgart.de

Alexandra Baier

Alexandra.Baier@ipvs.uni-stuttgart.de

Akram Hosseini

Akram.Hosseini@ipvs.uni-stuttgart.de

Tim Schneider

timphillip.schneider@ipvs.uni-stuttgart.de

This assignment sheet consists of theoretical and programming tasks.

Submit your solution in ILIAS as a single PDF file.¹ Make sure to list full names of all participants, immatriculation number, study program and B.Sc. or M.Sc on the first page. Optionally, you can *additionally* upload source files (e.g. PPTX files). If you have any questions, feel free to ask them in the exercise forum in ILIAS.

Submission is open until Monday, 02 May 2022, 11:59 AM.

¹Your drawing software probably allows to export as PDF. An alternative option is to use a PDF printer. If you create multiple PDF files, use a merging tool (like [pdfarranger](#)) to combine the PDFs into a single file.



K-Nearest Neighbors (Theoretical)

Task: The data points x_1, \dots, x_6 are given as follows:

$$x_1 = \begin{bmatrix} 4 \\ 6 \end{bmatrix}, x_2 = \begin{bmatrix} 7 \\ 2 \end{bmatrix}, x_3 = \begin{bmatrix} 9 \\ 3 \end{bmatrix}, x_4 = \begin{bmatrix} 3 \\ 7 \end{bmatrix}, x_5 = \begin{bmatrix} 10 \\ 7 \end{bmatrix}, x_6 = \begin{bmatrix} 7 \\ 6 \end{bmatrix}$$

The data points x_1, x_2 belong to class c_1 , the data points x_3, x_4, x_5 belong to class c_2 . The data point x_6 has not been classified, yet. Show step-by-step how the data point x_6 can be classified by the k-Nearest Neighbors algorithm once with $k=1$ and once with $k=3$. Use the squared Euclidean distance as distance metric.



K-Nearest Neighbors (Programming)

Task: Please download the Jupyter notebook `assignment1.ipynb`. Follow the instructions in the Jupyter notebook.