

Lab 7: ELF-introduction

This lab **may** be done in pairs.

Lab Goals

- Extracting useful information from files in ELF.
- Fixing files using this information: reverse engineering.

In the following labs, you will learn to handle object and executable files. We will begin by learning just some of the basics of ELF, together with applications you can already use at this level - editing binary files and writing software patches. Then, we will continue our study of ELF files, by beginning to parse the structures of ELF files, and to use them for various purposes. In particular, we will access the data in the section header table and in the symbol table.

Methodology

- [Get to know the ELF.](#)
- Learn how to use the *readelf* utility. By using *readelf* you can get, in a human readable format, all the ELF structural information.
- Experience basic ELF manipulation.

Recommended Operating Procedure

This advice is relevant for all tasks. Note that while at some point you will no longer be using *hexedit* to process the file and *readelf* to get the information, nevertheless in some cases you may still want to use these tools for debugging purposes. In order to take advantage of these tools and make your tasks easier, you should:

- Support debugging messages: in particular the offsets of the various items, as you discover them from the headers. Also, whenever the user is required to enter values, you should print the **parsed** values in their respective representation (e.g. string, decimal or hexadecimal).
- Use *hexedit* and *readelf* to compare the information you are looking for, especially if you run into unknown problems: *hexedit* is great if you know the exact location of the item you are looking for.
- Note that while the object files you will be processing will be linked using *ld*, and will, in most cases, use direct system calls in order to make the ELF file simpler, there is

no reason why the programs you write need use this interface. You are allowed to use the standard library when building your own C programs.

- In order to preserve your sanity, even if the code you MANIPULATE may be without `stdlib`, we advise that for your OWN CODE you DO use the C standard library! (Yes, this is repeated twice, so that you notice it!)
- In order to keep sane in the following labs as well, **understand** what you are doing and **keep track** of that and of your code, as you will be using them in future labs.

All the executable files we will work with in this session are 32-Bit ELF binaries. Compile your code accordingly.

Lab 7 Tasks

Deliverables

You should read and understand the reading material, and do task 0 before attending the lab. To be eligible for a full grade, you must complete all of tasks up-to (and including) task 3a, during the regular lab. Tasks 3b and 4 may be done in a completion lab, if you run out of time.

Task 0

Task 0a:

Download the following file: [a.out](#). Answer the following questions (be prepared to explain your answers to the lab instructor):

1. Where is the entry point specified, and what is its value?
2. How many sections are there in `a.out`?
3. What is the size of the `.text` section?
4. Does the symbol `_start` occur in the file? If so, where is it mapped to in virtual memory?
5. Does the symbol `main` occur in the file? If so, where is it mapped to in virtual memory?
6. Where in the file does the code of function "main" start?

Task 0b

Write a program called *hexeditplus*:

```
./hexeditplus
```

The `hexeditplus` program performs operations (read and write) on files and memory. File operations are done on a file *filename* as defined below. Each operation is done in units of *size* bytes, which indicates a unit size, i.e. the number of bytes we want to use as the basic unit in each operation of our program, such as "display file contents". Size can be either 1, 2 or 4, with 1 as the default.

The variables *size*, *filename* (initially null), as well as a pointer to a buffer in memory (also initially null) *data_pointer*, should all be global variables.

First, define a menu for the user with a number of predefined functions (as done in [Lab 2](#)), to which we will add functions as we go. The program prints the menu, obtains a choice from the user, acts on it, and repeats infinitely. For example, if the functions: "Toggle Debug Mode", "Set File Name", "Set Unit Size" and "Quit" are available, then the command line:

```
./hexeditplus
```

Will print:

```
Choose action:
0-Toggle Debug Mode
1-Set File Name
2-Set Unit Size
3-Quit
```

For this part, use an array with the above menu names and pointers to appropriate functions that implement each option.

At this point implement "Toggle Debug Mode", "Set File Name", "Set Unit Size", and "Quit".

Toggle debug mode means turn the debug flag on (if it is currently off, which it is in the initial state), and print "Debug flag now on". If the debug flag is on, this function prints "Debug flag now off", and turns the flag off. When the debug mode is on, you should print the value of the global variables: unit size, file name, and buffer address, every time just before the menu is printed.

Optional (bonus): the debug toggle function can require entering a secret password of your choice, and only activates debug mode if the password is provided by the user. Such passwords are known in the computer gaming industry as "cheat codes" (so called by the users).

Set File Name queries the user for a file name, and store it in a globally accessible buffer. You may assume that the file name is no longer than 100 characters. If debug mode is on, the function should also print: "Debug: file name set to 'filename' " (obviously, replacing 'filename' with the actual name).

The Set Unit Size option sets the size variable. The steps are:

1. Prompt the user for a number.
2. If the value is valid (1, 2, or 4), set the size variable accordingly.
3. If debug mode is on, print "Debug: set size to x", with x the appropriate size.
4. If not valid, print an error message and leave size unchanged.

Quit is a function that prints "quitting" (in debug mode), and calls `exit(0)` to quit the program.

The rest of the functions will be written in the next tasks. The menu should be extensible, you will change and extend it in each sub-task of task 1. It should be printed using a loop iterating over the menu array, and be `{NULL, NULL}` terminated.

All functions should be of the form:

```
void fun( );
```

Be sure to implement this code and test it carefully before the lab (that is why you have the debug option), as you will need to extend it during the lab!

Task 1: hexeditplus

In this task we will write our own version of *hexedit* for working with binary files. You will extend your code from task 0b.

Note: You should verify that there is no error when opening a file. In case of an error, you should print a message and abort the rest of the operation.

For this task you will be working with the following ELF file: [abc](#).

Task 1a: File Display

Write the function for the "File Display" option:

This option displays *length* units from the file *filename* (chosen using option 1 in the menu), starting at file location *location* (note: this is the same as the "offset" in the file). The units should be displayed once using a hexadecimal representation, and again using a decimal representation.

The steps are:

1. Check if *filename* is null, and if it is print an error message and return.
2. Open *filename* for reading. If this fails, print an error message and return.
3. Prompt the user for location (in hexadecimal) and a length (in decimal).
4. If debug mode is on, print the values of *<location>* and *<length>* retrieved from the user.
5. Allocate *<unit size> * <length>* bytes on the heap.
6. Read *length* units from file *filename*, starting from *location*, into the allocated memory.
7. Close the file.
8. Display in **hexadecimal**, the read units.
9. Display in **decimal**, the read units
10. Free the allocated memory

- Note that you should only read from the file once in order to implement both prints (decimal and hexadecimal).

For example, the command line:

```
./hexeditplus
```

Will print:

```
Choose action:
0-Toggle Debug Mode
1-Set File Name
2-Set Unit Size
3-File Display
4-Quit
```

After the user set the unit size to 2 and chooses 3 with *location* "40" and *length* "5" - your program will print the 5 units, starting from the location 0x40, and ending in location 0x49.

The prompt should look as follows:

```
3
Please enter <location> <length>
40 5
```

If the current file is "a.out", then the output should look something like this (for a unit size of 2):

```
Hexadecimal Representation:
8034 0804 00e0 0000 00e0
Decimal Representation:
32820 2052 224 0 224
```

- Note that, depending on the chosen unit size, the printed hexadecimal values may differ in order when compared with the output of *hexedit*. Why is that?

Use your newly implemented functionality to answer: what is the entry point of your own *hexeditplus* program? Verify your answer using `readelf -h`

Remember

- To read *location* and *length* use `fgets` and then `sscanf`, rather than `scanf` directly.
- *location* is entered in hexadecimal representation.

Task 1b: Load Into Memory

Write the function for the "Load Into Memory" option, which works as follows:

- Check if *filename* is null, and if it is print an error message and return.
- Open *filename* for reading. If this fails, print an error message and return.
- Prompt the user for *location* (in hexadecimal) and *length* (in decimal).
- If *data_pointer* points to a previously allocated memory, then free it.
- Allocate memory of *length* **bytes** on the heap, and point *data_pointer* to it.
- If debug flag is on, print the filename, as well as *data_pointer*, *location*, and *length*.
- Load into **hexeditplus** program memory, at address *data_pointer*, *length* **bytes** from *filename* starting from position *location*.
- Close the file.

For example, the command:

```
./hexeditplus
```

Will print:

```
Choose action:
0-Toggle Debug Mode
1-Set File Name
2-Set Unit Size
3-File Display
4-Load Into Memory
5-Quit
```

Assume that the user has already set the file name to "abc". If the user chooses 4, he is prompted for *location* and *length*. It should look as follows:

```
4
Please enter <location> <length>
12F 10
```

The program should open the file [abc](#) and load the 10 bytes, from byte 303 to byte 312 in the file into memory. The output should look like:

```
Loaded 10 bytes into 0xffbf4054
```

Task 1c: Save Into File

Write the function for the "Save Into File" option, which works as follows:
This option replaces *length* bytes at *target-location* of *filename* with bytes from the **hexeditplus** memory starting at virtual address *source-address*.

For example, the command:

```
./hexeditplus
```

Will print:

```
Choose action:
0-Toggle Debug Mode
1-Set File Name
2-Set Unit Size
3-File Display
4-Load Into Memory
5-Save Into File
6-Quit
```

When the user chooses option 5, the program should query the user for:

- *source-address* (source memory address, in hexadecimal), *source-address* can be set to `0`, in which case, the source address is *data_pointer*.
- *target-location* (target file offset, in hexadecimal),
- *length* (number of bytes, in decimal).

Implement the checks that the file can be opened (for writing and NOT truncating), and print appropriate debug messages in debug mode as in the previous task. Close the file after writing.

For example, after the file name was set to "abc", choosing option "5-Save Into File" using *source-address* 960c170, *target-location* 33 and *length* 4, the program should read *length* = 4 bytes from memory, starting at address 0x960c170, and write them to the file *abc*, starting from offset 0x33 (overwriting what was originally there). It should look as follows:

```
5
Please enter <source-address> <target-location> <length>
960c170 33 4
```

Note that the target file is the one specified using option 1 in the menu.

Also observe that after you execute this option, **only** *length* bytes of the file *filename* should be changed.

If `<target-location>` is greater than the size of `<filename>` you should print an error message and not copy anything.

You should use *hexedit* and task 1a (File Display), to verify that your code for tasks 1b and 1c works correctly, by loading a portion of a file into memory and saving it to another file. Here is some of *hexedit*'s output for the file [abc](#), verify that you understand why the output is as it is.

```
00000070 01 00 00 00 01 00 00 00 00 00 00 00 00 80 04 08
.....
00000080 00 80 04 08 EC 05 00 00 EC 05 00 00 05 00 00 00
.....
00000090 00 10 00 00 01 00 00 00 14 0F 00 00 14 9F 04 08
.....
000000A0 14 9F 04 08 0C 01 00 00 14 01 00 00 06 00 00 00
.....
000000B0 00 10 00 00 02 00 00 00 28 0F 00 00 28 9F 04 08
.....(...(
000000C0 28 9F 04 08 C8 00 00 00 C8 00 00 00 06 00 00 00
(.....
000000D0 04 00 00 00 04 00 00 00 48 01 00 00 48 81 04 08
.....H...H...
000000E0 48 81 04 08 44 00 00 00 44 00 00 00 04 00 00 00
H...D...D.....
000000F0 04 00 00 00 51 E5 74 64 00 00 00 00 00 00 00 00
....Q.td.....
00000100 00 00 00 00 00 00 00 00 00 00 00 00 06 00 00 00
.....
00000110 04 00 00 00 52 E5 74 64 14 0F 00 00 14 9F 04 08
....R.td.....
00000120 14 9F 04 08 EC 00 00 00 EC 00 00 00 04 00 00 00
.....
00000130 01 00 00 00 2F 6C 69 62 2F 6C 64 2D 6C 69 6E 75
....../lib/ld-linu
00000140 78 2E 73 6F 2E 32 00 00 04 00 00 00 10 00 00 00
x.so.2.....
00000150 01 00 00 00 47 4E 55 00 00 00 00 00 02 00 00 00
....GNU.....
00000160 06 00 00 00 0F 00 00 00 04 00 00 00 14 00 00 00
.....
00000170 03 00 00 00 47 4E 55 00 C1 4E 4D 18 B9 A6 21 8F
....GNU..NM...!.
```

Task 1d: File Modify

Write the function for the "File Modify" option:

This option replaces a unit at *location in file filename* with *val*.

The steps are:

1. Prompt the user for location and val (all in hexadecimal).
2. If debug mode is on, print the location and val given by the user.
3. Replace a unit at location in the file with the values given by val.

For example, the command:

```
./hexeditplus
```

Will print:

```
Choose action:
0-Toggle Debug Mode
1-Set File Name
2-Set Unit Size
3-File Display
4-Load Into Memory
5-Save Into File
6-File Modify
7-Quit
```

When the user chooses option 6, the program should query the user for:

- location (file location, in hexadecimal)
- val (new value, in hexadecimal)

For example, if unit size was set to 4, choosing option "6-File Modify" using location 0x40, val 0x804808a, will overwrite the 4 bytes starting at location 0x40, with the new value 804808a. It should look as follows:

```
6
Please enter <location> <val>
40 804808a
```

As in the previous task, you should check that the file is opened correctly and that the location chosen to be modified, given the current unit size, is valid, and act accordingly.

You can test the correctness of your code using task1a - "File Display".

Task 2: Reading ELF

Task 2a

Download the following file: [chezi](#).

`chezi` is an executable ELF file. It does not run as expected. Your task is to understand the reason for that.

Do the following:

1. Run the file.
2. Which function precedes `main` in execution ? (hint: The [assembly code in Lab 4](#)).
3. What is the virtual address to which this function is loaded (hint: use `readelf -s`)

Task 2b

Use your `hexeditplus` program from task 1 to display the entry point of a file.

What are the values of location/length? How do you know that?

Use the edit functions from `hexeditplus` program to fix the `chezi` file, so that it behaves as expected.

Task 3: Delving Deeper into the ELF Structure

task 3a

The goal of this task is to display the compiled code (in bytes) of the function `main`, in the `abc` executable above.

In order to do that, you need to:

1. find the offset (file location) of the function `main`.
2. find the size of the function `main`.
3. use your `hexeditplus` program to display the content of that function on the screen.

Finding the needed information:

1. Find the entry for the function `main` in the symbol table of the ELF executable (`readelf -s`).
2. In that reference you will find both the size of the function and the function's virtual address and section number.
3. In the section table of the executable, find the entry for the function's section (`readelf -s`).

4. Find both the section's virtual address (Addr), and the section's file offset (Off).
5. Use the above information to find the file offset of the function.

Task 3b-asm

This task is only for students of the architecture and splab course.

What are the first two machine instructions in function main, stated in assembly language?
I.e. you need to manually dis-assemble these first two instructions.
You can use the opcode information in the [nasm manual](#).

Have a look at [Practical session 3](#) page 9, before you delve into nasm manual.

Task 3b-splab

This task is for students registered for splab course only and NOT architecture.

Hack this executable file so that it does nothing when it is run: replace the code of the `main` function by [NOP](#) instructions.
Make sure you do NOT override the `ret` instruction ([Opcode](#): c3) in `main`.
Alternately, you can plant just one `ret` instruction (where?).

Task 4: Hacking: installing a patch using hexeditplus

The following file [ntsc](#) was meant to be a digit counter. Download it, and run it in the command-line.

```
./ntsc aabbaba123baacca  
./ntsc 1112111
```

What is the problem with the file? (hint, try this string: 0123456789)

Create a new program with a correct digit counter function (should get a `char*` and return an `int`), compile and test it. (remember to compile with the `-m32` flag in order to produce an ELF compatible with 32bits).

Use hexeditplus to replace (patch) the buggy `digit_cnt` function in the `ntsc` file with the corrected version from the new program.

You should do it using options 4 & 5 in hexeditplus.

(think: are there any kinds of restrictions on the code you wrote for the `digit_cnt` function?)

Explain how you did it, and show that it works.

Deliverables:

Tasks 1,2, and 3a must be completed during the regular lab. Tasks 3b and 4 may be done in a completion lab, but only if you run out of time during the regular lab. The deliverables must be submitted until the end of the day.

You must submit source files for task 1 and task 4 and a makefile that compiles them. The source files must be named task1.c, task4.c, and makefile.