Full Colour Multi Function Printer

RICOH IM C3000 IM C3500 IM C4500





Welcome to a new era of technology that keeps your workplace up to date with RICOH IM C3000 / C3500 / C4500 / C6000 range of intelligent devices. Device and technology that is designed to grow and adapt, just as your business does.

Today's workplace needs to be ready for tomorrow. RICOH Intelligent Devices provide smooth access to functionality upgrades and productivity enhancements when they are released, without needing to change your hardware. Turn your device into a powerful hub that helps you manage information workflows efficiently, usingtechnology that is scalable, secure, sustainable and simple.

Now is the time to:

- Protect your devices with easy access to security updates
- Take advantage of easy productivity upgrades at your own pace
- Save costs by bringing high-standard quality print output in-house
- Maximise productivity with streamlined workflows







Ricoh IM C4500 Outstanding 45-ppm Colour Copier MFP

Excellent Performance with the Best Quality Output

Greater Control of Scan and Print Management

Scanning of smaller sized documents can be easily done with the new small sized paper scan unit. The double feed detection unit helps to improve scan accuracy while the EFI controller enhances print management. Now, you can also create professional grade flyers at your own convenience with our inner multi-folding unit.



Seamless User Experience

Our intelligent devices offer efficient working and reduced user intervention by expanding paper capacity. Choose from our versatile finishing and paper options for a professional touch to save time and reduce outsourcing expenses. With RICOH Intelligent Support, experience maximum device uptime and minimal disruption across all your devices.





Maximise Cost Savings

Enjoy lower running costs and reduced energy consumption thanks to environmentally friendly low TEC (Typical Electricity Consumption) values. Furthermore, take advantage of RICOH Intelligent Support services that anticipate potential issues and send corrective instructions via the Smart Operation Panel, avoiding interruptions and prolonging the optimal performance of your device – avoiding the need for intervention by more costly IT resources.



Next-level Productivity with Smart Operations

Interact with the 10.1" Smart Operation Panel like a typical smart device and configure it for quick and easy access to apps you use most often. A variety of mobile connectivity options enable printing or scanning to the office network or cloud from a smart device with built in support for NFC, AirPrint or Mopria. All this underpinned by a unique suite of support apps from RICOH Smart Integration.

RICOH IM C3000 / IM C3500 / IM C4500 / IM C6000

MAIN SPECIFICATIONS

MODEL	RICOH IM C3000	RICOH IM C3500	RICOH IM C4500	RICOH IM C6000		
GENERAL	KICOTI IIVI C3000	KICOTI IWI C3300	RICOTT IN C4300	INICOTT INI COURT		
Warm-up Time		21 Seco	nds			
First Output Speed : B/W	4.5 Seconds	4.5 Seconds	3.6 Seconds	2.9 Seconds		
First Output Speed : Full Color	6.9 Seconds	6.9 Seconds	5.4 Seconds	4.2 Seconds		
Continuous Output Speed	30ppm	35ppm	45ppm	60ppm		
Memory Std/Max	зорріп			боррііі		
HDD Std/Max	2GB Std / 4GB Max					
ARDF Capacity	320GB Std/Max					
SPDF Capacity	100 Sheets 220 Sheets					
Weight [Mainframe]	Less Than 85.5Kg Less Than 87.5Kg					
Dimensions W x D x H [Standard]	Less Than 85.5Kg Less Than 87.5Kg 587 x 685 x 788 mm					
Dimensions W x D x H [Maximum]						
(excluding ARDF/SPDF)	668 x 738 x 1030 mm					
Power Source	220 - 240V 50/60Hz					
COPIER						
Multiple Copying		Up to 999	Copies			
Resolution		600 d	pi			
Zoom		From 25% to 400	% in 1% Step			
PRINTER						
CPU	Intel Atom Processor ApolloLake 1.3GHz Intel Atom Processor ApolloLake 1.6GHz					
Printer Language : Standard		PCL5c, PCL6, Postscript 3 (emula	tion), PDF direct (emulation)			
Printer Language : Option	Genu	ine Adobe® Postscript®3™, XPS, IPDS	S, PictBridge, PDF Direct from A	.dobe®		
Print Resolution		1,200 x 1,2	200 dpi			
Network Interface : Standard	Ethernet	10 base-T/100base-TX/1000 base-T, U	JSB Host I/F Type A, USB Device	I/F Type B		
Network Interface : Option	Bi-direction	nal IEEE 1284/ECP, Wireless LAN (IEE	E 802.11a/b/g/n), Additional NI	C (2nd port)		
Mobile Printing Capability	Apple A	AirPrint™, Mopria, Google Cloud Pri	int, NFC, Ricoh Smart Device Co	nnector		
Windows® environments	Windows® 7, Windows® 8	.1, Windows®10, Windows® Server 2		Windows® Server 2012R2,		
Mas Of anvironments		Windows® Se				
Mac OS environments	LINIV	Macintosh OS X1		M® AIV		
UNIX environments SAP® environments	UNIX	Sun® Solaris, HP-UX, SCO OpenServe SAP® S,		M- AIX		
		IBM iSe				
Other Supported environments SCANNER		ibivi ise	nes			
Scanning Speed		120inm (Simplex) / 2	240inm (dunley)			
Resolution : Maximum	120ipm (Simplex) / 240ipm (duplex)					
Compression Method	1,200 dpi TIFF (MH, MR, MMR, JBIG2), Grayscale					
compression wethou						
File Formats	Single Page TIFF, Single page JPEG, Single Page High compression PDF, Single page PDF-A, Multi page TIFF, Multi page PDF, Multi page High compression PDF, Multi Page PDF-A					
Scan Modes	Email, Folder, USB, SD Card					
FACSIMILE		2,	35, 35 ca. a			
Circuit		PSTN, P				
Tranmission Speed	2 Seconds					
·		2 Secon	nds			
Modem Speed : Maximum		2 Secon 33.6 Kk	nds ops			
Modem Speed : Maximum Resolution : Standard		2 Secor 33.6 Kt 8 x 3.65 line/mm,	nds ops 200 x 100 dpi			
Modem Speed : Maximum Resolution : Standard Resolution : Option		2 Secor 33.6 Kt 8 x 3.65 line/mm, 16 x 15.4 line/mm,	nds ops 200 x 100 dpi 400 x 400 dpi			
Modem Speed : Maximum Resolution : Standard Resolution : Option Compression Method		2 Secor 33.6 Kt 8 x 3.65 line/mm, 16 x 15.4 line/mm, MH, MR, Mt	nds ops 200 x 100 dpi .400 x 400 dpi MR, JBIG			
Modem Speed : Maximum Resolution : Standard Resolution : Option Compression Method Memory : Standard		2 Secor 33.6 Kl 8 x 3.65 line/mm, 16 x 15.4 line/mm, MH, MR, MN 4MB (320	nds ops 200 x 100 dpi 400 x 400 dpi MR, JBIG Pages)			
Modem Speed : Maximum Resolution : Standard Resolution : Option Compression Method Memory : Standard Memory : Maximum		2 Secor 33.6 Kt 8 x 3.65 line/mm, 16 x 15.4 line/mm, MH, MR, Mt	nds ops 200 x 100 dpi 400 x 400 dpi MR, JBIG Pages)			
Modem Speed: Maximum Resolution: Standard Resolution: Option Compression Method Memory: Standard Memory: Maximum PAPER HANDLING		2 Secor 33.6 Kt 8 x 3.65 line/mm, 16 x 15.4 line/mm, MH, MR, MN 4MB (320 60MB (4,800	nds ops 200 x 100 dpi 400 x 400 dpi MR, JBIG Pages)			
Modem Speed: Maximum Resolution: Standard Resolution: Option Compression Method Memory: Standard Memory: Maximum PAPER HANDLING Recommended Paper Size		2 Secor 33.6 Kt 8 x 3.65 line/mm, 16 x 15.4 line/mm, MH, MR, MN 4MB (320 60MB (4,800 SRA3, A3, A4, A5,	nds ops 200 x 100 dpi 400 x 400 dpi MR, JBIG Pages) D Pages) A6, B4, B5, B6			
Modem Speed: Maximum Resolution: Standard Resolution: Option Compression Method Memory: Standard Memory: Maximum PAPER HANDLING Recommended Paper Size Paper Input Capacity Std		2 Secor 33.6 Kt 8 x 3.65 line/mm, 16 x 15.4 line/mm, MH, MR, MN 4MB (320 60MB (4,800 SRA3, A3, A4, A5,	nds pps 200 x 100 dpi 400 x 400 dpi MR, JBIG Pages) D Pages) A6, B4, B5, B6 eets			
Modem Speed: Maximum Resolution: Standard Resolution: Option Compression Method Memory: Standard Memory: Maximum PAPER HANDLING Recommended Paper Size Paper Input Capacity Std Paper Input Capacity Max		2 Secor 33.6 Kt 8 x 3.65 line/mm, 16 x 15.4 line/mm, MH, MR, MN 4MB (320 60MB (4,800 5RA3, A3, A4, A5, 1,200 Sh	nds pps 200 x 100 dpi 400 x 400 dpi MR, JBIG Pages) D Pages) A6, B4, B5, B6 eets eets			
Modem Speed: Maximum Resolution: Standard Resolution: Option Compression Method Memory: Standard Memory: Maximum PAPER HANDLING Recommended Paper Size Paper Input Capacity Std Paper Output Capacity Std	1 625 9	2 Secor 33.6 Kt 8 x 3.65 line/mm, 16 x 15.4 line/mm, MH, MR, MN 4MB (320 60MB (4,800 5RA3, A3, A4, A5, 1,200 Sh 4,700 Sh	nds pps 200 x 100 dpi 400 x 400 dpi MR, JBIG Pages) D Pages) A6, B4, B5, B6 eets eets	s Sheets		
Modem Speed: Maximum Resolution: Standard Resolution: Option Compression Method Memory: Standard Memory: Maximum PAPER HANDLING Recommended Paper Size Paper Input Capacity Std Paper Output Capacity Std Paper Output Capacity Max	1,625 9	2 Secor 33.6 Kt 8 x 3.65 line/mm, 16 x 15.4 line/mm, MH, MR, MN 4MB (320 60MB (4,800 5RA3, A3, A4, A5, 1,200 Sh 4,700 Sh 500 She	nds pps 200 x 100 dpi 400 x 400 dpi MR, JBIG Pages) D Pages) A6, B4, B5, B6 eets eets 3,625	i Sheets		
Modem Speed: Maximum Resolution: Standard Resolution: Option Compression Method Memory: Standard Memory: Maximum PAPER HANDLING Recommended Paper Size Paper Input Capacity Std Paper Output Capacity Std		2 Secon 33.6 Kl 8 x 3.65 line/mm, 16 x 15.4 line/mm, MH, MR, MN 4MB (320 60MB (4,800 SRA3, A3, A4, A5, 1,200 Sh 4,700 Sh 500 She	nds pps 200 x 100 dpi 400 x 400 dpi WR, JBIG Pages) D Pages) A6, B4, B5, B6 eets eets eets gg/m²			
Modem Speed: Maximum Resolution: Standard Resolution: Option Compression Method Memory: Standard Memory: Maximum PAPER HANDLING Recommended Paper Size Paper Input Capacity Std Paper Output Capacity Std Paper Output Capacity Max		2 Secor 33.6 Kt 8 x 3.65 line/mm, 16 x 15.4 line/mm, MH, MR, MN 4MB (320 60MB (4,800 5RA3, A3, A4, A5, 1,200 Sh 4,700 Sh 500 She	nds pps 200 x 100 dpi 400 x 400 dpi MR, JBIG Pages) D Pages) A6, B4, B5, B6 eets eets g/m² etterhead, Cardstock, Preprinte			
Modem Speed: Maximum Resolution: Standard Resolution: Option Compression Method Memory: Standard Memory: Maximum PAPER HANDLING Recommended Paper Size Paper Input Capacity Std Paper Output Capacity Std Paper Output Capacity Max Paper Weight Paper Types		2 Secor 33.6 Kt 8 x 3.65 line/mm, 16 x 15.4 line/mm, MH, MR, MM 4MB (320 60MB (4,800 SRA3, A3, A4, A5, 1,200 Sh 4,700 Sh 500 She sheets 60 - 3000 paper, Special paper, Color paper, Le	nds pps 200 x 100 dpi 400 x 400 dpi MR, JBIG Pages) D Pages) A6, B4, B5, B6 eets eets g/m² etterhead, Cardstock, Preprinte			
Modem Speed: Maximum Resolution: Standard Resolution: Option Compression Method Memory: Standard Memory: Maximum PAPER HANDLING Recommended Paper Size Paper Input Capacity Std Paper Input Capacity Std Paper Output Capacity Std Paper Output Capacity Max Paper Weight Paper Types ECOLOGY	Plain paper, Recycle	2 Secor 33.6 Kl 8 x 3.65 line/mm, 16 x 15.4 line/mm, MH, MR, MN 4MB (320) 60MB (4,800) SRA3, A3, A4, A5, 1,200 Sh 4,700 Sh 500 She Sheets 60 - 300, paper, Special paper, Color paper, Le Coated paper, Envelope, Glos	nds pps 200 x 100 dpi 400 x 400 dpi WR, JBIG Pages) D Pages) A6, B4, B5, B6 eets eets eets g/m² etterhead, Cardstock, Preprinte s paper, Label paper, OHP	d paper, Bond paper,		
Modem Speed: Maximum Resolution: Standard Resolution: Option Compression Method Memory: Standard Memory: Maximum PAPER HANDLING Recommended Paper Size Paper Input Capacity Std Paper Input Capacity Std Paper Output Capacity Std Paper Weight Paper Types ECOLOGY Power Consumption: Max	Plain paper, Recycle Less Than	2 Secor 33.6 Kl 8 x 3.65 line/mm, 16 x 15.4 line/mm, MH, MR, MN 4MB (320) 60MB (4,800) SRA3, A3, A4, A5, 1,200 Sh 4,700 Sh 500 She sheets 60 - 300, paper, Special paper, Color paper, Le Coated paper, Envelope, Glos	nds pps 200 x 100 dpi 400 x 400 dpi MR, JBIG Pages) D Pages) A6, B4, B5, B6 eets eets eets g/m² etterhead, Cardstock, Preprinte s paper, Label paper, OHP Less Tha	d paper, Bond paper, in 1,850 W		
Modem Speed: Maximum Resolution: Standard Resolution: Option Compression Method Memory: Standard Memory: Maximum PAPER HANDLING Recommended Paper Size Paper Input Capacity Std Paper Input Capacity Std Paper Output Capacity Std Paper Output Capacity Max Paper Weight Paper Types ECOLOGY	Plain paper, Recycle	2 Secor 33.6 Kl 8 x 3.65 line/mm, 16 x 15.4 line/mm, MH, MR, MR 4MB (320) 60MB (4,800 SRA3, A3, A4, A5, 1,200 Sh 4,700 Sh 500 She sheets 60 - 300, paper, Special paper, Color paper, Le Coated paper, Envelope, Glos	nds pps 200 x 100 dpi 400 x 400 dpi MR, JBIG Pages) D Pages) A6, B4, B5, B6 eets eets eets g/m² etterhead, Cardstock, Preprinte s paper, Label paper, OHP Less Tha	d paper, Bond paper,		

RICOH IM C3000 / IM C3500 / IM C4500 / IM C6000

MAIN SPECIFICATIONS

MODEL	RICOH IM C3000	RICOH IM C3500	RICOH IM C4500	RICOH IM C6000		
OUTPUT TRAY AND FINISHER OPTION						
1 x 550-Sheets Paper Tray (PB 3270)	Paper Size : A6-SRA3, Paper Weight : 60-300g/m²					
2 x 550-Sheets Paper Tray (PB 3280)	Paper Size : A6-SRA3, Paper Weight : 60-300g/m²					
2,000-Sheets Large Capacity Tray (LCIT PB3290)	Paper Size : A4, Paper Weight : 60-300g/m²					
1,500-Sheets Large Capacity Tray (LCIT RT3040)	Paper Size : A4, Paper Weight : 60-300g/m²					
1,000-Sheets Hybrid Finisher (SR3260)	Paper Size : Proof Tray :A6-A3, Shift Tray : A6-A3, Paper weight : 60-300g/m² Staple paper size : A4-A3, Staple paper weight :52-105g/m Staple position : Top, Bottom, 2 Staples Staple capacity Max : 50 sheets (A4) 30 Sheets (A3) Stapleless capacity Max : 5 sheets (A4/A3)					
3,000-sheet Finisher (SR 3280) [Available for IM C4500, IM C6000 only]	Paper Size : Proof Tray :A6-A3, Shift Tray : A6-A3, Paper weight : 60-300g/m² Staple paper size : A4-A3, Staple paper weight :52-105g/m Staple position : Top, Bottom, 2 Staples, Top slant Staple capacity Max : 50 sheets (A4) 30 Sheets (A3)					
1,000-Sheet Booklet Finisher (SR3270)	Paper Size : Proof Tray :A6-A3, Shift Tray : A6-A3, Booklet tray : A4-A3 Paper weight : 60-300g/m² Staple paper size : A4-A3, Staple paper weight :52-105g/m Staple position : Top, Bottom, 2 Staples, Booklet Staple capacity Max : 50 sheets (A4) 30 Sheets (A3)					
2,000-Sheet Booklet Finisher (SR3290) [Available for IM C4500, IM C6000 only]	Paper Size : Proof Tray :A6-A3, Shift Tray : A6-A3, Booklet tray : A4-A3 Paper weight : 60-300g/m² Staple paper size : A4-A3, Staple paper weight :52-105g/m Staple position : Top, Bottom, 2 Staples, Booklet Staple capacity Max : 50 sheets (A4) 30 Sheets (A3)					
500-Sheet Internal Finisher (SR3250) (IM C6000 is not supported)	Paper Size : A6-A3, Paper weight : 60-300g/m² Staple paper size : A4-A3, Staple paper weight :52-105g/m Staple position : Top, Bottom, 2 Staples Staple capacity Max : 50 sheets (A4) 30 Sheets (A3)					
250-Sheet Internal Finisher (SR3300) (Available for IM C3000, IM C3500 only)	Paper Size : A6-A3, Paper weight : 60-300g/m² Staple paper size : A4-A3, Staple paper weight :52-105g/m Staple position : Top,1 Staple Staple capacity Max : 2-5 sheets (A4)					
Internal Shift Tray (SH3080)	Tray Capacity: 250 sheets, Paper size: 320 mm x 600 mm or smaller, Paper weight: 60-300g/m²					
One-bin tray (BN3130)	Tray Capacity: 125 sheets, Paper size: A5 - A3, Paper weight: 52-300g/m²					

OTHER OPTIONS

Platen Cover PN2000, DF3110, DF3120, Fax Option Type M37, G3 Interface Unit Type M37, Fax Connection unit Type M37, FAX Memory unit Type M19 64MB, Memory Unit Type M37 4GB, Caster Table Type M3, VM Card Type M37, Side Tray, Punch Unit NA/EU/SC (PU3070,PU3080,PU3090), Internal Multi-fold unit FD3010, Camera direct print card, Postscript3 Unit Type M37, XPS direct print Option Type M37, IEEE 1284 I/F Type M19, IEEE 802.11a/g/n I/F Type M19, Device server option Type M37, File format Converter Type M19, OCR Unit Type M12, M13, M1P aper Feeding Unit Type M37, Page Keeper Type M37, ADF Handle, External Keyboard Bracket Type M19, Optional Counter Interface Unit Type M12, Key Counter Bracket Type M3, NFC Card Reader Type M37, Smart Card Reader Built in Unit Type M37, External USB Keyboard (No bracket), Color Controller E-25C, Unicode Font Package for SAP®License.

^{*}AirPrint certification will be available in 2019.