Santa Jose State University

Department of Computer Science
Database Management Systems - I (CS 157A)

Homework #3 (Preview)

Q1 [1 pt]: using the same Movie schema we discussed in HW #2:
 Movies(title, year, length, genre, studioName, producerC#)
 StarsIn(movieTitle, movieYear, starName)
 MovieStar(name, address, gender, birthdate)
 MovieExec(name, address, cert#, netWorth)
 Studio(name, address, presC#)

Declare the following referential integrity constraints for the Movie database:

- a) The producer of a movie must be someone mentioned in MovieExec. Modification to MovieExec that violate this constraint are rejected?
- b) Repeat (a), but violations result in the producer# in Movie being set to NULL.
- c) Repeat (a), but violations result in the deletion or update of the offending Movie tuple.
- d) A movie that appears in StarIn must also appear in Movie. Handle violations by rejecting the modifications?

ANSWER)

```
CREATE TABLE Movies (
title CHAR(100),
year INT,
length INT,
genre CHAR(10),
studioName CHAR(30),
producerC# INT REFERENCES MovieExec(cert#)
ON DELETE SET NULL
ON UPDATE SET NULL,
PRIMARY KEY (title, year)
);
```

```
d)
CREATE TABLE StarsIn (
movieTitle CHAR(100) REFERENCES Movie(title),
movieYear INT,
starName CHAR(30),
PRIMARY KEY (movieTItle, movieYear, starName)
```

• Q2 [1 pt]: Write the following assertion to this schema:

Product(maker, model, type) PC(model, speed, ram, hd, price)

← hd: hard disk

Laptop(model, speed, ram, hd, screen, price)

Printer(model, color, type, price)

- a) No manufacturer of PC's may also make laptops?
- b) A manufacturer of a PC must also make a laptop with at least as great a processor speed?
- c) If a laptop has larger main memory than a PC, then the laptop must also have a higher price than the PC?
- d) If a relation Product mentions a model and its type, then this model must appear in the relation appropriate to that type?

ANSWER)

```
CREATE ASSERTION CHECK
  (NOT EXISTS
           (SELECT maker FROM Product NATURAL JOIN PC)
      INTERSECT
           (SELECT maker FROM Product NATURAL JOIN Laptop)
     )
 );
```

• Q3 [1 pt]: Write the following as triggers for the following schema. In each case disallow or undo the modification if it does not satisfy the stated constraint.

Product(maker, model, type) Laptop(model, speed, ram, hd, screen, price) Printer(model, color, type, price)

a) When updating the price of a PC, check that there is no lower

priced PC with the same speed?

- b) When inserting a new printer, check that the model number exists in product?
- c) When making any modification to the laptop relation, check that the average price of laptop for each manufacturer is at least \$1,500?
- d) When updating the RAM or Hard Disk of any PC check that the updated PC has at least 100 times as much hard disk as RAM?

ANSWER) a) CREATE TRIGGER LowPricePCTrigger AFTER UPDATE OF price ON PC REFERENCING OLD ROW AS OldRow, OLD TABLE AS OldStuff, NEW ROW AS NewRow, NEW TABLE AS NewStuff FOR EACH ROW WHEN (NewRow.price < ALL (SELECT PC.price FROM PC WHERE PC.speed = NewRow.speed)) BEGIN DELETE FROM PC WHERE (model, speed, ram, hd, price) IN NewStuff; INSERT INTO PC (SELECT * FROM OldStuff); END;

- Q4 [1 pt]: Construct the following Views from the Schema below:
 MovieStar(name, address, gender, birthdate)
 MovieExec(name, address, cert#, netWorth)
 Studio(name, address, presC#)
 - a) A view RichExec giving the name, address, certificate number, and net worth of all executives with a net worth of at least \$10,000,000?
 - b) A view StudioPress giving the name, address, and certificate number of all executives who are studio presidents?
 - c) A view ExecutiveStar giving the name, address, gender, birth date, certificate number, and net worth of all individuals who are both executives and stars?

```
ANSWER)
```

a)

CREATE VIEW RichExec AS

SELECT * FROM MovieExec WHERE netWorth >= 10000000;

• Q5 [1 pt]: Using the following base Tables:

Product(maker, model, type)

PC(model, speed, ram, hd, price)

Suppose we create the following View:

CREAT VIEW NewPC AS

SELECT maker, model, speed, ram, hd, price

FROM Product, PC

WHERE Product, model = PC. model AND type = 'PC';

Notice that we have made a check for consistency: that the model number not only appears in the PC relation, but the type attribute of Product indicates that the product is a PC.

- a) Is this View updatable?
- b) Write an instead-of trigger to handle an insertion into the view?
- c) Write an instead-of trigger to handle an update of the price?
- d) Write an instead-of trigger to handle a deletion of a specified tuple from this view?

ANSWER)

a) No, the view is not updatable since it is constructed from two different relations.

b)

CREATE TRIGGER NewPCInsert

INSTEAD OF INSERT ON NewPC

REFERENCING NEW ROW AS NewRow

FOR EACH ROW

(INSERT INTO Product VALUES(NewRow.maker, NewRow.model, 'pc'))

(INSERT INTO PC VALUES(NewRow.model, NewRow.speed, NewRow.ram, NewRow.hd, NewRow.price));