

```
#include <stdlib.h>
#include <string.h>
#include <ctype.h>
```

```
#define MAXPAROLA 30
#define MAXRIGA 80
```

```
int main(int argc, char *argv[])
{
    int freq[MAXPAROLA]; /* vettore di contatori
delle frequenze delle lunghezze delle parole */
    char riga[MAXRIGA];
    int i, inizio, lunghezza;
    FILE *f;
```

```
for(i=0; i<MAXPAROLA; i++)
    freq[i]=0;
```

```
if(argc != 2)
```

```
{
    printf(stderr, "ERRORE, serve un parametro con il nome del file\n");
    exit(1);
}
```

```
f = fopen(argv[1], "r");
if(f==NULL)
```

```
{
    printf(stderr, "ERRORE, impossibile aprire il file %s\n", argv[1]);
    exit(1);
}
```

```
while( fgets( riga, MAXRIGA, f ) != NULL )
```



Synchronization

Exercises on semaphores and mutexes

Stefano Quer

Dipartimento di Automatica e Informatica

Politecnico di Torino

License Information

This work is licensed under the license



Attribution-NonCommercial-NoDerivatives 4.0 International

This license requires that reusers give credit to the creator. It allows reusers to copy and distribute the material in any medium or format in unadapted form and for noncommercial purposes only.

① **BY:** Credit must be given to you, the creator.

② **NC:** Only noncommercial use of your work is permitted.

Noncommercial means not primarily intended for or directed towards commercial advantage or monetary compensation.

③ **ND:** No derivatives or adaptations of your work are permitted.

To view a copy of the license, visit:

<https://creativecommons.org/licenses/by-nc-nd/4.0/?ref=chooser-v1>

Exercise 01

- ❖ Implement a C or C++ program that
 - Runs 1 thread TA and 1 thread TB
 - TA and TB include an infinite cycle in which they display one single character 'A' or 'B', respectively
 - Synchronize threads such that for each set of 3 characters there is 1 character A and 2 characters B in any position
 - Execution example

pgrm

ABB

BBA

BAB

etc.

Solution

```
#include <iostream>
#include <semaphore>
#include <thread>
#include <unistd.h>
```

To "sleep" for a random time

```
using std::cout;
using std::endl;
```

Mutexes cannot be used because they must be locked and unlocked by the same thread

```
std::counting_semaphore sa{1}, sb{2}, me{1};
int n;
```

Counter

```
static void TA (int);
static void TB (int);
```

2 Threads
2 semaphores
1 mutex (semaphore)
TA (sa) is the one to start

Solution

```
int main (int argc, char **argv) {
    int n1, n2;

    if (argc != 2) {
        fprintf (stderr, "Syntax: %s num_threads\n", argv[0]);
        return (1);
    }
    n1 = atoi(argv[1]);
    n2 = 2 * n1;
    n = 0;

    std::thread ta (TA, n1);
    std::thread tb (TB, n2);

    ta.join();
    tb.join();

    return (0);
}
```

To avoid running for
ever we generate
n1 threads TA
n2 threads TB

Solution

```
static void TA (int nc) {  
    for (int i=0; i<nc; i++) {  
        sleep (rand()%2);  
        sa.acquire();  
        me.acquire();  
        cout << "A";  
        n++;  
        if (n>=3) {  
            cout << endl;  
            n = 0; sa.release(); sb.release(); sb.release();  
        }  
        me.release();  
    }  
    return;  
}
```

Wait for a random time

If TA starts

It must not
start with TB

The last thread wakes-up
one A and two B threads

Solution

```
static void TB (int nc) {  
    for (int i=0; i<nc; i++) {  
        sleep (rand()%2);  
        sb.acquire();  
        me.acquire();  
        cout << "B";  
        n++;  
        if (n>=3) {  
            cout << endl;  
            n = 0;  
            sa.release(); sb.release(); sb.release();  
        }  
        me.release();  
    }  
    return;  
}
```

Wait for a random time

If TB starts

It must not
start with TA

The last thread wakes-up
one A and two B threads

Exercise 02

Exam of September
08, 2023

- ❖ A C program can execute four different threads
 - TP (thread plus), TM (thread minus), TS (thread star), and TNL (thread newline)
- ❖ Each thread is organized through an infinite cycle containing synchronization instructions but a **single** IO instruction
 - Thread TP displays a "+"
 - Thread TM displays a "-"
 - Thread TS displays a "*"
 - Thread TNL displays a "\n" (endl)

Exercise 02

- ❖ Synchronize the four threads to print the following sequence of lines

+++++

+++++

etc.

- Where the number of characters on each row is given as a parameter to the main program (e.g., 10)

Solution

```
#include <iostream>
#include <semaphore>
#include <thread>
#include <unistd.h>

using std::cout;
using std::endl;

std::counting_semaphore sp{1}, sm{0}, ss{0}, snl{0};

static void TP (int);
static void TM (int);
static void TS (int);
static void TNL ();
```

4 Threads
4 Semaphores
SP (+) is the one to start

Solution

```
int main (int argc, char **argv) {  
    int n;  
    if (argc != 2) {  
        ... error ...  
    }  
    n = atoi(argv[1]);  
    std::thread tp (TP, n);  
    std::thread tm (TM, n);  
    std::thread ts (TS, n);  
    std::thread tnl (TNL);  
    tp.join();  
    tm.join();  
    ts.join();  
    tnl.join();  
    return (0);  
}
```

Threads never stop; but if we do not wait,
we return and we stop all threads
(there is no pthread_exit)

Solution

```
static void TP (int n) {  
    int np = 0;  
    while (1) {  
        sp.acquire();  
        cout << "+";  
        np++;  
        if (np < n) {  
            sp.release();  
        } else {  
            np = 0;  
            snl.release();  
        }  
    }  
    return;  
}
```

Re-wake up TP

Reset the number of calls
for TP and call TNL

Solution

```
static void TM (int n) {  
    int nm = 0;  
    while (1) {  
        sm.acquire();  
        cout << "-";  
        nm++;  
        if (nm < n) {  
            sm.release();  
        } else {  
            nm = 0;  
            snl.release();  
        }  
    }  
    return;  
}
```

Re-wake up TM

Reset the number of calls
for TM and call TNL

Solution

```
static void TS (int n) {  
    int ns = 0;  
    while (1) {  
        ss.acquire();  
        cout << "*";  
        ns++;  
        if (ns < n) {  
            ss.release();  
        } else {  
            ns = 0;  
            snl.release();  
        }  
    }  
    return;  
}
```

Re-wake up TS

Reset the number of calls
for TS and call TNL

Solution

```
static void TNL () {  
    int nml = 0;  
    while (1) {  
        snl.acquire(); nml++; cout << endl;  
        sleep (rand()%2);  
        if (nml==1) {  
            sm.release();  
        } else {  
            if (nml==2) {  
                ss.release();  
            } else {  
                sp.release(); nml = 0;  
            }  
        }  
    }  
}  
return;  
}
```

POSIX
(we can use C++ to sleep)

Wake up TM

Wake up TS

Wake up TP
and restart

Exercise 03

❖ Fairness consideration on synchronization primitives

➤ C++ synchronization primitives are unfair

- Some threads can lock a mutex more often than others
 - A simple experiment on Linux shows that if threads repeatedly try to lock the same mutex, some threads lock the mutex 1.13x more often than others
- Some threads can lock a semaphore or a spinlock 3.91x more often than others

Exercise 03

- ❖ Implement a **priority semaphore**, i.e., a semaphore in which
 - Each thread has an intrinsic priority
 - The priority is an integer value
 - The **higher** priority corresponds to the **lower** value
 - Unlocking is done in order following the threads priority

Solution

❖ Core idea

- The semaphore must have a **priority queue** associated with it, where threads await to be signalled
- When a call to the signal function wakes-up a thread, threads must be woken-up following their priority
 - We have to awake the threads with the higher priority among the ones waiting on that semaphore

In C++ lock and unlock must be called by the same thread.

We should use C++ semaphores but semaphores are not copyable

Solution

```
#include <iostream>
#include <algorithm>
#include <vector>
#include <map>
#include <thread>
#include <semaphore>
```

```
using std::cout;
using std::endl;
...
```

```
const int TIME = 3;
```

```
map<int, std::unique_ptr<std::binary_semaphore>> my_sem;
std::mutex m;
```

C++20 semaphore are neither copyable nor movable.
We need to carefully use dynamic memory allocation

Solution

Worker running threads

```
static void worker (int i, int priority) {  
    m.lock();  
    cout << "Locking thread " << i <<  
          " with priority " << priority << endl;  
    m.unlock();  
    my_sem.insert  
        ({priority, std::make_unique<std::binary_semaphore>(0)});  
    (*my_sem[priority]).acquire();  
    m.lock();  
    cout << "          Unlocked thread " << i <<  
          " with priority " << priority << endl;  
    m.unlock();  
    return;  
}
```

Solution

Main: Part 1

```
int main (int argc, char *argv[]) {  
    int i, priority;  
    if (argc != 2) {  
        cout << "Syntax: " << argv[0] << " num_threads\n";  
        return (1);  
    }  
    int n = atoi (argv[1]);  
    vector<thread> pool;  
    for (i=0; i<n; i++) {  
        priority = (i+1) * 10;  
        pool.emplace_back([i, priority] { worker (i, priority); });  
    }  
    std::this_thread::sleep_for  
        (std::chrono::seconds(rand()%TIME));  
}
```

Running workers

From POSIX sleep to C++

Put the thread in a sleep status for
rand()%TIME seconds

Solution

Main: Part 2

```
i = 0;
for (const auto &t : my_sem) {
    m.lock();
    cout << "      Unlocking thread " << i++ <<
          " with priority " << t.first << endl;
    m.unlock();
    (*(t.second)).release();
}
for (i=0; i<n; i++) {
    pool[i].join();
}
cout << "Main exits." << endl;
return (1);
}
```

Wait workers

Solution

```
Locking thread 0 with priority 10
Locking thread 6 with priority 70
Locking thread 2 with priority 30
Locking thread 1 with priority 20
Locking thread 9 with priority 100
...
    Unlocking thread 0 with priority 10
    Unlocking thread 1 with priority 20
    ...
        Unlocked thread 0 with priority 10
        Unlocked thread 1 with priority 20
    Unlocking thread 5 with priority 60
    ...
        Unlocked thread 5 with priority 60
        Unlocked thread 9 with priority 100
        Unlocked thread 4 with priority 50
        Unlocked thread 3 with priority 40
    ...
Main exits.
```

Output

Locking the threads

Unlocking them

...

... which then
start

Exercise 04

- ❖ Write a program to implement an **election algorithm** that elects a leader thread
 - The system has N threads
 - Each thread has its
 - Thread identifier
 - Rank, i.e., and integer value randomly generated
 - To elect the leader each thread must
 - Compare its own rank value with the current value in **best_rank** to decide if it is the leader or not
 - To do that, it synchronizes with all the other threads
 - It re-start when the election process is completed (i.e., all other threads have updated the value of **best_rank**)

Exercise 04

- When all threads have done their job, each thread displays
 - Its identifier and its rank value
 - The leader thread identifier and its rank value
- Restriction
 - Threads cannot access the rank value of other threads, only the current best thread rank value is available in a global variable **best_rank** together with the corresponding thread identifier
 - Hint: Referring to a voting algorithm, use a global variable to count the number of threads that completed their voting process

Solution

C Code

Write the corresponding C++

```
#include <sys/time.h>
#include <time.h>
#include <stdlib.h>

#define N 10

typedef struct best_s {
    int rank;
    long int id;
    int num_votes;
    pthread_mutex_t mutex;
} best_t;

best_t *best;
sem_t *sem;
int max_random (int max);
```

Thread structure

Semaphore to make
threads wait

Solution

```
int main (int argc, char **argv){
    pthread_t th;
    int i, j, k, pi;
    best = (best_t *) malloc (sizeof (best_t));
    best->rank = best->num_votes = 0;
    pthread_mutex_init (&best->mutex, NULL);
    sem = (sem_t *) malloc (sizeof (sem_t));
    sem_init (sem, 0, 0);
    for (i = 0; i < N; i++) {
        // Assign a rank to pi
        ...
        pthread_create (&th, NULL, process, (void *) pi);
    }
    pthread_exit (0);
}
```

Must assign
different rank values

Solution

```
static void *process (void *arg){  
    int rank = (int) arg;  
    int i;  
    long int id;  
    id = pthread_self ();  
    pthread_detach (pthread_self ());  
}
```

Solution

```
pthread_mutex_lock (&best->mutex);  
if (rank > best->rank) {  
    best->rank = rank;  
    best->id = id;  
}
```

Check personal rank
with best global rank

Update best rank

```
best->num_votes++;  
if (best->num_votes < N) {  
    pthread_mutex_unlock (&best->mutex);  
    sem_wait (sem);          /* wait for all to vote */  
} else {  
    pthread_mutex_unlock (&best->mutex);  
    for (i = 0; i < N - 1; i++)  
        sem_post (sem);      /* release all waiting */  
}
```


If not the last one,
wait the others

If the last one,
release all

```
printf ("my_id=%ld my_rank=%d leader_id=%ld leade_rank=%d\n",  
        id, rank, best->id, best->rank);
```

```
}
```


- ❖ Which computes the sum of the elements of the array as represented in the picture



Exercise 05

- ❖ In particular
 - All sums must be executed in parallel by $n/2$ (at most) separate threads
 - Each thread is associated with one of the first $n/2$ cells of the array
- ❖ Note that the number of sums each thread will have to execute depends on the position of the cell
- ❖ Manage synchronization between threads with semaphores, so that all sums are made respecting precedence

Solution

C Code

Write the corresponding C++

```
#include <stdio.h>
#include <stdlib.h>
#include <unistd.h>
#include <pthread.h>
#include <semaphore.h>
```

```
typedef struct {
    int *vet;
    sem_t *sem;
    int n;
    int id;
} args_t;
```

```
... main ...
```

Array of n elements

Array of n/2 semaphores

User and thread identifier

Initialize variables and
calls function array_sum

Solution

Call the thread functions

```
int array_sum (int *vet, int n) {
    int k=n/2; pthread_t *tids; args_t *args; sem_t *sem;
    tids = (pthread_t *) malloc (k*sizeof(pthread_t));
    sem = (sem_t *) malloc (k*sizeof(sem_t));
    for (int i=0; i<k; ++i) sem_init(&sem[i], 0, 0);
    args = (args_t *) malloc (k*sizeof(args_t));
    for (int i=0; i<k; ++i) {
        args[i].id = i; args[i].vet = vet;
        args[i].n = n; args[i].sem = sem;
    }
    for (int i=0; i<k; ++i)
        pthread_create (&tids[i], NULL, adder, &args[i]);
    pthread_join (tids[0], NULL);
    for (int i=0; i<k; ++i) sem_destroy(&sem[i]);
    free (tids);
    free (sem);
    free (args);
    return vet[0];
}
```

n/2 Ts and
Sems

Initialize

Run threads

Wait for
threads and
free memory

Solution

Thread function

```

void *adder (void * arg) {
    sem_t *sem = ((args_t *) arg)->sem;
    int *vet = ((args_t *) arg)->vet;
    int id = ((args_t *) arg)->id;
    int n = ((args_t *) arg)->n;
    int k = n/2, i = 0;
    while (k != 0) {
        if (i!=0 && k<n/2)
            sem_wait (&sem[id + k]);
        else
            i++;
        vet[id] += vet[id + k];
        k = k/2;
        if (id >= k) {
            sem_post (&sem[id]);
            break;
        }
    }
    pthread_exit(0);
}

```

k = # iterations

... but not during the first cycle

Make the sum

My sum has been done

This thread must stop

Wait for the previous sum to be done $id \in [0, n/2[$ 