

Student verification (CLI) for Bonus-A

1) Prove EC2 is private (no public IP)

```
aws ec2 describe-instances \
--instance-ids <INSTANCE_ID> \
--query "Reservations[].Instances[].PublicIpAddress"
```

```
#####
#####
```

```
LAB1/c/lab-1c-chewbacca on  main [!?] via  default on  (us-east-1) on  took 2s
> aws ec2 describe-instances \
  --filters "Name=tag:Name,Values=lew-ec201" \
  --query "Reservations[].Instances[].PublicIpAddress"
[]
```

Code Text:

```
> aws ec2 describe-instances \
  --filters "Name=tag:Name,Values=lew-ec201" \
  --query "Reservations[].Instances[].PublicIpAddress"
[]
```

```
#####
#####
```

Expected:

null

2) Prove VPC endpoints exist

```
aws ec2 describe-vpc-endpoints \
--filters "Name=vpc-id,Values=<VPC_ID>" \
--query "VpcEndpoints[].ServiceName"
```

Expected: list includes:

```
ssm
ec2messages
ssmmessages
logs
secretsmanager
s3
```

```
#####
#####
```

```
LAB1/c/lab-1c-chewbacca on ʘ main [!?] via ʘ default on ʘ (us-east-1) on ʘ
> aws ec2 describe-vpc-endpoints \
  --region ap-northeast-1 \
  --query "VpcEndpoints[].ServiceName"
[
  "com.amazonaws.ap-northeast-1.s3",
  "com.amazonaws.ap-northeast-1.logs",
  "com.amazonaws.ap-northeast-1.secretsmanager",
  "com.amazonaws.ap-northeast-1.ssmmessages",
  "com.amazonaws.ap-northeast-1.ec2messages",
  "com.amazonaws.ap-northeast-1.kms",
  "com.amazonaws.ap-northeast-1.ssm",
  "com.amazonaws.ap-northeast-1.s3",
  "com.amazonaws.ap-northeast-1.ec2messages",
  "com.amazonaws.ap-northeast-1.secretsmanager",
  "com.amazonaws.ap-northeast-1.ssm",
  "com.amazonaws.ap-northeast-1.ssmmessages",
  "com.amazonaws.ap-northeast-1.logs"
]
```

Code Text:

```
> aws ec2 describe-vpc-endpoints \
--region ap-northeast-1 \
--query "VpcEndpoints[].ServiceName"
[
  "com.amazonaws.ap-northeast-1.s3",
  "com.amazonaws.ap-northeast-1.logs",
  "com.amazonaws.ap-northeast-1.secretsmanager",
  "com.amazonaws.ap-northeast-1.ssmmessages",
  "com.amazonaws.ap-northeast-1.ec2messages",
  "com.amazonaws.ap-northeast-1.kms",
  "com.amazonaws.ap-northeast-1.ssm",
  "com.amazonaws.ap-northeast-1.s3",
```

```
"com.amazonaws.ap-northeast-1.ec2messages",  
"com.amazonaws.ap-northeast-1.secretsmanager",  
"com.amazonaws.ap-northeast-1.ssm",  
"com.amazonaws.ap-northeast-1.ssmmessages",  
"com.amazonaws.ap-northeast-1.logs"  
]
```

```
#####  
#####
```

3) Prove Session Manager path works (no SSH)

```
aws ssm describe-instance-information \
--query "InstanceInformationList[].InstanceId"
```

```
#####
#####
```

```
LAB1/c/lab-1c-chewbacca on  main [!?] via  default on  (us-east-1) on  took 28m51s
> aws ssm describe-instance-information \
  --region ap-northeast-1 \
  --query "InstanceInformationList[*].[InstanceId, PingStatus, LastPingDateTime]" \
  --output table
```

DescribeInstanceInformation		
i-04a23ea21a8fdf432	Online	2026-02-05T01:12:59.202000-08:00

Code Text:

```
> aws ssm describe-instance-information \
  --region ap-northeast-1 \
  --query "InstanceInformationList[*].[InstanceId, PingStatus, LastPingDateTime]" \
  --output table
```

```
-----
|           DescribeInstanceInformation           |
+-----+-----+-----+
| i-04a23ea21a8fdf432 | Online | 2026-02-05T01:12:59.202000-08:00 |
+-----+-----+-----+
```

```
#####
#####
```

Expected: your private EC2 instance ID appears

4) Prove the instance can read both config stores

Run from SSM session:

aws ssm get-parameter --name /lab/db/endpoint

```
#####  
#####  
LAB1/c/lab-1c-chewbacca on ʘ main [!?] via ❖ default on ☁ (us-east-1) on ☁ took 2s  
○ > aws ssm start-session --target i-04a23ea21a8fdf432 --region ap-northeast-1  
  
Starting session with SessionId: AWSCLI-ldc7divvt5tqopshq2afoc5rl8  
sh-5.2$ aws ssm get-parameter --name /lab/db/endpoint  
{  
  "Parameter": {  
    "Name": "/lab/db/endpoint",  
    "Type": "String",  
    "Value": "lew-rds01.cpiqy8aw8ntg.ap-northeast-1.rds.amazonaws.com",  
    "Version": 1,  
    "LastModifiedDate": "2026-02-03T04:44:25.358000+00:00",  
    "ARN": "arn:aws:ssm:ap-northeast-1:127214194163:parameter/lab/db/endpoint",  
    "DataType": "text"  
  }  
}  
sh-5.2$
```

Code Text:

LAB1/c/lab-1c-chewbacca on main [!?] via ❖ default on ☁ (us-east-1) on ☁ took 2s
➤ aws ssm start-session --target i-04a23ea21a8fdf432 --region ap-northeast-1

Starting session with SessionId: AWSCLI-ldc7divvt5tqopshq2afoc5rl8

sh-5.2\$ aws ssm get-parameter --name /lab/db/endpoint

```
{  
  "Parameter": {  
    "Name": "/lab/db/endpoint",  
    "Type": "String",  
    "Value": "lew-rds01.cpiqy8aw8ntg.ap-northeast-1.rds.amazonaws.com",  
    "Version": 1,  
    "LastModifiedDate": "2026-02-03T04:44:25.358000+00:00",  
    "ARN": "arn:aws:ssm:ap-northeast-1:127214194163:parameter/lab/db/endpoint",  
    "DataType": "text"  
  }  
}  
}  
#####  
#####
```

aws secretsmanager get-secret-value --secret-id <your-secret-name>

```
sh-5.2$ aws secretsmanager get-secret-value --secret-id "lew/lab-1a/rds/mysql"
{
  "ARN": "arn:aws:secretsmanager:ap-northeast-1:127214194163:secret:lew/lab-1a/rds/mysql-kYWcr5",
  "Name": "lew/lab-1a/rds/mysql",
  "VersionId": "terraform-202602050200280959000000008",
  "SecretString": "{\"dbname\":\"labdb\",\"host\":\"lew-rds01.cpiqy8aw8ntg.ap-northeast-1.rds.amazonaws.com\",\"password\":\"Bigpimpin6\",\"port\":\"3306\",\"username\":\"admin\"}",
  "VersionStages": [
    "AWSCURRENT"
  ],
  "CreateDate": "2026-02-05T02:00:28.470000+00:00"
}
sh-5.2$
```

Code Text:

```
sh-5.2$ aws secretsmanager get-secret-value --secret-id "lew/lab-1a/rds/mysql"
{
  "ARN":
  "arn:aws:secretsmanager:ap-northeast-1:127214194163:secret:lew/lab-1a/rds/mysql-kYWcr5",
  "Name": "lew/lab-1a/rds/mysql",
  "VersionId": "terraform-202602050200280959000000008",
  "SecretString":
  "{\"dbname\":\"labdb\",\"host\":\"lew-rds01.cpiqy8aw8ntg.ap-northeast-1.rds.amazonaws.com\",\"
  password\":\"Bigpimpin6\",\"port\":\"3306\",\"username\":\"admin\"}",
  "VersionStages": [
    "AWSCURRENT"
  ],
  "CreateDate": "2026-02-05T02:00:28.470000+00:00"
}
```

```
#####
#####
```

5) Prove CloudWatch logs delivery path is available via endpoint

```
aws logs describe-log-streams \
--log-group-name /aws/ec2/<prefix>-rds-app
```

```
#####
#####
```

```
LAB1/c/lab-1c-chewbacca on  main [!?] via  default on  (us-east-1) on  took 3s
● > aws logs describe-log-streams \
  --log-group-name "/aws/ec2/lew-rds-app" \
  --region ap-northeast-1
{
  "logStreams": [
    {
      "logStreamName": "i-04a23ea21a8fdf432",
      "creationTime": 1770256887994,
      "firstEventTimestamp": 1770256882950,
      "lastEventTimestamp": 1770259328705,
      "lastIngestionTime": 1770259333717,
      "uploadSequenceToken": "49039859660786709643655584078982208293231049190413832903",
      "arn": "arn:aws:logs:ap-northeast-1:127214194163:log-group:/aws/ec2/lew-rds-app:log-stream:i-04a23ea21a8fdf432",
      "storedBytes": 0
    }
  ]
}
```

Code Text:

```
> aws logs describe-log-streams \
  --log-group-name "/aws/ec2/lew-rds-app" \
  --region ap-northeast-1
```

```
{
  "logStreams": [
    {
      "logStreamName": "i-04a23ea21a8fdf432",
      "creationTime": 1770256887994,
      "firstEventTimestamp": 1770256882950,
      "lastEventTimestamp": 1770259328705,
      "lastIngestionTime": 1770259333717,
      "uploadSequenceToken":
"49039859660786709643655584078982208293231049190413832903",
      "arn":
"arn:aws:logs:ap-northeast-1:127214194163:log-group:/aws/ec2/lew-rds-app:log-stream:i-04a23
ea21a8fdf432",
      "storedBytes": 0
    }
  ]
}
```

```
#####
#####
```

How this maps to “real company” practice (short, employer-credible)

Private compute + SSM is standard in regulated orgs and mature cloud shops.

VPC endpoints reduce exposure and dependency on NAT for AWS APIs.