ROTO-CONTROL SYSEX API

Version 1.2

Disclaimer

The software API is provided "as is" without any warranties or guarantees of any kind, either express or implied, including but not limited to the implied warranties of merchantability, fitness for a particular purpose, or non-infringement. All parts of this API are subject to change, additions or deletions without notice. The use of the API is at your own risk. The authors or contributors of this API do not offer any technical support, updates, or maintenance, and make no representations regarding the performance, reliability, or suitability of the API for any particular purpose. In no event shall the authors or contributors be liable for any damages arising from the use or inability to use this API, including but not limited to direct, indirect, incidental, special, or consequential damages, even if advised of the possibility of such damages.

Revision History

Version	Date	Change
1.0	23/02/2025	First release.
1.1	07/04/2025	**This version is NOT backwards compatible with v1.0** Updates to support MACRO params: • LEARN PARAM • PARAM LEARNED • SET MAPPED CONTROL NAME (new)
1.2	23/06/2025	**This version is NOT backwards compatible with v1.1** General updates and updates to support Bitwig Studio: • DAW PING RESPONSE • ROTO-DAW CONNECTED (new) • REQUEST ROTO FW VERSION (new) • ROTO FW VERSION (new) • TRACK DETAILS • PLUGIN DETAILS • DAW SELECT PLUGIN • LEARN PARAM • CONTROL MAPPED (renamed, was PARAM LEARNED) • MACRO PLUGIN PAGE INDEX (new) • CONTROL LEARNED (new) • TOGGLE REMOTE PAGE (new) • TOGGLE TRACK GROUPING (new) • DAW SELECT TRACK • REQUEST SEND TRACK NAMES (new) • SEND TRACK NAMES (new) Document formatting improvements.

Compatibility

Version	Compatibility
1.0	• ROTO-SETUP v1.0.0 • ROTO-SETUP v1.1.1 • ROTO-SETUP v1.1.2
1.1	• ROTO-SETUP v1.1.3 • ROTO-SETUP v1.1.4
1.2	• ROTO-SETUP v2.0.0

1. Introduction

The ROTO-CONTROL SYSEX API allows communication and configuration with an external DAW such as Ableton. The interface used is MIDI via USB.

The interface is bi-directional in that commands can be sent to ROTO-CONTROL and received from ROTO-CONTROL asynchronously.

Note 1: For conciseness ROTO-CONTROL is also referred to as ROTO throughout this document.

Note 2: All values are specified in hexadecimal.

1.2 Command Format

All ROTO-CONTROL SYSEX commands take the following format:

F0 00 22 03 02 <data> F7

Where:

- F0 = Start SYSEX message byte.
- 00 22 03 = Melbourne Instruments SYSEX ID.
- 02 = ROTO-CONTROL v1 device ID.
- <data> = The command payload.
- F7 = End SYSEX message byte.

1.3 Commands Overview

Type	Sub-type	Description	To ROTO	From ROTO
0A: GENERAL	01: DAW STARTED	The DAW has started a session with ROTO	Y	N
	02: PING DAW	Ping to check if the DAW is running	N	Y
	03: DAW PING RESPONSE	Ping response from the DAW	Y	N
	04: NUM TRACKS	Number of tracks	Y	N
	05: FIRST TRACK	First track page index	Y	N
	06: SET FIRST TRACK	Set the first track page index	N	Y
	07: TRACK DETAILS	Track details in the current track page	Y	N
	08: TRACK DETAILS END	Finished sending track details	Y	N
	09: ROTO SELECT TRACK	ROTO-Control has selected a track	N	Y
	0A: REQUEST TRANSPORT STATUS	Request the current transport status	N	Y

	0B: TRANSPORT STATUS	The current transport status	Y	N
	0C: ROTO-DAW CONNECTED	The ROTO has received the DAW PING RESPONSE, and the ROTO and DAW are now connected.	N	Y
	0D: REQUEST ROTO FW VERSION	The DAW has requested the ROTO firmware version	Y	N
	0E: ROTO FW VERSION	The ROTO firmware version	N	Y
0B: PLUGIN	**01: SET PLUGIN MODE**	Set the DAW in PLUGIN mode	N	Y
	02: NUM PLUGINS	Returns the number of PLUGINs on the current track	Y	N
	03: FIRST PLUGIN	First PLUGIN page index	Y	Y
	04: SET FIRST PLUGIN	Set the first PLUGIN page index	N	Y
	05: PLUGIN DETAILS	Details of a PLUGIN	Y	N
	06: PLUGIN DETAILS END	Finished sending PLUGIN details	Y	N
	07: ROTO SELECT PLUGIN	The ROTO-CONTROL has selected a PLUGIN	Y	N
	08: DAW SELECT PLUGIN	The DAW has selected a PLUGIN	Y	N
	09: SET PLUGIN LEARN	Put the DAW in learn mode	Y	N
	0A: LEARN PARAM	A param has been learned	Y	N
	0B: CONTROL MAPPED	Mapped control details	N	Y
	0C: SET PLUGIN ENABLE	Enable/disable a PLUGIN	N	Y
	0D: SET PLUGIN LOCK	Lock/unlock PLUGINs	N	Y
	0E: UNMAP CONTROL	Un-map a learned control	Y	N
	0F: SET MAPPED CONTROL NAME	Set the name of a mapped control	Y	N

	10: MACRO PLUGIN PAGE INDEX	Current MACRO PLUGIN page index	N	Y
	11: CONTROL LEARNED	A param has been learned and assigned to a control	N	Y
	12: TOGGLE REMOTE PAGE	Request the DAW to toggle the remote page in a PLUGIN	N	Y
0C: MIX	**01: SET MIX ALL TRACKS MODE**	Set MIX into "all tracks" mode	N	Y
	02: SET MIX TRACK MODE	Set MIX into "single track" mode	N	Y
	03: NUM SEND TRACKS	The number of available send tracks	Y	N
	04: DAW SELECT TRACK	The DAW has selected a track	Y	N
	05: SET ALL TRACKS MODE	Set the "all tracks" mode	N	Y
	06: TOGGLE TRACK GROUPING	Toggle track grouping on the currently selected track	N	Y
	07: REQUEST SEND TRACK NAMES	Request a set of 8 send track names	N	Y
	08: SEND TRACK NAMES	A set of 8 send track names	Y	N

2. GENERAL Commands: 0A

2.1 DAW STARTED: 01

Command
`F0 00 22 03 02 ` **`0A 01`** ` F7`

Description
This is sent by the DAW when it first starts (or a new session is started). The DAW should not send any further commands until it receives PING DAW from ROTO.

Direction		DAW Compatibility	
TO ROTO	Y	Ableton Live	Y
FROM ROTO	N	Bitwig Studio	Y

2.2 PING DAW: 02

Command
`F0 00 22 03 02 ` **`0A 02`** ` F7`

Description
This is sent by ROTO to check if a DAW is connected – it will be sent by ROTO after receiving DAW STARTED or when ROTO is plugged into a PC. The DAW should respond with DAW PING RESPONSE when this is received. The DAW should not send any further commands until it receives ROTO-DAW CONNECTED from ROTO.

Note: ROTO will send this command every second for 1 minute to poll for a connected DAW. |

Direction		DAW Compatibility	
TO ROTO	N	Ableton Live	Y
FROM ROTO	Y	Bitwig Studio	Y

2.3 DAW PING RESPONSE: 03

Command
`F0 00 22 03 02 ` **`0A 03`** ` <DT>  F7` `DT = DAW Type: Ableton Live (01), Bitwig Studio (02)`

Description
This command should be sent by the DAW when it receives the PING DAW command from ROTO.

Direction		DAW Compatibility	
TO ROTO	Y	Ableton Live	Y
FROM ROTO	N	Bitwig Studio	Y

2.4 NUM TRACKS: 04

Command
`F0 00 22 03 02 ` **`0A 04`** ` <NT> F7`

```
NT = Number of tracks
```

Description

This command is sent from the DAW to indicate the number of tracks – either the number of audio or master-return tracks depending on the mixer mode.

Direction		DAW Compatibility	
TO ROTO	Y	Ableton Live	Y
FROM ROTO	N	Bitwig Studio	Y

2.5 FIRST TRACK: 05

Command
```
F0 00 22 03 02 0A 05 <FT> F7
FT = First track index in multiples of 8 (00 = Track page 1, 08 = Track page 2, etc.)
```

Description

This command is sent from the DAW to indicate the current tracks page.

Direction		DAW Compatibility	
TO ROTO	Y	Ableton Live	Y
FROM ROTO	N	Bitwig Studio	Y

2.6 SET FIRST TRACK: 06

Command
```
F0 00 22 03 02 0A 06 <FT> F7
FT = First track index in multiples of 8 (00 = Track page 1, 08 = Track page 2, etc.)
```

Description

This command is sent from ROTO to indicate when the page of tracks has been changed.

Direction		DAW Compatibility	
TO ROTO	N	Ableton Live	Y
FROM ROTO	Y	Bitwig Studio	Y

2.7 TRACK DETAILS: 07

Command
```
F0 00 22 03 02 0A 07 <TI TN:0D CS GT> F7
TI = Track index
TN = Track name: 0D-byte NULL terminated ASCII string, padded with 00s if needed
CS = Colour scheme: 00 – 52
GT = Grouped track: NO (00), YES (01)
```

Description

This command is sent from the DAW for each track on the current tracks page.

Direction		DAW Compatibility	
TO ROTO	Y	Ableton Live	Y
FROM ROTO	N	Bitwig Studio	Y

2.8 TRACK DETAILS END: 08

Command
F0 00 22 03 02 **0A 08** F7

Description
This command is sent from the DAW once all TRACK DETAILS commands have been sent.

Direction		DAW Compatibility	
TO ROTO	Y	Ableton Live	Y
FROM ROTO	N	Bitwig Studio	Y

2.9 ROTO SELECT TRACK: 09

Command
F0 00 22 03 02 **0A 09** \<TI\> F7
TI = Index of the track to select

Description
This command is sent when a track is selected via ROTO.

Direction		DAW Compatibility	
TO ROTO	N	Ableton Live	Y
FROM ROTO	Y	Bitwig Studio	Y

2.10 REQUEST TRANSPORT STATUS: 0A

Command
F0 00 22 03 02 **0A 0A** F7

Description
This command is sent from ROTO to request the current transport controls status.

Direction		DAW Compatibility	
TO ROTO	N	Ableton Live	Y
FROM ROTO	Y	Bitwig Studio	Y

2.11 TRANSPORT STATUS: 0B

Command
F0 00 22 03 02 **0A 0B** \<PS SS RS SR LS PI PO AS\> F7
PS = Play status: Off (00), On (01)

```
SS = Stop status: Off (00), always this value
RS = Record status: Off (00), On (01)
SR = Session Record status: Off (00), On (01)
LS = Loop status: Off (00), On (01)
PI = Punch-in status: Off (00), On (01)
PO = Punch-out status: Off (00), On (01)
AS = Re-enable automation status: Off (00), On (01)
```

Description
This command is sent from the DAW in response to the REQUEST TRANSPORT STATUS command.

Direction		DAW Compatibility	
TO ROTO	Y	Ableton Live	Y
FROM ROTO	N	Bitwig Studio	Y

2.12 ROTO-DAW CONNECTED: 0C

Command
F0 00 22 03 02 **0A 0C** F7

Description
This is sent by ROTO once it has received and finished processing DAW PING RESPONSE from a DAW. Once the DAW has received this command it can send other commands to ROTO as needed.

Direction		DAW Compatibility	
TO ROTO	N	Ableton Live	Y
FROM ROTO	Y	Bitwig Studio	Y

2.13 REQUEST ROTO FW VERSION: 0D

Command
F0 00 22 03 02 **0A 0D** F7

Description
This command is sent from the DAW to request the ROTO firmware version.

Direction		DAW Compatibility	
TO ROTO	Y	Ableton Live	Y
FROM ROTO	N	Bitwig Studio	Y

2.14 ROTO FW VERSION: 0E

Command
F0 00 22 03 02 **0A 0E** <VX VY VZ GC:7> F7
VX = ROTO-CONTROL major version
VY = ROTO-CONTROL minor version
VZ = ROTO-CONTROL patch version
GC = Short GIT commit in ASCII bytes

Description
This command is sent from ROTO after receiving the REQUEST ROTO FW VERSION command.

Direction		DAW Compatibility	
TO ROTO	N	Ableton Live	Y
FROM ROTO	Y	Bitwig Studio	Y

3. PLUGIN Commands: 0B

3.1 SET PLUGIN MODE: 01

Command
F0 00 22 03 02 **0B 01** F7

Description
This command is sent from ROTO when PLUGIN mode is selected.

Direction		DAW Compatibility	
TO ROTO	N	Ableton Live	Y
FROM ROTO	Y	Bitwig Studio	Y

3.2 NUM PLUGINS: 02

Command
F0 00 22 03 02 **0B 02** <NP> F7
NP = Number of PLUGINS on the current track

Description
This command is sent from the DAW to indicate how many PLUGINs are on the currently selected track.

Direction		DAW Compatibility	
TO ROTO	Y	Ableton Live	Y
FROM ROTO	N	Bitwig Studio	Y

3.3 FIRST PLUGIN: 03

Command
F0 00 22 03 02 **0B 03** <FP> F7
FP = First PLUGIN index in multiples of 8 (00 = PLUGIN page 1, 08 = PLUGIN page 2, etc.)

Description
This command is sent from the DAW to indicate the current PLUGIN page.

Direction		DAW Compatibility	
TO ROTO	Y	Ableton Live	Y
FROM ROTO	N	Bitwig Studio	Y

3.4 SET FIRST PLUGIN: 04

Command
F0 00 22 03 02 **0B 04** <FP> F7
FP = First PLUGIN index in multiples of 8 (00 = PLUGIN page 1, 08 = PLUGIN page 2, etc.)

Description
This command is sent from ROTO to indicate when the page of PLUGINs has been changed.

Direction		DAW Compatibility	
TO ROTO	**N**	Ableton Live	**Y**
FROM ROTO	**Y**	Bitwig Studio	**Y**

3.5 PLUGIN DETAILS: 05

Command
F0 00 22 03 02 **0B 05** <PI PH:8 PE PN:0D PT NP> F7
PI = PLUGIN index
PH = PLUGIN hash
PE = PLUGIN enabled status: Disabled (00), Enabled (01)
PN = PLUGIN name: 0D-byte NULL terminated ASCII string, padded with 00s if needed
PT = PLUGIN type: Normal (00), MACRO PLUGIN (01), Third-party PLUGIN (02)
NP = Number of MACRO PLUGIN control pages, set to 00 if not a MACRO PLUGIN. Ignored if the connected DAW is Ableton Live

Description
This command is sent from the DAW for each PLUGIN on the current PLUGIN page.

Direction		DAW Compatibility	
TO ROTO	**Y**	Ableton Live	**Y**
FROM ROTO	**N**	Bitwig Studio	**Y**

3.6 PLUGIN DETAILS END: 06

Command
F0 00 22 03 02 **0B 06** F7

Description
This command is sent from the DAW once all PLUGIN DETAILS commands have been sent.

Direction		DAW Compatibility	
TO ROTO	**Y**	Ableton Live	**Y**
FROM ROTO	**N**	Bitwig Studio	**Y**

3.7 ROTO SELECT PLUGIN: 07

Command
F0 00 22 03 02 **0B 07** <PI> F7
PI = Index of the PLUGIN to select

Description
This command is sent from ROTO when a PLUGIN is selected.

Direction		DAW Compatibility	
TO ROTO	**N**	Ableton Live	**Y**
FROM ROTO	**Y**	Bitwig Studio	**Y**

3.8 DAW SELECT PLUGIN: 08

Command

```
F0 00 22 03 02 0B 08 <PI MP FS> F7

PI = Index of the PLUGIN to select

MP = MACRO PLUGIN page index (zero-based), set to 00 if not a MACRO PLUGIN. Ignored if the

connected DAW is Ableton Live

FS = Force selection of the PLUGIN, overriding PLUGIN lock if needed: No force (00), Force

(01)
```

Description

This command is sent from the DAW when a PLUGIN is selected.

Direction		DAW Compatibility	
TO ROTO	**Y**	Ableton Live	**Y**
FROM ROTO	**N**	Bitwig Studio	**Y**

3.9 SET DEVICE LEARN: 09

Command

```
F0 00 22 03 02 0B 09 <DL> F7

DL = Device learn status: Off (00), On (01)
```

Description

This command is sent from ROTO when entering or exiting learn mode.

Direction		DAW Compatibility	
TO ROTO	**N**	Ableton Live	**Y**
FROM ROTO	**Y**	Bitwig Studio	**Y**

3.10 LEARN PARAM: 0A

Command

```
F0 00 22 03 02 0B 0A <PI:2 PH:6 MP CI NS PP:2 PN:0D SN:NS*0D> F7

PI = Param index

PH = Param hash

MP = MACRO param: NO (00), YES (01)

CI = Add a centre (top) indent: NO (00), YES (01). If this is set to YES, the number of

steps (NS) setting is ignored. Only applies to knob controls.

NS = Number of steps: 00 or 02 – 18

PP = Param position: 0 – 16383, formatted as two 7-bit values

PN = Param name: 0D-byte NULL terminated ASCII string, padded with 00s if needed

SN = If NS is <= 10: An array of NS x 0D-byte NULL terminated ASCII strings, each string

    padded with 00s if needed

    If NS > 10: No data
```

Description

This command is sent from the DAW when in learn mode and a PLUGIN param has been selected in the DAW to be learned. It is also sent from the DAW in response to each CONTROL MAPPED command received via ROTO.

Direction		DAW Compatibility	
TO ROTO	Y	Ableton Live	Y
FROM ROTO	N	Bitwig Studio	Y

3.11 CONTROL MAPPED: 0B

Command
F0 00 22 03 02 **0B 0B** <PI:2 PH:6 CT CI MP> F7
PI = Param index
PH = Param hash
CT = Control type: Knob (00), Switch (01)
CI = Index of the control within the current PLUGIN page
MP = MACRO param: NO (00), YES (01)

Description
This command is sent from ROTO for each control that is mapped on the current PLUGIN page.

Direction		DAW Compatibility	
TO ROTO	N	Ableton Live	Y
FROM ROTO	Y	Bitwig Studio	Y

3.12 SET PLUGIN ENABLED: 0C

Command
F0 00 22 03 02 **0B 0C** <PI ES> F7
PI = PLUGIN index
ES = PLUGIN enabled status: Disabled (00), Enabled (01)

Description
This command is sent from ROTO when the selected PLUGIN is enabled or disabled.

Direction		DAW Compatibility	
TO ROTO	N	Ableton Live	Y
FROM ROTO	Y	Bitwig Studio	Y

3.13 SET PLUGINS LOCK: 0D

Command
F0 00 22 03 02 **0B 0D** <LS> F7
LS = PLUGINS lock status: Unlocked (00), Locked (01)

Description
This command is sent from ROTO when the selected PLUGIN is locked or unlocked.

Direction		DAW Compatibility	
TO ROTO	N	Ableton Live	Y
FROM ROTO	Y	Bitwig Studio	Y

3.14 UNMAP CONTROL: 0E

Command

```
F0 00 22 03 02 0B 0E <CT CI> F7
CT = Control type: Switch (00), Knob (01)
CI = Index of the control within the current PLUGIN page
```

Description

This command can be sent from a DAW to unmap a mapped control on the current controls page.

Direction		DAW Compatibility	
TO ROTO	Y	Ableton Live	Y
FROM ROTO	N	Bitwig Studio	Y

3.15 SET MAPPED CONTROL NAME: 0F

Command

```
F0 00 22 03 02 0B 0F <PI:2 PH:6 PN:0D> F7
PI = Param index
PH = Param hash
PN = Param name: 0D-byte NULL terminated ASCII string, padded with 00s if needed
```

Description

This command can be sent from a DAW to update the displayed name of a macro param.

Direction		DAW Compatibility	
TO ROTO	Y	Ableton Live	Y
FROM ROTO	N	Bitwig Studio	Y

3.16 MACRO PLUGIN PAGE INDEX: 10

Command

```
F0 00 22 03 02 0B 10 <PI> F7
PI = MACRO PLUGIN Page index (zero based). Not sent if the plugin is not a MACRO PLUGIN.
```

Description

This command is sent from ROTO when a MACRO PLUGIN is selected, and the page of controls is changed via the arrow keys

Direction		DAW Compatibility	
TO ROTO	N	Ableton Live	N
FROM ROTO	Y	Bitwig Studio	Y

3.17 CONTROL LEARNED: 11

Command

```
F0 00 22 03 02 0B 11 <CT CI> F7
CT = Control type: Switch (00), Knob (01)
CI = PLUGIN control index (00 - 3F)
```

Description
This command is sent from ROTO when a control (knob or switch) has been successfully learned.

Direction		DAW Compatibility	
TO ROTO	N	Ableton Live	Y
FROM ROTO	Y	Bitwig Studio	Y

3.18 TOGGLE REMOTE PAGE: 12

Command
F0 00 22 03 02 **0B 12** F7

Description
This command is sent from ROTO to request the DAW to toggle the remote page in a PLUGIN.

Direction		DAW Compatibility	
TO ROTO	N	Ableton Live	N
FROM ROTO	Y	Bitwig Studio	Y

4. MIX Commands: 0C

4.1 SET MIX ALL TRACKS MODE: 01

Command
F0 00 22 03 02 **0C 01** <AM KM SM SI> F7 AM = All tracks mode: Audio (00), Master-Return (01) KM = Knob mode: Level (00), Pan (01), Send (02) SM = Switch mode: Mute (00), Solo (01), Arm Recording (02) SI = Send index: The (zero-based) index of the send to control if the Knob mode is Send. Ranges from 0 – Number of available sends

Description
This command is sent from ROTO to set the mixer in MIX all tracks mode.

Direction		DAW Compatibility	
TO ROTO	N	Ableton Live	Y
FROM ROTO	Y	Bitwig Studio	Y

4.2 SET MIX TRACK MODE: 02

Command
F0 00 22 03 02 **0C 02** <CI> F7 CI = Track control page index in multiples of 8 (00 = Track controls page 1, 08 = Track controls page 2, etc.)

Description
This command is sent from ROTO to set the mixer in MIX track mode.

Direction		DAW Compatibility	
TO ROTO	N	Ableton Live	Y
FROM ROTO	Y	Bitwig Studio	Y

4.3 NUM SEND TRACKS: 03

Command
F0 00 22 03 02 **0C 03** <NS> F7 NS = Number of available send tracks

Description
This command is sent from the DAW to indicate how many send tracks are available.

Direction		DAW Compatibility	
TO ROTO	Y	Ableton Live	Y
FROM ROTO	N	Bitwig Studio	Y

4.4 DAW SELECT TRACK: 04

Command
F0 00 22 03 02 **0C 04** <TI TN:0D CS GT> F7

```
TI = Track index
TN = Track name: 0D-byte NULL terminated ASCII string, padded with 00s if needed
CI = Colour scheme: 00 – 52
GT = Grouped track: NO (00), YES (01)
```

Description
This command is sent from the DAW when a mixer track is selected.

Direction		DAW Compatibility	
TO ROTO	Y	Ableton Live	Y
FROM ROTO	N	Bitwig Studio	Y

4.5 SET ALL TRACKS MODE: 05

Command
F0 00 22 03 02 **0C 05** <AM> F7 AM = All tracks mode: Audio (00), Master-Return (01)

Description
This command is sent from ROTO when the MIX all tracks mode is changed to show audio or master-return tracks.

Direction		DAW Compatibility	
TO ROTO	N	Ableton Live	Y
FROM ROTO	Y	Bitwig Studio	Y

4.6 TOGGLE TRACK GROUPING: 06

Command
F0 00 22 03 02 **0C 06** <TI> F7 TI = Track index

Description
This command is sent from ROTO to toggle track grouping on the currently selected track (if grouping is applicable for that track).

Direction		DAW Compatibility	
TO ROTO	N	Ableton Live	Y
FROM ROTO	Y	Bitwig Studio	Y

4.7 REQUEST SEND TRACK NAMES: 07

Command
F0 00 22 03 02 **0C 07** <SI> F7 SI = SEND names index (zero based)

Description
Request a block of 8 send track names from the DAW containing the send track names index.

Direction		DAW Compatibility	
TO ROTO	N	Ableton Live	N
FROM ROTO	Y	Bitwig Studio	Y

4.8 SEND TRACK NAMES: 08

Command

```
F0 00 22 03 02 0C 08 <SI SN:08*0D> > F7
SI = SEND names index (zero based)
SN = An array of 8 x 0D-byte NULL terminated ASCII strings, each string padded with 00s if
needed
```

Description

This command should be sent by the DAW after receiving either the SET MIX ALL TRACKS MODE, SET MIX TRACK MODE, or REQUEST SEND TRACK NAMES commands and at least one send track is present in the DAW:

1. SET MIX ALL TRACKS MODE command is received:
   It must send a block of 8 send track names with the start index being a multiple of 8 and containing the send index received in the command. Examples:
   - Send index is 00, the send track names sent should be from index 00.
   - Send index is 07, the send track names sent should be from index 00.
   - Send index is 08, the send track names sent should be from index 08.
   - Send index is 14, the send track names sent should be from index 10.
   Note: If the track with the send index is renamed, the block of 8 track names must be re-sent to ROTO.

2. SET MIX TRACK MODE command is received:
   It must send a block of 8 SEND names with the start index being calculated based on the track control page index received in the command. Examples:
   - Track control page index is 00, the send track names sent should be from index 00.
   - Track control page index is 08, the send track names sent should be from index 06.
   - Track control page index is 10, the send track names sent should be from index 0E.

3. REQUEST SEND TRACK NAMES command is received:
   It must send a block of 8 send track names with the start index being a multiple of 8 and containing the send index received in the command.

Note: If there is no send track name then set all 00s for that string.

Direction		DAW Compatibility	
TO ROTO	Y	Ableton Live	N
FROM ROTO	N	Bitwig Studio	Y