NetLab Findings Report

Simulation Engineering Summary

Generated 31/10/2026, 22.25.00

Executive Summary

- Devices in topology: 7
- Links in topology: 6 total (6 up, 0 down)
- DHCP lease coverage: 0%
- Node adjacency reachability: 100%
- Active lab findings: 2
- Architecture score: 96/100
- Simulation engine: running

Architecture Score

Overall score: 96/100

resilience: 100/100
security: 100/100
performance: 100/100
operability: 76/100
wirelessHealth: 100/100
Primary drag is operability at 76/100.

Topology Snapshot

2911 (router) Power: on Active ports: 2
PT-Switch (switch) Power: on Active ports: 3
PT-Switch2 (switch) Power: on Active ports: 3
PC (enddevice) Power: on Active ports: 1
PC2 (enddevice) Power: on Active ports: 1
PC3 (enddevice) Power: on Active ports: 1
PC4 (enddevice) Power: on Active ports: 1

Operational Highlights

PC

Event: Ping reply received
Event: Ping reply received

Key Findings

PC has no default gateway [HIGH]

The end device has IPv4 addressing but no default gateway while remote subnets exist in the lab.

Evidence: FastEthernet0 gateway field is empty

Fix preview: ip default-gateway <router-interface-ip>

Recommendation: Configure the router interface IP as the default gateway on this PC/server.

PC2 has no default gateway [HIGH]

The end device has IPv4 addressing but no default gateway while remote subnets exist in the lab.

Evidence: FastEthernet0 gateway field is empty

Fix preview: ip default-gateway <router-interface-ip>

Recommendation: Configure the router interface IP as the default gateway on this PC/server.