

Project #3 : **Polymorphism in Action**
CpSc 4160/6160: Data-Driven 2D Video Game Development
Computer Science Division, Clemson University
Brian Malloy, PhD
October 8, 2018

Due Date:

To receive credit for this assignment, your solution must meet the requirements specified in this document and be submitted, using the `handin` facility, by 8 AM, Friday, October 12th, 2018. The handin close date is set at three days after the due date. If you submit after the due date but before the handin close date there will be a ten point deduction. No submissions will be accepted after the handin close date and no submissions will be accepted by email.

Project Submission:

To submit your solution through handin, copy the README file from the project directory in the repo to your project directory, fill in the blanks in the README, make clean in your project directory, and compress the project directory using `tar` or `zip`.

Project Specification:

The purpose of this assignment is to: help you to become familiar with: (1) C++ language constructs including inheritance and polymorphism; (2) design patterns including factory and singleton; (3) data-driven programming, and (4) a tracker framework, included in the directory for project #3. An execution of the tracker framework is illustrated in Figure 1 where it is “tracking” a yellow star. Once you begin this project you should consider the tracker framework to be yours, since you will be modifying and extending it for the rest of the course.



Figure 1: Tracker

To complete this project, get and use the tracker framework to complete the following tasks:

1. Convert the while loops, in the following functions, into ranged for loops:
 - `ParseXML::display()`,
 - `Gamedata::displayData()`
2. Convert the first 3 ranged for loops in the `ImageFactory` destructor to while loops without using `auto`.
3. Convert `ImageFactory` and `RenderContext` from GoF singletons to Meyers singletons.
4. Use `loMod` and C++ stringstream to write the fps of your game to the screen, and write your name in the lower left corner of the screen and it must be readable.
5. Add generality to `loMod` by permitting the user to write text in a different color font. One way to do this is by overloading `loMod::writeText` to accept an additional parameter, the new font color, and use this font to write the text.
6. Incorporate parallax scrolling into the animation by using at least two backgrounds. The `readTexture` and `readSurface` routines in `loMod` work with either an *alpha channel* or a transparency bit (see transparency in `game.xml`). If your sprite sheet doesn't have an alpha channel, you can add it using gimp: (1) Make sure the *image* → *mode* is **RGB**; (2) choose *layer* → *transparency* → *color to alpha*.

7. Use **delete** to “explicitly disallow compiler generated functions” in Engine, and ImageFactory.
8. With some small changes, your Engine class in the *tracker framework* will contain a polymorphic vector of Drawable* which you must populate with at least two different kinds of sprites and one of them must be implemented by you. You can use Sprite and/or MultiSprite for one of the types but you must implement a new type. For example, a *two-way multi-frame sprite* might be a good choice. You must have a total of at least 7 sprites.

A two-way multi-frame sprite is a sprite that can travel in two directions with a different set of frames for each direction; the pterodactyl in Figure 2 is an example. You must have at least two different types of sprites in your polymorphic vector and one of them must be a two-way multi-frame sprite.

9. Your game or animation must be coherent, with a consistent theme. Creating a coherent animation entails replacing the images currently used in the *tracker framework* with your images. **You may not use my images in your animation.** You may use images from the internet but you must cite the source in your README. Creating your own images may be time consuming but always makes for a more authentic animation and will earn more points; if you don’t claim ownership of the sprites I will assume you downloaded them.

To instantiate a sprite multiple times, you will have to modify game.xml, and the constructors in the respective classes. **if you don’t modify the relevant constructors your sprites will appear on top of each other.** You may also have to modify your ImageFactory class, since your ImageFactory should create and destroy all the images in your animation.



(a) Pter flying left.



(b) Pter flying right.

Figure 2: This figure illustrates a two-way multi-frame sprite.

10. Your submission must be *data driven*, with no warnings (USE **g++**), and no user memory leaks.
11. A video of your animation in mp4 format, not more than 20 seconds in length, where the filename uses your username as the prefix. Submit your mp4, with your username as prefix, with your project. You can make the video by:
 - (a) using your FrameGenerator class to generate frames, and then use avconv to make an mp4; Read the HOWTO file in the frames directory.
 - (b) using a video capture tool, for example, simplescreenrecorder.