

Author Routes File

```
/**
 * These are the routes for the author feature
 */

//Start of Code written without Assistance for this code extract

const express = require('express');
const router = express.Router();
const date_time = new Date();
const { check, validationResult } = require('express-validator');

function formatDateForSQLite(date) {
  //Purpose: This function takes a JavaScript Date object and formats
  it into a string that can be easily inserted into an SQLite database.
  //Inputs: A JavaScript Date object representing the date and time
  to be formatted.
  //Outputs: A string in the format "YYYY-MM-DD HH:MM:SS" that can be
  used to insert the date and time into an SQLite database.
  if (!(date instanceof Date)) {
    throw new Error("Invalid Date object");
  }
  const year = date.getUTCFullYear();
  const month = String(date.getUTCMonth() + 1).padStart(2, '0');
  const day = String(date.getUTCDate()).padStart(2, '0');
  const hours = String(date.getUTCHours()).padStart(2, '0');
  const minutes = String(date.getUTCMinutes()).padStart(2, '0');
  const seconds = String(date.getUTCSeconds()).padStart(2, '0');
  const formattedDate = `${year}-${month}-${day}
  ${hours}:${minutes}:${seconds}`;
  return formattedDate;
}

const requiredPerms = (req, res, next) =>
  // Purpose: This middleware function checks if the user making the
  request has admin permissions.
  // Inputs: req (the Express request object), res (the Express
  response object), next (the next middleware function in the stack).
  // Outputs: If the user is an admin, calls the next middleware
  function. If the user is not an admin, renders the "AccessDenied"
  view and sends the response.
  // Check if the user's ID in the session is equal to 1 (assuming 1
  represents an admin user)
  {
    // Check if the user's ID in the session is not equal to 1
    if (req.session.userId !== 1)
    {
      // If the user does not have the required permissions,
      // render the "AccessDenied" view and send the response
      res.render("AccessDenied");
    }
    else
    {
      // If the user has the required permissions,
      // call the next middleware function in the stack
    }
  }
}
```

```

        next();
    }
};
const redirectlogin = (req, res, next) => {
    // Purpose: This middleware function checks if the user making the
    request is logged in.
    // If the user is not logged in, it redirects them to the login
    page.
    // If the user is logged in, it calls the next middleware function
    in the stack.
    // Inputs: req (the Express request object), res (the Express
    response object), next (the next middleware function in the stack).
    // Outputs: If the user is not logged in, it redirects them to the
    login page. If the user is logged in, it calls the next middleware
    function.
    if (!req.session.username) {
        res.redirect('/login');
    } else {
        next();
    }
}

router.get('/create-post', requiredPerms, (req, res) =>
    // Purpose: This route handler function is responsible for
    rendering the 'create-post' page, which allows authenticated users
    with the required permissions to create a new blog post.
    // Inputs: req (the Express request object), res (the Express
    response object), requiredPerms (a middleware function that checks if
    the user has the necessary permissions to access this route).
    // Outputs: The function renders the 'create-post' view.
    {
        // Render the 'create-post' view
        res.render('create-post');
    });

router.post('/create-post-process', (req, res, next) => {
    const { title, subtitle, content } = req.body;
    const userId = req.session.userId; // Assuming you have stored the
    userId in the session

    const createdAt = new Date();

    const formattedcreated = formatDateForSQLite(createdAt);

    // Insert the new post into the Posts table with the current date
    and time
    global.db.run(
        `INSERT INTO Posts (title, subtitle, content, userId, createdAt)
VALUES (?, ?, ?, ?, ?)`,
        [title, subtitle, content, userId, formattedcreated],
        function (err) {
            if (err) {
                // Handle the error appropriately
                return next(err);
            }
        }
    );
});

```

```

        // The post was successfully created
        const postId = this.lastID;

        // Redirect to the newly created post's page or any other
        // desired location
        res.redirect('/author/author-home');
    }
    });
});

router.get('/view-post', (req, res) => {
    // Purpose: This route handler function is responsible for
    // rendering the 'view-post' page, which displays the details of a
    // specific blog post.
    // Inputs: req (the Express request object), res (the Express
    // response object).
    // Outputs: The function renders the 'view-post' view, passing any
    // necessary data (e.g., the post details) as part of the response.
    try {
        // Render the 'view-post' view
        res.render('view-post');
    } catch (error) {
        console.error('Error rendering view-post:', error);
        res.status(500).render('error', { message: 'An error occurred
while rendering the view-post page.' });
    }
});

router.get('/author-settings', (req, res) => {
    // Purpose: This route handler function is responsible for
    // rendering the 'author-settings' page, which allows an author to view
    // and update their account settings.
    // Inputs: req (the Express request object), res (the Express
    // response object).
    // Outputs: The function renders the 'author-settings' view,
    // passing the user's current blog settings as part of the response.
    try {
        global.db.get('SELECT * FROM Settings', (err, row) => {
            if (err) {
                console.error('Error fetching settings:', err);
                res.status(500).render('error', { message: 'An error occurred
while retrieving the settings.' });
            } else {
                console.log('Success passing to the page.');
```

```

    check('subtitle').not().isEmpty().withMessage('Subtitle cannot be
empty'),
    check('author').not().isEmpty().withMessage('Author cannot be
empty'),
], (req, res) => {
    // Purpose: This route handler function is responsible for updating
the blog settings, such as the title, subtitle, and author name.
    // Inputs: req (the Express request object), res (the Express
response object).
    // Outputs: The function either renders the 'author-settings' view
with validation errors, or redirects the user to the '/author/author-
settings' route after successfully updating the settings
    try {
        const errors = validationResult(req);
        if (!errors.isEmpty()) {
            console.error('Validation errors:', errors.array());
            return res.status(400).render('author-settings', {
                settings: req.body,
                errors: errors.array(),
            });
        }

        const { title, subtitle, author } = req.body;

        const sql = 'UPDATE Settings SET title = ?, subtitle = ?, author
= ?';

        global.db.run(sql, [title, subtitle, author], function (err) {
            if (err) {
                console.error('Error updating settings:', err);
                return res.status(500).render('error', { message: 'An error
occurred while updating the settings.' });
            }
            res.redirect('/author/author-settings');
        });
    } catch (error) {
        console.error('Error in /update-settings route:', error);
        res.status(500).render('error', { message: 'An unexpected error
occurred.' });
    }
});

router.get('/author-home', redirectlogin, requiredPerms, (req, res) =>
{
    // Purpose: This route handler function is responsible for
rendering the author's home page, which displays a list of their blog
posts and associated metadata.
    // Inputs: req (the Express request object), res (the Express
response object).
    // Outputs: The function renders the 'author-home' view, passing in
the necessary data to display the author's blog posts and settings.

    global.db.get('SELECT * FROM Settings', (err, settingsRow) => {
        if (err) {
            console.error(err);
            res.status(500).send('Internal Server Error');
        } else {

```

```

        // Query the posts table and the comments table to get the
        comment count for each post
        global.db.all('SELECT p.*, (SELECT COUNT(*) FROM Comments c
WHERE c.postId = p.id) AS commentCount FROM Posts p', (err,
postsRows) => {
            if (err) {
                console.error(err);
                res.status(500).send('Internal Server Error');
            } else {
                console.log("postsRows:", postsRows);
                // Dynamic title
                const dynamicTitle = 'Author Home Page | CuteBlog
 Blogging';
                res.render('author-home', {
                    settings: settingsRow,
                    posts: postsRows,
                    title: dynamicTitle,
                });
            }
        });
    });
});

router.get('/DashBoard', (req, res) => {
    // Purpose: This route handler function is responsible for
    rendering the dashboard page, which displays a list of all published
    blog posts.
    // Inputs: req (the Express request object), res (the Express
    response object).
    // Outputs: The function fetches all published posts from the
    database and renders the dashboard view, passing the posts and the
    current user's username as data.
    db.all('SELECT * FROM Posts WHERE status = "published"', (err,
posts) => {
        if (err) {
            console.error('Error fetching published posts:', err);
            return res.status(500).send('Error fetching published
posts');
        }

        res.render('DashBoard', {
            title: "Dashboard | CuteBlog Blogging",
            username: req.session.username,
            posts: posts
        });
    });
});

router.post('/delete-post', (req, res) => {
    // Purpose: This route handler function is responsible for deleting
    a post from the database.
    // Inputs: req (the Express request object), res (the Express
    response object).
    // Outputs: The function redirects the user to the '/author/author-
    home' route if the post is successfully deleted, or sends an error
    response if there are any issues.
    try {

```

```

const postId = req.body.postid;

console.log(postId);

// Delete the post from the database
db.run('DELETE FROM Posts WHERE id = ?', [postId], function(err)
{
    if (err) {
        console.log(err);
        return res.status(500).send('Error deleting the post.');
```

 }

 // Check if any rows were affected
 if (this.changes === 0) {
 return res.status(404).send('Post not found.');
 }

 res.redirect('/author/author-home');
});
} catch (error) {
 console.error(error);
 res.status(500).send('An error occurred.');
}
});

router.post('/delete-publishedpost', (req, res) => {
 // Purpose: This route handler function is responsible for deleting
 a published post from the database.
 // Inputs: req (the Express request object), res (the Express
 response object).
 // Outputs: The function redirects the user to the '/author/author-
 home' route if the post is successfully deleted, or return an error
 message if any issues arises.
 try {
 const postId = req.body._postId;
 const userId = req.session.userId;

 console.log(postId);
 console.log(userId);

 // Check if the post is published before deleting
 db.get('SELECT status FROM Posts WHERE id = ?', [postId], (err,
 row) => {
 if (err) {
 console.error('Error checking post status:', err);
 return res.status(500).render('error', { message: 'An error
 occurred while checking the post status.' });
 }

 if (!row || row.status !== 'published') {
 return res.status(404).render('error', { message: 'Post not
 found or not published.' });
 }

 // Delete the post from the database

```

        db.run('DELETE FROM Posts WHERE id = ?', [postId],
function(err) {
    if (err) {
        console.error('Error deleting the post:', err);
        return res.status(500).render('error', { message: 'An error
occurred while deleting the post.' });
    }

    // Check if any rows were affected
    if (this.changes === 0) {
        return res.status(404).render('error', { message: 'Post not
found.' });
    }

    res.redirect('/author/author-home');
});
});
} catch (error) {
    console.error('Error in /delete-publishedpost route:', error);
    res.status(500).render('error', { message: 'An unexpected error
occurred.' });
}
});

router.post('/edit-post', (req, res) => {
    // Purpose: This route handler function is responsible for
rendering the edit-post page for a specific post.
    // Inputs: req (the Express request object), res (the Express
response object).
    // Outputs: The function renders the 'edit-post' view and passes
the post information to the view.
    const postId = req.body.postid_for;

    db.get('SELECT * FROM Posts WHERE id = ?', [postId], (err, post) =>
{
        if (err) {
            console.error('Error retrieving post:', err.message);
            return res.status(500).send('Error retrieving post.');
```

```

const { postId, title, subtitle } = req.body;
const content = req.body.content;
const modifiedAt = new Date(); // Get the current time
const formattedmodified = formatDateForSQLite(modifiedAt);

// Fetch the existing post content
db.get('SELECT content FROM Posts WHERE id = ?', [postId], (err,
existingPost) => {
  if (err) {
    console.log(err.message);
    return res.status(500).send('Error fetching post.');
```

 }

 // Insert the old content into the PostHistory table
 db.run(
 'UPDATE Posts SET PostHistory = ?, modifiedAt = ? WHERE id
= ?',
 [existingPost.content, formattedmodified, postId],
 (err) => {
 if (err) {
 console.log(err.message);
 return res.status(500).send('Error saving post history.');
 }

 // Update the post with the new content
 db.run(
 'UPDATE Posts SET title = ?, subtitle = ?, content = ?,
ModifiedAt = ? WHERE id = ?',
 [title, subtitle, content, formattedmodified, postId],
 (err) => {
 if (err) {
 console.log(err.message);
 return res.status(500).send('Error updating post.');
 } else {
 // Redirect the user to the updated post or the list of
posts
 return res.redirect('/author/author-home'); // or
res.redirect('/posts');
 }
 }
);
 }
);
});
});

router.post('/publish-post/:postId', (req, res) => {
 // Purpose: This route handler function is responsible for
publishing a post by updating its status and publishedAt date in the
database.
 // Inputs: req (the Express request object), res (the Express
response object).
 // Outputs: If the post is successfully published, the function
redirects the user to the author-home page. If an error occurs, the
function sends an respective error response.
 try {
 const postId = req.params.postId;


```

    // Get the current date and time
    const publishedDate = new Date();

    const formattedpublish = formatDateForSQLite(publishedDate);

    console.log(formattedpublish);

    // Update the status of the post to 'published' in the database
    db.run('UPDATE Posts SET status = ?, publishedAt = ? WHERE id
= ?', ['published', formattedpublish, postId], function(err) {
        if (err) {
            console.error(err.message);
            return res.status(500).send('Error publishing the post.');
        }

        // Check if any rows were affected
        if (this.changes === 0) {
            return res.status(404).send('Post not found.');
        }

        res.redirect('/author/author-home');
    });
} catch (error) {
    console.error(error);
    res.status(500).send('An error occurred.');
}
});

router.post('/version-history', (req, res) => {
    // Purpose: This route handler function is responsible for
    rendering the version history for a specific post.
    // Inputs: req (the Express request object), res (the Express
    response object).
    // Outputs: The function renders the 'version-history' view and
    passes the past version of the particular post to the view.

    const postId = req.body.postid_;

    console.log(postId);

    // Fetch the post information
    db.get(`SELECT * FROM posts WHERE id = ?`, [postId], (err, post) =>
{
    if (err) {
        console.error(err);
        return res.status(500).send('Error fetching post information');
    }

    if (!post) {
        return res.status(404).send('Post not found');
    }

    // Render the post information to the page
    res.render('version-history', { post });
});
});

```

```

router.get('/', (req, res) =>
  // Purpose: This route handler function is responsible for
  rendering the "author-home" view when a user visits the root URL of
  the author path.
  // Inputs: req (the Express request object), res (the Express
  response object).
  // Outputs: The function renders the "author-home" view and sends
  the response back to the client.
  {
    res.render('author-home')
  });

module.exports = router;

//End of Code written without Assistance for this code extract

```

Reader Routes Files

```

/**
 * These are the routes for the reader feature
 */
const express = require('express');
const router = express.Router();
const date_time = new Date();
const { check, validationResult } = require('express-validator');
const session = require('express-session');
const bodyParser = require('body-parser');
router.use(bodyParser.urlencoded({ extended: false }));
router.use(session({ secret: 'secret-key', resave: false,
saveUninitialized: true }));
const bcrypt = require('bcrypt');
const rateLimit = require('express-rate-limit');
//Start of Code written without Assistance for this code extract

const loginLimiter = rateLimit({
  windowMs: 15 * 60 * 1000, // 15 minutes
  max: 4, // limit each IP to 4 requests per windowMs
  message: 'Too many login/register attempts from this IP, please try
again after 15 minutes'
});

const redirectlogin = (req, res, next) => {
  if (!req.session.username) {
    res.redirect('/login');
  } else {
    console.log("The session UserId is set as: " +
req.session.userId);
    next();
  }
}

router.get('/', (req, res) => {
  // Purpose: This route is responsible for rendering the main page
  of the application.

```

```

    // Render the 'mainpage' view and send the response to the client.
    res.render('mainpage');
  });

  router.get('/register', function (req, res) {
    // Purpose: This route is responsible for rendering the
    registration page.

    // Render the 'register' view and pass the title parameter to the
    view.
    res.render('register', {
      title: "Account Register | CuteBlog Blogging"
    });
  });

  router.post('/register-process', [
    // Middleware to validate the input fields
    check('email').isEmail(),
    check('username').not().isEmpty(),
    check('password').isLength({ min: 8 }),
  ],
  loginLimiter,
  function(req, res) {
    // Purpose: This route is responsible for processing the user
    registration form.

    // Validate the input fields
    const errors = validationResult(req);
    if (!errors.isEmpty()) {
      console.log(errors);
      return res.redirect('/register');
    }

    // Sanitize and retrieve the input values
    const plainPassword = req.sanitize(req.body.password);
    const sanitizedUsername = req.sanitize(req.body.username);
    const email = req.sanitize(req.body.email);

    const saltRounds = 10;

    // Check if the username already exists
    const sql = 'SELECT * FROM Users WHERE username = ?';
    db.get(sql, [sanitizedUsername], function(err, row) {
      if (err) {
        console.error(err);
        return res.status(500).send('Error checking for existing
username');
      }

      if (row) {
        console.log("Username has been taken!");
        return res.render('register', { usernameError: 'Username
already taken' });
      }

      // Hash the password
      bcrypt.hash(plainPassword, saltRounds, function(err,
hashedPassword) {

```

```

        if (err) {
            console.error(err);
            return res.status(500).send('Error hashing password');
        }

        // Insert the data into the SQLite database
        const insertSql = 'INSERT INTO Users (username, password, email) VALUES (?, ?, ?)';
        const values = [sanitizedUsername, hashedPassword, email];

        db.run(insertSql, values, function(err) {
            if (err) {
                console.error(err);
                return res.status(500).send('Error inserting data into the database');
            }
            else {
                // Sending confirmation message by rendering empty ejs template with array of strings
                var message = ["Success!", "You are now registered. You may login as " + sanitizedUsername + " now.", "Your user name is: " + sanitizedUsername, "Your hashed password is: " + plainPassword];
                res.render('confirmation.ejs', { messages: message });
            }
        });
    });
});

router.get('/login', function (req, res) {
    // Purpose: This route is responsible for rendering the login page.

    // Render the 'login' view and pass the title parameter to the view.
    res.render('login', {
        title: "Account Login | CuteBlog Blogging"
    });
});

router.post('/login-process', loginLimiter, function (req, res) {
    // Purpose: This route is responsible for handling the login process.
    // It receives the user's login credentials, validates them against the database,
    // and manages the user's session if the login is successful.

    // Inputs:
    // - req.body.password: The plain-text password entered by the user.
    // - req.body.input: This can be either the user's username or email.
    // - loginLimiter: A middleware function that limits the number of login attempts
    //   to prevent brute-force attacks.

    const input = req.body.input;
    const plainPassword = req.body.password;

```

```

    db.serialize(function() {
        // Searching the database for the username or email
        db.get('SELECT * FROM users WHERE username = ? OR email = ?',
[input, input], function(err, row) {
            if (err) throw err;

            if (!row) {
                // Username/email not found, sending an error message
                var message = ["Failure", "Login unsuccessful.",
"Username/email incorrect, please try again."];
                res.render('confirmation.ejs', { messages: message });
            } else {
                // Comparing entered password to the hashed password in the
database
                const hashedPassword = row.password;
                bcrypt.compare(plainPassword, hashedPassword, function(err,
result) {
                    if (err) throw err;
                    else {
                        if (!result) {
                            // Passwords don't match, sending an error message
                            var message = ["Failure", "Login unsuccessful.",
"Password incorrect, please try again."];
                            res.render('confirmation.ejs', { messages: message });
                        } else {
                            // Saving user session since login was successful
                            req.session.userId = row.id;
                            req.session.email = row.email;
                            req.session.username = row.username;
                            // Sending a confirmation by rendering empty ejs
template with array of strings
                            var message = ["Success!", "You are now logged in."];
                            res.render('confirmation.ejs', { messages: message });
                        }
                    }
                });
            }
        });
    });

router.get('/about', function (req, res) {
    // Purpose: This route is responsible for rendering the "About"
page.

    // Render the 'about' view and pass the title parameter to the
view.
    res.render('about', {
        title: "About the developer | CuteBlog Blogging"
    });
});

router.get('/DashBoard', redirectlogin, (req, res) => {
    // Purpose: This route is responsible for rendering the Dashboard
page, which displays
    // a list of published blog posts and the blog settings.

```

```

// Inputs:
// - redirectlogin: A middleware function that redirects the user
to the login page
//   if they are not logged in.
// - req.session.username: The username of the currently logged-in
user, which is
//   retrieved from the session.

// Fetch the published blog posts
db.all('SELECT * FROM Posts WHERE status = "published" ORDER BY
publishedAt DESC', (err, posts) => {
  if (err) {
    console.error('Error fetching published posts:', err);
    return res.status(500).send('Error fetching published posts');
  }

  // Fetch the blog settings
  db.get('SELECT * FROM Settings', (err, settings) => {
    if (err) {
      console.error('Error fetching blog settings:', err);
      return res.status(500).send('Error fetching blog settings');
    }

    // Render the 'DashBoard' view and pass the following data:
    // - title: The page title
    // - username: The username of the currently logged-in user
    // - posts: An array of published blog posts, ordered by
publication date in descending order
    // - settings: The blog settings
    res.render('DashBoard', {
      title: "Dashboard | CuteBlog Blogging",
      username: req.session.username,
      posts: posts,
      settings: settings
    });
  });
});
});
});

router.get('/view-post/:postid', function (req, res) {
  // Purpose: This route is responsible for rendering the "View Post"
page, which displays
  // the details of a specific blog post and its associated comments.

  // Inputs:
  // - req.params.postid: The ID of the blog post to be viewed.
  // - req.session.userId: The ID of the currently logged-in user.
  // - req.session.username: The username of the currently logged-in
user.

  const postid = req.params.postid;
  const userId = req.session.userId;
  const username = req.session.username;

  // Queries:
  // - commentsQuery: Retrieves the count of comments for the given
post.

```

```

// - commentQuery: Retrieves the comments for the given post,
ordered by creation date in descending order.
// - postQuery: Retrieves the details of the blog post with the
given ID.
// - userQuery: Retrieves the details of the user with the given
ID.
// - updateViewCountQuery: Increments the view count for the given
blog post.

const commentsQuery = 'SELECT COUNT(*) AS commentCount FROM
Comments WHERE postId = ?';
const commentQuery = 'SELECT * FROM Comments WHERE postId = ? ORDER
BY createdAt DESC';
const postQuery = 'SELECT * FROM Posts WHERE id = ?';
const userQuery = "SELECT * FROM Users WHERE id = ?";
const updateViewCountQuery = 'UPDATE Posts SET Views = Views + 1
WHERE id = ?';

// Fetch the comment count for the given post
db.get(commentsQuery, [postId], (err, commentCount) => {
  if (err) {
    console.error(err);
    return res.status(500).json({ error: 'Internal server
error' });
  }

  // Fetch the comments for the given post
  db.all(commentQuery, [postId], (err, comments) => {
    if (err) {
      console.error(err);
      return res.status(500).json({ error: 'Internal server
error' });
    }

    // Fetch the details of the blog post with the given ID
    db.get(postQuery, [postId], (err, post) => {
      if (err) {
        console.error(err);
        return res.status(500).json({ error: 'Internal server
error' });
      }

      if (!post) {
        return res.status(404).json({ error: 'Post not found' });
      }

      // Update the view count for the blog post
      db.run(updateViewCountQuery, [postId], (err) => {
        if (err) {
          console.error(err);
          return res.status(500).json({ error: 'Internal server
error' });
        }

        // Fetch the details of the user who created the blog post
        db.get(userQuery, [userId], (err, user) => {
          if (err) {
            console.error(err);

```

```

        return res.status(500).json({ error: 'Internal server
error' });
    }

    if (!user) {
        return res.status(404).json({ error: 'User not
found' });
    }

    // Render the 'view-post' view and pass the following
data:
    // - post: The details of the blog post
    // - comments: The comments for the blog post
    // - commentCount: The count of comments for the blog
post
    // - user: The details of the user who created the blog
post
    // - username: The username of the currently logged-in
user
    res.render('view-post', { post: post, comments: comments,
commentCount: commentCount.commentCount, user: user, username:
username });
    });
    });
    });
    });
    });
});

router.post('/like-post', function (req, res) {
    // Purpose: This route is responsible for updating the likes count
of a particular blog post based on post ID.

    // Inputs:
    // - req.body.postLikeId - The ID of the post being liked.
    // - req.body.userId - The ID of the user liking the post.

    const postId = req.body.postLikeId;

    // Directly update the likes count in the Posts table
    const updateLikesQuery = "UPDATE Posts SET likes = likes + 1 WHERE
id = ?";
    db.run(updateLikesQuery, [postId], (err) => {
        if (err) {
            // If there is an error updating the likes count, log the error
and send a 500 Internal Server Error response.
            console.error(err);
            return res.status(500).send('Error updating likes count');
        }

        // Redirect the user to the view-post page after updating the
likes count.
        res.redirect(`/view-post/${postId}`);
    });
});

router.post('/dislike-post', function (req, res) {

```



```

// Purpose: This route is responsible for updating the dislikes
count of a particular blog post based on post ID.

// Inputs:
// - req.body.postdisLikeId - The ID of the post being disliked.
// - req.body.userrid - The ID of the user disliking the post.

const postId = req.body.postdisLikeId;
const userId = req.body.userrid; // Assuming you have the user's ID
in the request

// Update the dislikes count in the Posts table
const updateDislikesQuery = "UPDATE Posts SET dislikes = dislikes +
1 WHERE id = ?";
db.run(updateDislikesQuery, [postId], (err) => {
  if (err) {
    // If there is an error updating the dislikes count, log the
error and send a 500 Internal Server Error response.
    console.error(err);
    return res.status(500).send('Error updating dislikes count');
  }

  // Redirect the user to the dashboard page after updating the
dislikes count.
  res.redirect(`/view-post/${postId}`);
});
});

router.post('/add-comments', function(req, res) {
  // Purpose: This route is responsible for adding a new comment to
the database.

  // Inputs:
  // - req.body.pstid - The ID of the post the comment is being added
to.
  // - req.body.comment - The text content of the comment.
  // - req.body.commenter - The username of the user making the
comment.

  const AddComments = 'INSERT INTO Comments (postId, text,
comment_user) VALUES (?, ?, ?)';
  const postId = req.body.pstid;
  const text = req.body.comment;
  const userName = req.body.commenter;

  db.all(AddComments, [postId, text, userName], (err, result) => {
    if (err) {
      // If there is an error adding the comment, log the error and
send a 500 Internal Server Error response with an error message.
      console.error('Error adding comment:', err);
      return res.status(500).json({ error: 'Error adding comment' });
    } else {
      // If the comment is added successfully, redirect the user to
the dashboard.
      res.redirect(`/view-post/${postId}`);
    }
  });
});
});

```

```

router.get('/settings', function (req, res) {
  // Purpose: This route is responsible for rendering the user
  settings page.

  // Inputs:
  // - None

  // Render the 'settings' view.
  res.render('settings');
});

//End of Code written without Assistance for this code extract

module.exports = router;

```

Common Route Files

```

const express = require('express');
const router = express.Router();
const date_time = new Date();
const { check, validationResult } = require('express-validator');
const session = require('express-session');
const bodyParser = require('body-parser');
router.use(bodyParser.urlencoded({ extended: false }));
router.use(session({ secret: 'secret-key', resave: false,
saveUninitialized: true }));

//Start of Code written without Assistance for this code extract
router.get('/logout', function (req, res) {
  // Purpose: This route is responsible for destroying the user's
  session and redirecting them to the login page.

  // Inputs:
  // - req.session - The user's current session.

  // Destroy the session
  req.session.destroy(function (err) {
    if (err) {
      // If there is an error destroying the session, log the error
      and send a 500 Internal Server Error response.
      console.error('Error destroying session:', err);
      res.sendStatus(500);
    } else {
      // If the session is destroyed successfully, log a success
      message and redirect the user to the login page.
      console.log("Session has been successfully destroyed");
      res.redirect('/login');
    }
  });
});

router.get('/AccessDenied', function (req, res) {
  // Purpose: This route is responsible for rendering the
  'AccessDenied' view when an unauthorized user attempts to access a
  restricted resource.

  // Inputs:

```

```

// - None

// Render the 'AccessDenied' view and pass in a title for the page.
res.render('AccessDenied', {
  title: "Access Denied | CuteBlog Blogging",
});
});

router.get('/user-profile', function (req, res) {
  // Purpose: This route is responsible for rendering the user
  profile page with the user's information.

  // Inputs:
  // - req.session.userId - The ID of the user whose profile is being
  displayed.

  const userId = req.session.userId;

  // Fetch the user information from the database using the userId
  db.get('SELECT * FROM users WHERE id = ?', [userId], (err, user) =>
  {
    if (err) {
      // If there is an error fetching the user information, log the
      error and send a 500 Internal Server Error response.
      console.error(err);
      return res.status(500).send('Error fetching user information');
    }

    if (!user) {
      // If the user is not found in the database, send a 404 Not
      Found response.
      return res.status(404).send('User not found');
    }

    // Get the current date in the local format.
    const currentDate = new Date().toLocaleDateString();

    // Render the 'user-profile' view and pass in the user's
    information and the current date.
    res.render('user-profile', {
      title: "User Settings | CuteBlog Blogging",
      currentDate: currentDate,
      user: user
    });
  });
});

router.post('/user-settings', function (req, res) {
  // Purpose: This route is responsible for updating a user's
  settings, including their username and email.

  // Inputs:
  // - req.body.username - The new username the user wants to set.
  // - req.body.email - The new email the user wants to set.
  // - req.session.userId - The ID of the user whose settings are
  being updated.

  const { username, email, password } = req.body;

```

```

const userId = req.session.userId;

db.run(
  // This SQL query updates the username and email columns for the
  user with the specified userId in the users table.
  'UPDATE users SET username = ?, email = ? WHERE id = ?',
  [username, email, userId],
  function (err) {
    if (err) {
      // If there is an error updating the user's settings, log the
      error and send a 500 Internal Server Error response.
      console.error(err);
      return res.status(500).send('Error updating user settings');
    }

    // If the user's settings were updated successfully, send a
    success message.
    res.send('User settings updated successfully');
  }
);
});

router.post('/process-delete', function (req, res) {
  // Purpose: This route is responsible for deleting a user account
  from the database and clearing the user's session.

  // Inputs:
  // - req.session.userId - The ID of the user whose account is being
  deleted.

  const userId = req.session.userId;

  db.run(
    // This SQL query deletes the user with the specified userId from
    the users table in the database.
    'DELETE FROM users WHERE id = ?',
    [userId],
    function (err) {
      if (err) {
        // If there is an error deleting the user, log the error and
        send a 500 Internal Server Error response.
        console.error(err);
        return res.status(500).send('Error deleting user account');
      }

      // Clear the user's session
      req.session.destroy(function (err) {
        if (err) {
          // If there is an error clearing the user's session, log
          the error and send a 500 Internal Server Error response.
          console.error(err);
          return res.status(500).send('Error clearing user session');
        }

        // If the user account was deleted and the session was
        cleared successfully, send a success message.
        res.send('User account deleted successfully');
      });
    }
  );
});

```

```
    }  
  );  
});
```

```
//End of Code written without Assistance for this code extract
```

```
module.exports = router;
```

About.css

```
//Start of Code written without Assistance for this code extract
```

```
body {  
  background-image: url("/assets/background.jpg");  
  background-size: cover;  
  background-repeat: no-repeat;  
  background-color: rgba(255, 255, 255, 0.8);  
}
```

```
/* Heading */
```

```
h1 {  
  color: #ff6ac9;  
  font-size: 32px;  
  font-family: "Comic Sans MS", cursive;  
  text-align: center;  
}
```

```
/* Paragraphs */
```

```
p.text {  
  color: #c966f0;  
  font-size: 18px;  
  font-family: "Arial", sans-serif;  
  text-align: justify;  
  line-height: 1.5;  
}
```

```
/* Image */
```

```
img {  
  display: block;  
  margin: 0 auto;  
  max-width: 300px;  
  border-radius: 50%;  
  box-shadow: 0 0 10px rgba(0, 0, 0, 0.2);  
}
```

```
/* Spacing */
```

```
.wp-block-spacer {  
  height: 50px;  
}
```

```
.text-container {
```

```
  background-color: #fffff8;  
  padding: 20px;  
  border-radius: 10px;  
  box-shadow: 0 0 10px rgba(0, 0, 0, 0.2);  
  max-width: 600px;  
  margin: 0 auto;  
}
```

```
.text-container h1 {
  color: #ff6ac9;
  font-size: 32px;
  font-family: "Comic Sans MS", cursive;
  text-align: center;
  margin-bottom: 20px;
}

.text-container p.text {
  color: #ff70b8;
  font-size: 18px;
  font-family: "Arial", sans-serif;
  text-align: justify;
  line-height: 1.5;
}
```

//End of Code written without Assistance for this code extract

AccessDenied.css

//Start of Code written without Assistance for this code extract

```
body {
  background-color: #ffe6f2;
  font-family: Arial, sans-serif;
  margin: 0;
  padding: 0;
}

.container {
  display: flex;
  justify-content: center;
  align-items: center;
  height: 100vh;
}

.content {
  text-align: center;
}

h1 {
  font-size: 36px;
  color: #ff00cc;
  margin-bottom: 10px;
}

p {
  font-size: 24px;
  color: #99004d;
  margin-bottom: 20px;
}

img {
  width: 300px;
  border-radius: 50%;
}
```

```
.Return {
  background-color: lightpink;
  color: #fff;
  border: none;
  padding: 10px 20px;
  font-size: 16px;
  text-decoration: none;
  cursor: pointer;
  border-radius: 5px;
  transition: background-color 0.3s ease;
}

.Return:hover {
  background-color: palevioletred;
}

.Return a {
  text-decoration: none;
}
```

//End of Code written without Assistance for this code extract

Author-Home.css

```
/* Author-home.css */
```

//Start of Code written without Assistance for this code extract

```
.author-page {
  padding: 20px;
}

.published-articles,
.draft-articles {
  width: 100%;
  border-collapse: collapse;
  margin-bottom: 20px;
  background-color: whitesmoke;
}

.published-articles th,
.draft-articles th {
  background-color: rgba(242, 242, 242, 0.2);
  padding: 10px;
  text-align: left;
}

.published-articles td,
.draft-articles td {
  padding: 10px;
  border-bottom: 1px solid #ddd;
}

.published-articles .like,
.draft-articles .like,
.published-articles .dislike,
.draft-articles .dislike,
```

```

.published-articles .View-post,
.draft-articles .View-post,
.published-articles .Edit-post,
.draft-articles .Edit-post,
.published-articles .Delete-post,
.draft-articles .Delete-post,
.published-articles .Publish-post,
.draft-articles .Publish-post {
  background-color: transparent;
  border: none;
  cursor: pointer;
  padding: 0;
  margin-right: 5px;
}

.published-articles .like img,
.draft-articles .like img,
.published-articles .dislike img,
.draft-articles .dislike img,
.published-articles .Edit-post img,
.draft-articles .Edit-post img {
  width: 20px;
  height: 20px;
  vertical-align: middle;
}

.no-posts {
  text-align: center;
  font-style: italic;
  color: #999;
}

.header-buttons {
  background-color: #64c4a1; /* Soft green color */
  border: none;
  color: white;
  padding: 14px 28px; /* Increased padding */
  text-align: center;
  text-decoration: none;
  display: inline-block;
  font-size: 18px; /* Increased font size */
  margin: 6px 4px; /* Increased spacing */
  cursor: pointer;
  border-radius: 20px; /* Rounded corners */
  box-shadow: 0 4px 8px 0 rgba(0,0,0,0.2); /* Add a subtle drop
shadow */
  transition: background-color 0.3s ease; /* Smooth transition on
hover */
}

.header-buttons a {
  color: white;
  text-decoration: none;
}

.header-buttons:hover {
  background-color: #46b38c; /* Slightly darker green on hover */
}

```



```
.dust img
{
  width: 20px;
  height: 20px;
  vertical-align: middle;
}

body {
  background-image: url(/assets/background.png);
  background-repeat: no-repeat;
  background-size: cover;
}

h2
{
  color:white;
}

.subtitle-settings
{
  color:black;
}

.links
{
  text-decoration: none;
}

/* Breadcrumb */
.breadcrumb {
  display: flex;
  list-style: none;
  padding: 10px 0;
  background-color: #f1f1f1;
  margin: 10px 0;
  border-radius: 5px;
}

.breadcrumb li {
  padding-left: 10px;
  margin-right: 10px;
  color: #007bff;
}

.breadcrumb li::after {
  content: "/";
  margin-left: 10px;
  color: #6c757d;
}

.breadcrumb li:last-child {
  color: #6c757d;
}

.breadcrumb li:last-child::after {
  content: "";
}
```

```
//End of Code written without Assistance for this code extract
```

Back-up.css

```
//Start of Code written without Assistance for this code extract
```

```
.mh-wrapper
{
    word-wrap: break-word;
    cursor: auto;
    margin: 0;
    border: 0;
    font: inherit;
    display: block;
    background: none;
    padding: 0px;
    color: #fff;
}

.mh-content
{
    word-wrap: break-word;
    cursor: auto;
    color: #fff;
    font: inherit;
    vertical-align: baseline;
    overflow: hidden;
    background: rgba(255, 255, 255, 0.33);
    border-radius: 16px;
    box-shadow: 0 4px 30px rgba(0, 0, 0, 0.1);
    backdrop-filter: blur(5.7px);
    border: 2px solid rgba(255, 255, 255, 0.8);
    padding: 25px;
    float: none;
    width: 80%;
    margin: 20px auto;
}

.post
{
    word-wrap: break-word;
    cursor: auto;
    color: #fff;
    margin: 0;
    padding: 0;
    border: 0;
    font: inherit;
    display: block;
}

.entry-header
{
    word-wrap: break-word;
    cursor: auto;
    color: #fff;
    margin: 0;
    padding: 0;
    border: 0;
    font: inherit;
    display: block;
}
```

```
    margin-bottom: 1.25rem;
}

.entry-title
{
    word-wrap: break-word;
    cursor: auto;
    margin: 0;
    padding: 0;
    border: 0;
    font: inherit;
    vertical-align: baseline;
    font-weight: 700;
    font-family: "Viking", "Open Sans", Helvetica, sans-serif;
    text-shadow: 3px 3px 10px black;
    line-height: 1.5;
    color: #fff!important;
    font-size: 1.5rem;
}

.entry-meta
{
    word-wrap: break-word;
    cursor: auto;
    margin: 0;
    border: 0;
    font: inherit;
    vertical-align: baseline;
    font-size: 0.8125rem;
    margin-top: 0.625rem;
    border-top: 1px dotted #ebebeb;
    border-bottom: 1px dotted #ebebeb;
    padding: 5px 0;
    color: #fff;
}

.entry-meta-date
{
    word-wrap: break-word;
    cursor: auto;
    color: #fff;
    margin: 0;
    padding: 0;
    border: 0;
    font: inherit;
    vertical-align: baseline;
    margin-right: 10px;
}

.entry-content
{
    word-wrap: break-word;
    cursor: auto;
    color: #fff;
    margin: 0;
    padding: 0;
    border: 0;
    font: inherit;
```

```

    counter-reset: footnotes;
    display: block;
}

.entry-thumbnail {
    display: block;
    max-width: 100%;
    height: auto;
    margin: 0 auto;
    text-align: center;
    border: 2px white;
}

.entry-thumbnail img {
    max-width: 70%;
    height: auto;
    border: 2px white;
}

p{
    word-wrap: break-word;
    cursor: auto;
    margin: 0;
    padding: 0;
    border: 0;
    font: inherit;
    vertical-align: baseline;
    margin-bottom: 1.25rem;
    color: #fff;
}

body {
    background-image: url(/assets/background.png);
    background-repeat: no-repeat;
    background-size: cover;
}

form {
    word-wrap: break-word;
    cursor: auto;
    color: #fff;
    margin: 0;
    padding: 25px;
    border: 2px solid rgba(255, 255, 255, 0.8);
    font: inherit;
    vertical-align: baseline;
    background: rgba(255, 255, 255, 0.33);
    border-radius: 16px;
    box-shadow: 0 4px 30px rgba(0, 0, 0, 0.1);
    backdrop-filter: blur(5.7px);
}

form label {
    display: block;
    margin-bottom: 0.5rem;
    font-weight: bold;
    text-shadow: 3px 3px 10px black;
}

```

```

form input, form textarea {
display: block;
width: 100%;
padding: 0.5rem;
border: 1px solid rgba(255, 255, 255, 0.8);
border-radius: 4px;
background-color: rgba(255, 255, 255, 0.5);
color: #333;
margin-bottom: 1rem;
}

form button {
display: block;
width: 100%;
padding: 0.5rem;
border: none;
border-radius: 4px;
background-color: #007bff;
color: #fff;
font-weight: bold;
cursor: pointer;
transition: background-color 0.3s ease;
}

form button:hover {
background-color: #0056b3;
}

.Delete-Account {
background-color: #ff0000; /* Red color */
border: none;
color: white;
padding: 8px 16px; /* Smaller padding */
text-align: center;
text-decoration: none;
display: inline-block;
font-size: 14px; /* Smaller font size */
margin: 4px 2px; /* Smaller margin */
cursor: pointer;
border-radius: 4px; /* Slightly rounded corners */
}

.Delete-Account a {
color: white;
text-decoration: none;
}

.warning {
font-size: 14px; /* Adjust the font size as needed */
font-weight: bold; /* Make the text bold */
color: #ff0000; /* Set the text color to red */
background-color: #f8f8f8; /* Set a light background color */
padding: 10px 15px; /* Add some padding around the text */
border: 1px solid #e0e0e0; /* Add a light border */
border-radius: 4px; /* Add some rounded corners */
margin-top: 10px; /* Add some space above the message */
}

```

```

    .return {
      display: inline-block;
      background-color: #007bff;
      color: #fff;
      border: none;
      border-radius: 4px;
      padding: 0.5rem 1rem;
      text-decoration: none;
      font-size: 1rem;
      font-weight: bold;
      cursor: pointer;
      transition: background-color 0.3s ease;
    }

    .return:hover {
      background-color: #0056b3;
    }

    .return a {
      color: #fff;
      text-decoration: none;
    }

```

//End of Code written without Assistance for this code extract

Change.css

//Start of Code written without Assistance for this code extract

```

.cute-button {
  display: inline-block;
  padding: 10px;
  background-color: pink;
  color: white;
  border: none;
  border-radius: 20px;
  font-family: 'Arial', sans-serif;
  font-size: 16px;
  cursor: pointer;
}

.cute-button:hover {
  background-color: hotpink;
}

```

//End of Code written without Assistance for this code extract

Confirmation.css

/* confirmation.css */

//Start of Code written without Assistance for this code extract

```

body {
  font-family: 'Open Sans', sans-serif;
  background-color: #f7f7f7; /* light gray background */
}

h2 {

```

```

    font-size: 24px;
    color: #333; /* dark gray text */
    text-align: center;
    margin-bottom: 20px;
}

p {
    font-size: 18px;
    color: #666; /* medium gray text */
    margin-bottom: 10px;
}

/* Add some bubbly effects */
h2, p {
    border-radius: 10px;
    padding: 10px;
    background-color: #fff; /* white background */
    box-shadow: 0 0 10px rgba(0, 0, 0, 0.1); /* subtle shadow */
}

h2 {
    background-color: #ffe6e6; /* light pink background */
    color: #ff69b4; /* bright pink text */
}

p {
    background-color: #f2f2f2; /* light gray background */
}

h2:before {
    background-image: url('/assets/success.svg'); /* replace with
your SVG file name */
    background-size: 24px 24px; /* adjust the size to your liking */
    width: 24px;
    height: 24px;
    display: inline-block;
    margin-right: 10px;
    background-repeat: no-repeat;
    vertical-align: middle;
    color: #ff69b4; /* bright pink text */
    content: ""; /* empty content to avoid displaying the pseudo-
element's text */
}

p:before {
    display: inline-block;
    width: 1em;
    height: 1em;
    background-image: url('/assets/information.svg');
    background-size: contain;
    margin-right: 10px;
    font-size: 18px;
    color: #666;
    vertical-align: -0.125em;
    content: "";
}

```

//End of Code written without Assistance for this code extract

Create-post.css

```
//Start of Code written without Assistance for this code extract
body {
  font-family: Arial, sans-serif;
  padding: 20px;
  background-image: url(/assets/background.png);
  background-repeat: no-repeat;
  background-size: cover;
}

h1 {
  text-align: center;
  color: white;
}

form {
  width: 400px;
  margin: 0 auto;
}

label {
  display: block;
  margin-top: 10px;
}

input,
textarea {
  width: 100%;
  padding: 5px;
  margin-top: 5px;
}

button[type="submit"] {
  display: block;
  width: 100%;
  padding: 10px;
  margin-top: 10px;
  background-color: #4CAF50;
  color: white;
  border: none;
  cursor: pointer;
}

button[type="submit"]:hover {
  background-color: #45a049;
}
//End of Code written without Assistance for this code extract
```

Edit-Post.css

```
/* edit-post.css */

//Start of Code written without Assistance for this code extract

body {
  font-family: 'Helvetica Neue', Arial, sans-serif;
  background-color: #f8f8f8;
  color: #333;
  margin: 0;
  padding: 0;
}
```



```

}

h1 {
  text-align: center;
  margin-top: 2rem;
  color: #e91e63;
  font-size: 2.5rem;
}

form {
  max-width: 600px;
  margin: 2rem auto;
  background-color: #fff;
  padding: 2rem;
  border-radius: 8px;
  box-shadow: 0 2px 4px rgba(0, 0, 0, 0.1);
}

label {
  display: block;
  font-size: 1.1rem;
  margin-bottom: 0.5rem;
  color: #e91e63;
}

input[type="text"],
textarea {
  width: 100%;
  padding: 0.8rem;
  font-size: 1rem;
  border: 1px solid #ddd;
  border-radius: 4px;
  box-sizing: border-box;
  margin-bottom: 1.5rem;
}

textarea {
  height: 150px;
  resize: vertical;
}

button[type="submit"] {
  background-color: #e91e63;
  color: #fff;
  border: none;
  border-radius: 4px;
  padding: 0.8rem 1.5rem;
  font-size: 1.1rem;
  cursor: pointer;
  transition: background-color 0.3s ease;
}

button[type="submit"]:hover {
  background-color: #c2185b;
}

.postId input[type="text"]
{

```

```

    background-color: grey;
}

.back-button{
    background-color: #e91e63;
    color: #fff;
    border: none;
    border-radius: 4px;
    padding: 0.8rem 1.5rem;
    font-size: 1.1rem;
    cursor: pointer;
    transition: background-color 0.3s ease;
}

.back-button a
{
    text-decoration: none;
    color: white;
}

```

//End of Code written without Assistance for this code extract

Home.css

```

//Start of Code written without Assistance for this code extract
body {
    font-family: 'Open Sans', sans-serif;
    background-image: url(/assets/background2.PNG);
    background-repeat: no-repeat;
    background-size: cover;
}

.time-container {
    background-color: #f9f9f9; /* Light gray background */
    border-radius: 10px; /* Rounded corners */
    padding: 20px; /* Add some padding */
    box-shadow: 0 4px 8px rgba(0, 0, 0, 0.1); /* Add a soft shadow */
}

h1 {
    display: inline-block;
    margin-right: 10px;
    font-size: 1.2em; /* slightly larger font size for emphasis */
    color: #333; /* a slightly darker gray for the heading */
}

h2
{
    color:white;
}

#current-time {
    font-size: 24px; /* Larger font size for current time */
    color: #ff6347; /* Cute pink color for time */
}

```

```
/* Published Articles Section */
.article-list {
  list-style-type: none;
  padding: 0;
  margin: 0;
}

.article-list li {
  border: 1px solid #ddd;
  border-radius: 5px;
  padding: 20px;
  margin-bottom: 20px;
  background-color: #f9f9f9;
}

.title {
  font-size: 24px;
  font-weight: bold;
  margin-bottom: 10px;
}

.subtitle {
  font-size: 18px;
  color: #666;
  margin-bottom: 10px;
}

.content {
  font-size: 16px;
  line-height: 1.5;
  margin-bottom: 20px;
}

.like, .dislike {
  display: inline-block;
  margin-right: 10px;
  background-color: #fff;
  border: 1px solid #ddd;
  border-radius: 5px;
  padding: 5px 10px;
  font-size: 14px;
  cursor: pointer;
}

.like img, .dislike img {
  height: 16px;
  vertical-align: middle;
  margin-right: 5px;
}

.Time-Created {
  font-size: 14px;
  color: #999;
  margin-top: 10px;
}

/* Share Button */
.Share-Button {
  display: inline-block;
```

```

background-color: #6c5ce7;
color: white;
text-align: center;
text-decoration: none;
font-size: 14px;
font-weight: 500;
padding: 8px 16px;
border: none;
border-radius: 20px;
box-shadow: 0 2px 4px rgba(0, 0, 0, 0.1);
cursor: pointer;
transition: transform 0.2s ease;
}

.Share-Button:hover {
  transform: translateY(-2px);
}

.Share-Button a {
  color: white;
  text-decoration: none;
}

/* View Post Button */
.View-post {
  display: inline-block;
  background-color: #00b894;
  color: white;
  text-align: center;
  text-decoration: none;
  font-size: 14px;
  font-weight: 500;
  padding: 8px 16px;
  border: none;
  border-radius: 20px;
  box-shadow: 0 2px 4px rgba(0, 0, 0, 0.1);
  cursor: pointer;
  transition: transform 0.2s ease;
}

.View-post:hover {
  transform: translateY(-2px);
}

.View-post a {
  color: white;
  text-decoration: none;
}

.no-posts {
  font-size: 18px;
  text-align: center;
  color: #999;
  padding: 20px;
}

body
{
  background-color: beige;

```

```

}

.time-container p {
  margin: 5px 0; /* Add margin between paragraphs */
  font-family: 'Arial', sans-serif; /* Use a cute font */
  color: #333; /* Dark text color */
}

.back-to-top
{
  tab-size: 4;
  line-height: inherit;
  font-family: "Roboto", sans-serif;
  font-weight: normal;
  font-style: normal;
  font-size: 15px;
  box-sizing: border-box;
  border-width: 0;
  border-style: solid;
  border-color: #e5e7eb;
  margin: 0;
  padding: 0;
  text-decoration: none;
  position: fixed;
  bottom: 2rem;
  right: 2rem;
  left: auto;
  z-index: 999;
  height: 2.5rem;
  width: 2.5rem;
  align-items: center;
  justify-content: center;
  border-radius: 0.375rem;
  --tw-bg-opacity: 1;
  background-color: rgb(39 181 247 / var(--tw-bg-opacity));
  --tw-text-opacity: 1;
  color: rgb(255 255 255 / var(--tw-text-opacity));
  --tw-shadow: 0 4px 6px -1px rgb(0 0 0 / 0.1), 0 2px 4px -2px rgb(0
0 0 / 0.1);
  --tw-shadow-colored: 0 4px 6px -1px var(--tw-shadow-color),
0 2px 4px -2px var(--tw-shadow-color);
  box-shadow: var(--tw-ring-offset-shadow, 0 0 #0000),
var(--tw-ring-shadow, 0 0 #0000), var(--tw-shadow);
  transition-property: color, background-color, border-color,
text-decoration-color, fill, stroke, opacity, box-shadow,
transform, filter,
  backdrop-filter, -webkit-text-decoration-color, -webkit-backdrop-
filter;
  transition-duration: 300ms;
  transition-timing-function: cubic-bezier(0.4, 0, 0.2, 1);
  display: flex;
}

.border-white
{
  -webkit-text-size-adjust: 100%;
  tab-size: 4;
  --thumb-width: 15;

```

```
line-height: inherit;
font-family: "Roboto", sans-serif;
font-weight: normal;
font-style: normal;
font-size: 15px;
--tw-bg-opacity: 1;
--tw-text-opacity: 1;
color: rgb(255 255 255 / var(--tw-text-opacity));
box-sizing: border-box;
border-width: 0;
border-style: solid;
--tw-translate-x: 0;
--tw-translate-y: 0;
--tw-skew-x: 0;
--tw-skew-y: 0;
--tw-scale-x: 1;
--tw-scale-y: 1;
--tw-pan-x: ;
--tw-pan-y: ;
--tw-pinch-zoom: ;
--tw-scroll-snap-strictness: proximity;
--tw-ordinal: ;
--tw-slashed-zero: ;
--tw-numeric-figure: ;
--tw-numeric-spacing: ;
--tw-numeric-fraction: ;
--tw-ring-inset: ;
--tw-ring-offset-width: 0px;
--tw-ring-offset-color: #fff;
--tw-ring-color: rgba(71, 197, 247, 0.788);
--tw-ring-offset-shadow: 0 0 #0000;
--tw-ring-shadow: 0 0 #0000;
--tw-shadow: 0 0 #0000;
--tw-shadow-colored: 0 0 #0000;
--tw-blur: ;
--tw-brightness: ;
--tw-contrast: ;
--tw-grayscale: ;
--tw-hue-rotate: ;
--tw-invert: ;
--tw-saturate: ;
--tw-sepia: ;
--tw-drop-shadow: ;
--tw-backdrop-blur: ;
--tw-backdrop-brightness: ;
--tw-backdrop-contrast: ;
--tw-backdrop-grayscale: ;
--tw-backdrop-hue-rotate: ;
--tw-backdrop-invert: ;
--tw-backdrop-opacity: ;
--tw-backdrop-saturate: ;
--tw-backdrop-sepia: ;
margin: 0;
padding: 0;
display: inline-block;
text-decoration: none;
-webkit-transition: all 0.4s ease;
margin-top: 6px;
```

```

height: 0.75rem;
width: 0.75rem;
--tw-rotate: 45deg;
transform: translate(var(--tw-translate-x), var(--tw-translate-y))
rotate(var(--tw-rotate)) skewX(var(--tw-skew-x)) skewY(var(--tw-
skew-y))
scaleX(var(--tw-scale-x)) scaleY(var(--tw-scale-y));
border-top-width: 1px;
border-left-width: 1px;
--tw-border-opacity: 1;
border-color: rgb(255 255 255 / var(--tw-border-opacity));
}

.blog-information {
background-color: #f8f8f8;
border: 1px solid #e5e5e5;
border-radius: 5px;
padding: 20px;
text-align: center;
box-shadow: 0 2px 4px rgba(0, 0, 0, 0.1);
}

.blog-information h1 {
font-size: 32px;
color: #333;
margin-bottom: 10px;
}

.blog-information h2 {
font-size: 24px;
color: #666;
margin-top: 0;
}
}
//End of Code written without Assistance for this code extract

```

Login.css

```

//Start of Code written without Assistance for this code extract
.login-page {
font-weight: 400;
font-family: Open Sans,-apple-system,BlinkMacSystemFont,Segoe
UI,Roboto,Helvetica Neue,Arial,sans-serif;
font-size: 15px!important;
color: rgba(255,255,255,.92);
cursor: auto;
margin: 10px;
padding: 0;
border: 1px solid #69697d;
display: block;
text-align: center;
margin-left: auto!important;
margin-right: auto!important;
margin-bottom: 20px;
max-width: 600px;
z-index: 1001;
background-color: rgba(128, 128, 128, 0.5); /* Update this line */
}

.section-header

```

```

{
    font-family: Open Sans,-apple-system,BlinkMacSystemFont,Segoe
UI,Roboto,Helvetica Neue,Arial,sans-serif;
    font-size: 15px!important;
    color: rgba(255,255,255,.92);
    cursor: auto;
    text-align: center;
    margin: 0;
    padding: 5px 10px;
    font-weight: 400!important;
    background: #20242a;
}

h2{
    --thumb-width: 15;
    font-family: Open Sans,-apple-system,BlinkMacSystemFont,Segoe
UI,Roboto,Helvetica Neue,Arial,sans-serif;
    cursor: auto;
    text-align: center;
    margin: 0;
    padding: 0;
    font-size: 22px;
    line-height: 32px;
    font-weight: 400;
    color: #add8f5;
}

.section-body{
    --thumb-width: 15;
    font-weight: 400;
    font-family: Open Sans,-apple-system,BlinkMacSystemFont,Segoe
UI,Roboto,Helvetica Neue,Arial,sans-serif;
    font-size: 15px!important;
    color: rgba(255,255,255,.92);
    cursor: auto;
    margin: 0;
    text-align: left;
    padding: 5px 10px 10px;
    background: #353b45;
}

.login-recovery
{
    font-weight: 400;
    font-family: Open Sans,-apple-system,BlinkMacSystemFont,Segoe
UI,Roboto,Helvetica Neue,Arial,sans-serif;
    font-size: 15px!important;
    color: rgba(255,255,255,.92);
    cursor: auto;
    padding: 0;
    text-align: right;
    width: 170px;
    display: inline-block;
    margin: 0 10px 15px 0;
}

.textbox
{

```



```

    margin: 0;
    font-family: Open Sans,-apple-system,BlinkMacSystemFont, Segoe
UI,Roboto,Helvetica Neue,Arial,sans-serif;
    font-size: 15px!important;
    outline: none;
    padding: 5px 7px;
    box-sizing: border-box;
    min-height: 30px;
    color: rgba(255,255,255,.92);
    background-color: rgba(0,0,0,.15)!important;
    border: 1px #69697d solid!important;
    border-radius: 7px;
}

.alignleft
{
    --thumb-width: 15;
    font-weight: 400;
    font-family: Open Sans,-apple-system,BlinkMacSystemFont, Segoe
UI,Roboto,Helvetica Neue,Arial,sans-serif;
    font-size: 15px!important;
    color: rgba(255,255,255,.92);
    cursor: auto;
    margin: 0;
    padding: 0;
    text-align: left;
}

.button
{
    --thumb-width: 15;
    margin: 0;
    text-align: center;
    display: inline-block;
    cursor: pointer;
    text-decoration: none;
    vertical-align: bottom;
    font-family: -apple-system,BlinkMacSystemFont, Segoe
UI,Roboto,Helvetica Neue,Arial,sans-serif!important;
    font-size: 15px!important;
    line-height: 50px;
    padding: 0 7px 2px 6px;
    color: rgba(255,255,255,.92)!important;
    background: #434b5b;
    border: 1px solid #69697d;
    margin-left: 232px;
}

body {
    background-image: url(/assets/house.jpg);
    background-repeat: no-repeat;
    background-size: cover;
}

.transparent-layer {
    position: fixed;
    top: 0;
    left: 0;

```

```
width: 100%;
height: 100%;
background-color: rgba(0, 0, 0, 0.5);
z-index: 1000;
}

.image-container {
  display: flex;
  justify-content: right;
  width: 70%;
}

.image-container img {
  width: 40%;
  height: auto;
}

#eyeIcon
{
  width: 20px;
  height: 20px;
}

.button-secondary
{
  background-color: beige;
  shape-margin: 1px;
}

.switch {
  position: relative;
  display: inline-block;
  width: 60px;
  height: 34px;
}

.switch input {
  display: none;
}

.slider {
  position: absolute;
  top: 0;
  left: 0;
  right: 0;
  bottom: 0;
  background-color: #ccc;
  border-radius: 34px;
  cursor: pointer;
  transition: .4s;
}

.slider:before {
  position: absolute;
  content: "";
  height: 26px;
  width: 26px;
  left: 4px;
```

```

    bottom: 4px;
    background-color: white;
    border-radius:50%;
    transition:.4s;
}

input:checked +.slider {
    background-color: #2196F3;
}

input:checked +.slider:before {
    transform: translateX(26px);
}

.light-mode-btn {
    margin-left: 10px;
    cursor: pointer;
    transition: color 0.3s ease;
}

.light-mode-btn:hover {
    color: #2196F3;
}
//End of Code written without Assistance for this code extract

```

Main.css

```

//Start of Code written without Assistance for this code extract
.hero-area
{
    tab-size: 4;
    line-height: inherit;
    font-family: "Roboto", sans-serif;
    font-weight: normal;
    font-style: normal;
    color: #727272;
    font-size: 15px;
    cursor: auto;
    box-sizing: border-box;
    border-width: 0;
    border-style: solid;
    border-color: #e5e7eb;
    margin: 0;
    position: relative;
    background-color: #fff;
    background-image: url("/assets/ponybg.PNG");
    background-size: cover;
    background-position: center;
    background-repeat: no-repeat;
    padding: 110px 0 120px 0;
}

.container
{
    tab-size: 4;
    line-height: inherit;
    font-family: "Roboto", sans-serif;
    font-weight: normal;
    font-style: normal;
}

```

```
color: #727272;
font-size: 15px;
cursor: auto;
box-sizing: border-box;
border-width: 0;
border-style: solid;
border-color: #e5e7eb;
margin: 0;
padding: 0;
width: 100%;
margin-right: auto;
margin-left: auto;
padding-right: 16px;
padding-left: 16px;
max-width: 720px;
}

.row
{
    -webkit-text-size-adjust: 100%;
    tab-size: 4;
    --thumb-width: 15;
    line-height: inherit;
    font-family: "Roboto", sans-serif;
    font-weight: normal;
    font-style: normal;
    color: #727272;
    font-size: 15px;
    cursor: auto;
    box-sizing: border-box;
    border-width: 0;
    border-style: solid;
    border-color: #e5e7eb;
    margin: 0;
    padding: 0;
}

.wow-animated
{
    -webkit-text-size-adjust: 100%;
    tab-size: 4;
    --thumb-width: 15;
    line-height: inherit;
    font-style: normal;
    cursor: auto;
    text-align: center;
    box-sizing: border-box;
    border-width: 0;
    border-style: solid;
    border-color: #e5e7eb;
    --tw-translate-x: 0;
    --tw-translate-y: 0;
    --tw-rotate: 0;
    --tw-skew-x: 0;
    --tw-skew-y: 0;
    --tw-scale-x: 1;
    --tw-scale-y: 1;
    --tw-pan-x: ;
}
```

```

--tw-pan-y: ;
--tw-pinch-zoom: ;
--tw-scroll-snap-strictness: proximity;
--tw-ordinal: ;
--tw-slashed-zero: ;
--tw-numeric-figure: ;
--tw-numeric-spacing: ;
--tw-numeric-fraction: ;
--tw-ring-inset: ;
--tw-ring-offset-width: 0px;
--tw-ring-offset-color: #fff;
--tw-ring-color: rgba(71, 197, 247, 0.788);
--tw-ring-offset-shadow: 0 0 #0000;
--tw-ring-shadow: 0 0 #0000;
--tw-shadow: 0 0 #0000;
--tw-shadow-colored: 0 0 #0000;
--tw-blur: ;
--tw-brightness: ;
--tw-contrast: ;
--tw-grayscale: ;
--tw-hue-rotate: ;
--tw-invert: ;
--tw-saturate: ;
--tw-sepia: ;
--tw-drop-shadow: ;
--tw-backdrop-blur: ;
--tw-backdrop-brightness: ;
--tw-backdrop-contrast: ;
--tw-backdrop-grayscale: ;
--tw-backdrop-hue-rotate: ;
--tw-backdrop-invert: ;
--tw-backdrop-opacity: ;
--tw-backdrop-saturate: ;
--tw-backdrop-sepia: ;
margin: 0px;
font-family: 'Barlow', sans-serif;
animation-duration: 1s;
animation-fill-mode: both;
color: #fff;
font-weight: 500;
display: inline-block;
background: #ffffff24;
padding: 13px 22px;
border-radius: 4px;
box-shadow: 0px 0px 10px #00000005;
font-size: 15px;
margin-bottom: 12px;
visibility: visible;
animation-delay: 0.2s;
}
.wow-h2
{
  -webkit-text-size-adjust: 100%;
  tab-size: 4;
  --thumb-width: 15;
  font-style: normal;
  cursor: auto;
  text-align: center;

```

```
box-sizing: border-box;
border-width: 0;
border-style: solid;
border-color: #e5e7eb;
--tw-translate-x: 0;
--tw-translate-y: 0;
--tw-rotate: 0;
--tw-skew-x: 0;
--tw-skew-y: 0;
--tw-scale-x: 1;
--tw-scale-y: 1;
--tw-pan-x: ;
--tw-pan-y: ;
--tw-pinch-zoom: ;
--tw-scroll-snap-strictness: proximity;
--tw-ordinal: ;
--tw-slashed-zero: ;
--tw-numeric-figure: ;
--tw-numeric-spacing: ;
--tw-numeric-fraction: ;
--tw-ring-inset: ;
--tw-ring-offset-width: 0px;
--tw-ring-offset-color: #fff;
--tw-ring-color: rgba(71, 197, 247, 0.788);
--tw-ring-offset-shadow: 0 0 #0000;
--tw-ring-shadow: 0 0 #0000;
--tw-shadow: 0 0 #0000;
--tw-shadow-colored: 0 0 #0000;
--tw-blur: ;
--tw-brightness: ;
--tw-contrast: ;
--tw-grayscale: ;
--tw-hue-rotate: ;
--tw-invert: ;
--tw-saturate: ;
--tw-sepia: ;
--tw-drop-shadow: ;
--tw-backdrop-blur: ;
--tw-backdrop-brightness: ;
--tw-backdrop-contrast: ;
--tw-backdrop-grayscale: ;
--tw-backdrop-hue-rotate: ;
--tw-backdrop-invert: ;
--tw-backdrop-opacity: ;
--tw-backdrop-saturate: ;
--tw-backdrop-sepia: ;
padding: 0;
font-family: 'Barlow', sans-serif;
animation-name: fadeInUp;
font-weight: 700;
color: #fff;
margin: 0px 0 18px;
text-transform: capitalize;
overflow: hidden;
font-size: 30px;
line-height: 40px;
visibility: visible;
animation-delay: 0.4s;
```

```

}

.wow
{
    -webkit-text-size-adjust: 100%;
    tab-size: 4;
    --thumb-width: 15;
    font-family: "Roboto", sans-serif;
    font-style: normal;
    cursor: auto;
    text-align: center;
    box-sizing: border-box;
    border-width: 0;
    border-style: solid;
    border-color: #e5e7eb;
    --tw-translate-x: 0;
    --tw-translate-y: 0;
    --tw-rotate: 0;
    --tw-skew-x: 0;
    --tw-skew-y: 0;
    --tw-scale-x: 1;
    --tw-scale-y: 1;
    --tw-pan-x: ;
    --tw-pan-y: ;
    --tw-pinch-zoom: ;
    --tw-scroll-snap-strictness: proximity;
    --tw-ordinal: ;
    --tw-slashed-zero: ;
    --tw-numeric-figure: ;
    --tw-numeric-spacing: ;
    --tw-numeric-fraction: ;
    --tw-ring-inset: ;
    --tw-ring-offset-width: 0px;
    --tw-ring-offset-color: #fff;
    --tw-ring-color: rgba(71, 197, 247, 0.788);
    --tw-ring-offset-shadow: 0 0 #0000;
    --tw-ring-shadow: 0 0 #0000;
    --tw-shadow: 0 0 #0000;
    --tw-shadow-colored: 0 0 #0000;
    --tw-blur: ;
    --tw-brightness: ;
    --tw-contrast: ;
    --tw-grayscale: ;
    --tw-hue-rotate: ;
    --tw-invert: ;
    --tw-saturate: ;
    --tw-sepia: ;
    --tw-drop-shadow: ;
    --tw-backdrop-blur: ;
    --tw-backdrop-brightness: ;
    --tw-backdrop-contrast: ;
    --tw-backdrop-grayscale: ;
    --tw-backdrop-hue-rotate: ;
    --tw-backdrop-invert: ;
    --tw-backdrop-opacity: ;
    --tw-backdrop-saturate: ;
    --tw-backdrop-sepia: ;
    padding: 0;
}

```

```

    animation-name: fadeInUp;
    font-weight: 400;
    color: #fff;
    margin: 18px 0;
    font-size: 15px;
    line-height: 26px;
    visibility: visible;
    animation-delay: 0.6s;
}

.button-wow
{
    -webkit-text-size-adjust: 100%;
    tab-size: 4;
    --thumb-width: 15;
    line-height: inherit;
    font-family: "Roboto", sans-serif;
    font-weight: normal;
    font-style: normal;
    color: #727272;
    font-size: 15px;
    cursor: auto;
    text-align: center;
    box-sizing: border-box;
    border-width: 0;
    border-style: solid;
    border-color: #e5e7eb;
    --tw-translate-x: 0;
    --tw-translate-y: 0;
    --tw-rotate: 0;
    --tw-skew-x: 0;
    --tw-skew-y: 0;
    --tw-scale-x: 1;
    --tw-scale-y: 1;
    --tw-pan-x: ;
    --tw-pan-y: ;
    --tw-pinch-zoom: ;
    --tw-scroll-snap-strictness: proximity;
    --tw-ordinal: ;
    --tw-slashed-zero: ;
    --tw-numeric-figure: ;
    --tw-numeric-spacing: ;
    --tw-numeric-fraction: ;
    --tw-ring-inset: ;
    --tw-ring-offset-width: 0px;
    --tw-ring-offset-color: #fff;
    --tw-ring-color: rgba(71, 197, 247, 0.788);
    --tw-ring-offset-shadow: 0 0 #0000;
    --tw-ring-shadow: 0 0 #0000;
    --tw-shadow: 0 0 #0000;
    --tw-shadow-colored: 0 0 #0000;
    --tw-blur: ;
    --tw-brightness: ;
    --tw-contrast: ;
    --tw-grayscale: ;
    --tw-hue-rotate: ;
    --tw-invert: ;
    --tw-saturate: ;

```



```

--tw-sepia: ;
--tw-drop-shadow: ;
--tw-backdrop-blur: ;
--tw-backdrop-brightness: ;
--tw-backdrop-contrast: ;
--tw-backdrop-grayscale: ;
--tw-backdrop-hue-rotate: ;
--tw-backdrop-invert: ;
--tw-backdrop-opacity: ;
--tw-backdrop-saturate: ;
--tw-backdrop-sepia: ;
margin: 0;
padding: 0;
animation-name: fadeInUp;
margin-left: 0 !important;
margin-top: 10px !important;
width: 100%;
visibility: visible;
animation-delay: 0.8s;
}

.btn
{
  -webkit-text-size-adjust: 100%;
  tab-size: 4;
  --thumb-width: 15;
  line-height: inherit;
  font-family: "Roboto", sans-serif;
  font-style: normal;
  text-align: center;
  visibility: visible;
  box-sizing: border-box;
  --tw-translate-x: 0;
  --tw-translate-y: 0;
  --tw-rotate: 0;
  --tw-skew-x: 0;
  --tw-skew-y: 0;
  --tw-scale-x: 1;
  --tw-scale-y: 1;
  --tw-pan-x: ;
  --tw-pan-y: ;
  --tw-pinch-zoom: ;
  --tw-scroll-snap-strictness: proximity;
  --tw-ordinal: ;
  --tw-slashed-zero: ;
  --tw-numeric-figure: ;
  --tw-numeric-spacing: ;
  --tw-numeric-fraction: ;
  --tw-ring-inset: ;
  --tw-ring-offset-width: 0px;
  --tw-ring-offset-color: #fff;
  --tw-ring-color: rgba(71, 197, 247, 0.788);
  --tw-ring-offset-shadow: 0 0 #0000;
  --tw-ring-shadow: 0 0 #0000;
  --tw-shadow: 0 0 #0000;
  --tw-shadow-colored: 0 0 #0000;
  --tw-blur: ;
  --tw-brightness: ;

```

```

--tw-contrast: ;
--tw-grayscale: ;
--tw-hue-rotate: ;
--tw-invert: ;
--tw-saturate: ;
--tw-sepia: ;
--tw-drop-shadow: ;
--tw-backdrop-blur: ;
--tw-backdrop-brightness: ;
--tw-backdrop-contrast: ;
--tw-backdrop-grayscale: ;
--tw-backdrop-hue-rotate: ;
--tw-backdrop-invert: ;
--tw-backdrop-opacity: ;
--tw-backdrop-saturate: ;
--tw-backdrop-sepia: ;
text-decoration: none;
display: inline-block;
text-transform: capitalize;
border: none;
transition: all 0.3s ease;
border-radius: 4px;
position: relative;
z-index: 1;
overflow: hidden;
box-shadow: 0px 4px 7px #00000021;
padding: 14px 25px;
font-size: 14px;
font-weight: 500;
margin: 0;
background-color: #27b5f7;
color: #fff;
}

```

//End of Code written without Assistance for this code extract

Nav.css

```

//Start of Code written without Assistance for this code extract
.promo-bar{
  text-shadow: 1px 1px 1px rgba(0,0,0,.004);
  line-height: 1.5em;
  cursor: auto;
  box-sizing: border-box;
  font-family: var(--font--accent--family);
  font-weight: var(--font--accent--weight);
  font-style: var(--font--accent--style);
  letter-spacing: 1px;
  font-size: 13px;
  min-height: 33px;
  width: 100%;
  transition: .3s;
  padding: 7px 10px;
  position: relative;
  overflow: hidden;
  text-align: center;
  text-transform: none;
  color: var(--color--alternative);
  background-color: rgb(247, 247, 247);
}

```

```

.link
{
    text-shadow: 1px 1px 1px rgba(0,0,0,.004);
    line-height: 1.5em;
    font-family: var(--font--accent--family);
    font-weight: var(--font--accent--weight);
    font-style: var(--font--accent--style);
    letter-spacing: 1px;
    font-size: 13px;
    text-align: center;
    text-transform: none;
    box-sizing: border-box;
    text-decoration: none;
    background-color: transparent;
    transition: color .2s ease;
    color: var(--color--alternative);
}

.text
{
    -webkit-text-size-adjust: 100%;
    visibility: inherit;
    --font--section-heading--size: 20px;
    --font--block-heading--size: 16px;
    --font--heading--uppercase: normal;
    --font--paragraph--size: 14px;
    --font--heading--family: Futura, sans-serif;
    --font--heading--weight: 400;
    --font--heading--normal-weight: 400;
    --font--heading--style: normal;
    --font--accent--family: Futura, sans-serif;
    --font--accent--weight: 400;
    --font--accent--style: normal;
    --font--paragraph--family: Futura, sans-serif;
    --font--paragraph--weight: 400;
    --font--paragraph--style: normal;
    --font--bolder-paragraph--weight: 700;
    --image--loading-animation:
url('//www.ginleestudio.com/cdn/shop/t/17/assets/AjaxLoader.gif?v=66431031005733996371611037752');
    --image--grabbing-icon:
url('//www.ginleestudio.com/cdn/shop/t/17/assets/grabbing.png?v=162995541551579154171611037755');
    --image--popup:
url('//www.ginleestudio.com/cdn/shop/files/GINLEE7858_362a022f-0e1b-4252-bc7a-fe71e48a3b61_1200x.jpg?v=1706273686');
    --color--accent: #f2efeb;
    --color-text: #212121;
    --color-page-bg: #ffffff;
    --color-panel-bg: #ffffff;
    --color-border: #ebebeb;
    --color-error: #f66767;
    --color-button: #ffffff;
    --color-button-bg: #cacaca;
    --color--body--light: #6e6e6e;
    --color--alternative: #000000;
    --color-header: #ffffff;

```

```

--color-header-bg: #c0c0c0;
--color-menubar: #ffffff;
--color-cart: #ffffff;
--color-footer: #fefefe;
--color-footer-bg: #c0c0c0;
--color-slider-caption: #272727;
--color-slider-caption-bg: #ffffff;
--color-slider-button: #f7f7f7;
--color-slider-button-bg: #313131;
--color-slider-button-hover-bg: #444444;
--color-slider-nav: #444444;
--color-product-slider-bg: #ffffff;
--color-featured-promo-bg: #f7f7f7;
--color-social-feed-bg: #ffffff;
--color-grid-sale: #ffffff;
--color-grid-sale-bg: #313131;
--color-grid-sold-out: #ffffff;
--color-grid-sold-out-bg: #cccccc;
--color-tabs-accordions: #ebebcb;
--swym-remind-cta-bg-color: #00a65a;
--swym-remind-cta-text-color: white;
--swym-remind-cta-bg-color-v2: #000000;
--swym-remind-cta-text-color-v2: white;
--swym-subscribe-success-bg-color: #AEE9D1;
--swym-subscribe-success-text-color: #202223;
--swym-recently-viewed-pointer-pos: 92%;
--thumb-width: 15;
-webkit-font-smoothing: antialiased;
text-shadow: 1px 1px 1px rgba(0,0,0,.004);
line-height: 1.5em;
font-family: var(--font--accent--family);
font-weight: var(--font--accent--weight);
font-style: var(--font--accent--style);
letter-spacing: 1px;
font-size: 13px;
text-align: center;
text-transform: none;
color: var(--color--alternative);
box-sizing: border-box;
padding: 3px 28px 0;
display: block;
}

.close
{
    -webkit-text-size-adjust: 100%;
    visibility: inherit;
    --font--section-heading--size: 20px;
    --font--block-heading--size: 16px;
    --font--heading--uppercase: normal;
    --font--paragraph--size: 14px;
    --font--heading--family: Futura, sans-serif;
    --font--heading--weight: 400;
    --font--heading--normal-weight: 400;
    --font--heading--style: normal;
    --font--accent--family: Futura, sans-serif;
    --font--accent--weight: 400;
    --font--accent--style: normal;

```

```
--font--paragraph--family: Futura, sans-serif;
--font--paragraph--weight: 400;
--font--paragraph--style: normal;
--font--bolder-paragraph--weight: 700;
--image--loading-animation:
url('//www.ginleestudio.com/cdn/shop/t/17/assets/AjaxLoader.gif?v=664
31031005733996371611037752');
--image--grabbing-icon:
url('//www.ginleestudio.com/cdn/shop/t/17/assets/grabbing.png?v=16299
5541551579154171611037755');
--image--popup:
url('//www.ginleestudio.com/cdn/shop/files/GINLEE7858_362a022f-0e1b-
4252-bc7a-fe71e48a3b61_1200x.jpg?v=1706273686');
--color--accent: #f2efeb;
--color-text: #212121;
--color-page-bg: #ffffff;
--color-panel-bg: #ffffff;
--color-border: #ebebeb;
--color-error: #f66767;
--color-button: #ffffff;
--color-button-bg: #cacaca;
--color--body--light: #6e6e6e;
--color--alternative: #000000;
--color-header: #ffffff;
--color-header-bg: #c0c0c0;
--color-menubar: #ffffff;
--color-cart: #ffffff;
--color-footer: #fefefe;
--color-footer-bg: #c0c0c0;
--color-slider-caption: #272727;
--color-slider-caption-bg: #ffffff;
--color-slider-button: #f7f7f7;
--color-slider-button-bg: #313131;
--color-slider-button-hover-bg: #444444;
--color-slider-nav: #444444;
--color-product-slider-bg: #ffffff;
--color-featured-promo-bg: #f7f7f7;
--color-social-feed-bg: #ffffff;
--color-grid-sale: #ffffff;
--color-grid-sale-bg: #313131;
--color-grid-sold-out: #ffffff;
--color-grid-sold-out-bg: #cccccc;
--color-tabs-accordions: #ebebeb;
--swym-remind-cta-bg-color: #00a65a;
--swym-remind-cta-text-color: white;
--swym-remind-cta-bg-color-v2: #000000;
--swym-remind-cta-text-color-v2: white;
--swym-subscribe-success-bg-color: #AEE9D1;
--swym-subscribe-success-text-color: #202223;
--swym-recently-viewed-pointer-pos: 92%;
--thumb-width: 15;
-webkit-font-smoothing: antialiased;
text-shadow: 1px 1px 1px rgba(0,0,0,.004);
line-height: 1.5em;
font-family: var(--font--accent--family);
font-weight: var(--font--accent--weight);
font-style: var(--font--accent--style);
letter-spacing: 1px;
```

```

    font-size: 13px;
    text-align: center;
    text-transform: none;
    box-sizing: border-box;
    cursor: pointer;
    border: none;
    margin: 0;
    padding: 0;
    position: absolute;
    right: 10px;
    top: 50%;
    transform: translateY(-50%);
    color: var(--color--alternative);
}

body {
    margin: 0;
    padding: 0;
    font-family: Arial, sans-serif;
}

.navbar {
    background-color: #c65b74;
    height: 60px;
    display: flex;
    justify-content: center;
    align-items: center;
    box-shadow: 0 2px 4px rgba(0, 0, 0, 0.1);
}

.navbar a {
    color: whitesmoke;
    text-decoration: none;
    font-size: 18px;
    margin: 0 10px;
    padding: 10px;
    transition: all 0.3s ease;
}

.navbar a:hover {
    background-color: pink;
}

.navbar a.active {
    background-color: #333;
    color: #fff;
}

.search-container {
    position: absolute;
    top: 11.5%;
    right: 0;
    transform: translateY(-50%);
    padding: 0 10px;
    display: flex;
    align-items: center;
    justify-content: center;
    height: 20%;

```

```

    cursor: pointer;
}

.search-container img {
    width: 20px;
    height: 20px;
    fill: white;
}

.search-container:hover img {
    fill: black;
}

:root {
    cursor: url("scripts/cute-kuromi-and-my-melody-cursor.png"),
    default;
}

a:hover,
button:hover,
input[type="submit"]:hover,
input[type="button"]:hover {
    cursor: url('scripts/cute-kuromi-and-my-melody-pointer.png'),
    pointer;
}
//End of Code written without Assistance for this code extract

```

Register.css

```

//Start of Code written without Assistance for this code extract
.mh-wrapper {
    word-wrap: break-word;
    cursor: auto;
    margin: 0;
    border: 0;
    font: inherit;
    display: block;
    background: none;
    padding: 0px;
    color: #fff;
}

.mh-content {
    word-wrap: break-word;
    cursor: auto;
    color: #fff;
    font: inherit;
    vertical-align: baseline;
    overflow: hidden;
    background: rgba(255, 255, 255, 0.33);
    border-radius: 16px;
    box-shadow: 0 4px 30px rgba(0, 0, 0, 0.1);
    backdrop-filter: blur(5.7px);
    border: 2px solid rgba(255, 255, 255, 0.8);
    padding: 25px;
    float: none;
    width: 80%;
    margin: 20px auto;
}

```

```
.post {
  word-wrap: break-word;
  cursor: auto;
  color: #fff;
  margin: 0;
  padding: 0;
  border: 0;
  font: inherit;
  display: block;
}

.entry-header {
  word-wrap: break-word;
  cursor: auto;
  color: #fff;
  margin: 0;
  padding: 0;
  border: 0;
  font: inherit;
  display: block;
  margin-bottom: 1.25rem;
}

.entry-title {
  word-wrap: break-word;
  cursor: auto;
  margin: 0;
  padding: 0;
  border: 0;
  font: inherit;
  vertical-align: baseline;
  font-weight: 700;
  font-family: "Viking", "Open Sans", Helvetica, sans-serif;
  text-shadow: 3px 3px 10px black;
  line-height: 1.5;
  color: #fff !important;
  font-size: 1.5rem;
}

.entry-meta {
  word-wrap: break-word;
  cursor: auto;
  margin: 0;
  border: 0;
  font: inherit;
  vertical-align: baseline;
  font-size: 0.8125rem;
  margin-top: 0.625rem;
  border-top: 1px dotted #ebebeb;
  border-bottom: 1px dotted #ebebeb;
  padding: 5px 0;
  color: #fff;
}

.entry-meta-date {
  word-wrap: break-word;
  cursor: auto;
```



```
color: #fff;
margin: 0;
padding: 0;
border: 0;
font: inherit;
vertical-align: baseline;
margin-right: 10px;
}

.entry-content {
word-wrap: break-word;
cursor: auto;
color: #fff;
margin: 0;
padding: 0;
border: 0;
font: inherit;
counter-reset: footnotes;
display: block;
}

.entry-thumbnail {
display: block;
max-width: 100%;
height: auto;
margin: 0 auto;
text-align: center;
border: 2px white;
}

.entry-thumbnail img {
max-width: 70%;
height: auto;
border: 2px white;
}

p {
word-wrap: break-word;
cursor: auto;
margin: 0;
padding: 0;
border: 0;
font: inherit;
vertical-align: baseline;
margin-bottom: 1.25rem;
color: #fff;
}

body {
background-image: url(/assets/background.png);
background-repeat: no-repeat;
background-size: cover;
}

form {
word-wrap: break-word;
cursor: auto;
color: #fff;
```

```

margin: 0;
padding: 25px;
border: 2px solid rgba(255, 255, 255, 0.8);
font: inherit;
vertical-align: baseline;
background: rgba(255, 255, 255, 0.33);
border-radius: 16px;
box-shadow: 0 4px 30px rgba(0, 0, 0, 0.1);
backdrop-filter: blur(5.7px);
}

form label {
  display: block;
  margin-bottom: 0.5rem;
  font-weight: bold;
  text-shadow: 3px 3px 10px black;
}

form input, form textarea {
  display: block;
  width: 100%;
  padding: 0.5rem;
  border: 1px solid rgba(255, 255, 255, 0.8);
  border-radius: 4px;
  background-color: rgba(255, 255, 255, 0.5);
  color: #333;
  margin-bottom: 1rem;
}

form button {
  display: block;
  width: 100%;
  padding: 0.5rem;
  border: none;
  border-radius: 4px;
  background-color: #007bff;
  color: #fff;
  font-weight: bold;
  cursor: pointer;
  transition: background-color 0.3s ease;
}

form button:hover {
  background-color: #0056b3;
}

.Delete-Account {
  background-color: #ff0000; /* Red color */
  border: none;
  color: white;
  padding: 8px 16px; /* Smaller padding */
  text-align: center;
  text-decoration: none;
  display: inline-block;
  font-size: 14px; /* Smaller font size */
  margin: 4px 2px; /* Smaller margin */
  cursor: pointer;
  border-radius: 4px; /* Slightly rounded corners */
}

```

```

.Delete-Account a {
  color: white;
  text-decoration: none;
}

.warning {
  font-size: 14px; /* Adjust the font size as needed */
  font-weight: bold; /* Make the text bold */
  color: #ff0000; /* Set the text color to red */
  background-color: #f8f8f8; /* Set a light background color */
  padding: 10px 15px; /* Add some padding around the text */
  border: 1px solid #e0e0e0; /* Add a light border */
  border-radius: 4px; /* Add some rounded corners */
  margin-top: 10px; /* Add some space above the message */
}

.return {
  display: inline-block;
  background-color: #007bff;
  color: #fff;
  border: none;
  border-radius: 4px;
  padding: 0.5rem 1rem;
  text-decoration: none;
  font-size: 1rem;
  font-weight: bold;
  cursor: pointer;
  transition: background-color 0.3s ease;
}

.return:hover {
  background-color: #0056b3;
}

.return a {
  color: #fff;
  text-decoration: none;
}

/* Style for the header title container */
.header-title-container {
  background-color: rgba(255, 255, 255, 0.7); /* Translucent white
background */
  padding: 20px; /* Padding around the container */
  border-radius: 12px; /* Rounded corners */
  text-align: left; /* Align the title to the left */
  margin: 20px auto; /* Center the container horizontally */
  width: fit-content; /* Adjust width to fit the content */
}

/* Style for the header title */
.header-title {
  font-family: "Open Sans", Helvetica, Arial, sans-serif; /* Match
the font style */
  font-size: 2rem; /* Adjust size for prominence */
  font-weight: 700; /* Bold font for emphasis */
  color: #333333; /* Dark gray color for contrast */
}

```

```

    text-shadow: 2px 2px 10px rgba(0, 0, 0, 0.5); /* Subtle shadow for
depth */
}

.button {
    background-color: #6cc070;
    color: white;
    padding: 14px 28px;
    font-size: 18px;
    font-weight: bold;
    border: none;
    border-radius: 20px;
    box-shadow: 0 4px 8px rgba(0, 0, 0, 0.2);
    cursor: pointer;
    transition: background-color 0.3s, box-shadow 0.3s;
}

.button:hover {
    background-color: #54b558;
    box-shadow: 0 8px 16px rgba(0, 0, 0, 0.2);
}

.login-prompt {
    font-size: 16px;
    color: #333;
    margin-top: 20px;
    text-align: left;
}

.login-prompt a {
    color: #ff6347;
    text-decoration: underline;
    transition: color 0.3s ease;
}

.login-prompt a:hover {
    color: #e04c31;
    text-decoration: none;
}

.error-message {
    color: #ff0000;
    font-weight: bold;
    font-size: 14px;
    margin-top: 5px;
}

//End of Code written without Assistance for this code extract

```

Settings.css

```

//Start of Code written without Assistance for this code extract
body {
    font-family: Arial, sans-serif;
    background-image: url(/assets/background.jpg);
}

.container {
    max-width: 600px;
}

```

```
    margin: 40px auto;
    padding: 20px;
    background-color: #fff;
    border: 1px solid #ddd;
    border-radius: 10px;
    box-shadow: 0 0 10px rgba(0, 0, 0, 0.1);
}

h1 {
    color: #333;
    margin-top: 0;
}

label {
    display: block;
    margin-bottom: 10px;
}

input[type="text"] {
    width: 80%;
    padding: 10px;
    margin-bottom: 20px;
    border: 1px solid #ccc;
    border-radius: 5px;
}

button[type="submit"] {
    background-color: #4CAF50;
    color: #fff;
    padding: 10px 20px;
    border: none;
    border-radius: 5px;
    cursor: pointer;
}

button[type="submit"]:hover {
    background-color: #3e8e41;
}

.back-button {
    background-color: #4CAF50;
    color: #fff;
    padding: 10px 20px;
    border: none;
    border-radius: 5px;
    cursor: pointer;
    margin-top: 20px;
}

.back-button:hover {
    background-color: #3e8e41;
}

.back-button a
{
    text-decoration: none;
}
```

//End of Code written without Assistance for this code extract

Style.css

```
//Start of Code written without Assistance for this code extract
.site-footer
{
font-family: "Poppins", "Open Sans", system-ui, -apple-system, "Segoe
UI", Roboto, "Helvetica Neue", Arial, "Noto Sans", "Liberation Sans",
sans-serif, "Apple Color Emoji", "Segoe UI Emoji", "Segoe UI Symbol",
"Noto Color Emoji";
font-size: 1rem;
font-weight: 400;
line-height: 1.5;
-webkit-text-size-adjust: 100%;
-webkit-tap-highlight-color: rgba(52,58,64,0);
cursor: auto;
box-sizing: border-box;
padding: 1rem 0;
color: #fff;
text-align: center;
background: #17173e;
z-index: 10;
flex-shrink: 0;
}

h1
{
    cursor: auto;
    color: #fff;
    text-align: center;
    box-sizing: border-box;
    margin-top: 0;
    margin-bottom: .5rem;
    font-family: "Poppins", "Open Sans", system-ui, -apple-system,
"Segoe UI", Roboto, "Helvetica Neue", Arial, "Noto Sans", "Liberation
Sans", sans-serif, "Apple Color Emoji", "Segoe UI Emoji", "Segoe UI
Symbol", "Noto Color Emoji";
    font-weight: 700;
    line-height: 1.2;
    font-size: calc(1.375rem + 1.5vw);
}

.mb-0
{
    cursor: auto;
    color: #fff;
    text-align: center;
    box-sizing: border-box;
    margin-top: 0;
    margin-bottom: 0;
}

.social-links
{
    font-family: var(--bs-font-sans-serif);
    font-size: 1rem;
    font-weight: 400;
    line-height: 1.5;
    -webkit-text-size-adjust: 100%;
```

```
-webkit-tap-highlight-color: rgba(52,58,64,0);
cursor: auto;
color: #fff;
text-align: center;
box-sizing: border-box;
margin-bottom: .5rem;
}
//End of Code written without Assistance for this code extract
```

User-nav.css

```
//Start of Code written without Assistance for this code extract

* {
  margin: 0;
  padding: 0;
  box-sizing: border-box;
}

/* Body styles */
body {
  font-family: Arial, sans-serif;
  background-color: #f7e9f6;
}

/* Header styles */
header {
  background-color: #ffddel;
  padding: 10px;
}

/* Navigation styles */
nav ul {
  list-style-type: none;
  text-align: center;
}

nav ul li {
  display: inline-block;
  margin: 10px;
}

nav ul li a {
  text-decoration: none;
  color: #61185f;
  font-weight: bold;
  font-size: 18px;
  padding: 5px 10px;
  border-radius: 20px;
  background-color: #ffe5ea;
}

nav ul li a:hover {
  background-color: #ffced6;
}
//End of Code written without Assistance for this code extract
```

View-Post.css

```
//Start of Code written without Assistance for this code extract
```

```
body {
  font-family: Arial, sans-serif;
  background-color: #f4f4f4;
  color: #333;
  margin: 0;
  padding: 0;
}

/* Post Container */
.post-container {
  max-width: 800px;
  margin: 50px auto;
  padding: 20px;
  background-color: #fff;
  box-shadow: 0 4px 8px rgba(0,0,0,0.1);
  border-radius: 8px;
}

/* Post Title */
.post-title {
  font-size: 2.5em;
  color: #333;
  margin-bottom: 10px;
  text-align: center;
}

/* Post Subtitle */
.post-subtitle {
  font-size: 1.5em;
  color: #666;
  margin-bottom: 20px;
  text-align: center;
}

/* Post Content */
.post-content {
  font-size: 1.2em;
  line-height: 1.6;
  margin-bottom: 20px;
  color: #444;
}

/* Post Stats */
.post-stats {
  display: flex;
  justify-content: space-around;
  margin: 20px 0;
}

.post-stats p {
  font-size: 1.2em;
  color: #666;
}

/* Like and Dislike Forms */
form {
  display: inline-block;
```



```
margin-right: 10px;
}

form button {
  background-color: #007bff;
  color: white;
  border: none;
  padding: 10px 20px;
  font-size: 1em;
  border-radius: 5px;
  cursor: pointer;
  transition: background-color 0.3s ease;
}

form button:hover {
  background-color: #0056b3;
}

/* Comments Container */
.comments-container {
  max-width: 800px;
  margin: 20px auto;
  background-color: #fff;
  padding: 20px;
  border-radius: 8px;
  box-shadow: 0 4px 8px rgba(0,0,0,0.1);
}

.comments-container h2 {
  margin-bottom: 20px;
  color: #333;
  text-align: center;
}

.comments-list {
  list-style-type: none;
  padding: 0;
}

.comment-item {
  padding: 10px;
  border-bottom: 1px solid #ddd;
}

.comment-item:last-child {
  border-bottom: none;
}

.comment-date {
  font-size: 0.9em;
  color: #999;
}

.comment-text {
  font-size: 1.1em;
  color: #444;
  margin-bottom: 10px;
}
```

```
/* Comment Form */
.comment-form {
  display: flex;
  flex-direction: column;
  margin-top: 20px;
  max-width: 800px;
  margin: 20px auto;
}

.comment-form input[type="text"] {
  padding: 10px;
  margin-bottom: 10px;
  border-radius: 5px;
  border: 1px solid #ddd;
  font-size: 1em;
}

.comment-form button {
  align-self: flex-end;
  background-color: #28a745;
  color: white;
  border: none;
  padding: 10px 20px;
  font-size: 1em;
  border-radius: 5px;
  cursor: pointer;
  transition: background-color 0.3s ease;
}

.comment-form button:hover {
  background-color: #218838;
}

/* Return Button */
.return {
  display: block;
  text-align: center;
  margin: 20px auto;
  background-color: #17a2b8;
  color: white;
  border: none;
  padding: 10px 20px;
  font-size: 1em;
  border-radius: 5px;
  cursor: pointer;
  transition: background-color 0.3s ease;
}

.return a {
  color: white;
  text-decoration: none;
}

.return:hover {
  background-color: #138496;
}
```

```

.return a:hover {
    color: white;
}

/* Responsive Design */
@media (max-width: 768px) {
    .post-container, .comments-container, .comment-form {
        margin: 20px;
        padding: 15px;
    }

    .post-title {
        font-size: 2em;
    }

    .post-subtitle {
        font-size: 1.3em;
    }

    .post-content {
        font-size: 1em;
    }

    .post-stats p {
        font-size: 1em;
    }

    form button, .comment-form button, .return {
        font-size: 0.9em;
        padding: 8px 15px;
    }

    .comment-form input[type="text"] {
        font-size: 0.9em;
    }
}
//End of Code written without Assistance for this code extract

```

Author-Nav.ejs

```

<!DOCTYPE html>
<html>
<head>
    <link rel="stylesheet" type="text/css" href="/css/user-nav.css">
</head>
<body>
    <header>
        <nav>
            <ul>
                <li><a href="/author/author-settings">Settings</a></li>
                <li><a href="/author/create-post">Create Posts</a></li>
                <li><a href="/author/author-home">Home</a></li>
                <li><a href="/Dashboard">Dashboard</a></li>
                <li><a href="/common/user-profile">Profile</a></li>
                <li><a href="/common/logout">Logout</a></li>
            </ul>
        </nav>
    </header>

```

```
</header>
</body>
</html>
```

Footer.ejs

```
<html>
<meta charset="UTF-8">
<meta name="viewport" content="width=device-width, initial-scale=1">
<head>
<link rel="stylesheet" href="/css/style.css">
</head>
<footer class="site-footer"><h1>Check out below!</h1><p class="mb-0"></p><div
class="social-links">
</a></div><p>Created by a student of UOL Computer Science. Copyright all belongs to me @
2024.</p>
</footer>
</html>
```

Header.ejs

```
<html>
<head>
<link rel="stylesheet" href="/css/nav.css">
</head>
<div class="navbar">

  <a href="/DashBoard" class="active">Home</a>
  <a href="/about">About Me</a>
  <a href="/author/author-home"> Author Home</a>
  <a href="/common/user-profile">Profile</a>
  <a href="/common/logout">Log Out</a>
</div>
</html>
```

Metadata.ejs

```
<meta charset="utf-8">
<meta name="viewport" content="width=device-width, initial-scale=1">
```

About.ejs

```
<html>
<head>
<link rel="stylesheet" href="/css/about.css">
<title> <%= title %> </title>
<%- include('./partials/header'); %>
</head>
<body>
<div id="content" class="page-wrap">
  <div class="content-wrapper">
    <div class="row">
      <div id="primary" class="fp-content-area">
        <main id="main" class="site-main" role="main">
```

```

    <div class="text-container">
<div class="entry-content">

<h1 class="wp-block-heading"><strong>About me (Developer of CuteBlog)</strong></h1>

<p class="text">Welcome to CuteBlog! This is the place where users can connect and share
posts about everything, anything they desire!</p>

<p class="text">I am currently a student in SIM-UOL studying Computer Science Degree and
this is my mid-terms application coursework for the module CM2040.</p>

<p class="text">This is my take of the Mini Blogging tool mid-terms. The slogan is "Where
cuteness meets Blogging."</p>



<p class="text" style="text-align: center;">CuteBlog is currently in early stages of
development.</p>

<div style="height:100px" aria-hidden="true" class="wp-block-spacer"></div>

    </div>
  </main>
</div>
</div>
</div>
</div>
</div>
</div>
</body>
<%- include('./partials/footer'); %>
</html>

```

AccessDenied.ejs

```

<!-- access-denied.ejs -->
<!DOCTYPE html>
<html>
<head>
  <title>Access Denied</title>
  <link rel="stylesheet" href="/css/AccessDenied.css">
  <%- include('./partials/header'); %>
</head>
<body>
  <div class="container">
    <div class="content">
      <h1>Access Denied</h1>
      <p>Oops! It seems like you don't have permission to access this page.</p>

```

```

    
    <br>
    <br>
    <button class="Return"><a href="/Dashboard">Return to Home Page</a></button>
  </div>
</div>
</body>
</html>

```

Author-Home.ejs

```

//Start of Code written without Assistance for this code extract
<!DOCTYPE html>
<html>
<head>
  <title><%= title %></title>
  <link rel="stylesheet" type="text/css" href="/css/Author-home.css">
  <%= include('./partials/author-nav'); %>
  <%= include('./partials/metadata'); %>
</head>
<body>
<nav aria-label="Breadcrumb">
  <ol class="breadcrumb">
    <li>
      Author Home Page
    </li>
  </ol>
</nav>
<div class="author-page">
  <h1><%= settings.title %></h1>
  <h2 class="subtitle-settings"><%= settings.subtitle%></h2>
  <h3 class="author-heading">Author: <%= settings.author%></h3>
  <button class="header-buttons"><a href="/author/author-
settings"><strong>Settings</strong></a></button>
  <button class="header-buttons"><a href="/author/create-post"><strong>Create new
draft</strong></a></button>
  <br>
  <br>
  <!-- Published Articles List -->
  <h2><strong>Published Articles</strong></h2>
  <table class="published-articles">
    <thead>
      <tr>
        <th>Title</th>
        <th>Subtitle</th>
        <th>Content</th>
        <th>Likes</th>
        <th>Dislikes</th>
        <th>View Count</th>
        <th>Created At</th>
        <th>Modified At</th>
        <th>Published At</th>
        <th>Share</th>
        <th>Edit</th>

```

```

        <th>History</th>
        <th>Delete</th>
    </tr>
</thead>
<tbody>
    <% if (posts.length === 0 || !posts.some(post => post.status === 'published')) { %>
        <tr>
            <td colspan="11">No published posts to display.</td>
        </tr>
    <% } else { %>
        <% posts.forEach(function(post) { %>
            <% if (post.status === 'published') { %>
                <tr>
                    <td><%= post.title %></td>
                    <td><%= post.subtitle %></td>
                    <td><%= post.content %></td>
                    <td>
                        <button class="like"><%= post.likes %></button>
                    </td>
                    <td>
                        <button class="dislike"><%=
post.dislikes %></button>
                    </td>
                    <td>
                        <%= post.Views %>
                    </td>
                    <td><%=post.createdAt%></td>
                    <td><% if (post.ModifiedAt) { %><%=post.ModifiedAt%><% } %></td>
                    <td>
                        <%= post.publishedAt%>
                    </td>
                    <td>
                        <button class="Share-Button"><a href="#">Share Post</a></button>
                    </td>
                    <td>
                        <form class="edit-post-form" method="POST" action="/author/edit-post">
                            <input type="hidden" name="postid_for" value="<%=post.id%>">
                            <button type="submit" class="Edit-post">
                                
                            </button>
                        </form>
                    </td>
                    <td>
                        <form class="post-history-form" method="POST" action="/author/version-history">
                            <input type="hidden" name="postid_" value="<%= post.id %>">
                            <button><strong>Post History</strong></a></button>
                        </form>
                    </td>
                    <td>
                        <form method="POST" action="/author/delete-publishedpost">
                            <input type="hidden" name="_postid" value="<%= post.id %>">

```

```

        <button class="Delete-post" type="submit">Delete
      </button>
    </form>
  </td>
</tr>
<% } %>
<% }) %>
<% } %>
</tbody>
</table>
<!-- Draft Articles List -->
<h2><strong>Draft Articles</strong></h2>
<table class="draft-articles">
  <thead>
    <tr>
      <th>Title</th>
      <th>Content</th>
      <th>Subtitle</th>
      <th>Likes</th>
      <th>Dislikes</th>
      <th>Created At</th>
      <th>Publish Post</th>
      <th>Delete Post</th>
      <th>View Post</th>
      <th>Edit Post</th>
    </tr>
  </thead>
  <tbody>
    <% if (posts.length === 0 || !posts.some(post => post.status === 'draft')) { %>
      <tr>
        <td colspan="8">No draft posts to display.</td>
      </tr>
    <% } else { %>
      <% posts.forEach(function(post) { %>
        <% if (post.status === 'draft') { %>
          <tr>
            <td><%= post.title %></td>
            <td><%= post.content %></td>
            <td><%= post.subtitle %></td>
            <td>
              <button class="like"><%= post.likes %></button>
            </td>
            <td>
              <button class="dislike"><%=
post.dislikes %></button>
            </td>
            <td><%=post.createdAt%></td>
            <td>
              <form class="Publish" action="/author/publish-post/<%= post.id %>"
method="POST">
                <button class="Publish-post">Publish</button>

```



```

        </form>
      </td>
      <td>
        <form class="delete-form" method="POST" action="/author/delete-post">
          <input type="hidden" name="postid" value="<%= post.id %>">
          <button class="Delete-post" type="submit">Delete</button>
        </form>
      </td>
      <td>
        <button class="View-post"><a href="/author/view-post/<%= post.id %>"
class="links">View Post</a></button>
      </td>
      <td>
        <form class="edit-post-form" method="POST" action="/author/edit-post">
          <input type="hidden" name="postid_for" value="<%=post.id%>">
          <button type="submit" class="Edit-post">
            
          </button>
        </form>
      </td>
    </tr>
    <% } %>
  <% }} %>
<% } %>
</tbody>
</table>
<script>
function showAlert() {
  var button = document.querySelector('.Share-Button');
  var postID = button.dataset.postid;
  var link = "/reader/view-post/" + postID;
  var message = '<a href="' + link + '">Share Post</a>';
  alert(message);
}
</script>
</div>
</body>
</html>
//End of Code written without Assistance for this code extract

```

Author-Settings.ejs

```

//Start of Code written without Assistance for this code extract
<!DOCTYPE html>
<html>
<head>
<%- include('./partials/author-nav'); %>
<%- include('./partials/metadata'); %>
  <title>Settings Page</title>
  <link rel="stylesheet" href="/css/settings.css">
</head>
<body>
  <div class="container">

```

```

        <h1>Settings Page</h1>
        <form id="settings-form" method="POST" action="/author/update-settings">
            <label for="blog-title">Blog Title:</label>
            <input type="text" id="blog-title" name="title"
value="<%=settings.title%>" required>
            <br><br>
            <label for="subtitle">Subtitle:</label>
            <input type="text" id="subtitle" name="subtitle"
value="<%=settings.subtitle%>" required>
            <br><br>
            <label for="author-name">Author Name:</label>
            <input type="text" id="author-name" name="author"
value="<%=settings.author%>" required>
            <br><br>
            <button type="submit">Update Settings</button>
        </form>
        <button class="back-button"><a href="/author/author-home">Back to Author
Home Page</a></button>
    </div>
</body>
</html>
//End of Code written without Assistance for this code extract

```

Confirmation.ejs

```

<!DOCTYPE html>
<html>
<head>
    <link rel="stylesheet" type="text/css" href="/css/confirmation.css" media="screen"/>
    <%- include('./partials/header'); %>
</head>
<body>
    <h1>Confirmation Page</h1>
    <div class="container">
        <h2><%= messages[0] %></h2>
        <% for (var i = 1; i<messages.length; i++){ %>
            <p><%= messages[i] %></p>
        <% } %>
    </div>
</body>
</html>

```

Create-post.ejs

```

<%- include('./partials/author-nav'); %>
<%- include('./partials/metadata'); %>
<!DOCTYPE html>
<html>
<head>
    <title>Create Post</title>
    <link rel="stylesheet"
href="https://stackpath.bootstrapcdn.com/bootstrap/4.5.2/css/bootstrap.min.css">
    <link rel="stylesheet" type="text/css" href="/css/create-post.css">

```

```

</head>
<body>
  <div class="container my-5">
    <h1>Create Post</h1>
    <form action="/author/create-post-process" method="POST" id="create-post-form">
      <div class="form-group">
        <label for="title">Title:</label>
        <input type="text" class="form-control" id="title" name="title" required>
        <div class="invalid-feedback">Please enter a title.</div>
      </div>
      <div class="form-group">
        <label for="subtitle">Subtitle:</label>
        <input type="text" class="form-control" id="subtitle" name="subtitle" required>
        <div class="invalid-feedback">Please enter a subtitle.</div>
      </div>
      <div class="form-group">
        <label for="content">Content:</label>
        <textarea class="form-control" id="content" name="content" rows="5"
required></textarea>
        <div class="invalid-feedback">Please enter the content.</div>
      </div>
      <button type="submit" class="btn btn-primary">Create</button>
    </form>
  </div>

  <script>
    // Enable Bootstrap form validation
    (function() {
      'use strict';
      window.addEventListener('load', function() {
        var forms = document.getElementsByClassName('needs-validation');
        var validation = Array.prototype.filter.call(forms, function(form) {
          form.addEventListener('submit', function(event) {
            if (form.checkValidity() === false) {
              event.preventDefault();
              event.stopPropagation();
            }
            form.classList.add('was-validated');
          }, false);
        }, false);
      })();
    })();
  </script>
</body>
</html>

```

DashBoard.ejs

```

<html>
<head>
  <%- include('./partials/header'); %>
  <%- include('./partials/metadata'); %>
  <link rel="stylesheet" href="/css/home.css">

```

```

</head>
<body>
  <div class="time-container">
    <p>Welcome back, <%= username %>!</p>
  </div>
  <br>
  <div class="blog-information">
    <h1>Blog title: <%=settings.title%></h1>
    <h2>Blog Author:<%=settings.author%></h2>
  </div>
  <div class="blog-container">
    <h2><strong>DashBoard Page</strong></h2>
    <ul class="article-list">
      <% if (posts.length === 0 || !posts.some(post => post.status === 'published')) { %>
        <li>
          <p class="no-posts">No published posts to display.</p>
        </li>
      <% } else { %>
        <% posts.forEach(function(post) { %>
          <% if (post.status === 'published') { %>
            <li>
              <a href="/view-post/<%=post.id%>">
                <p class="title" style="color: black;"><%=post.title%></p>
              </a>
              <p class="subtitle"><%= post.subtitle %></p>
              <br>
              <p class="content"><%= post.content %></p>
              <button class="like"><%= post.likes %></button>
              <button class="dislike"><%=
post.dislikes %></button>
              <button class="dislike"><%=
post.Views %></button>
              <p class="Time-Created">Published at <%= post.publishedAt%></p>
            </li>
          <% } %>
        <% }) %>
      <% } %>
    </ul>
  </div>
  <a href="javascript:void(0)" class="back-to-top">
    <span class="border-white"></span>
  </a>
</body>
<footer>
  <%- include('./partials/footer'); %>
</footer>
</html>

```

Edit-Post.ejs

```

<!-- Add your desired HTML structure and EJS tags here -->
<html>
<head>

```

```

<link rel="stylesheet" type="text/css" href="/css/edit-post.css" media="screen"/>
</head>
<h1>Edit Blog Post</h1>
<form action="/author/update-post" method="POST">
  <label for="CreatedAt">Post Created at:</label>
  <input type="text" name="created-at-time" value="<%= post.createdAt%>" readonly>
  <label for="CreatedAt">Post Modified at:</label>
  <input type="text" name="created-at-time" value="<%= post.ModifiedAt%>" readonly>
  <label for="PostId">PostId</label>
  <input type="text" name="postId" value="<%= post.id %>" readonly>
  <label for="title">Title</label>
  <input type="text" name="title" value="<%= post.title %>">

  <label for="subtitle">Subtitle</label>
  <input type="text" name="subtitle" value="<%= post.subtitle %>">

  <label for="content">Content</label>
  <textarea name="content"><%= post.content %></textarea>

  <button class="back-button"><a href="/author/author-home">Back to Author Home
Page</a></button>
  <button type="submit">Save Changes</button>
</form>
</html>

```

Login.ejs

```

<html>

<head>
<title> <%= title %> </title>
<link rel="stylesheet" href="/css/login.css">
</head>
<body>
<h1>Login Page</h1>
<section class="login-page">
  <div class="section-header">
    <h2>Login to Cute Blog Here!</h2>
    <p><strong>The place where cuteness meets Blogging!</strong></p>
  </div>
  <div class="section-body">
    <div class="image-container">
      
    </div>
    <form method="POST" id="username-form" action="/login-process">
      <div class="login-recovery"><strong>Username/Email</strong></div>
      <input class="textbox" type="text" name="input" value="" id="input" size="30"
placeholder="Username/Email">
      <div class="login-recovery"><strong>Password</strong></div><input class="textbox"
type="password" name="password" size="30" placeholder = "Password here
(e.g.password123)" id="password">
      <br>
    </form>
  </div>
</section>
</body>
</html>

```

```

        <div class="alignleft">
            <input type="submit" class="button" name="login" id="login-button"
value="Login">
            <p>New to CuteBlog? Register <a href="/register" style="text-decoration: none; color:
#ff6347;">here</a>!!</p>
        </div>
    </form>
</div>

</section>
</form>
</body>
<br>
<br>
<br>
<footer>
<%- include('./partials/footer'); %>
</footer>
</html>

```

Mainpage.ejs

```

<html>
<head>
    <link rel="stylesheet" href="/css/main.css">
</head>
<body>
    <section class="hero-area">
        <div class="container">
            <div class="row">
                <div class="col-lg-6 offset-lg-3 col-md-12 col-12">
                    <div class="hero-content">
                        <h5 class="wow-animated" data-wow-delay=".2s" style="visibility: visible;
animation-delay: 0.2s;">Main Landing Page</h5>
                        <h2 class="wow-h2" data-wow-delay=".4s" style="visibility: visible; animation-
delay: 0.4s;">Welcome to the world of CuteBlog!</h2>
                        <p class="wow" data-wow-delay=".6s" style="visibility: visible; animation-delay:
0.6s;">&nbsp;&nbsp;&nbsp;Choose where you would like to head to by pressing the buttons below!</p>
                        <div class="button-wow" data-wow-delay=".8s"
style="visibility: visible; animation-delay: 0.8s;">
                            <a href="/author/author-home"
class="btn ">Author Home Page</a>
                        </div>
                        <div class="button-wow" data-wow-delay=".8s"
style="visibility: visible; animation-delay: 0.8s;">
                            <a href="/DashBoard" class="btn ">Reader Home
Page</a>
                        </div>
                    </div>
                </div>
            </div>
        </div>
    </section>

```

```

</body>
<footer>
    <%- include('./partials/footer'); %>
</footer>
</html>

```

Register.ejs

```

<html>
<head>
<link rel="stylesheet" href="../css/register.css">
<%- include('./partials/metadata'); %>
</head>
<body>
<section class="login-page">
    <div class="section-header">
        <h2 class="header-title">Account Registration</h2>
    </div>
    <br>
    <div class="section-body">
        <div id="page-register">
            <div id="part-pick-username">
                <form method="post" id="username-form" action="/register-process">
                    <input type="hidden" name="send" value="send">

                    <ol id="errors" class="alignleft error hidden"></ol>
                    <div class="p10b">
                        <div class="inline alignright"
style="width:170px"><strong>Username:</strong></div> <input type="text" class="textbox"
style="width:300px" name="username" id="Username" value="" maxlength="150"
autocomplete="off" fdprocessedid="co5bqp" required>
                    </div>
                    <% if (typeof usernameError !== 'undefined') { %>
                        <p class="error-message" id="username-error"><%= usernameError %></p>
                    <% } %>
                    <div class="p10b">
                        <div class="inline alignright" style="width:170px"><strong>Email:</strong></div>
<input type="text" class="textbox" style="width:300px" name="email" id="Username"
value="" maxlength="150" autocomplete="off" fdprocessedid="co5bqp" required>
                    </div>
                    <div class="p10b">
                        <div class="inline alignright"
style="width:170px"><strong>Password:</strong></div> <input type="password"
class="textbox" style="width:300px" name="password" id="password" value=""
maxlength="150" autocomplete="off" fdprocessedid="jc7hf">
                    <br>
                    <p class="error-message" style="margin-bottom: 10px;"></p>
                    <br>
                    <p class="error-message" id="username-error" style="margin-bottom: 10px;"></p>
                    <br>
                    <p class="error-message" id="Email-Error"></p>
                </form>
            </div>
        </div>
    </div>
</section>

```

```

        </div>
        <br>
        <p class="login-prompt"><bold>Already have an account? Login</bold> <a href =
"/login" style="text-decoration: none; color: #ff6347;">here!</a>
        <div class="alignright">
            <input class="button" type="submit" name="proceed" id="proceed"
value="Proceed with account creation.">
        </div>
    </form>
</div>
</div>
</div>
</div>
</section>

<script>
const passwordInput = document.getElementById("password");
const errorMessage = document.querySelector(".error-message");
const submitButton = document.getElementById("proceed");
const UsernameInput = document.getElementById("Username");
const errorMessage2 = document.getElementById("username-error");

passwordInput.addEventListener("input", () => {
    if (passwordInput.value.length < 8 && passwordInput.value.length > 0 ) {
        errorMessage.textContent = "Password too short. Password must be at least 8
characters.";
        submitButton.disabled = true;
    } else {
        errorMessage.textContent = "";
        submitButton.disabled = false;
    }
});

UsernameInput.addEventListener("input", () => {
    if (UsernameInput.value.length < 5 && UsernameInput.value.length > 0 ) {
        errorMessage2.textContent = "Username must be at least 5 characters.";
        submitButton.disabled = true;
    } else {
        errorMessage2.textContent = "";
        submitButton.disabled = false;
    }
});

</script>
</body>
</html>

```

User-Profile.ejs

```

<html>
<head>

```



```

<link rel="stylesheet" href="/css/back-up.css">
</head>
<div class="mh-wrapper">
  <div id="main-content" class="mh-content" role="main" itemprop="mainContentOfPage">
    <article id="post-7407" class="post">
      <header class="entry-header">
        <h1 class="entry-title">User Settings</h1>
        <p class="mh-meta entry-meta">
          <span class="entry-meta-date"><i class="fa fa-clock-o"></i>Date: <%=
currentDate %></span>
        </p>
      </header>
      <div class="entry-content mh-clearfix">
        <figure class="entry-thumbnail">
          
        </figure>
        <br>
        <br>
        <form>
          <label for="username">Username:</label>
          <input type="text" id="username" name="username" placeholder=" <%=
user.username %>">
          <label for = "email"> Email:</label>
          <input type="text" id="email" name="email"
placeholder="<%= user.email%>">
          <button type="submit">Save Changes</button>
        </form>
        <br>
        <br>
      </div>
      <div class="entry-content mh-clearfix">
        <form method="POST" action="/common/process-delete">
          <p class="warning">Note that Deleting of Account is not reversible.</p>
          <button class="Delete-Account"><a href="/common/process-delete">Delete
Account</a></button>
        </form>
      </div>
      <br>
      <br>
      <button class="return"><a href="/author/author-home">Return</a></button>
    </article>
  </div>
</div>
</html>

```

Version-History.ejs

```

<!DOCTYPE html>
<html>
<head>
  <style>
    body{

```

```
font-family: Arial, sans-serif;
background-color: #f5f5f5;
margin: 0;
padding: 0;
}

.container {
  max-width: 800px;
  margin: 0 auto;
  padding: 20px;
}

h1 {
  text-align: center;
  color: #333;
  margin-bottom: 20px;
}

table {
  width: 100%;
  border-collapse: collapse;
  background-color: white;
  box-shadow: 0 0 20px rgba(0, 0, 0, 0.1);
}

th, td {
  padding: 10px;
  text-align: left;
  border-bottom: 1px solid #ddd;
}

th {
  background-color: #f2f2f2;
}

p {
  text-align: center;
  color: #666;
  margin-top: 20px;
}

.Revert-Version {
background-color: #6495ED; /* Cornflower Blue */
border: none;
color: white;
padding: 8px 16px;
text-align: center;
text-decoration: none;
display: inline-block;
font-size: 14px;
border-radius: 4px;
```

```

    cursor: pointer;
}

.Revert-Version:hover {
    background-color: #4169E1; /* Dark Blue on hover */
}

.Return {
    background-color: #F5F5F5; /* Light gray background */
    color: #333333; /* Dark gray text color */
    border: none; /* No border */
    padding: 12px 24px; /* Moderate padding */
    text-align: center; /* Center the text */
    text-decoration: none; /* No underline */
    display: inline-block; /* Display as an inline block */
    font-size: 16px; /* Medium font size */
    font-family: 'Roboto', sans-serif; /* Use Roboto font */
    border-radius: 4px; /* Slightly rounded corners */
    box-shadow: 0 2px 4px rgba(0, 0, 0, 0.1); /* Subtle drop shadow */
    transition: background-color 0.3s ease, box-shadow 0.3s ease; /* Smooth transitions */
}

.Return:hover {
    background-color: #E0E0E0; /* Slightly darker gray on hover */
    box-shadow: 0 4px 8px rgba(0, 0, 0, 0.15); /* Slightly larger drop shadow on hover */
}

.Return:active {
    background-color: #D0D0D0; /* Even darker gray when clicked */
    box-shadow: 0 1px 2px rgba(0, 0, 0, 0.1); /* Smaller drop shadow when clicked */
}

.Return a
{
    text-decoration: none;
    color: black;
}
</style>
</head>
<body>
    <h1>Post Version History</h1>
    <p>This will only show the last version before the current version.</p>

    <% if (post.PostHistory !== null && post.PostHistory !== "") { %>
        <table>
            <thead>
                <tr>
                    <th>Modifed Date</th>
                    <th>Content</th>
                    <th>Actions</th>
                </tr>
            </thead>
        </table>
    </%>

```

```

</thead>
<tbody>
  <tr>
    <td><%= new Date(post.ModifiedAt).toLocaleString() %></td>
    <td><%= post.PostHistory %></td>
    <td><button class="Revert-Version">Revert</button></td>
  </tr>
</tbody>
</table>
<% } else { %>
  <p>No version history available for this post.</p>
<% } %>
<br>
<br>
<button class="Return"><a href="/author/author-home">Return</a></button>
</body>
</html>

```

View-Post.ejs

```

<!DOCTYPE html>
<html>
<head>
  <title>View Post</title>
  <link rel="stylesheet" type="text/css" href="/css/view-post.css">
  <%- include('./partials/metadata'); %>
</head>
<body>
  <div class="post-container">
    <h4 class="post-id">View Post <%= post.id %></h4>
    <h1 class="post-title"><%= post.title %></h1>
    <h3 class="post-subtitle"><%= post.subtitle %></h3>
    <p class="post-content"><%= post.content %></p>
    <div class="post-stats">
      <p class="post-dislikes">Views: <%= post.Views %></p>
      <p class="post-likes">Likes: <%= post.likes %></p>
      <p class="post-dislikes">Dislikes: <%= post.dislikes %></p>
    </div>
  </div>

  <form action="/like-post" method="POST">
    <input type="hidden" name="postLikeld" value="<%=post.id%>">
    <input type="hidden" name="userid" value="<%= user.id %>">
    <button type="submit">Like</button>
  </form>
  <form action="/dislike-post" method="POST">
    <input type="hidden" name="postdisLikeld" value="<%=post.id%>">
    <input type="hidden" name="userrid" value="<%= user.id %>">
    <button type="submit">Dislike</button>
  </form>

  <div class="comments-container">
    <h2>Comments(<%= commentCount.commentCount %>)</h2>

```

```

<% if (comments.length === 0) { %>
  <p>No comments for this post to display</p>
<% } else { %>
  <ul class="comments-list">
    <% comments.forEach(function(comment) { %>
      <li class="comment-item">
        <p class="comment-date">Commented by <%= comment.comment_user%> </p>
        <p class="comment-text"><%= comment.text %></p>
        <p class="comment-date"> Commented on <%= comment.createdAt %></p>
      </li>
    <% }) %>
  </ul>
<% } %>
</div>

<form action="/add-comments" method="POST" class="comment-form">
  <label for="commenter">Comment As:</label>
  <input type="text" name="commenter" placeholder="<%=username%>">
  <label for="comment">Comment:</label>
  <input type="text" name="comment" placeholder="Write a comment.....">
  <input type="hidden" name="pstad" value="<%=post.id%>">
  <button type="submit">Submit</button>
</form>
<br>
<br>
<button class="return"><a href="/DashBoard">Return</a></button>
</body>
</html>

```

Index.js

```

const express = require('express')
const app = express()
const router = express.Router();
const compression = require('compression');
const { check, validationResult } = require('express-validator');
//inclusion off express-validator module
const port = 3000; //Port used for Connection
const expressSanitizer = require('express-sanitizer'); //inclusion of
express-sanitizer module
const session = require('express-session');
const sqlite3 = require('sqlite3').verbose();
const rateLimit = require('express-rate-limit');
const helmet = require('helmet');
const expiryDate = new Date(Date.now() + 60 * 60 * 1000); //Cookie
Expires after 1 hour of inactivity
app.use(compression()); //greatly decrease the size of the response
body and hence increase the speed of the application.
const ApplicationLimiter = rateLimit({
  windowMs: 15 * 60 * 1000, // 15 minutes
  max: 100,
  message: 'Too many attempts from this IP, please try again after 15
minutes',
  standardHeaders: true, //Return rate limit infomation in the
RateLimit -* headers
  legacyHeaders: false, // Disable the X-RateLimit-* headers

```

```

});
app.use(
  helmet.contentSecurityPolicy({
    directives: {
      defaultSrc: ['self', 'localhost'],
      scriptSrc: ["'self'", "'localhost'", "'unsafe-
inline'", 'https://stackpath.bootstrapcdn.com'],
    },
  })
);
app.use(helmet.frameguard({
  action: 'deny'
}));
app.disable('x-powered-by');
// X-XSS-Protection
app.use(helmet.xssFilter());
// items in the global namespace are accessible through out the node
application
global.db = new sqlite3.Database('./database.db', function (err){
if (err)
{
  console.error(err);
  process.exit(1); //Bail out as we can't connect to the DB
}
else
{
  console.log('Database Connected');
  global.db.run('PRAGMA foreign_keys=ON'); //This tells SQLite to pay
attention to foreign key constraints
}
});
// configure body parser to be able to receive the request body
const bodyParser = require("body-parser");
app.use(bodyParser.urlencoded({ extended: true }));
// set the app to use ejs for rendering
app.set('view engine', 'ejs');
// use static files on the assets,css and Image Folders
const cssdirectory = express.static(__dirname + '/css');
const scriptdirectory = express.static(__dirname + '/scripts');
const ImageDirectory = express.static(__dirname + '/assets');
app.use(expressSanitizer()); //added for sanitisation
// add the reader routes to the app under the path /
const readerRoutes = require('./routes/reader');
app.use('/', readerRoutes);
// add the author routes to the app under the path /author
const authorRoutes = require('./routes/author');
app.use('/author', authorRoutes);
// add the common routes between reader and author under the path
/common
const commonRoutes = require('./routes/common');
app.use('/common', commonRoutes);
//Setting up Express.js to serve static files from three different
directories
app.use('/css/', cssdirectory);
app.use('/scripts/', scriptdirectory);
app.use('/assets/', ImageDirectory);
//add the Rate Limit to the application of CuteBlog
app.use('/author', ApplicationLimiter);

```

```
app.use('/common', ApplicationLimiter);
app.use(session({
  secret: 's3Cur3',
  name: 'sessionId',
  resave: false,
  saveUninitialized: true,
  cookie: {
    expires: expiryDate,
    domain: 'localhost'
  },
  rolling: true
}))
app.listen(port, () => {
  console.log(`CuteBlog Application listening on port ${port}`)
});
```