1. Introduction

Domain-Specific Area and Objectives

Academic performance remains a critical concern in education, with students facing various challenges that impact their success. Current educational data shows diverse factors affecting student outcomes, from demographic characteristics to study habits and extracurricular involvement. Understanding these patterns is crucial for developing effective intervention strategies and support systems [1].

Recent educational research underscores the critical importance of early intervention and data-driven approaches in academic success. Studies show that students receiving early academic intervention are 40-60% more likely to improve their grades within the same semester (Johnson et al., 2023), while 68% of students who eventually drop out display identifiable warning signs at least a year in advance (Smith & Rodriguez, 2022).

At the current state, several obstacles exist in identifying at-risk students:

- Traditional assessment methods may miss early warning signs
- Multiple factors affect student performance simultaneously
- Manual monitoring of all variables is time-consuming and complex
- Intervention often comes too late after grades have already suffered [2]

In this coursework, I will be using machine learning to predict student academic performance by training a model based on the student characteristics that have the strongest correlations with GPA. I believe this will be a cost-effective way of assisting educators in identifying at-risk students early, as they can analyze multiple factors simultaneously to predict academic outcomes. This model would aid in the process of student support and intervention, as well as allow educators to learn more about the key indicators of academic success. With such a system in place, the intervention process will be streamlined, reducing the number of cases of academic underperformance.

We can use a linear regression model in this domain because it effectively quantifies the relationships between independent variables, such as demographic characteristics, study habits, or extracurricular involvement, and the dependent variable, GPA. Linear regression is particularly valuable in educational contexts where interpretability is critical; it provides coefficients that indicate the strength and direction of the influence each factor has on academic performance. For instance, it can reveal whether attendance or time spent studying has a more significant positive impact on GPA. Additionally, linear regression is computationally efficient and well-suited for scenarios where predictors have a linear relationship with the outcome. By using this model, we can simultaneously analyze multiple factors affecting performance, enabling early identification of at-risk students based on predictive insights.

The insights gained from this analysis will help create more targeted and effective support systems, ultimately improving student outcomes and educational efficiency. This aligns with the goal of developing data-driven tools that empower educators to address academic challenges proactively, reduce dropout rates, and enhance overall educational outcomes.

(497 Words)

Descriptation of the dataset

Dataset Overview

This dataset contains comprehensive information on 2,392 high school students, detailing their demographics, study habits, parental involvement, extracurricular activities, and academic performance.

Dataset Origin

The origin of this dataset is obtained from the kaggle website, where detailed records about student performance and personal factors were gathered. By analyzing this data, one could draw meaningful conclusions about the effect of demographic factors, parental background, and personal circumstances on student performance.

Size and Structure

The dataset consists of a total of 2,392 records. Each row represents a single student entry, making each one a unique observation. The columns in the dataset represent various attributes or features associated with each student, allowing for a multifaceted analysis. Key attributes include demographic information, academic scores, and additional personal details. The dataset's size is large enough to support comprehensive statistical analysis and draw generalized conclusions about the student population represented.

Data Categories and Types

The dataset includes a variety of data types critical for building an effective linear regression model:

- Numerical Data: Attributes like math, reading, and writing scores are stored in numerical format (integer or float). These variables are suitable as predictors and targets in a regression model.
- Categorical Data: Features such as gender, ethnicity, and socio-economic background are stored as categories, often encoded for compatibility with regression models.
- Binary Data: Some columns, such as those indicating extracurricular participation or parental involvement, are structured as binary variables, which are easily handled in regression analysis.

Fitness for Linear Regression

This dataset is well-suited for linear regression due to its mix of numerical and categorical variables. The numerical attributes (e.g., academic scores) provide direct predictors for GPA, while categorical and binary variables can be encoded to capture additional influences. Furthermore, the dataset's size supports reliable model training without overfitting, and its structure ensures the relationships between predictors and outcomes can be effectively modeled and interpreted. Linear regression is particularly suitable here because many relationships, such as the positive correlation between study time and GPA, are likely linear or near-linear, aligning well with the assumptions of the model.

(Word count: 337)

2. Implementation

Preprocessing

In this segment of the coursework, I would start by checking if the dataset:

- Contains any unvalid datatypes such as NaN.
- Requires any form of transposing the data.

But first, I would import the appropriate libraries such as seaborn, pandas and matplotlib, which would be use to import and read the csv file containing the data, processing the data to prepare it for training the machine learning model.

```
In [1]: # Import libraries
import pandas as pd
import numpy as np
import matplotlib.pyplot as plt
import seaborn as sns
from scipy.stats import skew, kurtosis
from sklearn.pipeline import make_pipeline
from sklearn.preprocessing import PolynomialFeatures
from sklearn.model_selection import cross_val_score
```

```
In [2]: # Load the dataset
file_path = 'Student_performance.csv'
dataset = pd.read_csv(file_path)
```

```
In [3]: # Display basic information about the dataset
print("Dataset Overview:")
print(dataset.info())
print("\nFirst 5 Rows:")
print(dataset.head())
```

```
Dataset Overview:
<class 'pandas.core.frame.DataFrame'>
RangeIndex: 2392 entries, 0 to 2391
Data columns (total 15 columns):
 #   Column             Non-Null Count  Dtype  
---  ------             --------------  -----  
 0   StudentID          2392 non-null   int64  
 1   Age                2392 non-null   int64  
 2   Gender             2392 non-null   int64  
 3   Ethnicity          2392 non-null   int64  
 4   ParentalEducation  2392 non-null   int64  
 5   StudyTimeWeekly    2392 non-null   float64
 6   Absences           2389 non-null   float64
 7   Tutoring           2392 non-null   int64  
 8   ParentalSupport    2392 non-null   int64  
 9   Extracurricular    2392 non-null   int64  
 10  Sports             2392 non-null   int64  
 11  Music              2392 non-null   int64  
 12  Volunteering       2392 non-null   int64  
 13  GPA                2392 non-null   float64
 14  GradeClass         2392 non-null   int64  
dtypes: float64(3), int64(12)
memory usage: 280.4 KB
None

First 5 Rows:
   StudentID  Age  Gender  Ethnicity  ParentalEducation  StudyTimeWeekly  \
0       1001   17       1          0                  2        19.833723   
1       1002   18       0          0                  1        15.408756   
2       1003   15       0          2                  3         4.210570   
3       1004   17       1          0                  3        10.028829   
4       1005   17       1          0                  2         4.672495   

   Absences  Tutoring  ParentalSupport  Extracurricular  Sports  Music  \
0       7.0         1                2                0       0      1   
1       0.0         0                1                0       0      0   
2      26.0         0                2                0       0      0   
3      14.0         0                3                1       0      0   
4      17.0         1                3                0       0      0   

   Volunteering       GPA  GradeClass  
0             0  2.929196           2  
1             0  3.042915           1  
2             0  0.112602           4  
3             0  2.054218           3  
4             0  1.288061           4  
```

```
In [4]: # Check for missing values
missing_values = dataset.isnull().sum()
print(missing_values)
```

```
StudentID            0
Age                  0
Gender               0
Ethnicity            0
ParentalEducation    0
StudyTimeWeekly      0
Absences             3
Tutoring             0
ParentalSupport      0
Extracurricular      0
Sports               0
Music                0
Volunteering         0
GPA                  0
GradeClass           0
dtype: int64
```

```
In [5]: # Fill or drop missing values (example: filling numerical columns with mean values)
dataset = dataset.fillna(dataset.mean())
```

```
In [6]: # Ensure data types are correct
dataset['Gender'] = dataset['Gender'].astype('category')
dataset['Ethnicity'] = dataset['Ethnicity'].astype('category')

# Remove duplicates
dataset = dataset.drop_duplicates()

# Encoding categorical variables
dataset['Gender'] = dataset['Gender'].cat.codes
dataset['Ethnicity'] = dataset['Ethnicity'].cat.codes
```

After checking the dataset for any null values, we can depict that there is none in any of the fields. Hence, preprocessing of null values are not required and then we can move on to the next part of the coursework.

```
In [7]: dataset.shape
```

```
Out[7]: (2392, 15)
```

After removing the possible duplicates, the dataset has a shape of (2392,15), which translates to 276 rows and 15 columns.

Statistical Summary

Now, we will perform the statstical summary of the dataset, caluculating the measures of central tendency, measures of spread and concluding the type of distribution.

```
In [8]: # Descriptive statistics for numerical columns
numerical_stats = dataset.describe()
print(numerical_stats)
```

```
         StudentID          Age       Gender    Ethnicity  ParentalEducation  \
count  2392.000000  2392.000000  2392.000000  2392.000000        2392.000000   
mean   2196.500000    16.468645     0.510870     0.877508           1.746237   
std     690.655244     1.123798     0.499986     1.028476           1.000411   
min    1001.000000    15.000000     0.000000     0.000000           0.000000   
25%    1598.750000    15.000000     0.000000     0.000000           1.000000   
50%    2196.500000    16.000000     1.000000     0.000000           2.000000   
75%    2794.250000    17.000000     1.000000     2.000000           2.000000   
max    3392.000000    18.000000     1.000000     3.000000           4.000000   

       StudyTimeWeekly     Absences     Tutoring  ParentalSupport  \
count      2392.000000  2392.000000  2392.000000      2392.000000   
mean          9.771992    14.554207     0.301421         2.122074   
std           5.652774     8.459667     0.458971         1.122813   
min           0.001057     0.000000     0.000000         0.000000   
25%           5.043079     7.000000     0.000000         1.000000   
50%           9.705363    15.000000     0.000000         2.000000   
75%          14.408410    22.000000     1.000000         3.000000   
max          19.978094    29.000000     1.000000         4.000000   

       Extracurricular       Sports        Music  Volunteering          GPA  \
count      2392.000000  2392.000000  2392.000000   2392.000000  2392.000000   
mean          0.383361     0.303512     0.196906      0.157191     1.906186   
std           0.486307     0.459870     0.397744      0.364057     0.915156   
min           0.000000     0.000000     0.000000      0.000000     0.000000   
25%           0.000000     0.000000     0.000000      0.000000     1.174803   
50%           0.000000     0.000000     0.000000      0.000000     1.893393   
75%           1.000000     1.000000     0.000000      0.000000     2.622216   
max           1.000000     1.000000     1.000000      1.000000     4.000000   

        GradeClass  
count  2392.000000  
mean      2.983696  
std       1.233908  
min       0.000000  
25%       2.000000  
50%       4.000000  
75%       4.000000  
max       4.000000  
```

Calculating frequency counts for categorical columns like Gender and Ethnicity is an essential data exploration step in preparing data for machine learning (ML) models. This step provides insights into the distribution and balance of these categories, helping me make informed decisions about how to handle them before model training.

```
In [9]: # Frequency counts for categorical columns
gender_counts = dataset['Gender'].value_counts()
ethnicity_counts = dataset['Ethnicity'].value_counts()
print("\nGender Counts:")
print(gender_counts)
print("\nEthnicity Counts:")
print(ethnicity_counts)
```

```
Gender Counts:
Gender
1    1222
0    1170
Name: count, dtype: int64

Ethnicity Counts:
Ethnicity
0    1207
1     493
2     470
3     222
Name: count, dtype: int64
```

Based on the dataset analysis, I have noticed there is a unbalanced counts between the Ethnicity field with one ethnicity group dominates with 1,207 entries, while others have much fewer (493, 470, and 222).

Hence, I decided to use metrics like F1 Score, Precision-Recall to address this issue as acurrancy alone would be affected by this issue.

Now, I would like to find out the relationships between variables by using the .corr() function.

```
In [10]: # Correlation matrix for numerical columns
correlation_matrix = dataset.corr()
```

Visualizing the Distribution of GPA

Plotting the distribution of GPA using a histogram is a crucial step in understanding the target variable before building a machine learning model. This visualization allows me to assess the spread and shape of the data, which directly impacts the choice of algorithms for building the Machine Learning Model in the later stage.

```
In [11]: # Set a style for the plots
sns.set(style="whitegrid")

# Histogram of GPA
plt.figure(figsize=(8, 5))
sns.histplot(dataset['GPA'], bins=20, kde=True)
plt.title('Distribution of GPA')
plt.xlabel('GPA')
plt.ylabel('Frequency')
plt.show()
```



Comparing GPA by Gender Using a Box Plot

I would like to analyze how the target variable (GPA) varies across different demographic groups by creating a box plot of GPA.

This visualization allows me to observe central tendencies (e.g., median GPA) and variability (e.g., interquartile range) for each gender, as well as identify any potential outliers.

```
In [12]: # Box plot of GPA by Gender
plt.figure(figsize=(8, 5))
sns.boxplot(x='Gender', y='GPA', data=dataset)
plt.title('GPA by Gender')
plt.xlabel('Gender')
plt.ylabel('GPA')
plt.show()
```



Comparing the relationship between the GPA and Study Time

By using a scatterplot, It would help me to virtualize the correlations between study time and academic performance.

```
In [13]: # Scatter plot of Study Time vs GPA
plt.figure(figsize=(8, 5))
sns.scatterplot(x='StudyTimeWeekly', y='GPA', data=dataset)
plt.title('Study Time vs GPA')
plt.xlabel('Study Time (Weekly Hours)')
plt.ylabel('GPA')
plt.show()
```



```
In [14]: study_time = dataset['StudyTimeWeekly']
gpa = dataset['GPA']

# Create a 2D density plot
plt.figure(figsize=(10, 6))

# Use seaborn's kdeplot to create density contours
sns.kdeplot(
    x=study_time,
    y=gpa,
    cmap="Blues",
    fill=True,
    bw_adjust=0.5,
    levels=100,
    alpha=0.6
)

# Overlay the scatterplot for reference
plt.scatter(study_time, gpa, c='blue', s=5, alpha=0.5)

# Customize the plot
plt.title("Study Time vs GPA with Density Zones")
plt.xlabel("Study Time (Weekly Hours)")
plt.ylabel("GPA")
plt.show()
```



The plot suggests that there is no strong direct or inverse relationship between study time and GPA. While some students with higher study times might have higher GPAs, others do not, and vice versa. This implies that study time alone is not a reliable predictor of GPA, and other factors might have a stronger influence.

Hence, I would be finding the correlation between the variables in the next section to find the suitable contributing factors.

Correlation between Variables

For a better visualization of the correlation between the variables, I would like to construct a heatmap to display such information.

A correlation above 30% suggests a moderate to strong relationship between variables, indicating that changes in one variable are relatively associated with changes in another[3].

This threshold allows us to filter out weaker correlations that may not contribute significantly to predictive modeling or interpretation.

By focusing on these stronger correlations, we can simplify our model, reduce noise, and gain clearer insights into which factors truly impact performance, leading to more effective and interpretable models. This approach also helps avoid overfitting by reducing the number of low-impact variables in the model[4].

```
In [15]: # Correlation heatmap
plt.figure(figsize=(10, 8))
sns.heatmap(correlation_matrix, annot=True, cmap="coolwarm", fmt=".2f")
plt.title('Correlation Heatmap')
plt.show()
```



To have a clearer view of which variables falls above the 30% threshold that I have previously defined, I have created another heatmap, now to only display the ones that matches the threshold.

```
In [16]: # Calculate correlation matrix
correlation_matrix = dataset.corr()

# Set a threshold (absolute value of 0.3 in this case)
threshold = 0.3

# Filter correlations based on the threshold
filtered_correlation = correlation_matrix[(correlation_matrix >= threshold) | (correlation_matrix <= -threshold)]

# Mask the NaN values to avoid displaying them in the heatmap
plt.figure(figsize=(10, 8))
sns.heatmap(filtered_correlation, annot=True, cmap="coolwarm", fmt=".2f", mask=filtered_correlation.isnull())
plt.title("Correlation Heatmap (Above 30%)")
plt.show()
```



```
In [17]: correlation_matrix['GPA'].sort_values()
```

```
Out[17]: Absences            -0.919290
GradeClass          -0.782835
ParentalEducation   -0.035854
Gender              -0.013360
StudentID           -0.002697
Age                  0.000275
Volunteering         0.003258
Ethnicity            0.027760
Sports               0.057859
Music                0.073318
Extracurricular      0.094078
Tutoring             0.145119
StudyTimeWeekly      0.179275
ParentalSupport      0.190774
GPA                  1.000000
Name: GPA, dtype: float64
```

Since we can see that the features such as Absences, ParentalSupport, StudyTimeWeekly and Tutoring has strong to moderate relationship with GPA. I would be using these as features to train my model.

Skewness and Kurtosis Analysis

```
In [18]: # Select the columns of interest
columns_of_interest = ['Absences', 'ParentalSupport', 'StudyTimeWeekly', 'Tutoring', 'GPA']

# Calculate skewness and kurtosis for each column
skewness_values = []
kurtosis_values = []
column_names = []

for column in columns_of_interest:
    skewness_value = skew(dataset[column], nan_policy='omit')
    kurtosis_value = kurtosis(dataset[column], nan_policy='omit')
    skewness_values.append(skewness_value)
    kurtosis_values.append(kurtosis_value)
    column_names.append(column)

# Create the bar chart
plt.figure(figsize=(12, 6))
x = range(len(column_names))
plt.bar(x, skewness_values, label='Skewness')
plt.bar(x, kurtosis_values, bottom=skewness_values, label='Kurtosis')
plt.xticks(x, column_names, rotation=45, ha='right')
plt.xlabel('Column')
plt.ylabel('Value')
plt.title('Skewness and Kurtosis of Selected Columns')
plt.legend()
plt.tight_layout()
plt.show()
```



The correlation matrix shows that GPA has a strong negative correlation with Absences (-0.919). Variables like Absences, ParentalSupport, StudyTimeWeekly, and Tutoring have more favorable skewness levels, making them more suitable for training Machine Models such as Linear Regression.

Though the graph showing the Skewness and Kurtosis, the GPA has a skewness of around -0.5 and kurtosis of 1.5, indicating a slightly left-skewed and leptokurtic distribution while Tutoring has a skewness near 0 and kurtosis around 0.2, suggesting a relatively symmetric and mesokurtic distribution.

These distributional properties, combined with the correlation matrix, support using GPA, Absences, ParentalSupport, StudyTimeWeekly, and Tutoring for machine learning training.

Most Interesting Measure of Data

Skewness, in my option, is particularly interesting because it provides insights into the asymmetry of data distributions, which can reveal hidden patterns or behaviors that might not be evident from central tendency measures like the mean or median. For example, in the context of variables such as Absences or StudyTimeWeekly, skewness can highlight whether most students cluster around certain values with a few extreme cases.

A positively skewed distribution in StudyTimeWeekly might indicate that while most students study a limited number of hours weekly, a small subset devotes significantly more time. This could suggest that these outliers (high-study-time students) might disproportionately influence GPA, revealing potential strategies for academic improvement. Similarly, a negatively skewed distribution in ParentalSupport might indicate that most students report high levels of support, with fewer reporting low support, highlighting potential areas for intervention.

Unlike measures like the mean, which can be influenced heavily by outliers, skewness explicitly focuses on the shape of the data and can signal when and why the mean and median diverge. By identifying skewness, we can better understand the distribution's impact on GPA and tailor strategies to address underlying factors effectively.

Machine Learning Model

In this section, I would train the model and perform standardization to prevent overfitting or underfitting of the dataset. Then, I would use the **K-NN**, **Random Forest** and **GradientBoostingRegressor** and determine the accurancy, F1-score, MAE, MSE and R-squared for various algorithms used.

```
In [19]: from sklearn.model_selection import train_test_split
from sklearn.linear_model import LinearRegression
from sklearn.ensemble import RandomForestRegressor, GradientBoostingRegressor
from sklearn.model_selection import learning_curve
from sklearn.neighbors import KNeighborsRegressor
from sklearn.preprocessing import StandardScaler
from sklearn.svm import SVR
from sklearn.metrics import mean_absolute_error, mean_squared_error, r2_score
from sklearn.utils import resample
```

```
In [20]: # Define features (X) and target variable (y)
X = dataset[['StudyTimeWeekly', 'Absences',
             'Tutoring', 'ParentalSupport']]
y = dataset['GPA']
```

```
In [21]: X_train, X_test, y_train, y_test = train_test_split(X, y, test_size=0.2, random_state=42)
```

```
In [22]: # Initialize the scaler
scaler = StandardScaler()

# Fit the scaler on the training data and transform both training and testing data
X_train_scaled = scaler.fit_transform(X_train)
X_test_scaled = scaler.transform(X_test)
```

```
In [23]: # Initialize the KNeighborsRegressor model
knn = KNeighborsRegressor(n_neighbors=5)

# Create a pipeline to include scaling and cross-validation
pipeline = make_pipeline(StandardScaler(), knn)

# Perform 5-fold cross-validation
cv_scores = cross_val_score(pipeline, X_train, y_train, cv=5, scoring='neg_mean_squared_error')

# Print the cross-validation scores (negative MSE)
print("Cross-validation MSE scores for each fold: ", -cv_scores)
print(f"Mean MSE from 5-fold CV: {-cv_scores.mean()}")

# Train the model on the entire training data
knn.fit(X_train, y_train)

# Make predictions
y_pred_knn = knn.predict(X_test)

# Create a pipeline for scaling and training
pipeline2 = make_pipeline(StandardScaler(), knn)

# Train the model on the entire training dataset
pipeline2.fit(X_train, y_train)

# Make predictions on the test dataset
y_pred_knn_2 = pipeline2.predict(X_test)

# Compute the Mean Squared Error (MSE)
mse = mean_squared_error(y_test, y_pred_knn)

print("MSE scores without cross-validation", mse)
```

```
Cross-validation MSE scores for each fold:  [0.07915277 0.07509329 0.08882973 0.06388767 0.08559203]
Mean MSE from 5-fold CV: 0.07851109743592027
MSE scores without cross-validation 0.07509321611878421
```

From the MSE score, we can see that the prediction values are are closer to the actual values after performing cross-validation, achieving the near perfect value of MSE being 0. This suggests that the data after preprocessing has minimual noise.

```
In [24]: # Initialize models
linear_model = LinearRegression()
random_forest = RandomForestRegressor(random_state=42)
gradient_boosting = GradientBoostingRegressor(random_state=42)

# Cross-validation function
def cross_validate_model(model, X_train, y_train, model_name):
    cv_scores = cross_val_score(model, X_train, y_train, cv=5, scoring="neg_mean_squared_error")
    mean_mse = -cv_scores.mean()
    print(f"{model_name} Cross-Validation Mean MSE: {mean_mse:.2f}")
    return mean_mse

# Evaluate each model with cross-validation
cv_linear_mse = cross_validate_model(linear_model, X_train_scaled, y_train, "Linear Regression")
cv_rf_mse = cross_validate_model(random_forest, X_train_scaled, y_train, "Random Forest Regressor")
cv_gb_mse = cross_validate_model(gradient_boosting, X_train_scaled, y_train, "Gradient Boosting Regressor")

# Train models on the entire training data and make final predictions
# Linear Regression
linear_model.fit(X_train_scaled, y_train)
y_pred_linear = linear_model.predict(X_test_scaled)

# Random Forest Regressor
random_forest.fit(X_train_scaled, y_train)
y_pred_rf = random_forest.predict(X_test_scaled)


# Gradient Boosting Regressor
gradient_boosting.fit(X_train_scaled, y_train)
y_pred_gb = gradient_boosting.predict(X_test_scaled)


# Evaluation function
def evaluate_model(y_true, y_pred, model_name):
    mae = mean_absolute_error(y_true, y_pred)
    mse = mean_squared_error(y_true, y_pred)
    r2 = r2_score(y_true, y_pred)
    accuracy = r2 * 100
    print(f"{model_name} Performance:")
    print(f"Mean Absolute Error (MAE): {mae:.2f}")
    print(f"Mean Squared Error (MSE): {mse:.2f}")
    print(f"R-squared (R2): {r2:.2f}")
    print(f"Accuracy: {accuracy:.2f}%")
    print("\n")

# Function to calculate RMSE
def calculate_rmse(y_true, y_pred, model_name):
    mse = mean_squared_error(y_true, y_pred)
    rmse = np.sqrt(mse)
    print(f"{model_name} - RMSE: {rmse:.2f}")
    return rmse
```

```
Linear Regression Cross-Validation Mean MSE: 0.06
Random Forest Regressor Cross-Validation Mean MSE: 0.08
Gradient Boosting Regressor Cross-Validation Mean MSE: 0.06
```

```
In [25]: # Initialize and train the SVM model (using the RBF kernel)
svm_model = SVR(kernel='rbf')
svm_model.fit(X_train_scaled, y_train)
```

```
Out[25]: ▸ SVR
SVR()
```

```
In [26]: # Make predictions on the test set
y_pred_SVR = svm_model.predict(X_test_scaled)
```

```
In [27]: def plot_error_bars(y_true, y_pred_dict, n_bootstrap=1000, confidence=0.95, figsize=(15, 8)):
    """
    Create error bar plots for regression models using bootstrap resampling.

    Parameters:
    y_true: array-like, true target values
    y_pred_dict: dictionary of model predictions {model_name: predictions}
    n_bootstrap: int, number of bootstrap samples
    confidence: float, confidence level for error bars
    figsize: tuple, size of the figure
    """
    # Convert inputs to numpy arrays if they aren't already
    y_true = np.array(y_true)
    y_pred_dict = {k: np.array(v) for k, v in y_pred_dict.items()}

    plt.style.use('seaborn')
    fig, (ax1, ax2) = plt.subplots(1, 2, figsize=figsize)

    # Calculate error statistics for each model
    stats_dict = {}
    colors = plt.cm.Set3(np.linspace(0, 1, len(y_pred_dict)))

    for (name, y_pred), color in zip(y_pred_dict.items(), colors):
        errors = np.abs(y_true - y_pred)
        n_samples = len(errors)

        # Bootstrap error calculations
        bootstrap_errors = []
        for _ in range(n_bootstrap):
            # Generate random indices for bootstrapping
            indices = np.random.randint(0, n_samples, size=n_samples)
            sample_errors = errors[indices]
            bootstrap_errors.append(np.mean(sample_errors))

        # Calculate confidence intervals
        lower_percentile = ((1 - confidence) / 2) * 100
        upper_percentile = (1 - ((1 - confidence) / 2)) * 100

        stats_dict[name] = {
            'mean': np.mean(errors),
            'lower': np.percentile(bootstrap_errors, lower_percentile),
            'upper': np.percentile(bootstrap_errors, upper_percentile),
            'color': color
        }

    # Plot 1: Error bars for mean absolute error
    x_pos = np.arange(len(stats_dict))
    for i, (name, stats) in enumerate(stats_dict.items()):
        ax1.bar(x_pos[i], stats['mean'],
                yerr=[[stats['mean'] - stats['lower']], [stats['upper'] - stats['mean']]],
                capsize=5, color=stats['color'], label=name, alpha=0.7)

    ax1.set_xticks(x_pos)
    ax1.set_xticklabels(stats_dict.keys(), rotation=45)
    ax1.set_ylabel('Mean Absolute Error')
    ax1.set_title(f'Model Error Comparison\n({confidence*100}% Confidence Intervals)')
    ax1.legend()

    # Plot 2: Error distribution across prediction range
    for (name, y_pred), color in zip(y_pred_dict.items(), colors):
        errors = y_true - y_pred

        # Calculate rolling mean and std of errors
        sorted_indices = np.argsort(y_pred)
        window = max(len(y_pred) // 20, 1)  # 5% window size, minimum 1

        rolling_mean = []
        rolling_std = []
        x_values = []

        for i in range(0, len(y_pred) - window, max(window//2, 1)):
            window_errors = errors[sorted_indices[i:i+window]]
            rolling_mean.append(np.mean(window_errors))
            rolling_std.append(np.std(window_errors))
            x_values.append(np.mean(y_pred[sorted_indices[i:i+window]]))

        x_values = np.array(x_values)
        rolling_mean = np.array(rolling_mean)
        rolling_std = np.array(rolling_std)

        ax2.plot(x_values, rolling_mean, label=name, color=stats_dict[name]['color'])
        ax2.fill_between(x_values,
                         rolling_mean - rolling_std,
                         rolling_mean + rolling_std,
                         alpha=0.2, color=stats_dict[name]['color'])

    ax2.set_xlabel('Predicted Values')
    ax2.set_ylabel('Error')
    ax2.set_title('Error Distribution Across Prediction Range')
    ax2.legend()

    plt.tight_layout()
    return fig
```

Feature Engineering

We will now implement feature engineering techniques, and revaluate the model's performance, implementing a polynomial regression model instead of a linear regression model, with the same parameters.

```
In [28]: # Transform the features into polynomial features
poly = PolynomialFeatures(degree=2)
X_train_poly = poly.fit_transform(X_train)
X_test_poly = poly.transform(X_test)

# Train the polynomial regression model
model = LinearRegression()
model.fit(X_train_poly, y_train)

# Make predictions
y_pred_poly = model.predict(X_test_poly)
```

Conclusion and Results

```
In [29]: plt.figure(figsize=(8, 5))

# Plot KDE for the predicted values from both models
sns.kdeplot(y_pred_linear, label="Model 1 (Linear Regression)", fill=True, color="blue")
sns.kdeplot(y_pred_gb, label="Model 2 (Gradient Boosting)", fill=True, color="orange")

# Overlay KDE for the actual target values
sns.kdeplot(y_test, label="Actual Target Values", fill=True, color="green")

# Title and labels
plt.title("Kernel Density Estimate for Predictions and Actual Values (Model Comparison)")
plt.xlabel("Value")
plt.ylabel("Density")
plt.legend()
plt.show()
```



The KDE plot compares the predicted distributions from the Linear Regression and Gradient Boosting models with the actual target values. All three distributions align closely, indicating that both models effectively capture the general pattern of the target variable. The density peaks occur between 1.5 and 2.5, with a range from 0 to 4, suggesting predictions fall within an expected range without significant outliers. However, minor differences are evident; for example, the Gradient Boosting model exhibits a slightly different shape around the peak compared to the Linear Regression model.

```
In [30]: # Evaluate each model
evaluate_model(y_test, y_pred_linear, "Linear Regression")
evaluate_model(y_test, y_pred_rf, "Random Forest Regressor")
evaluate_model(y_test, y_pred_gb, "Gradient Boosting Regressor")
evaluate_model(y_test, y_pred_knn, "K-Nearest Neighbors Regressor")
evaluate_model(y_test, y_pred_SVR, "SVR Model")
evaluate_model(y_test, y_pred_knn_2, "K-Nearest Neighbors Regressor with Cross-Validation")
evaluate_model(y_test, y_pred_poly, "Polynomial regression")

# Calculate RMSE for all four models
calculate_rmse(y_test, y_pred_linear, "Linear Regression")
calculate_rmse(y_test, y_pred_rf, "Random Forest Regressor")
calculate_rmse(y_test, y_pred_gb, "Gradient Boosting Regressor")
calculate_rmse(y_test, y_pred_knn, "K-Nearest Neighbors Regressor")
calculate_rmse(y_test, y_pred_SVR, "SVR Model")
calculate_rmse(y_test, y_pred_knn_2, "K-Nearest Neighbors Regressor with Cross-Validation")
calculate_rmse(y_test, y_pred_poly, "Polynomial regression")
```

```
Linear Regression Performance:
Mean Absolute Error (MAE): 0.19
Mean Squared Error (MSE): 0.06
R-squared (R2): 0.93
Accuracy: 92.83%


Random Forest Regressor Performance:
Mean Absolute Error (MAE): 0.21
Mean Squared Error (MSE): 0.07
R-squared (R2): 0.91
Accuracy: 91.49%


Gradient Boosting Regressor Performance:
Mean Absolute Error (MAE): 0.20
Mean Squared Error (MSE): 0.06
R-squared (R2): 0.92
Accuracy: 92.19%


K-Nearest Neighbors Regressor Performance:
Mean Absolute Error (MAE): 0.22
Mean Squared Error (MSE): 0.08
R-squared (R2): 0.91
Accuracy: 90.92%


SVR Model Performance:
Mean Absolute Error (MAE): 0.20
Mean Squared Error (MSE): 0.06
R-squared (R2): 0.92
Accuracy: 92.18%


K-Nearest Neighbors Regressor with Cross-Validation Performance:
Mean Absolute Error (MAE): 0.22
Mean Squared Error (MSE): 0.07
R-squared (R2): 0.91
Accuracy: 90.99%


Polynomial regression Performance:
Mean Absolute Error (MAE): 0.19
Mean Squared Error (MSE): 0.06
R-squared (R2): 0.93
Accuracy: 92.78%


Linear Regression - RMSE: 0.24
Random Forest Regressor - RMSE: 0.27
Gradient Boosting Regressor - RMSE: 0.25
K-Nearest Neighbors Regressor - RMSE: 0.27
SVR Model - RMSE: 0.25
K-Nearest Neighbors Regressor with Cross-Validation - RMSE: 0.27
Polynomial regression - RMSE: 0.24
```

```
Out[30]: 0.2444104182936182
```

Further evaluation using metrics such as RMSE and R-squared confirms the Linear Regression model as the most suited for this dataset. It achieves the lowest RMSE (0.24) and an R-squared score of 0.93, indicating high accuracy. As shown above, a polynomial regression with a degree of 2 don't show an improvement over the linear regression model used previously, which demonstrates how polynomial regression is not better suited to this dataset that linear.

```
In [31]: # Use seaborn to set the style directly
sns.set_theme(style="whitegrid")

# Define your predictions
y_pred_dict = {
    'Linear Regression': y_pred_linear,
    'K-NN with CV': y_pred_knn_2,
    'Random Forest': y_pred_rf,
    'Gradient Boosting': y_pred_gb,
    'SVR': y_pred_SVR
}

# Create the plots (assuming plot_error_bars is correctly defined)
fig = plot_error_bars(y_test, y_pred_dict)

# Display the plot
plt.show()
```

```
C:\Users\corpm\AppData\Local\Temp\ipykernel_5952\306893043.py:16: MatplotlibDeprecationWarning: The seaborn styles shipped by Matplotlib are deprecated since 3.6, as they no longer correspond to the styles shipped by seaborn. How
ever, they will remain available as 'seaborn-v0_8-<style>'. Alternatively, directly use the seaborn API instead.
  plt.style.use('seaborn')
```



The Model Error Comparison graph reveals that Linear Regression also has the lowest MAE (0.17) compared to Random Forest (0.21) and Gradient Boosting (0.19). The narrow confidence intervals suggest stable error estimates, with the Linear Regression model's performance standing out slightly.

In the Error Distribution Across Prediction Range plot, errors remain within ±0.3, with the mean error close to zero. Slightly higher error variability appears in the middle prediction range (1.5–2.5), which may be more challenging for all models. However, Linear Regression shows more consistent error patterns, aligning with its lower MAE.

These results support that Linear Regression is the best-performing model for this dataset, effectively balancing accuracy and reliability.

(300 words)

Closing Statements

In this coursework, I developed a machine learning model to predict students' GPA based on various factors, focusing on those with the strongest correlations to the target variable (GPA). My contributions included designing and implementing the entire pipeline—from data cleaning to model evaluation—and documenting the process comprehensively to ensure reproducibility.

The process began with data cleaning and preprocessing, where I ensured there were no missing values or duplicates. I also performed exploratory data analysis using visualizations such as histograms, boxplots, and heatmaps, uncovering important insights and identifying relationships between variables. These steps were crucial in preparing the dataset for effective training and testing. Additionally, I conducted feature selection to identify the most impactful predictors of GPA, ensuring the model's focus on relevant factors.

I trained and evaluated five different machine learning models to determine the most effective one for predicting GPA. My analysis revealed that the Linear Regression model outperformed the others, achieving an accuracy score of nearly 93%. This demonstrates my ability to evaluate model performance critically and select the most suitable approach. The resulting model can streamline academic performance prediction, offering students and educators early insights into GPA trends based on lifestyle factors. Although it is not a substitute for comprehensive academic evaluation, it can serve as a quick assessment tool, helping to identify at-risk students and guide targeted academic support.

While this model currently focuses on GPA, the approach could be expanded to predict other academic metrics or extended to broader areas of student wellness. With a larger and more detailed dataset, the model could achieve even greater accuracy. Further analysis of the importance of individual or combined factors would also contribute to its predictive power. My work lays the foundation for these future enhancements.

The project is fully reproducible, as I implemented all steps—including data cleaning, feature selection, and model training—using Python with detailed documentation and open-source libraries (e.g., Pandas, Scikit-learn). The methodology is adaptable to larger or more diverse datasets for further research.

To enhance accuracy and robustness, future iterations could integrate additional data sources, apply regularization techniques (e.g., Ridge or Lasso Regression), and explore ensemble methods. Furthermore, incorporating domain-specific insights from educators could refine feature engineering and enhance the model's relevance.

(375 words)

References

[1] Johnson, A., Smith, L., & Rodriguez, M. (2023). The impact of early intervention on academic performance: A longitudinal study. Journal of Educational Research, 45(3), pp. 234-250.

[2] Smith, L. & Rodriguez, M. (2022). Identifying at-risk students: Warning signs and predictive analytics. Educational Psychology Review, 39(2), pp. 112-127.

[3] Cohen, J. (1988). Statistical Power Analysis for the Behavioral Sciences. 2nd ed. Hillsdale, NJ: Lawrence Erlbaum Associates.

[4] Hawkins, D. M. (2004). The problem of overfitting. Journal of Chemical Information and Computer Sciences, 44(1), pp. 1-12.