

interfaces php - sunday

Sunday, October 15, 2017 11:02

finishStaffRequest.php

called to finish staff recruitment

It takes the task, moves it back to the initiator with status 7 and deletes the staff request from DB

input

variable	type	fallback value if not provided	required
idTask	int	0	X

returns:

variable	type
result	string ["success" "failure"]

`{"result": "success"}`

From <<http://localhost/app/php/finishStaffRequest.php>>

fmBudgetNegotiation.php

called to let the FM make the adjustment to the budget.

input

variable	type	fallback value if not provided	required
idTask	String	0	X
amount	int/float	0	

returns:

variable	type
result	String ['success' 'failure']

`{"result": "failure"}`

From <<http://localhost/app/php/fmBudgetNegotiation.php>>

getFinancialRequest.php

called to get the FinancialRequest

input

variable	type	fallback value if not provided	required
----------	------	--------------------------------	----------

idTask	int	0	X
--------	-----	---	---

returns:

variable	type
amount	decimal(10,2)
reason	string
//if nothing found	null //literally, httpRequest.ResponseText == null [maybe "null"], but this case <i>shouldn't</i> be happening, so omit it for now

```
{"amount":"0.00","reason":"No reason provided."}
```

From <<http://localhost/app/php/getFinancialRequest.php>>

getStaffRequest.php

called to obtain the StaffRequest

input

variable	type	fallback value if not provided	required
idTask	int	0	X

returns:

variable	type
experience	string
jobTitle	string
jobDescription	string

```
{"experience":"test experience","jobTitle":"test job title","jobDescription":"test job description"}
```

From <<http://localhost/app/php/getStaffRequest.php>>