



Fault Rules and Error Responses

Terminology

- 1) Raise Fault policy

Terminology

- 1) Raise Fault policy
- 2) Apigee Edge raises an error during policy execution

Terminology

- 1) Raise Fault policy
- 2) Apigee Edge raises an error during policy execution
- 3) Fault Rule = Fault Handler (error flow)

Fault Handling

<FaultRules> located in

- **Proxy Endpoint**
- **Target Endpoint**

Fault Handling

<FaultRules> located in

- **Proxy Endpoint**
- **Target Endpoint**

```
<Step>
|   <Name>SpikeArrest</Name>
</Step>
<Step>
|   <Name>SetConfigurationVariables</Name>
</Step>
<Step>
|   <Name>VerifyApiKey</Name>
</Step>
<Step>
|   <Name>QuotaPolicy</Name>
</Step>
```

Fault Handling

<FaultRules> located in

- **Proxy Endpoint**
- **Target Endpoint**

```
<Step>
  <Name>SpikeArrest</Name>
</Step>
<Step>
  <Name>SetConfigurationVariables</Name>
</Step>
<Step>
  <Name>VerifyApiKey</Name>
</Step>
<Step>
  <Name>QuotaPolicy</Name>
</Step>
```

Fault Handling

<FaultRules> located in

- Proxy Endpoint
- Target Endpoint

```
<Step>
  <Name>SpikeArrest</Name>
</Step>
<Step>
  <Name>SetConfigurationVariables</Name>
</Step>
<Step>
  <Name>VerifyApiKey</Name>
</Step>
<Step>
  <Name>QuotaPolicy</Name>
</Step>
```



Fault Handling

<FaultRules> located in

- Proxy Endpoint
- Target Endpoint

```
<Step>
  <Name>SpikeArrest</Name>
</Step>
<Step>
  <Name>SetConfigurationVariables</Name>
</Step>
<Step>
  <Name>VerifyApiKey</Name>
</Step>
<Step>
  <Name>QuotaPolicy</Name>
</Step>
```



```
1 <DefaultFaultRule>
2   <Step>
3     <Name>SyslogPolicy</Name>
4   </Step>
5   <AlwaysEnforce>true</AlwaysEnforce>
6 </DefaultFaultRule>
7 <FaultRules>
8   <FaultRule name ="Fault.InvalidKey">
9     <Step>
10      <Name>Add-WWW-Authenticate-Header</Name>
11    </Step>
12    <Condition>(fault.name == "invalid_consumer_key")</Condition>
13  </FaultRule>
14 </FaultRules>
15 <HTTPProxyConnection>
16   <BasePath>/certification/v1/weather</BasePath>
17   <VirtualHost>default</VirtualHost>
18   <VirtualHost>secure</VirtualHost>
19 </HTTPProxyConnection>
```

Fault Handling

<FaultRules> located in

- Proxy Endpoint
- Target Endpoint

```
<Step>
  <Name>SpikeArrest</Name>
</Step>
<Step>
  <Name>SetConfigurationVariables</Name>
</Step>
<Step>
  <Name>VerifyApiKey</Name>
</Step>
<Step>
  <Name>QuotaPolicy</Name>
</Step>
```



```
1 <DefaultFaultRule>
2   <Step>
3     <Name>SyslogPolicy</Name>
4   </Step>
5   <AlwaysEnforce>true</AlwaysEnforce>
6 </DefaultFaultRule>
7 <FaultRules>
8   <FaultRule name ="Fault.InvalidKey">
9     <Step>
10      <Name>Add-WWW-Authenticate-Header</Name>
11    </Step>
12    <Condition>(fault.name == "invalid_consumer_key")</Condition>
13  </FaultRule>
14 </FaultRules>
15 <HTTPProxyConnection>
16   <BasePath>/certification/v1/weather</BasePath>
17   <VirtualHost>default</VirtualHost>
18   <VirtualHost>secure</VirtualHost>
19 </HTTPProxyConnection>
```

Fault Handling

Proxy Endpoint

```
1 <DefaultFaultRule>
2   <Step>
3     <Name>SyslogPolicy</Name>
4   </Step>
5   <AlwaysEnforce>true</AlwaysEnforce>
6 </DefaultFaultRule>
7 <FaultRules>
8   <FaultRule name ="Fault.InvalidKey">
9     <Step>
10      <Name>Add-WWW-Authenticate-Header</Name>
11    </Step>
12    <Condition>(fault.name == "invalid_consumer_key")</Condition>
13  </FaultRule>
14 </FaultRules>
```

Fault Handling

Proxy Endpoint



```
1 <DefaultFaultRule>
2   <Step>
    <Name>SyslogPolicy</Name>
  </Step>
  <AlwaysEnforce>true</AlwaysEnforce>
</DefaultFaultRule>
<FaultRules>
  <FaultRule name ="Fault.InvalidKey">
    <Step>
      <Name>Add-WWW-Authenticate-Header</Name>
    </Step>
    <Condition>(fault.name == "invalid_consumer_key")</Condition>
  </FaultRule>
</FaultRules>
```

Fault Handling

Proxy Endpoint



```
1 <DefaultFaultRule>
2   <Step>
      <Name>SyslogPolicy</Name>
    </Step>
    <AlwaysEnforce>true</AlwaysEnforce>
  </DefaultFaultRule>
  <FaultRules>
    <FaultRule name ="Fault.InvalidKey">
      <Step>
        <Name>Add-WWW-Authenticate-Header</Name>
      </Step>
      <Condition>(fault.name == "invalid_consumer_key")</Condition>
    </FaultRule>
  </FaultRules>
```

Target Endpoint

```
1 <DefaultFaultRule>
2   <Step>
      <Name>SyslogPolicy</Name>
    </Step>
    <AlwaysEnforce>true</AlwaysEnforce>
  </DefaultFaultRule>
  <FaultRules>
    <FaultRule name ="Fault.InvalidKey">
      <Step>
        <Name>Add-WWW-Authenticate-Header</Name>
      </Step>
      <Condition>(fault.name == "invalid_consumer_key")</Condition>
    </FaultRule>
  </FaultRules>
  <HTTPProxyConnection>
    <BasePath>/certification/v1/weather</BasePath>
    <VirtualHost>default</VirtualHost>
    <VirtualHost>secure</VirtualHost>
  </HTTPProxyConnection>
```

Fault Handling

Proxy Endpoint

```
1 <DefaultFaultRule>
2   <Step>
      <Name>SyslogPolicy</Name>
    </Step>
    <AlwaysEnforce>true</AlwaysEnforce>
  </DefaultFaultRule>
  <FaultRules>
    <FaultRule name ="Fault.InvalidKey">
      <Step>
        <Name>Add-WWW-Authenticate-Header</Name>
      </Step>
      <Condition>(fault.name == "invalid_consumer_key")</Condition>
    </FaultRule>
  </FaultRules>
```



Target Endpoint

```
1 <DefaultFaultRule>
   <Step>
     <Name>SyslogPolicy</Name>
   </Step>
   <AlwaysEnforce>true</AlwaysEnforce>
</DefaultFaultRule>
<FaultRules>
  <FaultRule name ="Fault.InvalidKey">
    <Step>
      <Name>Add-WWW-Authenticate-Header</Name>
    </Step>
    <Condition>(fault.name == "invalid_consumer_key")</Condition>
  </FaultRule>
14 </FaultRules>
15 <HTTPProxyConnection>
16   <BasePath>/certification/v1/weather</BasePath>
17   <VirtualHost>default</VirtualHost>
18   <VirtualHost>secure</VirtualHost>
19 </HTTPProxyConnection>
```



Fault Handling

- <FaultRules>
 - Support for multiple fault rules, executed conditionally.

Fault Handling

- <FaultRules>
 - Support for multiple fault rules, executed conditionally.
- <DefaultFaultRule>
 - catch all
 - executes when no FaultRule matches
 - <AlwaysEnforce>

Rewriting Backend Error Responses

Edge has a pre-defined fault response format:

```
{
  "fault":{
    "faultstring":"%errorMessage#",
    "detail":{
      "errorcode":"%errocode#"
    }
  }
}
```

Rewriting Backend Error Responses

Edge has a pre-defined fault response format:

```
{
  "fault":{
    "faultstring":"%errorMessage#",
    "detail":{
      "errorcode":"%errocode#"
    }
  }
}
```

You can either:

1. Rewrite backend error responses to match Apigee Edge's format.
2. Rewrite Edge fault responses to match the backend error response format.

Raise Fault policy

Code: raise_fault_invalid_post

```
1 <?xml version="1.0" encoding="UTF-8" standalone="yes"?>
2 <RaiseFault async="false" continueOnError="false" enabled="true" name="raise_fault_invalid_post">
3   <DisplayName>raise_fault_invalid_post</DisplayName>
4   <FaultRules/>
5   <Properties/>
6   <FaultResponse>
7     <Set>
8       <Headers/>
9       <Payload contentType="application/json">\{"error":"Invalid Post Data"}</Payload>
10      <StatusCode>400</StatusCode>
11      <ReasonPhrase>Bad Request</ReasonPhrase>
12    </Set>
13  </FaultResponse>
14  <IgnoreUnresolvedVariables>true</IgnoreUnresolvedVariables>
15 </RaiseFault>
```

Raise Fault policy

```
<PreFlow name="PreFlow">
  <Request>
    <Step>
      <Name>RaiseFaultMissingNameParam</Name>
      <Condition>request.queryparam.name == null</Condition>
    </Step>
  </Request>
  <Response/>
</PreFlow>
```



Thank You

Fault Handling

<FaultRule>

- Support for multiple fault rules, executed conditionally.
- Raised manually or automatically upon policy failure.
- If multiple conditional FaultRules defined, their conditions are evaluated in reverse order (bottom up).

<DefaultFaultRule>

- A catch-all / post processing fault rule is available using the flow
- If no FaultRule is matched, this flow will execute.
- Use <AlwaysEnforce>true</AlwaysEnforce> to use this flow for post processing in error flows. This will ensure the flow executes after a matched fault rule has completed its processing.

3 scenarios where processing will switch to fault processing:


- Using RaiseFault policy.
- Any policy failure when continueOnError=false (default setting).
- Non-success response received from service callout or



```
1  <DefaultFaultRule>
    <Step>
      <Name>SyslogPolicy</Name>
    </Step>
    <AlwaysEnforce>true</AlwaysEnforce>
  </DefaultFaultRule>
  <FaultRules>
    <FaultRule name ="Fault.InvalidKey">
      <Step>
        <Name>Add-WWW-Authenticate-Header</Name>
      </Step>
      <Condition>{fault.name == "invalid_consumer_key"}</Condition>
    </FaultRule>
  </FaultRules>
14 </HTTPProxyConnection>
15 <HTTPProxyConnection>
16   <BasePath>/certification/v1/weather</BasePath>
17   <VirtualHost>default</VirtualHost>
18   <VirtualHost>secure</VirtualHost>
19 </HTTPProxyConnection>
```

Raise Faults work with conditions

Select Post Ratings Resource from navigation pane



Add a condition to the Step (policy)

Code: post_ratings

```
1  <Flow name="post_ratings">
2    <Description/>
3    <Request>
4      <Step>
5        <FaultRules/>
6        <Name>extract_post_data_ratings</Name>
7      </Step>
8      <Step>
9        <FaultRules/>
10       <Name>raise_fault_invalid_post</Name>
11       <Condition>((truck = NULL) or (comment = NULL) or (commenter = NULL) or (score = NULL))</Condition>
12     </Step>
13   </Request>
14   <Response/>
15   <Condition>(proxy.pathsuffix matchesPath &quot;ratings&quot;) and request.verb = &quot;POST&quot;</Condition>
16 </Flow>
```

Raise Fault policy

Add a Raise Fault Policy



Name and Select the Proxy Endpoint (Ratings (Post)) from the flows,

Policy Display Name:

Policy Name:

Attach Policy: ☒

Flow:

Segment: ☒ Request ☐ Response

Modify the content to return an appropriate fault message

Code: raise_fault_invalid_post

```
1 <?xml version="1.0" encoding="UTF-8" standalone="yes"?>
2 <RaiseFault async="false" continueOnError="false" enabled="true" name="raise_fault_invalid_post">
3   <DisplayName>raise_fault_invalid_post</DisplayName>
4   <FaultRules/>
5   <Properties/>
6   <FaultResponse>
7     <Set>
8       <Headers/>
9       <Payload contentType="application/json">\{"error":"Invalid Post Data"></Payload>
10      <StatusCode>400</StatusCode>
11      <ReasonPhrase>Bad Request</ReasonPhrase>
12    </Set>
13  </FaultResponse>
14  <IgnoreUnresolvedVariables>true</IgnoreUnresolvedVariables>
15 </RaiseFault>
```


Raise Fault Policy Details

Fault Response Tag Format

- Set – Allows you to build an inline response to fault
 - StatusCode – HTTP Status Code
 - ReasonPhrase – HTTP Reason Phrase
 - Payload – Message Contents for your fault (follows same spec as assign message)
- Copy – Allows you to copy the request or the response into the fault response
 - Attr:source – request or response object

Raise Faults work with conditions

Code: post_ratings

```
1  <Flow name="post_ratings">
2    <Description/>
3    <Request>
4      <Step>
5        <FaultRules/>
6        <Name>extract_post_data_ratings</Name>
7      </Step>
8    </Request>
9    <Response/>
10   <Condition>(proxy.pathsuffix MatchesPath &quot;/ratings&quot;); and (request.verb = &quot;POST&quot;)</Condition>
11   <Step>
12     <FaultRules/>
13     <Name>raise_fault_invalid_post</Name>
14     <Condition>((truck = NULL) or (comment = NULL) or (commenter = NULL) or (score = NULL))</Condition>
15   </Step>
16 </Flow>
```

