

1. Show all database inside your machine.

```
MariaDB [(none)]> SHOW DATABASES;
+-----+
| Database |
+-----+
| chinookcs |
| db_bsit2a |
| hehehey   |
| hehehey copy |
| information_schema |
| monfraise_db |
| mysql     |
| performance_schema |
| phpmyadmin |
| test      |
+-----+
10 rows in set (0.001 sec)
```

2. Create database with database name `db_faith`

```
MariaDB [(none)]> CREATE DATABASE db_faith;
Query OK, 1 row affected (0.001 sec)

MariaDB [(none)]> SHOW DATABASE;
ERROR 1064 (42000): You have an error in your SQL syntax; ch
riaDB server version for the right syntax to use near 'DATAB
MariaDB [(none)]> SHOW DATABASES;
+-----+
| Database |
+-----+
| chinookcs |
| db_bsit2a |
| db_faith  |
| hehehey   |
| hehehey copy |
| information_schema |
| monfraise_db |
| mysql     |
| performance_schema |
| phpmyadmin |
| test      |
+-----+
```

3. Use database `db_faith`;

```
MariaDB [(none)]> USE db_faith;  
Database changed  
MariaDB [db_faith]> |
```

4. Create table with table name `tbl_students`, following fields:

Field Name	Data Type	Length	Extra
id	INT		PRIMARY KEY, AUTO_INCREMENT
lastname	VARCHAR	100	
firstname	VARCHAR	100	
department	VARCHAR	10	
course	VARCHAR	10	
year	INT	2	
status	VARCHAR	10	

```

MariaDB [db_faith]> CREATE TABLE tbl_students (
  -> id INT AUTO_INCREMENT PRIMARY KEY,
  -> lastname VARCHAR(100),
  -> firstname VARCHAR(100),
  -> department VARCHAR(10),
  -> course VARCHAR(10),
  -> year INT (2),
  -> status VARCHAR(10)
  -> );
Query OK, 0 rows affected (0.031 sec)

MariaDB [db_faith]> SHOW TABLE;
ERROR 1064 (42000): You have an error in your SQL syntax; check the ma
riaDB server version for the right syntax to use near '' at line 1
MariaDB [db_faith]> DESCRIBE tbl_students;
+-----+-----+-----+-----+-----+-----+
| Field      | Type          | Null | Key | Default | Extra          |
+-----+-----+-----+-----+-----+-----+
| id         | int(11)       | NO   | PRI | NULL    | auto_increment |
| lastname   | varchar(100)  | YES  |     | NULL    |                |
| firstname  | varchar(100)  | YES  |     | NULL    |                |
| department | varchar(10)   | YES  |     | NULL    |                |
| course     | varchar(10)   | YES  |     | NULL    |                |
| year       | int(2)        | YES  |     | NULL    |                |
| status     | varchar(10)   | YES  |     | NULL    |                |
+-----+-----+-----+-----+-----+-----+

```

5. INSERT the following record inside tbl_students in following order:

- a. Cruz/Jerwin/CCIT/BSIT/2/ACTIVE
- b. Garcia/John/CCIT/BSCS/2/ACTIVE
- c. Mercado/Daniel/CBA/BSA/3/REMOVED

```
MariaDB [db_faith]> INSERT INTO tbl_students (lastname, firstname, department, course, year, status)
-> VALUES
-> ('Cruz', 'Jerwin', 'CCIT', 'BSIT', 2, 'ACTIVE'),
-> ('Garcia', 'John', 'CCIT', 'BSCS', 2, 'ACTIVE'),
-> ('Mercado', 'Daniel', 'CBA', 'BSA', 3, 'REMOVED');
```

Query OK, 3 rows affected (0.040 sec)
Records: 3 Duplicates: 0 Warnings: 0

```
MariaDB [db_faith]> SELECT * FROM tbl_students;
```

id	lastname	firstname	department	course	year	status
1	Cruz	Jerwin	CCIT	BSIT	2	ACTIVE
2	Garcia	John	CCIT	BSCS	2	ACTIVE
3	Mercado	Daniel	CBA	BSA	3	REMOVED

3 rows in set (0.000 sec)

6. Display all record of 3rd year students.

```
MariaDB [db_faith]> SELECT * FROM tbl_students WHERE year=3;
```

id	lastname	firstname	department	course	year	status
3	Mercado	Daniel	CBA	BSA	3	REMOVED

1 row in set (0.001 sec)

7. Display all record of student/s if the status is equal to 'REMOVED'.

```
MariaDB [db_faith]> SELECT * FROM tbl_students WHERE status='REMOVED';
```

id	lastname	firstname	department	course	year	status
3	Mercado	Daniel	CBA	BSA	3	REMOVED

1 row in set (0.000 sec)

8. Display the firstname of all students under CCIT department.

```
MariaDB [db_faith]> SELECT firstname FROM tbl_students WHERE department='CCIT';
```

firstname
Jerwin
John

2 rows in set (0.000 sec)

9. Update the lastname to Miranda if the id = 3.

```
MariaDB [db_faith]> UPDATE tbl_students SET lastname = 'Miranda' WHERE id = 3;  
Query OK, 1 row affected (0.003 sec)  
Rows matched: 1  Changed: 1  Warnings: 0
```

```
MariaDB [db_faith]> SELECT * FROM tbl_students;
```

id	lastname	firstname	department	course	year	status
1	Cruz	Jerwin	CCIT	BSIT	2	ACTIVE
2	Garcia	John	CCIT	BSCS	2	ACTIVE
3	Miranda	Daniel	CBA	BSA	3	REMOVED

```
3 rows in set (0.000 sec)
```

10. Delete Jerwin Cruz data.

```
MariaDB [db_faith]> DELETE FROM tbl_students WHERE id = 1;  
Query OK, 1 row affected (0.012 sec)
```

```
MariaDB [db_faith]> SELECT * FROM tbl_students;
```

id	lastname	firstname	department	course	year	status
2	Garcia	John	CCIT	BSCS	2	ACTIVE
3	Miranda	Daniel	CBA	BSA	3	REMOVED

```
2 rows in set (0.000 sec)
```