Network Layer

- Reference
  - Chapter 04, *Computer Networking: A Top Down Approach,* 6/E, Jim Kurose, Keith Ross, Addison-Wesley
  - Adapted from part of the slides provided by the authors

Network layer

- transport segment from sending to receiving host
- on sending side encapsulates segments into datagrams
- on receiving side, delivers segments to transport layer
- network layer protocols in *every* host, router
- router examines header fields in all IP datagrams passing through it



Interplay between routing and forwarding



Connection, connection-less service

- *datagram* network provides network-layer *connectionless* service
  - used in today's Internet
- *virtual-circuit* network provides network-layer *connection* service
  - used in ATM, frame-relay, X.25
  - not used in today's Internet
- analogous to TCP/UDP connecton-oriented / connectionless transport-layer services, but:
  - *service:* host-to-host
  - *no choice:* network provides one or the other
  - *implementation:* in network core

Datagram networks



- no call setup at network layer
- routers: no state about end-to-end connections
  - no network-level concept of "connection"
- packets forwarded using destination host address

Datagram forwarding table



Datagram forwarding table

Destination Address Range	Link Interface
11001000 00010111 00010000 00000000 through **11001000 00010111 00010111 11111111**	0
11001000 00010111 00011000 00000000 through **11001000 00010111 00011000 11111111**	1
11001000 00010111 00011001 00000000 through **11001000 00010111 00011111 11111111**	2
otherwise	3

Q: but what happens if ranges don't divide up so nicely?

Longest prefix matching

longest prefix matching

when looking for forwarding table entry for given destination address, use *longest* address prefix that matches destination address.

11001000 00010111 00011000 ********* is excluded from 11001000 00010111 00011*** *********

Destination Address Range	Link interface
11001000 00010111 00010*** *********	0
11001000 00010111 00011000 *********	1
11001000 00010111 00011*** *********	2
otherwise	3

examples:

DA: 11001000 00010111 00010110 10100001 which interface?

DA: 11001000 00010111 00011000 10101010 which interface?

Router architecture overview



two key router functions:

- run routing algorithms/protocol (RIP, OSPF, BGP)
- *forwarding* datagrams from incoming to outgoing link

Input port functions



decentralized switching:

- given datagram dest., lookup output port using forwarding table in input port memory *("match plus action")*
- goal: complete input port processing at 'line speed'
- queuing: if datagrams arrive faster than forwarding rate into switch fabric

Switching fabrics

- transfer packet from input buffer to appropriate output buffer
- switching rate: rate at which packets can be transfer from inputs to outputs
  – often measured as multiple of input/output line rate
  – N inputs: switching rate N times line rate desirable
- three types of switching fabrics



Switching via memory

first generation routers:

- traditional computers with switching under direct control of CPU
- packet copied to system's memory
- speed limited by memory bandwidth (2 bus crossings per datagram)



Switching via a bus

- datagram from input port memory to output port memory via a shared bus
- *bus contention:* switching speed limited by bus bandwidth
- 32 Gbps bus, Cisco 5600: sufficient speed for access and enterprise routers



bus

Switching via interconnection network

- overcome bus bandwidth limitations
- banyan networks, crossbar, other interconnection nets initially developed to connect processors in multiprocessor
- advanced design: fragmenting datagram into fixed length cells, switch cells through the fabric.
- Cisco 12000: switches 60 Gbps through the interconnection network



Output ports



- *buffering* required when datagrams arrive from fabric faster than the transmission rate
- *scheduling discipline* chooses among queued datagrams for transmission

Output port queueing



- buffering when arrival rate via switch exceeds output line speed
- *queueing (delay) and loss due to output port buffer overflow!*

Input port queuing



output port contention: only one red datagram can be transferred. (fabric speedup = 1)
lower red packet is blocked

one packet time later: green packet experiences HOL blocking

- fabric slower than input ports combined -> queueing may occur at input queues
  - *queueing delay and loss due to input buffer overflow!*
- Head-of-the-Line (HOL) blocking: queued datagram at front of queue prevents others in queue from moving forward

The Internet network layer

host, router network layer functions:



IP datagram format



how much overhead?
- 20 bytes of TCP
- 20 bytes of IP
- = 40 bytes + app layer overhead

IP fragmentation, reassembly

- network links have MTU (max.transfer size) - largest possible link-level frame
  - different link types, different MTUs
- large IP datagram divided (“fragmented”) within net
  - one datagram becomes several datagrams
  - “reassembled” only at final destination
  - IP header bits used to identify, order related fragments



IP fragmentation, reassembly

example:
- 4000 byte datagram
- MTU = 1500 bytes



IP addressing: introduction

- *IP address:* 32-bit identifier for host, router *interface*
- *interface:* connection between host/router and physical link
  - router's typically have multiple interfaces
  - host typically has one or two interfaces (e.g., wired Ethernet, wireless 802.11)
- *IP addresses associated with each interface*



$$223.1.1.1 = \underbrace{11011111}_{223}\ \underbrace{00000001}_{1}\ \underbrace{00000001}_{1}\ \underbrace{00000001}_{1}$$

IP addressing: introduction

Q: how are interfaces actually connected?

A: we'll learn about that in chapter 5, 6.



A: wired Ethernet interfaces connected by Ethernet switches

For now: don't need to worry about how one interface is connected to another (with no intervening router)

A: wireless WiFi interfaces connected by WiFi base station

IP addressing: introduction

Q: how are interfaces actually connected?

A: we'll learn about that in chapter 5, 6.



A: wired Ethernet interfaces connected by Ethernet switches

For now: don't need to worry about how one interface is connected to another (with no intervening router)

A: wireless WiFi interfaces connected by WiFi base station

Subnets

- IP address:
  - subnet part - high order bits
  - host part - low order bits
- *what's a subnet ?*
  - device interfaces with same subnet part of IP address
  - can physically reach each other ***without intervening router***



network consisting of 3 subnets

Subnets

recipe

- to determine the subnets, detach each interface from its host or router, creating islands of isolated networks
- each isolated network is called a *subnet*



Network Prefix: 223.1.1.0/24

<first address of a network>/<bit-length of the prefix>

Subnets

how many?



IP addressing: CIDR

- CIDR: Classless InterDomain Routing
  - subnet portion of address of arbitrary length
  - address format: a.b.c.d/x, where x is # bits in subnet portion of address

← subnet part → ← host part →

11001000 00010111 00010000 00000000

200.23.16.0/23

Q: How does a *host* get IP address?

- hard-coded by system admin in a file
  - Windows: control-panel->network->configuration->tcp/ip->properties
  - UNIX: /etc/rc.config
- DHCP: Dynamic Host Configuration Protocol: dynamically get address from as server
  - "plug-and-play"

IP addresses: how to get one?

Q: how does *network* get subnet part of IP addr?

A: gets allocated portion of its provider ISP's address space

ISP's block	11001000 00010111 00010000	00000000	200.23.16.0/20
Organization 0	11001000 00010111 00010000	00000000	200.23.16.0/23
Organization 1	11001000 00010111 00010010	00000000	200.23.18.0/23
Organization 2	11001000 00010111 00010100	00000000	200.23.20.0/23
...	.....	....	....
Organization 7	11001000 00010111 00011110	00000000	200.23.30.0/23

Q: how does an ISP get block of addresses?

A: ICANN: Internet Corporation for Assigned Names and Numbers http://www.icann.org/

- allocates addresses
- manages DNS
- assigns domain names, resolves disputes

Hierarchical addressing: route aggregation

hierarchical addressing allows efficient advertisement of routing information:



Hierarchical addressing: more specific routes

ISPs-R-Us has a more specific route to Organization 1



NAT: network address translation



all datagrams *leaving* local network have *same* single source NAT IP address: 138.76.29.7,different source port numbers

datagrams with source or destination in this network have 10.0.0/24 address for source, destination (as usual)

NAT: network address translation

- *motivation:* local network uses just one IP address as far as outside world is concerned:
  - range of addresses not needed from ISP: just one IP address for all devices
  - can change addresses of devices in local network without notifying outside world
  - can change ISP without changing addresses of devices in local network
  - devices inside local net not explicitly addressable, visible by outside world (a security plus)

NAT: network address translation

- *implementation*: NAT router must:
  - *outgoing datagrams: replace* (source IP address, port #) of every outgoing datagram to (NAT IP address, new port #)

    . . . remote clients/servers will respond using (NAT IP address, new port #) as destination addr
  - *remember (in NAT translation table)* every (source IP address, port #) to (NAT IP address, new port #) translation pair
  - *incoming datagrams: replace* (NAT IP address, new port #) in dest fields of every incoming datagram with corresponding (source IP address, port #) stored in NAT table

NAT: Private Network

- RFC 1918, RFC 4193
- A private network uses private IP Addresses:
  – not globally delegated
  – not allocated to any specific organization
  – IP packets addressed by them cannot be transmitted onto the public Internet
  – anyone may use these addresses without approval from a Regional Internet Registry (RIR).
  – A NAT (Network Address Translator) router or a proxy server must be used to connect a private network to the Internet

NAT: Private IPv4 Address Spaces

RFC 1918 name	**IP address range**	**number of addresses**	**Classful description**	**largest CIDR block (subnet mask)**	**host id size**	**mask bits**
24-bit block	10.0.0.0 - 10.255.255.255	16,777,216	Single class A network	10.0.0.0/8 (255.0.0.0)	24 bits	8 bits
20-bit block	172.16.0.0 - 172.31.255.255	1,048,576	16 contiguous class B network	172.16.0.0/12 (255.240.0.0)	20 bits	12 bits
16-bit block	192.168.0.0 - 192.168.255.255	65,536	256 contiguous class C network	192.168.0.0/16 (255.255.0.0)	16 bits	16 bits

NAT: network address translation



NAT: network address translation

- 16-bit port-number field:
  - 60,000 simultaneous connections with a single LAN-side address!
- NAT is controversial:
  - NAT traversal problem
  - routers should only process up to layer 3
  - violates end-to-end argument
    - NAT possibility must be taken into account by app designers, e.g., P2P applications
  - address shortage should instead be solved by IPv6

NAT traversal problem

- client wants to connect to server with address 10.0.0.1
  - server address 10.0.0.1 local to LAN (client can't use it as destination addr)
  - only one externally visible NATed address: 138.76.29.7
- *solution1:* statically configure NAT to forward incoming connection requests at given port to server
  - e.g., (123.76.29.7, port 2500) always forwarded to 10.0.0.1 port 25000



NAT traversal problem

- *solution 2:* Universal Plug and Play (UPnP) Internet Gateway Device (IGD) Protocol. Allows NATed host to:
  - learn public IP address (138.76.29.7)
  - add/remove port mappings (with lease times)

i.e., automate static NAT port map configuration



NAT traversal problem

- *solution 3:* relaying (used in Skype)
  - NATed client establishes connection to relay
  - external client connects to relay
  - relay bridges packets between to connections



ICMP: internet control message protocol

- used by hosts & routers to communicate network-level information
  - error reporting: unreachable host, network, port, protocol
  - echo request/reply (used by ping)
- network-layer "above" IP:
  - ICMP msgs carried in IP datagrams
- ICMP message: type, code plus first 8 bytes of IP datagram causing error

Type	Code	description
0	0	echo reply (ping)
3	0	dest. network unreachable
3	1	dest host unreachable
3	2	dest protocol unreachable
3	3	dest port unreachable
3	6	dest network unknown
3	7	dest host unknown
4	0	source quench (congestion control - not used)
8	0	echo request (ping)
9	0	route advertisement
10	0	router discovery
11	0	TTL expired
12	0	bad IP header

Traceroute and ICMP

- source sends series of UDP segments to dest
  - first set has TTL =1
  - second set has TTL=2, etc.
  - unlikely port number
- when *n*th set of datagrams arrives to nth router:
  - router discards datagrams
  - and sends source ICMP messages (type 11, code 0)
  - ICMP messages includes name of router & IP address
- when ICMP messages arrives, source records RTTs

stopping criteria:

- UDP segment eventually arrives at destination host
- destination returns ICMP "port unreachable" message (type 3, code 3)
- source stops



IPv6: motivation

- *initial motivation:* 32-bit address space soon to be completely allocated.
- additional motivation:
  - header format helps speed processing/forwarding
  - header changes to facilitate QoS
- *IPv6 datagram format:*
  - fixed-length 40 byte header
  - no fragmentation allowed

IPv6 datagram format

- *priority:* identify priority among datagrams in flow
- *flow Label:* identify datagrams in same "flow."
  (concept of "flow" not well defined).
- *next header:*
  - *options:* allowed, but outside of header, indicated by "Next Header" field
  - E.g., identify upper layer protocol for data



Other changes from IPv4

- *checksum*: removed entirely to reduce processing time at each hop
- *options:* allowed, but outside of header, indicated by "Next Header" field
- *ICMPv6:* new version of ICMP
  - additional message types, e.g. "Packet Too Big"
  - multicast group management functions

Transition from IPv4 to IPv6

- not all routers can be upgraded simultaneously
  - no "flag days"
  - how will network operate with mixed IPv4 and IPv6 routers?
- *tunneling:* IPv6 datagram carried as *payload* in IPv4 datagram among IPv4 routers



Tunneling



Tunneling



Graph abstraction



graph: G = (N,E)

N = set of routers = { u, v, w, x, y, z }

E = set of links ={ (u,v), (u,x), (v,x), (v,w), (x,w), (x,y), (w,y), (w,z), (y,z) }

aside: graph abstraction is useful in other network contexts, e.g., P2P, where *N* is set of peers and *E* is set of TCP connections

Graph abstraction: costs



$c(x,x')$ = cost of link (x,x')
e.g., $c(w,z) = 5$

cost could always be 1, or inversely related to bandwidth, or inversely related to congestion

cost of path $(x_1, x_2, x_3,\ldots, x_p) = c(x_1,x_2) + c(x_2,x_3) + \ldots + c(x_{p-1},x_p)$

key question: what is the least-cost path between u and z ?
routing algorithm: algorithm that finds that least cost path

Routing algorithm classification

Q: global or decentralized information?

global:

- all routers have complete topology, link cost info
- "link state" algorithms

decentralized:

- router knows physically-connected neighbors, link costs to neighbors
- iterative process of computation, exchange of info with neighbors
- "distance vector" algorithms

Q: static or dynamic?

static:

- routes change slowly over time

dynamic:

- routes change more quickly
  - periodic update
  - in response to link cost changes

A Link-State Routing Algorithm

Dijkstra's algorithm

- net topology, link costs known to all nodes
  - accomplished via "link state broadcast"
  - all nodes have same info
- computes least cost paths from one node ("source") to all other nodes
  - i.e., shortest-path tree
  - gives *forwarding table* for that node
- iterative: after k iterations, know least cost path to k dest.'s

notation:

- c(x,y): link cost from node x to y; = ∞ if not direct neighbors
- D(i): current value of cost of path from source to dest. i
- p(i): predecessor node along path from source to i
- (x,y): edge (i.e., link) from node x to y
- N': set of nodes whose least cost path definitively known
- Y': set of edges currently known to be in shortest-path tree rooted at "source" node

Iterative update:

- add a node from N – N', that has a shortest path from source node, using only nodes in N' as intermediates

Dijsktra's Algorithm

```
Initialization:
  N' = {u};       Y' = ∅ (empty set)
  for all nodes i
    if i adjacent to u
       then D(i) = c(u,i), p(i) = u
    else D(i) = ∞

Loop
  find k not in N' such that D(k) is a minimum
  add node k to N'
  add edge (p(k), k) to Y'
  update D(i) and p(i) for all i adjacent to k and not in N' :
     if D(k) + c(k,i) < D(i)
        then D(i) = D(k) + c(k,i) and p(i) = k
  /* new cost to i is either old cost to i or known
   shortest path cost to k plus cost from k to i */
until all nodes in N'
```

Dijkstra's algorithm: example

Step	N'	D(v) p(v)	D(w) p(w)	D(x) p(x)	D(y) p(y)	D(z) p(z)
0	u	7,u	3,u	5,u	∞	∞
1	uw	6,w		5,u	11,w	∞
2	uwx	6,w			11,w	14,x
3	uwxv				10,v	14,x
4	uwxvy					12,y
5	uwxvyz					

notes:
- Q: How Y' is updated step-by-step?
- construct shortest path tree by tracing predecessor nodes
- ties can exist (can be broken arbitrarily)



Dijkstra's algorithm: another example

Step	N'	D(v),p(v)	D(w),p(w)	D(x),p(x)	D(y),p(y)	D(z),p(z)
0	u	2,u	5,u	1,u	∞	∞
1	ux	2,u	4,x		2,x	∞
2	uxy	2,u	3,y			4,y
3	uxyv		3,y			4,y
4	uxyvw					4,y
5	uxyvwz					

Q: How Y' is updated step-by-step?



Dijkstra's algorithm: another example (cont.)

resulting shortest-path tree from u:



Q: Which result of Dijkstra's algorithm represents such shortest-path tree?

Y'

resulting forwarding table in u:

destination	link
v	(u,v)
x	(u,x)
y	(u,x)
w	(u,x)
z	(u,x)

Q: What is the algorithm of creating such forwarding table in the source node u using the results of Dijkstra's algorithm?

```
for each node i in N' but i != u
   j = i
   while (p(j) != u)
      j = p(j)
   end while
   add entry dest = i, link = (u, j) into fwd table
end for
```


Distance vector algorithm

Bellman-Ford equation (dynamic programming)

let

$d_x(y)$:= cost of least-cost path from x to y

then

$$d_x(y) = \min_i \{c(x,i) + d_i(y)\}$$

cost from neighbor i to destination y

cost to neighbor i

min taken over all neighbors i of x

Bellman-Ford example



clearly, $d_v(z) = 5$, $d_x(z) = 3$, $d_w(z) = 3$

B-F equation says:

$$
\begin{aligned}
d_u(z) &= \min \{ c(u,v) + d_v(z), \\
&\qquad c(u,x) + d_x(z), \\
&\qquad c(u,w) + d_w(z) \} \\
&= \min \{2 + 5, \\
&\qquad 1 + 3, \\
&\qquad 5 + 3\} = 4
\end{aligned}
$$

node achieving minimum, **node x**, is next hop in shortest path, used in the forwarding table at **node u** to the destination **node z**. i.e., at **node u**,

destination	link
…	
z	(u, x)
…	

Distance vector algorithm

- Node x maintains distance vector $\mathbf{D}_x = [D_x(j): j \in N]$ and link vector $\mathbf{L}_x = [L_x(j): j \in N]$ (forwarding table)
  - $D_x(j)$ = estimate of least cost from x to j
  - $L_x(j) = (x, n_x(j))$, node $n_x(j)$ is the neighboring node achieving least cost, i.e., next hop in the path with least cost from node x to node j
  - N: set of nodes in the network (maybe including node x itself)
- Meanwhile, node x also:
  - knows cost to each neighbor i: **c(x, i)**
  - maintains its neighbors' distance vectors. For each neighbor i, node x maintains $\mathbf{D}_i = [D_i(j): j \in N]$

Distance vector algorithm

key idea:

- from time-to-time, each node sends its own distance vector estimate to neighbors
- when x receives new DV estimate from neighbor, it updates its own DV using B-F equation:

  $D_x(j) \leftarrow \min_i\{c(x, i) + D_i(j)\}$ *for each node* $j \in N$,

  where min is taken over all neighbors i of node x

  $L_x(j) \leftarrow (x, k)$ *for each node* $j \in N$,

  where node k is the neighbor achieving the min
- under minor, natural conditions, the estimate $D_x(y)$ *converge to the actual least cost* $d_x(y)$

Distance vector algorithm

iterative, asynchronous:

each local iteration caused by:

- local link cost change
- DV update message from neighbor

distributed:

- each node notifies neighbors *only* when its DV changes
  - neighbors then notify their neighbors if necessary

each node:

wait for (change in local link cost or msg from neighbor)

recompute estimates

if DV to any dest has changed, *notify* neighbors

$D_x(y) = \min\{c(x,y) + D_y(y),\ c(x,z) + D_z(y)\}$
$= \min\{2+0\ ,\ 7+1\} = 2$

$D_x(z) = \min\{c(x,y) +$
$D_y(z),\ c(x,z) + D_z(z)\}$
$= \min\{2+1\ ,\ 7+0\} = 3$

node x table

from \ cost to	x	y	z
x	0	2	7
y	∞	∞	∞
z	∞	∞	∞

from \ cost to	x	y	z
x	0	2	3
y	2	0	1
z	7	1	0

node y table

from \ cost to	x	y	z
x	∞	∞	∞
y	2	0	1
z	∞	∞	∞

node z table

from \ cost to	x	y	z
x	∞	∞	∞
y	∞	∞	∞
z	7	1	0



time

$D_x(y) = \min\{c(x,y) + D_y(y),\ c(x,z) + D_z(y)\}$
$= \min\{2+0\ ,\ 7+1\} = 2$

$D_x(z) = \min\{c(x,y) +$
$D_y(z),\ c(x,z) + D_z(z)\}$
$= \min\{2+1\ ,\ 7+0\} = 3$

node x table

from \ cost to	x	y	z
x	0	2	7
y	∞	∞	∞
z	∞	∞	∞

from \ cost to	x	y	z
x	0	2	3
y	2	0	1
z	7	1	0

from \ cost to	x	y	z
x	0	2	3
y	2	0	1
z	3	1	0

node y table

from \ cost to	x	y	z
x	∞	∞	∞
y	2	0	1
z	∞	∞	∞

from \ cost to	x	y	z
x	0	2	7
y	2	0	1
z	7	1	0

from \ cost to	x	y	z
x	0	2	3
y	2	0	1
z	3	1	0

node z table

from \ cost to	x	y	z
x	∞	∞	∞
y	∞	∞	∞
z	7	1	0

from \ cost to	x	y	z
x	0	2	7
y	2	0	1
z	3	1	0

from \ cost to	x	y	z
x	0	2	3
y	2	0	1
z	3	1	0



time

Distance vector: link cost changes

link cost changes:

- node detects local link cost change
- updates routing info, recalculates distance vector
- if DV changes, notify neighbors



"good news travels fast"

t_0 : *y* detects link-cost change, updates its DV, informs its neighbors.

t_1 : *z* receives update from *y*, updates its table, computes new least cost to *x* , sends its neighbors its DV.

t_2 : *y* receives *z*'s update, updates its distance table. *y*'s least costs do *not* change, so *y* does *not* send a message to *z*.

Distance vector: link cost changes

link cost changes:



- node detects local link cost change
  - t_0: y detects the change
  - t_1: y updates Dy(x) as 6 via (y, z) because y now has Dz(x) = 5 and c(y, z) = 1 now
  - t_2: y notifies z and z updates Dz(x) as 7 via (z, y) because z now has Dy(x) = 6 and c(z, y) = 1
  - t_3: z notifies y and y updates Dy(x) as 8 via (y, z) because y now has Dz(x) = 7 and c(y, z) = 1
  - t_4: y notifies z and z updates Dz(x) as 9 via (z, y) because z now has Dy(x) = 8 and c(z, y) = 1
- *bad news travels slow* - "count to infinity" problem!
- 44 iterations before algorithm stabilizes
- A routing loop exists before algorithm stabilizes
  - At node y, a datagram to x is bounced between y and z

Hierarchical routing

scale: with 600 million destinations:

- can't store all dest's in routing tables!
- routing table exchange would swamp links!

administrative autonomy

- internet = network of networks
- each network admin may want to control routing in its own network

hierarchical routing:

- aggregate routers into regions, "autonomous systems" (AS)
- routers in same AS run same routing protocol
  - "intra-AS" routing protocol
  - routers in different AS can run different intra-AS routing protocol

gateway router:

- at "edge" of its own AS
- has link to router in another AS

Interconnected ASes



- forwarding table configured by both intra- and inter-AS routing algorithm
  - intra-AS sets entries for internal dests
  - inter-AS & intra-AS sets entries for external dests

Inter-AS tasks

- suppose router in AS1 receives datagram destined outside of AS1:
  - router should forward packet to gateway router, but which one?

AS1 must:

1. learn which dests are reachable through AS2, which through AS3
2. propagate this reachability info to all routers in AS1

job of inter-AS routing!



Intra-AS Routing

- also known as *interior gateway protocols (IGP)*
- most common intra-AS routing protocols:
  - RIP: Routing Information Protocol
  - **OSPF: Open Shortest Path First**
  - IGRP: Interior Gateway Routing Protocol (Cisco proprietary)

OSPF (Open Shortest Path First)

- "open": publicly available
- uses link state algorithm
  - LS packet dissemination
  - topology map at each node
  - route computation using Dijkstra's algorithm
- OSPF advertisement carries one entry per neighbor
- advertisements flooded to *entire* AS
  - carried in OSPF messages directly over IP (rather than TCP or UDP)
- *IS-IS routing* (Intermediate System to Intermediate System) protocol: nearly identical to OSPF

Hierarchical OSPF



Hierarchical OSPF

- *two-level hierarchy:* local area, backbone.
  - link-state advertisements only in area
  - each nodes has detailed area topology; only know direction (shortest path) to nets in other areas.
- *area border routers:* "summarize" distances to nets in own area, advertise to other Area Border routers.
- *backbone routers:* run OSPF routing limited to backbone.
- *boundary routers:* connect to other AS's.

Internet inter-AS routing: BGP

- BGP (Border Gateway Protocol): *the* de facto inter-domain routing protocol
  - "glue that holds the Internet together"
- BGP provides each AS a means to:
  - eBGP: obtain subnet reachability information from neighboring ASs.
  - iBGP: propagate reachability information to all AS-internal routers.
  - determine "good" routes to other networks based on reachability information and policy.
- allows subnet to advertise its existence to rest of Internet: *"I am here"*

BGP basics



- BGP session: two BGP routers ("peers") exchange BGP messages:
  - advertising *paths* to different destination network prefixes ("path vector" protocol)
  - exchanged over semi-permanent TCP connections
- when AS3 advertises a prefix to AS1:
  - AS3 *promises* it will forward datagrams towards that prefix
  - AS3 can aggregate prefixes in its advertisement

BGP basics: distributing path information



- using eBGP session between 3a and 1c, AS3 sends prefix reachability info to AS1.
  - 1c can then use iBGP do distribute new prefix info to all routers in AS1
  - 1b can then re-advertise new reachability info to AS2 over 1b-to-2a eBGP session
- when router learns of new prefix, it creates entry for prefix in its forwarding table.

Path attributes and BGP routes

- advertised prefix includes BGP attributes
  - prefix + attributes = "route"
- two important attributes:
  - AS-PATH: contains ASs through which prefix advertisement has passed: e.g., AS 67, AS 17
  - NEXT-HOP: indicates specific internal-AS router to next-hop AS. (may be multiple links from current AS to next-hop-AS)
- gateway router receiving route advertisement uses import policy to accept/decline
  - e.g., never route through AS x
  - *policy-based* routing

BGP route selection

- router may learn about more than 1 route to destination AS, selects route based on:
  1. local preference value attribute: policy decision
  2. shortest AS-PATH
  3. closest NEXT-HOP router: hot potato routing
  4. additional criteria

BGP messages

- BGP messages exchanged between peers over TCP connection
- BGP messages:
  - OPEN: opens TCP connection to peer and authenticates sender
  - UPDATE: advertises new path (or withdraws old)
  - KEEPALIVE: keeps connection alive in absence of UPDATES; also ACKs OPEN request
  - NOTIFICATION: reports errors in previous msg; also used to close connection

BGP routing policy



- A,B,C are *provider networks*
- X,W,Y are customer (of provider networks)
- X is *dual-homed:* attached to two networks
  - X does not want to route from B via X to C
  - .. so X will not advertise to B a route to C

BGP routing policy



- A advertises path AW to B
- B advertises path BAW to X
- Should B advertise path BAW to C?
  - No way! B gets no "revenue" for routing CBAW since neither W nor C are B's customers
  - B wants to force C to route to w via A
  - B wants to route only to/from its customers!