		REVISIONS						
	REV.		DESCRIPTION		REV. BY	NO.	DATE	APV'E
	03	+/- 0.05 TOLER ADDED KNURL	ANCE ADDED TO 19.05, GD&1 PITCH & DEPTH NOTE.	Γ ADDED.				
Ø11.90 MAX Ø11.58 MIN AFTER KNURL  M6 X 1.0 - 6H MINOR Ø5.21 / 5.05	1. [ = — Z	27 GROOVES 3 PLACES A—	19.05±0.05		⊅11.10 DRE KNUI	RL 5 A /	DETAIL SCALE	A A 4:1
NOTES:  1) DIN 933 CLASS 8.8 OR EQUIVALENT 2) KNURL (2 X 0.300" LONG)  KNURL PITCH AND DEPTH X: 3.0-4.0 mm	M	INA	RY		RLED SUF NOTE 2	RFACE		
Y: 1.5-2.0 mm Z: 0.20-0.4 mm	HRC:	RIAL: BON STEEL :22-32 S COMPLIANT	STANDARD TOLERANCES: (UNLESS OTHERWISE SPECIFIED)  UNITS: MM  X ± 0.40  X.X ± 0.40 X ± 2°  X.XX ± 0.25 X.X ± 1°	PART DESC		ILLE	RAWN BY: A.A.S	6.
	TRIV	H: LOW ZINC YALENT OMATE OR IVALENT	XXX ± 0.25 X.X ± 1° X.XXX ± 0.12 FILE NAME:  V1602091600	PART NUMI	6 X 1.0 K BER:	209	160 ED INSER	

SHEET SIZE: A

DO NOT SCALE PRINT

SHEET 1 OF 1