



香港中文大學(深圳)

The Chinese University of Hong Kong, Shenzhen

***INTRODUCTION TO COMPUTER SCIENCE:  
PROGRAMMING METHODOLOGY***

**TUTORIAL 3  
PYTHON BASICS**

# Outline

- 1. Data types, e.g. integer, string, boolean etc.
- 2. `print()` function.
- 3. Some arithmetic operators, e.g. `+`, `-`, `*`, `/`, `//`, `%`, `**` etc.
- 4. `input()` function.
- 5. `eval()` function.

# I.D

- There are several data types very often used:
  - i) **Integer**, e.g. 1, 19, -36...
  - ii) **Floating-point number**, e.g. 3.14159, 9.80...
  - iii) **String**, e.g. 'hello world', '123', 'www.cuhk.edu.cn'...
  - iv) **Boolean**, the value can only be **True** or **False**, e.g. 5 > 9, 'b' < 'a', 1 == '1'...
  - v) **List**, e.g. [1, 2, 3], ['h', 'e', 'l', 'l', 'o']...
- Assign some value of different types to a variable will make it become different data types.
- Using `type()` function you can check the data type of a variable.
- Data types can be forced to change if possible,  
e.g. `int(9.8)`->9, `str(123)`->'123', `float('9.8')`->9.8,  
`list('hello')`-> ['h', 'e', 'l', 'l', 'o'] ...

## 2. print() Function

- `print()` is a function-something you can realize some functionalities by calling it.
- The “`()`” is for you to put in some variables as input.
- You can use `help(print)` in shell to check how it is used.
- The parameters usually used in `print()` function is `print(value, sep, end)`.
  - “value” is the content you want to print out, e.g. `print(“hello”)`, `print(1,2,3)` etc.
  - “sep” is the symbol you use to separate many values, by default it is ‘ ’ if without mentioned. But you can change it to ‘,’, ‘-’ or ‘\*’ ... e.g. `print(1,2,3,sep=',')`.
  - “end” is the symbol you use to end you output, by default it is ‘\n’ if not being mentioned. You can change it to ‘ ’, ‘;’ or ‘end’ ... e.g. `print(“hello”, end='#')`.

```
>>> a=1
>>> b=2
>>> c=3
>>> print(a, b, c)
1 2 3
>>> print(a, b, c, sep=';')
1;2;3
>>> print(a, b, c, end=';')
1 2 3;
```

## 2.

- “d” in `print('%d'%v)` means the variable v is integer type;  
 “f” in `print('%f'%v)` means the variable v is a floating point number;  
 “s” in `print('%s'%v)` means the variable v is a string.
- Determine the space for the variable to be shown:  
 the number('8') before 'd' in `print('%8d'%v)` means 8 spaces for the integer v;  
 the number('7.2') before 'f' in `print('%7.2f'%v)` means 7 spaces for the floating point number v while keeping the 2 digits after decimal point '.'.
- To align the result leftward, add the symbol '-': `print('%-8d'%v)` will make the integer v printed from the left of the 8 spaces. Without '-' will align the result rightward.

```
>>> a=1.0
>>> print('%d'%a)
1
>>> print('%f'%a)
1.000000
>>> print('%s'%a)
1.0
```

```
>>> a=1
>>> print('%8d'%a)
      1
>>> print('%7.2f'%a)
    1.00
```

```
>>> a=1
>>> b=2
>>> print('%-8d\n%-8d'%(a,b))
1
      2
```


## 2. F F B

➤ To print many values within some predefined formats:

```
print('%s has %d petals and is worth %.2f yuan a bunch.'%(FlowerName,  
NumOfPetal, Price ))
```

where the variable 'FlowerName' is the name of a flower(string type),  
'NumOfPetal' is the number of petals of the flower(integer type),  
'Price' is the price of the flower (floating point number).


```
>>> a=1  
>>> b=2  
>>> print(' a+b' )  
a+b  
>>> print(a+b)  
3  
>>> print(' a is %d; b is %d; a+b=%d'%(a,b,(a+b)))  
a is 1; b is 2; a+b=3  
>>> print(' a is',a,'; b is',b,'; a+b=%d'%(a+b))  
a is 1 ; b is 2 ; a+b=3
```



- Write a program that display the following table (8 spaces for each number and they are aligned leftward):

a	b	a ** b
1	2	1
2	3	8
3	4	81
4	5	1024
5	6	15625

### 3.A



➤ Some arithmetic operators often used: Addition +, Subtraction -, Multiplication \*, Division /, Modulus(Remainder) %, Exponent(Power) \*\*, Floor division // etc.

➤ Order of operations(Operator precedence):


- ✓ Parenthesis are always with highest priority
- ✓ Power
- ✓ Multiplication, division and remainder
- ✓ Addition and subtraction
- ✓ Left to right



➤ Augmented assignment operators: “x+=1” means “x=x+1”, “x//=10” means “x=x//10”, similar for “x-=1”, “x%=10”, “x\*\*=2”,...



## 3.A



➤ Some operators for string type variables:

+: Concatenation - Adds values on either side of the operator

\*: Repetition - Creates new strings, concatenating multiple copies of the same string

[ ]: Slice - Gives the character from the given index

[ : ]: Range Slice - Gives the characters from the given range

```
>>> a='test1'
>>> b='test2'
>>> a+b
'test1test2'
>>> a*3
'test1test1test1'
>>> a[0]
't'
>>> a[0:3]
'tes'
>>> a*b
Traceback (most recent call last):
  File "<pyshell#168>", line 1, in <module>
    a*b
TypeError: can't multiply sequence by non-int of type 'str'
>>> a**3
Traceback (most recent call last):
  File "<pyshell#169>", line 1, in <module>
    a**3
TypeError: unsupported operand type(s) for ** or pow(): 'str' and 'int'
```

## 4. F

- `input()` is a function used for instructing the users to input a string for a variable. Notice that the data type that `input()` function return is a **string**, that is, if you assign the result to a variable e.g. `v=input()`, then `v` is a string data type.
- You can use a string as a variable for the `input()` function as an instruction, e.g. `input("Please input a number:")`

```
>>> a=input('Please enter a number: ')
Please enter a number: 2
>>> a
'2'
>>> type(a)
<class 'str'>
```

## 5. FUNCTIONS

- `eval()` is a function used to parse and evaluate the Python expression (a string) you put as a variable for the `eval()` function, i.e. as if the “ of the expression is taken away.
- `eval()` is often used together with `input()` in order to change the string, which is returned by `input()` function, into the data type you want, e.g. `N=eval(input())` will make the value passed to variable `N` be an integer, a floating-point number or a boolean if you input 9, 3.14 or `3>5` respectively, for instance.

```
>>> a=input('Please enter a number: ')
Please enter a number: 1
>>> type(a)
<class 'str'>
>>> b=eval(input('Please enter a number: '))
Please enter a number: 1
>>> type(b)
<class 'int'>
```

```
>>> input('Please enter a number:')
Please enter a number:test
'test'
>>> eval(input('Please enter a number: '))
Please enter a number: test
Traceback (most recent call last):
  File "<pyshell#199>", line 1, in <module>
    eval(input('Please enter a number: '))
  File "<string>", line 1, in <module>
NameError: name 'test' is not defined
```

## 5. F

➤ Example: what are the outputs of the following cases?

i)

```
a=1
b=3
c='a+b'
d=eval('a+b')
print(c)
print(d)
```

ii)

```
a=2
aa=4
aaa=8
b=eval('a+aa')
print(b)
```


□□□□□□□□□□2:C□□□□□□□□C□□□□□□□□F□□□□□□□□□□

- Write a program that reads a Celsius degree from the console and converts it to Fahrenheit and displays the result. The formula for the conversion is as follows:

$$\text{fahrenheit} = (9/5) * \text{celsius} + 32$$

Here is a sample:

```
Enter a degree in Celsius:43
Celsius degree 43 equals to Fahrenheit degree 109.4.
```



- Write a program that reads in the radius and length of a cylinder and computes the area and volume using the following formulas:

$$\text{area} = \text{radius} * \text{radius} * \pi$$

$$\text{volume} = \text{area} * \text{length}$$

Here is a sample:

```
Enter radius of the cylinder:12
Enter length of the cylinder:33
The area is:452.39
The volume is:14928.85
```

- Write a program that reads an integer between 0 and 1000 and adds all the digits in the integer. For example, if an integer is 932, the sum of all its digits is 14. (Hint: Use the % operator to extract digits, and use the // operator to remove the extracted digit. For instance,  $932 \% 10 = 2$  and  $932 // 10 = 93$ .)

## Here is a sample:

Enter a number between 0 and 1000:932  
Sum up all the digits as: 14

- Write a program that prompts the user to enter the minutes (e.g., 1 billion), and displays the number of years and days for the minutes. For simplicity, assume a year has 365 days.

## Here is a sample:

Enter the number of minutes: 1000000000  
That minutes will equal to 1902 years and 214 days.



- Suppose you save \$100 each month into a saving account with monthly interest rate 0.417%. That is, i) after the first month, the value in the account becomes  $100 * (1 + 0.00417) = 100.417$ ; ii) after the second month, the value in the account becomes  $(100 + 100.417) * (1 + 0.00417) = 201.252$ ; iii) after the third month, the value in the account becomes  $(100 + 201.252) * (1 + 0.00417) = 302.507$ ; and so on. Write a program that prompts the user to enter a monthly saving amount and displays the account value after the sixth month.

## Here is a sample:

Enter the monthly saving amount:\$100

After the sixth month, the account value is:\$608.82