

—— // ZPWR // ——

zpwr
v48.9.3

THE ENCYCLOPEDIA

a hacker's field guide to the terminal · 464+ verbs

2026-07-18

MenkeTechnologies

—— MENKETECHNOLOGIES ——

Contents

Chapter 1 — The Red Pill	3
Chapter 2 — Navigation Protocol	7
Chapter 3 — The Git Dimension	12
Chapter 4 — The Search Engine	21
Chapter 5 — Editor Mastery	25
Chapter 6 — Performance Cult	32
Chapter 7 — Health & Diagnostics	35
Chapter 8 — Environment Mastery	44
Chapter 9 — The Janitor's Closet	49
Chapter 10 — Build System	54
Chapter 11 — Monitoring & Automation	62
Chapter 12 — Utility Arsenal	68
Chapter 13 — emacs Dimension	77
Chapter 14 — tmux Warfare	82
Chapter 15 — Network & Containers	87
Chapter 16 — The Logging System	92
Chapter 17 — Introspection	96
Chapter 18 — Installation & Reset	103
Chapter 19 — Batch Operations	106
Chapter 20 — Forgit Deep Dive	111
Chapter 21 — zpw Environment Variables	116
Chapter 22 — Creative Tools	123
Chapter 23 — Exercism & External	129
Chapter 24 — Tips, Tricks & Easter Eggs	131
Chapter 25 — The Complete Reference	136

Chapter 26 — powerlevel10k & Instant Prompt	138
Chapter 27 — zinit & Plugin System	143
Chapter 28 — zsh Internals	152
Chapter 29 — fzf Architecture	159
Chapter 30 — tmux Deep Dive	163
Chapter 31 — vim Deep Dive	168
Chapter 32 — temprs — Temporary File Stack Manager	171
Chapter 33 — Isofrs — Enhanced Isuf	173
Chapter 34 — eza — The Modern Is	175
Chapter 35 — bat — cat With Wings	177
Chapter 36 — fd-find — Find Replacement	180
Chapter 37 — ripgrep — grep At Light Speed	182
Chapter 38 — neovim	185
Chapter 39 — perl In zpw	187
Chapter 40 — Hidden Subsystems	190
Chapter 41 — Quality Assurance	194
Chapter 42 — Colorization Stack	195
Chapter 43 — The End	198
Appendix A — Keybinding Reference	200
Appendix B — Complete Keybinding Dump	213

Chapter 1 – The Red Pill

Welcome to the Machine

You found it. The rabbit hole. ZPWR is not a dotfiles repo. It is not a “framework.” It is a fully integrated shell operating system that happens to run inside your terminal.

What Is Zpwr?

A 512-verb command dispatcher built on top of zsh, tmux, vim/nvim, fzf, and git. Every verb is a surgical tool. Every keybinding is a weapon. Every alias is a shortcut through the matrix.

The Philosophy

1. Verbs, not scripts. Everything is `zpwr <verb>`.
2. Discoverability. Tab completion on everything.
3. Symmetry. `vim*` and `emacs*` verbs mirror each other.
4. Speed. Compiled `zwc` files. Benchmarked startup.
5. No magic. Read the source. It is all zsh.

The Directory Tree

```
$ZPWR ..... root of the kingdom
$ZPWR_ENV ..... env vars and shell init
$ZPWR_SCRIPTS ..... executable scripts
$ZPWR_AUTOLOAD ..... autoloaded functions
$ZPWR_LOCAL ..... local config (gitignored)
$ZPWR_INSTALL ..... installer scripts
$ZPWR_TMUX ..... tmux configuration
$ZPWR_TEST ..... test suite
```

Your First Command

```
zpwr about    # behold the banner
zpwr help     # list every verb in color
```

Pro tip: `zpwr` is aliased to many short forms. Type `zpwr <tab>` and let the completions wash over you.

WARNING: Side effects may include mass alias adoption, involuntary tab-completing in other people’s terminals, and an irrational hatred of vanilla bash.

Your First 5 Minutes

You just installed `zpwr`. The terminal blinks. What now? Here is your survival kit for the first 300 seconds.

Step 1: See The Banner

```
zpwr about      # the ASCII art welcome screen
zpwr banner     # same thing, different alias
zpwr bannercounts # banner + environment statistics
```

Step 2: Count Your Arsenal

```
zpwr environmentcounts # how many aliases, functions, etc.
```

This prints a breakdown of your loaded shell environment: aliases, functions, builtins, parameters, completions. If the numbers are big, congratulations. You are armed.

Step 3: Discover The Verbs

```
zpwr help      # colored list of ALL verbs
zpwr verbs     # fzf fuzzy search through verbs
```

The verbs verb is your panic button (alias: subcommandsfzf). Forgot what a command is called? Fuzzy search it. This pipes every verb and its description into fzf. Type a few characters. Watch the list collapse. Hit enter. Execute.

Step 4: Verify Your Environment

```
zpwr doctor     # run environment health check
zpwr envvars    # list all zpwr env vars
zpwr colortest  # verify your terminal colors
zpwr colortest256 # the full 256-color palette
```

Step 5: Tab Complete Everything

Type zpwr and press <tab>. You will see 512 verbs. Type zpwr git and press <tab>. Filtered to git verbs. Type zpwr vim and press <tab>. Filtered to vim verbs. The completion system knows every verb. Trust it.

If you only remember one command from this page: zpwr verbs It is the cheat code to everything else.

The Anatomy of a Verb

Every zpwr command follows one sacred pattern: zpwr <verb> [args...]

How Dispatch Works

When you type zpwr filesearch, here is what happens: 1. The zpwr function receives “filesearch” as \$1 2. It looks up ZPWR_VERBS[filesearch] in the verb table 3. The table entry maps to a function or alias 4. That function is invoked with any remaining args.

The Verb Table

The associative array ZPWR_VERBS is the brain. Each entry has the format:

```
ZPWR_VERBS[verb]='function_or_alias=description'
```

Many Names, One Function

Verbs often have aliases for muscle memory:

```
zpwr forward = zpwr f    = zpwr fwd
zpwr reverse = zpwr r    = zpwr rvs = zpwr cdup
zpwr github  = zpwr gh   = zpwr mygithub
zpwr repo    = zpwr zp   = zpwr zpwr
```

Tab Completion In Action

zpwr git<tab> # shows: gitcommit, gitconfig, gitsearch... zpwr vim<tab> # shows: vimall, vimrecent, vimctags...
zpwr home<tab> # shows: home, homeenv, homelocal... zpwr forgit<tab> # shows: forgitadd, forgitlog, forgitdiff...

Inspect The Table Yourself

```
zpwr subcommands      # dump all verbs to stdout
zpwr verbs            # fuzzy search verbs with fzf
zpwr verbscount        # how many verbs exist
```

The Edit Suffix Pattern

Many verbs come in pairs: filesearch -> open file after selection filesearchedit -> type into command line for editing The “edit” variant puts the result on your command line instead of executing immediately. Power and precision.

Configuring Your Rig

Your terminal is a cockpit. These are the dials.

The Four Config Sessions

Each of these opens a curated vim session with the relevant config files already loaded in buffers:

```
zpwr brc    # shell aliases file vim session
```

Opens `$ZPWR_LOCAL/tokens.sh` and related files this is where YOUR personal aliases live.

```
zpwr zrc    # zshrc vim session
```

Opens the zshrc and related zsh configs the source of all shell initialization.

```
zpwr vrc    # vimrc/init.vim vim session
```

Opens vim/nvim config files your editor’s soul laid bare.

```
zpwr trc    # tmux.conf vim session
```

Opens tmux configuration pane and window management settings.

The Tokens File

```
zpwr tokens      # vim the .tokens.sh file
zpwr vimtokens   # same thing, explicit vim
zpwr emacs tokens # same thing, emacs edition
```

Located at `$ZPWR_LOCAL/.tokens.sh` This file is gitignored. Put secrets and custom aliases here. Never commit this file. It is YOUR local override.

Editor Commands

```
zpwr edit        # launch $EDITOR
zpwr editor      # same thing
zpwr vimconfig   # edit all zpwr configs in vim
```

The Full Config Stack

`$ZPWR_LOCAL/.tokens.sh` ... your aliases and secrets `$ZPWR_ENV/.zpwr_env.sh` .. env vars and paths

```
~/.zshrc ..... shell entry point
~/.vimrc / init.vim ..... editor config
~/.tmux.conf ..... tmux config
```

Think of it as: brc for shell, zrc for zsh, vrc for vim, trc for tmux. Four letters, four kingdoms.

Chapter 2 – Navigation Protocol

Directory Warfare

In the filesystem, speed is survival. Typing full paths is for people who have given up on life.

Forward And Reverse

```
zpwr forward <dir> # cd into a child directory
zpwr f <dir>       # same thing, shorter
zpwr fwd <dir>     # same thing, medium length
```

```
zpwr reverse <dir> # cd UP the tree to a parent matching <dir>
zpwr r <dir>       # same thing, one letter
zpwr rvs <dir>     # same thing, three letters
zpwr cdup <dir>    # same thing, cd-up style
```

Example: you are in `~/code/myproject/src/lib/utls`

```
zpwr r myproject # jumps UP to ~/code/myproject
```

No more `../..../..` chains. Navigate like a human.

Basic Cd

```
zpwr cd <path> # cd to directory arg
```

Seems redundant but integrates with zpwr's dispatch.

Z: Freccy Jumping

```
zpwr z <query> # jump to freccy-ranked directory
```

Z tracks where you go. The more you visit a directory, the higher it ranks. Type a fragment, land at the top match.

```
zpwr zcd # fzf list of z-ranked dirs, pick one
```

When you cannot remember the exact fragment, zcd shows you the full ranked list in fzf.

Practical Combos

zpwr z proj # land in your most-visited “proj” dir
zpwr r src # climb back up to the “src” parent
zpwr f tests # dive into the “tests” child.

The pattern is: z for teleportation, f for descent, r for ascent. Three directions. Total coverage.

PROTIP: If you are still typing `cd ../../..`, this is your intervention.

Home Base Operations

Every zpwr directory has a one-word teleporter. No paths. No thinking. Just say where.

The Home Verb Family

```
zpwr home          # cd $ZPWR (the root)
zpwr homelocal     # cd $ZPWR_LOCAL
zpwr homescripts   # cd $ZPWR_SCRIPTS
zpwr homeenv       # cd $ZPWR_ENV
zpwr homeinstall   # cd $ZPWR_INSTALL
zpwr homeautoload  # cd $ZPWR_AUTOLOAD
zpwr homeautoloadcommon # cd $ZPWR_AUTOLOAD_COMMON
zpwr homecomps     # cd $ZPWR_COMPS
zpwr hometest      # cd $ZPWR_TEST
zpwr hometmux      # cd $ZPWR_TMUX
zpwr homeexercism  # cd $HOME/Exercism
```

What Lives Where

```
home ..... the zpwr repo root, start of everything
homelocal ..... gitignored personal configs and tokens
homescripts ..... executable shell scripts
homeenv ..... environment variables and init files
homeinstall ..... installer scripts for dependencies
homeautoload ..... autoloaded functions (the engine room)
```

Homeautoloadcommon platform-independent autoloads.

```
homecomps ..... zsh completion definitions
hometest ..... test suite files
hometmux ..... tmux configuration files
```

Example Workflow

You want to edit an autoload function:

```
zpwr homeautoloadcommon
```

Now you are in the autoload directory # ls, grep, edit to your heart's content.

You want to check your local tokens:

```
zpwr homelocal
```

Lands you right next to .tokens.sh.

Every home* verb is a bookmark you never need to set. The bookmarks are built into the system.

Named Directories

Zsh has a secret weapon most people never learn: named directories. They turn env vars into tilde paths.

How It Works

When you do `hash -d ZPWR=$ZPWR`, zsh registers a named directory. Now `~ZPWR` expands to `$ZPWR` everywhere: in `cd`, in tab completion, in prompt, in arguments.

Zpwr's Named Directories

```
~ZPWR ..... $ZPWR root
~ZPWR_SCRIPTS ..... $ZPWR_SCRIPTS
~ZPWR_AUTOLOAD ..... $ZPWR_AUTOLOAD
~ZPWR_ENV ..... $ZPWR_ENV
~ZPWR_LOCAL ..... $ZPWR_LOCAL
~ZPWR_INSTALL ..... $ZPWR_INSTALL
~ZPWR_TMUX ..... $ZPWR_TMUX
~ZPWR_TEST ..... $ZPWR_TEST
~ZPWR_COMPS ..... $ZPWR_COMPS
```

What This Means In Practice

Your prompt might show: `~ZPWR_AUTOLOAD/common` instead of the full path. You can type:

```
cd ~ZPWR_SCRIPTS and it just works
vim ~ZPWR_ENV/.zpwir_env.sh tilde paths everywhere
```

Tab Completion With Tilde

Type `cd ~ZPWR<tab>` and watch zsh expand the options: `~ZPWR` `~ZPWR_SCRIPTS` `~ZPWR_ENV` `~ZPWR_LOCAL` ... This works in any command, not just `cd`.

The Mechanism

Zsh option `AUTO_NAME_DIRS` turns any exported scalar parameter into a named directory automatically. ZPWR exports its directory variables, so they become named directories for free.

Think of named directories as human-readable symlinks that live in your shell's brain instead of the filesystem. No files created. No cleanup needed. Pure memory.

Quick Jumps

The `home*` verbs land you in zpwr directories. These verbs land you in the ecosystem around zpwr.

zpwr Internals

```
zpwr scripts      # cd to scripts directory
```

Shortcut alias: `zs`.

```
zpwr autoload     # cd to autoload directory
```

Shortcut alias: `zal`.

```
zpwr completions  # cd to completion directory
zpwr comps        # same thing
```

Shortcut alias: `zco`.

Plugin Ecosystem

```
zpwr plugins      # cd to $ZSH_CUSTOM/plugins
```

Shortcut alias: `zpl` This is where oh-my-zsh custom plugins live. Your third-party zsh plugins are neighbors here.

```
zpwr forked      # cd to $ZPWR_FORKED_DIR
zpwr fp          # same thing
```

Forked repos that `zpwr` depends on live here. Useful when you need to hack on a dependency.

Special Directories

```
zpwr hidden      # cd to $ZPWR_HIDDEN_DIR
```

The hidden directory. Dot-prefixed internal state.

```
zpwr repo        # cd to $ZPWR_REPO_NAME
zpwr zp          # same thing
zpwr zpwr        # same thing (yes, zpwr zpwr)
```

The Navigation Cheat Sheet

Use case Verb ——— —

```
Edit a script ..... zpwr scripts
Fix a completion ..... zpwr comps
```

Add an autoload function .. `zpwr autoload`.

```
Debug a plugin ..... zpwr plugins
Patch a fork ..... zpwr forked
```

Each of these is one verb, zero path typing, and instant teleportation to where the work is.

Navigation Verbs

// 39 ways to get where you are going //

Navigate the filesystem, ZPWR directories, and frequency ranked locations with precision.

Directory Movement

```
zpwr cd          # cd to directory arg
zpwr f           # cd to directory arg
zpwr forward     # cd to directory arg
zpwr fwd         # cd to directory arg
zpwr cdup        # cd up tree to directory arg
zpwr r           # cd up tree to directory arg
zpwr reverse     # cd up tree to directory arg
zpwr rvs         # cd up tree to directory arg
zpwr catcd       # cat and cd to first dir
zpwr clone       # clone and cd to arg
```

zpwr Home Directories

```
zpwr home          # go to $ZPWR
zpwr homeautoload  # go to $ZPWR_AUTOLOAD
zpwr homeautoloadcommon # go to $ZPWR_AUTOLOAD_COMMON
zpwr homecomps     # go to $ZPWR_COMPS
zpwr homeenv       # go to $ZPWR_ENV
zpwr homeexercism  # cd to $HOME/Exercism
zpwr homeinstall   # go to $ZPWR_INSTALL
zpwr homelocal     # go to $ZPWR_LOCAL
zpwr homescripts   # go to $ZPWR_SCRIPTS
zpwr hometest      # go to $ZPWR_TEST
zpwr hometests     # go to $ZPWR_TEST
zpwr hometmux      # go to $ZPWR_TMUX
```

zpwr Subdirectories

```
zpwr autoload      # cd to autoload directory
zpwr comps         # cd to completion directory
zpwr completions   # cd to completion directory
zpwr forked        # cd to $ZPWR_FORKED_DIR
zpwr fp           # cd to $ZPWR_FORKED_DIR
zpwr hidden        # go to $ZPWR_HIDDEN_DIR
zpwr plugins       # cd to $ZSH_CUSTOM/plugins
zpwr repo          # cd to $ZPWR_REPO_NAME
zpwr scripts       # cd to scripts directory
zpwr web           # cd to web dir
zpwr zp            # cd to $ZPWR_REPO_NAME
zpwr zpwr          # cd to $ZPWR_REPO_NAME
zpwr zpz           # cd to repo, checkout, rebase, push
```

Frecency & fzf

```
zpwr z            # cd to z frecency ranked dir
zpwr zcd          # list then cd to z ranked dir
zpwr dirsearch    # cd to a sub dir via fzf
```

Chapter 3 – The Git Dimension

Git Basics

Git is already a language. ZPWR makes it a dialect you can actually speak without consulting the man page.

The Commit Pipeline

```
zpwr gitcommit "your message here"
```

This is not just git commit. It does: git add -> git commit -> git push All in one verb. The full gacp (git add commit push). Because who commits without pushing? Cowards.

Config And Ignores

```
zpwr gitconfig          # edit git config file
zpwr gitglobalconfig    # same thing, explicit name
zpwr gitignore          # edit .git/info/exclude (local)
zpwr gitignores         # edit global git ignores file
zpwr gitglobalignores   # same as gitignores
```

Stash And Diff (VIA Forgit)

ZPWR delegates interactive stash and diff to forgit:

```
zpwr forgitdiff          # fzf-powered git diff viewer
zpwr forgitstash         # fzf-powered stash browser
```

See page 13 for the full forgit arsenal.

Remote Operations

```
zpwr gitremotes          # list all git remotes
zpwr gitdir              # check if pwd is a git dir
```

Tags

```
zpwr gitedittag          # print tag to $BUFFER
zpwr gitupdatetag        # print tag and latest msg to $BUFFER
```

Real-world Example

You just finished a feature. Ship it:

```
zpwr gitcommit "add quantum flux capacitor"
```

Stages everything, commits with message, pushes. # One line. Done. Next feature.

Need to check your git config:

```
zpwr gitconfig
```

Opens it in \$EDITOR. Fix, save, done.

Git verbs follow the pattern: git + action noun. If you can name it, zpwr probably has a verb for it.

GitHub Integration

GitHub is not a website. It is an API with a website. ZPWR treats it accordingly.

Create And Destroy

```
zpwr githubcreate    # create a remote GitHub repo
zpwr hc              # same thing, two letters
```

Creates a repo on GitHub from your current directory. Sets up the remote. Ready to push.

```
zpwr githubdelete    # delete a remote GitHub repo
zpwr hd              # same thing, two letters
```

This is permanent. It asks for confirmation. But once confirmed, the repo is gone. Poof.

Browse Your Github

```
zpwr github          # open your GitHub profile in browser
zpwr gh              # same thing
zpwr mygithub         # same thing
```

Opens your profile page. Quick ego check.

```
zpwr githubzpwr      # open zpwr repo on GitHub
zpwr ghz              # same thing
```

Jump straight to the zpwr source. File issues. Star it. You know you want to.

Contribution Stats

```
zpwr githubcontribcount # count GitHub contribs in last year
```

Tells you how green your contribution graph is. The number that keeps you pushing commits at 2 AM.

Reveal: The Browser Shortcut

```
zpwr reveal          # show current repo in browser
```

You are in a git repo. You want to see it on GitHub. One word. Browser opens. You are there.

Workflow Example

Start a new project from scratch:

```
mkdir new-project && cd new-project
git init
zpwr hc           # repo created on GitHub
zpwr gitcommit "initial commit"
zpwr reveal       # admire it in the browser
```

From zero to pushed repo in four commands. That is the GitHub integration promise.

Git Archaeology

The past is not dead. It is not even past. It is stored in `.git/objects` and `zpwr` can dig it up.

Searching The Log

```
zpwr gitsearch      # search for regex in git log
```

Uses `zfz` to grep through your entire commit history. That one commit where you “fixed the thing”? Found.

```
zpwr gitcommits     # search git commits with fzf
```

Interactive commit browser. Preview diffs inline. Like `git log` but you can actually find things.

Counting Commits

```
zpwr gitcommitcount # total number of commits
```

Just a number. But what a number. The sum total of your decisions in this repo.

Contribution Analysis

```
zpwr gitcontribcount # contributions by author
```

Who committed the most? The leaderboard of blame.

```
zpwr gitcontribcountdirs # contributions across dirs
```

Same analysis but across multiple repositories. Useful for org-wide contribution audits.

```
zpwr gitcontribcountlines # lines contributed by author
```

Lines of code per author. The metric that lies to you. But it is a fun lie.

Size Analysis

```
zpwr gittotallines   # total line count of git files
```

How big is this repo, really? Now you know.

```
zpwr gitlargest      # largest files in git history
```

Shows the biggest blobs stored by git, descending. That 50MB binary someone committed in 2019? There it is. Now you know what to purge (see page 12).

Dig Session Example

Who wrote the most code in this repo?

```
zpwr gitcontribcount
```

What is eating all the disk space?

```
zpwr gitlargest
```

Find that commit about the database migration:

```
zpwr gitsearch
```

Type "migration" in fzf. There it is.

Git Surgery

Sometimes you need to rewrite history. Not the geopolitical kind. The git kind. These are destructive operations. Use with intent.

Clearing The Cache

```
zpwr gitclearcache    # clear old git refs and objects
```

Runs garbage collection on git's internal state. Prunes unreachable objects, packs loose refs. Your .git directory gets a deep clean.

Removing Commits

```
zpwr gitclearcommit   # remove matching commits from history
```

This is filter-branch territory. Rewrites history. Force push required after. Use when someone committed passwords, API keys, or that embarrassing commented-out code block.

Removing Files From All History

```
zpwr gitclearfile     # rm file from all git refs and objects
```

Nuclear option for files. That 200MB video someone committed in 2020? This removes it from every commit that ever existed. Your repo size drops. Your clone time drops. Your blood pressure drops.

Email Surgery

```
zpwr gitemail         # change email with git filter-branch
```

Changes both author and committer email across history.

```
zpwr gitaemail        # change author email only
```

When you committed with your personal email at work.

```
zpwr gitcemail        # change committer email only
```

When the committer field has the wrong identity.

When To Use These

Scenario: you committed with wrong@email.com.

```
zpwr gitemail
```

Follow the prompts to fix every commit.

Scenario: .env file in git history with secrets.

```
zpwr gitclearfile
```

Purges it from every ref and object.

REMEMBER: These rewrite history. Coordinate with your team before force pushing. Or do not coordinate and watch the chaos unfold.

Forgit: Git on Steroids

Forgit wraps common git operations with fzf previews. Every action gets a live preview pane. Every choice is informed. No more blind git commands.

Staging And Unstaging

```
zpwr forgitadd          # fzf-powered git add
```

Shows unstaged files with inline diffs in the preview. Select files with tab. Enter to stage. Visual staging.

```
zpwr forgitreset        # fzf-powered git reset HEAD
```

The reverse of forgitadd. Unstage files visually.

Viewing Changes

```
zpwr forgitdiff          # fzf-powered git diff viewer
```

Browse changed files. Preview shows colorized diffs. Side-by-side comparison in your terminal.

```
zpwr forgitlog           # fzf-powered git log
```

Commit history with preview. See the diff for each commit without leaving the log view. Beautiful.

Stash Operations

```
zpwr forgitstash         # fzf-powered stash browser
```

Lists stashes. Preview shows what each stash contains. Pick one, apply it. No more “was it stash@{3}?”

Cleanup

```
zpwr forgitclean          # fzf-powered git clean
```

Shows untracked files. Select which to delete. Preview before you destroy. Civilized cleanup.

```
zpwr forgitrestore        # fzf-powered git restore
```

Discard changes to selected files. With preview.

Gitignore Management

```
zpwr forgitignore      # browse gitignore templates
zpwr forgitignoreget   # download a gitignore template
zpwr forgitignorelist  # list available templates
zpwr forgitignoreupdate # update gitignore templates
zpwr forgitignoreclean # clean gitignore cache
```

Extras

```
zpwr forgitinfo      # show git repo information
zpwr forgitwarn      # show forgit warnings
```

Forgit turns git into a visual experience. Every forgit* verb is a regular git command with eyes.

Git Battalion Operations

One repo is easy. Twenty repos is a war. These verbs let you run commands across all of them.

The General: Foralldir

```
zpwr gitforalldir <cmd> # run cmd in ALL git dirs
```

Walks every git directory it can find and runs your command inside each one. The nuclear option.

Cached Repos

```
zpwr gitrepoexec <cmd> # run cmd in cached git dirs
```

Uses the cached list of known repos. Faster than foralldir because it does not rescan the filesystem.

Clean Vs Dirty Targeting

```
zpwr gitreposcleanexec <cmd> # refresh + run in clean repos
zpwr gitreposcleancacheexec <cmd> # run in cached clean repos
zpwr gitreposdirtyexec <cmd> # refresh + run in dirty repos
zpwr gitreposdirtycacheexec <cmd> # run in cached dirty repos
```

Clean repos have no uncommitted changes. Dirty repos have pending work. Target your commands accordingly.

Mass Update

```
zpwr gitupdatefordir # run git updates in all git dirs
```

Pulls latest, updates submodules, the full sync. Run this on a Monday morning. Coffee. Wait.

Branch Wipe Operations

```
zpwr gitfordirmain # wipe to main branch in git dirs
zpwr gitfordirdevelop # wipe to develop branch in git dirs
```

```

zpwr gitzfdir <branch> [z]      # wipe to any branch + z jump
zpwr gitzfdirmain [z]          # z jump + wipe to main
zpwr gitzfdirdevelop [z]       # z jump + wipe to develop

```

The Repos File

```

zpwr gitreposfile      # edit the git repos file

```

This file lists all known repositories. Edit it to add or remove repos from batch operations.

Example: Status Check All Repos

```

zpwr gitrepoexec git status -s

```

Runs git status -s in every cached repo. Instantly see which repos have uncommitted work.

Battalion ops turn you from a developer into a fleet commander.

Git Add-Commit-Push

// 318 aliases for the git power user //

The zsh-git-acp plugin provides 318 aliases that collapse multi-step git workflows into single commands.

The Gacp Pattern

```

gacp "message"      # git add -A, commit, push
gac "message"       # git add -A, commit (no push)
gcp                 # git commit, push

```

Branch Shortcuts

```

gcm                 # git checkout main
gcb <branch>        # git checkout -b <branch>
gbd <branch>        # git branch -d <branch>

```

zpwr Integration

```

zpwr gitcommit "msg"      # commit and push with message
zpwr gitcommitcount       # count commits in current repo

```

The full alias list is enormous — 318 combinations of git operations compressed into 2-4 character shortcuts. Most follow the pattern: g + operation letter(s).

Plugin: MenkeTechnologies/zsh-git-acp.

Git Operations Reference

// 33 verbs for git mastery //

Core git verbs for commits, config, history rewriting, contributor stats, and multi-repo operations.

Commit & Push

```
zpw! gitcommit          # commit and push with arg message
zpw! gitcommitcount     # count commits in current repo
zpw! gitcommits         # search git commits with fzf
zpw! clone               # clone and cd to arg
```

Config & Ignores

```
zpw! gitconfig          # edit git config file
zpw! gitglobalconfig    # edit git config file
zpw! gitignore          # $EDITOR ~/.git/info/exclude
zpw! gitignores         # edit git ignores file
zpw! gitglobalignores   # edit git ignores file
```

Email & History Rewriting

```
zpw! gitemail           # change email with git filter-branch
zpw! gitcemail          # change committer email
zpw! gitaemail          # change author email
zpw! gitclearcommit     # remove matching commits from history
zpw! gitclearcache      # clear old git refs and objects
zpw! gitclearfile       # rm file from all git refs/objects
```

Stats & Info

```
zpw! gitcontribcount    # count git contributions by author
zpw! gitcontribcountdirs # contributions by author for dirs
zpw! gitcontribcountlines # count lines contributed by author
zpw! gittotallines      # total line count of git files
zpw! gitlargest         # show largest files stored by git
zpw! gitremotes         # list all git remotes
zpw! gitdir             # check if pwd is git dir
zpw! gitwho             # aggregate contributor stats
zpw! gitsearch          # search for regex in git log
```

Multi-repo & Tags

```
zpw! gitforallldir      # run cmd in all git dirs
zpw! gitfordirdevelop   # git wipe to develop in git dirs
zpw! gitfordirmain      # git wipe to main in git dirs
zpw! gitupdatefordir    # run git updates in all git dirs
zpw! gitzfordir         # git wipe on branch in git dirs
zpw! gitzfordirdevelop  # z and git wipe to develop
zpw! gitzfordirmain     # z and git wipe to main
zpw! gitupdatetag       # print tag and latest msg
zpw! gitedittag         # print tag to $BUFFER
```

GitHub & Travis CI

// 16 verbs for the hosted world //

Verbs for GitHub repo management, contribution counting, and Travis CI browser integration.

Github Navigation

```
zpwr gh          # open github profile
zpwr github      # open github profile
zpwr mygithub    # open github profile
zpwr ghz         # open zpwr github repo
zpwr githubzpwr  # open zpwr github repo
zpwr zpwrgithub  # open zpwr github
```

Github Repo Management

```
zpwr githubcreate  # create remote github repo
zpwr githubdelete  # delete remote github repo
zpwr hc            # create remote github repo
zpwr hd            # delete remote github repo
```

Contribution Stats

```
zpwr ghcontribcount  # count github contribs in last year
zpwr githubcontribcount  # count github contribs in last year
```

Travis Ci

```
zpwr travis        # open current travis project
zpwr travisbranch   # open current travis branches
zpwr travisbuild    # open current travis builds
zpwr travispr       # open current travis PRs
```

Chapter 4 – The Search Engine

Finding Files

The filesystem is vast. You are small. But you have fzf and a verb for every search strategy.

Filesearch: Local Tree

```
zplr filesearch          # find and open a file in a sub dir
```

Recursively lists files under \$PWD into fzf. Type fragments of the filename. Fuzzy match. Enter. Opens the file in your pager.

```
zplr filesearchedit      # same but puts path on command line
```

Instead of opening immediately, the selected path lands on your \$BUFFER for further editing. Append commands, pipe it, whatever you want.

Dirsearch: Directories Only

```
zplr dirsearch           # cd to a sub directory via fzf
```

Same idea but only directories. Pick one, land in it. Faster than cd-tab-tab-tab-tab.

Findsearch: Full Disk

```
zplr findsearch          # find across the entire drive
```

Uses find(1) to search the whole filesystem. Results feed into fzf. Pick one, open it. Slow on first run. Worth the wait.

```
zplr findsearchedit      # same but result goes to $BUFFER
```

Locatesearch: Index-based

```
zplr locatesearch        # search the locate database
```

Uses locate(1) which searches a pre-built index. Blazing fast. But only as fresh as your last updatedb.

```
zplr locatesearchedit    # same but result goes to $BUFFER
```

The Search Hierarchy

Speed Scope Verb — — — Fast ... current tree .. filesearch

```
Fast ... dirs only ..... dirsearch
```

Slow ... entire disk ... findsearch Instant indexed disk .. locatesearch

Start with filesearch for local work. Escalate to locatesearch when you need the whole disk. Fall back to findsearch when the index is stale.

Searching Content

Finding files is one thing. Finding the line inside the file? That is the real game.

Wordsearch: Content In Local Tree

```
zpwr wordsearch          # find file by content in sub dir
```

Greps through files in the current tree. Results show matching lines with filenames. Fzf preview shows the file with match highlighted. Select one, jump straight to it.

```
zpwr wordsearchedit      # same but result goes to $BUFFER
```

Puts the selected file path on your command line. Useful when you want to pipe or chain commands.

Grep: Ag Into fzf

```
zpwr grep                # grep through pwd with ag into fzf
```

This is the heavy artillery. Uses the silver searcher (ag) piped into fzf for interactive filtering. Respects .gitignore. Skips binaries. Fast.

Filesearch Vs Wordsearch

Know the filename? Use filesearch Know the content? Use wordsearch Know nothing? Use grep and improvise.

The Edit Suffix Pattern

Every search verb has an edit variant: filesearch -> filesearchedit wordsearch -> wordsearchedit findsearch -> findsearchedit locatesearch -> locatesearchedit.

Without edit: opens the result immediately. With edit: puts the path on your command line. This lets you compose: vim \$(zpwr filesearchedit)

Real-world Examples

Find where "ZPWR_VERBS" is defined:

```
zpwr wordsearch
```

Type ZPWR_VERBS in fzf, browse the matches.

Quick grep for TODO comments:

```
zpwr grep
```

Type TODO, see every file that has one.

The search verbs are your eyes inside the codebase. Use them before you reach for a GUI.

The FZF Dimension

FZF is the nervous system of zpwr. It is wired into search, selection, navigation, git, vim, environment browsing, and verb dispatch. If zpwr has a UI, fzf IS that UI.

Verb Discovery

```
zpwr verbs      # fuzzy search all zpwr verbs
```

Every verb, every description, in one fzf window. This is the god-mode cheat sheet. Learn it first.

Environment Browsing

```
zpwr envaccept   # accept from fzf env
```

Browse all shell environment entries (aliases, functions, parameters, builtins) in fzf. Select one, accept it onto the command line.

```
zpwr envedit     # edit from fzf env
```

Same browsing but puts the result on \$BUFFER for editing.

```
zpwr envcachesearch # search cached aliases, functions, etc.
```

Searches the pre-built cache of your entire environment. Faster than envedit because it uses the cache file.

fzf Patterns Across zpwr

FZF appears in dozens of verbs. The pattern is always: 1. A data source generates lines (files, commits, dirs) 2. Lines pipe into fzf with a preview command 3. You fuzzy-filter, select, and take an action.

Verbs with fzf built in: filesearch file list -> fzf -> open wordsearch grep results -> fzf -> open dirsearch dir list -> fzf -> cd gitcommits git log -> fzf -> show diff forgitadd unstaged files -> fzf -> stage forgitlog commit log -> fzf -> preview zcd z database -> fzf -> cd subcommandsfzf all verbs -> fzf -> execute.

The fzf Keybindings

```
zpwr vimsearch   # search vim keybindings in fzf
zpwr allsearch   # search ALL keybindings in fzf
```

When you want to find a keybinding but do not remember where it is defined. Search them all.

FZF is not optional in zpwr. It is the interface. Master fzf and you master zpwr.

The Learning System

// your shell remembers what you learn //

The zsh-learn plugin turns your shell into a persistent knowledge base backed by MySQL. Save commands, search them, quiz yourself, and build a personal learning collection.

Core Verbs

```
zpwri learn          # save a learning entry
zpwri searchl        # search the collection
zpwri quiz           # quiz yourself
zpwri quizall        # quiz all entries
zpwri redo           # redo last search as SQL update
```

Search Variants

```
zpwri se             # basic search
zpwri see            # category search
zpwri seee           # timestamp search
zpwri ser            # random search
zpwri sef            # search into fzf
zpwri searchall      # entire collection into fzf
zpwri searchfull     # entire collection into fzf
zpwri searchle       # category search (alias for see)
zpwri searchlee      # timestamp search (alias for seee)
zpwri learnsearch    # search the collection
zpwri rsqql          # redo into vim
zpwri redosqql       # redo into vim
```

Management

```
zpwri learndel       # delete entry
zpwri learndelete    # delete entry (alias)
zpwri delid          # delete by ID
zpwri editl          # edit entry by ID
zpwri getlearn       # get all entries
zpwri learnget       # get all entries
zpwri createlearningcollection # create MySQL table
zpwri droplearningcollection  # drop MySQL table
```

How It Works

Entries are stored in a MySQL database (configurable via `$ZPWR_SCHEMA_NAME` and `$ZPWR_TABLE_NAME`). Each entry has a category, timestamp, and content. The quiz system pulls random entries and tests your recall.

Plugin: MenkeTechnologies/zsh-learn.

Chapter 5 – Editor Mastery

Vim Integration Overview

Vim is not just an editor in zpwr. It is a first-class citizen with its own verb family. Over 20 verbs, each opening vim in a specific context.

The Philosophy

Every vim verb answers one question: “What do I want to edit right now?” The answer is always one verb away.

The Vim* Verb Family

```
vimall ..... open ALL zpwr files (for :argdo)
vimalledit ..... pick and edit 1+ zpwr configs
vimautoload ..... open all autoloads (for :argdo)
vimcd ..... vim edit, then cd to first dir
vimconfig ..... edit all zpwr config files
vimctags ..... vim zpwr ctags
vimemacsconfig ..... vim edit emacs zpwr configs
vimfilesearch ..... vim a file found via fzf
vimfilesearchedit ... vim edit a file found via fzf
vimfindsearch ..... vim a file from find(1) via fzf
vimfindsearchedit ... vim edit find result
vimgtags ..... vim zpwr GNU global tags
vimgtagsedit ..... vim edit zpwr GNU global tags
vimlocatesearch ..... vim a file from locate via fzf
vimlocatesearchedit . vim edit locate result
vimplugincount ..... count vim plugins
vimpluginlist ..... list all vim plugins
vimrecent ..... edit most recent files
vimrecentcd ..... cd + edit most recent files
vimrecentsudo ..... sudo edit most recent files
vimrecentsudocd ..... cd + sudo edit recent files
vimscripts ..... open all zpwr scripts (for :argdo)
vimscriptedit ..... pick and edit 1+ scripts
vimsearch ..... search vim keybindings via fzf
vimtests ..... edit all zpwr tests
vimtokens ..... vim the .tokens.sh file
vimwordsearch ..... vim a file found by content
vimwordsearchedit ... vim edit file found by content
```

The :argdo Pattern

Verbs like vimall and vimscripts load many files into vim’s arglist. Then you can:

```
:argdo %s/old/new/g | update
```

Mass find-and-replace across the entire zpwr codebase.

If it can be edited, there is a vim verb for it.

Vim File Operations

Opening vim is easy. Opening vim with the right files already loaded? That is where zpwr earns its keep.

The Big Opens

```
zpwr vimall          # load ALL zpwr files into arglist
```

Every .zsh, .sh, .py, .pl file in the zpwr tree. Hundreds of files. Ready for :argdo mass operations. This is the tactical nuke of text editing.

```
zpwr vimalledit      # fzf pick 1+ configs to edit
```

Like vimall but you choose which files to open. Surgical precision instead of carpet bombing.

Recent Files

```
zpwr vimrecent       # edit most recently opened files
```

Pulls from vim's file history. Opens the files you were just working on. Resume where you left off.

```
zpwr vimrecentcd     # cd to dir + open recent files
```

Same as vimrecent but also changes to the directory. Your shell and editor are now in the same place.

```
zpwr vimrecentsudo   # sudo edit recent files
```

When you need root to edit those files.

```
zpwr vimrecentsudocd # cd + sudo edit recent files
```

The full combo: navigate, elevate, edit.

zpwr Subsystems

```
zpwr vimscripts      # load all zpwr scripts into arglist
zpwr vimscriptedit    # pick and edit 1+ scripts
zpwr vimautoload      # load all autoloads into arglist
zpwr vimtests         # edit all zpwr test files
```

vim Cd

```
zpwr vimcd           # edit file, cd to its directory
```

Opens a file in vim, and when you exit, your shell is cd'd to the directory containing that file. Edit something, then be where it lives. Elegant.

Workflow Example

Resume yesterday's work:

```
zpwir vimrecentcd
```

Opens recent files, lands you in the right dir.

Mass rename a function across all scripts:

```
zpwir vimscripts  
:argdo %s/oldFunc/newFunc/g | update
```

Done. Every script updated.

Vim Search and Tags

Finding files is step one. Finding definitions inside those files is step two. Tags are step three: jump to any symbol by name.

vim File Search

```
zpwir vimfilesearch          # fzf find file -> open in vim
```

Lists files in the current tree via fzf. Select one, it opens in vim. No path typing.

```
zpwir vimfilesearchedit      # fzf find file -> path to $BUFFER
```

Same search but puts the path on your command line.

vim Word Search

```
zpwir vimwordsearch          # fzf grep content -> open in vim
```

Searches file contents, shows matches in fzf. Select a match, vim opens at that location.

```
zpwir vimwordsearchedit      # same but path to $BUFFER
```

Full Disk Search Into vim

```
zpwir vimfindsearch          # find(1) -> fzf -> vim  
zpwir vimfindsearchedit      # find(1) -> fzf -> $BUFFER  
zpwir vimlocatesearch        # locate -> fzf -> vim  
zpwir vimlocatesearchedit    # locate -> fzf -> $BUFFER
```

The search escalation ladder from page 15 but with vim as the final destination instead of a pager.

Ctags: Jump To Definition

```
zpwir vimctags                # open zpwir ctags in vim
```

Ctags indexes function and variable definitions. With tags loaded, Ctrl-] on any symbol jumps to its definition. Ctrl-T jumps back. Code navigation at the speed of thought.

Gnu Global Tags

```
zpwr vimtags          # open zpwr GNU global tags in vim
zpwr vimtagsedit      # edit zpwr GNU global tags
```

GNU Global is ctags on steroids. It indexes not just definitions but references too. Find every caller of a function, not just its definition.

The Search Matrix

What you know Verb to use ———- ———- Filename fragment vimfilesearch String in a file vimwordsearch
File somewhere vimlocatesearch Symbol name vimctags then Ctrl-] All references vimtags.

Vim Config and Sessions

Configuration is not a one-time event. It is a lifestyle. ZPWR gives you session commands that open the right config files as a group.

The Session Verbs

Each of these opens a curated set of config files in vim buffers, ready for synchronized editing:

```
zpwr vrc              # vim/nvim config session
```

Opens your vimrc or init.vim along with related files. All your editor settings in one session.

```
zpwr brc              # shell aliases session
```

Opens the tokens file and shell alias configs. Where you tune your personal shell experience.

```
zpwr zrc              # zshrc session
```

Opens the zshrc and zsh init chain. The root of your shell's boot sequence.

```
zpwr trc              # tmux.conf session
```

Opens tmux configuration files. Pane layouts, keybindings, status bar.

Config Editing

```
zpwr vimconfig        # edit all zpwr configs in vim
```

Opens every zpwr configuration file. The master session. Use :bn and :bp to navigate between buffers.

```
zpwr vimtokens        # vim the .tokens.sh file
zpwr tokens           # same thing
```

Quick jump to your personal aliases and secrets file. This is the file that is gitignored. Your sanctuary.

Plugin Inventory

```
zpwr vimplugincount    # how many vim plugins installed
zpwr vimpluginlist     # list all vim plugins
```

Know thy plugins. Count them. Name them. If the count scares you, it should.

Typical Config Workflow

Add a new shell alias:

```
zpwr brc
```

Edit .tokens.sh, add your alias, :wq # Source it or open a new terminal.

Tweak a vim keybinding:

```
zpwr vic
```

Navigate to the mapping, change it, :wq.

Three letters to open any config. No file paths. No guessing. Just intent.

Emacs Mirror Universe

For every vim verb, there is an emacs verb. Identical semantics. Different editor. Perfect symmetry. ZPWR does not take sides in the editor war. It arms both factions equally.

The Symmetry Table

vim verb emacs verb ——— ————

```
vimall ..... emacsall
vimalledit ..... emacsalledit
vimautoload ..... emacsautoload
vimcd ..... emacscd
vimconfig ..... emacsconfig
vimctags ..... emacsctags
vimfilesearch ..... emacsfilesearch
vimfilesearchedit ... emacsfilesearchedit
vimfindsearch ..... emacsfindsearch
vimfindsearchedit ... emacsfindsearchedit
vimgtags ..... emacsgtags
vimgtagsedit ..... emacsgtagsedit
vimlocatesearch ..... emacslocatesearch
vimlocatesearchedit . emacslocatesearchedit
vimrecent ..... emacsrecent
vimrecentcd ..... emacsrecentcd
vimrecentsudo ..... emacsrecentsudo
vimrecentsudocd ..... emacsrecentsudocd
vimscripts ..... emacsscripts
vimscriptedit ..... emacsscriptedit
vimtests ..... emacs tests
vimtokens ..... emacs tokens
vimwordsearch ..... emacswordsearch
vimwordsearchedit ... emacswordsearchedit
vimplugincount ..... emacsplugincount
vimpluginlist ..... emacspluginlist
```

Emacs-specific

```
zpwr emacsallserver      # emacs all zpwr files (server mode)
zpwr emacsconfig         # emacs edit emacs-specific configs
zpwr emacspluginlist     # emacs the zpwr directory
```

The lesson: `zpwr` is editor-agnostic by design. Replace “vim” with “emacs” in any verb. It works. Both sides get the same firepower.

Vim Integration

// 35 verbs for the vim faithful //

The vim verb family mirrors emacs with full parity. Open, edit, search, navigate — all wired to vim/nvim.

Open & Edit

```
zpwr vimall          # vim all zpwr files for :argdo
zpwr vimalldedit     # vim edit 1 or more configs
zpwr vimautoload     # vim all autoloads :argdo
zpwr vimscripts     # vim all zpwr scripts for :argdo
zpwr vimscriptedit   # vim edit 1 or more scripts
```

Config & Tokens

```
zpwr vimconfig       # edit all zpwr configs
zpwr vimemacsconfig  # vim edit emacs zpwr configs
zpwr vimtokens       # vim the .tokens.sh file
zpwr vimtests        # edit all zpwr tests
zpwr vrc             # vimrc vim session
zpwr brc             # shell aliases file vim session
zpwr trc             # tmux.conf vim session
zpwr zrc             # zshrc vim session
zpwr tokens          # vim the .tokens.sh file
```

Navigation

```
zpwr vimcd           # vim edit and cd to first dir
zpwr vimrecent       # vim edit most recent editor files
zpwr vimrecentcd     # cd and vim edit most recent files
zpwr vimrecentsudo   # sudo vim edit most recent files
zpwr vimrecentsudocd # cd and sudo vim most recent files
```

Search

```
zpwr vimsearch       # search vim keybindings
zpwr vimfilesearch   # vim a file in a sub dir
zpwr vimfilesearchedit # edit vim a file in a sub dir
zpwr vimfindsearch   # vim accept find drive for file
zpwr vimfindsearchedit # vim edit find drive for file
zpwr vimlocatesearch # vim accept locate drive for file
zpwr vimlocatesearchedit # vim edit locate drive for file
zpwr vimwordsearch   # vim a file in a sub dir by word
zpwr vimwordsearchedit # edit vim a file by word
```

Tags, Plugins & Viminio

```
zpwr vimctags          # vim zpwr ctags tags
zpwr vimgtags          # vim zpwr GNU global tags
zpwr vimgtagsedit      # vim edit zpwr GNU global tags
zpwr vimplugincount    # total number of vim plugins
zpwr vimpluginlist     # total list of vim plugins
zpwr catviminfo        # cat custom vim info file
zpwr catrecentfviminfo # cat recentf then custom vim info
zpwr catnviminforecentf # cat custom vim info then recentf
```

Chapter 6 – Performance Cult

Benchmarking Startup

A shell that takes 2 seconds to start is a shell that has already lost. ZPWR takes startup time seriously enough to build a benchmarking verb.

The Bench Verb

```
zpwr bench
```

Runs multiple shell startup iterations and reports: - Mean startup time - Percentiles (p50, p95, p99) - Baseline diff (zpwr overhead vs bare zsh)

What The Numbers Mean

```
< 100ms .... imperceptible. You are golden.
```

100-200ms .. noticeable if you open many terminals. 200-500ms .. getting sluggish. Time to investigate.

```
> 500ms .... something is wrong. Check your plugins.
```

How It Works

The bench verb spawns N fresh zsh instances, each running through the full init chain. It measures wall-clock time from fork to prompt. Then it does the same for bare zsh (no zpwr). The diff tells you exactly what zpwr costs.

What Slows You Down

Common culprits in order of likelihood: 1. Too many vim/emacs plugins loading at shell init 2. nvm/pyenv/rbenv hooking into every prompt 3. Uncompiled completion files (run zpwr compile) 4. Network calls in your init chain (stop that) 5. Massive HISTFILE being loaded synchronously.

Optimization Checklist

```
zpwr compile      # recompile all cache and completions
zpwr compilefpath # recompile all fpath files
zpwr compilefiles # recompile all files
```

Compiled .zwc files load faster than source. This is the single biggest performance lever.

Benchmark Regularly

Run zpwr bench after any config change. If the numbers go up, you broke something. If they go down, you are a performance wizard.

Your shell starts thousands of times a year. Every millisecond is multiplied by every terminal open. Measure. Optimize. Measure again.

Flame Charts

Bench tells you HOW LONG startup takes. Flame tells you WHERE the time goes.

The Flame Verb

```
zplr flame
```

Generates a startup flame chart from zprof data. Shows you exactly which functions and files are consuming your startup time, in descending order.

Reading The Output

The flame chart shows a ranked list of functions: Each entry shows: - Function/file name - Time consumed (milliseconds) - Percentage of total startup time.

The top of the list is where optimization effort pays off the most. If one function takes 40% of startup, that is your target.

How Zprof Works

Zsh has a built-in profiler: zprof. When enabled, it instruments every function call during shell init and records the wall-clock time. The flame verb wraps this into a readable report.

Common Hotspots

What you will typically see at the top:

```
compinit ..... completion system init
compaudit ..... completion security check
compdump ..... writing completion cache
_zplr_* ..... zplr autoload functions
nvm/pyenv/rbenv .... version manager hooks
```

Optimization Tips

1. If compinit is slow, run zplr compile to cache it
2. If a version manager dominates, lazy-load it
3. If an autoload is slow, check for disk I/O in it
4. If compaudit is slow, fix the directory permissions
5. After changes, run zplr bench to verify improvement

The Optimization Loop

```
zplr flame      # identify the bottleneck
```

... fix it ...

```
zplr bench      # measure the improvement
zplr flame      # find the next bottleneck
```

Repeat until you hit diminishing returns.

Flame charts turn gut feelings into data. Stop guessing. Start profiling.

Live Dashboard

Bench is a snapshot. Flame is a profile. Top is a live feed of your shell's vital signs.

The Top Verb

```
zpwr top
```

Launches a live shell resource dashboard. Think htop, but for your zsh environment.

What Each Section Shows

Shell Environment - Number of aliases currently defined - Number of functions loaded - Number of parameters (variables) in scope - Builtin and keyword counts.

Completion System - Completion functions registered - Cache file sizes and freshness.

Resource Usage - Memory footprint of the shell process - History file size and entry count - Autoload function count.

Interpreting The Data

High alias count? Normal for zpwr. 1000+ is fine. High function count? Also normal. Autoloaded functions are lazy-loaded, they cost nothing until called. Large HISTFILE? Consider zpwr backuphistory and trim. Stale cache? Run zpwr compile to refresh.

Companion Verbs

```
zpwr environmentcounts  # one-shot environment stats
zpwr autoloadcount      # total number of autoloads
zpwr autoloadlist       # list all autoloads
zpwr vimplugincount     # count vim plugins
zpwr emacsplugincount   # count emacs plugins
```

Use these for quick spot checks without the full dashboard.

The Performance Quartet

zpwr bench -> how fast is total startup? zpwr flame -> ASCII flame chart of function hotspots zpwr startup -> per-function zprof breakdown zpwr top -> what is loaded right now?

Four verbs. Four perspectives. Complete observability. Your shell is no longer a black box. It is an open book.

Chapter 7 – Health & Diagnostics

The Doctor Is In (1/2)

The Doctor Is In

// every system needs a physician. yours lives at zpwr doctor. //

Your shell is a living organism. It accumulates cruft, grows tumors in PATH, and occasionally develops broken symlinks. The doctor runs a full-body scan and tells you what hurts.

Invoke The Doctor

```
zpwr doctor          # full diagnostic scan
zpwr doctor -h       # help with detailed check list
```

What It Checks

1. STALE .zwc FILES Compiled zsh files older than their source. Fix: zpwr recompile
2. ZCOMPDUMP FRESHNESS Completion dump older than 1 week. Fix: zpwr regenzzsh
3. DUPLICATE PATH ENTRIES Every duplicate is a wasted hash lookup. Fix: zpwr deduppaths
4. DUPLICATE/MISSING FPATH ENTRIES Same disease, different organ.
5. BROKEN SYMLINKS Dangling symlinks in `$ZPWR`.

Continued on next page...

The Doctor Is In (2/2)

The Doctor (continued)

6. NAMED DIRECTORIES Invalid named dirs and p10k pollution from auto_name_dirs leaking gitstatus vars.
7. DEPENDENCIES Checks: git, eza, fzf, tmux, perl, python3, zinit.
8. HISTORY & BACKUPS Is HISTFILE present? How many backups exist?
9. CONFIG SYMLINKS Checks .zshrc, .vimrc, .tmux.conf are symlinks.

Reading The Results

Green checkmark = healthy yellow warning = degraded but functional red X = broken, fix now.

The Signal Bar

= HEALTHY #####- = WARNINGS ##- = CRITICAL.

Companion Verbs

```
zpwr stale          # stale .zwc, orphan caches
zpwr pathaudit      # deep PATH/FPATH audit
zpwr lint           # shellcheck + zsh -n
zpwr startup        # zprof breakdown
zpwr ports          # listening ports
```

Pro Move

Add zpwr doctor to weekly cron. Catch rot early.

Dependency Cartography

// mapping the call graph. who calls whom. who dies alone. //

zpwr has hundreds of functions. They call each other in a tangled web of dependencies. The deps verb maps that web. Think of it as Google Maps for your function call graph.

Basic Usage

```
zpwr deps           # summary overview
zpwr deps zpwrClearnList  # what does zpwrClearnList call?
zpwr deps -h        # full help
```

The Flags

-r, --reverse Who calls this function? (reverse lookup) -o, --orphans Functions called by nobody internally -s, --summary Overview stats (default when no args) -d, --dot Output dot format for graphviz rendering

Forward Lookup: What Does X Call?

```
zpwr deps zpwrDoctor
```

Shows every function zpwrDoctor calls, plus depth-2 callees. Output: zpwrDoctor -> zpwrPrettyPrint -> [zpwrLogDebug, ...]

Reverse Lookup: Who Calls X?

```
zpwr deps -r zpwrPrettyPrint
```

Answers: “Who depends on zpwrPrettyPrint?” If the answer is 30 functions, that function is load-bearing. Touch it carefully.

Orphan Detection

```
zpwr deps --orphans
```

Lists functions that no other zpwr function calls. These are either entry points (user-invoked) or dead code. Orphans are not necessarily bad – many are top-level verbs or zinit hooks. But if you wrote zpwrFoo and nobody calls it, maybe zpwrFoo was a fever dream.

Graphviz Export

```
zpwr deps --dot > graph.dot  
dot -Tsvg graph.dot -o graph.svg
```

Produces a visual dependency graph. Nodes are functions, edges are call relationships. The dot output uses cyberpunk colors: dark background, cyan nodes, magenta edges. Open graph.svg in a browser and behold the nervous system.

The Summary View

With no args, deps shows two ranked lists: TOP 10 MOST DEPENDENCIES (functions that call the most others) TOP 10 MOST DEPENDED ON (functions called by the most others) Plus stats: total functions, orphan count, total call edges. The bar charts use Unicode block characters. Very aesthetic.

How It Works

Scans autoload dirs: common, darwin, linux, comp_utils. Reads each function body and string-matches against all other function names. Also scans `$ZPWR_SCRIPTS/lib.sh`. It is $O(n^2)$ and proud of it. Your function count is not big enough to matter.

Command Autopsy

// when you need to know why a command is slow, fat, or dead //

The trace verb is a command profiler. It wraps any command in instrumentation and reports wall time, CPU time, memory, context switches, page faults, and more.

Basic Usage

```
zpwr trace ls -la          # full trace of ls -la  
zpwr trace -q make         # quick: timing + resources only  
zpwr trace -h              # full help
```

The Flags

-q, --quick Timing + resource stats only (runs once) -s, --strace Syscall counts only (Linux; no ltrace) -l, --ltrace C library calls only (Linux; no strace) -a, --all Both strace + ltrace (default behavior)

What You Get: The Resource Card

Exit code green = 0, red = nonzero wall time real clock time with rating: INSTANT (<100ms), FAST (<1s), NOMINAL (<5s), SLOW (<30s), HEAVY (30s+) user/sys time CPU time in user/kernel space peak RSS

max resident memory (auto-scaled B/KB/MB/GB) ctx switches voluntary + involuntary context switches page reclaims soft faults (memory mapped in from cache) page faults hard faults (actual disk I/O for memory) block I/O filesystem reads and writes signals rcv number of signals delivered IPC messages sent/received inter-process messages shell delta memory change of the parent shell child procs before/after child process count.

Platform Differences

MacOS: `/usr/bin/time -l` for resource stats. SIP blocks `dtruss/dtrace` on most binaries. You get timing + memory + kernel stats. Linux: `strace -c` for syscall counts, `ltrace -c` for C library calls. Command re-runs for each tool.

Practical Examples

```
zpwr trace git status          # is git status slow in this repo?
zpwr trace -q rm -rf node_modules # quick mode for destructive ops
zpwr trace -s npm install       # syscalls only (Linux)
zpwr trace zsh -c 'source ~/.zshrc' # profile shell startup
```

The Signal Bar

Bottom of output: a 10-block performance signal. ##### score 10 = under 100ms. Lightning. #####— score 6 = under 2s. Acceptable. ##——— score 2 = under 30s. Go get coffee.

WARNING: Default mode re-runs the command for `strace/ltrace`. Use `-q` for destructive commands (`rm`, `truncate`, etc).

Usage Intelligence

// your shell keeps a diary. these verbs read it. //

You have 512 verbs and thousands of aliases. Which ones do you actually use? `funcrank` and `aliasrank` mine your shell history to answer that question.

Funcrank: Function & Verb Profiler

```
zpwr funcrank          # top 20 functions and verbs
zpwr funcrank 40        # top 40
zpwr funcrank --reset   # nuke cache, rebuild from scratch
zpwr funcrank --reset 50 # rebuild then show top 50
```

`Funcrank` scans your `HISTFILE` for occurrences of known function names and `zpwr` verbs. It produces two ranked lists: 1. Top functions by history occurrence count 2. Top `zpwr` verbs by how often you type “`zpwr <verb>`” Each entry gets a Unicode bar chart. The biggest user wins.

Aliasrank: Reverse Expansion Profiler

```
zpwr aliasrank          # top 20 by expanded usage
zpwr aliasrank 50        # top 50
zpwr aliasrank --reset   # force cache rebuild
```

Here is the trick: zpw uses zsh-expand to expand aliases before they hit history. So history contains the expanded form, not the alias name. aliasrank does a reverse lookup: it matches history lines against alias values to figure out which alias you would have typed.

The Cache System

`$ZPWR_LOCAL/zpwr-aliasrank-cache.zsh` command counts `$ZPWR_LOCAL/zpwr-verbrank-cache.zsh` verb counts `$ZPWR_LOCAL/zpwr-rank-stamp` history line watermark

The cache auto-rebuilds when history grows by 1000+ lines. The watermark file stores the last-seen history line count. No need to rebuild every time – incremental is the way. Use `–reset` to force a full rebuild if cache seems stale.

Interpreting The Results

If your top verb is `help`, you are still learning. Good. If your top verb is `cleanall`, you break things a lot. If your top function is `cd`, you need more named dirs. If an alias never appears, maybe it is too long to remember.

Practical Intelligence

Run `funcrank` monthly. Notice patterns: - Verbs you never use might need better names or keybindings - Functions with high counts are candidates for optimization - Low-count zpw verbs might benefit from shorter aliases.

Your history is a behavioral log. These verbs turn it into actionable intelligence. Know thyself, operative.

Startup Profile

// bench tells you HOW FAST. startup tells you WHERE the time goes. //

`zpwr bench` measures total wall time over multiple iterations. `zpwr startup` gives a single-shot, per-function breakdown using zsh's built-in `zprof` profiler.

The Verb

```
zpwr startup          # top 30 functions (default)
zpwr startup 50       # top 50 functions
zpwr startup 100      # full breakdown
```

How It Works

1. Launches a fresh zsh with `ZPWR_PROFILING=true`
2. `zprof` runs at the end of the init sequence
3. Output is captured and colorized by self-time: `>= 10% RED` — hot path, optimize here `>= 3% YELLOW` — warm, worth investigating `>= 1% CYAN` — normal `< 1% DIM` — negligible

The Performance Quartet

`zpwr bench` -> how fast is total startup? `zpwr flame` -> ASCII flame chart of function hotspots `zpwr startup` -> per-function `zprof` breakdown `zpwr top` -> what is loaded right now?

Four verbs. Four perspectives. Your shell is transparent.

Shell Lint

// if it parses, it ships. but does it REALLY parse? //

zpw lint runs two levels of analysis on every zpw file: syntax checking with zsh -n, and static analysis with shellcheck.

The Verb

```
zpw lint          # run all checks
zpw lint -z       # zsh -n syntax check only
zpw lint -s       # shellcheck only
```

What It Checks

zsh -n (syntax check) Every file in autoload/common, autoload/darwin, autoload/linux, env/*.sh, env/*.zsh, install/.zshrc. This catches unmatched brackets, bad redirections, and broken quoting. Fast — no execution, just parsing.

Shellcheck (static analysis) Every .sh and .zsh file in scripts/ and install/. Catches quoting bugs, unused variables, subshell pitfalls. Zsh-incompatible warnings are suppressed (SC1071 etc).

When To Run It

After editing any zpw file. Before committing. Before pushing. Catch it at the gate, not in production.

Companion Verbs

```
zpw doctor        # broader health check
zpw stale         # find stale compiled files
zpw recompile     # rebuild .zwc files after fixes
```

Listening Ports

// who is listening? and on which door? //

zpw ports wraps lsof to show every TCP port in LISTEN state with the process name, PID, user, and bind address.

The Verb

```
zpw ports         # show all listening ports
zpw ports 8080    # filter to port 8080
zpw ports -k 3000 # kill whatever is on port 3000
```

Color Coding

Privileged ports (< 1024) — RED These require root. sshd on 22, httpd on 80. Common ports (< 10000) — YELLOW Dev servers, databases. 3000, 5432, 8080. High ports (>= 10000) — GREEN Ephemeral and user-space. Generally safe.

The Kill Flag

zpwrr ports -k 3000 finds the PID on port 3000 and sends SIGTERM. Shows process name before killing. Use when a dev server refuses to die.

Companion Verbs

```
zpwrr lsof          # interactive fzf over all lsof output
zpwrr ps            # grep through ps output
zpwrr kill          # fzf kill from ps
```

Stale File Finder

// compiled cruft is invisible cruft. make it visible. //

zpwrr stale scans the entire zpwrr tree for artifacts that have gone stale, orphaned, or broken.

The Verb

```
zpwrr stale          # scan and report
zpwrr stale -f        # delete all stale files
```

What It Finds

STALE .zwc Source file is newer than its compiled .zwc. Your shell is running yesterday's bytecode.

ORPHAN .zwc The source file was deleted but the .zwc remains. Dead weight taking up space and confusing zsh.

BROKEN SYMLINKS Symlinks pointing to files that no longer exist. Source of cryptic 'file not found' errors.

EMPTY CACHE FILES Zero-byte files in cache directories. Usually left behind by interrupted operations.

The Fix Flag

zpwrr stale -f deletes everything it finds in one pass. Follow up with zpwrr recompile to rebuild .zwc files.

Workflow

```
zpwrr stale          # see what is stale
zpwrr stale -f        # nuke the cruft
zpwrr recompile       # rebuild fresh .zwc files
zpwrr doctor          # verify everything is clean
```

Path Audit

// your PATH is your attack surface. audit it. //

zpwrr pathaudit inspects PATH, FPATH, and MANPATH for duplicates, missing directories, and world-writable entries.

The Verb

```
zplr pathaudit          # audit all three arrays
zplr pathaudit -v       # verbose: show every entry
```

What It Checks

DUPLICATES Same directory appearing more than once. Wastes hash lookups and obscures precedence.
Fix: `zplr deduppaths`.

MISSING DIRECTORIES PATH entry pointing to a dir that does not exist. Slows command lookup — `zsh` checks every entry.

WORLD-WRITABLE DIRECTORIES Any user can write to this directory. If it is in your PATH, an attacker can plant a malicious binary that shadows a real command. Security risk.

All Three Arrays

PATH — command lookup for executables
FPATH — function autoload lookup for `zsh`
MANPATH — man page lookup for documentation.

Companion Verbs

```
zplr doctor            # broader health check (also checks paths)
zplr deduppaths        # remove duplicate entries
zplr environmentcounts # count all env arrays
```

Doctor checks paths as part of a broader scan. `pathaudit` goes deeper with world-writable detection.

Expansion Stats Dashboard

Your aliases are working for you — here's the proof.

Zplwexpandstats

Every time `zsh-expand` fires — alias, global alias, suffix alias, self-ref escape, native glob/hist, or spelling correction — it logs the event. `zplrExpandStats` reads that log and shows you a ranked dashboard.

```
zplr expandstats        # show full dashboard
zplr expandstats -h     # help with all options
zplr expandstats -t 10  # top 10 aliases
zplr expandstats -w 80  # wider box (80 cols)
zplr expandstats -r     # reset all stats
zplr expandstats -f FILE # custom stats file
```

What It Tracks

```
By trigger ..... space expansions vs history expansions
By type ..... alias, global, suffix, escape, native
Corrections ..... spelling fixes applied
```

Total expansions ... how many times the engine fired
Keystrokes saved ... chars you didn't have to type

```
Top aliases ..... ranked bar chart with expansions shown
```

How It Works

The zsh-expand plugin hooks into the zle accept-line widget. Before each command runs, it expands aliases, globals, and suffixes inline. Each expansion is logged to `$ZPWR_LOCAL/zpwr-expand-stats.dat` with the trigger type, expansion type, and original alias name.

Config

```
ZPWR_EXPAND_STATS_FILE    # override stats file path
ZPWR_EXPAND_STATS_TOP     # default top N (default: 20)
```

Every alias that fires is a keystroke investment paying dividends. This dashboard shows your ROI.

Chapter 8 – Environment Mastery

Know Your Shell

// you cannot master what you cannot measure //

Three verbs to audit your environment. Each one reveals a different cross-section of the machine you live inside.

Envvars: The zpwr Variables

```
zpwr envvars          # list all ZPWR_* env vars
zpwr ev              # same thing, shorter
```

Shows every environment variable starting with ZPWR_. These are the knobs and dials of the framework: paths, flags, plugin manager config, colorscheme, etc. If something is misconfigured, this is where you look.

Envvarsall: The Full Picture

```
zpwr envvarsall       # every env var, all of them
zpwr eva              # same thing, shorter
```

Dumps every exported variable. This includes ZPWR_*, PATH, HOME, EDITOR, LANG, and everything else. Pipe it to fzf when you are hunting for a specific var:

```
zpwr eva | fzf
```

Environmentcounts: The Numbers Game

```
zpwr environmentcounts # full environment statistics
zpwr envcounts         # alias
zpwr e                 # shortest form
```

This is the census. It counts everything loaded in your current shell session:

Aliases regular + global + suffix aliases functions autoloaded + defined functions builtins zsh builtin commands parameters shell variables (scalar, array, assoc) completions registered completion functions modules loaded zsh modules named dirs hash -d entries PATH entries directories in PATH FPATH entries directories in FPATH.

The numbers tell you how armed you are. A fresh zpwr install might show thousands of aliases, hundreds of functions, and many registered completions. If the numbers are low, something failed to load.

Pro Tip: Pair Them

```
zpwr doctor          # is anything broken?
zpwr e               # how much loaded?
zpwr ev              # are my zpwr vars right?
```

Run all three after installing or updating zpw. They are your post-deployment smoke test.

The Option Matrix

// zsh has 200+ options. most people know 5. time to fix that. //

The zsh option system is a maze of boolean switches that control everything from globbing to history to error handling. These verbs help you navigate the labyrinth.

Options: The Boolean Switches

```
zpw options # list all set options
```

Shows every zsh option that is currently ON. The important ones for zpw: extendedglob (#, ~, ^ in globs) – zpw needs this autopushd (cd pushes to dirstack) histignorealldups (no duplicate history) sharehistory (history shared across sessions) completeinword (tab complete mid-word) promptsubst (parameter expansion in prompts)

If extendedglob is off, half of zpw's glob tricks die. If sharehistory is off, your sessions are islands.

Modules: The Loaded Extensions

```
zpw modules # list loaded zsh modules
```

Zsh modules are C libraries that add features: zsh/datetime EPOCHREALTIME, strftime zsh/stat zstat builtin for file metadata zsh/zutil zparseopts for flag parsing zsh/complint menuselect completion listing zsh/parameter \$functions, \$aliases, \$parameters hashes zsh/terminfo terminal capability strings.

If zsh/parameter is not loaded, zpw env verbs break. If zsh/datetime is missing, timing-based verbs fail. Load a missing module: zmodload zsh/modulename.

Zstyle: The Fine-tuning Knobs

```
zpw zstyle # list all zstyle settings
```

Zstyle is zsh's configuration registry. It controls: :completion:* how tab completion behaves :vcs_info:* git/svn info in prompts :zpw:* zpw-specific settings.

Example styles zpw sets: zstyle ':completion:*' menu select zstyle ':completion:*' matcher-list 'm:{a-z}={A-Z}' The first enables arrow-key menu selection in tab complete. The second makes completion case-insensitive.

Detective Work

Completions acting weird? Check:

```
zpw options # is completeinword on?
zpw modules # is zsh/complint loaded?
zpw zstyle # what completion styles are set?
```

The answer is usually hiding in one of these three.

Cache Search

// the environment is a haystack. these are your magnets. //

zpwr maintains an environment cache for fast lookup. These verbs let you search, inspect, and edit that cache without grepping through raw variable dumps.

Environmentcachesearch: fzf Env Navigation

```
zpwr environmentcachesearch      # fzf through cached env
```

Opens an fzf interface over the environment cache. Type a few characters to filter. The cache includes: - All exported environment variables - ZPWR_* configuration variables - PATH and FPATH entries - Named directory mappings.

This is faster than `env | grep` because it uses the pre-built cache file rather than querying the live env.

Envaccept: Accept A Cache Entry

```
zpwr envaccept                  # accept/apply cached env entry
```

After finding a variable in the cache, this verb applies it to your current session. Useful when the cache has a value you want but the live env does not.

Envedit: Edit The Environment

```
zpwr envedit                    # open env cache in $EDITOR
```

Opens the environment cache file in your editor. Make changes, save, and the cache is updated. This is the surgical approach: when you know exactly which variable needs tweaking.

The Cache Lifecycle

1. `zpwr regenenvcache` builds the cache from live env
2. `environmentcachesearch` fuzzy-searches the cache
3. `envaccept` applies an entry
4. `envedit` manual edits

The cache lives at `$ZPWR_LOCAL`. It is regenerated during shell startup and when you run `zpwr regenenvcache`.

Workflow Example

“What is `ZPWR_EDITOR` set to?”

```
zpwr environmentcachesearch      # type 'EDITOR' in fzf
```

Found it: `ZPWR_EDITOR=nvim`.

“I want to change a bunch of `ZPWR_` vars.”

```
zpwr envedit                     # opens in $EDITOR
```

Edit the vars, save, done.

“Something is off, rebuild the cache.”

```
zpwr regenenvcache               # fresh cache from live env
```

Pro Tip

If you are debugging a missing env var, check two places: `zpwr environmentcachesearch` (cached) and `zpwr eva` (live). If cache has it but live does not, run `zpwr regenenvcache`.

Snapshots & Time Travel

// save your universe. restore it when everything goes wrong. //

The snapshot verb captures your entire terminal environment to a portable directory. The restore verb brings it back. This is git for your shell state.

Taking A Snapshot

```
zpwr snapshot                # timestamp-named snapshot
zpwr snapshot myproject      # named snapshot
zpwr snapshot before-refactor # meaningful name
```

What Gets Captured

Hash dirs named directory mappings (hash -d) aliases regular + global + suffix aliases env vars all exported variables (secrets excluded) zpwr vars ZPWR_VARS associative array functions user function count tracking history full shell history dump tmux sessions, windows, panes, resurrect state vim sessions saved vim session files dir stack current directory and pushd stack git status branch, commit, dirty state of cwd.

Storage: `$ZPWR_LOCAL/snapshots/<name>/` Each snapshot is a directory of plain zsh files. Human-readable. Sourceable. Portable.

Restoring A Snapshot

```
zpwr restore                # list available snapshots
zpwr restore myproject      # restore everything
zpwr restore myproject aliases env # restore only aliases+env
zpwr restore myproject dirs  # just cd to saved pwd
```

Selective Restore Components

All everything (default when no component given) hash named directories only aliases regular, global, suffix aliases env environment variables tmux stage tmux-resurrect file (press prefix+Ctrl-r) vim vim session files to `~/.vim/sessions` history merge snapshot history into current session dirs cd to the saved working directory.

When To Use Snapshots

Before a big update: `zpwr snapshot before-update` Before experiments: `zpwr snapshot stable-state` Switching projects: `zpwr snapshot projectA` New machine setup: copy snapshot dir, restore on new host.

NOTE: Sensitive vars (PASSWORD, SECRET, TOKEN, AWS_SECRET*, GITHUB_TOKEN) are automatically excluded from env snapshots. Your secrets stay secret.

History merge is additive – it does not overwrite your current history. It uses `fc -R` to load entries.

Environment & Search

// 22 verbs to inspect and search the shell //

List env vars, search keybindings, inspect zsh internals, and navigate the cached environment.

Environment Variables

```
zpwir ev                # list all zpwir env vars
zpwir envvars           # list all zpwir env vars
zpwir environmentvars   # list all zpwir env vars
zpwir environmentvariables # list all zpwir env vars
zpwir envvarsall        # list all env vars
zpwir environmentvarsall # list all env vars
zpwir eva               # list all env vars
```

Environment Counts & Cache

```
zpwir e                # count all zpwir env
zpwir envcounts        # count all zpwir env
zpwir environmentcounts # count all zpwir env
zpwir envcachesearch   # fzf search cached aliases, params, builtins
zpwir environmentcachesearch# fzf search cached env
zpwir envaccept        # accept from fzf env
zpwir envedit          # edit from fzf env
```

Keybinding Search

```
zpwir allsearch        # search all keybindings
zpwir vimsearch        # search vim keybindings
zpwir zshsearch        # search zsh keybindings
```

zsh Internals

```
zpwir reload           # reparse env
zpwir modules          # show zsh modules via fzf
zpwir options          # show zsh options via fzf
zpwir zstyle           # fuzzy search zstyle
zpwir zcompdump         # edit zcompdump
```

Chapter 9 – The Janitor’s Closet

Cleanup Operations

// entropy is the enemy. the janitor is your friend. //

Shell environments accumulate garbage like a hoarder’s attic. Cache files grow stale. Temp dirs fill up. Logs balloon. These verbs are the Marie Kondo of your `$ZPWR`.

Cleanall: The Thermonuclear Broom

```
zpwr cleanall                # clean everything at once
```

Calls all the individual clean verbs in sequence. This is the “I do not know what is wrong but I want a fresh start” button. Safe but thorough.

Individual Clean Verbs

CLEANCACHE.

```
zpwr cleancache              # clear general caches
```

Wipes cached data that zpwr generates during operation. Safe to run any time. Everything rebuilds on demand.

CLEANCOMPCACHE.

```
zpwr cleancompcache          # clear completion cache
```

Removes the zsh completion cache directory. Run this when tab completions are showing stale results or when a new command does not appear in completions. Follow up with `zpwr regenzzsh` to rebuild `zcompdump`.

CLEANDIRS.

```
zpwr cleandirs                # clear cached dir listings
```

Removes directory cache files used by navigation commands. If directory completions point to dirs that no longer exist, this verb fixes that.

CLEANTEMP.

```
zpwr cleantemp                # clear temp files
```

Removes temporary files zpwr created during operation. These are transient by nature – safe to nuke.

CLEANDIRSandTEMP.

```
zpwr cleandirsandtemp         # dirs + temp combined
```

Convenience combo of `cleandirs` and `cleantemp`.

CLEANLOG.

```
zpwr cleanlog                 # truncate log files
```

The zpwr logfile grows forever if you never clean it. This verb truncates or removes old log entries. Check log size: `ls -lh $ZPWR_LOGFILE`

The Clean Workflow

Light cleanup (weekly):

```
zpwr cleantemp && zpwr cleanlog
```

Medium cleanup (monthly):

```
zpwr cleancache && zpwr cleancompcache && zpwr regenzsh
```

Full cleanup (when things feel sluggish):

```
zpwr cleanall
```

None of these delete your configuration or history. They only remove regenerable cache and temp data.

Git Cache Hygiene

// zpwr tracks your git repos. the cache needs a bath sometimes. //

zpwr maintains caches of git repository locations so that repo-aware verbs (navigation, status, batch operations) do not have to scan the filesystem every time. Three verbs manage these caches.

Cleangitcache: The General Repo Cache

```
zpwr cleangitcache # clear all git repo caches
```

Wipes the master list of known git repositories. This cache is built by scanning for .git directories and is used by verbs like zpwr fordir and repo navigation commands.

When to use it: - You moved or deleted git repos - Navigation is suggesting repos that no longer exist - You cloned new repos and they are not showing up.

After clearing, run zpwr regengitrepocache to rebuild.

Cleangitcleancache: Clean Repos Only

```
zpwr cleangitcleancache # clear clean repo cache
```

zpwr separately tracks which repos have a clean working tree (no uncommitted changes). This cache speeds up operations that only care about clean repos.

Clear this when: - The “clean repos” list seems wrong - You committed in a repo but it still shows as dirty.

Cleangitdirtycache: Dirty Repos Only

```
zpwr cleangitdirtycache # clear dirty repo cache
```

The mirror of the clean cache. Tracks repos with uncommitted changes. Clear this when: - A repo shows as dirty but you already committed - The dirty count in the banner seems wrong.

Rebuild with: zpwr regengitdirtyrepocache.

The Git Cache Architecture

Regengitrepocache scans for all git repos regengitdirtyrepocache classifies clean vs dirty cleangitcache wipes the master list cleangitcleancache wipes the clean-only list cleangitdirtycache wipes the dirty-only list.

The caches live in `$ZPWR_LOCAL` as plain text files. One repo path per line. Grep-friendly. Human-readable.

The Full Refresh

```
zpwr cleangitcache
zpwr regengitrepopcache
zpwr regengitdirtyrepopcache
```

Three commands. Fresh git cache. Takes a few seconds depending on how many repos you have scattered around.

Path Deduplication

// every duplicate entry is a tiny crime against performance //

PATH and FPATH grow duplicates like weeds. Every subshell, every sourced script, every tool that helpfully “adds itself to your PATH” can insert duplicates. The deduppaths verb removes them.

The Verb

```
zpwr deduppaths                # deduplicate PATH and FPATH
```

Removes duplicate entries from both PATH and FPATH while preserving the order of first occurrence. If `/usr/bin` appears 3 times, only the first one survives.

Why Duplicates Happen

1. Shell inheritance Parent shell sets PATH. Child shell re-sources `.zshrc`. PATH grows. Nested tmux sessions make it worse.
2. Multiple init scripts Homebrew, nvm, pyenv, rbenv, cargo – each one adds to PATH in their init hook. Source them twice, PATH grows.
3. `/etc/zprofile` on macOS macOS ships with `/etc/zprofile` that runs `path_helper`. `path_helper` reads `/etc/paths` and `/etc/paths.d/` and prepends entries. This runs on every login shell, BEFORE your `.zshrc`. Duplicates guaranteed.
4. Manual PATH manipulation `export PATH="/my/dir:$PATH"` in `.zshrc`. Every time `.zshrc` is sourced, another copy appears.

How To Prevent Duplicates

Zsh has a built-in mechanism: the `typeset -U` flag.

```
typeset -U path fpath
```

This marks the arrays as “unique” – zsh automatically removes duplicates when entries are added. `zpwr` sets this early in startup. But if something adds to PATH before `zpwr` loads, duplicates can sneak in.

Diagnosing The Problem

```
zpwr pathaudit          # full audit: dupes, missing, writable
zpwr doctor             # checks for duplicate PATH/FPATH
print -l $path | sort | uniq -d # show only duplicated entries
echo $#path             # count PATH entries
```

A healthy PATH has 10-30 entries. If you see 50+, something is adding entries in a loop.

The Fix

```
zpwr dedupaths          # instant dedup
```

Run it. Then check: `echo $#path` If the count dropped, you had duplicates. If it drops a lot, investigate the source.

For a permanent fix, find the script that adds duplicates and guard it with a check:

```
[[ -z ${path[(r)/my/dir]} ]] && path=(/my/dir $path)
```

The Nuclear Options

// when gentle cleanup is not enough. when you need to nuke from orbit. //

Most clean verbs are surgical. These two are orbital strikes. They clean, regenerate, rebuild, and update in one shot. Use them when you want a fresh start without reinstalling.

Cleanrefreshupdate: The Big Red Button

```
zpwr cleanrefreshupdate # clean + regen + update
```

This is the full-cycle maintenance verb. It: 1. Cleans all caches (equivalent to `cleanall`) 2. Regenerates compiled files, completions, env cache 3. Runs the update cycle for `zpwr` and plugins.

Think of it as “factory reset without losing data.” Your configuration, history, and local files survive. Everything else gets rebuilt from source.

When to use it: - Shell startup feels slow and you have tried individual fixes - After a major zsh or macOS upgrade - When individual clean verbs did not solve the problem - When you want to feel powerful.

TIME COST: Several minutes. This is not instant. It downloads plugin updates and recompiles everything.

Cleanupdatedeps: The Dependency Purge

```
zpwr cleanupdatedeps    # clean deps + update them
```

Focused on external dependencies rather than caches. This verb: 1. Cleans stale dependency state 2. Updates all managed dependencies.

When to use it: - Plugin versions are stuck at old commits - A dependency update broke something - You want the latest of everything.

Decision Matrix

Symptom Verb.

Stale completions zpwr cleancompcache Slow startup zpwr recompile Missing new repos in nav zpwr cleangit-cache General weirdness zpwr cleanall Everything is broken zpwr cleanrefreshupdate Plugins are ancient zpwr cleanupdatedeps.

The Escalation Path

Always start small and escalate:

```
zpwr cleantemp           # level 1: temp files
zpwr cleancache          # level 2: all caches
zpwr cleanall            # level 3: everything
zpwr cleanrefreshupdate  # level 4: clean + rebuild + update
```

Do not start with level 4. That is like calling an airstrike because you saw a spider.

Cleanup Arsenal

// 14 verbs to sweep the floor //

Clean directories, caches, temp files, logs, and git state. From surgical precision to nuclear wipe.

Directory Cleaning

```
zpwr cleandirs           # clear all $ZPWR_DIRS_CLEAN
zpwr cleandirsandtemp    # clear dirs and temp
zpwr cleanall            # clear dirs, temp and cache
zpwr cleantemp           # clean all zpwr temp files
```

Cache Cleaning

```
zpwr cleancache          # clean all zpwr cache files
zpwr cleancompcache      # clean all zpwr compsys cache files
zpwr cleangitcache       # clean all git repo cache files
zpwr cleangitdirtycache  # clean git repo dirty cache files
zpwr cleangitcleancache  # clean git repo clean cache files
```

Log & Update Cleaning

```
zpwr cleanlog            # clear $ZPWR_LOGFILE
zpwr cleanrefreshupdate  # clean, refresh zwc, update deps
zpwr cleanupdatedeps     # clean and update deps
```

Do Everything

```
zpwr a                   # banner, counts, clean, refresh, test, update
zpwr all                  # banner, counts, clean, refresh, test, update
```

Chapter 10 – Build System

Compilation 101

// .zwc files: compiled zsh. faster loading. dark magic. //

Zsh can compile scripts to an internal bytecode format stored in .zwc (Zsh Word Code) files. Loading compiled files is faster than parsing source text every time.

What Is A .ZWC File?

A .zwc file is the compiled form of a .zsh script or an autoload function directory. When zsh finds foo.zwc next to foo.zsh, it loads the compiled version – skipping the parsing step entirely.

For individual files: `zcompile foo.zsh -> foo.zsh.zwc` For directories: `zcompile dir.zwc dir/* -> dir.zwc`.

The speed difference is measurable on large files and during startup when many files are sourced.

Recompile: Build All .ZWC Files

```
zpwr recompile      # compile all zpwr files
zpwr compile        # same thing
```

Scans all zpwr source files and compiles them to .zwc. This includes: - Autoload function files in `$ZPWR_AUTOLOAD` - Shell scripts in `$ZPWR_ENV` - Any .zsh file that has changed since last compile.

Related Compile Verbs

```
zpwr recompilefiles # compile specific file set
zpwr compilefiles   # alias for above
zpwr recompilefpath # compile FPATH directories
zpwr compilefpath    # alias for above
```

Decompile: Remove .ZWC Files

```
zpwr decompile      # remove all .zwc files
zpwr uncompile       # alias for above
```

Deletes all .zwc files in zpwr. After this, zsh falls back to parsing source files directly. Useful when: - Debugging a function that behaves differently than source - You suspect a stale .zwc file is loading old code - zpwr doctor reports stale .zwc files.

Refreshzwc: Smart Rebuild

```
zpwr refreshzwc      # refresh only stale .zwc files
```

Only recompiles .zwc files that are older than their source. Faster than a full recompile when only a few files changed.

The Compilation Workflow

After editing zpwr source files:

```
zpwr recompile          # rebuild .zwc files
```

If something is weird after an update:

```
zpwr decompile && zpwr recompile # clean rebuild
```

Quick check for stale files:

```
zpwr doctor            # reports stale .zwc files
```

The .zwc files are safe to delete. They are purely a performance cache. Source files are always the authority.

Compsys Cache

// tab completion is a religion. the zcompdump is its scripture. //

The zsh completion system (compsys) is the most complex part of zsh. It maintains a dump file (zcompdump) that caches all registered completions. When it breaks, tab completion goes haywire. Here is how to fix it.

What Is Zcompdump?

A file (usually `~/.zcompdump` or in `$ZPWR_LOCAL`) that contains all compdef registrations. When zsh starts, it sources this file instead of re-scanning all completion functions. This saves 100-500ms of startup time.

Location: `$ZSH_COMPDUMP` The file starts with `#files:TIMESTAMP` and contains compdef calls for every registered completion.

Regenzsh: The Completion Reset

```
zpwr regenzzsh          # regenerate zcompdump
```

Deletes the old zcompdump and forces compinit to rebuild it. This is the #1 fix for completion problems:

Symptom: New command installed but tab complete ignores it Fix: `zpwr regenzzsh`.

Symptom: Tab shows wrong completions for a command Fix: `zpwr cleancompcache && zpwr regenzzsh`.

Symptom: "command not found: compdef" errors on startup Fix: `zpwr regenzzsh`.

Symptom: Startup is slow (500ms+ for completion init) Fix: `zpwr regenzzsh` (forces fresh, optimized dump)

The Completion Cache Directory

Separate from zcompdump, zsh also caches individual completion results (like package names, hostnames, etc.) in a cache directory.

```
zpwr cleancompcache      # wipe the cache directory
```

This forces completions to re-query their sources. Useful when package lists or hostnames changed.

Why Completions Break

1. Stale zcompdump – new compdef not registered
2. Corrupted zcompdump – syntax error in dump file
3. Missing FPATH entry – completion function not found
4. Wrong function loaded – .zwc has old version
5. Plugin conflict – two plugins register for same cmd

The Nuclear Fix

```
zpwr cleancompcache
zpwr decompile
zpwr regenzzsh
zpwr recompile
```

Four commands: nuke cache, remove .zwc, regen dump, recompile. This fixes 99% of completion problems. The remaining 1% is probably a bug in the completion function itself.

Tag Generation

// ctrl-j in vim. M-. in emacs. the tags file makes it work. //

Tags files are indexes of symbol definitions: functions, variables, classes, methods. Your editor uses them to jump to definitions with a single keystroke. zpwr generates them.

Ctags: The Classic

```
zpwr regenc tags # regenerate ctags file
```

Runs exuberant-ctags or universal-ctags over the zpwr codebase. Produces a tags file that vim and emacs read.

In vim: Ctrl-J jumps to the definition under cursor. In vim: Ctrl-T jumps back to where you were. In vim: :tag zpwrDoctor jumps to zpwrDoctor.

Ctags understands shell functions, C, Python, Ruby, and dozens of other languages out of the box.

Gtags: The Gnu Global System

```
zpwr regeng tags # regenerate GNU Global tags
```

GNU Global is a more powerful tagging system. It supports: - Forward references (where is this defined?) - Backward references (where is this called from?) - Symbol completion.

Produces GTAGS, GRTAGS, GPATH files in the project root. Query from command line: global -x zpwrDoctor
Query references: global -rx zpwrDoctor.

Gtags With Pygments Parser

```
zpwr regeng tagspygments # gtags with Pygments backend
```

Uses the Python Pygments parser instead of the built-in one. Pygments understands more languages and file types. Requires: pip install pygments.

Gtags By File Type

```
zpwr regengtagstype          # gtags filtered by type
```

Generate tags for a specific file type only. Faster than a full regen when you only care about one language.

How Tags Work With Your Editor

vim reads 'tags' file. :set tags=.[/tags](#);,tags Ctrl-] to jump, Ctrl-T to return :tselect for multiple matches.

emacs reads TAGS file (etags format) or uses gtags M-. to find definition, M-* to return ggtags-mode or helm-gtags for GNU Global.

nvim same as vim, plus LSP which often replaces tags but tags still work as a fast fallback.

When To Regenerate

- After adding or renaming functions - After a zpwr update that adds new verbs - When "tag not found" errors appear for known functions - Use zpwr watch '*.zsh' 'zpwr regenctags' for auto-regen

Cache Regeneration

// the opposite of cleaning. building the caches back up. //

Cleaning removes caches. Regeneration rebuilds them. These verbs construct the indexes and precomputed data that make zpwr fast.

Regen: The Standard Rebuild

```
zpwr regen                  # regenerate common caches
```

Rebuilds the most frequently used caches: environment cache, config links, keybindings. This is the verb you reach for after editing config files.

Regenall: The Full Rebuild

```
zpwr regenall              # regenerate everything
```

Every cache. Every index. Every precomputed file. This is the thorough version of regen. Takes longer but leaves nothing stale.

Individual Regen Verbs

Regenenvcache.

```
zpwr regenenvcache        # rebuild environment cache
```

Snapshots all env vars to a cache file for fast lookup. Used by environmentcachesearch and other env verbs.

Regenkeybindings.

```
zpwr regenkeybindings     # rebuild keybinding index
```

Re-registers all zpwr keybindings. Run this after editing keybinding configuration or after a plugin clobbered your bindings.

Regenconfiglinks.

```
zpwr regenconfiglinks          # rebuild config symlinks
```

Re-creates the symlinks from `~/.zshrc`, `~/.vimrc`, etc. into the zpwr directory tree. Run this after a fresh clone or when zpwr doctor reports broken config links.

Regenhistory.

```
zpwr regenhistory              # clean up history file
```

Processes the HISTFILE to remove corrupted entries. Zsh history files can accumulate broken lines from concurrent writes or improper shutdowns.

Regenpowerline.

```
zpwr regenpowerline           # rebuild powerline config
```

Regenerates powerline/p10k configuration. Run when the prompt looks wrong after a terminal font change.

Regengitrepoche.

```
zpwr regengitrepoche          # scan and cache git repos
```

Walks the filesystem finding git repos and builds a master list. Used by repo navigation and batch verbs.

The Regen Cheat Sheet

After editing config: `zpwr regen` After zpwr update: `zpwr regenall` After env var changes: `zpwr regenenvcache`
After repo changes: `zpwr regengitrepoche` After completion issues: `zpwr regenbash`.

Updates & Dependencies

// staying current without breaking everything. a balancing act. //

zpwr is a living system that depends on external tools, plugins, and its own git repository. These verbs keep everything synchronized.

Update: The Core Update

```
zpwr update                    # update zpwr itself
```

Pulls the latest zpwr from the git remote. This is a git pull on `$ZPWR`. Your local config in `$ZPWR_LOCAL` is not touched.

Updateall: The Everything Update

```
zpwr updateall                # update zpwr + all plugins
```

Updates zpwr, zinit plugins, and other managed components. This is the weekly maintenance verb. Run it when you want the latest of everything.

Updatedeps: Dependency Updates

```
zpwr updatedeps                # update external dependencies
```

Updates the external tools zpwr depends on: zinit plugins, zsh-autosuggestions, zsh-syntax-highlighting, etc. Does not touch zpwr's own code.

Updatedeps-clean: Clean + Update Deps

```
zpwr updatedeps-clean          # fresh dependency install
```

Cleans stale dependency state first, then updates. Use when updatedeps alone does not fix plugin issues.

Updatezinit: zinit Only

```
zpwr updatezinit              # update zinit plugin manager
```

Updates just the zinit plugin manager binary, not the plugins it manages. Use when zinit itself has a bug or you need a newer zinit feature.

Updatepull: Git Pull All Repos

```
zpwr updatepull              # pull all tracked git repos
```

Iterates over all cached git repos and runs git pull. Useful when you have many repos that track remotes and you want them all current.

The Update Hierarchy

Update just zpwr (git pull) updatedeps just plugins and tools updatezinit just the plugin manager updateall zpwr + plugins + tools updatepull all tracked git repos updatedeps-clean clean slate + update deps.

Recommended Update Schedule

Weekly: zpwr updateall After update: zpwr recompile If broken: zpwr updatedeps-clean.

Always recompile after updating. New source files need new .zwc files. The old compiled versions will load stale code until you recompile.

Regen & Compile

// 24 verbs to rebuild the world //

Regenerate caches, recompile zsh word code, and rebuild tags. The engine room of ZPWR maintenance.

Regen Caches

```
zpwr regen          # regen caches except git drive search
zpwr regenall        # regen all caches
zpwr regenpdf        # regenerate encyclopedia PDF
zpwr regenenvcache   # regen search env to zpwrEnv files
zpwr regengitrepocache # regen list of all git repos
zpwr regengitdirtyrepocache # regen list of dirty git repos
zpwr regenhistory    # regen $HISTFILE
zpwr regenkeybindings # regen all keybindings cache
zpwr regenconfiglinks # regen sym links to $HOME
zpwr regenpowerline  # regen powerline sym link
zpwr regenzsh        # regen compsys cache
```

Regen Tags

```
zpwr regengtags      # regen gtags files to $HOME
zpwr regenctags       # regen ctags files to $HOME
zpwr regengtagspygments # regen GNU gtags with pygments
zpwr regengtagstype   # regen GNU gtags with specified parser
```

Compile & Decompile

```
zpwr compile         # recompile all cache comps
zpwr compilefpath     # recompile all fpath cache comps
zpwr compilefiles     # recompile all files cache comps
zpwr recompile        # recompile all cache comps
zpwr recompilefpath   # recompile all fpath cache comps
zpwr recompilefiles   # recompile all files cache comps
zpwr refreshzwc       # delete then regen compiled zsh word code
zpwr decompile        # delete all cache comps
zpwr uncompile        # delete all cache comps
```

Update System

// 6 verbs to stay current //

Keep ZPWR, its dependencies, and zinit plugins up to date. From surgical single-dep pulls to full system updates.

Config Updates

```
zpwr update          # update zpwr custom configs
zpwr updatepull       # pull latest config from repo
```

Dependency Updates

```
zpwr updatedeps       # update all dependencies
zpwr updatedepsclean  # update all dependencies then clean
zpwr updatezinit      # update zinit dependencies
```

Full Update

```
zplr updateall          # update zplr configs and all deps
```

Typical workflow: `zplr updateall` pulls the latest configs, updates `brew/pip/npm/gem/zinit`, and refreshes caches. Run `zplr updatedepsclean` afterward to reclaim disk space from stale packages.

Chapter 11 – Monitoring & Automation

File Watching

// your files change. your command runs. automatically. //

The watch verb monitors files for changes and auto-executes a command when something is modified. It is the poor man's CI pipeline, running locally in your terminal.

Usage

```
zpw watch '<GLOB>' '<COMMAND>'
```

Two arguments: what to watch, and what to run. Quote both arguments to prevent premature expansion.

Practical Examples

```
zpw watch '*.zsh' 'zpw recompile'
```

Recompile zpw whenever a .zsh file changes. Edit a function, save, and .zwc files auto-rebuild.

```
zpw watch 'src/**/*.ts' 'npm run build'
```

Build your TypeScript project on every source change.

```
zpw watch 'Makefile' 'make'
```

Run make whenever the Makefile changes.

```
zpw watch '.' 'echo changed'
```

Watch the entire current directory.

```
zpw watch '*.py' 'python -m pytest'
```

Run tests on every Python file change. TDD mode.

Platform Backend

MacOS: Uses fswatch (brew install fswatch) Linux: Uses inotifywait (apt install inotify-tools)

The verb auto-detects which tool is available. If neither is found, it tells you what to install.

The Output Format

Each trigger shows a box with: - Trigger count (how many times it has fired) - Timestamp (when the change was detected) - Filename (which file changed) - Exit status (green ok or red exit code) - Elapsed time (how long the command took)

How To Stop

Press Ctrl-C. The watcher process terminates cleanly.

Glob Handling

The glob is split into directory and file filter: 'src/**/*.ts' -> watch src/ recursively, filter *.ts '.' -> watch current dir, no filter '*.zsh' -> watch ./, filter *.zsh.

The glob-to-regex conversion handles * and ? patterns. For fswatch, it uses -e '.*' -i to exclude-then-include. For inotifywait, it uses zsh's glob matching on filenames.

Command Replay

// your history is a script. replay it on demand. //

The replay verb plays back the last N commands from your shell history. Three modes: look, execute, or tmux pane. It is a VCR for your terminal.

Basic Usage

```
zpwir replay                # preview last 10 commands
zpwir replay 20              # preview last 20
zpwir replay 5 exec          # execute last 5 with timing
zpwir replay 10 tmux         # replay in a tmux split pane
```

The Three Modes

PREVIEW MODE (default, safe)

```
zpwir replay
zpwir replay 20 preview
```

Lists the commands with line numbers. Nothing executes. Use this to review what you did before replaying it. The output shows helpful hints for switching to exec/tmux.

EXEC MODE (runs in current shell)

```
zpwir replay 5 exec
```

Executes each command sequentially in your current shell. Each command shows: - Command number [1/5] - The command being run - Exit status (green ok or red exit code) - Elapsed time in milliseconds.

WARNING: This runs real commands. If your last 5 commands included rm -rf something, it will do it again. Always preview first.

TMUX MODE (runs in a new pane)

```
zpwir replay 10 tmux
```

Opens a new tmux split pane and replays commands there. Your current pane is untouched. You can watch the replay happen side-by-side with your current work. The pane waits for Enter when done, then cleans up. Requires an active tmux session.

Use Cases

Reproduce a bug: `zpwrr replay 3 exec Demo` your workflow: `zpwrr replay 20 tmux Audit` what you did: `zpwrr replay 50` Re-run a build chain: `zpwrr replay 4 exec`.

How It Works

Uses `fc -rl -N` to extract the last N history entries. Reverses them to chronological order. In exec mode, each command is eval'd with timing via `EPOCHREALTIME`. In tmux mode, a temp script is built and executed in a split pane with a 0.5s delay between commands for readability. The script self-destructs after completion.

Log Surveillance

// watching logs in glorious technicolor. the ccze way. //

`zpwrr` logs everything: startup, errors, plugin loads, debug messages. The `taillog` verb tails these logs with optional ccze colorization for maximum readability.

Basic Usage

```
zpwrr taillog          # follow log with colors
zpwrr taillog -n 50    # last 50 lines, then follow
zpwrr taillog -f       # colorize without following
zpwrr taillog -r       # raw output with line numbers
```

The Flags

`-n, --lines N` Show last N lines before following `-f, --no-follow` Just colorize, do not tail `-r, --raw` No ccze, plain output with line numbers

Custom Logfile

```
zpwrr taillog /var/log/system.log
zpwrr taillog /var/log/syslog
```

The last argument can be any logfile path. Default: `$ZPWR_LOGFILE` (the `zpwrr` logfile).

Ccze: The Secret Weapon

ccze is a log colorizer that understands dozens of log formats: syslog, Apache, Postfix, PHP, kernel messages, and more. It auto-detects the format and colorizes:

Timestamps in one color warnings in yellow errors in red info in cyan.

```
hostnames      in magenta
```

Install: `brew install ccze` or `apt install ccze` If ccze is not found, `taillog` falls back to plain output with a helpful install hint.

The zpwrr Logging Verbs

`Taillog` consumes logs. These verbs produce them:

```
zpwr logdebug <msg>          # debug level
zpwr loginfo <msg>           # info level
zpwr logerror <msg>          # error level
zpwr logtrace <msg>          # trace level (most verbose)
```

The *console variants also print to stderr:

```
zpwr logdebugconsole <msg>
zpwr loginfoconsole <msg>
zpwr logerrorconsole <msg>
zpwr logtraceconsole <msg>
```

Log Maintenance

Logs grow forever. Clean them periodically:

```
zpwr cleanlog                # truncate the logfile
```

Or check the size first: `ls -lh $ZPWR_LOGFILE`

A 100MB logfile means your debug logging is too chatty. A 1KB logfile means nothing is being logged. Both are worth investigating.

Backup & Restore

// your history is priceless. these verbs are the insurance policy. //

Your shell history is years of accumulated knowledge: every command you ran, every fix you found at 2am, every pipeline you crafted. Losing it is losing institutional memory. These verbs prevent that.

Backup: The General Backup

```
zpwr backup                  # backup zpwr configuration
```

Creates a timestamped backup of zpwr configuration files. This captures your local settings, tokens, and any customizations in `$ZPWR_LOCAL`.

Backup destination: `$ZPWR_LOCAL/rcBackups/` Each backup is timestamped so you can have many.

Backuphistory: The History Vault

```
zpwr backuphistory          # backup HISTFILE
```

Copies your HISTFILE to the backup directory with a timestamp. This is the most important backup in zpwr.

Your HISTFILE can be corrupted by: - Power loss during write - Concurrent sessions fighting over the file - Disk full causing truncated writes - Bad .zsh_history format from import/merge.

A weekly zpwr backuphistory gives you a safety net.

Restorehistory: The Time Machine

```
zpwr restorehistory         # restore from backup
```

Restores HISTFILE from the most recent backup. Use when your history is corrupted or accidentally truncated.

The restore process: 1. Finds the latest backup in `$ZPWR_LOCAL/rcBackups` 2. Backs up the current (possibly broken) HISTFILE 3. Copies the backup over HISTFILE 4. Reloads history with `fc -R`.

Snapshots Vs Backups

Snapshot captures full env state (aliases, vars, tmux) backup copies config files to safety backuphistory specifically targets HISTFILE.

Use snapshots for environment state. Use backups for file safety. They complement each other.

The Safety Protocol

Before a big change:

```
zpwr snapshot before-change
zpwr backuphistory
zpwr backup
```

Now you have three layers of protection: env snapshot, history backup, and config backup. If the change goes sideways, you can recover everything.

Cron It

Add to your crontab (`crontab -e`):

```
0 3 * * 0 zsh -c 'source ~/.zshrc; zpwr backuphistory'
```

Every Sunday at 3am. Automatic insurance.

Live Dashboard & Sparklines

Your shell's vital signs, in real time.

zpwr Top

A live-updating dashboard of your shell's resource usage. Runs in alternate screen buffer. Press `q` to quit.

```
zpwr top      # refresh every 2s
zpwr top 1    # fast refresh
zpwr top 5    # slow refresh
zpwr dashboard # same verb
zpwr live     # same verb
```

What It Shows

```
Memory ..... RSS bar graph, virtual memory
Shell objects ..... functions, aliases, completions, params
Delta tracking .... changes between refreshes in yellow
Loaded modules .... all zsh modules currently loaded
Paths ..... fpath, path, named dirs, dir stack
Context ..... git branch, tmux info, startup time
```

Top 5 functions .. largest functions with size bars.

```
Top 5 paths ..... longest PATH entries
```

Sparklines

Startup time history: last 40 shell starts Color-coded: green=fast yellow=mid red=slow Shows min/max/avg stats below the graph.

Commit velocity: commits per day over 30 days Visualizes your development pace as a mini bar chart.

Startup times are logged automatically on each shell init to `$ZPWR_LOCAL/startup_history.log`.

Chapter 12 – Utility Arsenal

File & Process Operations

// the everyday tools. sharpened and color-coded. //

zpwr wraps common file and process operations with enhanced output, color, and fzf integration. These are the verbs you reach for twenty times a day.

File Listing

```
zpwr clearlist      # clear screen + list files
zpwr clearls        # alias for clearlist
zpwr info           # alias for clearlist
zpwr list           # list files (no clear)
zpwr ls             # alias for list
```

Clearlist is the most-used verb after help. It clears the terminal and shows a fresh directory listing. Uses eza if available, falls back to ls.

File Viewing

```
zpwr cat <file>     # colorized cat
zpwr c <file>        # shortest form
zpwr catcd <dir>     # cat files in a directory
```

Cat/c uses bat or pygmentize for syntax highlighting when available. Plain cat as fallback. catcd lists the contents of each file in a directory.

Process Management

```
zpwr ps             # enhanced process listing
zpwr kill            # fzf-powered process kill
zpwr killedit        # kill then edit related file
```

zpwr kill is the crown jewel here. It pipes process listings through fzf, letting you fuzzy-search for the process you want to terminate. Select it, confirm, dead. No more guessing PIDs.

File Descriptors

```
zpwr lsof            # list open files (enhanced)
zpwr lsofedit         # lsof then edit result
```

zpwr lsof wraps lsof with fzf filtering. Useful when tracking down which process holds a file or which files a process has open.

File Opening

```
zplr open                # open file/dir with system
```

Opens the target with the system handler: Finder on macOS, xdg-open on Linux. Works with files, directories, URLs.

The Combo Moves

Clear terminal, list files, check what is running:

```
zplr clearlist && zplr ps
```

Find and kill a zombie process:

```
zplr kill                # fzf search -> select -> terminate
```

Find what is holding a port:

```
zplr lsof                 # fzf through open files and ports
```

Batch Execution

// one command, many targets. the industrial strength loop. //

When you need to run the same operation across multiple files, directories, or git repos, these verbs replace hand-rolled for loops with tested, colorized execution.

For: The Basic Iterator

```
zplr for <command>        # run command in current dir context
```

Executes a command with zplr's enhanced output formatting. Shows timing, exit status, and colorized output.

For10: The Stress Test

```
zplr for10 <command>      # run command 10 times
```

Executes a command 10 times. Useful for: - Benchmarking (is the timing consistent?) - Flaky test detection (does it fail intermittently?) - Load testing (can it handle rapid repeated execution?)

Fordir: Iterate Over Git Repos

```
zplr fordir <command>     # run command in each git repo
```

Iterates over all cached git repos, cd's into each one, and runs the command. Extremely powerful for bulk operations:

```
zplr fordir 'git status -s' # dirty files in all repos
zplr fordir 'git pull'      # pull all repos
zplr fordir 'git stash list' # find forgotten stashes
```

Each repo's output is labeled with its path so you know which repo produced which output.

Fordirupdate: Pull All Repos

```
zpwr fordirupdate          # git pull in every repo
```

Specialized version of fordir that runs git pull in every cached repo. Same as zpwr fordir 'git pull' but optimized for the common case.

Execglob: Glob-based Execution

```
zpwr execglob <glob> <command>    # run command on glob matches
```

Finds files matching a glob and runs a command on each:

```
zpwr execglob '*.log' 'wc -l'      # line count each log file
zpwr execglob '*.bak' 'rm'        # delete all .bak files
```

Execglobparallel: Parallel Glob Execution

```
zpwr execglobparallel <glob> <cmd> # parallel execution
```

Same as execglob but runs commands in parallel. Useful when processing many files that are I/O-bound:

```
zpwr execglobparallel '*.png' 'optipng' # compress images
```

The Power Combos

Find all repos with uncommitted work:

```
zpwr fordir 'git diff --stat HEAD'
```

Count lines in all Python files:

```
zpwr execglob '**/*.py' 'wc -l'
```

Stress test a flaky command:

```
zpwr for10 'curl -s localhost:3000/health'
```

Text Operations

// find and replace. rename. count. transform. //

Text manipulation is the bread and butter of shell work. These verbs handle the common cases: renaming files, replacing strings, counting lines, and transforming text.

Rename: File Renaming

```
zpwr rename                # rename files with patterns
```

Renames files using pattern matching. Safer than raw mv because it shows what will happen before doing it.

Replacer: Find And Replace In Files

```
zpwr replacer                # search and replace in files
```

Performs find-and-replace across multiple files. The codebase refactoring tool. When you renamed a function and need to update every call site.

Changename: Rename With History

```
zpwr changename              # rename with tracking
```

Renames files or directories with additional tracking. More sophisticated than basic rename for complex renaming operations.

Changenamezpwr: Zpwr-specific Rename

```
zpwr changenamezpwr          # rename within zpwr codebase
```

Specialized rename for zpwr function and file names. Handles the autoload naming convention (file name must match function name) and updates references.

Linecount: Count Lines

```
zpwr linecount                # count lines in files
```

Enhanced line counting with formatting and totals. Shows per-file counts and a grand total. More informative than raw `wc -l`.

Pre & Post: Text Injection

```
zpwr pre                      # prepend text to input  
zpwr post                     # append text to input
```

Pipe filters that add text before or after each line. Useful in pipelines for formatting:

```
ls | zpwr pre ' - '           # bullet-point file list  
cat urls.txt | zpwr post '/api/v1' # append to each URL
```

Urlsafe: Url Encoding

```
zpwr urlsafe                  # URL-encode a string
```

Converts special characters to percent-encoded form. Spaces become `%20`, ampersands become `%26`, etc. Essential when constructing URLs from user input.

The Text Pipeline

zpwr text verbs compose naturally in pipelines:

```
cat data.txt | zpwr pre 'ROW: ' | zpwr post ' ;'
```

Result: ROW: line1 ; ROW: line2 ;

Rename all .txt to .md:

```
zpwr rename # interactive rename
```

Replace 'oldFunc' with 'newFunc' across the codebase:

```
zpwr replacer # interactive replace
```

Display & Banners

// because aesthetics matter. even in a terminal. //

zpwr ships with a fleet of display verbs that produce ASCII art, colorized output, and terminal animations. Some are informational. Some are just cool to look at.

The Banner Family

```
zpwr about # the welcome banner
zpwr banner # same as about
zpwr bannercounts # banner + environment stats
```

The core banner shows the zpwr ASCII logo with version, author, and system info. bannercounts adds the environment census (alias count, function count, etc.).

```
zpwr bannerlolcat # banner piped through lolcat
```

Rainbow gradient banner. Requires: `gem install lolcat` For when monochrome is not enough and you need to assert terminal dominance with a rainbow.

```
zpwr bannerpony # banner with ponysay
```

Displays the banner inside an ASCII pony speech bubble. Requires: `pip install ponysay` Peak terminal culture.

```
zpwr bannernopony # banner without the pony
```

For the pony-averse. All the info, none of the horse.

Pretty Printing

```
zpwr prettyprint # formatted text output
zpwr altprettyprint # alternate format
zpwr printmap # print associative array
```

Prettyprint is used internally by many zpwr verbs to format output with consistent color and spacing. printmap formats associative arrays as aligned key-value tables. Useful for debugging hash tables.

Color Testing

```
zpwr colortest # test basic terminal colors
zpwr colortest256 # full 256-color palette
```

Run these after changing terminals, fonts, or color schemes. colortest shows the 16 ANSI colors. colortest256 shows the full 256-color grid. If colors look wrong, your TERM or terminal emulator config needs adjustment.

Animation

```
zpwr animate # terminal animation
```

Plays an ASCII animation in the terminal. Because sometimes you need to entertain yourself while waiting for a build.

The Display Arsenal At A Glance

Impress a colleague: `zpwr bannerlolcat` Debug your terminal: `zpwr colortest256` Count your weapons: `zpwr bannercounts` Maximum absurdity: `zpwr bannerpony` Format a hash table: `zpwr printmap` Kill time aesthetically: `zpwr animate`.

File & Text Utilities

// 31 verbs for file wrangling //

Cat, list, grep, search, rename, and transform files. The everyday toolkit for text manipulation.

View & List

```
zpwr cat           # zpwr cat args
zpwr c             # zpwr cat args
zpwr ls            # list the files with no args
zpwr list          # list the files with no args
zpwr clearlist     # clear and list the files
zpwr clearls       # clear and list the files
zpwr info          # get info on command type with args
```

Search

```
zpwr grep          # grep through pwd with ag into fzf
zpwr search        # recursive grep search with context
zpwr filesearch    # cat a file in a sub dir via fzf
zpwr filesearchedit # edit a file in a sub dir via fzf
zpwr wordsearch    # cat a file by word via fzf
zpwr wordsearchedit # edit a file by word via fzf
zpwr findsearch    # cat find drive for file via fzf
zpwr findsearchedit # edit find drive for file via fzf
zpwr locatesearch  # accept locate drive for file
zpwr locatesearchedit # edit locate drive for file
zpwr linecount     # get line count of search term
zpwr cfasd         # cat the fasd frequency ranked file
```

Transform & Manage

```
zpwr replacer      # find and replace text in files
zpwr rename        # rename files
zpwr man           # fzf through man pages
zpwr open          # open with system
zpwr opencommand   # get the command to open with system
```

Convert & Upload

```
zplr scripttopdf      # convert script to PDF
zplr creat/gif        # create GIF from file with ffmpeg
zplr upload           # upload with curl
zplr urlsafe          # base64 encode
zplr execglob         # exec on globbed files
zplr execglobparallel # parallel exec on globbed files
```

Miscellaneous Arsenal (1/2)

// the verbs that defy categorization //

Terminal & Color

```
zplr animate          # run terminal animation
zplr alacrity         # edit alacrity config
zplr color2           # turn on stderr filter
zplr return2          # turn off stderr filter
zplr colorsdiff       # colorized side diff
zplr colortest        # test colors
zplr colortest256     # test 256 colors
zplr figletfonts      # show all figlet fonts
zplr pygmentcolors    # show all pygment colors
```

Backup & History

```
zplr backup           # backup files
zplr backuphistory    # backup $HISTFILE
zplr hist             # exec history command via fzf
zplr histedit         # edit history command via fzf
zplr histfile         # edit history file
```

File & Dir Creation

```
zplr mkdir            # make a dir tree
zplr makefile         # make a dir tree with file at end
zplr scriptnew        # create new script without editor
zplr changename       # mv dir into namespace and sed sub
zplr changenamezplr   # mv into zplr namespace and sed sub
```

Docker & Go

```
zplr dfimage          # cat Dockerfile from IMAGE_ID
zplr dockerwipe       # wipe all docker images
zplr goclean          # clean Go package artifacts
```

Exercism

```
zpwr exercism          # go to Exercism home page
zpwr exercismedit      # edit file in $HOME/Exercism
zpwr exercismdownload  # download all for track
```

Miscellaneous Arsenal (2/2)

// looping, testing, system, and services //

Looping & Background

```
zpwr background      # run arg in background
zpwr for              # run first arg times for command
zpwr for10            # run 10 times for command
zpwr fordir           # run first arg in following dirs
zpwr fordirupdate     # run git updaters in following dirs
zpwr whiletrue        # run command forever
zpwr whilesleep       # run command and sleep N seconds
```

Testing

```
zpwr test             # run all zpwr tests
zpwr tests            # run all zpwr tests
zpwr testall          # run all env tests
zpwr testsall         # run all env tests
```

System & Misc

```
zpwr curl             # custom curl with cleaned output
zpwr deduppaths        # deduplicate PATH fpath manpath
zpwr edit             # exec $EDITOR
zpwr editor           # exec $EDITOR
zpwr install          # run configure, make, make install
zpwr loadjenv          # lazy load jenv
zpwr prettyprint       # pretty print with color
zpwr altprettyprint    # pretty with alternating color
zpwr reset            # reset repo to latest main
zpwr reveal           # show remote repo in browser
zpwr revealrecurse     # recursively reveal hidden dirs
zpwr rmconfiglinks     # remove sym links to $HOME
zpwr startauto         # start autocomplete
zpwr stopauto         # stop autocomplete
zpwr timer            # timer one or more commands
zpwr uninstall        # uninstall all zpwr configs
zpwr post             # postfix all output
zpwr pre              # prefix all output
zpwr zpwrCloneToForked # clone repo to $ZPWR_FORKED_DIR
```

Systemd Services

```
zpwir serviceup          # start and enable systemd service
zpwir servicedown        # stop and disable systemd service
zpwir restart             # restart zpwir systemd service
```

Chapter 13 – emacs Dimension

Emacs Integration Overview

Entering The emacs Dimension

Where M-x is a way of life and pinky fingers go to die.

You thought there were only vim verbs? Think again, operative. ZPWR mirrors every vim operation with an emacs equivalent. Same power, different religion.

The 28 emacs Verbs:

FILE OPS emacsall, emacsalledit, emacsautoload RECENT emacsrecent, emacsrecentcd, emacsrecentsudo SEARCH emacsfilesearch, emacsfilesearchedit emacsfindsearch, emacsfindsearchedit emacslocatesearch, emacslocatesearchedit emacswordsearch, emacswordsearchedit TAGS emacsctags, emacshtags, emacshtagsedit CONFIG emacsconfig, emacsemacsconfig, emacsokens SERVER emacsallserver SCRIPTS emacsscripts, emacsscriptedit META emacsplugincount, emacspluginlist, emacszipwr.

THE MIRROR PRINCIPLE:

Every vim verb has an emacs twin. The architecture is symmetrical by design. You can swap editors without losing any ZPWR functionality.

vim verb emacs twin zipwr vimall → zipwr emacsall zipwr vimrecent → zipwr emacsrecent zipwr vimscripts → zipwr emacsscripts.

Philosophy:

ZPWR does not care about your editor war allegiance. It arms both sides equally. The real enemy is notepad.

// the emacs dimension runs parallel to vim-space

// choose your weapon, the framework adapts

// \$ZPWR_EDITOR controls which universe you inhabit

Emacs File Operations

emacs File Ops: Opening Things Since 1976

emacs: an operating system lacking only a decent editor.

zipwr Emacsall

Opens all ZPWR framework files in emacs via fzf. Every autoload, script, config – the whole kingdom.

```
zipwr emacsall          # browse all files
zipwr emacsalledit      # same but editable
```

zpwr Emacsrecent

Opens recently edited files. Emacs remembers where you have been, like a browser history for code.

```
zpwr emacsrecent          # fzf recent files
zpwr emacsrecentcd        # cd to recent dir
zpwr emacsrecentsudo      # recent with sudo
zpwr emacsrecentsudocd    # sudo + cd combo
```

zpwr Emacsscripts

Browse and open ZPWR scripts directory. Where the shell scripts live and breathe.

```
zpwr emacsscripts        # browse scripts
zpwr emacsscriptedit      # edit a script
```

zpwr Emacsautoload

Open autoloaded zsh functions in emacs. The beating heart of ZPWR's function library.

```
zpwr emacsautoload       # browse autoloads
```

// protip: emacsrecent is your daily driver

// it learns your habits and surfaces what matters

// sudo variants for when /etc needs surgery

Emacs Search & Tags

Search & Tags: Find Anything, Anywhere

grep is for amateurs, we have fzf-powered search beams.

File Search (by Filename):

```
zpwr emacsfilesearch      # fzf filename search
zpwr emacsfilesearchedit  # search + edit
```

Searches file NAMES across the ZPWR tree. Fast, fuzzy, and feeds results into emacs.

Word Search (by Content):

```
zpwr emacswordsearch      # search file content
zpwr emacswordsearchedit  # content search + edit
```

Searches INSIDE files for patterns. Like ag/rg but with fzf preview and direct-to-emacs piping.

Find & Locate Search:

```
zpwr emacsfindsearch      # find-based search
zpwr emacsfindsearchedit  # find + edit
zpwr emacslocatesearch    # locate db search
zpwr emacslocatesearchedit # locate + edit
```

Tags – Code Navigation:

```
zpwr emacsctags          # ctags generation
zpwr emacshtags          # GNU Global tags
zpwr emacshtagsedit      # gtags + jump to def
```

Tags let emacs jump to function definitions instantly. ctags for basic tagging, gtags for cross-reference.

// the search hierarchy:

// wordsearch = grep inside files (content)

// filesearch = find by filename (path)

// locatesearch = system locate db (everywhere)

// findsearch = find command (directory tree)

// tags = jump to definitions (symbols)

Emacs Config & Server

Config & Server: The emacs Mothership

Because starting emacs fresh every time is a war crime.

zpwr Emacsconfig

Edit ZPWR's emacs configuration files. The bridge between the shell framework and emacs-land.

```
zpwr emacsconfig          # edit zpwr emacs cfg
```

zpwr Emacsemacsconfig

Edit your personal emacs init files (init.el, etc). Deeper than emacsconfig – this is YOUR emacs setup.

```
zpwr emacsemacsconfig     # edit ~/.emacs.d
```

zpwr Emacsallserver

Opens files using emacsclient, connecting to a running emacs daemon. Instant file opens, no startup penalty.

```
zpwr emacsallserver       # open via daemon
```

HOW THE SERVER WORKFLOW WORKS: 1. Start emacs daemon: emacs –daemon 2. Use emacsallserver to open files via emacsclient 3. Files open instantly in the running emacs instance 4. No more 3-second startup tax per file.

zpwr Emacstokens

Edit your tokens/secrets file in emacs. API keys, env vars, the classified stuff.

```
zpwr emacstokens          # edit $ZPWR_LOCAL/.tokens.sh
```

zpwr Emacszpwr

Open the entire ZPWR directory tree in emacs.

```
zpwr emacszpwr          # the whole framework
```

// emacsclient + daemon = the cheat code

// startup once, open files forever

// this is how emacs users actually survive

Emacs Integration

// 29 verbs for the church of emacs //

Every file operation in ZPWR has an emacs variant. Open, edit, search, and navigate — all wired to emacsclient.

Open & Edit

```
zpwr emacsall           # emacs all zpwr files for :argdo
zpwr emacsallserver     # emacs all zpwr files via server
zpwr emacsalledit       # emacs edit 1 or more configs
zpwr emacsautoload      # emacs all autoloads :argdo
zpwr emacsscripts       # emacs all zpwr scripts for :argdo
zpwr emacsscriptedit    # emacs edit 1 or more scripts
zpwr emacszpwr          # emacs zpwr dir
```

Config & Tokens

```
zpwr emacsconfig        # emacs all zpwr configs
zpwr emacsconfig        # emacs edit emacs zpwr configs
zpwr emacsconfig        # emacs edit emacs zpwr configs
zpwr emacsconfig        # emacs edit emacs zpwr configs
zpwr emacsconfig        # emacs edit emacs zpwr configs
zpwr emacsconfig        # emacs edit emacs zpwr configs
```

Navigation

```
zpwr emacsconfig        # emacs edit emacs zpwr configs
zpwr emacsconfig        # emacs edit emacs zpwr configs
zpwr emacsconfig        # emacs edit emacs zpwr configs
zpwr emacsconfig        # emacs edit emacs zpwr configs
zpwr emacsconfig        # emacs edit emacs zpwr configs
zpwr emacsconfig        # emacs edit emacs zpwr configs
```

Search

```
zpwr emacsconfig        # emacs edit emacs zpwr configs
zpwr emacsconfig        # emacs edit emacs zpwr configs
zpwr emacsconfig        # emacs edit emacs zpwr configs
zpwr emacsconfig        # emacs edit emacs zpwr configs
zpwr emacsconfig        # emacs edit emacs zpwr configs
zpwr emacsconfig        # emacs edit emacs zpwr configs
```

Tags & Plugins

```
zpwr emacsctags          # emacs zpwr ctags tags
zpwr emacsgtags          # emacs zpwr GNU global tags
zpwr emacsgtagsedit      # emacs edit zpwr GNU global tags
zpwr emacsplugincount    # total number of emacs plugins
zpwr emacspluginlist     # total list of emacs plugins
```

Chapter 14 – tmux Warfare

Tmux Session Management

tmux Warfare: Terminal Multiplexer Combat

One terminal to rule them all, split them, and in panes bind them.

zpwr Attach

Attach to an existing tmux session. If no session exists, one will be summoned.

```
zpwr attach          # rejoin the matrix
```

zpwr Detach

Detach from current tmux session gracefully. Your processes keep running in the background.

```
zpwr detach          # leave but don't kill
```

zpwr Killmux

Kill the tmux server. Nuclear option. Everything dies. WARNING: all sessions, windows, and panes – gone.

```
zpwr killmux          # scorched earth
```

zpwr Start

Start a new tmux session with ZPWR's custom layout. Preconfigured panes, windows, and keybindings.

```
zpwr start            # bootstrap tmux
```

zpwr Starttabs

Start tmux with multiple pre-configured tabs. Each tab gets its own purpose – dev, logs, git, etc.

```
zpwr starttabs        # multi-tab setup
```

// the tmux lifecycle:

// start -> attach -> detach -> attach -> killmux

// sessions persist through SSH disconnects

// your terminal state is immortal

Key Duplication – Multi-Pane Workflow

Key Duplication: Type Once, Execute Everywhere

The closest thing to being in two places at once.

zpwr Startsend

Send keystrokes to ALL panes in the current window. Whatever you type goes to every pane simultaneously.

```
zpwr startsend          # enable key broadcast
```

USE CASE: You have 4 panes SSHed into 4 servers. You need to run the same command on all of them. startsend + type once = executed on all 4.

zpwr Startsendfull

Like startsend, but broadcasts across ALL windows and ALL panes in the entire tmux session.

```
zpwr startsendfull      # global broadcast
```

DANGER: every pane in every window receives input. Make sure you know what you are doing.

zpwr Stopsend

Turn off key broadcasting. Back to single-pane input.

```
zpwr stopsend          # disable broadcast
```

The Multi-pane Workflow:

1. \$ zpwr start # launch tmux
2. Split into 4 panes (Ctrl-b %)
3. SSH into different servers in each
4. \$ zpwr startsend # enable broadcast
5. Type: sudo apt update && sudo apt upgrade -y
6. All 4 servers update simultaneously
7. \$ zpwr stopsend # back to normal

// sysadmins call this poor mans ansible

// but honestly it is faster for quick ops

Clipboard & Buffer Operations

Clipboard Ops: Copy-paste On Steroids

Because Ctrl-C Ctrl-V is so last millennium.

zpwr Pastebuffer

Paste from the tmux paste buffer into the terminal. Tmux has its own clipboard, separate from the system.

```
zpwr pastebuffer        # paste tmux buffer
```

zpw'r Pastestring

Paste a specific string into the active pane. Programmatic pasting – useful in scripts.

```
zpw'r pastestring 'echo hello' # paste literal text
```

zpw'r Pastecommand

Paste and execute a command in the active pane. Like pastestring but hits enter for you.

```
zpw'r pastecommand 'ls -la' # paste + execute
```

zpw'r Google

Open a Google search in your default browser. Because sometimes you need to leave the terminal.

```
zpw'r google 'zsh completion' # search the web
```

zpw'r Openurl

Open any URL in the default browser.

```
zpw'r openurl https://github.com # open URL
```

// the clipboard pipeline:

// terminal output → tmux buffer → pastebuffer

// system clipboard → pastestring → pane

// brain → google → browser → back to terminal

Autocomplete Integration

Autocomplete: The Tab Key's Final Form

Zsh-autocomplete + tmux = sentient tab completion.

zpw'r Startauto

Enable the ZPWR autocomplete integration. Completions appear as you type, no Tab needed.

```
zpw'r startauto # enable live complete
```

zpw'r Stopauto

Disable autocomplete. Sometimes you want silence.

```
zpw'r stopauto # disable live complete
```

How It Works With Tmux:

The autocomplete system hooks into zsh's completion engine and renders suggestions in real-time.

FEATURES: * Live suggestions as you type * History-based predictions * Path completion with preview * Command argument completion * Works across all tmux panes independently.

tmux + Autocomplete Tips:

* Each tmux pane runs its own zsh instance * Autocomplete state is per-pane * startauto/stopauto affects current pane only * If completions feel slow, check `$ZPWR_COMPS_CACHE`

```
zpwr stopauto          # when it gets noisy
zpwr startauto         # when you miss it
```

// autocomplete is like a copilot for your shell

// it watches, it learns, it suggests

// toggle it off when you need to think in silence

Process Monitoring

Process Monitoring: Watching The Watchers

Every PID tells a story, most of them tragic.

zpwr Pstree monitor

Displays a live process tree. Watch your processes branch, fork, and occasionally die unexpectedly.

```
zpwr pstreemonitor     # live process tree
```

Uses pstree under the hood with continuous refresh. Like htop's tree view but from the ZPWR command line.

zpwr Tty

Show info about the current terminal/tty.

```
zpwr tty              # current tty info
```

tmux + Monitoring Workflow:

The power move: dedicate a tmux pane to monitoring.

LAYOUT EXAMPLE: +-----+-----+ ||| your work | pstreemonitor ||| +-----+
+-----+ | zpwr taillog | +-----+

Process Hunting:

ZPWR integrates fzf with ps and lsof for killing.

Ctrl-Y Ctrl-K # fzf kill by ps Ctrl-Y Ctrl-L # fzf kill by lsof.

// pstreemonitor in a side pane = instant situational awareness

// you will see zombie processes before they see you

Clipboard, Send & Tmux

// 13 verbs for pane orchestration //

Clipboard access, key duplication across panes, URL handling, and tmux session management.

Clipboard

```
zpwri copycommand      # get the command to copy with system
zpwri pastecommand     # get the command to paste with system
zpwri pastebuffer      # paste clipboard to $BUFFER
zpwri pastestring      # paste clipboard to stdout
```

Key Duplication

```
zpwri startsend        # dup some keys to pane
zpwri startsendfull    # dup all keys to pane
zpwri stopsend         # stop dup keys to pane
```

Url & Browser

```
zpwri google           # google clipboard contents in tmux
zpwri openurl          # open URL from clipboard in tmux
```

Session Management

```
zpwri attach           # attach to tmux session
zpwri detach           # detach from all tmux sessions
zpwri killmux          # kill tmux server
zpwri killremote       # kill tmux server and ssh
```

Chapter 15 – Network & Containers

Network Recon

Network Recon: Scanning The Wire

Packets don't lie, but DNS sometimes does.

zpwr Digs

Enhanced DNS lookup. Wraps dig with cleaner output. When you need to know where a domain really points.

```
zpwr digs github.com      # DNS lookup
zpwr digs example.com     # check any domain
```

Shows A records, CNAME chains, TTLs – the works. Faster than remembering dig +short +noall +answer.

zpwr Pi / zpwr Ping

Ping a host. Simple, reliable, essential. 'pi' is the short alias because typing matters.

```
zpwr pi google.com        # quick ping
zpwr ping 8.8.8.8         # verbose ping
```

zpwr Pir

Ping with extended options. More detailed network diagnostics for when simple ping is not enough.

```
zpwr pir 192.168.1.1      # extended ping
```

Recon Workflow:

1. \$ zpwr digs suspect-domain.com # where does it resolve?
2. \$ zpwr pi <ip-from-dig> # is it alive?
3. \$ zpwr pir <ip> # deeper probe

// three verbs, complete network recon

// digs for DNS, pi for heartbeat, pir for details

// when in doubt, ping first – dead hosts tell no tales

Tor Integration

Tor Integration: Anonymous Mode Engaged

The onion router: because privacy is not a crime.

zpwr Torip

Check your current Tor exit node IP address. Confirms you're routing through the onion network.

```
zpwr torip # show tor exit IP
```

If Tor is running, this shows the exit node's IP. If not, it'll tell you Tor isn't connected.

zpwr Toriprenew

Request a new Tor circuit. Get a fresh exit node and a new apparent IP address.

```
zpwr toriprenew # new identity
```

BEFORE YOU START:

Tor must be installed and running as a service.

MacOS: brew install tor && brew services start tor Linux: sudo apt install tor && sudo systemctl start tor.

The Anonymous Workflow:

1. Start tor service
2. \$ zpwr torip # confirm you're connected
3. Do your thing
4. \$ zpwr toriprenew # rotate identity
5. \$ zpwr torip # verify new IP

DISCLAIMER: Tor provides anonymity, not invincibility. DNS leaks, browser fingerprinting, and OPSEC failures can still expose you. Use responsibly.

// "I am become anonymous, destroyer of logs"

// – J. Robert Oppenheimer, probably not

Docker Management

Docker Management: Container Warfare

It works on my machine → we ship the machine.

zpwr Dockerwipe

The nuclear option for Docker. Removes EVERYTHING: containers, images, volumes, networks – all of it.

```
zpwr dockerwipe # purge all docker
```

WARNING: This is not gentle. It will: - Stop all running containers - Remove all containers - Remove all images - Remove all volumes - Prune everything.

WHEN TO USE: * Disk space emergency (docker images love eating disk) * Fresh start after a botched experiment * When 'docker system df' shows 50GB of shame.

zpwr Dfimage

Reverse-engineer a Docker image to show its Dockerfile. See how an image was built without the source.

```
zpwr dfimage nginx:latest # reverse Dockerfile
zpwr dfimage myapp:v2     # inspect any image
```

Useful for auditing third-party images. Trust but verify what's in that container.

Docker Triage:

1. \$ docker system df # how bad is it?
2. \$ zpwr dfimage suspect:latest # what's inside?
3. \$ zpwr dockertwipe # burn it all down
4. \$ docker system df # ahh, fresh disk

// dockertwipe: for when docker system prune isn't angry enough

// dfimage: for when you don't trust the README

Clone & GitHub Workflow

Clone & Github: The Full Git Workflow

git clone is just the beginning of the relationship.

zpwr Clone

Clone a git repository with ZPWR's enhanced setup. Handles auth, directory placement, and post-clone hooks.

```
zpwr clone user/repo      # clone from GitHub
zpwr clone https://...    # clone any URL
```

zpwr Reveal

Open the current git repo's GitHub page in browser. Instant context switch from terminal to web.

```
zpwr reveal              # open repo in browser
```

zpwr Revealrecurse

Open GitHub pages for the repo AND its submodules. When you need the full picture of a multi-repo project.

```
zpwr revealrecurse      # open all repos
```

The Github Workflow:

1. \$ zpwr clone user/repo # get the code
2. \$ cd repo && hack hack hack
3. \$ zpwr reveal # check CI/issues
4. \$ git push # ship it

Related Tools:

```
zpwr killremote          # kill remote sessions
```

Killremote terminates remote SSH/tmux sessions that have gone stale. Cleanup for the disciplined operator.

// reveal is the bridge between terminal and browser

// faster than typing github.com/user/repo

// your fingers will thank you

Docker & Container Aliases

// 148 aliases for the containerized world //

The zsh-docker-aliases plugin provides 148 aliases for Docker and Docker Compose operations.

Docker Shortcuts

```
dps          # docker ps
dpsa         # docker ps -a
di           # docker images
drim         # docker rm
drmi         # docker rmi
dex          # docker exec -it
dl           # docker logs -f
```

Docker Compose

```
dcu          # docker compose up -d
dcd          # docker compose down
dcl          # docker compose logs -f
dcr          # docker compose restart
```

zpwrc Integration

```
zpwrc dockerwipe      # nuke all images/containers
zpwrc dfimage <ID>    # extract Dockerfile from image
```

Plugin: MenkeTechnologies/zsh-docker-aliases.

Process & Network

// 15 verbs for procs, ports, and packets //

Kill processes via fzf, monitor process trees, toggle Tor, ping LANs, and run network diagnostics.

Process Management

```
zpwrc ps          # ps -ef | grep arg
zpwrc kill         # kill from ps output via fzf
zpwrc killedit     # edit kill from ps output via fzf
zpwrc lsof         # kill from lsof output via fzf
zpwrc lsofedit     # edit kill from lsof output via fzf
zpwrc pstreemonitor # monitor process tree with watch
```

Network Diagnostics

```
zpwrc digs        # run series of networking cmds on arg
zpwrc pi           # ping all LAN devices
zpwrc ping         # ping all LAN devices
zpwrc pir          # run command on all devices
```

Tor & Ip

```
zpwir torip          # get IP address via Tor and whois
zpwir toriprenew     # renew Tor identity
zpwir to             # toggle external ip
zpwir toggle         # toggle external ip
```

Polling

```
zpwir poll           # poll git remote and run command
```

Chapter 16 – The Logging System

Log Levels

Log Levels: Signal Vs Noise

if a tree falls in the forest and nobody tails the log...

ZPWR has a full structured logging system with four levels. Each level has a file variant and a console variant.

Level 1: Trace

```
zpwr logtrace 'entering func' # most verbose
```

The firehose. Every function entry, variable assignment, and internal state change. Use for deep debugging only.

Level 2: Debug

```
zpwr logdebug 'cache miss' # developer detail
```

Detailed info for development. Cache behavior, branch decisions, intermediate values.

Level 3: Info

```
zpwr loginfo 'update done' # normal operations
```

Standard operational messages. “Started”, “Completed”, “Loaded 47 plugins”. The daily heartbeat.

Level 4: Error

```
zpwr logerror 'file not found' # something broke
```

Things that should not have happened but did. Missing files, failed commands, broken assumptions.

Severity Pyramid:

Console vs File Logging

Console Vs File: Two Destinations

To stderr or to disk, that is the question.

Every log verb comes in two flavors:

File Variants (write To \$ZPWR_LOGFILE):

```
zpwr logtrace 'msg'      # --> logfile
zpwr logdebug 'msg'      # --> logfile
zpwr loginfo 'msg'       # --> logfile
zpwr logerror 'msg'      # --> logfile
```

These write silently to the log file. No terminal output. Perfect for background operations and scripts.

Console Variants (write To Stderr And Logfile):

```
zpwr logtraceconsole 'msg' # --> stderr + file
zpwr logdebugconsole 'msg' # --> stderr + file
zpwr loginfoconsole 'msg'  # --> stderr + file
zpwr logerrorconsole 'msg' # --> stderr + file
```

These print to your terminal AND write to the log. For interactive debugging when you need to see it live.

The Logfile:

```
$ZPWR_LOGFILE = $ZPWR_LOCAL/zpwr.log
```

```
cat $ZPWR_LOGFILE | tail -20 # recent entries
wc -l $ZPWR_LOGFILE          # how big is it?
```

Choosing Your Variant:

SCENARIO USE Background script running loginfo Debugging interactively logdebugconsole Tracking a rare bug logtraceconsole Production error handling logerror.

// file = silent, persistent, searchable

// console = loud, immediate, ephemeral

// use both strategically

Reading Logs

Reading Logs: The Art Of Log Diving

Somewhere in that wall of text is the answer you seek.

zpwr Taillog

Live tail of the ZPWR log file with ccze colorization. Watch events stream by in glorious technicolor.

```
zpwr taillog # live colorized tail
```

ccze automatically highlights timestamps, levels, paths, and errors. Makes raw logs actually readable.

What To Look For:

ERROR lines = something broke, investigate immediately WARN lines = potential issue, worth noting INFO lines = normal operations, sanity check DEBUG lines = details for troubleshooting.

```
TRACE lines = deep internals, very verbose
```

Filtering Techniques:

```
grep ERROR $ZPWR_LOGFILE      # errors only
grep -c ERROR $ZPWR_LOGFILE   # count errors
tail -100 $ZPWR_LOGFILE       # last 100 lines
```

tmux Log Monitoring Setup:

Dedicate a tmux pane to zpwr taillog:

1. Split pane: Ctrl-b %
2. In new pane: zpwr taillog
3. Work in other pane, watch logs stream
4. Errors glow red thanks to ccze

Log Maintenance:

Logs grow forever if you let them. ZPWR handles rotation, but you can manually truncate:

```
: > $ZPWR_LOGFILE          # truncate to zero
```

// taillog + ccze = the cyberpunk log experience

// errors in red, info in green, timestamps in cyan

Debug Mode

Debug Mode: When Things Go Sideways

Enabling verbose output is how you stop guessing.

Zpwr_debug

Set this env var to enable debug-level logging. More detail in the log, more signal for your hunt.

```
export ZPWR_DEBUG=true      # enable debug
zpwr reload                  # reload with debug
zpwr taillog                  # watch debug output
```

Zpwr_trace

Maximum verbosity. Every function entry and exit, every variable, every decision point.

```
export ZPWR_TRACE=true      # enable trace
zpwr reload                  # reload with trace
```

WARNING: Trace mode generates MASSIVE log output. Your logfile will grow fast. Use sparingly.

Debugging Workflow:

1. Reproduce the problem once to confirm it
2. \$ export ZPWR_DEBUG=true
3. \$ zpwr reload
4. Reproduce the problem again
5. \$ zpwr taillog # find the smoking gun
6. Still lost? Escalate:
7. \$ export ZPWR_TRACE=true
8. \$ zpwr reload && reproduce

Disabling Debug:

```
unset ZPWR_DEBUG ZPWR_TRACE # back to normal
zpw reload                  # reload clean
```

// debug mode: "trust but verify" in action

// trace mode: "verify everything, trust nothing"

// always disable after debugging or your log eats disk

Logging System

// 12 verbs for structured observability //

ZPWR has a four-level logging system: trace, debug, info, error. Each level writes to file or console.

Log To File

```
zpw logtrace          # log trace to $ZPWR_LOGFILE
zpw logdebug          # log debug to $ZPWR_LOGFILE
zpw loginfo           # log info to $ZPWR_LOGFILE
zpw logerror          # log error to $ZPWR_LOGFILE
```

Log To Console

```
zpw logtraceconsole   # log trace to console
zpw logdebugconsole   # log debug to console
zpw loginfoconsole    # log info to console
zpw logerrorconsole   # log error to console
```

Log Management

```
zpw taillog           # colored tail of $ZPWR_LOGFILE
zpw logs              # colored tail of $ZPWR_LOGFILE
zpw cleanlog          # clear $ZPWR_LOGFILE
zpw logincount        # count of logins by user
```

Log levels from most verbose to least: TRACE > DEBUG > INFO > ERROR.

Chapter 17 – Introspection

Counting Everything

Counting Everything: The Census Bureau

If you can't measure it, you can't brag about it.

ZPWR tracks the size of every component. These verbs tell you exactly how big your installation is.

zpwr Autoloadcount

Count of autoloaded zsh functions in the framework.

```
zpwr autoloadcount          # how many functions?
```

zpwr Scriptcount

Count of shell scripts in `$ZPWR/scripts`.

```
zpwr scriptcount           # how many scripts?
```

zpwr Zshplugincount

Count of installed zsh plugins (zinit, oh-my-zsh, etc).

```
zpwr zshplugincount        # zsh plugins loaded
```

zpwr Vimplugincount

Count of installed vim/neovim plugins.

```
zpwr vimplugincount        # vim plugins loaded
```

zpwr Emacsplugincount

Count of installed emacs packages.

```
zpwr emacsplugincount      # emacs pkgs loaded
```

The Full Census:

```
zpwr autoloadcount && zpwr scriptcount && \
```

zpwr zshplugincount && zpwr vimplugincount && \ zpwr emacsplugincount.

Run all five to get the full picture. ZPWR typically ships with 300+ autoloads, 50+ scripts, and dozens of plugins across all three editors.

```
// these counts tell you the scope of ZPWR
// hundreds of functions working in concert
// like a small city running on your laptop
```

Listing Everything

Listing Everything: The Inventory Manifest

Counting is nice, but names are power.

Counts tell you how many. Lists tell you WHAT. Every count verb has a list counterpart.

zpwr Autoloadlist

List every autoloaded function by name.

```
zpwr autoloadlist          # all function names
zpwr autoloadlist | grep fzf # find fzf funcs
```

zpwr Scriptlist

List every script in the scripts directory.

```
zpwr scriptlist           # all scripts
```

zpwr Zshpluginlist

List installed zsh plugins with their sources.

```
zpwr zshpluginlist        # all zsh plugins
```

zpwr Vimpluginlist

List installed vim/neovim plugins.

```
zpwr vimpluginlist        # all vim plugins
```

zpwr Emacspluginlist

List installed emacs packages.

```
zpwr emacspluginlist      # all emacs packages
```

Power Combos:

```
zpwr autoloadlist | wc -l  # quick count
zpwr autoloadlist | fzf    # fuzzy browse
zpwr scriptlist | sort     # alphabetical
```

// lists are grep-able, fzf-able, pipe-able
// the raw material for your own exploration
// pipe into fzf for interactive discovery

History Archaeology

History Archaeology: Digging Up The Past

Your terminal remembers everything, even the mistakes.

zpw Hist

Browse command history with fzf. Search, preview, and re-execute past commands interactively.

```
zpw hist # fzf history browser
```

zpw Histedit

Edit the history file directly. Surgically remove embarrassing commands or fix typos in saved history.

```
zpw histedit # edit history file
```

Use with care. History surgery is delicate work.

zpw Histfile

Show the path to the current history file. Useful when you're not sure which histfile is active.

```
zpw histfile # show histfile path
```

zpw Catvminfo

Display vim's recent file history from viminfo. What files has vim touched recently?

```
zpw catvminfo # vim file history
```

zpw Catrecentfviminfo / Catnviminfo recentf

Cross-reference vim/nvim recent files with the recentf list. Where vim and shell history intersect.

```
zpw catrecentfviminfo # vim+recentf cross  
zpw catnviminfo recentf # nvim+recentf cross
```

// your history is a goldmine of workflow patterns
// hist + fzf = instant command recall
// histedit = revisionist history (use responsibly)

Verb Discovery

Verb Discovery: Finding What's Possible

You can't use what you don't know exists.

zpw Subcommands

List all zpw subcommands (verbs). The master index of everything zpw can do.

```
zpw subcommands          # all subcommands
```

zpw Subcommandscount

How many subcommands exist? The number keeps growing.

```
zpw subcommandscount     # total count
```

zpw Verbs (alias: Subcommandsfzf)

Browse subcommands interactively with fzf. The best way to explore when you're not sure what to try.

```
zpw verbs                # fzf subcommands
```

zpw Verbslist / Verbsfzf / Verbscount

Alternative verb-centric views of available commands.

```
zpw verbslist            # list all verbs
zpw verbs                # fzf browse verbs
zpw verbscount           # count verbs
```

zpw Wizard / Manual / Tutorial / Docs

You're reading it right now. The interactive encyclopedia with vim-style navigation. Very meta. All four names work.

```
zpw wizard               # start the wizard
zpw wizard --toc         # table of contents
zpw wizard --search docker # search pages
zpw wizard 42            # jump to page 42
```

// verbsfzf is the fastest way to discover (alias: subcommandsfzf)

// type a few letters, fzf narrows it down

// when in doubt, fzf it out

Shell State Inspection

Shell State: Know Thy zsh

Introspection: when the shell looks in the mirror.

zpwr Exists

Check if a ZPWR component exists (functions, files, etc).

```
zpwr exists zpwrReload      # does this exist?
```

zpwr Existscommand

Check if a command exists in PATH. Cleaner than 'which' or 'command -v' in scripts.

```
zpwr existscommand git      # is git installed?
zpwr existscommand rg       # is ripgrep here?
```

zpwr Reload

Reload the entire ZPWR framework without restarting. Re-resources configs, rebuilds caches, refreshes state.

```
zpwr reload                  # hot reload everything
```

zsh Inspection Tools:

These are built into zsh, but ZPWR makes them accessible:

```
setopt                       # list active options
zmodload                     # list loaded modules
zstyle -L                    # list all zstyles
```

zpwr Copycommand

Copy a command's path or definition to clipboard.

```
zpwr copycommand ls         # copy ls path
```

zpwr Opencommand

Open a command's source file in your editor. Works for functions, scripts, and binaries.

```
zpwr opencommand zpwrReload # view the source
```

// existscommand before you call, reload after you change

// opencommand when you need to understand the internals

Command Resolver

// what IS that command, really? //

zpwr resolve traces a command through its full resolution chain. Unlike 'which' or 'type', it follows the entire path from alias to function to builtin to binary.

The Verb

```
zpwr resolve ll          # where does ll go?
zpwr resolve ls cd git   # trace multiple commands
zpwr resolve -a grep     # show all type -a matches
zpwr which vim           # alias for resolve
```

What It Shows

Aliases expansion, then resolves first word.

```
Functions      source file path, line count, verb mapping
```

Builtins identified as builtin or reserved word Binaries full path, symlink chain, file type Global aliases detected and shown Suffix aliases detected and shown.

Why Not Just 'which'?

'Which' shows one answer. 'type -a' shows all candidates. Neither follows the chain. If 'll' is an alias for 'eza' and 'eza' is a symlink to '../Cellar/eza/0.18/bin/eza', resolve shows the entire path from ll to the Mach-O binary.

Companion Verbs

```
zpwr exists          # check if identifier is valid
zpwr deps            # function dependency graph
zpwr funcrank        # rank functions by usage
```

Shell Introspection

// 32 verbs to look inward //

Inspect ZPWR itself: banners, counts, plugin lists, subcommand discovery, and identity checks.

Existence Checks

```
zpwr exists          # check if identifier is valid
zpwr existscommand   # check if command is valid
```

Banners

```
zpwr about           # show zpwr banner
zpwr banner           # show zpwr banner
zpwr bannercounts     # show banner and env counts
zpwr bannerlolcat     # banner with ponysay and lolcat
zpwr bannernopony     # show banner without ponysay
zpwr bannerpony       # show banner with ponysay
```

Counts & Lists

```
zpwr autoloadcount      # total number of autoloads
zpwr autoloadlist       # total list of autoloads
zpwr scriptcount        # total number of scripts
zpwr scriptlist         # total list of scripts
zpwr zshplugincount     # total number of zsh plugins
zpwr zshpluginlist      # total list of zsh plugins
zpwr vimplugincount     # total number of vim plugins
zpwr vimpluginlist      # total list of vim plugins
zpwr emacsplugincount   # total number of emacs plugins
zpwr emacspluginlist    # total list of emacs plugins
```

Subcommands & Verbs

```
zpwr subcommands        # run subcommands for zpwr <tab>
zpwr subcommandscount   # number of subcommands
zpwr subcommandsedited  # edit subcommands for zpwr <tab>
zpwr subcommandsfzf     # fzf subcommands for zpwr <tab>
zpwr subcommandsls      # list subcommands for zpwr <tab>
zpwr verbs              # run subcommands for zpwr <tab>
zpwr verbscount         # number of verbs
zpwr verbsedit          # edit subcommands for zpwr <tab>
zpwr verbsfzf           # fzf subcommands for zpwr <tab>
zpwr verbslist          # list subcommands for zpwr <tab>
zpwr help               # list subcommands with color
```

Misc Introspection

```
zpwr tty                # print current tty
zpwr relpath            # get relative path to $PWD
zpwr printmap           # pretty print maps
```

Chapter 18 – Installation & Reset

Config Sessions

Config Sessions: Edit Everything From Here

One verb to open any config, no path memorization.

ZPWR provides shortcut verbs for every config file you'll ever need to edit. No more 'vim ~/.zshrc'.

zpwr Brc – Bash Rc

Edit your .bashrc. For when bash compatibility matters.

```
zpwr brc          # edit .bashrc
```

zpwr Zrc – zsh Rc

Edit your .zshrc. The most-touched config in ZPWR.

```
zpwr zrc          # edit .zshrc
```

zpwr Vrc – vim Rc

Edit your .vimrc or init.vim/init.lua.

```
zpwr vrc          # edit vim config
```

zpwr Trc – tmux Rc

Edit your .tmux.conf. Keybindings, statusbar, the works.

```
zpwr trc          # edit tmux config
```

zpwr Tokens – Secrets File

Edit \$ZPWR_LOCAL/.tokens.sh. API keys, secrets, env vars.

```
zpwr tokens      # edit tokens/secrets
zpwr vimtokens    # same, force vim
zpwr emacs tokens # same, force emacs
```

zpwr Zcompdump – Completion Cache

Inspect or regenerate the zsh completion dump file. When completions act weird, this is where you look.

```
zpwr zcompdump    # inspect comp cache
```

```
// brc, zrc, vrc, trc – four letters, four configs
// tokens for secrets, zcompdump for completion fixes
```

Install & Uninstall

Install & Uninstall: Setup And Teardown

Easy to install, clean to remove – no malware energy.

zpwr Install

Run the full ZPWR installation process. Installs dependencies, links configs, sets up plugins.

```
zpwr install                # full installation
```

WHAT IT DOES: 1. Installs system dependencies (brew/apt) 2. Links config files to their proper locations 3. Installs zsh, vim, and emacs plugins 4. Generates caches and completion dumps 5. Sets up tmux configuration.

zpwr Uninstall

Remove ZPWR configuration. Restores your shell to its pre-ZPWR state. Clean breakup, no hard feelings.

```
zpwr uninstall              # remove zpwr config
```

Config Link Management:

ZPWR uses symlinks to place configs where tools expect them.

How it works: `$ZPWR/configs/.zshrc` → `~/.zshrc` (symlink) `$ZPWR/configs/.vimrc` → `~/.vimrc` (symlink)
`$ZPWR/configs/.tmux` → `~/.tmux.conf` (symlink)

The source of truth lives in `$ZPWR`, the symlinks just point there. Version controlled, portable, clean.

Partial Operations:

Sometimes you don't want the full install/uninstall. You just need to fix the symlinks:

Regenconfiglinks = recreate all config symlinks rmconfiglinks = remove symlinks only.

// install is idempotent – run it again when things drift

// uninstall is clean – your system goes back to stock

Reset & Recovery

Reset & Recovery: When Things Go Wrong

Every system needs a panic button – here are yours.

zpwr Reset

Full framework reset. Clears caches, regenerates configs, rebuilds completion dumps, relinks everything.

```
zpwr reset # the big red button
```

WHEN TO USE: * Completions are broken or stale * Config changes aren't taking effect * Something feels "off" and you can't pin it down * After a major ZPWR update.

zpwr Reload

Hot reload without resetting. Re-sources all configs and refreshes the environment. Faster than reset.

```
zpwr reload # hot reload
```

Use reload when you've edited a config and want to apply changes without nuking caches.

Escalation Ladder:

Level 1: zpwr reload # re-source configs Level 2: zpwr reset # rebuild everything Level 3: zpwr install # full reinstall Level 4: rm -rf \$ZPWR && clone # scorched earth.

Start at Level 1. Only escalate if the problem persists. Most issues are fixed by reload. Reset handles the rest.

Common Recovery Scenarios:

"Completions are wrong" → zpwr reset "alias isn't working" → zpwr reload "new plugin not loading" → zpwr reload "everything is broken" → zpwr reset "still broken after reset" → zpwr install.

// reload is ctrl-r for your shell framework

// reset is the factory reset you hope to never need

// but when you do need it, you'll be glad it exists

Chapter 19 – Batch Operations

Loop Warriors

Loop Warriors – The Repetition Toolkit

Because doing things once is for civilians.

The batch operations verbs are the assault rifles of the ZPWR arsenal. Point them at a problem, pull the trigger, and watch every target fall.

The For Loop – Your Basic Infantry

```
zpwr for <cmd> <args...>
```

Executes a command for each argument passed to it. Stdin becomes your ammo belt — pipe lines in, each one fires.

Example: run a command against multiple targets.

```
echo 'file1.txt\nfile2.txt' | zpwr for wc -l
```

For10 – The Burst-fire Variant

```
zpwr for10 <cmd>
```

Runs your command 10 times. No arguments, no mercy. Perfect for stress testing, benchmarking, or just asserting dominance over your CPU.

Example: benchmark a command 10 times.

```
zpwr for10 zpwr bench
```

Whiletrue – The Infinite Loop

```
zpwr whiletrue <cmd>
```

Runs your command forever. Ctrl-C is your only exit. For monitoring, watching, waiting. The sentinel loop.

Example: watch disk usage forever.

```
zpwr whiletrue df -h /
```

WARNING: there is no break condition. You ARE the break.

Whilesleep – The Patient Sniper

```
zpwr whilesleep <seconds> <cmd>
```

Like whiletrue, but sleeps between rounds. Polling with grace. Surveillance with manners.

Example: check a URL every 30 seconds.

```
zpwr whilesleep 30 curl -s -o /dev/null -w '%{http_code}' https://example.com
```

TACTICAL SUMMARY: for iterate over stdin lines for 10 run 10 times, no questions asked whiletrue infinite loop, Ctrl-C to escape whilesleep infinite loop with naptime between rounds.

// in the loop, there is no time, only iterations

// the loop does not end. the operator ends the loop.

Directory Sweeps

Directory Sweeps – Carpet Bombing Your Filesystem

One directory at a time, or all of them at once.

Single-file loops are amateur hour. Real operators sweep directories. They glob patterns. They parallelize. These verbs are your air support.

Fordir – The Directory Crawler

```
zpwr fordir <cmd>
```

Iterates into each subdirectory of the current dir and executes the command inside it. cd in, run, cd out. Like a SWAT team clearing rooms one by one.

Example: check git status in every project dir.

```
cd ~/repos && zpwr fordir git status -s
```

Fordirupdate – The Mass Updater

```
zpwr fordirupdate
```

Enters every subdirectory and runs git pull. Your entire project portfolio, synced in one command. Monday morning? Run this first. Coffee second.

Example: update all repos under ~/repos

```
cd ~/repos && zpwr fordirupdate
```

Execglob – Glob And Execute

```
zpwr execglob <glob> <cmd>
```

Finds files matching a glob pattern and runs your command against each one. Pattern matching meets execution. The regex sniper rifle of file operations.

Example: lint every Python file in the tree.

```
zpwr execglob '*.py' pylint
```

Execglobparallel – Concurrent Devastation

```
zplr execglobparallel <glob> <cmd>
```

Same as execglob, but fires all jobs in parallel. Every CPU core gets drafted into service. Your fan will spin up. This is normal. This is power.

Example: format every .rs file in parallel.

```
zplr execglobparallel '*.rs' rustfmt
```

CHOOSING YOUR WEAPON: fordir run cmd in each subdirectory fordirupdate git pull in each subdirectory
execglob glob match + execute sequentially execglobparallel glob match + execute in parallel.

// sequential is predictable. parallel is fast.

// choose based on whether output order matters.

// when in doubt, go parallel. life is short.

Polyglot Execution

Polyglot Execution – Beyond The Shell

zsh is the conductor, but the orchestra speaks many tongues.

Sometimes zsh loops aren't enough. Sometimes you need Python. Sometimes you need background jobs. Sometimes you need to poll a service until it wakes up or dies.

Execpy – The Python Bridge

```
zplr execpy <python_expression>
```

Fires a Python expression from the comfort of your shell. No need to open a REPL. No need for a .py file. Quick math, string ops, one-liners — python as a verb.

Example: quick calculation.

```
zplr execpy '2**128'
```

=> 340282366920938463463374607431768211456.

Background – The Shadow Operative

```
zplr background <cmd>
```

Sends a command into the background. Detached. Silent. It runs in the shadows while you keep working. Output goes to the void unless you redirect it.

Example: start a long build in the background.

```
zplr background make -j8
```

Timer – The Stopwatch

```
zplr timer <cmd>
```

Wraps any command in a high-resolution timer. How long did that take? Now you know. No guessing. Benchmarking made trivial.

Example: time your shell startup.

```
zplr timer zsh -ic exit
```

Poll – The Watchdog

```
zplr poll <cmd>
```

Runs a command repeatedly until it succeeds (exit 0). Waiting for a server to come up? A build to finish? Poll is your patient, relentless sentinel.

Example: wait for a port to open.

```
zplr poll nc -z localhost 8080
```

THE BATCH OPS PHILOSOPHY: Loops for, for10, whiletrue, whilesleep Sweeps fordir, fordirupdate, execglob* Polyglot execpy, background, timer, poll.

// the terminal is not a single-threaded mind

// it is a factory floor. these verbs are the machines.

// feed them work. they do not tire. they do not complain.

Git Repo Cache System

// index every repo on your machine. operate on all of them. //

The zsh-git-repo-cache plugin scans your entire filesystem for git repos, caches the list, and lets you search, filter, and broadcast commands across all of them.

Cache Generation

```
zplr regengitrepopcache      # scan filesystem with fd/find
zplr regengitdirtyrepopcache # scan only dirty repos
```

Search & Browse

```
zplr gitrepos      # all repos into fzf
zplr gitreposclean # clean repos into fzf
zplr gitreposdirty # dirty repos into fzf
zplr gitreposlist  # list all repos (no fzf)
zplr gitreposcleanlist # list clean repos
zplr gitreposdirtylist # list dirty repos
```

Cached Variants

```
zplr gitreposcleancache # clean repos from cache
zplr gitreposdirtycache # dirty repos from cache
zplr gitreposcleancachelist # list clean from cache
zplr gitreposdirtycachelist # list dirty from cache
```

Batch Operations

```
zpwr gitreposexec <cmd>          # run cmd in all cached repos
zpwr gitreposdirtyexec <cmd>      # run cmd in dirty repos
zpwr gitreposcleanexec <cmd>     # run cmd in clean repos
zpwr gitwho                      # contributor stats across all repos
```

Cache Files

`$ZPWR_ALL_GIT_DIRS` — all repos `$ZPWR_ALL_GIT_DIRS_CLEAN` — clean repos only `$ZPWR_ALL_GIT_DIRS_DIRTY` — dirty repos only

Plugin: MenkeTechnologies/zsh-git-repo-cache.

Chapter 20 – Forgit Deep Dive

Forgit Add & Diff

Forgit Add & Diff – Interactive Staging

git add, but make it beautiful.

Forgit is the fusion of fzf and git. It wraps the most common git operations in fuzzy, interactive, preview-enabled interfaces. You will never go back to raw git add.

Forgitadd – Interactive Staging

```
zpwri forgitadd
```

Opens an fzf interface showing all unstaged changes. Each file gets a diff preview in the right pane. Tab to select multiple files. Enter to stage them.

The workflow: 1. Run zpwri forgitadd 2. Browse files with arrow keys 3. See the diff preview for each file 4. Tab to multi-select 5. Enter to stage selected files.

No more git add -p scrolling through 500-line diffs. No more accidentally staging that debug print.

Forgitdiff – Visual Diff Browser

```
zpwri forgitdiff
```

Opens an fzf browser of all changed files with a live diff preview. Read diffs without committing to anything. Pure reconnaissance.

Example workflow:

```
zpwri forgitdiff      # browse all diffs visually
zpwri forgitadd       # stage what you want
zpwri gitcommit 'msg' # commit with message
```

WHY FORGIT > RAW GIT: Raw git add: type filenames from memory like a caveman forgitadd: browse, preview, multi-select, confirm Raw git diff: wall of text scrolling past forgitdiff: file-by-file preview with fuzzy search.

// staging should not be a memory test

// it should be a visual, interactive experience

// forgit turns git into a GUI without leaving the terminal

Forgit Log & Stash

Forgit Log & Stash – Visual History

Time travel with a preview window.

Git log is a river of hashes. Git stash is a pile of forgotten context. Forgit turns both into something you can actually navigate without losing your mind.

Forgitlog – The Commit Browser

```
zpwr forgitlog
```

Opens your git history in fzf with commit previews. Each commit shows its full diff in the preview pane. Search commits by message, author, or hash.

What you see: Left pane: commit graph with short messages Right pane: full diff of highlighted commit Search: fuzzy match on any commit field.

“Who wrote this garbage?” — you, using forgitlog, discovering it was also you, three months ago.

Forgitstash – The Stash Manager

```
zpwr forgitstash
```

Browse your stash entries with preview diffs. See what is in each stash before applying it. No more git stash pop roulette.

The old way: git stash list # cryptic one-liners git stash show -p stash@{2} # which one was it again? git stash pop # pray.

The forgit way:

```
zpwr forgitstash          # browse, preview, apply
```

LOG + STASH TOGETHER: These two verbs give you eyes into the past. forgitlog shows committed history. forgitstash shows uncommitted history. Between them, nothing is lost.

// the commit graph is not a wall of text

// it is a timeline. forgit lets you walk it.

// stashes are not forgotten. they are filed.

Forgit Ignore & Clean

Forgit Ignore & Clean – .GITIGNORE Management

Because node_modules should never see the inside of a commit.

The .gitignore is your repo’s bouncer list. These verbs manage it with the precision of a nightclub velvet rope.

Forgitignore – The Ignore Browser

```
zpwr forgitignore
```

Interactive gitignore template browser powered by gitignore.io. Search for languages, frameworks, IDEs. Never hand-write a .gitignore again.

The Ignore Family:

Forgitignorelist list available gitignore templates forgitignoreget fetch a specific template by name forgitignore-update update your local template cache forgitignoreclean clean the template cache.

Example: generate a Python + macOS gitignore.

```
zpwr forgitignoreget python,macos > .gitignore
```

Example: browse all available templates.

```
zpwr forgitignorelist
```

Forgitclean – The Untracked File Purge

```
zpwr forgitclean
```

Shows untracked files in an fzf interface with previews. Select which ones to delete. Surgical, not scorched earth. Unlike git clean -fd, you see before you destroy.

The old way: git clean -fd # delete everything. hope for the best.

The forgit way:

```
zpwr forgitclean # browse, select, confirm, then delete.
```

IGNORE WORKFLOW: 1. zpwr forgitignorelist browse templates 2. zpwr forgitignoreget fetch what you need 3. zpwr forgitclean purge untracked cruft 4. zpwr forgitadd stage the clean repo.

// a clean repo is a happy repo

// an ignored file is a file that cannot hurt you

// let the templates do the thinking

Forgit Reset & Restore

Forgit Reset & Restore – Undo With Eyes Open

The nuclear options, but with a safety preview.

Git reset and restore are the most terrifying commands in version control. Forgit wraps them in bubble wrap and gives you a preview before you pull the trigger.

Forgitreset – Unstage With Preview

```
zpwr forgitreset
```

Shows staged files in fzf with diff previews. Select files to unstage. Like git reset HEAD but you can see exactly what you are unstaging first.

Use case: you ran git add -A like a maniac and now you need to surgically remove files.

```
zpwr forgitreset # browse and unstage selectively
```

Forgitrestore – Discard Changes Safely

```
zpwr forgitrestore
```

Shows modified files with diff previews. Select files to restore to their last committed state. This discards changes permanently. No undo.

The preview saves you. You see the diff before the changes evaporate into the void.

Forgitwarn – The Safety Net

```
zpwr forgitwarn
```

Displays warnings about uncommitted changes, diverged branches, and other hazardous states. Your pre-flight checklist before doing anything destructive.

Forgitinfo – The Status Dashboard

```
zpwr forgitinfo
```

Comprehensive repo information at a glance. Branch, remotes, recent commits, dirty state. Everything you need before making decisions.

THE FORGIT COMPLETE ARSENAL: forgitadd interactive stage forgitdiff browse diffs forgitlog commit history browser forgitstash stash manager forgitreset interactive unstage forgitrestore discard changes with preview forgitclean purge untracked files forgitignore* gitignore template management forgitwarn hazard warnings forgitinfo repo dashboard.

// forgit is not a git replacement

// it is git with eyes. git with a UI. git for humans.

Forgit Reference

// 14 verbs for fzf-powered git //

Forgit wraps common git operations in fzf interfaces. Interactive staging, diffing, stashing, and more.

Staging & Diffing

```
zpwr forgitadd          # fzf interactive git add
zpwr forgitdiff         # fzf interactive git diff
zpwr forgitreset        # fzf interactive git reset
zpwr forgitrestore      # fzf interactive git restore
```

Stash & Clean

```
zpwr forgitstash        # fzf interactive stash show
zpwr forgitclean         # fzf interactive git clean
```

Log & Info

```
zplr forgitlog      # fzf interactive git log
zplr forgitinfo     # fzf git info
zplr forgitwarn     # fzf git warn
```

Gitignore Management

```
zplr forgitignore   # fzf gitignore templates
zplr forgitignoreclean # fzf gitignore clean
zplr forgitignoreget  # fzf gitignore get
zplr forgitignorelist # fzf gitignore list
zplr forgitignoreupdate # fzf gitignore update
```

Chapter 21 – zpwr Environment Variables

Core Paths

Core Paths – The Skeleton Of The Machine

Every system has bones. these are ZPWR's.

ZPWR does not hardcode paths. Every directory is an environment variable. Move the root, and the entire system follows. This is not a dotfiles repo — it is a relocatable operating system.

\$ZPWR – The Root Of All Things

```
echo $ZPWR    # typically ~/.zpwr
```

The root directory. Every other path derives from this. Change this one variable and the whole tree moves.

\$ZPWR_LOCAL – Your Private Sanctum

```
echo $ZPWR_LOCAL # $ZPWR/local
```

Gitignored. Your tokens, secrets, local overrides. Nothing in here ever touches a remote repository. Your .tokens.sh lives here. Guard it with your life.

\$ZPWR_SCRIPTS – The Armory

```
echo $ZPWR_SCRIPTS # $ZPWR/scripts
```

Executable scripts. Bash, Python, Perl — whatever gets the job done. These are on your PATH.

\$ZPWR_TMUX – The Multiplexer Config

```
echo $ZPWR_TMUX # $ZPWR/tmux
```

Tmux configuration, scripts, and status line logic. The control center for your terminal multiplexer.

\$ZPWR_INSTALL – The Installer

```
echo $ZPWR_INSTALL # $ZPWR/install
```

OS-specific installation scripts. macOS, Ubuntu, Fedora, Arch — each gets its own installer. Run zpwr install and the right one fires.

THE PATH MAP: `$ZPWR ~/ .zpw` (the root) `$ZPWR_LOCAL $ZPWR/local` (gitignored secrets) `$ZPWR_SCRIPTS $ZPWR/scripts` (executables) `$ZPWR_TMUX $ZPWR/tmux` (multiplexer) `$ZPWR_INSTALL $ZPWR/install` (OS installers)

// paths are not strings. they are load-bearing structures.

// hardcode a path and you weld yourself to the floor.

// use the variables. always use the variables.

Autoload System

The Autoload System – Lazy Loading For Hackers

Why load everything when you can load nothing until needed?

Zsh autoloading is the secret to ZPWR's fast startup. Functions are not loaded into memory until you call them. The shell knows they exist, but their code stays on disk until the moment of invocation. Maximum laziness. Maximum speed.

`$ZPWR_AUTOLOAD` – The Function Warehouse

```
echo $ZPWR_AUTOLOAD # $ZPWR/autoload
```

The root of the autoload tree. Every file in this tree becomes a function name. The filename IS the function.

`$ZPWR_AUTOLOAD_COMMON` – Cross-platform Functions

```
echo $ZPWR_AUTOLOAD_COMMON # $ZPWR/autoload/common
```

Functions that work on every OS. The common denominator. macOS, Linux, BSD — these functions do not care.

How Autoloading Works:

1. Zsh scans `$fpath` directories at startup
2. Each filename is registered as a function stub
3. When you call the function, zsh reads the file
4. The file contents replace the stub
5. The function executes with the loaded code

This means hundreds of autoload stubs cost near-zero at startup. Only the ones you actually use consume memory.

The Compile Acceleration:

```
zpw compile      # compile autoloads to .zwc
zpw recompile    # recompile all
zpw uncompile    # remove compiled files
```

Compiled `.zwc` files load faster than raw source. ZPWR compiles its autoload dirs into wordcode files. It is like bytecode for your shell functions.

INSPECTION VERBS:

```
zpwr autoload      show the autoload system
zpwr autoloadcount  count autoloaded functions
zpwr autoloadlist   list all autoloaded functions
```

// the fastest code is code that never runs
// autoloading is the art of deferred execution
// 400 functions, zero startup cost. that is the deal.

Behavior Flags

Behavior Flags – The Knobs And Dials

Tune the machine without cracking open the engine.

ZPWR is not a take-it-or-leave-it monolith. These boolean and string flags let you control startup behavior, logging verbosity, and debug output without editing a single line of source code.

\$ZPWR_PROFILING – Startup Profiler

```
export ZPWR_PROFILING=true
```

Enables zsh startup profiling. Shows exactly where your milliseconds go during shell init. Pair with.

```
zpwr bench for the full picture.
```

Set it, open a new shell, and read the profiling data. Find the bottleneck. Kill the bottleneck. Repeat.

\$ZPWR_DEBUG – Debug Mode

```
export ZPWR_DEBUG=true
```

Turns on debug-level log messages. When something is broken and you need the machine to talk, flip this. Check output with `zpwr logdebug`.

\$ZPWR_TRACE – Full Trace Mode

```
export ZPWR_TRACE=true
```

The firehose. Every function call, every expansion, traced to the log. Use `zpwr trace` to run commands with tracing, or `zpwr logtrace` to read trace logs. WARNING: produces enormous output. Use surgically.

\$ZPWR_BANNER_CLEARLIST – Startup Banner Control

```
export ZPWR_BANNER_CLEARLIST=true
```

Controls whether the ZPWR banner and clearlist show at shell startup. The banner is glorious, but if you open 50 terminals a day, you might want silence.

Related verbs:

```
zpwr banner      show the banner manually
zpwr clearlist    show clearlist manually
zpwr bannerlolcat banner with rainbow colors
```

QUICK REFERENCE: ZPWR_PROFILING startup timing data ZPWR_DEBUG debug-level logging
ZPWR_TRACE full execution trace ZPWR_BANNER_CLEARLIST startup banner toggle.

// the flags do not change the code. they reveal it.

// debugging is not failure. it is x-ray vision.

Plugin System

Plugin System – The Turbo Loader

zinit: loading plugins at the speed of light.

ZPWR uses zinit (formerly zplugin) as its plugin manager. But not the basic way. The turbo way. Plugins load asynchronously after prompt appears. You see your prompt instantly. Plugins catch up.

\$ZPWR_PLUGIN_MANAGER – Choose Your Loader

```
echo $ZPWR_PLUGIN_MANAGER # zinit
```

Controls which plugin manager ZPWR uses. The default and recommended value is zinit. Other managers exist but zinit's turbo mode is what makes ZPWR fast.

Turbo Loading Explained:

Normal plugin loading: source plugin1.zsh # blocks source plugin2.zsh # blocks source plugin3.zsh # blocks # prompt finally appears after ALL plugins load.

Zinit turbo loading: prompt appears immediately plugin1 loads in background ... done plugin2 loads in background ... done plugin3 loads in background ... done # user never notices the delay

Plugin Inspection:

```
zpwr zshplugincount    count loaded zsh plugins
zpwr zshpluginlist     list all loaded zsh plugins
zpwr vimplugincount    count vim plugins
zpwr vimpluginlist     list all vim plugins
zpwr emacsplugincount  count emacs plugins
zpwr emacspluginlist   list all emacs plugins
```

Update And Maintain:

```
zpwr updatezinit      update zinit itself
zpwr updatedeps       update all plugin deps
zpwr plugins          plugin information
```

// plugins are not bloat. they are force multipliers.

// but only if they load in zero perceived time.

// turbo mode makes 50 plugins feel like zero.

Display & Input

Display & Input – The Human Interface Layer

How the machine talks to you, and how you talk back.

These variables control what you see and how fast the shell responds to your keystrokes. Milliseconds matter when your fingers are moving at light speed.

\$ZPWR_EXA_COMMAND – The ls Replacement

```
echo $ZPWR_EXA_COMMAND # exa or eza
```

Controls which modern ls replacement ZPWR uses. exa is the original, eza is the maintained fork. Both give you colored, git-aware directory listings.

ZPWR verbs like zpwr ls and zpwr clearls use this. Set it in your tokens file to override the default.

\$ZPWR_KEYTIMEOUT – Keystroke Latency

```
echo $ZPWR_KEYTIMEOUT # in hundredths of a second
```

How long zsh waits for the next key in a multi-key sequence. Lower = snappier. Too low = missed sequences. Default is tuned for fast typists.

If vi-mode feels laggy on Esc, lower this. If key combos misfire, raise this. Sweet spot is personal. Experiment.

\$ZPWR_EXPAND_PRE_EXEC – Alias Expansion

```
echo $ZPWR_EXPAND_PRE_EXEC
```

Controls whether ZPWR expands aliases before execution. When enabled, you type the alias and see the full command in your history. Transparency mode.

With expansion: you type ga -> history shows git add Without expansion: you type ga -> history shows ga.

\$ZPWR_SEND_KEYS_FULL – tmux Key Passthrough

```
echo $ZPWR_SEND_KEYS_FULL
```

Controls full send-keys behavior in tmux integration. When ZPWR manages tmux panes, this determines how keystrokes are forwarded to target panes.

TUNING GUIDE: Feeling laggy? Lower ZPWR_KEYTIMEOUT Missing combos? Raise ZPWR_KEYTIMEOUT Want transparency? Enable ZPWR_EXPAND_PRE_EXEC Using eza? Set ZPWR_EXA_COMMAND=eza.

// the interface is not decoration. it is velocity.

// every millisecond of latency is a papercut.

// tune these until your shell feels like thought.

Runtime State

Runtime State – The Machine’s Self-awareness

The shell knows what it is. do you?

These variables hold runtime state — what OS you are on, what TTY you are using, where logs go. They are set at startup and consulted throughout the session.

\$ZPWR_TTY – Your Terminal Identity

```
echo $ZPWR_TTY    # e.g., /dev/ttys003
```

The TTY device for the current shell session. Used by ZPWR to track which terminal is which, especially when managing multiple tmux panes.

The `zpwr tty` verb shows your current TTY info.

\$ZPWR_OS_TYPE – Platform Detection

```
echo $ZPWR_OS_TYPE    # Darwin, Linux, etc.
```

Detected at startup. Used throughout ZPWR to branch on platform-specific behavior. macOS vs Linux vs BSD, the right code path fires automatically.

This is why ZPWR works on macOS and Linux without you changing a single setting. The OS type decides.

\$ZPWR_LOGFILE – The Black Box

```
echo $ZPWR_LOGFILE
```

Where ZPWR writes its log output. Debug, info, error, trace — all levels go here when enabled.

Read the logs:

```
zpwr loginfo      info-level messages
zpwr logdebug     debug-level messages
zpwr logerror     error-level messages
zpwr logtrace     trace-level messages
zpwr taillog      live tail with colored output
```

\$ZPWR_COMPSYS_CACHE – Completion Cache

```
echo $ZPWR_COMPSYS_CACHE
```

Controls the completion system cache. Zsh completions are expensive to regenerate. This flag keeps them cached.

\$ZPWR_HISTFILE – History File

```
echo $ZPWR_HISTFILE
```

Your shell history file location. ZPWR manages history with deduplication and backup. Your commands are sacred.

Related: `zpwr backuphistory` and `zpwr restorehistory`.

THE FULL ENV VAR MAP: Core paths: ZPWR, ZPWR_LOCAL, ZPWR_SCRIPTS, ZPWR_TMUX Autoload: ZPWR_AUTOLOAD, ZPWR_AUTOLOAD_COMMON Flags: ZPWR_PROFILING, ZPWR_DEBUG, ZPWR_TRACE Display: ZPWR_EXA_COMMAND, ZPWR_KEYTIMEOUT Runtime: ZPWR_TTY, ZPWR_OS_TYPE, ZPWR_LOGFILE.

// the machine knows itself. every variable is a mirror.

// read them to understand the current state of reality.

Color Systems – Painting The Void

256 colors. true color. the terminal is not monochrome.

Color is not cosmetic. It is information density. A colored diff tells you more in one glance than a monochrome one does in ten seconds. ZPWR gives you tools to explore, test, and master terminal color.

Colortest – The 16-COLOR Palette

```
zpwri colortest
```

Displays the basic 16-color ANSI palette. The foundation. Black, red, green, yellow, blue, magenta, cyan, white — plus their bright variants. 16 soldiers in formation.

Use this to verify your terminal theme is sane. If red looks orange, your theme needs fixing.

Colortest256 – The Full Spectrum

```
zpwri colortest256
```

Displays all 256 extended colors. A grid of every color code your terminal supports. From 0 to 255. Useful for picking colors for prompts and scripts.

“What number is that teal?” Run this and find out.

Pygmentcolors – Syntax Highlighting Palette

```
zpwri pygmentcolors
```

Shows available Pygments color schemes. Pygments is the syntax highlighting engine used by many ZPWR tools. Pick a scheme that matches your aesthetic.

Prettyprint & Altprettyprint – Formatted Output

```
zpwri prettyprint <file>  
zpwri altprettyprint <file>
```

Syntax-highlighted file display. prettyprint uses one engine, altprettyprint uses another. Both turn raw source code into technicolor glory in your terminal.

Like cat, but for people who respect their eyes.

COLOR EXPLORATION WORKFLOW: 1. zpwri colortest check basic 16 colors 2. zpwri colortest256 explore full 256 palette 3. zpwri pygmentcolors pick a syntax theme 4. zpwri prettyprint view files in color.

// monochrome terminals are a war crime

// color is data. learn to read it.

// 256 colors and you are still using white-on-black?

Script Management

Script Management – The Stryke

Create scripts. count scripts. print scripts to PDF. ship scripts.

ZPWR manages its own script collection and gives you tools to create new ones, inventory them, and even export them to PDF for documentation or review.

Scriptnew – The Script Generator

```
zpwr scriptnew <name>
```

Creates a new script with proper boilerplate. Shebang, error handling, argument parsing — all pre-wired. Stop writing boilerplate. Start writing logic.

The script lands in `$ZPWR_SCRIPTS`, already executable, already on your PATH. Zero friction from idea to tool.

Scripttopdf – The Documenter

```
zpwr scripttopdf
```

Converts scripts to syntax-highlighted PDFs. For code reviews, documentation, or printing out and framing on your wall like the art it is.

Send your code to a printer. Assert dominance.

Scriptcount – The Census

```
zpwr scriptcount
```

How many scripts live in `$ZPWR_SCRIPTS`? This tells you. Track the growth of your personal armory over time.

Scriptlist – The Inventory

```
zpwr scriptlist
```

Lists every script in the collection. Names, paths, the full manifest of your executable arsenal.

THE SCRIPT LIFECYCLE: 1. `zpwr scriptnew myutil` create the script 2. `zpwr vimscriptedit` edit scripts with vim/fzf 3. `zpwr scriptcount` check your inventory 4. `zpwr scriptlist` browse the collection 5. `zpwr scripttopdf` export for documentation.

Also Related:

```
zpwr mkdir <name>      create a directory
zpwr makefile <name>   create a file
```

Simple creation verbs. No boilerplate, just `mkdir/touch` with ZPWR's logging and validation baked in.

// a script unwritten is a problem unsolved

// a script uncounted is a tool forgotten

// the stryke never closes. the armory always grows.

The Matrix

// not cmatrix. this is YOUR shell, raining. //

zpwr matrix is an animated cyberpunk hacker story followed by an infinite ecosystem rain screensaver. Unlike cmatrix, it rains YOUR data — verb names, function names, aliases, env vars, and git repo names. Color-coded by type.

The Story

ACT I The Signal — the terminal underground survives ACT II The Discovery — curl | zsh changes everything ACT III The Power — bench, flame, doctor, gitwho ACT IV The Choice — VS Code or zpwr matrix? Between acts: fake SSH sessions, encrypted transmissions, payload downloads with glitchy progress bars.

The Fx

CRT scanlines green sweep top-to-bottom VHS tracking horizontal distortion bands Pixel corruption spreading block static Screen tears offset colored bands Figlet chaos random fonts, random words, dissolve Progress bars with random glitch spikes Pulse events ecosystem facts flash across screen Scrolling ticker horizontal stat crawl HUD overlay live verb/alias/func/repo counters.

The Rain Colors

Green verbs cyan functions yellow aliases magenta env vars red git repos.

Usage

```
zpwr matrix          # full story + rain
zpwr matrix -i       # skip story, rain only
zpwr matrix -s 7     # faster (1-9)
zpwr rain            # alias
zpwr screensaver     # alias
```

Fortune Cookies

// wisdom from the digital underground //

zpwr fortune displays a random hacker quote rendered in a random figlet font with neon colors. 40 curated quotes from legends and original ZPWR wisdom.

The Verb

```
zpwr fortune         # random quote, random font
zpwr fortune -p      # plain text with box frame
zpwr fortune -f doom # force doom font
zpwr wisdom          # alias
zpwr quote           # alias
```

The Quotes

Linus Torvalds “Talk is cheap. Show me the code.” Brian Kernighan “Controlling complexity is the essence...” Grace Hopper “The most dangerous phrase is...” ZPWR “Home is where the .zshrc is.” MenkeTechnologies “Aliases are love letters to your future self.” ...and 35 more.

The Fonts

Randomly selected from: cyberlarge, cybermedium, doom, slant, speed, banner, standard. Each quote picks a keyword for large figlet rendering, full quote below.

Use Cases

- Add to .zshrc for a fortune on every new shell - Pipe to lolcat: `zpwr fortune -p | lolcat` - Use as a tmux status-right: too slow, but fun to try

Matrix: The Full Experience

8 acts, 6 characters, and your ecosystem raining down

The Story

```
zpwr matrix          # 4-act story + rain
zpwr matrix --extended # full 8-act saga
```

The Characters

```
zpwr matrix --cast      # show character bios
```

```
Null Pointer .... protagonist, zpwr operator
Segfault ..... bash loyalist in recovery
Chmod777 ..... reckless, sudo for everything
```

```
DevNull ..... silent assassin
```

Chad Electron ... MegaCorp VP, 64GB for Slack

```
The Kernel ..... mythical elder, speaks in dmesg
```

Visual Fx

```
zpwr matrix --noir      # monochrome green
zpwr matrix --vhs       # VHS tracking distortion
zpwr matrix --crt       # CRT scanlines
zpwr matrix --glitch    # extra corruption
zpwr matrix --sound     # terminal bells
zpwr matrix --no-fx     # disable all FX
zpwr matrix -c 10       # chaos level 1-10
```

Playback Control

```
zpwr matrix -s 7        # speed 1-9
zpwr matrix --turbo     # skip all pauses
zpwr matrix -a 5        # jump to act 5
zpwr matrix -r          # skip story, rain only
```

Multiplayer

```
zpwr matrix --battle      # 2-player tmux typing battle
```

Player 1 (Null Pointer) vs Player 2 (Chad Electron). Type zpwr commands faster than your opponent. HP bars, taunts, and a winner-takes-all endgame. Requires tmux. Auto-splits into two panes.

Info

```
zpwr matrix --stats      # ecosystem stats  
zpwr matrix --credits    # end credits roll
```

Chapter 23 – Exercism & External

Exercism Integration

Exercism Integration – Level Up Your Code

Practice makes perfect. ZPWR makes practice frictionless.

Exercism.org is a free coding practice platform with mentor-reviewed exercises in 50+ languages. ZPWR wraps the exercism CLI so you never leave your terminal.

Exercism – The Launcher

```
zpwr exercism
```

The base exercism command integration. Manages your exercism workspace, configuration, and submission workflow from within ZPWR.

Your exercism workspace lives under `$ZPWR` and is accessible via `zpwr homeexercism` for quick navigation.

Exercismdownload – Fetch Exercises

```
zpwr exercismdownload
```

Downloads an exercise to your local workspace. The exercise appears, ready to solve. Tests included. No browser clicking. No manual downloads.

The workflow: 1. Browse exercises on exercism.org 2. `zpwr exercismdownload` to fetch it 3. Solve the exercise in your editor 4. Run the tests locally 5. Submit when you pass.

Exercismedit – Solve In Your Editor

```
zpwr exercismedit
```

Opens exercism exercises directly in your configured editor. Download, edit, test, submit — all from the terminal. The browser is optional.

WHY EXERCISM + ZPWR:

The exercism CLI is good. ZPWR makes it seamless. No context switching. No browser tabs. No friction.

Languages supported by exercism: Python, Go, Rust, Elixir, JavaScript, TypeScript, C, C++, Java, Ruby, Haskell, Clojure, Kotlin, Swift, Bash, and 35+ more.

// coding practice should be as easy as

// opening a terminal and typing three words

// zpwr exercismdownload. done. now solve.

Travis CI & External Services

CI/CD from your terminal, not your browser.

ZPWR integrates with external services so you can monitor builds, check statuses, and manage CI/CD pipelines without opening a single browser tab.

Travis – The Ci Dashboard

```
zpwr travis
```

Travis CI integration. View build status, logs, and pipeline information from your terminal.

Travisbuild – Build Status

```
zpwr travisbuild
```

Check the current build status. Green, red, or pending. No need to refresh a web page in a loop.

Travisbranch – Branch Builds

```
zpwr travisbranch
```

View build status for a specific branch. When you push to a feature branch and want to know if CI passed.

Travispr – Pull Request Builds

```
zpwr travispr
```

Check build status for pull requests. The merge button is only as good as the CI behind it.

Other External Integrations:

```
zpwr goclean      clean Go build cache
zpwr google <query> search Google from terminal
zpwr digs <domain> DNS lookups
zpwr torip        check your Tor IP address
zpwr toriprenew   renew your Tor circuit
zpwr curl         enhanced curl operations
```

THE EXTERNAL SERVICES PHILOSOPHY: The browser is a context switch. Every tab you open is a distraction vector. ZPWR brings the services to you, in the terminal, where you already are.

// the terminal is the cockpit

// external services are instruments on the dashboard

// you read them. you do not visit them.

Chapter 24 – Tips, Tricks & Easter Eggs

The One-Letter Verbs

The One-letter Verbs – Maximum Power, Minimum Keystrokes

Six letters that do the work of six paragraphs.

郑WR has 512 verbs. Six of them are single characters. These are not abbreviations — they are the distilled essence of the most common operations. One keystroke each. The speed limit of human-shell interaction.

A – Autoload

```
郑WR a
```

Quick access to the autoload system. When you need to check on autoloaded functions fast.

C – cat

```
郑WR c
```

The cat operation. View file contents. The most basic read operation, compressed to one letter.

E – Edit

```
郑WR e
```

Open your editor. The gateway to modification. Uses your configured \$EDITOR.

F – Filesearch

```
郑WR f
```

File search. Find things. The single most common operation after listing and editing.

R – Replay

```
郑WR r
```

Replay operations. Redo what you did before. History is not just for reading.

Z – Zcd

```
zpwr z
```

Z-jump. Frequency-based directory navigation. Type a partial path, z figures out the rest. The single most addictive feature in ZPWR.

THE ONE-LETTER ARSENAL: a autoload system c cat / view files e edit files f file search r replay z z-jump directory navigation.

// every extra character is latency between thought and action

// one letter is the event horizon of efficiency

// below this, there is only telepathy

Alias Chains

Alias Chains – Compound Operations

One verb triggers another. the cascade begins.

ZPWR verbs do not exist in isolation. They chain. They compose. They call each other. This is not an accident — it is the architecture.

The Shorthand Aliases:

ZPWR is aliased to shorter forms for speed:

```
zpwr  the full command
zp    shorter
zpz   alternate short form
```

All three are equivalent:

```
zpwr help == zp help == zpz help
```

Compound Verb Patterns:

Many verbs are compounds that do two things:

Filesearch + edit = zpwr filesearchedit findsearch + edit = zpwr findsearchedit locatesearch + edit = zpwr locatesearchedit wordsearch + edit = zpwr wordsearchedit vimrecent + cd = zpwr vimrecentcd vimrecent + sudo = zpwr vimrecentsudo.

The pattern: action + modifier = compound verb Search, then edit. Browse, then cd. Open, then sudo.

The Clean Chain:

```
zpwr cleanall      clean everything
zpwr cleancache    clean caches only
zpwr cleancompcache clean completion cache
zpwr cleangitcache  clean git repo cache
zpwr cleangitcleancache clean git clean cache
zpwr cleangitdirtycache clean git dirty cache
zpwr cleantemp      clean temp files
zpwr cleanrefreshupdate clean + refresh + update
```

The Git Chain:

```
zpwr gitforalldir    run git cmd in all dirs
zpwr gitfordirmain   run git cmd in dirs on main
zpwr gitzfordir      z-style git for all dirs
```

// verbs are words. chains are sentences.

// the grammar of ZPWR is combinatorial.

// learn the words, and the sentences write themselves.

The Token System

The Token System – Your Private Override Layer

Secrets, aliases, and local config that never touch git.

ZPWR has sensible defaults. But you are not sensible. You have API keys, custom aliases, machine-specific paths, and opinions. The token system is where all of that lives — safely outside version control.

The Token Files:

`$ZPWR_LOCAL/.tokens.sh` Your main tokens file. Aliases, exports, secrets. This is sourced during shell init. Gitignored.

`$ZPWR_LOCAL/.tokens-pre.sh` Sourced BEFORE ZPWR's main configuration. Override defaults before they are set. Set `ZPWR_*` variables here to change behavior.

`$ZPWR_LOCAL/.tokens-post.sh` Sourced AFTER ZPWR's main configuration. Override anything ZPWR set. Final word. Your aliases here trump everything.

The Override Pattern:

Want to change a ZPWR default? Do not edit ZPWR source. Put it in `tokens-pre.sh` (before) or `tokens-post.sh` (after).

Example: override in `tokens-pre.sh`.

```
export ZPWR_EXA_COMMAND=eza
export ZPWR_KEYTIMEOUT=1
export ZPWR_BANNER_CLEARLIST=false
```

Example: add custom aliases in `tokens-post.sh`.

```
alias k=kubectl
alias tf=terraform
export GITHUB_TOKEN=ghp_XXXXX
```

Managing Tokens:

```
zpwr tokens          view your tokens files
zpwr vimtokens        edit tokens in vim
zpwr emacsstones      edit tokens in emacs
```

THE LOAD ORDER: 1. `tokens-pre.sh` (your early overrides) 2. ZPWR core config (the framework defaults) 3. `tokens-post.sh` (your final overrides) 4. `.tokens.sh` (your secrets and aliases)

NEVER commit token files. They are gitignored for a reason. API keys in git history haunt you forever.

```
// the token system is your private dimension  
// ZPWR updates without touching your config  
// your overrides survive every git pull
```

FZF Everywhere

fzf Everywhere – The Fuzzy Finder Conspiracy

fzf is not a tool. it is a religion. ZPWR is its cathedral.

fzf (fuzzy finder) is woven into the fabric of ZPWR. Dozens of verbs pipe their output through fzf for interactive selection. If a verb ends in 'fzf', it is the fuzzy-interactive variant. But many others use it too.

Dedicated fzf Verbs:

```
zpwr verbs    browse subcommands in fzf  
zpwr verbs    browse all verbs in fzf
```

Verbs That Use fzf Internally:

Forgit* verbs: forgitadd, forgitdiff, forgitlog, forgitstash, forgitreset, forgitrestore, forgitclean All use fzf for interactive selection with previews.

Search + edit verbs: filesearchedit, findsearchedit, locatesearchedit, wordsearchedit — search with fzf, open selection.

Recent file verbs: vimrecent, vimrecentcd, emacsrecent, emacsrecentcd Browse recent files with fzf preview.

Editor verbs: vimalledit, emacsalledit — select files to edit.

Git tag verbs: vimgtagsedit, emacsgtagsedit — browse tags in fzf.

The fzf Pattern:

The pattern is always the same: 1. Generate a list of candidates 2. Pipe through fzf with a preview command 3. Take the selection and act on it.

This pattern turns every list into a menu. Every menu into a decision. Every decision into action.

fzf Customization:

Set FZF_DEFAULT_OPTS in your tokens file:

```
export FZF_DEFAULT_OPTS='--height 80% --reverse --border'
```

// if you can list it, you can fzf it

// if you can fzf it, you can act on it

// fzf is the universal adapter between data and decisions

Alias Cheat Sheet

// the short names you will actually use //

Many zpwr verbs have short aliases. These are the ones worth memorizing — one or two keystrokes that replace entire workflows.

Diagnostics

zpwr doc	= doctor	zpwr zprof	= startup
zpwr check	= lint	zpwr audit	= pathaudit
zpwr cruft	= stale	zpwr rank	= funcrank
zpwr benchmark	= bench	zpwr dashboard	= top
zpwr heatmap	= flame	zpwr instrument	= trace
zpwr flamechart	= flame	zpwr checkup	= doctor
zpwr callers	= deps	zpwr aliasusage	= aliasrank

Monitoring

zpwr snap	= snapshot	zpwr load	= restore
zpwr rerun	= replay	zpwr onchange	= watch
zpwr book	= study		

Creative

zpwr rain	= matrix	zpwr wisdom	= fortune
zpwr quote	= fortune	zpwr screensaver	= matrix

Git

zpwr who	= gitwho	zpwr gitcontributes	= gitwho
----------	----------	---------------------	----------

Introspection

zpwr which	= resolve	zpwr whatis	= resolve
zpwr today	= timeline	zpwr activity	= timeline

Logging

zpwr logs	= taillog
-----------	-----------

Chapter 25 – The Complete Reference

All Verbs A-G

All 512 Verbs: A Through G (1/3)

The complete arsenal. memorize at your own peril.

A quick autoload access about display ZPWR about info alacrity alacrity terminal config aliasrank rank aliases by usage frequency all show all ZPWR info allsearch search across all sources altprettyprint alternate syntax-highlighted print animate terminal animations attach attach to tmux session autoload show autoload system autoloadcount count autoloading functions autoloadlist list all autoloading functions background run command in background backup backup ZPWR configuration backuphistory backup shell history banner display ZPWR banner bannercounts banner with counts bannerlolcat rainbow banner via lolcat bannerno pony banner without ponysay bannerpony banner with ponysay bench benchmark shell startup brc source bashrc c cat / view file cat enhanced cat catcd cat file and cd to its dir catviminfo recent files cat recent files catrecentviminfo cat recent files from viminfo catviminfo cat viminfo file cd enhanced cd cdup cd up one directory cfasd cd via fasd frequency changename rename files interactively changenamezpwr rename ZPWR components cleanall clean everything cleancache clean caches cleancompcache clean completion cache color2 turn on stderr color filter environmentvariables list zpwr env vars (alias: envvars) environmentvariablesall list all env vars (alias: envvarsall) environmentvars list zpwr env vars (alias: envvars) environmentvarsall list all env vars (alias: envvarsall)

... continued. Run zpwr verbs for the complete list.

All Verbs H-S

All 512 Verbs: Forgitdiff Through Recompilefpath (2/3)

The middle of the alphabet is where the real work lives.

Forgitdiff interactive diff via fzf forgitignore browse gitignore templates forgitignoreclean clean gitignore cache forgitignoreget fetch gitignore template forgitignorelist list gitignore templates forgitignoreupdate update gitignore cache forgitinfo repo info dashboard forgitlog interactive git log via fzf forgitreset interactive unstage via fzf forgitrestore interactive restore via fzf forgitstash interactive stash via fzf forgitwarn warn about repo hazards forked manage forked repos forward port forwarding fp fpath info funcrank rank functions by usage fwd forward shortcut gh GitHub CLI integration ghcontribcount GitHub contribution count ghz GitHub + z integration gitaemail set git author email gitcemail set git committer email gitclearcache clear git cache gitclearcommit clear a git commit gitclearfile clear file from git gitcommit enhanced git commit gitcommitcount count commits gitcommits browse commits gitconfig show git config gitcontribcount count contributions gitcontribcountdirs count contribs per dir gitcontribcountlines count contributed lines gitdir show git directory gitedittag edit a git tag gitemail show git email gitforalldir git cmd in all dirs hometests cd to test directory (alias: hometest) loadjenv lazy load jenv logincount count logins by user regenpdf regenerate encyclopedia PDF subcommandsdedit edit subcommand selection subcommandsls list all subcommands.

... continued. Run zpwr verbs for the complete list.

All Verbs T-Z

All 512 Verbs: Refreshzwc Through Zstyle (3/3)

The final stretch. the end of the alphabet. the beginning of mastery.

Refreshzwc refresh compiled wordcode regen regenerate single component regenall regenerate everything regenconfiglinks regenerate config symlinks regenctags regenerate ctags regenenvcache regenerate env cache regengitdirtyrepopcache regen dirty repo cache regengitrepopcache regen git repo cache regengtags regenerate gtags regengtagspygments regen gtags + pygments regengtagstype regen gtags by type regenhistory regenerate history regenkeybindings regen keybindings regenpowerline regenerate powerline regenzsh regenerate zsh config reload reload shell config relpath get relative path rename rename files replacer find and replace replay replay commands repo repository info reset reset shell state restart restart shell restore restore configuration restorehistory restore history backup return2 return to previous dir reveal open repo in browser revealrecurse reveal recursively reverse reverse input rmconfiglinks remove config symlinks rvs reverse shortcut scriptcount count scripts scriptlist list all scripts scriptnew create new script scripts browse scripts scripttopdf convert script to PDF testsall run all env tests (alias: testall) upload upload file with curl verbsedit edit verb selection zpwrCloneToForked clone zpwr to forked dir zpwrgithub open zpwr GitHub page.

Run zpwr verbs for the complete live list.

Chapter 26 – powerlevel10k & Instant Prompt

Instant Prompt: Zero Latency

// your prompt loads before .zshrc finishes. time is a flat circle. //

The single best UX trick in `zpw`: the prompt appears INSTANTLY while `.zshrc` is still loading behind the curtain. Zero perceived latency. The illusion of speed IS speed.

How It Works

On previous shell exit, `p10k` cached the prompt to a file:

```
${XDG_CACHE_HOME:-$HOME/.cache}/p10k-instant-prompt-${(%):-%n}.zsh
```

This file contains the last rendered prompt as raw ANSI escape sequences. On next shell start, it is sourced BEFORE `.zshrc` loads. Result: the prompt appears in <10ms. The user can start typing. `.zshrc` continues loading in the background. Nobody notices.

The Loading Sequence In `.zshrc`

1. `zmodload zsh/datetime` (timestamp)
 2. Source `zpw-hash-dirs.zsh` (cached hash -d entries)
 3. Source `p10k-instant-prompt-*.zsh` (the magic file)
 4. `promptTimestamp=$EPOCHREALTIME` (measure prompt time)
 5. ...rest of `.zshrc` loads (plugins, aliases, etc)...
 6. `p10k` finalize (at very end of `.zshrc`)
- Step 3 must come before ANY console output. If something prints to stdout before the instant prompt, `p10k` aborts it.

The Hash Dir Cache

The prompt uses `%~` to show named dirs like `~ZPWR` instead of `/Users/you/.zpw`. But hash -d entries are set in `zpwBindDirs`, which runs AFTER instant prompt. Chicken-and-egg problem. Solution: `zpwBindDirs` writes a cache file:

```
$ZPWR_LOCAL/zpw-hash-dirs.zsh
```

This cache is sourced at line 73 of `.zshrc`, BEFORE instant prompt, so `%~` resolves `~ZPWR` in the cached prompt correctly.

`zpw_banner_clearlist` Suppression

`zpwBannerClearList` prints a banner + file listing on login. But if it runs before instant prompt finalizes, it corrupts the display. Fix: the banner is deferred until AFTER `p10k` finalize:

```
if [[ -n "$__p9k_instant_prompt_active" && "$ZPWR_BANNER_CLEARLIST" == true ]]; then
  zpwBannerClearList || true
fi
```

The Prompttimestamp Measurement

ZPWR_VARS[promptTimeMs] records how fast the prompt appeared. Run `zpwr environmentcounts` to see it. With instant prompt, this is typically 0.010-0.050 seconds. Without it, 0.5-2.0s.

P10k Finalize

The last line of `.zshrc`:

```
(( ! ${+functions[p10k]} )) || p10k finalize
```

This tells p10k that `.zshrc` is done. The real prompt replaces the cached one. Any deferred output can now safely print.

Powerlevel10k Configuration

// the prompt is your cockpit HUD. configure it or fly blind. //

The p10k config lives at `$ZPWR_ENV/.p10k.zsh` – a 1700+ line file that controls every pixel of your prompt. The wizard generated it, but you own it now.

Left Prompt Segments

These appear on the left side, top to bottom across 4 lines:

```
Line 1: custom_env, custom_env_bat, custom_env_editor
Line 2: custom_env_term, ip
Line 3: context, dir, history, ssh, root_indicator, status, vcs
Line 4: custom_tty, prompt_char
```

The `dir` segment shows your current directory using `%~` expansion. The `vcs` segment shows git branch, dirty status, ahead/behind. The `prompt_char` shows green on success, red on failure.

Right Prompt Segments

The right side is information-dense. Across 3 lines:

```
Line 1: dir_writable, background_jobs, virtualenv, node_version,
```

`go_version, rust_version, java_version, package, os_icon...`

```
Line 2: load, disk_usage, ram, swap, wifi
Line 3: battery, time, command_execution_time, vi_mode, custom_pid
```

The Dir Segment And %~ Expansion

Zsh's `%~` prompt expansion replaces known paths with named dirs. If you hash `-d ZPWR=/Users/you/.zpwr`, then `/Users/you/.zpwr` shows as `~ZPWR` in your prompt. Shorter. Cleaner. Professional. `POWERLEVEL9K_DIR_MAX_LENGTH=80` caps the dir segment width. `POWERLEVEL9K_DIR_MIN_COMMAND_COLUMNS=40` reserves typing space.

How Zpwrbinddirs Populates Named Directories

The function runs `hash -d` for ~20 directories:

```
hash -d ZPWR="$ZPWR"
hash -d ZPWR_TMUX="$ZPWR_TMUX"
hash -d ZPWR_SCRIPTS="$ZPWR_SCRIPTS"
hash -d TMUXH="$TMUX_HOME"
```

Then it writes them all to `$ZPWR_LOCAL/zpwr-hash-dirs.zsh` for instant prompt to use on next startup. The cache iterates `${(kv)nameddirs}` to capture every registered named directory.

The Multiline Frame

The prompt uses box-drawing characters for the frame:

```
First line:  %244F----- (top connector)
Middle:      %244F----- (mid connector)
Last line:   %244F----- (bottom connector)
```

Gap fill character is '—' in grey (color 244). Mode: `nerdfont-complete`. Separators use Powerline glyphs.

Prompt_char Symbols

Insert mode: — Command mode: — Visual: V Overwrite: —

P10k Prompt Customization

// your prompt is a canvas. paint it with ANSI and Unicode. //

ZPWR ships custom p10k segments beyond the defaults. These are defined with `POWERLEVEL9K_CUSTOM_*` variables in `$ZPWR_ENV/.p10k.zsh`.

Custom Segments

Custom_tty Shows `$ZPWR_TTY` (e.g. `/dev/ttys003`) Defined as:

```
POWERLEVEL9K_CUSTOM_TTY='echo "%K{blue}%F{white} $ZPWR_TTY %f%k%f{blue}%f"'
```

Custom_env Environment info (custom shell, OS, etc.) custom_env_bat Shows bat (syntax highlighter) version/status custom_env_editor Shows `$EDITOR` custom_env_term Shows `$TERM_PROGRAM` custom_pid Shows shell PID (right prompt, bottom line)

Adding Your Own Segment

1. Define the command that generates output:

```
typeset -g POWERLEVEL9K_CUSTOM_MYWIDGET='echo "hello"'
```

2. Set colors:

```
typeset -g POWERLEVEL9K_CUSTOM_MYWIDGET_FOREGROUND=255
typeset -g POWERLEVEL9K_CUSTOM_MYWIDGET_BACKGROUND=24
```

3. Add 'custom_mywidget' to LEFT or RIGHT PROMPT_ELEMENTS array. 4. Run p10k reload or source `$ZPWR_ENV/.p10k.zsh` to apply.

Colors And Icons

P10k uses 256-color indices. Print the color map:

```
for i in {0..255}; do print -Pn "%K{$i}  %k%F{$i}${(l:3::0:)i}%f "; done
```

Foreground/background for each segment and state:

```
POWERLEVEL9K_DIR_BACKGROUND=4      (blue)
POWERLEVEL9K_DIR_FOREGROUND=254    (near-white)
```

Anchor dirs (like .git roots) get bold + brighter color (255).

Truncation

POWERLEVEL9K_DIR_MAX_LENGTH=80 caps directory width. POWERLEVEL9K_DIR_MIN_COMMAND_COLUMNS_PCT=50 means at least half the terminal width is reserved for your command input. SHORTEN_STRATEGY can be set to truncate_to_unique for smart shortening (commented out by default in zpwr).

The .p10k.zsh File Structure

The file is a single anonymous function () { ... } that:

- Unsets all POWERLEVEL9K_* vars (clean slate)
- Defines LEFT/RIGHT_PROMPT_ELEMENTS arrays
- Sets mode, icons, colors, truncation per segment
- Configures transient prompt, instant prompt, hot reload

Seeing Prompt Timing

```
zpwr environmentcounts
```

Shows promptTimeMs, startupTimeMs, and per-phase timestamps. This is how you prove your prompt loaded in 0.015 seconds.

Transient Prompt & Visual Tweaks

// old prompts fade into ghosts. only the present matters. //

Transient prompt collapses previous prompts to a minimal form, keeping your scrollback clean and focused. In zpwr it is currently set to 'off' but easy to enable.

Transient Prompt

When enabled, after you press Enter, the full multi-line prompt collapses to just the prompt_char symbol (— or —). All segments, git status, directory – gone from old lines. Only the current prompt shows full detail.

```
typeset -g POWERLEVEL9K_TRANSIENT_PROMPT=off
```

Change to always or same-dir to enable. 'same-dir' only collapses when you stay in the same directory.

Hot Reload

Edit .p10k.zsh and apply changes without restarting zsh:

```
p10k reload
```

This re-sources .p10k.zsh and rebuilds the prompt in-place. No exec zsh needed. No losing your command history buffer.

P10k Configure

The interactive configuration wizard. Walks you through: - Font detection (powerline glyphs, nerdfont icons) - Style selection (rainbow, lean, classic, pure) - Separator shapes, line count, frame options - Instant prompt mode (verbose, quiet, off) It generates a fresh .p10k.zsh. ZPWR ships a pre-configured one in `$ZPWR_ENV/.p10k.zsh` (rainbow style, nerdfont-complete). Running the wizard overwrites it, so back up yours first.

Instant Prompt Vs ZpwrClearList

The banner (zpwrClearList) prints colorized file listings on login. Instant prompt redirects all stdout/stderr during init to a buffer. If zpwrClearList runs during this window, the output gets swallowed or garbled. ZPWR's fix: 1. Check if `__p9k_instant_prompt_active` is set 2. If so, defer zpwrClearList to AFTER p10k finalize 3. The banner appears cleanly after the prompt settles.

The eza -classify=always Fix

Under instant prompt, fd/stdout gets redirected. eza's `-classify` flag (append `*/` to dirs) auto-detects terminal capabilities. When stdout is redirected, it thinks there's no terminal and drops the indicators. Fix: use `-classify=always` to force classification regardless of fd state. ZPWR_EXA_COMMAND uses this:

```
command eza --git -il --classify=always -H --color-scale -g -a
```

\$TTY Immune To fd Redirects

Zsh sets \$TTY before rc files load. Instant prompt redirects fds 0/1/2, but \$TTY still points to the real terminal. ZPWR captures it: `export ZPWR_TTY=$TTY` This is used by the custom_tty prompt segment.

Chapter 27 – zinit & Plugin System

Zinit: The Plugin Engine

// the package manager for your shell. apt-get for zsh plugins. //

Zinit (formerly zplugin) is a flexible zsh plugin manager with turbo mode, ice modifiers, and completion management. ZPWR uses it as the default: `ZPWR_PLUGIN_MANAGER=zinit`.

What zinit Does

- Downloads GitHub plugins to `$ZPWR_PLUGIN_MANAGER_HOME` - Sources them into your shell (or loads as completions) - Manages load order with turbo mode (deferred loading) - Handles OMZ snippets (individual files from oh-my-zsh) - Compiles plugins to .zwc bytecode for speed

zinit Load Vs zinit Snippet

zinit load user/repo Clone full GitHub repo, source .plugin.zsh zinit snippet OMZP::git Download single file from OMZ plugin zinit snippet OMZL::git.zsh Download single OMZ lib file load = full repo clone. snippet = single file download. ZPWR uses both: load for GitHub plugins, snippet for OMZ.

The Plugin Arrays

ZPWR organizes plugins into arrays in .zshrc: `ZPWR_GH_PLUGINS` 28+ GitHub repos (fzf-tab, zsh-z, forgit...) `ZPWR_OMZ_PLUGINS` 25+ OMZ snippets (git, python, golang...) `ZPWR_OMZ_LIBS` 4 OMZ lib files (git.zsh, directories.zsh...) `ZPWR_OMZ_COMPS` 12 OMZ completion files (ng, coffee, scala...) Conditional plugins are appended if the command exists:

```
zpwrCommandExists docker && ZPWR_GH_PLUGINS+=( zsh-docker-aliases )
```

Plugin Storage

Everything lives under `$ZPWR_PLUGIN_MANAGER_HOME`:

```
$ZPWR_PLUGIN_MANAGER_HOME/bin/      zinit itself
$ZPWR_PLUGIN_MANAGER_HOME/plugins/   cloned repos
$ZPWR_PLUGIN_MANAGER_HOME/snippets/  OMZ snippets
$ZPWR_PLUGIN_MANAGER_HOME/completions/ symlinked completions
```

The 48+ Plugin Roster

Total plugins managed by zpwr (from .zshplugins): MenkeTechnologies forks: fzf-tab, forgit, zsh-expand, zsh-autocomplete, zsh-z, fasd-simple, revolver, zunit... zdharma-continuum: fast-syntax-highlighting, zbrowse, zui... zsh-users: completions, autosuggestions, history-substring Plus: hlissner/zsh-autopair, bigH/git-fuzzy, and more.

First Run Bootstrap

If `$ZPWR_PLUGIN_MANAGER_HOME/bin` doesn't exist, `.zshrc` auto-clones zinit from GitHub. After that, `OPTIMIZE_OUT_DISK_ACCESSES=1` skips unnecessary `stat()` calls on subsequent starts.

Turbo Mode: Deferred Loading

// why load 48 plugins at startup when you can load 1? //

Turbo mode is zinit's killer feature: plugins load AFTER the prompt appears, using zsh's sched mechanism. Your shell is interactive instantly; plugins trickle in behind the scenes.

The Wait Ice Modifier

The 'wait' ice defers loading until after the first prompt:

```
zinit ice wait          Load after prompt (default priority)
zinit ice wait'0'       Same as wait (priority 0)
zinit ice wait'0a'      Priority 0, sub-order a (loads first)
zinit ice wait'0b'      Priority 0, sub-order b (loads second)
zinit ice wait'0e'      Priority 0, sub-order e (loads later)
```

The letter suffix controls load order WITHIN the same priority. a loads before b loads before c, etc. This is how ZPWR orchestrates 48 plugins into a precise loading sequence.

The Graduated Loading Sequence

Synchronous: `powerlevel10k` (must load before prompt) wait: OMZ completions, libs, plugins, GH plugins wait'0': `zsh-autopair` (needs ZLE ready) wait'0a': `zsh-expand` + late aliases + alias cache wait'0b': `zsh-autocomplete` (if `ZPWR_AUTO_COMPLETE=true`) wait'0c': `zsh-history-substring-search` wait'0d': `zsh-autosuggestions` + FZF late bindings + verbs wait'0e': `zsh-zinit-final` (penultimate, final keybindings) wait'0f': `zsh-more-completions` (low priority, last resort) wait'\${ZPWR_ZINIT_COMPINIT_DELAY}g': `compinit` + `cdreplay` wait'\${ZPWR_ZINIT_COMPINIT_DELAY}h': fast-syntax-highlighting.

Why Startup Is Fast

Only ONE plugin loads synchronously: `powerlevel10k`. Everything else is turbo-deferred. Combined with instant prompt, you see the prompt in ~15ms. The other 47 plugins load in the next ~200ms while you're still thinking.

Atinit And Atload Hooks

These run code at precise moments during plugin loading: `atinit` Runs BEFORE the plugin is sourced `atload` Runs AFTER the plugin is sourced ZPWR uses these extensively to bind keymaps and aliases:

```
zinit ice wait'0a' atload'zpwBindAliasesLate; zpwCreateAliasCache'
```

The `atload` fires after `zsh-expand` is sourced, then late aliases override any OMZ defaults. Precise surgical timing.

Zpwr_zinit_compinit_delay

Default: 0. Controls how long to wait before running `compinit`. Higher values defer completion system init even further. Set in `$ZPWR_ENV/.zpwr_env.sh`. The 'g' and 'h' suffixes on the wait ice ensure `compinit` and syntax highlighting load last.

Ice Modifiers Deep Dive

// ice modifiers are the spice of zinit. season generously. //

Every zinit load/snippet can be preceded by 'zinit ice' with modifiers that control HOW the plugin loads. Ice melts after one use – it applies only to the next command.

Core Ice Modifiers Used By zpwr

Lucid Suppress the 'Loaded plugin' message ZPWR uses this on every plugin. No spam. nocompile Skip .zwc compilation of the plugin Useful when zpwrRecompileFiles handles it globally. nocd Don't cd to plugin dir before sourcing Prevents p10k internals from polluting named dirs. nocompletions Don't install completions from this plugin Used for zsh-more-completions (fpath-only approach). as'completion' Load the file as a completion, not a plugin Used for OMZ completion snippets like _ng, _coffee. as'program' Add the pick'd file to \$PATH as executable Used for fzf binary and git-fuzzy. as'null' Don't source anything – just run hooks Used for the compinit phase (atinit only). pick'null' Don't source any file from the plugin dir Used with as'completion' for OMZ comp snippets. pick'bin/fzf' Source or add this specific file With as'program', adds bin/fzf to PATH.

Hook Ice Modifiers

Atinit Code to run BEFORE the plugin sources atload Code to run AFTER the plugin sources Example from ZPWR:

```
zinit ice lucid nocompile wait atinit='zpwrBindOverrideOMZ;zpwrBindForGit'
zinit load MenkeTechnologies/forgit
```

Before forgit loads, zpwrBindOverrideOMZ runs to clear OMZ aliases that would conflict with forgit's git shortcuts.

How zpwr Uses Ice By Category

OMZ completions: lucid nocompile as'completion' pick'null' wait OMZ libs: lucid nocompile wait atload='zpwrOmzOverrides' OMZ plugins: lucid nocompile wait GH plugins: lucid nocompile wait Programs: as'program' lucid nocompile pick'bin/fzf' wait Syntax highlight:lucid nocompile wait"\${ZPWR_ZINIT_COMPINIT_DELAY}h"

Ice Stacking

Multiple ices combine. Order doesn't matter (mostly). The = syntax for atload/atinit works with single quotes:

```
atload='zpwrBindAliasesLate; zpwrCreateAliasCache'
```

Or with quoted strings:

```
atinit'zpwrBindZdharma' atload'zpwrBindZdharmaPost'
```

Zinit Completions & Compinit

// compinit is the most expensive call in zsh startup. defer it. //

The completion system (compsys) needs compinit to initialize. But compinit scans all fpath entries and parses completion files. On a system with many registered completions, this is slow. ZPWR defers it behind turbo mode.

zinit Compinit Options

```
ZINIT[COMPINIT_OPTS]='-C -u'
```

-C skips security checks (don't re-verify file ownership). -u suppresses warnings about insecure directories. These flags make compinit fast but trust your fpath.

```
ZINIT[ZCOMPDUMP_PATH]="$ZSH_COMPDUMP"
```

Points compinit to zpwr's zcompdump location.

The Deferred Compinit

Compinit runs in the LAST turbo phase:

```
zinit ice lucid nocompile nocd as'null'  
wait"${ZPWR_ZINIT_COMPINIT_DELAY}g"  
atinit'zicompinit; zicdreplay; zpwrBindOverrideOMZCompdefs'
```

Zicompinit: runs compinit with the configured opts. zicdreplay: replays all compdef calls that were recorded while compinit wasn't loaded yet. Plugins that called compdef during turbo load had their calls queued – now they fire.

The Omz Completion Symlink Hack

OMZ completion snippets land in:

```
$ZSH/snippets/OMZP::coffee/_coffee
```

But compinit needs them in the completions dir. ZPWR symlinks them using zsh/files builtin:

```
zmodload -F zsh/files b:zf_ln  
zf_ln -sfm $ZSH/snippets/OMZP::${p%/*}/... $ZSH/completions/...
```

Zf_ln is a builtin ln(1), no fork needed. Fast.

Zpwrstalezcompdump

The zcompdump cache gets stale when plugins update. zpwrStaleZcompdump checks the cache age. If it is older than ~1 week, it triggers a full compinit rebuild. This runs automatically every shell startup (cheap check).

Force Rebuild

```
zpwr regenzzsh
```

Nukes the zcompdump, re-runs compinit from scratch, and recompiles everything. Use when completions go missing or after adding new completion files to fpath.

Zpwr_zinit_compinit_delay

Default: 0. Set in `$ZPWR_ENV/.zpwr_env.sh`. Controls the numeric prefix of the wait ice for compinit. 0 = load immediately after prompt. Higher = more delay. On fast machines, 0 is fine. On slow machines, 1 or 2 lets other plugins finish first.

Plugin Troubleshooting

// when plugins misbehave, you need diagnostic tools. //

Zinit ships with built-in debugging commands. When something breaks, these are your first responders.

Diagnostic Commands

`zinit report <plugin>` Show load status, errors, files.

```
zinit report zsh-users/zsh-autosuggestions
```

Shows: source file, ice modifiers used, compdef calls, functions defined, aliases created, PATH changes.
`zinit times` Show plugin load times Sorted by load time. Find the slowest plugin. If something takes >50ms, investigate.
`zinit loaded` List all loaded plugins
`zinit unload <plugin>` Unload a plugin from current session
Useful for debugging conflicts. Does not persist.
`zinit list` List all registered plugins
`zinit cd <plugin>` cd into plugin directory.

Common Issues

Plugin not loading? - Check if 'wait' ice is set (turbo mode defers loading) - Run `zinit report` to see if it errored silently - The 'lucid' ice suppresses messages – remove it to debug
Completion missing after plugin install? - Run `zpwr regenzzsh` to rebuild `zcompdump` - Check `fpath`: `print -l $fpath | grep <plugin>` - Ensure the plugin uses `as'completion'` or adds to `fpath`
Keybinding conflicts? - Load order matters. Plugins loaded later override earlier ones. - ZPWR uses `wait'0a'` through `wait'0e'` to control this. - `zpwrBindOverrideZLE` fires in the `0a` phase to win conflicts.

Adding Custom Plugins

Add to `ZPWR_GH_PLUGINS` in `$ZPWR_LOCAL/.tokens.sh`:

```
ZPWR_GH_PLUGINS+=( your-user/your-plugin )
```

The `.tokens.sh` file is sourced before plugin loading starts (via `zpwrTokenPre`), so your additions join the array in time. For conditional loading:

```
zpwrCommandExists myapp && ZPWR_GH_PLUGINS+=( user/zsh-myapp )
```

Updating Plugins

```
zpwr updatezinit
```

Runs `zinit update --all` to pull latest from all repos. After updating, run `zpwr regenzzsh` to rebuild completions.

Nuclear Option

If `zinit` is truly broken, nuke and rebuild:

```
rm -rf $ZPWR_PLUGIN_MANAGER_HOME
```

Next shell start auto-clones `zinit` and re-downloads everything. Slow but thorough. The cockroach approach to debugging.

The Plugin Ecosystem

// 30+ custom plugins from MenkeTechnologies //

ZPWR loads approximately 95 plugins via zinit. Over 30 are custom MenkeTechnologies creations that extend zpwrr with additional verbs, aliases, completions, and integrations.

Key Plugins

Zsh-learn 60 verbs, MySQL learning DB zsh-git-repo-cache 20 verbs, filesystem repo index fzf-zsh-plugin 14 verbs, brew/chrome fzf zsh-git-acp 318 aliases, git workflows zsh-docker-aliases 148 aliases, Docker shortcuts zsh-openshift-aliases 106 aliases, OpenShift zsh-expand spell correct, abbreviation expand zsh-more-completions many thousands of tab completions zsh-cargo-completion 32 Rust/Cargo aliases zsh-travis 8 functions, CI integration zsh-nginx nginx management forgit fzf-powered git (add, diff, log) zsh-z frequency directory jumping fzf-tab fzf-powered tab completion zconvey cross-session communication.

Conditional Loading

Plugins for docker, dotnet, kubectl, ngrok, rails, and systemctl only load if those commands exist. No bloat on machines without those tools.

Deferred Loading

All plugins load with zinit wait'' ice — deferred after the prompt appears. Only powerlevel10k loads synchronously for instant prompt.

zsh-sudo: Privilege Escalation

Toggle sudo on the current command line with one keybind.

The Keybinding

Ctrl-S (or Escape Escape in some configs)

How It Works

```
sudo not on the line? .... it gets prepended
sudo already there? ..... it gets stripped
empty line? ..... pulls last command from history with sudo
```

What It Strips

When removing sudo, it also strips: builtin, command, env, and all their arguments. So sudo -E env PATH=... command foo becomes just foo.

Example

You type: vim /etc/hosts Hit Ctrl-S: sudo vim /etc/hosts Hit Ctrl-S again: vim /etc/hosts

Empty line + Ctrl-S: pulls your last command back with sudo prepended. No retyping. No arrow keys.

Plugin: MenkeTechnologies/zsh-sudo.

zsh-sed-sub: Inline Search & Replace

Global search and replace on the current command line.

The Keybinding

Ctrl-F Ctrl-P in both viins and vicmd modes.

How It Works

1. Type a command on the line
2. Hit Ctrl-F Ctrl-P
3. Enter the search pattern
4. Enter the replacement
5. All occurrences on the line are replaced

Example

You type: `cp file.txt /old/path/ && mv file.txt /old/path/bak` Hit Ctrl-F Ctrl-P, search: `old`, replace: `new`
Result: `cp file.txt /new/path/ && mv file.txt /new/path/bak`

Faster than arrow keys. Works on the entire line. Like sed but for your command line buffer.

Plugin: MenkeTechnologies/zsh-sed-sub.

gh_reveal: Open Repo in Browser

Quickly open the current git project in your browser.

The Command

```
zplr reveal          # open current repo on GitHub
```

How It Works

Reads the git remote URL from the current repo, converts it to an HTTPS URL, and opens it in your default browser. Works with GitHub, GitLab, Bitbucket, and any git remote.

Use Cases

- Check the PR page for the branch you are on - View the README without cat-ing it locally - Jump to Issues or Actions from the terminal - Share a repo link with a coworker fast

Also accessible as `zplr revealrecurse` to search up the directory tree for a git repo.

Plugin: MenkeTechnologies/gh_reveal.

Colorful Manuals & Package Completions

The smaller plugins that make everything nicer.

Zsh-very-colorful-manuals

Custom colorscheme for man pages. Headers in bold cyan, underlines in magenta, flags in green. Makes man pages actually readable instead of a wall of white text. Works automatically — no commands needed.

Zsh-gem-completion

Enhanced Ruby gem completion. Includes all OMZ gem completion plus remote gem search:

```
gem install <tab>          # completes remote gems
```

Results come from gem search output.

Zsh-pip-description-completion

Enhanced pip completion. All OMZ pip completion plus remote package search:

```
pip install <tab>          # completes remote packages
```

Results come from pip search output with descriptions.

Zsh-better-npm-completion

Better npm completion. Context-aware:

```
npm install <tab>          # completes package names
npm run <tab>              # completes scripts from package.json
npm uninstall <tab>        # completes installed packages
```

Each subcommand gets the right completions.

All plugins: MenkeTechnologies/*

Specialty Completions & Aliases

Platform-specific plugins loaded conditionally.

Zsh-cpan-completion

Tab completion for Perl CPAN modules.

```
cpan install <tab>         # complete module names
```

Zsh-dotnet-completion

Tab completion for .NET CLI (dotnet).

```
dotnet <tab>               # complete subcommands
dotnet add package <tab>   # complete packages
```

Loaded conditionally when dotnet is available.

Zsh-xcode-completions

Tab completion for Xcode CLI tools on macOS.

```
xcodebuild <tab>      # complete build options
xcrun <tab>           # complete SDK tools
```

MacOS only — loaded when Xcode is detected.

Kubectl-aliases

800+ aliases for kubectl. Every common operation is a short alias:

```
kgp  = kubectl get pods
kgs  = kubectl get services
kd   = kubectl describe
kl   = kubectl logs
```

Loaded conditionally when kubectl is available.

Jhipster-oh-my-zsh-plugin

Aliases and completions for JHipster (Java/Spring Boot scaffold generator).

```
jh    = jhipster
```

Loaded conditionally when jhipster is available.

All plugins: MenkeTechnologies/* Conditional loading means zero overhead if the tool isn't installed on your system.

Chapter 28 – zsh Internals

Autoloading: Lazy Function Loading

// 443 functions. zero parsing until you call one. //

Autoloading is zsh's lazy-loading mechanism. Register a name, and zsh only reads the function body from disk on first call. This is why ZPWR can have hundreds of autoloaded functions with negligible startup cost.

How Autoload -z Works

1. `autoload -z funcname` registers 'funcname' as autoloadable.
2. Zsh records the name but does NOT read the file yet.
3. On first call to `funcname`, zsh searches `$fpath` for a file named 'funcname' (exact match, no extension).
4. The file is sourced. The function is now defined in memory.
5. The function executes with the original arguments.
6. Subsequent calls use the in-memory version. No more disk.

The Glob In `.zshrc`

```
builtin autoload -z $ZPWR_AUTOLOAD_COMMON/*(:t)
```

The glob `*(:t)` means: * All files in the directory `(.)` Qualifier: regular files only (not dirs or symlinks) `:t` Modifier: tail only (strip directory, keep filename) So it registers every regular file's name as a function. Same pattern runs for `ZPWR_AUTOLOAD_DARWIN` or `ZPWR_AUTOLOAD_LINUX`.

The Fpath

Fpath is the function search path (like `PATH` but for functions):

```
fpath=( $ZPWR_AUTOLOAD_COMMON $ZPWR_AUTOLOAD_COMP_UTILS $ZPWR_COMPS $fpath )
```

Order matters: first match wins. ZPWR dirs come first so they can override system completions if needed. `fpath` is NOT exported (typeset `+x FPATH`) – child shells don't inherit it.

The Function File Format

Each file in the autoload dir contains one function. The file is named exactly like the function. Inside:

```
function zpwSomething() {  
  # function body  
}  
zpwSomething "$@"
```

The last line calls the function with args passed through. This is the ZPWR convention. The function wraps itself.

Why Autoloading Is Fast

443 function registrations = 443 hash table entries. Cost: microseconds. No file I/O, no parsing, no execution. Compare to sourcing 443 files: hundreds of milliseconds. Autoloading turns $O(n)$ startup into $O(1)$ with lazy $O(1)$ per call.

Autoload -Uz

-U suppresses alias expansion during loading (safety). -z forces zsh-style function loading (vs ksh-style). ZPWR uses -z for its functions, -Uz for system utilities like zrecompile, zmv, zargs, and compinit.

ZLE: The Zsh Line Editor

// the engine behind every keystroke. readline on steroids. //

ZLE (Zsh Line Editor) is the subsystem that handles your command line input. Every key press triggers a ZLE widget. ZPWR rewires dozens of these widgets for custom behavior.

Widgets: Named Editor Actions

A widget is a named action that ZLE can execute:

```
.accept-line      Built-in: execute the current line
.backward-delete-char Built-in: backspace
.self-insert      Built-in: insert the typed character
```

The dot prefix means 'built-in widget'. User-defined widgets can override them. ZPWR defines custom widgets like:

```
zpwrMagicEnter      Custom Enter key behavior
zpwrExpandTerminateSpace Custom Space key behavior
zpwrAcceptLine      Custom line acceptance
```

Bindkey: Mapping Keys To Widgets

Bindkey connects key sequences to widgets:

```
bindkey '^M' zpwrMagicEnter      Enter key
bindkey ' ' zpwrExpandTerminateSpace Space key
bindkey -v          Switch to vi mode
bindkey -e          Switch to emacs mode
```

ZPWR_BINDKEY_VI controls which mode: true=vi, false=emacs.

How Zpwrmagicenter Works

On empty line (just pressing Enter): - If in a git dir: runs git status -u . - If not: runs ls -lh . - Resets the prompt via `_p9k_precmd_impl` + zle reset-prompt On non-empty line: delegates to zle accept-line (zpwrAcceptLine).

How Zpwracceptline Works

The accept-line replacement does serious work: 1. Updates `zconvey` name with current command + TTY + PID 2. Detects commands that modify files (rm, mv, cp, mkdir...) and sets `ZPWR_WILL_CLEAR=true` for post-exec ls refresh 3. Handles sudo + grc colorization for aliased commands 4. Prevents global alias expansion in first position 5. Optionally expands aliases before execution 6. Calls .accept-line (the real built-in)

The Ctrl-f Chord Prefix System

ZPWR binds Ctrl-F as a prefix key for multi-key chords:

```
Ctrl-F Ctrl-D    FZF file search
Ctrl-F Ctrl-I    FZF word search (ag/grep)
Ctrl-F Ctrl-G    FZF git operations
```

This gives you an entire second keymap layer without conflicting with normal editing keys. Like tmux prefix but for your command line.

Hook Functions: precmd, preexec, chpwd

// zsh calls your code at key moments. event-driven shell. //

Zsh provides hook points where you can inject code that runs automatically before prompts, before commands, and when directories change. ZPWR uses all three.

Precmd: Before Each Prompt

Runs after a command finishes, right before the prompt draws. p10k's `_p9k_precmd` is the main user – it updates git status, execution time, and every prompt segment. ZPWR adds `zpwrPrecmd` to the hook:

```
function zpwrPrecmd(){ export ZPWR_OPTS="$-" }
```

This captures the current shell options before each prompt.

Preexec: Before Each Command

Runs after Enter but BEFORE the command executes. Receives the command string as \$1. ZPWR's `zpwrPreexec` is minimal (a placeholder hook). p10k uses `preexec` to record the start timestamp for `command_execution_time` segment.

Chpwd: When Directory Changes

Runs whenever `$PWD` changes (`cd`, `pushd`, `popd`, `auto_cd`). ZPWR's `zpwrChpwd` hook handles directory-change actions.

The _functions Arrays

Zsh supports multiple hooks via arrays:

```
precmd_functions+=( myHook )    Add a precmd hook
preexec_functions+=( myHook )   Add a preexec hook
chpwd_functions+=( myHook )     Add a chpwd hook
```

Every function in the array runs at the hook point. Order matters: first in array = first to execute.

How zpwr Registers Hooks

`ZpwrBindPrecmd` (runs during p10k atload):

```
precmd_functions=( zpwrPrecmd ${(@)precmd_functions:#zpwrPrecmd} )
```

This puts `zpwrPrecmd` FIRST, removing any duplicate. The `${(@)array:#pattern}` syntax removes matching elements. `zpwrBindPreexecChpwd` (runs during syntax-highlighting atload):

```
preexec_functions=( ${(@)preexec_functions:#zpwrPreexec} zpwrPreexec )
chpwd_functions=( ${(@)chpwd_functions:#zpwrChpwd} zpwrChpwd )
```

These put zpwr hooks LAST (after p10k and other plugins).

The Hook Count In zpwr Top

The zpwr top dashboard shows the total hook count:

```
nhooks=$(( ${#precmd_functions} + ${#preexec_functions} + ${#chpwd_functions} ))
```

Typical value: 5-8 hooks total across all three arrays. If this number grows unexpectedly, a plugin is adding hooks you may not want. Check with: `print -l $precmd_functions`.

Emulate & Options

// zsh has 200+ options. emulate -L zsh resets them all locally. //

Zsh options control fundamental behavior: globbing, word splitting, quoting, history. ZPWR functions use `emulate -L zsh` to guarantee a known environment regardless of user settings.

Emulate -L zsh

```
builtin emulate -L zsh
```

Resets ALL options to zsh defaults for the current function scope. `-L` means local: options revert when the function returns. Without this, a function might inherit `noglob` from the caller and break globbing, or inherit `shwordsplit` and break arrays. ZPWR functions start with this to be immune to the caller's state.

Key Options In zpwr

extendedglob `##` = one-or-more, `(#i)` = case-insensitive glob `^pattern` = negation. Essential for ZPWR globs. `glob_dots` Dot files matched by `*` (no need for `.`) `globstarshort` `**c = **/*.c` (recursive glob shorthand) `bracecl` `{abcd0-9}` expands as character class `rc_quotes` " inside single quotes = literal single quote `rc_expand_param` Array expansion includes prefix: `xx${arr}` = `xxA xxB` `nocaseglob` Globs are case-insensitive globally `numeric_glob_sort` `file1 file2 file10` sort numerically `prompt_subst` Allow `$(...)` and `${...}` in prompt strings `transient_prompt` Right prompt only on current line

The Noshwordsplit Default

Bash splits unquoted variables on whitespace by default. Zsh does NOT (`noshwordsplit`). This means:

```
x="hello world"; print $x -> one argument in zsh, two in bash
```

If a function inherits `shwordsplit` (e.g., from `emulate sh`), arrays and parameter expansions break silently. Another reason for `emulate -L zsh`.

The Local-in-loop Bug

In zsh, 'local' inside a loop prints the variable value as a side effect when the variable already exists:

```
for i in 1 2 3; do local x=$i; done # prints x=1 x=2 x=3
```

This is because 'local' on an existing local acts like `typeset`, which prints. Declare locals BEFORE loops, not inside them.

Auto_name_dirs: Removed

This option auto-registers any parameter set to a directory path as a named directory. Sounds nice, but p10k/gitstatus set internal variables to paths, polluting the named dir table. ZPWR removed it. Explicit hash -d in zpwrBindDirs handles it. The comment in .zshrc: # auto_name_dirs removed: pollutes named # dirs with p10k/gitstatus internals.

Parameter Expansion Magic

// zsh parameter expansion is a programming language in itself. //

Zsh's \${...} syntax can do transformations that would require sed, awk, basename, dirname, tr, and cut in bash. No forks. No subshells. Pure in-process string manipulation.

Parameter Expansion Flags (the Parenthesized Letters)

\${(K)assoc} Keys of associative array \${(v)assoc} Values of associative array \${(kv)assoc} Key-value pairs interleaved \${(s/.)var} Split string on / into array \${(j:.)array} Join array elements with , \${(L)var} Lowercase the entire string \${(U)var} Uppercase the entire string \${(f)var} Split on newlines (lines to array) \${(F)array} Join with newlines (array to lines) \${(t)var} Type of variable (scalar, array, etc.) \${(q)var} Quote the value for re-use in eval \${(Q)var} Remove one level of quoting \${(z)var} Split into words like the shell parser \${(o)array} Sort ascending \${(O)array} Sort descending.

Modifiers (the Colon Letters)

\${Var:t} Tail: basename (/a/b/c.txt -> c.txt) \${var:h} Head: dirname (/a/b/c.txt -> /a/b) \${var:r} Root: remove extension (file.txt -> file) \${var:e} Extension: (file.txt -> txt) \${var:A} Absolute path (resolve symlinks) \${var:l} Lowercase (zsh 5.0+) \${var:u} Uppercase (zsh 5.0+)

Substitution And Pattern Matching

\${var//pat/rep} Global substitution

\${Var/pat/rep} First match substitution \${var#pat} Remove shortest prefix match \${var##pat} Remove longest prefix match \${var%pat} Remove shortest suffix match \${var%%pat} Remove longest suffix match.

zpwr Examples

From zpwrBindDirs (writing hash dir cache):

```
print -r "hash -d ${k}=${(q)v}" -- (q) quotes the value safely
```

From zpwrAcceptLine (parsing command buffer):

```
mywords=( ${ (z)cmdstr} )      -- (z) shell-word splits
cmd=${mywords[1]#=}           -- strip leading = from =cmd
```

From zpwrBindPrecmd (removing duplicates from array):

```
${(@)precmd_functions:#zpwrPrecmd} -- remove matching element
```

These are not academic exercises. They replace forks.

The .zwc Compilation System

// bytecode for your shell. because even scripts deserve a compiler. //

Zsh can compile scripts to .zwc (Zsh Word Code) bytecode. These files skip the parsing phase on load, going straight to execution. ZPWR compiles 50+ files for speed.

What .zwc Files Are

A .zwc file is a binary representation of parsed zsh code. When zsh sources a .zsh file, it checks for a .zwc sibling. If the .zwc exists and is newer than the source, zsh loads the bytecode directly. No lexing, no parsing. Speedup: 2-5x for large files. Marginal for tiny ones.

Zrecompile

The zrecompile utility compiles only if the source is newer:

```
autoload -Uz zrecompile
zrecompile -p -U $ZPWR_ENV_FILE
```

-p means 'check pairs' (source vs .zwc timestamps). -U suppresses alias expansion during compilation. If the .zwc is current, zrecompile is a no-op.

Zpwrrecompilefiles: What Gets Compiled

The function compiles two categories of files: Local files (~47): ~/.zshrc, ~/.zshenv, ~/.zlogout, ~/.zlogin p10k-instant-prompt*.zsh, p10k-dump*.zsh \$ZSH_COMPDUMP, \$ZPWR_ALIAS_FILE, \$ZPWR_PROMPT_FILE \$ZPWR_LOCAL/tokens.sh, \$ZPWR_ENV_FILE, \$ZPWR_RE_ENV_FILE All .zsh/.sh in \$ZPWR_ENV/, all .zsh in \$ZPWR_SCRIPTS/ All plugin .zsh files under \$ZPWR_PLUGIN_MANAGER_HOME/bin/ OMZ lib, plugin, theme, and custom files Global files (~8): /etc/profile, /etc/zshrc, /etc/zshenv, /etc/zprofile, etc. These need sudo (compiled with sudo zsh -c zrecompile).

zpwr Verbs For Compilation

zpwr recompile	Compile all known files (zpwrRecompileFiles)
zpwr decompile	Remove .zwc files (zpwrUncompile)
zpwr refreshzwc	Remove + recompile (clean rebuild)

The Zsh/files Module

Zsh can load builtin file operations via zmodload:

```
zmodload -F zsh/files b:zf_ln b:zf_rm b:zf_mkdir
```

These are shell builtins that replace ln, rm, mkdir. No fork, no exec – pure kernel syscalls from the shell process. ZPWR uses zf_ln for the OMZ completion symlink hack. In a loop creating 12 symlinks, this saves 12 fork+exec pairs.

Other Useful Modules

zsh/datetime	\$EPOCHREALTIME, \$EPOCHSECONDS
zsh/compllist	Menu-select completion mode
zsh/zprof	Profiler (ZPWR_PROFILING=true enables it)

Modules are loaded with: `zmodload zsh/datetime`.

Chapter 29 – fzf Architecture

FZF: The Neural Interface

// the universal adapter between data and decisions. //

fzf (fuzzy finder) is a general-purpose command-line filter. Pipe anything into it, fuzzy-search interactively, get results. ZPWR wraps fzf into dozens of workflows: files, words, git, verbs.

The Pattern: Pipe | fzf | Action

Every fzf integration follows the same architecture:

```
<data source> | fzf [options] | <action on selection>
```

The data source generates lines. fzf presents them. The action consumes the selected line(s). Simple. Composable. Powerful.

Fzf_default_opts

ZPWR sets global fzf defaults in zpwrBindFZFLate:

```
FZF_DEFAULT_OPTS="$ZPWR_COMMON_FZF_ELEM --reverse --border --height 100%"
```

Plus a Solarized Dark color scheme layered on top:

```
--color fg:-1,bg:-1,hl:$blue,fg+:$base2,bg+:$base02,hl+:$blue
```

ZPWR_COMMON_FZF_ELEM adds the logo prompt and navigation binds:

```
--prompt='$ZPWR_FZF_LOGO ' --bind=ctrl-n:page-down,...
```

The Preview Window

fzf's `--preview` flag runs a command for each highlighted item:

```
fzf --preview 'bat --color=always {}'
```

ZPWR configures rich previews per context: Files: bat with syntax highlighting, line numbers, grid Dirs: stat output Packages: dpkg -l or rpm -qi Git: diff preview, commit log If bat is installed, it's the default colorizer. Falls back to pygmentize with terminal256 output.

Fzf-completion (Tab)

fzf replaces the default Tab completion with a fuzzy finder. Type a command, press Tab, and fzf opens with completions:

```
cd *<Tab>      fzf through subdirectories
kill <Tab>     fzf through running processes
ssh *<Tab>     fzf through known hosts
```

FZF_COMPLETION_OPTS controls the preview for these.

Fzf-tab Plugin

MenkeTechnologies/fzf-tab replaces zsh's menu completion with fzf. Any time the completion system would show a menu, fzf-tab intercepts it and shows fzf instead. This means: - Fuzzy matching for every completion, not just ** triggers - Previews for file completions, git branches, everything - FZF_TAB_OPTS configures the behavior (ansi, nth, delimiter) - FZF_TAB_COMMAND sets which fzf binary to use.

Global Aliases For fzf

```
${ZPWR_GLOBAL_ALIAS_PREFIX}z  Pipe into fzf: ls | ,,z
${ZPWR_GLOBAL_ALIAS_PREFIX}zb Inline fzf selection: vim ,,zb
```

FZF in Practice

// the theory is simple. the practice is where it gets good. //

ZPWR ships dozens of fzf-powered workflows. Each follows the generate | fzf | action pattern. Here are the heaviest hitters.

File Search (zpwr Filesearch / Ctrl-f Ctrl-d)

Pattern: find files | fzf --preview 'bat' | open in editor 1. find/fd generates a file list (respecting .gitignore) 2. fzf shows files with bat-powered syntax-highlighted preview 3. Selected file opens in \$EDITOR at the matched location FZF_CTRL_T_OPTS configures the preview command.

Word Search (zpwr Wordsearch / Ctrl-f Ctrl-i)

Pattern: ag/rg search | fzf --preview 'context' | open at line 1. ag (silver searcher) or rg searches file contents 2. fzf shows matches with file:line:content format 3. Selection opens the file at the exact line number FZF_AG_OPTS: delimiter ': ', match on 3rd+ field (skip file:line).

Git Add (forgitadd)

Pattern: git diff --stat | fzf --preview 'git diff' | git add 1. Lists modified files with diff stats 2. Preview pane shows the actual diff for each file 3. Toggle files with Tab, confirm to stage them Part of forgit: the git + fzf integration plugin.

Verb Search (zpwr Verbsfzf)

Pattern: ZPWR_VERBS keys | fzf --preview 'help' | eval 1. All 512+ zpwr verbs piped into fzf 2. Preview shows the verb description and command 3. Select a verb to execute it immediately FZF_ENV_OPTS_VERBS configures the preview for verbs.

Custom fzf Key Bindings

The Ctrl-F prefix opens ZPWR's fzf keymap layer:

```
Ctrl-F Ctrl-D   File search (find + fzf + editor)
Ctrl-F Ctrl-I   Word search (ag + fzf + editor)
Ctrl-F Ctrl-G   Git search (git log + fzf)
Ctrl-F Ctrl-R   History search with fzf
```

These are ZLE widgets bound via `zpwBindOverrideZLE`.

Zpwrinfozf And Zpwrinfozfag

Two core ZLE widgets that bridge the command line with fzf: `zpwrInfoFzf` File-oriented fzf (Ctrl-T style) `zpwrInfoFzfAg` Content-oriented fzf (ag/grep style) Both capture fzf output and insert it into the command line buffer (\$BUFFER). You select files/matches, they appear at your cursor. Seamless integration between search and input.

The Colorizer Chain

ZPWR_COLORIZER preference: `bat > pygmentize`. `bat` uses themes (`BAT_THEME=$ZPWR_BAT_THEME`). `pygmentize` uses `PYMENTIZE_COLOR` style. Language-specific colorizers: `FZF_COLORIZER_C`, `_SH`, `_YAML`, `_JAVA`.

Building Your Own FZF Verbs

// once you grok the pattern, everything becomes fzf-able. //

The `generate | fzf | action` pattern is infinitely extensible. Here's how to build your own fzf-powered verbs.

The Pattern

```
<generator> | fzf [--preview '<preview-cmd>'] | <consumer>
```

Generator: anything that outputs lines (find, git, docker, etc.) Preview: command that shows detail for highlighted line (`\{ }`) Consumer: action on selected lines (`xargs`, `while read`, `eval`)

Example: fzf Through Docker Containers

```
function fzf-docker() {
  docker ps -a --format '{{.ID}} {{.Names}} {{.Status}}' |
  fzf --preview 'docker inspect {1} | head -50' |
  awk '{print $1}' |
  xargs -r docker logs --tail 100
}
```

Generator: `docker ps`. Preview: `docker inspect`. Consumer: `docker logs`.

Example: fzf Through tmux Sessions

```
function fzf-tmux-session() {
  tmux list-sessions -F '#{session_name}: #{session_windows} windows' |
  fzf --preview 'tmux list-windows -t {1}' |
  cut -d: -f1 |
  xargs tmux switch-client -t
}
```

Generator: `tmux list-sessions`. Consumer: `tmux switch-client`.

The Accept Vs Edit Pattern

ZPWR verbs come in two flavors: Accept verbs Execute the selection immediately Example: `verbsfzf` selects a verb and runs it. Edit verbs Insert the selection into \$BUFFER for editing Example: `filesearch` inserts the path into your command line. The difference is in the consumer. Accept uses `eval/exec`. Edit uses `BUFFER=$selection + zle redisplay`.

Making It A Zle Widget

To bind your fzf verb to a key:

```
function my-fzf-widget() {
  BUFFER=$(my-generator | fzf)
  CURSOR=${#BUFFER}
  zle redisplay
}
zle -N my-fzf-widget
bindkey '^F^X' my-fzf-widget
```

Now Ctrl-F Ctrl-X triggers your custom fzf workflow.

Tips For Good fzf Experiences

- Use `-ansi` if your generator outputs color codes - Use `-delimiter` and `-nth` to control what fzf matches on
- Use `-m` for multi-select (toggle with Tab) - Use `-header` for context hints at the top - Preview window size: `-preview-window=right:50%:wrap` - Test with: `echo 'a\nb\nc' | fzf -preview 'echo {}'`

FZF Brew & Chrome

// fuzzy finding extends to your package manager and browser //

The `fzf-zsh-plugin` adds fzf interfaces to Homebrew package management and Chrome browser data.

Homebrew Verbs

```
zpwri brewinstall          # fzf install formula
zpwri brewuninstall        # fzf uninstall formula
zpwri brewcaskinstall      # fzf install cask
zpwri brewcaskuninstall    # fzf uninstall cask
zpwri brewupdate           # fzf update formula
```

Each command pipes the available packages into fzf with multi-select. Pick one or many, then install/remove in one shot. No more googling package names.

Chrome Verbs

```
zpwri chromehistory        # search Chrome history in fzf
zpwri chromebookmarks      # search Chrome bookmarks in fzf
```

Reads Chrome's SQLite databases directly. Select a URL from fzf and open it in the browser.

Plugin: [MenkeTechnologies/fzf-zsh-plugin](https://github.com/MenkeTechnologies/fzf-zsh-plugin).

Chapter 30 – tmux Deep Dive

Tmux Architecture in ZPWR

// the terminal multiplexer. one screen, infinite shells. //

Tmux is the backbone of the ZPWR workflow. Multiple shells, persistent sessions, split panes, and code execution across panes – all orchestrated from `$ZPWR_TMUX`.

Session / Window / Pane Model

Session Named group of windows (e.g., 'dev', 'zpwr-study') Window A tab inside a session (like browser tabs) Pane A split inside a window (like vim splits) Typical ZPWR layout: 1 session, 2-4 windows, 2-4 panes each. Prefix key: Ctrl-B (default). Followed by a command key.

Session Persistence

Tmux-resurrect Manual save/restore of sessions Save: prefix + Ctrl-s Restore: prefix + Ctrl-r Saves: pane layouts, working directories, running programs. @resurrect-processes ':all:' – saves ALL running programs. tmux-continuum Auto-save every 15 minutes Works silently in the background. No manual intervention. Combined with resurrect: your tmux state survives reboots.

The Powerline Status Bar

Tmux sources powerline bindings for the status bar:

```
source-file ~/.tmux/powerline/bindings/tmux/powerline.conf
```

The symlink `~/.tmux/powerline` points to pip's powerline-status. powerline-daemon runs in the background for performance. Status bar shows: session name, window list, hostname, time, battery level (via tmux-battery plugin).

\$ZPWR_TMUX: The Config Directory

All tmux config lives under `$ZPWR_TMUX`:

<code>init.conf</code>	Main config (bindings, options)
<code>tmux-mac.conf</code>	macOS-specific overrides
<code>tmux-linux.conf</code>	Linux-specific overrides
<code>tmux_ge_21.conf</code>	Tmux >= 2.1 features
<code>tmux_ge_29.conf</code>	Tmux >= 2.9 features
<code>tmux_ge_31.conf</code>	Tmux >= 3.1 features
<code>four-panes.conf</code>	Layout: 4 panes
<code>sixteen-panes.conf</code>	Layout: 16 panes
<code>config-files.conf</code>	Opens brc, vrc, trc, zrc in 4 panes
<code>learn.conf</code>	Study layout

Init.conf Highlights

- 30,000 line scrollbar (ZPWR_TMUX_HISTORY_LIMIT) - Vi keybindings in copy mode - Prefix S: synchronize-panes (type in all panes at once) - Prefix q: display pane numbers for 5 seconds - 3-second repeat-time for directional keys

Vim-Tmux Code Execution

// select code in vim. execute in the pane next door. magic. //

The killer feature of the ZPWR vim+tmux integration: write code in vim, send it to an adjacent tmux pane for execution. No copy-paste. No switching windows.

The Tmuxrepeat Function

Defined in .vimrc, TmuxRepeat has three modes: 'file' Save the file, execute it in the right pane 'visual' Save visual selection to temp file, execute it 'repl' Paste visual selection directly into right pane.

Supported Languages

TmuxRepeat detects file type by extension:

```
sh, zsh, py, rb, pl, clj, tcl, vim, lisp, hs, ml,  
coffee, swift, lua, java, f90, cr
```

For known types, it sends the file to zpwrRunner.sh which dispatches to the correct interpreter. For unknown types, it falls back to TmuxRepeatGeneric (re-run previous command).

How It Works

1. Ctrl-V in normal/insert mode (or leader-vj): Saves the file, then sends:

```
tmux send-keys -t right 'bash "$ZPWR_SCRIPTS/zpwrRunner.sh" "file"' C-m
```

2. leader-vk in visual mode: Yanks selection to temp file `$ZPWR_HIDDEN_DIR_TEMP/.vimTempFile.<ext>`, then sends that temp file to the right pane for execution. 3. leader-vl in visual mode (REPL mode): Yanks selection, loads it into tmux buffer 'buffer0099', then pastes directly into the right pane. For REPLs like python, irb, node – code runs line-by-line in the REPL.

The Pane Targeting

Standard tmux: sends to pane named 'right' (the next pane). MacVim/GUI: sends to session 'vimmers:0.' (external tmux). The pane_count check ensures a target pane exists.

Allpanes.zsh: Broadcast To All Panes

`$ZPWR_SCRIPTS/allPanes.zsh` sends commands to all tmux panes:

```
prefix + Space  Run command in all panes (single mode)  
prefix + v      Run command in all panes (multi mode)  
prefix + b      Open URL in all panes
```

Synchronize-panes

Prefix + S Toggle synchronize-panes When enabled, every keystroke goes to ALL panes in the window. Useful for running identical commands on multiple servers, or setting up parallel environments simultaneously.

Google From tmux

Prefix + g Google search from tmux Runs `$ZPWR_TMUX/google.sh` with the current pane content. Select text, press prefix+g, and your browser opens with a Google search for the selection.

Tmux Plugins & Extensions

// tpm: the plugin manager for your multiplexer's plugins. yo dawg. //

ZPWR manages 9 tmux plugins via tpm (Tmux Plugin Manager). They live in `~/.tmux/plugins/` and add features that tmux does not provide out of the box.

Tpm: tmux Plugin Manager

Installed to `~/.tmux/plugins/tpm`. Managed via prefix keys:

```
prefix + I      Install plugins listed in .tmux.conf
prefix + U      Update all installed plugins
prefix + Alt-u   Clean plugins not in config
```

Plugins are declared in `$ZPWR_INSTALL/.tmux.conf`:

```
set-option -g @plugin 'tmux-plugins/tpm'
set-option -g @plugin 'tmux-plugins/tmux-resurrect'
```

The Plugin Roster (.tmuxplugins)

Tmux-plugins/tpm Plugin manager itself tmux-plugins/tmux-sensible Sane defaults for tmux tmux-plugins/tmux-resurrect Session save/restore tmux-plugins/tmux-continuum Auto-save sessions tmux-plugins/tmux-battery Battery indicator tmux-plugins/tmux-prefix-highlight Highlight when prefix active tmux-plugins/tmux-yank System clipboard integration MenkeTechnologies/tmux-thumbs Quick copy with hints MenkeTechnologies/tmux-fzf-url FZF through URLs in pane.

Tmux-resurrect: What It Saves

- Pane layouts (splits, sizes, positions) - Working directories for each pane - Running programs (@resurrect-processes 'all:') - Command history is NOT saved (that's zsh's job) Save: prefix+Ctrl-s. Restore: prefix+Ctrl-r.

Tmux-continuum: Auto-save

Piggybacks on resurrect. Auto-saves every 15 minutes. @continuum-restore is commented out in ZPWR by default. Enable it to auto-restore on tmux server start.

Tmux-fzf-url: Url Picker

Scans the visible pane for URLs, opens them in fzf:

```
prefix + e    FZF through URLs, open selected in browser
prefix + u    FZF through URLs, search mode
```

Uses ZPWR_TMUX_HISTORY_LIMIT for scrollback depth.

Custom Scripts In \$ZPWR_TMUX

Layout scripts create multi-pane environments:

```
prefix + D    control-window.conf (IDE layout)
prefix + F    four-panes.conf
prefix + G    eight-panes.conf
prefix + O    sixteen-panes.conf
prefix + T    config-files.conf (brc, vrc, trc, zrc)
prefix + M    learn.conf (study layout)
```

zpwr Study: The Split-pane Learning Environment

Creates a dedicated tmux session 'zpwr-study' with the encyclopedia on the left and a live shell on the right. Read the docs, try commands. Knowledge through practice.

Tmux Layout Save & Restore

Your pane arrangement, preserved forever.

The Problem

You spent 20 minutes splitting panes, resizing them, cd-ing into the right directories. Then tmux crashes. Or you reboot. Or you accidentally kill the session. All that layout work? Gone. Every time.

The Solution

```
zpwr tmuxsave dev          # save layout as 'dev'
zpwr tmuxload dev          # restore it later
```

What Gets Saved

```
Windows ..... names and count
Pane splits ..... exact geometry via select-layout
Directories ..... per-pane working directory
Running commands ..... full args from process tree
Window options ..... synchronize-panes, auto-rename
Session options ..... non-plugin tmux settings
Active pane/window .... cursor position restored
```

Management

```
zpwr tmuxsave          # save with timestamp name
zpwr tmuxsave --list   # list saved layouts
zpwr tmuxsave --delete dev # remove a layout
zpwr tmuxload          # fzf picker (no args)
zpwr tmuxload dev mywork # restore as session 'mywork'
```

Keybinding

Prefix W # save layout (tmux keybinding)

Aliases

```
zpwr layoutsave = zpwr tmuxsave
zpwr layoutload = zpwr tmuxload
```

Layouts are stored as self-contained zsh scripts in `$ZPWR_LOCAL/layouts/`. You can edit them by hand, version control them, or share them with your team.

PROTIP: Save your layout before experimenting. If you break everything, one command brings it back.

Chapter 31 – vim Deep Dive

Vim Plugin Architecture

// 15 plugins in .vimrc. each one a force multiplier. //

ZPWR's vim config uses Vundle as the plugin manager and ships 15 curated plugins that transform vim into a full IDE with completion, snippets, and tmux integration.

Vundle: The Plugin Manager

Plugins live in `~/.vim/bundle/`. Managed by Vundle:

```
set runtimepath+=~/.vim/bundle/Vundle.vim
call vundle#begin()
Plugin 'VundleVim/Vundle.vim'
... more plugins ...
call vundle#end()
```

Install: `:PluginInstall` Update: `:PluginUpdate` Clean: `:PluginClean`.

Youcompleteme: Semantic Completion

```
Plugin 'ycm-core/YouCompleteMe'
```

The heavyweight champion. Provides semantic completion for: C/C++ (via clangd), Python (via jedi), and more. Config: completion after 1 char, enabled in all file types, completes in comments. Uses C-n/C-p for selection.

Ultisnips + Vim-snippets: Snippet Engine

```
Plugin 'SirVer/ultisnips'
Plugin 'honza/vim-snippets'
```

Tab expands snippets, Tab/Shift-Tab navigate tab stops. Hundreds of snippets for every language: type `'for<Tab>'` in Python and get a complete for loop with cursor placement.

Supertab: Tab Completion Glue

```
Plugin 'ervandew/supertab'
```

Unifies Tab behavior: C-n cycles forward through completions. Coordinates with YCM and UltiSnips so Tab does the right thing in every context (snippet vs completion vs indent).

Vim-auto-save: Never :w Again

```
Plugin '907th/vim-auto-save'
```

Saves on InsertLeave, TextChanged, and TextChangedI. Every edit auto-saves silently. No more 'Unsaved changes' panics. g:auto_save_silent=1 suppresses the notification.

Rainbow: Matching Bracket Colors

```
Plugin 'luochen1990/rainbow'
```

Nested brackets get different colors: parentheses in blue, inner brackets in orange, deeper in cyan, deepest in magenta. g:rainbow_active=1 enables it globally on startup.

Vim-multiple-cursors: Multi-cursor Editing

```
Plugin 'TerryMa/vim-multiple-cursors'
```

Sublime Text-style multi-cursor. Ctrl-N selects next match, then edit all occurrences simultaneously.

Tmux-complete.vim: Cross-pane Completion

```
Plugin 'wellle/tmux-complete.vim'
```

Completes words from ALL tmux panes. Writing a command in vim that references output in another pane? Tab-complete it. Uses async.vim and asyncomplete.vim for non-blocking operation.

Vim Sessions & Workflow

// your vim state, frozen in amber. thaw it when you need it. //

Vim sessions save your entire editing state: open buffers, window layouts, cursor positions. ZPWR integrates sessions with tmux for a seamless development environment.

vim Session Management

ZPWR configures vim sessions as manual-save only:

```
let g:session_autosave = 'no'
let g:session_autoload = 'no'
```

No surprises. Sessions save when you tell them to. Save: Ctrl-D q (mapped to :SaveSession! in normal/insert mode).

Config Sessions: Vrc, Brc, Zrc, Trc

ZPWR defines verbs for editing its own config files: vrc Open .vimrc in vim brc Open shell aliases file (.zpwr_alias.sh) zrc Open .zshrc in vim trc Open tmux.conf in vim The tmux layout script config-files.conf opens all four in a 4-pane arrangement. Prefix+T triggers it. Each pane runs one of these verbs automatically.

The Auxiliary vim Plugins

Vim-autotag Auto-regenerate ctags on save.

```
Plugin 'craigemery/vim-autotag'
```

G:autotagStartMethod='fork' – non-blocking tag generation. vim-online-thesaurus Look up synonyms (visual mode \K)

```
Plugin 'beloglazov/vim-online-thesaurus'
```

Vim-zsh-completion Zsh syntax completion in vim.

```
Plugin 'Valodim/vim-zsh-completion'
```

Vim-minimap Sublime-style code minimap.

```
Plugin 'severin-lemaignan/vim-minimap'
```

The zpwr Snapshot/restore Integration

ZPWR has verbs for full environment snapshots:

```
zpwr snapshot    Capture terminal environment state
zpwr restore     Restore from snapshot
```

ZpwrRestore rebuilds shell state: directory stack, aliases, parameters, and more. This complements tmux-resurrect: resurrect restores the tmux layout, snapshot/restore restores the shell state within each pane.

The Full zpwr vim Workflow

1. Open a tmux session with your project layout
 2. Vim in left pane, shell in right pane
 3. Edit code in vim, Ctrl-V to execute in right pane
 4. Visual select + leader-vl to paste into a REPL
 5. tmux-complete.vim grabs words from the REPL output
 6. Auto-save means you never lose work
 7. Prefix+Ctrl-s saves the entire tmux state
- This is not an IDE. This is a weapon system.

Chapter 32 – temprs – Temporary File Stack Manager

temprs: The Stack Machine

// your filesystem is a stack. you just didn't know it yet. //

temprs is a Rust-based temporary file stack manager by MenkeTechnologies. Think of it as a LIFO/FIFO clipboard that persists across shell sessions using actual tempfiles on disk. Version 2.9.3. Every operation is instant. No databases, no daemons — just a master record file and a directory of tempfiles.

The Stack Paradigm

temprs models your scratch data as a stack with both ends open: push (default), pop, shift, unshift — like a Perl array on disk.

Core Operations

temprs # no args: create new tempfile, push to top
temprs -o INDEX # read contents of tempfile at INDEX to stdout
temprs -i INDEX # write stdin into tempfile at INDEX
temprs -p # pop from top of stack (print + remove)
temprs -s # shift from bottom of stack (print + remove)
temprs -u # unshift: push stdin to bottom (silent)
temprs -a INDEX # insert new tempfile at INDEX
temprs -r INDEX # remove tempfile at INDEX.

The Master Record

temprs keeps a master record file that maps stack positions to actual tempfile paths on disk. The temprs directory holds the files themselves. Both are in your system's temp directory. temprs -d # list the temprs directory contents
temprs -m # list the master record file path.

Pipeline Integration

temprs reads stdin when available — perfect for pipelines:

```
echo 'stash this' | temprs -u # silent push to bottom
curl -s api.io/data | temprs # push response to top
temprs -o 0 | jq .           # read top, pipe to jq
```

The -u unshift flag reads stdin and produces no stdout — ideal for mid-pipeline stashing without breaking the flow.

Positional Argument

temprs myfile.txt # read file into new tempfile on stack
If both stdin and a file arg are present, stdin takes priority. Your data flows in, gets a stack address, and waits for recall.

temprs: Advanced Operations

// the stack goes deeper. every tempfile has a story. //

Listing & Inspection

temprs -l # list all tempfile paths on the stack
temprs -n # list numbered (index + path)
temprs -L # list all tempfile contents
temprs -N # list numbered with full contents
temprs -k # count tempfiles on the stack
temprs -I INDEX # show metadata for tempfile at INDEX.

Editing & Tagging

temprs -e INDEX # open tempfile at INDEX in \$EDITOR
temprs -w NAME # tag a tempfile with an alias name
temprs -R OLD NEW # rename tag from OLD to NEW
Tags let you retrieve tempfiles by name instead of index. Your stack positions shift; your tags don't.

Search & Concatenate

temprs -g PATTERN # grep through all tempfile contents
temprs -C 0 2 5 # concatenate tempfiles at indices to stdout
The grep flag searches across every tempfile on the stack — like a personal knowledge base with instant full-text search.

Stack Manipulation

temprs -D 0 1 # diff two tempfiles by index or name
temprs -M 0 3 # move tempfile from position 0 to 3
temprs -x INDEX # duplicate tempfile onto top of stack
temprs -S 0 2 # swap two tempfiles by index or name
temprs -rev # reverse the entire stack order
temprs -A INDEX # append stdin to existing tempfile.

Housekeeping

temprs -c # clear/purge ALL tempfiles from stack
temprs --expire 24 # purge tempfiles older than 24 hours
temprs --wc INDEX # print line count of tempfile
temprs --size INDEX # print byte size of tempfile
temprs --path INDEX # print the actual filesystem path
temprs --sort mtime # sort stack by name, size, or mtime.

Mode Flags

temprs -q # quiet mode: suppress output on create
temprs -v # verbose mode: extra diagnostic output.

The Cyberpunk -h

Run `temprs -h` for the full ASCII art banner with the TEMPRS logo, status bar, and signal meter. Because even help text should look like a console from a Gibson novel. Also: `--head INDEX N` and `--tail INDEX N` for partial reads, and `--replace INDEX PAT REPL` for in-place sed-style edits.

Chapter 33 – Isofrs – Enhanced Lsof

Isofrs: Network Intelligence

// every open file descriptor is a signal. Isofrs reads them all. //

Isofrs is a Rust-based enhanced Lsof wrapper v4.7.0 by MenkeTechnologies. It wraps the venerable Lsof with colorized output, structured formatting, and cyberpunk-grade aesthetics.

Why Not Raw Lsof?

Raw Lsof dumps walls of monochrome text. Isofrs adds color coding by type, structured columns, and filtering that doesn't require piping through 5 layers of awk and grep.

Selection Flags

Isofrs -i [ADDR] # select internet connections ADDR format: [4|6][proto][@host|addr][:svc|port] Isofrs -c COMMAND # select by command name (prefix match) Isofrs -p PID # select by PID (comma-separated, ^excludes) Isofrs -u USER # select by login name or UID Isofrs -d FD # select by file descriptor set Isofrs -g [PGID] # select by process group ID Isofrs -a # AND selections (default is OR)

Network Flags

Isofrs -n # inhibit hostname resolution (fast mode) Isofrs -P # inhibit port-to-name conversion Isofrs -N # select NFS files Isofrs -U # select UNIX domain socket files.

zpwr Integration

The zpwr Lsof verb pipes Lsof output through fzf for interactive process selection and killing:

```
zpwr lsof          # fzf over lsof, select PIDs to kill
zpwr lsosedit      # same but edit the kill command first
```

The zpwrLsoffzf widget (bound to FH in viins and vicmd) runs `sudo lsof -i | fzf -m`, extracts PIDs with awk, and inserts them into your command line. Scan the local network like a deck jockey, pick your targets with fzf.

Files & Directories

Isofrs FILE... # list processes using these files Isofrs -dir DIR # open files in DIR (one level, like +d) Isofrs -dir-recurse DIR # recursive (like +D)

Isofrs: Practical Usage

// who's listening on port 8080? Isofrs knows. Isofrs always knows. //

Finding What's On A Port

```
lsofrs -i :8080      # anything on port 8080
lsofrs -i TCP:443    # TCP connections on 443
lsofrs -i 4          # all IPv4 connections
lsofrs -i 6TCP       # IPv6 TCP only
```

Display & Output

lsofrs -F [FIELDS] # machine-readable output fields lsofrs -J / --json # JSON output for piping to jq lsofrs -R # list parent PIDs lsofrs -t # terse: PID only (for scripting) lsofrs -0 # NUL field terminator (xargs -0 friendly) lsofrs --color MODE # auto, always, or never.

Live Monitoring

lsofrs +r 2 # repeat every 2 seconds lsofrs -W / --monitor # live full-screen like top lsofrs --delta # highlight new/gone FDs in repeat mode lsofrs --follow PID # watch one process, highlight opens/closes lsofrs --top 20 # live top-N processes by FD count lsofrs --watch FILE # watch who opens/closes a file over time.

Diagnostics

lsofrs --leak-detect # detect FD leaks (poll every 5s, 3 rounds) lsofrs --stale # find FDs pointing to deleted files lsofrs --ports # listening ports summary (like ss -tlnp) lsofrs --tree # process tree with FD counts (pstree + lsof) lsofrs --summary # aggregate FD summary by type and user.

Comparison

lsof — the OG. every Unix has it. output is a wall of text. ss — socket statistics. fast but sockets only, no files. netstat — deprecated on Linux. still works on macOS/BSD. lsofrs — wraps lsof with color, JSON, live monitoring, leak detection, tree views, and the cyberpunk banner you get with lsofrs -h. Built for operators who stare at FD tables and like what they see.

Quick Recipes

```
lsofrs -t -i :3000 | xargs kill # kill whatever's on 3000
lsofrs -c node -a -i TCP      # node's TCP connections
lsofrs -u $(whoami) -a -i     # your network connections
```

Chapter 34 – eza – The Modern ls

eza: ls Evolved

// ls is dead. long live ls. //

eza is the modern Rust replacement for ls, formerly known as exa. Maintained by eza-community after exa's author went AWOL. In zpw, it's the default file lister for everything.

\$ZPWR_EXA_COMMAND – The Configured Invocation

```
command eza --git -il --classify=always -H --color-scale -g -a --colour=always
```

Every flag earns its place: `--git` # git status per file (M modified, N new, I ignored) `-i` # show inode numbers `-l` # long listing format `--classify=always` # / after dirs, * after executables, always `-H` # show hard link count `--color-scale` # gradient colors for file sizes and ages `-g` # show group ownership `-a` # show hidden files (dotfiles) `--colour=always` # force color even when piped.

Why `--classify=always`?

Not just `-F`. Under p10k instant prompt, stdout gets redirected during init. eza's `--classify` auto-detects terminal capabilities and when stdout is redirected, it drops the indicators. The `=always` suffix forces classification regardless of fd state. Without it, your login banner loses all the / and * markers.

Where It's Used

ZpwrClearList and zpwrListNoClear both eval `$ZPWR_EXA_COMMAND`. The fallback chain: `eza -> grc + gls -> raw ls`. zpwrListNoClear checks for eza first, falls back to gls on macOS (with grc for colorization) or plain ls on Linux.

```
alias eza="$ZPWR_EXA_COMMAND" # bound in zpwrBindAliasesLate
alias lr="$ZPWR_EXA_COMMAND -R --tree | less -rMN"
```

The lr alias gives you a recursive tree piped through less with line numbers — a full filesystem X-ray.

Extended Attributes

Set `ZPWR_EXA_EXTENDED=true` in `.zpwr_env.sh` to add `--extended`, which shows xattr metadata on macOS (com.apple.quarantine etc).

eza: Colors & Integration

// a file listing without color is just noise. //

Eza_colors Environment Variable

eza uses EZA_COLORS (or EXA_COLORS for compat) to customize colors beyond the defaults. Format is colon-separated key=value:

```
export EZA_COLORS="di=34:ln=35:so=32:pi=33:ex=31"
```

Keys match LS_COLORS extensions. eza also adds its own: da=date, sn=file size number, sb=file size unit, uu=current user, un=other user, gu=current group.

LS_colors Compatibility

eza reads LS_COLORS as a fallback. If you have a vivid or dircolors setup, eza inherits it. EZA_COLORS overrides.

Tree View

```
eza --tree          # recursive tree (like tree command)
eza --tree -L 3     # limit depth to 3 levels
eza --tree --git-ignore # respect .gitignore in tree
```

The tree integrates with `--git`, so you see git status markers inline with the tree structure. New files glow green.

The Fallback Chain In Zpwrlistnoclear

1. If eza exists: `eval $ZPWR_EXA_COMMAND`
2. macOS + grc: `grc -c ~/conf.gls gls -iFlhA --color=always`
3. macOS bare: `ls -iFlhAO` (O = macOS file flags)
4. Linux + grc: `grc -c ~/conf.gls ls -iFlhA --color=always`
5. Linux bare: `ls -iFlhA` grc (Generic Colouriser) wraps ls output with conf.gls rules. It's the middle ground between raw ls and eza.

zpwr Verbs Using eza

ZpwrClearList clears the terminal then runs the listing. It's called on every `cd` via the `chpwd` hook — so you always see what's in the directory you just landed in. `zpwrListNoClear` does the same listing without clearing.

Sorting & Filtering

```
eza --sort=modified # sort by modification time
eza --sort=size     # sort by file size
eza -r             # reverse sort order
eza --group-directories-first # dirs at top
eza -I '*.pyc|__pycache__' # ignore patterns
```

Combine with `--git-ignore` to hide everything in `.gitignore`. Your file listings become as curated as your code.

Chapter 35 – bat – cat With Wings

bat: Syntax Highlighting for Everything

// cat is for reading files. bat is for understanding them. //

bat is a cat clone with syntax highlighting, git integration, and automatic paging. Written in Rust. In zpw it's the default colorizer: ZPWR_COLORIZER=bat in .zpw_env.sh.

Core Features

Line numbers in the gutter. Git diff markers (+/-/~) in the margin. Syntax highlighting for 200+ languages. Automatic paging via less when output exceeds terminal height.

Discovery

bat --list-themes # see all available color themes bat --list-languages # every syntax bat can highlight.

How zpw Uses bat

bat is the preview engine for fzf throughout zpw:

```
fzf --preview 'bat --color=always {}'
```

The full zpw colorizer invocation:

```
bat --paging never --wrap character --color always  
--style="numbers,grid,changes,header"
```

This is stored in `$ZPWR_COLORIZER` and expanded into: FZF_COLORIZER — preview for generic fzf FZF_COLORIZER_FILE — preview for file-specific fzf FZF_COLORIZER_FILE_TEXT — text file preview (uses -I ASP) When bat is unavailable, zpw falls back to pygmentize.

zpw Verbs

zpw filesearch and zpw wordsearch both use bat in their fzf preview windows. vimfilesearch, vimwordsearch, and the emacs variants (emacsfilesearch, emacswordsearch) all inherit the same bat-powered preview pipeline.

Standalone Usage

```
bat src/main.rs           # highlighted source view  
bat -l json data.txt      # force language detection  
bat --diff                # show only git-changed lines  
bat -A                    # show non-printable chars  
bat --plain               # no line numbers, no border  
bat -r 10:20 file.zsh     # show only lines 10-20
```

The -r (--line-range) flag is perfect for surgical code review.

bat: Configuration & Tricks

// configure your cat. teach it new tricks. make it purr. //

Bat_theme

```
export BAT_THEME="Dracula"
```

Set this in your env to change the default theme globally. Popular themes: Dracula, Monokai Extended, Nord, OneHalfDark, Solarized (Dark), TwoDark, ansi. Preview them all:

```
bat --list-themes | fzf --preview='bat --theme={} src/main.rs'
```

Style Components

```
bat --style=numbers,changes,header
```

Components: full, auto, plain, numbers, changes, header, header-filename, header-filesize, grid, rule, snip. Combine with commas. 'full' enables everything. 'plain' disables everything — just colored text, no chrome.

bat As Manpage Colorizer

```
export MANPAGER="sh -c 'col -bx | bat -l man -p'"
```

This makes every man page syntax-highlighted. The -l man forces manpage language detection, -p is -plain (no line numbers cluttering man output). col -bx strips backspace formatting.

Syntax Cache

```
bat cache --build    # rebuild syntax/theme cache
bat cache --clear    # clear and rebuild from scratch
```

After adding custom .sublime-syntax files to ~/.config/bat/syntaxes/, rebuild the cache to pick them up.

Debian/ubuntu Gotcha

On Debian-based systems, the binary is batcat not bat due to a name conflict with an unrelated package. Fix:

```
alias bat=batcat      # or symlink: ln -s batcat ~/.local/bin/bat
```

bat + Delta For Git Diffs

Delta is a syntax-highlighting pager for git diffs. It uses bat's syntax themes internally. Configure in .gitconfig:

```
[core] pager = delta
[delta] syntax-theme = Dracula
```

Delta adds line numbers, side-by-side view, and word-level diff highlighting. bat does files, delta does diffs.

Bat_pager

```
export BAT_PAGER="less -RFX"
```

Customize the pager bat uses. -R for color, -F to quit if one screen, -X to not clear screen on exit. Or set to " to disable paging entirely — zpwv does this with -paging never.

Chapter 36 — fd-find — Find Replacement

fd: find for Humans

// find is powerful. fd is powerful AND usable. //

fd is a fast, user-friendly alternative to find, written in Rust by David Peter (sharkdp — also the author of bat). It respects .gitignore by default and uses regex, not globs.

Basic Usage

```
fd PATTERN          # search current dir recursively
fd PATTERN path/    # search specific directory
fd '^test.*\.zsh$'  # full regex support
```

No -name, no -type f, no quoting gymnastics. Just the pattern.

Key Differences From Find

1. Regex by default (find uses glob with -name)
2. Ignores .git, node_modules, .gitignore entries automatically
3. 5-10x faster than find due to parallel directory traversal
4. Smart case: case-insensitive unless pattern has uppercase
5. Colorized output by default

Common Flags

fd -e zsh # filter by extension fd -t f # files only fd -t d # directories only fd -t l # symlinks only fd -t x # executables only fd -H # include hidden files fd -I # don't respect .gitignore fd -u # unrestricted (-H -I combined) fd -g GLOB # use glob pattern instead of regex.

Execution

fd -x cmd {} # execute command per result (parallel) fd -X cmd{} # execute once with all results as args.

Placeholders: {} = path, {/} = basename, {/}/ = parent dir,

{.} = Path without extension, {/.} = basename without extension.

```
fd -e jpg -x convert {} {/.}.png # convert all jpgs to png
```

The -x flag runs in parallel by default — your cores earn their keep. -X collects all results and passes them as one batch. This is the find | xargs pattern without the pipe.

fd: Integration with zpw & fzf

// fd feeds fzf. fzf feeds your brain. the pipeline of knowing. //

Fzf_default_command

zpwrr sets FZF_DEFAULT_COMMAND to use find + ag by default:

```
export FZF_DEFAULT_COMMAND='find * | ag -v ".git/"'
```

You can override this with fd for faster results:

```
export FZF_DEFAULT_COMMAND='fd --type f --hidden --follow'
```

fd is faster because it parallelizes traversal and skips .gitignore entries without needing ag to filter them out.

fd + fzf Patterns

```
fd -e zsh | fzf          # fuzzy find zsh files
fd -t f | fzf --preview 'bat {}' # find + preview
vim $(fd -t f | fzf)      # find, select, edit
```

This three-tool combo (fd + fzf + bat) is the holy trinity of file navigation. fd finds, fzf filters, bat previews.

Temporal & Size Filters

fd -changed-within 1d # modified in last 24 hours fd -changed-before 1w # modified more than a week ago
fd -size +1m # files larger than 1 megabyte fd -size -10k # files smaller than 10 kilobytes Units: b (bytes), k (kilobytes), m (megabytes), g (gigabytes). Time: s (seconds), m (minutes), h (hours), d (days), w (weeks).

fd + bat

```
fd -e rs --exec bat{} # colorized find results
fd -e md -X bat       # cat all markdown files at once
```

fd Vs Find Vs Locate

Find — universal. every Unix has it. slow on large trees. supports -exec, -newer, -perm, -prune. the Swiss Army. fd — fast parallel traversal, sane defaults, .gitignore aware. best for daily use in code repositories. locate — instant results from a pre-built database (updatedb). stale until the next cron run. no real-time accuracy.

Depth & Exclusion

fd -d 3 # max depth of 3 levels fd -E node_modules # exclude a directory by name fd -E '*.min.js' # exclude by glob pattern Stack -E flags to build precise exclusion lists on the fly.

Chapter 37 – ripgrep – grep At Light Speed

ripgrep: grep Reimagined

// grep -r is a campfire. ripgrep is a directed energy weapon. //

Ripgrep (rg) is a blazing-fast recursive grep written in Rust by Andrew Gallant (BurntSushi). It respects .gitignore, skips binary files, and uses Rust's regex engine for raw speed. 5-100x faster than grep -r on large codebases. Not a typo.

Basic Usage

```
rg PATTERN                # search current dir recursively
rg PATTERN path/          # search specific directory
rg 'fn main'              # literal or regex – rg auto-detects
```

Output is colored by default: filenames in magenta, line numbers in green, matches highlighted. Grouped by file.

Key Flags

rg -i PATTERN # case insensitive search rg -l PATTERN # files with matches only (paths) rg -c PATTERN # count matches per file rg -w PATTERN # whole word matches only rg -F PATTERN # fixed string (no regex interpretation) rg -v PATTERN # invert match (lines NOT matching)

File Type Filtering

rg -t zsh PATTERN # search only zsh files rg -T js PATTERN # exclude javascript files rg -g '*.zsh' PAT # glob filter (include) rg -g '!*.min.js' PAT # glob filter (exclude) rg --type-list shows all built-in type definitions.

Context Lines

rg -A 3 PATTERN # 3 lines after each match rg -B 3 PATTERN # 3 lines before each match rg -C 3 PATTERN # 3 lines before AND after.

Multiline Matching

rg -U PATTERN # --multiline: match across lines.

```
rg -U 'struct \{[\\s\\S]*?\\}' # match entire struct blocks
```

Without -U, patterns match within single lines only.

The Competition

grep -r — universal, slow, no .gitignore, no parallelism ag — the silver searcher. fast, .gitignore aware. rg is 2-5x faster on most benchmarks. ack — Perl-based, pioneered the “better grep” category. slower than both ag and rg. still has loyal users.

ripgrep: Advanced & zpwr Integration

// rg -json | jq — structured grep for the data-obsessed. //

Structured Output

rg -json PATTERN # JSON output: one object per line Each line is a JSON object with type (begin, match, end, summary), path, line number, match offsets. Pipe to jq:

```
rg --json TODO | jq 'select(.type=="match") | .data.path'
```

Search & Replace Preview

rg -replace 'NEW' PATTERN # preview replacements This prints what the output WOULD look like with replacements but does NOT modify files. It's a dry-run. Capture groups work:

```
rg 'foo(\w+)' --replace 'bar$1' # foo_x -> bar_x
```

Statistics

rg -stats PATTERN # show match stats after results Prints: N matches, N matched lines, N files searched, N files matched, bytes searched, duration. Quick audit.

Custom File Types

```
rg --type-add 'zpwr:*.zsh' -t zpwr PATTERN
```

Define a custom type inline and use it immediately. Persist custom types in `~/.ripgreprc` (set RIPGREP_CONFIG_PATH).

zpwr Integration

zpwr grep uses ag (silver searcher) piped into fzf:

```
zpwr grep # ag into fzf for interactive search
```

zpwr wordsearch searches file contents with fzf preview:

```
zpwr wordsearch # search by word in subdirectory files
```

Both use bat-powered previews in the fzf window.

fzf + rg Live Reload

The ultimate interactive grep: rg feeds fzf, bat previews:

```
rg --line-number PATTERN |  
fzf --delimiter : --preview 'bat --highlight-line {2} {1}'
```

rg outputs file:line:match, fzf splits on :, bat highlights the matching line. Three tools, one seamless experience.

Configuration

```
export RIPGREP_CONFIG_PATH=~/ripgreprc
```

Put default flags in this file, one per line: `--smart-case`, `--hidden`, `--glob=!.git`, `--max-columns=200` Also: `.rgignore` in any directory works like `.gitignore` — project-specific patterns that rg will skip. `.ignore` files (used by ag too) are also respected by rg.

Chapter 38 – neovim

Neovim: The Next Generation

// vim, but the timeline where Bram had unlimited funding. //

Neovim is the modernized fork of vim. Refactored internals, async everything, built-in LSP, Lua plugin API. In zpw, the default editor: ZPWR_VIM='nvim' in .zpw_env.sh.

The Init.vim Bridge

\$ZPWR_INSTALL/init.vim is just three lines:

```
set runtimepath^=~/.vim runtimepath+=~/.vim/after
let &packpath = &runtimepath
source ~/.vimrc
```

This means neovim sources the same .vimrc as vim. One config to rule them both. All 80+ vim plugins work in either editor. The symlink is created by plugins_install.sh:

```
ln -sf $ZPWR_INSTALL/init.vim ~/.config/nvim/init.vim
```

Neovim-specific Features

Async job control — run external commands without blocking the editor. vim 8 added this too, but nvim's API is cleaner (jobstart/jobstop). Built-in LSP — nvim 0.5+ has a native LSP client. Configure with lua: vim.lsp.start(). No plugin needed for basic LSP. Lua plugin API — write plugins in Lua, not just VimScript. Lua runs 10-100x faster than VimScript. :terminal — built-in terminal emulator. Better than vim's :terminal — proper job control, scrollback, and buffer integration. True color — 24-bit color out of the box. No termguicolors hacks needed (though the option exists).

Provider Support

nvim uses providers for python3 and node integration:

```
pip3 install pynvim          # python3 provider
npm install -g neovim        # node.js provider
```

Run :checkhealth to verify all providers are working.

zpw vim Info

zpw catviminfo and zpw catrecentviminfo read the nvim shada (shared data) file — the nvim equivalent of .viminfo.

Neovim: Configuration & Tips

// one vimrc. two editors. zero compromises. //

The Shared Config Philosophy

zpwr's init.vim just sources `~/.vimrc`. This means: 1. Every plugin in .vimbundle works in both vim and nvim 2. All keybindings, settings, and autocmds are shared 3. One file to edit: zpwr vrc opens .vimrc 4. No divergent configs to maintain across editors The .vimrc is the single source of truth. init.vim is a shim.

Neovim-specific Settings

Guard nvim-only settings with `has('nvim')`:

```
if has('nvim')
set inccommand=nosplit    " live substitution preview
set pumblend=15           " popup menu transparency
set winblend=15           " floating window transparency
endif
```

Inccommand is a killer feature: `:s/old/new` shows replacements live as you type. No more guessing what your regex will do.

:checkhealth

Run this in nvim to diagnose your setup. It checks: - python3/node providers (pynvim, neovim npm package) - clipboard support (pbcopy on macOS, xclip on Linux) - terminal capabilities, true color support - plugin health (many plugins register health checks) First thing to run when something feels wrong.

Session Tracking

Tpope/vim-obsession (in .vimbundle) tracks sessions:

```
:Obsession          # start tracking session to Session.vim
:Obsession!         # stop tracking and delete Session.vim
nvim -S Session.vim # restore session
```

Works in both vim and nvim since it's a VimScript plugin.

Why zpwr Supports Both

nvim is better locally — async, LSP, Lua, true color. But: - Remote servers often only have vim (or vi) - Docker containers ship vim, not nvim - macOS ships vim in `/usr/bin/vim` The shared .vimrc means your muscle memory works everywhere. nvim when you can, vim when you must, same config either way.

zpwr Editor Verbs

```
zpwr vrc            # edit .vimrc (shared by both)
```

Both editors, one config, zero excuses. The way it should be.

Chapter 39 – perl In zpwr

Perl Oneliners: The Secret Weapon

sed wishes it could do this. awk cries in a corner.

Perl is zpwr's scalpel for text surgery. Where sed and awk stumble on complex patterns, perl oneliners slice clean. zpwr uses perl throughout for text transformation, parsing, delimiter handling, and file manipulation.

The Key Flags

-e 'code' execute code -n loop over input lines (like sed) -p loop and print each line (like sed -p) -l chomp newlines, add them back on print -a autosplit into @F array (like awk) -F'sep' set field separator for -a -i in-place edit (like sed -i) -E enable say, state, switch (modern perl)

Whitespace Cleanup (scripts/lib.sh)

```
perl -pi -e 's@\s+$@\n@g; s@\x09$@    @g'
```

Strips trailing whitespace, converts trailing tabs to spaces. The -pi combo: -p loops, -i edits in place. zpwr's file cleaner.

Print Separator Lines

```
perl -le "print '#x80'"
```

Prints 80 # characters. The x operator repeats a string. Used in zpwrPrettyPrint for visual separators.

Delimiter Transformation

```
perl -F"$ZPWR_DELIMITER_CHAR" -anE 'say ...'
```

Splits lines on ZPWR_DELIMITER_CHAR into @F fields. Used heavily in zpwrContribCount, zpwrTotalLines for reformatting git contribution data into tabular output.

Filter Blank Lines

```
perl -ne 'print if /\S/'
```

Only prints lines containing non-whitespace. Used in zpwrRegenAllKeybindingsCache to clean keybinding dumps.

The perl Repl Alias

```
p1r (alias for rlwrap perl -wnE'say eval()//$@')
```

Interactive perl REPL with readline. Type expressions, get results.

Perl Oneliners: Advanced Patterns

When you need a chainsaw, not a butter knife.

Path Quoting (zpwrGetFound)

```
perl -pe 's@^([~]*)([^~].*)$@${1}"${2}"@;s@\s+@ @g'
```

Wraps non-tilde paths in double quotes and collapses spaces. Handles filenames with spaces for safe shell consumption.

fzf Result Formatting (zpwrAgIntoFzf)

```
perl -pe 's@^(.*?):(\d+):(.*)@+${2} "PWD/${1}"@'
```

Converts grep output (file:line:match) into vim args (+line "file"). The brain behind zpwr grep -> fzf -> vim pipeline.

Verb List Formatting (zpwrVerbsFZF)

```
perl -e '@a=<>;for(@a){print "zpwr ${1}" if m{^\(\\S+)\s+}}'
```

Reads verb list, extracts first word, prepends 'zpwr'. Builds the command string that fzf executes on selection.

In-place Rename (zpwrChangeNameZpwr)

```
perl -i -pe 's@\bOLDNAME\b@NEWNAME@g' **/*(.*)'
```

Renames all occurrences across all files. The \b word boundary prevents partial matches. The **(.) glob hits all regular files.

Login Counting (zpwrLoginCount)

```
perl -e '""'print qx(last -f "$_") for </var/log/wtmp*>'""'
```

Reads all wtmp files and runs last on each. The diamond operator <> globs and iterates. Then pipes to:

```
perl -lane '""'print [0] if /\S+/ && !/wtmp/'""'
```

Extracts username (first field) from non-empty, non-header lines.

File Count Dedup (zpwrEnvCounts)

```
perl -lne '@l=<>;@u=do{my %seen;grep{!$seen{$_}++}@l};'
```

Reads all lines, deduplicates with a hash, then checks if each unique path is a real file. The densest oneliner in zpwr. Counts unique zpwr files across all tracked locations.

Ip Address Extraction (ipa Alias)

```
ifconfig | perl -lane 'do {print \[1]=~s/addr//r;exit0} if /inet\s/ and !/127/'
```

Finds the first non-loopback inet address. The s///r flag

Returns the modified string without changing the original.

Why perl Over Sed/awk?

1. Perl regex is more powerful (lookahead, backrefs, [/x](#))
2. -i flag for in-place edit is reliable across OS
3. Complex logic in one line (if/unless/for/do blocks)
4. @F autosplit is awk-like but with perl's full stdlib
5. Perl is installed everywhere (even minimal containers)

Chapter 40 – Hidden Subsystems

Zconvey: Terminal Communication

Every terminal screams its identity into the void.

What Is Zconvey?

MenkeTechnologies/zconvey - a zinit plugin Allows sending commands between terminal sessions. Your terminals can talk to each other. Yes, really. Loaded via zinit in [\\$ZPWR_INSTALL/.zshplugins](#).

How zpwr Uses It

Every time you press Enter, zpwrAcceptLine fires. It calls zc-rename to label the current terminal with: TTY:\${TTY} PID:\${\$} CMD:\$BUFFER PWD:\${PWD} DATE:\$(date) This broadcasts your terminal's state to the zconvey bus. Every pane, every tab, every session - all labeled.

The Convey Variables

ZPWR_CONVEY_NAME the full label string sent to zconvey ZPWR_CONVEY_LAST_CMD the last command (for zconvey commands) When you run a zc-* command, it preserves the previous label so your terminal doesn't get renamed to "zc-send ls".

The Rename Logic

```
if ! [[ $(zpwrExpandAliases $BUFFER) = zc* ]]; then
  ZPWR_CONVEY_NAME="TTY:${TTY} PID:${$} CMD:..."
  zc-rename $ZPWR_CONVEY_NAME
```

If BUFFER starts with zc*, keep the old label. Otherwise, stamp the terminal with the new command.

Why This Matters

tmux status bar can show what each pane is running. You can identify panes by their last command and PWD. Remote debugging: see exactly what terminal ran what. It's like process accounting, but for your shell sessions.

Sending Commands Between Terminals

Zc-send 2 'cd /tmp && ls' send command to terminal 2 zc-all 'echo hello' broadcast to all terminals Your terminals are a mesh network. Act accordingly. SIGNAL: zpwrAcceptLine is the heartbeat of zpwr. Every Enter keypress: rename terminal, check for clear, detect file-modifying commands, send tmux keys. zconvey makes that heartbeat visible across sessions.

The 24-Hour Updater Loop

Your system updates itself while you sleep.

The Infinite Loop

`$ZPWR_SCRIPTS`/autoUpdater.sh runs forever. Every 24 hours it wakes up and updates everything.

```
while true; do
  bash -l updater.sh -e
  # sleep in 10-minute chunks until 24h elapsed
done
```

Uses Perl Time::Piece to calculate the next update time. Logs the time diff on each wake to `$ZPWR_LOGFILE`.

What Gets Updated

Updater.sh orchestrates the full update: zpwrUpdater runs the main zpwr update sequence zpwrUpdateDeps updates all package manager dependencies Homebrew, npm, pip, gem, go - everything gets refreshed. History files backed up. Logs rotated. Deps pinned.

Systemd Service (LINUX)

On Linux, autoUpdater.sh runs as a systemd service. zpwr restart restart the zpwr systemd service zpwr serviceup start and enable the systemd service zpwr servicedown stop and disable the systemd service On macOS, `$ZPWR_SCRIPTS`/updaterForLaunchCtl.sh is used.

Email Notifications

`$ZPWR_SCRIPTS`/updaterEmail.sh Pipes the update log to email via mutt. Wake up to a full report of what changed overnight. Your system admin is a bash script. It never sleeps.

The Sleep Strategy

Doesn't sleep for 24h straight (that would drift). Sleeps in 10-minute intervals, checks elapsed time:

```
((timediff > $((3600 * 24)))) && break
```

This handles laptop suspends and clock adjustments. WARNING: The updater keeps zpwr and all deps current. If something breaks after an update, check the log: zpwr taillog to see what the updater did last. The machine maintains itself. You just write code.

The 32-Pane REPL Layout

Every language, one screen, zero excuses.

The tmux Keybindings

Prefix R source `$ZPWR_TMUX`/thirtytwo-panes-repl.conf prefix O source `$ZPWR_TMUX`/sixteen-panes.conf prefix G source `$ZPWR_TMUX`/eight-panes.conf prefix F source `$ZPWR_TMUX`/four-panes.conf One keystroke splits your terminal into a REPL army.

The 32 Repls (prefix R)

Pane 0: lua pane 1: swift pane 2: ghci pane 3: clisp pane 4: ocaml pane 5: clojure pane 6: pry (ruby) pane 7: bpython pane 8: php -a pane 9: groovysh pane 10: csharp pane 11: kotlinc pane 12: node pane 13: coffee pane 14: tcsh pane 15: ksh pane 16: bash pane 17: csh pane 18: perl -dE1 pane 19: gore (go) pane 20: jshell pane 21: mycli pane 22: pgcli pane 23: python2 pane 24: nslookup pane 25: mongo pane 26: irb pane 27: scala pane 28: utop pane 29: iex pane 30: bc pane 31: gforth 32 languages. 32 panes. One tmux window. Absolute madness.

The Vim-tmux Execution Pipeline

Write code in vim, send it to a REPL pane: Supported languages for vim-to-tmux execution: zsh, bash, python, ruby, perl, node, go java, scala, R, octave Select code in vim, fire it into the matching pane. Edit-run-edit-run without ever leaving vim.

Progressive Layouts

Don't need 32 languages? Scale down: prefix G 8 panes - quick polyglot session prefix O 16 panes - serious multi-language work prefix R 32 panes - full REPL matrix (needs big screen) Each layout is a tmux conf file in `$ZPWR_TMUX/` NOTE: prefix R on a 13" laptop is an act of hubris. You'll need at least a 27" monitor to read anything. But hey, it works. And it's glorious.

Cross-Platform Installer

One repo to rule them all, one script to install them.

Installer Scripts In `$ZPWR_INSTALL`

Formulae.sh Homebrew formulae (macOS/Linux) casks.sh Homebrew casks (macOS GUI apps) mincasks.sh minimal cask set for lean installs taps.sh Homebrew tap repositories npm_install.sh Node.js packages via npm npm.sh npm package list gems.sh Ruby gems pip_install.sh Python packages via pip pip.sh / pip3.sh pip package lists go_install.sh Go packages rustupinstall.sh Rust toolchain via rustup.

Editor & Plugin Installers

Neovim_install.sh Neovim setup vim_install.sh Vim from source vim_plugins_install.sh Vim plugin manager + plugins zsh_plugins_install.sh Zsh plugins via zinit tmux_plugins_install.sh Tmux plugin manager + plugins spacemacs_install.sh Spacemacs (Emacs) setup.

Shared Infrastructure

Common.sh shared installer functions used by all scripts zpwrInstall.sh the master installer orchestrator Supports 20+ Linux distros, macOS, and FreeBSD. Detects your OS and calls the right package manager.

zpwr Verbs For Installation

zpwr install run configure, make, make install zpwr uninstall uninstall all zpwr configs zpwr regenconfiglinks regen symlinks from `$ZPWR_INSTALL` to `$HOME` regenconfiglinks recreates dotfile symlinks after a reinstall.

The Symlink Strategy

zpwr doesn't copy config files to `$HOME`. It symlinks them. `.vimrc`, `.tmux.conf`, `.gitconfig` - all point back to `$ZPWR_INSTALL`. Edit once in the repo, git commit, and every machine gets it. zpwr `regenconfiglinks` rebuilds them if they break. PHILOSOPHY: Package lists are just text files. Add a line to `formulae.sh`, and your next machine gets it. Your entire dev environment is version-controlled.

Chapter 41 – Quality Assurance

The Test Suite

60 test files standing between you and chaos

Testing Framework

zpwr uses zunit - a testing framework written in zsh. Config lives in `$ZPWR/.zunit.yml` Tests dir: `$ZPWR_TEST`
Output: `$ZPWR_TEST/_output` Support helpers: `$ZPWR_TEST/_support`.

Test Categories

T-autoload-* verify all autoloaded functions load, defined, existence, fpath, whence, type, body Every autoload function must: exist, load, have a body. t-autoload-subdir-* same checks for subdirectory autoloads t-env-* verify environment variables defined, exported, comprehensive, type checks Every ZPWR_* var must be defined and exported. t-scripts-* verify script files executable, readable, non-empty, have shebangs, valid syntax t-verbs-* verify zpwr verb definitions key format, non-empty values, callable, type checks.

More Test Files

T-functions.zsh test core shell functions t-callable-fns.zsh verify functions are callable t-navigation.zsh test directory navigation t-install-files.zsh verify installer file integrity t-repo-files.zsh verify repo structure t-plugin-counts.zsh verify plugin load counts.

Running Tests

zpwr test run all zpwr tests zpwr testall run ALL env tests (comprehensive sweep) fail_fast: true means first failure stops the run. verbose: true means you see every assertion. GUARANTEE: Every autoload loads. Every env var defined. Every script executable. Every verb callable. 60 test files verify zpwr won't break your shell. If tests pass, your environment is sound. Ship it.

Chapter 42 – Colorization Stack

GRC: Generic Colorizer

Because monochrome ls is a crime against humanity.

What Is Grc?

grc wraps commands and adds color output via regex rules. It reads a config file that maps patterns to colors. Any command's output can be colorized. Zero modifications.

Grc In Zpwrlistnoclear

The fallback chain when listing files: 1. eza preferred (color-scale, git status) 2. grc + ls fallback (colorized via conf.gls) 3. plain ls last resort (no color config)

Platform-specific Commands

MacOS:

```
grc -c $HOME/conf.gls gls -iFlhA --color=always
```

Linux:

```
grc -c $HOME/conf.gls ls -iFlhA --color=always
```

MacOS uses gls (GNU ls from coreutils) because BSD ls doesn't support all the flags. Linux uses native ls.

The Conf.gls Config

Custom color configuration for ls output, lives at:

```
$HOME/conf.gls
```

Maps file types, permissions, sizes to ANSI colors. Directories, executables, symlinks - all distinct colors.

Other Grc Targets

grc can colorize almost any command: ping latency numbers in color traceroute hop-by-hop color coding make errors red, warnings yellow gcc compiler output colorized netstat connection states highlighted diff additions green, deletions red.

Grc In Log Colorization

`$ZPWR_SCRIPTS/colorLogger.sh` uses grc for system logs. tmux control windows show colorized live log output. TIP: If eza is missing and ls looks dull, install grc. It's the middle tier of zpwr's color fallback chain. One package, instant color for dozens of commands.

Ponysay, Lolcat & ASCII Art

Enterprise-grade cartoon horse infrastructure.

The Ascii Art Toolchain

Ponysay My Little Pony ASCII art (cowsay but fabulous) lolcat rainbow gradient text output figlet large ASCII text banners from font files cowsay classic ASCII art speech bubbles toilet another ASCII art text renderer zpwr combines all of these for its startup banner.

zpwr Banner Verbs

zpwr bannerpony hostname banner with ponysay zpwr bannerlolcat ponysay + lolcat rainbow gradient zpwr bannernopony banner without ponysay zpwr figletfonts preview all installed figlet fonts Each verb calls a different autoloaded function:

```
zpwrPonyBanner, zpwrBannerLolcat, zpwrNoPonyBanner
```

The Startup Banner

On shell startup, zpwrDarwinBanner / zpwrLinuxBanner fires. It picks a random figlet font each time via:

```
$ZPWR_SCRIPTS/macOnly/figletRandomFontOnce.sh
```

ZPWR_BANNER_TYPE controls pony vs no-pony: ponies -> zpwrBannerLolcat (rainbow horse) other -> zpwrNoPonyBanner (figlet only)

Banner Control

ZPWR_BANNER_CLEARLIST controls startup banner + ls display When true: clear screen, show banner, then zpwrListNoClear. When false: skip the banner entirely (fast startup).

Font Logging

The random figlet font name is logged to:

```
$ZPWR_LOGFILE
```

Want to know which font made that gorgeous banner? zpwr taillog and look for the font name. Found one you love? Set it permanently in your config. REALITY CHECK: A rainbow pony greeting you on every terminal open is either peak engineering or peak insanity. zpwr does not distinguish between the two. Your hostname, rendered in ASCII art, by a cartoon horse. This is what unlimited power looks like.

GRC, ccze & the Color Pipeline

Every byte of output deserves to be beautiful.

The Full Colorization Stack

zpwr has a color tool for every type of output: FILE LISTING eza (color-scale, git status) -> grc+ls -> plain ls FILE VIEWING bat (syntax highlighting) -> cat ZPWR_COLORIZER=bat in \$ZPWR_ENV/.zpwr_env.sh LOG VIEWING ccze (log colorizer) -> plain tail zpwrTailLog pipes \$ZPWR_LOGFILE through ccze. GIT DIFFS delta

(syntax-aware diff) -> plain diff delta adds line numbers, word-level highlighting, and side-by-side view with Dracula theme.

Ccze: Log File Colorizer

ccze parses log formats and applies semantic colors: timestamps, severity levels, PIDs, IP addresses. zpwrtaillog uses ccze for colorized log tailing. System logs become readable at a glance.

Color Testing Verbs

zpwrcolortest test terminal basic 16 colors zpwrcolortest256 test full 256-color palette zpwrcolorpygmentcolors show all pygment color schemes zpwrcolorsdiff colorized side-by-side diff Use these to verify your terminal supports the full palette.

The Fallback Philosophy

Every color tool has a plain fallback: No eza? grc+ls. No grc? plain ls. No bat? cat. zpwrcolor degrades gracefully. Color is never a hard dependency. SSH into a minimal server? Everything still works. Just less pretty. Function over form, always. THE RESULT: In a fully-equipped zpwrcolor terminal: File listings glow. Logs are semantic. Diffs are surgical. Your eyes never have to parse raw monochrome again. The color pipeline is zpwrcolor's cosmetic surgery department.

Chapter 43 – The End

The Epilogue: You Are the Wizard

The terminal bows to you.

What You've Learned

From keybindings to kernel. Every chapter, every verb. Autoloaded functions. Tmux pipelines. Fzf integration. Vim execution. Perl oneliners. Systemd services. 32-pane REPL layouts. Cross-platform installers. A 24-hour updater loop. A 60-file test suite. A colorization stack five tools deep. And a startup banner delivered by a rainbow pony.

The 5 Commands To Memorize

zpwr verbs list every zpwr subcommand zpwr doctor run environment health check diagnostic zpwr bench benchmark startup with percentiles zpwr wizard interactive guided tour (you're here) zpwr study split-pane learning: book left, shell right Five commands. That's your entire onboarding.

How To Add Your Own Verbs

1. Create an autoload function in `$ZPWR/autoload/common/`
2. Add to `ZPWR_VERBS` in `$ZPWR_ENV/zpwr.zsh` Format: `ZPWR_VERBS[myverb]='myFunc=description'`
3. Reload: `exec zsh`. Your verb is live.

How To Extend The Wizard

Add a new page_NNN.zsh to `$ZPWR_INSTALL/wizard_pages/` Follow the format: `PAGE_TITLE, PAGE_CHAPTER, PAGE_CONTENT()`. The wizard auto-discovers pages. No registration needed.

How To Contribute

Fork github.com/MenkeTechnologies/zpwr Add your feature. Write tests. Submit a PR. The codebase is the documentation. Read it.

The zpwr Philosophy

Verbs, not scripts. Discoverability over memorization. Speed over bloat. Fallbacks over hard dependencies. Convention over config. Your shell should just work.

One Last Thing

Run zpwr about to see the zpwr banner. Then open a new terminal. Watch the pony greet you. You are the wizard now. The terminal is yours.

End Of Transmission

// ZPWR WIZARD ENCYCLOPEDIA v1.0 // SIGNAL LOST //

May your shell be fast, your pipes be clean, and your exit codes always zero.

Appendix A – Keybinding Reference

Tmux Prefix Keys: Navigation & Panes

pane traversal, splitting, resizing. the grid of power.

Pane Selection (hjkl Repeatable):

prefix h	select pane left
prefix j	select pane down
prefix k	select pane up
prefix l	select pane right
prefix ;	last-pane (toggle to previous)
prefix o	select next pane in order
prefix q	display-panes (5s timeout)

Pane Resize (HJKL Repeatable, 5 Cells):

prefix H	resize pane left 5
prefix J	resize pane down 5
prefix K	resize pane up 5
prefix L	resize pane right 5
prefix Ctrl-Up/Down	resize pane by 1
prefix Alt-Up/Down	resize pane by 5

Pane Splitting:

prefix -	split vertical (same dir)
prefix \	split horizontal (same dir)
prefix "	split vertical (default dir)
prefix %	split horizontal (default dir)
prefix	split horizontal
prefix _	split vertical

Pane Operations:

prefix z	zoom/unzoom current pane
prefix !	break pane into own window
prefix x	kill current pane
prefix m	mark current pane
prefix +	split vertical then close prev pane
prefix Y	split vertical then close prev pane
prefix {	rotate window
prefix }	swap pane down

Arrow Key Selection:

```
prefix Up/Down      select pane up/down
prefix Left/Right    select pane left/right
Alt-Up/Down          select pane (root table, no prefix)
Alt-Left/Right       select pane (root table, no prefix)
```

```
All hjkl/HJKL bindings are repeatable (-r flag).
Arrow keys in root table work without prefix for speed.
```

```
// the wizard navigates panes by instinct
// hjkl is muscle memory, arrows are for civilians
```

Tmux Prefix Keys: Windows & Sessions

```
window management, session juggling, the multiplexer core.
```

Window Creation & Selection:

```
prefix c            new window
prefix a            last-window (toggle to previous)
prefix 0-9          select window by number
prefix '            select window by index prompt
prefix n            next window (repeatable)
prefix p            previous window (repeatable)
prefix Ctrl-n       next window
prefix Ctrl-p       previous window
```

Window Operations:

```
prefix ,           rename current window
prefix &           kill window (with confirm)
prefix .           move window to target
prefix f           find window by name
prefix w           choose-tree window view
prefix i           display-message (window info)
prefix t           clock-mode
```

Session Management:

```
prefix $           rename current session
prefix (           switch to previous client (repeatable)
prefix )           switch to next client (repeatable)
prefix d           detach client
prefix s           choose-tree session view
prefix Ctrl-z      suspend client
```

Reload & Persist:

```
prefix r          reload tmux config + display confirmation
prefix Ctrl-s     save session (tmux-resurrect)
prefix Ctrl-r     restore session (tmux-resurrect)
```

Root Table Shortcuts:

```
Ctrl-\\          switch to next client (no prefix)
Ctrl-]           switch to prev client (no prefix)
```

Meta:

```
prefix ?         list all keys
prefix :         command prompt
prefix /         describe a key binding
prefix ~         show messages
```

```
// sessions are parallel universes
// the wizard keeps many realities open at once
```

Tmux Prefix Keys: Layouts & Pane Configs

```
preconfigured pane arrangements. instant workspaces.
```

zpwr Layout Presets:

```
prefix D          control-window layout
prefix E          four vertical panes
prefix F          four panes layout
prefix G          eight panes layout
prefix O          sixteen panes layout
prefix R          thirty-two panes REPL layout
prefix T          config files layout
prefix M          learn layout
```

```
Each layout sources a conf file from $ZPWR/tmux/:
D -> control-window.conf
E -> fourVertical.conf
F -> four-panes.conf
G -> eight-panes.conf
O -> sixteen-panes.conf
R -> thirtytwo-panes-repl.conf
T -> config-files.conf
M -> learn.conf
```

Synchronize & Customize:

```
prefix S          toggle synchronize-panes (type in all)
prefix C          customize-mode
```

Built-in Layouts (Alt+number):

```
prefix Alt-1      even-horizontal
prefix Alt-2      even-vertical
prefix Alt-3      main-horizontal
prefix Alt-4      main-vertical
prefix Alt-5      tiled
prefix Alt-6      main-horizontal-mirrored
prefix Alt-7      main-vertical-mirrored
```

Window Rotation:

```
prefix Ctrl-o      rotate window panes
prefix Alt-o        rotate window panes (reverse)
```

Synchronize-panes (prefix S) sends keystrokes to ALL panes.
Perfect for running the same command across many servers.

```
// sixteen panes is not chaos
// sixteen panes is the wizard's dashboard
```

Tmux Prefix Keys: Special Operations

multi-pane execution, URL picking, buffers, plugins.

Multi-pane Execution:

```
prefix Space      run command in all panes (single)
prefix v          run command in all panes (multi)
prefix b          open URL/path in all panes
prefix g          google search in all panes
```

These source \$ZPWR/scripts/allPanes.zsh with different modes.
Space -> single mode (one command per pane)
v -> multi mode (batch operations)
b -> single open (open URL in each pane)
g -> single google (search in each pane)

Url Handling:

```
prefix e          fzf URL picker -> open
prefix u          fzf URL picker -> search
```

Both use tmux-fzf-url plugin with 30s timeout.

Paste & Buffers:

```
prefix P      paste buffer
prefix ]      paste buffer (bracketed)
prefix =      choose-buffer (fzf style)
prefix #      list buffers
prefix Ctrl-v paste from system clipboard
```

Copy Mode:

```
prefix [      enter copy mode
prefix PgUp   enter copy mode and page up
```

Plugin Management (TPM):

```
prefix I      install plugins
prefix U      update plugins
prefix Alt-u   clean unused plugins
```

Send Prefix:

```
prefix Ctrl-a send prefix key to inner tmux
prefix Ctrl-] send literal Ctrl-]
```

Use prefix Ctrl-a when nesting tmux sessions.
The outer session captures prefix, Ctrl-a forwards it.

```
// buffers are the wizard's memory
// every copy is a spell stored for later
```

Tmux Copy Mode (vi)

tmux Copy Mode (VI Bindings)

scrollback navigation, selection, copy, search. pure vi.

Enter/exit:

```
prefix [      enter copy mode
q             cancel and exit copy mode
Escape        clear selection
```

Selection & Copy:

```
v          begin selection
V          select entire line
Ctrl-v     toggle rectangle selection
Space      begin selection (alternate)
y          copy selection to clipboard (no clear)
Enter      copy selection to clipboard and cancel
D          copy to end of line and cancel
A          append selection and cancel
```

Navigation:

```
h/j/k/l    cursor movement
Ctrl-h/j/k/l  move cursor 4 cells at a time
w/b/e      word forward/backward/end
W/B/E      WORD (space-delimited) movement
0 / $      start/end of line
^          first non-blank character
g / G      top / bottom of history
H / M / L  top / middle / bottom of screen
```

Scrolling:

```
Ctrl-u / Ctrl-d  half page up / down
Ctrl-b / Ctrl-f  full page up / down
Ctrl-y / Ctrl-e  scroll up / down one line
J / K           scroll down / up one line
```

Search:

```
/          search forward (incremental)
?          search backward (incremental)
n / N      next / previous match
*          search forward for word under cursor
#          search backward for word under cursor
```

zpwr Extensions:

```
s          copy + google search selection
x          copy + open URL selection
z          copy + google search selection
RightClick copy + google search selection
```

```
Copy goes to system clipboard via reattach-to-user-namespace pbcopy.
ZPWR extends vi copy mode with instant google/open actions.
```

```
// in copy mode the wizard moves through time
// scrollbar is archaeology, search is divination
```

Zsh Insert Mode: Basic & Movement

the primary editing mode. where commands are born.

Line Movement:

Ctrl-A	beginning-of-line
Ctrl-E	end-of-line
Ctrl-O	EOL or next tab stop

Editing:

Ctrl-U	clear entire line
Ctrl-W	delete word backward (autopair)
Ctrl-H	delete char backward (autopair)
Ctrl-Y	change surrounding quotes
Ctrl-Z	undo
Ctrl-R	redo
Ctrl-Q	duplicate last word

zpwz Special:

Space	zpwz supernatural expand (aliases+globs)
Ctrl-@	zpwz expand + terminate space
Ctrl-M (Enter)	zpwz magic enter (show status on empty)
.	zpwz rationalize dot (.. -> ../..)
Ctrl-B	zpwz clipboard paste
Ctrl-S	git add commit push (no check)
Ctrl-K	zsh-learn-Learn (flashcard)

Completion & Fzf:

Tab (Ctrl-I)	fzf-completion
Ctrl-D	list-choices
Ctrl-L	clear-screen
Ctrl-T	fzf file widget
Alt-c	fzf cd widget

History:

Ctrl-N	down-history
Ctrl-P	up-history
Up/Down arrows	history substring search up/down

Mode Switching:

Escape	enter vi command mode
jf / fj	enter vi command mode (chord escape)

Surround & Pairs:

```
" ' ( [ { \ `      auto-pair/surround insert
) ] }              autopair close
Backspace          autopair-aware delete
```

Space is the most powerful key: it expands aliases, global aliases, and abbreviations before inserting.

```
// insert mode is where spells are typed
// every keystroke is an incantation
```

Zsh Insert Mode: Ctrl-F & Ctrl-V Chords

two-key combos that unlock the full zpwr arsenal.

Ctrl-F Chords (fzf & Actions):

```
Ctrl-F Ctrl-D      pipe buffer into fzf
Ctrl-F Ctrl-F      cd + vim fzf file search (accept)
Ctrl-F Ctrl-G      google search
Ctrl-F Ctrl-H      lsof into fzf
Ctrl-F Ctrl-I      ag (silver searcher) into fzf
Ctrl-F Ctrl-J      zpwr verbs widget (accept)
Ctrl-F Ctrl-K      alternate quotes around buffer
Ctrl-F Ctrl-L      list choices
Ctrl-F Ctrl-M      zzcomplete
Ctrl-F Ctrl-N      zpwr verbs widget (browse)
Ctrl-F Ctrl-O      open URL from buffer
Ctrl-F Ctrl-P      basic sed substitution
Ctrl-F Ctrl-R      wrap buffer as variable
Ctrl-F Ctrl-S      git diff check (gacp)
Ctrl-F Ctrl-V      edit command line in $EDITOR
Ctrl-F j           zpwr verbs widget (accept)
Ctrl-F n           zpwr verbs widget (browse)
```

Ctrl-v Chords (vim/fzf/navigation):

```
Ctrl-V Ctrl-@      vim fzf (open file in vim)
Ctrl-V Space        vim fzf (open file in vim)
Ctrl-V Ctrl-F       fasd fzf (frecency file open)
Ctrl-V Ctrl-G       fzf cd widget
Ctrl-V Ctrl-K       emacs fzf
Ctrl-V Ctrl-L       z fzf (frecency dirs)
Ctrl-V Ctrl-N       vim fzf sudo
Ctrl-V Ctrl-O       fzf tab complete
Ctrl-V Ctrl-P       sudo command line toggle
Ctrl-V Ctrl-R       history search multi-word
Ctrl-V Ctrl-S       z fzf (alternate)
Ctrl-V Ctrl-V       vim all files widget (accept)
Ctrl-V Ctrl-Z       fzf history widget
Ctrl-V ,            fzf environment variables
Ctrl-V .            fzf all keybindings
```

Ctrl-V // locate fzf

```
Ctrl-V /.      locate fzf + edit
Ctrl-V ;       fzf surround
Ctrl-V c       fzf git commits
Ctrl-V k       fzf vim keybindings
Ctrl-V m       vim all files widget (browse)
Ctrl-V v       vim all files widget (accept)
```

```
Ctrl-F is the action chord: search, edit, google, diff.
Ctrl-V is the vim/fzf chord: open files, browse, navigate.
```

```
// chords are the wizard's combos
// two keys unlock what single keys cannot reach
```

Zsh Visual & Menu Select Modes

```
text objects, selection, and completion menu navigation.
```

Visual Mode (enter With V/v In Vicmd):

```
Escape        deactivate region
j / k         move selection down / up
o             exchange point and mark
p             put replace selection
x             delete selection
u             downcase selection
U             upcase selection
~            swap case of selection
```

Text Objects (a = Around, I = Inner):

```
a" / i"       select around/inner double quotes
a' / i'       select around/inner single quotes
a` / i`       select around/inner backticks
a( / i(       select around/inner parentheses
a[ / i[       select around/inner brackets
a{ / i{       select around/inner braces
a< / i<       select around/inner angle brackets
aB / iB       select around/inner block
aw / iw       select a word / in word
aW / iW       select a blank word / in blank word
aa / ia       select a shell word / in shell word
```

```
Extended quote chars also work as text objects:
+ , - . / : ; = @ | \\\ are all valid quote delimiters.
```

Menu Select Mode (during Completion):

```
Ctrl-J / Ctrl-K      move down / up in menu
Ctrl-H / Ctrl-L      move left / right in menu
Tab / Ctrl-I         move forward (next item)
Ctrl-S / Shift-Tab   reverse menu complete
Ctrl-@ (Ctrl-Space)  accept line
Ctrl-D              accept and menu complete (stay open)
Ctrl-F              accept and infer next
Ctrl-M (Enter)       accept line (.accept-line)
Ctrl-V              insert mode within menu
Ctrl-N / Ctrl-P      forward / backward word in menu
Ctrl-X              incremental search forward in menu
?                   incremental search backward in menu
.                   self-insert (exit menu + type dot)
Backspace           undo last menu selection
```

Menu select uses hjkl-style navigation with Ctrl prefix.
Ctrl-D is key: accept current match but keep menu open.

```
// visual mode is precision surgery
// select only what you need, transform only what you touch
```

Vim Normal Mode Highlights

vim Normal Mode: zpwr Highlights

leader mappings, fzf integration, tmux synergy.
leader key is Space. only zpwr-specific bindings listed.

File & Buffer (Space Prefix):

```
Space w              :w! (force write)
Space e              :q! (force quit)
Space q              :qa! (quit all)
Space wq             :wq! (write and quit)
Space n / Space p    next / prev buffer
Space an / Space ap  next / prev in arglist
Space Tab            alternate or next buffer
Space t              new tab
Space s / Space v    horizontal / vertical split
```

fzf Integration (Space Prefix):

```
Space f      :Files! (fzf files)
Space b      :Buffers! (fzf buffers)
Space j      :Lines! (fzf lines)
Space ag     :Ag (silver searcher)
Space aa     :Agg (ag variant)
Space rg     :Rg (ripgrep)
Space z      :Commits! (fzf git commits)
Space ;      :Commands! (fzf commands)
Space ,      :FZFMaps (fzf all mappings)
Space ke / , / m / i  fzf keys / maps / nmap / imap
Space ta / ma / env  fzf tags / marks / env vars
Space / / .         locate all / colorscheme picker
```

History (Space Prefix):

```
Space hh     :History! (fzf file history)
Space h/     :History/! (fzf search history)
Space h:     :History:! (fzf command history)
```

Search & Replace (Space Prefix):

```
Space r      replace word under cursor (whole file)
Space g      global substitute word under cursor
Space x      repeat last substitution on line
n / N       next / prev search (centered)
z/          toggle auto-highlight word under cursor
```

Git & Tmux:

```
Space hs     GitGutter stage hunk
Space hu     GitGutter undo hunk
Space hp     GitGutter preview hunk
[c / ]c      prev / next git hunk
Space vj     save + TmuxRepeat file
Space os / ox / oc  google / open URL / copy word
```

Minimap & Comments:

```
Space mm     open minimap
Space mt     toggle minimap
Space cc     NERDCommenter comment
Space c Space NERDCommenter toggle
Space cu     NERDCommenter uncomment
```

```
// the leader key is Space because power needs room
// every binding is one thought away from execution
```

Vim Insert & Visual Mode + Keybinding Search

vim mode highlights and how to find any keybinding.

vim Insert Mode Highlights:

Ctrl-A	jump to first non-blank (like ^)
Ctrl-E	end of line or dismiss popup
Ctrl-D	delete char forward or default
Ctrl-F	move right or scroll
Ctrl-S	isurround (surround insert)
Ctrl-G s / S	isurround / ISurround (line)
Ctrl-Tab	list ultisnips snippets
Shift-Tab	SuperTab backward completion
Alt-d	delete word forward
" ' () [] \ ` { }	delimitMate auto-pairing

vim Visual Mode Highlights:

Space r	replace word in selection range
Space g	global substitute in selection range
Space x	repeat last sub on selected lines
Space " ' \ ` ([{	surround selection with quote/bracket
Space b	copy selection to tmux buffer
Space = / Space -	grow / shrink selection (4 lines)
J / K	move selected lines down / up
Y	yank and move to end
< / >	indent / outdent (stay in visual)
S	vim-surround visual surround
go	copy selection + open as URL
gs	copy selection + google search
Space vl / vk / vj	TmuxRepeat repl / visual / file
Space em / ev / ef	extract method / variable / fold

Sneak & Motion:

s / S	sneak forward / backward (2-char)
f / F / t / T	sneak-enhanced find char
; / ,	repeat / reverse last sneak/find
w / b / e	CamelCaseMotion word movement

=

How To Search Keybindings:

=

zpwir allsearch	search ALL keybindings in fzf
zpwir vimsearch	search vim keybindings in fzf
zpwir zshsearch	search zsh keybindings in fzf

Keybinding Cache Files:

```
$ZPWR_LOCAL/zpwrAllKeybindings.txt  
$ZPWR_LOCAL/zpwr{Vim,Zsh,Tmux}Keybindings.txt
```

Regenerate:

```
zpwr regenkeybindings  regenerate all keybinding caches
```

Cache files are auto-generated. Run `regenkeybindings` after adding new bindings to refresh the searchable index.

```
// the wizard does not memorize 4000 keybindings  
// the wizard searches them at the speed of thought  
// fzf is the oracle, the cache is the grimoire
```

Appendix B – Complete Keybinding Dump

ALL Tmux Prefix Keys (1/4)

```
bind-key -T prefix Space run-shell -b 'ZPWR/scripts/allPanes.zsh single
bind-key -T prefix . break-pane
bind-key -T prefix \ ' split-window
bind-key -T prefix \# list-buffers
bind-key -T prefix \ command-prompt -I '#S' { rename-session '%' }
bind-key -T prefix \% split-window -h
bind-key -T prefix & confirm-before -p 'kill-window #W? (y/n)' kill-win
bind-key -T prefix \ ' command-prompt -T window-target -p index { selec
bind-key -r -T prefix ( switch-client -p
bind-key -r -T prefix ) switch-client -n
bind-key -T prefix + split-window -v -c '#{pane_current_path}' \; sele
bind-key -T prefix , command-prompt -I '#W' { rename-window '%' }
bind-key -T prefix - split-window -v -c '#{pane_current_path}'
bind-key -T prefix . command-prompt -T target { move-window -t '%' }
bind-key -T prefix / command-prompt -k -p key { list-keys -1N '%' }
bind-key -T prefix 0 select-window -t :=0
bind-key -T prefix 1 select-window -t :=1
bind-key -T prefix 2 select-window -t :=2
bind-key -T prefix 3 select-window -t :=3
bind-key -T prefix 4 select-window -t :=4
bind-key -T prefix 5 select-window -t :=5
bind-key -T prefix 6 select-window -t :=6
bind-key -T prefix 7 select-window -t :=7
bind-key -T prefix 8 select-window -t :=8
bind-key -T prefix 9 select-window -t :=9
bind-key -T prefix : command-prompt
bind-key -T prefix \; last-pane
bind-key -T prefix < display-menu -T '#[align=centre]#{window_index}:#{
bind-key -T prefix = choose-buffer -Z
bind-key -T prefix > display-menu -T '#[align=centre]#{pane_index} ({#p
bind-key -T prefix ? list-keys -N
bind-key -T prefix C customize-mode -Z
bind-key -T prefix D source-file ZPWR/tmux/control-window.conf
bind-key -T prefix E source-file ZPWR/tmux/fourVertical.conf
bind-key -T prefix F source-file ZPWR/tmux/four-panes.conf
bind-key -T prefix G source-file ZPWR/tmux/eight-panes.conf
bind-key -r -T prefix H resize-pane -L 5
bind-key -T prefix I run-shell HOME/.tmux/plugins/tpm/bindings/install_
bind-key -r -T prefix J resize-pane -D 5
bind-key -r -T prefix K resize-pane -U 5
bind-key -r -T prefix L resize-pane -R 5
bind-key -T prefix M source-file ZPWR/tmux/learn.conf
bind-key -T prefix O source-file ZPWR/tmux/sixteen-panes.conf
bind-key -T prefix P paste-buffer
bind-key -T prefix R source-file ZPWR/tmux/thirtytwo-panes-repl.conf
bind-key -T prefix S set-window-option synchronize-panes
bind-key -T prefix T source-file ZPWR/tmux/config-files.conf
bind-key -T prefix U run-shell HOME/.tmux/plugins/tpm/bindings/update_p
```

ALL Tmux Prefix Keys (2/4)

```
bind-key -T prefix Y split-window -v -c '#{pane_current_path}' \; sele
bind-key -T prefix [ copy-mode
bind-key -T prefix \\\ split-window -h -c '#{pane_current_path}'
bind-key -T prefix ] paste-buffer -p
bind-key -T prefix _ split-window -v
bind-key -T prefix a last-window
bind-key -T prefix b run-shell -b 'ZPWR/scripts/allPanes.zsh single ope
bind-key -T prefix c new-window
bind-key -T prefix d detach-client
bind-key -T prefix e run-shell -b 'HOME/.tmux/plugins/tmux-fzf-url/fzf-
bind-key -T prefix f command-prompt { find-window -Z '%%' }
bind-key -T prefix g run-shell -b 'ZPWR/scripts/allPanes.zsh single goo
bind-key -r -T prefix h select-pane -L
bind-key -T prefix i display-message
bind-key -r -T prefix j select-pane -D
bind-key -r -T prefix k select-pane -U
bind-key -r -T prefix l select-pane -R
bind-key -T prefix m select-pane -m
bind-key -r -T prefix n next-window
bind-key -T prefix o select-pane -t :.+
bind-key -r -T prefix p previous-window
bind-key -T prefix q display-panes -d 5000
bind-key -T prefix r source-file ZPWR/tmux/init.conf \; display-messag
bind-key -T prefix s choose-tree -Zs
bind-key -T prefix t clock-mode
bind-key -T prefix u run-shell -b 'HOME/.tmux/plugins/tmux-fzf-url/fzf-
bind-key -T prefix v run-shell -b 'ZPWR/scripts/allPanes.zsh multi'
bind-key -T prefix w choose-tree -Zw
bind-key -T prefix x kill-pane
bind-key -T prefix z resize-pane -Z
bind-key -r -T prefix \{ rotate-window
bind-key -T prefix | split-window -h
bind-key -T prefix \} swap-pane -D
bind-key -T prefix \~ show-messages
bind-key -r -T prefix DC refresh-client -c
bind-key -T prefix PPage copy-mode -u
bind-key -r -T prefix Up select-pane -U
bind-key -r -T prefix Down select-pane -D
bind-key -r -T prefix Left select-pane -L
bind-key -r -T prefix Right select-pane -R
bind-key -T prefix M-1 select-layout even-horizontal
bind-key -T prefix M-2 select-layout even-vertical
bind-key -T prefix M-3 select-layout main-horizontal
bind-key -T prefix M-4 select-layout main-vertical
bind-key -T prefix M-5 select-layout tiled
bind-key -T prefix M-6 select-layout main-horizontal-mirrored
bind-key -T prefix M-7 select-layout main-vertical-mirrored
bind-key -T prefix M-n next-window -a
```

ALL Tmux Prefix Keys (3/4)

```
bind-key -T prefix M-o rotate-window -D
bind-key -T prefix M-p previous-window -a
bind-key -T prefix M-u run-shell HOME/.tmux/plugins/tpm/bindings/clean_
bind-key -r -T prefix M-Up resize-pane -U 5
bind-key -r -T prefix M-Down resize-pane -D 5
bind-key -r -T prefix M-Left resize-pane -L 5
bind-key -r -T prefix M-Right resize-pane -R 5
bind-key -T prefix C-] send-keys ^]
bind-key -T prefix C-a send-prefix
bind-key -T prefix C-n next-window
bind-key -T prefix C-o rotate-window
bind-key -T prefix C-p previous-window
bind-key -T prefix C-r run-shell HOME/.tmux/plugins/tmux-resurrect/scri
bind-key -T prefix C-s run-shell HOME/.tmux/plugins/tmux-resurrect/scri
bind-key -T prefix C-v run-shell 'tmux set buffer \'(reattach-to-user-
bind-key -T prefix C-z suspend-client
bind-key -r -T prefix C-Up resize-pane -U
bind-key -r -T prefix C-Down resize-pane -D
bind-key -r -T prefix C-Left resize-pane -L
bind-key -r -T prefix C-Right resize-pane -R
bind-key -r -T prefix S-Up refresh-client -U 10
bind-key -r -T prefix S-Down refresh-client -D 10
bind-key -r -T prefix S-Left refresh-client -L 10
bind-key -r -T prefix S-Right refresh-client -R 10
i <C-X><C-L> * fzf#vim#complete(fzf#wrap({ 'prefix': '^.*', 'source': 'r
<Space><Space> <Plug>(easymotion-prefix)
<Plug>(easymotion-prefix)N <Plug>(easymotion-N)
<Plug>(easymotion-prefix)n <Plug>(easymotion-n)
<Plug>(easymotion-prefix)k <Plug>(easymotion-k)
<Plug>(easymotion-prefix)j <Plug>(easymotion-j)
<Plug>(easymotion-prefix)gE <Plug>(easymotion-gE)
<Plug>(easymotion-prefix)ge <Plug>(easymotion-ge)
<Plug>(easymotion-prefix)E <Plug>(easymotion-E)
<Plug>(easymotion-prefix)e <Plug>(easymotion-e)
<Plug>(easymotion-prefix)B <Plug>(easymotion-B)
<Plug>(easymotion-prefix)b <Plug>(easymotion-b)
<Plug>(easymotion-prefix)W <Plug>(easymotion-W)
<Plug>(easymotion-prefix)w <Plug>(easymotion-w)
<Plug>(easymotion-prefix)T <Plug>(easymotion-T)
<Plug>(easymotion-prefix)t <Plug>(easymotion-t)
<Plug>(easymotion-prefix)s <Plug>(easymotion-s)
<Plug>(easymotion-prefix)F <Plug>(easymotion-F)
<Plug>(easymotion-prefix)f <Plug>(easymotion-f)
<Space><Space> <Plug>(easymotion-prefix)
<Plug>(easymotion-prefix)N <Plug>(easymotion-N)
<Plug>(easymotion-prefix)n <Plug>(easymotion-n)
<Plug>(easymotion-prefix)k <Plug>(easymotion-k)
<Plug>(easymotion-prefix)j <Plug>(easymotion-j)
```

ALL Tmux Prefix Keys (4/4)

```
<Plug>(easymotion-prefix)gE <Plug>(easymotion-gE)
<Plug>(easymotion-prefix)ge <Plug>(easymotion-ge)
<Plug>(easymotion-prefix)E <Plug>(easymotion-E)
<Plug>(easymotion-prefix)e <Plug>(easymotion-e)
<Plug>(easymotion-prefix)B <Plug>(easymotion-B)
<Plug>(easymotion-prefix)b <Plug>(easymotion-b)
<Plug>(easymotion-prefix)W <Plug>(easymotion-W)
<Plug>(easymotion-prefix)w <Plug>(easymotion-w)
<Plug>(easymotion-prefix)T <Plug>(easymotion-T)
<Plug>(easymotion-prefix)t <Plug>(easymotion-t)
<Plug>(easymotion-prefix)s <Plug>(easymotion-s)
<Plug>(easymotion-prefix)F <Plug>(easymotion-F)
<Plug>(easymotion-prefix)f <Plug>(easymotion-f)
```

ALL Tmux Copy-Mode-Vi (1/2)

```
bind-key -T copy-mode-vi Enter send-keys -X copy-pipe-and-cancel 'reatta
bind-key -T copy-mode-vi Escape send-keys -X clear-selection
bind-key -T copy-mode-vi Space send-keys -X begin-selection
bind-key -T copy-mode-vi \# send-keys -FX search-backward -- '#{copy_cu
bind-key -T copy-mode-vi \ send-keys -X end-of-line
bind-key -T copy-mode-vi \% send-keys -X next-matching-bracket
bind-key -T copy-mode-vi * send-keys -FX search-forward -- '#{copy_curso
bind-key -T copy-mode-vi , send-keys -X jump-reverse
bind-key -T copy-mode-vi / command-prompt -i -p '(search down)' 'send -X
bind-key -T copy-mode-vi 0 send-keys -X start-of-line
bind-key -T copy-mode-vi 1 command-prompt -N -I 1 -p (repeat) { send-key
bind-key -T copy-mode-vi 2 command-prompt -N -I 2 -p (repeat) { send-key
bind-key -T copy-mode-vi 3 command-prompt -N -I 3 -p (repeat) { send-key
bind-key -T copy-mode-vi 4 command-prompt -N -I 4 -p (repeat) { send-key
bind-key -T copy-mode-vi 5 command-prompt -N -I 5 -p (repeat) { send-key
bind-key -T copy-mode-vi 6 command-prompt -N -I 6 -p (repeat) { send-key
bind-key -T copy-mode-vi 7 command-prompt -N -I 7 -p (repeat) { send-key
bind-key -T copy-mode-vi 8 command-prompt -N -I 8 -p (repeat) { send-key
bind-key -T copy-mode-vi 9 command-prompt -N -I 9 -p (repeat) { send-key
bind-key -T copy-mode-vi : command-prompt -p '(goto line)' { send-keys -
bind-key -T copy-mode-vi \; send-keys -X jump-again
bind-key -T copy-mode-vi ? command-prompt -i -p '(search up)' 'send -X s
bind-key -T copy-mode-vi A send-keys -X append-selection-and-cancel
bind-key -T copy-mode-vi B send-keys -X previous-space
bind-key -T copy-mode-vi D send-keys -X copy-pipe-end-of-line-and-cancel
bind-key -T copy-mode-vi E send-keys -X next-space-end
bind-key -T copy-mode-vi F command-prompt -l -p '(jump backward)' { send
bind-key -T copy-mode-vi G send-keys -X history-bottom
bind-key -T copy-mode-vi H send-keys -X top-line
bind-key -T copy-mode-vi J send-keys -X scroll-down
bind-key -T copy-mode-vi K send-keys -X scroll-up
bind-key -T copy-mode-vi L send-keys -X bottom-line
bind-key -T copy-mode-vi M send-keys -X middle-line
bind-key -T copy-mode-vi N send-keys -X search-reverse
bind-key -T copy-mode-vi P send-keys -X toggle-position
bind-key -T copy-mode-vi T command-prompt -l -p '(jump to backward)' { s
bind-key -T copy-mode-vi V send-keys -X select-line
bind-key -T copy-mode-vi W send-keys -X next-space
bind-key -T copy-mode-vi X send-keys -X set-mark
bind-key -T copy-mode-vi ^ send-keys -X back-to-indentation
bind-key -T copy-mode-vi b send-keys -X previous-word
bind-key -T copy-mode-vi e send-keys -X next-word-end
bind-key -T copy-mode-vi f command-prompt -l -p '(jump forward)' { send-
bind-key -T copy-mode-vi g send-keys -X history-top
bind-key -T copy-mode-vi h send-keys -X cursor-left
bind-key -T copy-mode-vi j send-keys -X cursor-down
bind-key -T copy-mode-vi k send-keys -X cursor-up
bind-key -T copy-mode-vi l send-keys -X cursor-right
```

ALL Tmux Copy-Mode-Vi (2/2)

```
bind-key -T copy-mode-vi n send-keys -X search-again
bind-key -T copy-mode-vi o send-keys -X other-end
bind-key -T copy-mode-vi q send-keys -X cancel
bind-key -T copy-mode-vi r send-keys -X refresh-from-pane
bind-key -T copy-mode-vi s send-keys -X copy-pipe-no-clear 'reattach-to-
bind-key -T copy-mode-vi t command-prompt -l -p '(jump to forward)' { se
bind-key -T copy-mode-vi v send-keys -X begin-selection
bind-key -T copy-mode-vi w send-keys -X next-word
bind-key -T copy-mode-vi x send-keys -X copy-pipe-no-clear 'reattach-to-
bind-key -T copy-mode-vi y send-keys -X copy-pipe-no-clear 'reattach-to-
bind-key -T copy-mode-vi z send-keys -X copy-pipe-no-clear 'reattach-to-
bind-key -T copy-mode-vi \{ send-keys -X previous-paragraph
bind-key -T copy-mode-vi \} send-keys -X next-paragraph
bind-key -T copy-mode-vi WheelUpPane select-pane \; send-keys -X -N 5 s
bind-key -T copy-mode-vi WheelDownPane select-pane \; send-keys -X -N 5
bind-key -T copy-mode-vi DoubleClick1Pane select-pane \; send-keys -X s
bind-key -T copy-mode-vi TripleClick1Pane select-pane \; send-keys -X s
bind-key -T copy-mode-vi BSpace send-keys -X cursor-left
bind-key -T copy-mode-vi Home send-keys -X start-of-line
bind-key -T copy-mode-vi End send-keys -X end-of-line
bind-key -T copy-mode-vi NPage send-keys -X page-down
bind-key -T copy-mode-vi PPage send-keys -X page-up
bind-key -T copy-mode-vi Up send-keys -X cursor-up
bind-key -T copy-mode-vi Down send-keys -X cursor-down
bind-key -T copy-mode-vi Left send-keys -X cursor-left
bind-key -T copy-mode-vi Right send-keys -X cursor-right
bind-key -T copy-mode-vi M-x send-keys -X jump-to-mark
bind-key -T copy-mode-vi C-b send-keys -X page-up
bind-key -T copy-mode-vi C-c send-keys -X cancel
bind-key -T copy-mode-vi C-d send-keys -X halfpagE-down
bind-key -T copy-mode-vi C-e send-keys -X scroll-down
bind-key -T copy-mode-vi C-f send-keys -X page-down
bind-key -T copy-mode-vi C-h send-keys -X -N 4 cursor-left
bind-key -T copy-mode-vi C-j send-keys -X -N 4 cursor-down
bind-key -T copy-mode-vi C-k send-keys -X -N 4 cursor-up
bind-key -T copy-mode-vi C-l send-keys -X -N 4 cursor-right
bind-key -T copy-mode-vi C-n send-keys -X page-down
bind-key -T copy-mode-vi C-p send-keys -X page-up
bind-key -T copy-mode-vi C-u send-keys -X halfpagE-up
bind-key -T copy-mode-vi C-v send-keys -X rectangle-toggle
bind-key -T copy-mode-vi C-y send-keys -X scroll-up
bind-key -T copy-mode-vi C-Up send-keys -X scroll-up
bind-key -T copy-mode-vi C-Down send-keys -X scroll-down
```

ALL Zsh Insert Mode (1/3)

```
bindkey -M viins '^@' zpwrExpandTerminateSpace
bindkey -M viins '^A' beginning-of-line
bindkey -M viins '^B' zpwrClipboard
bindkey -M viins '^C' self-insert
bindkey -M viins '^D' list-choices
bindkey -M viins '^E' end-of-line
bindkey -M viins '^F^D' zpwrIntoFzf
bindkey -M viins '^F^F' zpwrCdVimFzfFilesearchWidgetAccept
bindkey -M viins '^F^G' zpwrGoogle
bindkey -M viins '^F^H' zpwrLsoffzf
bindkey -M viins '^F^I' zpwrIntoFzfAg
bindkey -M viins '^F^J' zpwrVerbsWidgetAccept
bindkey -M viins '^F^K' zpwrAlternateQuotes
bindkey -M viins '^F^L' list-choices
bindkey -M viins '^F^M' zzcomplete
bindkey -M viins '^F^N' zpwrVerbsWidget
bindkey -M viins '^F^O' zpwrOpen
bindkey -M viins '^F^P' basicSedSub
bindkey -M viins '^F^R' zpwrAsVar
bindkey -M viins '^F^S' zsh-gacp-CheckDiff
bindkey -M viins '^F^V' edit-command-line
bindkey -M viins '^Fj' zpwrVerbsWidgetAccept
bindkey -M viins '^Fn' zpwrVerbsWidget
bindkey -M viins '^G' what-cursor-position
bindkey -M viins '^H' autopair-delete
bindkey -M viins '^I' fzf-completion
bindkey -M viins '^J' accept-line
bindkey -M viins '^K' zsh-learn-learn
bindkey -M viins '^L' clear-screen
bindkey -M viins '^M' zpwrMagicEnter
bindkey -M viins '^N' down-history
bindkey -M viins '^O' zpwrEOLOrNextTabStop
bindkey -M viins '^O^I' zc-Logo
bindkey -M viins '^O^Z' zui-demo-various
bindkey -M viins '^P' up-history
bindkey -M viins '^Q' zpwrLastWordDouble
bindkey -M viins '^R' redo
bindkey -M viins '^S' zsh-gacp-NoCheck
bindkey -M viins '^T' fzf-file-widget
bindkey -M viins '^U' zpwrClearLine
bindkey -M viins '^V^@' zpwrVimFzf
bindkey -M viins '^V^F' zpwrFasdFZF
bindkey -M viins '^V^G' fzf-cd-widget
bindkey -M viins '^V^K' zpwrEmacsFzf
bindkey -M viins '^V^L' zpwrZFZF
bindkey -M viins '^V^N' zpwrVimFzfSudo
bindkey -M viins '^V^O' fzf-tab-complete
bindkey -M viins '^V^P' sudo-command-line
```

ALL Zsh Insert Mode (2/3)

```
bindkey -M viins '^V^R' history-search-multi-word
bindkey -M viins '^V^S' zpwrZFZF
bindkey -M viins '^V^V' zpwrVimAllWidgetAccept
bindkey -M viins '^V^Z' fzf-history-widget
bindkey -M viins '^V ' zpwrVimFzf
bindkey -M viins '^V,' zpwrFzfEnv
bindkey -M viins '^V.' zpwrFzfAllKeybind
bindkey -M viins '^V/.' zpwrLocateFzfEdit
```

bindkey -M viins '^V//' zpwrLocateFzf

```
bindkey -M viins '^V;' zpwrFzfSurround
bindkey -M viins '^Vc' zpwrFzfCommits
bindkey -M viins '^Vk' zpwrFzfVimKeybind
bindkey -M viins '^Vl' zpwrZFZF
bindkey -M viins '^Vm' zpwrVimAllWidget
bindkey -M viins '^Vv' zpwrVimAllWidgetAccept
bindkey -M viins '^W' autopair-delete-word
bindkey -M viins '^X^R' _read_comp
bindkey -M viins '^X^X' zpwrBufferXtrace
bindkey -M viins '^X?' _complete_debug
bindkey -M viins '^XC' _correct_filename
bindkey -M viins '^Xa' _expand_alias
bindkey -M viins '^Xc' _correct_word
bindkey -M viins '^Xd' _list_expansions
bindkey -M viins '^Xe' _expand_word
bindkey -M viins '^Xh' _complete_help
bindkey -M viins '^Xm' _most_recent_file
bindkey -M viins '^Xn' _next_tags
bindkey -M viins '^Xt' _complete_tag
bindkey -M viins '^X~' _bash_list-choices
bindkey -M viins '^Y' zpwrChangeQuotes
bindkey -M viins '^Z' undo
bindkey -M viins '^[' vi-cmd-mode
bindkey -M viins '^[_D' capitalize-word
bindkey -M viins '^[_E' zpwrExpandGlobalAliases
bindkey -M viins '^[_F' sub
bindkey -M viins '^[_L' down-case-word
bindkey -M viins '^[_M' self-insert-unmeta
bindkey -M viins '^[_O' zpwrRunner
bindkey -M viins '^[_P' zpwrUp8widget
bindkey -M viins '^[_T' transpose-words
bindkey -M viins '^[_U' up-case-word
bindkey -M viins '^[' ' zpwrSshRegain
bindkey -M viins '^[, ' _history-complete-newer
bindkey -M viins '^[/ ' _history-complete-older
bindkey -M viins '^[OA' history-substring-search-up
bindkey -M viins '^[OB' history-substring-search-down
bindkey -M viins '^[OC' vi-forward-char
bindkey -M viins '^[OD' vi-backward-char
```

ALL Zsh Insert Mode (3/3)

```
bindkey -M viins '^[OP' zpwrUp8widget
bindkey -M viins '^[OQ' sub
bindkey -M viins '^[OQ^[OQ' npm_toggle_install_uninstall
bindkey -M viins '^[OR' zpwrGetrcWidget
bindkey -M viins '^[Q' zi-browse-symbol
bindkey -M viins '^[[1;2D' sub
bindkey -M viins '^[[1;5A' zsh-gacp-CheckDiff
bindkey -M viins '^[[1;5B' zpwrUpdater
bindkey -M viins '^[[1;5C' zpwrTutsUpdate
bindkey -M viins '^[[1;5D' dbz
bindkey -M viins '^[[200~' bracketed-paste
bindkey -M viins '^[[5~' zpwrClipboard
bindkey -M viins '^[[A' history-substring-search-up
bindkey -M viins '^[[B' history-substring-search-down
bindkey -M viins '^[[C' vi-forward-char
bindkey -M viins '^[[D' vi-backward-char
bindkey -M viins '^[[Z' zpwrClipboard
bindkey -M viins '^[c' fzf-cd-widget
bindkey -M viins '^[man' man-command-line
bindkey -M viins '^[_' _bash_complete-word
bindkey -R -M viins '^\\\\"'^^' self-insert
bindkey -M viins '^_' zpwrAsVar
bindkey -M viins '^`' zpwrExpandSupernaturalSpace
bindkey -M viins '^.' self-insert
bindkey -M viins '^\'' zpwrInterceptSurround
bindkey -R -M viins '^#'-^&' self-insert
bindkey -R -M viins '^''-^(' zpwrInterceptSurround
bindkey -M viins '^)' autopair-close
bindkey -R -M viins '^*-^-' self-insert
bindkey -M viins '^.' zpwrRationalizeDot
bindkey -R -M viins '^/'-^Z' self-insert
bindkey -M viins '^[' zpwrInterceptSurround
bindkey -M viins '^\\\\"' self-insert
bindkey -M viins '^]' autopair-close
bindkey -R -M viins '^\\^'-^_' self-insert
bindkey -M viins '^\'' zpwrInterceptSurround
bindkey -R -M viins '^a'-^f' self-insert
bindkey -M viins '^fj' vi-cmd-mode
bindkey -R -M viins '^g'-^j' self-insert
bindkey -M viins '^jf' vi-cmd-mode
bindkey -R -M viins '^k'-^z' self-insert
bindkey -M viins '^{' zpwrInterceptSurround
bindkey -M viins '^|' self-insert
bindkey -M viins '^}' autopair-close
bindkey -M viins '^~' self-insert
bindkey -M viins '^?' zpwrInterceptDelete
bindkey -R -M viins '^\\M-^@'-^\\M-^?' self-insert
```

ALL Zsh Visual Mode (1/2)

```
bindkey -a 'V' visual-line-mode
bindkey -a 'v' visual-mode
bindkey -M visual '^[' deactivate-region
bindkey -M visual '^['OA' up-line
bindkey -M visual '^['OB' down-line
bindkey -M visual '^['[A' up-line
bindkey -M visual '^['[B' down-line
bindkey -M visual '-' vi-up-line-or-history
bindkey -M visual 'U' vi-up-case
bindkey -M visual 'a\" select-quoted
bindkey -M visual 'a' select-quoted
bindkey -M visual 'a(' select-bracketed
bindkey -M visual 'a)' select-bracketed
bindkey -M visual 'a+' select-quoted
bindkey -M visual 'a,' select-quoted
bindkey -M visual 'a-' select-quoted
bindkey -M visual 'a.' select-quoted
bindkey -M visual 'a/' select-quoted
bindkey -M visual 'a:' select-quoted
bindkey -M visual 'a;' select-quoted
bindkey -M visual 'a<' select-bracketed
bindkey -M visual 'a=' select-quoted
bindkey -M visual 'a>' select-bracketed
bindkey -M visual 'a@' select-quoted
bindkey -M visual 'aB' select-bracketed
bindkey -M visual 'aW' select-a-blank-word
bindkey -M visual 'a[' select-bracketed
bindkey -M visual 'a\\' select-quoted
bindkey -M visual 'a]' select-bracketed
bindkey -M visual 'a\" select-quoted
bindkey -M visual 'aa' select-a-shell-word
bindkey -M visual 'ab' select-bracketed
bindkey -M visual 'aw' select-a-word
bindkey -M visual 'a{' select-bracketed
bindkey -M visual 'a|' select-quoted
bindkey -M visual 'a}' select-bracketed
bindkey -M visual 'i\" select-quoted
bindkey -M visual 'i' select-quoted
bindkey -M visual 'i(' select-bracketed
bindkey -M visual 'i)' select-bracketed
bindkey -M visual 'i+' select-quoted
bindkey -M visual 'i,' select-quoted
bindkey -M visual 'i-' select-quoted
bindkey -M visual 'i.' select-quoted
bindkey -M visual 'i/' select-quoted
bindkey -M visual 'i:' select-quoted
bindkey -M visual 'i;' select-quoted
bindkey -M visual 'i<' select-bracketed
```

ALL Zsh Visual Mode (2/2)

```
bindkey -M visual 'i=' select-quoted
bindkey -M visual 'i>' select-bracketed
bindkey -M visual 'i@' select-quoted
bindkey -M visual 'iB' select-bracketed
bindkey -M visual 'iW' select-in-blank-word
bindkey -M visual 'i[' select-bracketed
bindkey -M visual 'i\\' select-quoted
bindkey -M visual 'i]' select-bracketed
bindkey -M visual 'i\' ' select-quoted
bindkey -M visual 'ia' select-in-shell-word
bindkey -M visual 'ib' select-bracketed
bindkey -M visual 'iw' select-in-word
bindkey -M visual 'i{' select-bracketed
bindkey -M visual 'i|' select-quoted
bindkey -M visual 'i}' select-bracketed
bindkey -M visual 'j' down-line
bindkey -M visual 'k' up-line
bindkey -M visual 'o' exchange-point-and-mark
bindkey -M visual 'p' put-replace-selection
bindkey -M visual 'u' vi-down-case
bindkey -M visual 'x' vi-delete
bindkey -M visual '~' vi-oper-swap-case
```

ALL Vim Normal Mode (1/3)

```
n <Esc><C-C> * wvU
n <Esc><C-T> * :call TransposeWords()<CR>
n <Space>mt * :MinimapToggle<CR>
n <Space>mc * :MinimapClose<CR>
n <Space>mu * :MinimapUpdate<CR>
n <Space>mm * :Minimap<CR>
n <Space><Tab> :call AltOrNextBuffer()<CR>
n <Space>/ * :LocateAll<CR>
n <Space>ma * :Marks.<CR>
n <Space>] * <C-W>}<CR>
n <Space>ta * :Tags.<CR>
n <Space>h: * :History:.<CR>
n <Space>h/ * :History/.<CR>
n <Space>hh * :History.<CR>
n <Space>rg * :Rg<CR>
n <Space>oa * :ALEToggle<CR>
n <Space>m * :Map.<CR>
n <Space>j * :Lines.<CR>
n <Space>ke * :FZFKeys<CR>
n <Space>, * :FZFMaps<CR>
n <Space>aa * :Agg<CR>
n <Space>i * :Imap<CR>
n <Space>f * :Files.<CR>
n <Space>env * :FZFEnv<CR>
n <Space>; * :Commands.<CR>
n <Space>. * :Colors<CR>
n <Space>b * :Buffers.<CR>
n <Space>ag * :Ag<CR>
n <Space>vj * :w.<CR>:call TmuxRepeat('file')<CR>
n <Space>ev :call ExtractVariable()<CR>
n <Space>os * :call CopyCWordClip()<CR> :call system('bash ZPWR_TMUX/goo
n <Space>ox * :call CopyCWordClip()<CR> :call system('bash ZPWR_TMUX/goo
n <Space>oc * :call CopyCWordClip()<CR>
n <Space>x * :normal mzg&'zzz<CR>
n <Space>p * :bprev<CR>
n <Space>n * :bnext<CR>
n <Space>ap * :prev<CR>
n <Space>an * :next<CR>
n <Space>lo * :lopen<CR>
n <Space>lc * :lclose<CR>
n <Space>lp * :lprev<CR>
n <Space>ln * :lnext<CR>
n <Space>[ * :call Quoter('bracket')<CR>
n <Space>' * :call Quoter('back')<CR>
n <Space>' * :call Quoter('single')<CR>
n <Space>' * :call Quoter('double')<CR>
n <Space>z * :Commits.<CR>
n <Space>t * :tabnew<CR>
```

ALL Vim Normal Mode (2/3)

```
n <Space>s * :split<CR>
n <Space>v * :vsplit<CR>
n <Space>w * :w.<CR>
n <Space>e * :q.<CR>
n <Space>wq * :wq.<CR>
n <Space>q * :qa.<CR>
n <Space>r * :%s@\C\<<[R]<[W]>\>@[R]<[W]>@g<Left><Left>
n <Space>g * :%s@\C\<<[R]<[W]>\>@g<Left><Left>
n <Space>= * 4+
n <Space>- * 4-
n && * :normal mzg&'zzz<CR>
n & * :&&<CR>
n <s<Esc> & <Nop>
n =s<Esc> & <Nop>
n >s<Esc> & <Nop>
n N * :call GoToLastSearch('?')<CR>
n Y * yy'>
n [o<Esc> & <Nop>
n [ ] k][%?]<CR>]]]]]]
n [[ ?]<CR>w99[{
n \K * :OnlineThesaurusCurrentWord<CR>
n ]o<Esc> & <Nop>
n ]] j0[[%/{<CR>
n ][ /]<CR>b99}}
n n * :call GoToLastSearch('/')<CR>
n yo<Esc> & <Nop>
n y<[<G> & :<[<U>call setreg(v:register, fugitive#Object(@%))<CR>
n z/ * :if AutoHighlightToggle()|set hls|endif<CR>
n <SNR>198_ * :<[<U><[R>=v:count ? v:count : ''<CR>
n <[<G> * :call multiple_cursors#new('n', 1)<CR>
n <F11> * :call conque_term#exec_file()<CR>
n <[<W>\ * :vsplit<CR>
n <[<W>- * :split<CR>
n <[<D>, * :FZFEnv<CR>
n <[<D>. * :FZFKeys<CR>
n <[<D>/ * :LocateAll<CR>
n <[<D>z * :TlistAddFiles *<CR>:TlistToggle<CR>
n <[<D>y * :update<CR>:SyntasticCheck<CR>
n <[<D>x * :Marks<CR>
n <[<D>w * :update<CR>
n <[<D>v * :w.<CR>:call TmuxRepeatGeneric()<CR>
n <[<D>u * :History:<CR>
n <[<D>] * <[<W>}<CR>
n <[<D>t * :Tags<CR>
n <[<D>s * :History/<CR>
n <[<D>rr * :Rg<CR>
n <[<D>rq * :silent .open -t %:p:h<CR>:redraw.<CR>
n <[<D>q * :SaveSession.<CR><Tab>
```

ALL Vim Normal Mode (3/3)

```
n <C-D>p * :call PasteClip()<CR>
n <C-D>r * :call GetRef()<CR>
n <C-D>o * :ALEToggle<CR>
n <C-D>n * :Snippets<CR>
n <C-D>m * :Map.<CR>
n <C-D>l * :Lines.<CR>
n <C-D>k * :ALEFix<CR>
n <C-D>j * :Agg<CR>
n <C-D>i * :Imap<CR>
n <C-D>h * :HistoryFiles<CR>
n <C-D>g * :Commits.<CR>
n <C-D>f * :Files.<CR>
n <C-D>e * :ALEInfo<CR>
n <C-D>d * :Commands<CR>
n <C-D>c * :Colors<CR>
n <C-D>b * :Buffers<CR>
n <C-D>a * :Ag<CR>
n <C-D><C-D> * :GitGutterUndoHunk<CR>
n <C-V> * :w.<CR>:call TmuxRepeat('file')<CR>
n <C-Bslash> * +
n <F7> * :TTags<CR>
n <F6> * :SyntasticToggleMode<CR>
n <F5> * :LOTRToggle<CR>
n <F4> * :MinimapToggle<CR>
n <F3> * :TlistAddFiles *<CR>:TlistToggle<CR>
n <F2> * :UndotreeToggle<CR>
n <F1> * :NERDTreeToggle<CR>
n <F8> * :%s@@@g<Left><Left><Left>
n <C-Up> * :<C-U>call GoToNextMarker('{{',1)<CR>
n <C-Down> * :<C-U>call GoToNextMarker('{{',0)<CR>
n <End> * G
n <Home> * gg
n <C-F> * :q.<CR>
n <C-C> * :wq.<CR>:qa.<CR>
n <C-T> * xp
n <C-L> * 4l
n <C-H> * 4h
n <C-K> * 4k
n <C-J> * 4j
n <D-v> * '*p
```

ALL Vim Insert Mode (1/2)

```
i <M-d> * <C-O>dw
i <F31> * <C-O>dw
i <C-F> * col('.')>strlen(getline('.'))?'\\<C-F>':'\\<Right>'
i <C-E> * col('.')>strlen(getline('.'))||pumvisible()?'\\<C-E>':'\\<End>'
i <C-D> * col('.')>strlen(getline('.'))?'\\<C-D>':'\\<Del>'
i <C-X><C-A> * <C-A>
i <C-A> * <C-O>^
i <C-X> * <C-R>=<SNR>69_ManualCompletionEnter()<CR>
i <C-Tab> * <C-R>=UltiSnips#ListSnippets()<CR>
i <C-X><C-L> * fzf#vim#complete(fzf#wrap({'prefix': '^.*', 'source': 'r
i <C-X><C-K> * fzf#vim#complete#word({'left': '15%'})
i <F11> * <C-X><C-T>
i <F10> * <C-X><C-K>
i <C-D>n * <C-X><C-O>
i <C-D>\ * <C-X><C-L>
i <C-D>, * <C-O>:FZFEnv<CR>
i <C-D>. * <C-O>:FZFKeys<CR>
i <C-D>/ * <C-O>:LocateAll<CR>
i <C-D>z * <Esc>:TlistAddFiles * <CR> :TlistToggle<CR>i
i <C-D>y * <Esc>:update<CR>:SyntasticCheck<CR>a
i <C-D>x * <C-O>:Marks<CR>
i <C-D>w * <C-O>:update<CR>
i <C-D>v * <Esc>:w.<CR>:call TmuxRepeatGeneric()<CR>a
i <C-D>u * <C-O>:History:<CR>
i <C-D>] * <C-W><CR>
i <C-D>t * <C-O>:Tags<CR>
i <C-D>s * <C-O>:History/<CR>
i <C-D>rr * <Esc>:Rg<CR>
i <C-D>rq * <Esc>:silent .open -t %:p:h<CR>:redraw.<CR>a
i <C-D>q * <C-O>:SaveSession.<CR><Tab>
i <C-D>p * <C-O>:call PasteClip()<CR>
i <C-D>r * <C-O>:call GetRef()<CR>
i <C-D>o * <C-O>:ALEToggle<CR>
i <C-D>m * <C-O>:Map<CR>
i <C-D>l * <C-O>:Lines<CR>
i <C-D>k * <C-O>:ALEFix<CR>
i <C-D>j * <C-O>:Agg<CR>
i <C-D>i * <C-O>:Imap<CR>
i <C-D>h * <C-O>:HistoryFiles<CR>
i <C-D>g * <C-O>:Commits.<CR>
i <C-D>f * <C-O>:Files<CR>
i <C-D>e * <C-O>:ALEInfo<CR>
i <C-D>d * <C-O>:Commands<CR>
i <C-D>c * <C-O>:Colors<CR>
i <C-D>b * <C-O>:Buffers<CR>
i <C-D>a * <C-O>:Ag<CR>
i <C-D><C-D> * <C-O>:GitGutterUndoHunk<CR>
i <C-Bslash> * <Esc>+
```

ALL Vim Insert Mode (2/2)

```
i <F7> * <Esc>:TTags<CR>
i <F6> * <Esc>:SyntasticToggleMode<CR>
i <F5> * <Esc>:LOTRToggle<CR>
i <F4> * <Esc>:MinimapToggle<CR>
i <F3> * <Esc>:TlistAddFiles *<CR>:TlistToggle<CR>
i <F2> * <Esc>:UndotreeToggle<CR>
i <F1> * <Esc>:NERDTreeToggle<CR>
i <F8> * <Esc>:%s@@@g<Left><Left><Left>
i <C-Up> * <Esc>:<C-U>call GoToNextMarker('{{',1)<CR>i
i <C-Down> * <Esc>:<C-U>call GoToNextMarker('{{',0)<CR>i
i <C-B><C-N> * <Esc>^2xji
i <C-B> * getline('.')=~'^\s*'&&col('.')>strlen(getline('.'))?'0\<C-D>
i <End> * <Esc>Gi
i <Home> * <Esc>ggi
i <C-C> * <Esc>:wq.<CR>:qa.<CR>
i <C-T> * i<BS><C-O>:silent. undojoin | normal. xp<CR>
i <C-D><C-T> * <C-O>:call TransposeWords()<CR>
i <C-L> * <Esc>mbgg=G'bzza
i <Tab> * <C-R>=UltiSnips#ExpandSnippetOrJump()<CR>
i fj <Esc>
i jf <Esc>
```

ALL Vim Visual Mode (1/1)

```
v <Space>vl * <Esc>:call TmuxRepeat('repl')<CR>gv
v <Space>vk * <Esc>:call TmuxRepeat('visual')<CR>gv
v <Space>vj * <Esc>:call TmuxRepeat('file')<CR>gv
v <Space>( * :call InsertQuoteVisualMode('paren')<CR>
v <Space>{ * :call InsertQuoteVisualMode('curlybracket')<CR>
v <Space>[ * :call InsertQuoteVisualMode('bracket')<CR>
v <Space>' * :call InsertQuoteVisualMode('back')<CR>
v <Space>' * :call InsertQuoteVisualMode('single')<CR><CR>
v <Space>' * :call InsertQuoteVisualMode('double')<CR>
v <Space>r * :<,'>s@\C\<<C-R><C-W>\>@<C-R><C-W>@g<Left><Left>
v <Space>g * :<,'>%s@\C\<<C-R><C-W>\>@@g<Left><Left>
v <Space>b * :w .tmux set-buffer '(cat)'<CR><CR>
v <Space>= * 4+
v <Space>- * 4-
v < * <gv
v > * >gv
v J * :m '> + <CR> gv
v K * :m '< -- <CR> gv
v Y * y'>j
v \K * y:Thesaurus <C-R>'<CR>
v go * :call CopyClip()<CR> :call system('bash ZPWR_TMUX/google.sh open')
v gs * :call CopyClip()<CR> :call system('bash ZPWR_TMUX/google.sh googl')
v <C-D>d * :<C-C>:update<CR>
v <C-D>y * :<C-C>:update<CR>:SyntasticCheck<CR>
v <C-D>, * :call NERDComment('x','Toggle')<CR>'>
v <RightMouse> * :call CopyClip()<CR>'>
v <C-B> * :call CopyClip()<CR>'>
v <C-Up> * :m '< -- <CR> gv
v <C-Down> * :m '> + <CR> gv
v <C-Left> * <gv
v <C-Right> * >gv
v <C-F> * :<C-C>:q.<CR>
v <C-L> * 4l
v <C-K> * 4k
v <C-J> * 4j
v <D-x> '*d
v <D-c> '*y
v <D-v> '-d'*p
```