

—— // VIMLRS // ——

vimlrs – Language Reference

v0.2.1

LANGUAGE REFERENCE

every builtin · command · option · function

2026-07-18

MenkeTechnologies

—— MENKETECHNOLOGIES ——

Contents

String manipulation	2
List manipulation	9
Dictionary manipulation	12
Variables & Type	14
Number & Float	15
Files, Buffers & Lines	17
System & Environment	26
Functional & Misc	31
Ex Commands	55
Options	56
Special v: Variables	58

String manipulation

56 entries

byteidx

```
byteidx({string}, {nr} [, {utf16}])
```

Byte index of the {nr}'th character in {string}.

byteidxcomp

```
byteidxcomp({string}, {nr} [, {utf16}])
```

Like byteidx() but counting composing characters separately.

char2nr

```
char2nr({string} [, {utf8}])
```

Codepoint of the first character of {string}.

charclass

```
charclass({string})
```

Character class (0 white, 1 punctuation, 2 word, ...) of the first char of {string}.

charidx

```
charidx({string}, {idx} [, {countcc} [, {utf16}]])
```

Character index of byte {idx} in {string}.

digraph_get

```
digraph_get({chars})
```

The digraph character defined for the two-character {chars}.

digraph_getlist

```
digraph_getlist([listall])
```

List of [chars, digraph] pairs for the defined digraphs.

digraph_set

```
digraph_set({chars}, {digraph})
```

Define {chars} as a digraph producing {digraph}; returns v:true.

digraph_setlist

```
digraph_setlist({list})
```

Define multiple digraphs from a List of [chars, digraph] pairs.

escape

```
escape({string}, {chars})
```

{string} with each character in {chars} prefixed by a backslash.

expandcmd

```
expandcmd({string} [, {options}])
```

{string} with command-line special items ("% , '<word>', ...) expanded.

fnameescape

```
fnameescape({string})
```

{string} escaped for use as a Vim command file-name argument.

gettext

```
gettext({text} [, {package}])
```

Translated {text} via gettext (identity when no catalog).

iconv

```
iconv({string}, {from}, {to})
```

{string} converted from encoding {from} to {to}.

join

```
join({list} [, {sep}])
```

String of {list} items joined by {sep} (default space).

keytrans

```
keytrans({string})
```

{string} with key codes translated to readable form (e.g. <C-A>).

list2str

```
list2str({list} [, {utf8}])
```

String built from the List of codepoint numbers {list}.

match

```
match({expr}, {pat} [, {start} [, {count}]])
```

Byte index where {pat} matches in {expr}, else -1.

matchbufline

```
matchbufline({buf}, {pat}, {lnum}, {end} [, {dict}])
```

List of matches of {pat} in buffer {buf} lines {lnum}..{end}.

matchend

```
matchend({expr}, {pat} [, {start} [, {count}]])
```

Byte index just after the match of {pat} in {expr}, else -1.

matchfuzzy

```
matchfuzzy({list}, {str} [, {dict}])
```

Items of {list} fuzzy-matching {str}, best first.

matchfuzzypos

```
matchfuzzypos({list}, {str} [, {dict}])
```

Like matchfuzzy() plus match positions and scores.

matchlist

```
matchlist({expr}, {pat} [, {start} [, {count}]])
```

List of the full match and submatches of {pat} in {expr}.

matchstr

```
matchstr({expr}, {pat} [, {start} [, {count}]])
```

Matched substring of {pat} in {expr}, or empty string.

matchstrlist

```
matchstrlist({list}, {pat} [, {dict}])
```

List of dicts describing matches of {pat} across the strings in {list}.

matchstrpos

```
matchstrpos({expr}, {pat} [, {start} [, {count}]])
```

[match, start, end] of {pat} in {expr}.

nr2char

```
nr2char({expr} [, {utf8}])
```

Character whose codepoint is {expr}.

printf

```
printf({fmt} [, {expr1} ...])
```

Formatted string from printf-style {fmt} and arguments.

repeat

```
repeat({expr}, {count})
```

{expr} (String or List) repeated {count} times.

sha256

```
sha256({string})
```

SHA-256 hex digest of {string}.

shellescape

```
shellescape({string} [, {special}])
```

{string} quoted for safe use as a shell command argument.

soundfold

```
soundfold({word})
```

Sound-folded (phonetic) form of {word}.

split

```
split({string} [, {pat} [, {keepempty}]])
```

List of {string} split on {pat} (default whitespace).

str2float

```
str2float({string} [, {quoted}])
```

Float parsed from {string}.

str2list

```
str2list({string} [, {utf8}])
```

List of codepoint numbers for each character in {string}.

str2nr

```
str2nr({string} [, {base}])
```

Leading integer parsed from {string} in {base} (default 10).

strcharlen

```
strcharlen({string})
```

Number of characters in {string}, ignoring composing characters.

strcharpart

```
strcharpart({src}, {start} [, {len} [, {skipcc}]])
```

Character substring of {src} from char {start} for {len} chars.

strchars

```
strchars({string} [, {skipcc}])
```

Number of characters in {string}, counting composing chars unless {skipcc}.

strdisplaywidth

```
strdisplaywidth({string} [, {col}])
```

Display cell width of {string}, honoring 'tabstop'.

strgetchar

```
strgetchar({str}, {index})
```

Codepoint at char {index} of {str}, or -1.

stridx

```
stridx({haystack}, {needle} [, {start}])
```

Byte index of first {needle} in {haystack} at/after {start}, else -1.

string

```
string({expr})
```

String representation of {expr}, quoting embedded strings (inverse of eval()).

strlen

```
strlen({string})
```

Number of bytes in {string}.

strpart

```
strpart({src}, {start} [, {len} [, {chars}]])
```

Byte (or char) substring of {src} from {start} for {len}.

stridx

```
stridx({haystack}, {needle} [, {start}])
```

Byte index of last {needle} in {haystack} at/before {start}, else -1.

strtrans

```
strtrans({string})
```

{string} with unprintable characters shown as ^X / <xx>.

strutf16len

```
strutf16len({string} [, {countcc}])
```

Number of UTF-16 code units in {string}.

strwidth

```
strwidth({string})
```

Display cell width of {string} (no tab expansion).

submatch

```
submatch({nr} [, {list}])
```

The {nr}'th submatch of the substitute() replacement.

substitute

```
substitute({string}, {pat}, {sub}, {flags})
```

{string} with matches of {pat} replaced by {sub}; {flags} 'g' replaces all.

tolower

```
tolower({string})
```

{string} with all letters lowercased.

toupper

```
toupper({string})
```

{string} with all letters uppercased.

tr

```
tr({src}, {fromstr}, {tostr})
```

{src} with each char in {fromstr} replaced by the matching char in {tostr}.

trim

```
trim({text} [, {mask} [, {dir}]])
```

{text} with leading/trailing {mask} chars (default whitespace) removed.

utf16idx

```
utf16idx({string}, {idx} [, {countcc} [, {charidx}]])
```

UTF-16 code-unit index of byte {idx} in {string}.

List manipulation

22 entries

add

```
add({object}, {expr})
```

Append {expr} to List or Blob {object}; returns {object}.

blob2list

```
blob2list({blob})
```

List of byte-value Numbers for each byte of {blob}.

copy

```
copy({expr})
```

Shallow copy of {expr}.

count

```
count({comp}, {expr} [, {ic} [, {start}]])
```

Number of times {expr} occurs in String/List/Dict {comp}.

deepcopy

```
deepcopy({expr} [, {noref}])
```

Recursive (deep) copy of {expr}.

flatten

```
flatten({list} [, {maxdepth}])
```

Flatten nested List {list} in place up to {maxdepth}.

flattennew

```
flattennew({list} [, {maxdepth}])
```

Flattened copy of nested List {list}, leaving {list} unchanged.

foreach

```
foreach({expr1}, {expr2})
```

Apply {expr2} to each item of {expr1} for its side effects; returns {expr1}.

index

```
index({object}, {expr} [, {start} [, {ic}]])
```

Index of first item equal to {expr} in {object}, else -1.

indexof

```
indexof({object}, {expr} [, {opts}])
```

Index of first item for which {expr} is true, else -1.

insert

```
insert({object}, {item} [, {idx}])
```

Insert {item} into List/Blob {object} before index {idx} (default 0).

list2blob

```
list2blob({list})
```

Blob built from the List of byte-value Numbers {list}.

mapnew

```
mapnew({expr1}, {expr2})
```

Like map() but returns a new container, leaving {expr1} unchanged.

max

```
max({expr})
```

Maximum value among the items of List/Dict {expr} (0 if empty).

min

```
min({expr})
```

Minimum value among the items of List/Dict {expr} (0 if empty).

range

```
range({expr} [, {max} [, {stride}]])
```

List of numbers from {expr} to {max} stepping by {stride}.

reduce

```
reduce({object}, {func} [, {initial}])
```

Fold {object} to a single value via {func}, starting at {initial}.

remove

```
remove({object}, {idx} [, {end}])
```

Remove and return item {idx} (or range {idx}..{end}) from {object}.

reverse

```
reverse({object})
```

Reverse List/Blob {object} in place; returns {object}.

slice

```
slice({expr}, {start} [, {end}])
```

Sub-list/Blob/String of {expr} from {start} up to (not including) {end}.

sort

```
sort({list} [, {how} [, {dict}])
```

Sort {list} in place; {how} sets comparison; returns {list}.

uniq

```
uniq({list} [, {how} [, {dict}])
```

Remove adjacent duplicate items from sorted {list} in place.

Dictionary manipulation

9 entries

dictwatcheradd

```
dictwatcheradd({dict}, {pattern}, {callback})
```

Register {callback} to fire when keys matching {pattern} in {dict} change.

dictwatcherdel

```
dictwatcherdel({dict}, {pattern}, {callback})
```

Remove a watcher previously added with dictwatcheradd().

extend

```
extend({expr1}, {expr2} [, {expr3}])
```

Append/merge {expr2} into List/Dict {expr1} in place; returns {expr1}.

extendnew

```
extendnew({expr1}, {expr2} [, {expr3}])
```

Like extend() but returns a new container, leaving {expr1} unchanged.

get

```
get({collection}, {key} [, {default}])
```

Item {key}/{idx} of Dict/List/Blob, or {default} if absent.

has_key

```
has_key({dict}, {key})
```

1 if {dict} has an entry {key}, else 0.

items

```
items({dict})
```

List of [key, value] pairs in {dict}.

keys

```
keys({dict})
```

List of all keys in {dict}.

values

```
values({dict})
```

List of all values in {dict}.

Variables & Type

8 entries

empty

```
empty({expr})
```

1 if {expr} is empty (0, "", [], {}, v:null), else 0.

exists

```
exists({expr})
```

1 if variable/option/function/command {expr} exists, else 0.

funcref

```
funcref({name} [, {arglist}] [, {dict}])
```

Funcref bound by reference to {name} (ignores later redefinition).

function

```
function({name} [, {arglist}] [, {dict}])
```

Funcref for builtin/user function {name}, optionally bound to args/dict.

garbagecollect

```
garbagecollect([{atexit}])
```

Run the cyclic-reference garbage collector (stub in standalone).

islocked

```
islocked({expr})
```

1 if the variable named by {expr} is locked, else 0 (stub in standalone).

len

```
len({expr})
```

Length of String/List/Dict/Blob {expr}.

type

```
type({expr})
```

Numeric type code of {expr} (0 Number, 1 String, 2 Func, 3 List, 4 Dict, ...).

Number & Float

13 entries

abs

```
abs({expr})
```

Absolute value of {expr} (Float in -> Float out).

and

```
and({expr1}, {expr2})
```

Bitwise AND of {expr1} and {expr2}.

atan2

```
atan2({expr1}, {expr2})
```

Arc tangent of {expr1}/{expr2} in radians (-pi..pi).

float2nr

```
float2nr({expr})
```

{expr} truncated toward zero to a Number.

fmod

```
fmod({expr1}, {expr2})
```

Floating-point remainder of {expr1} / {expr2}.

invert

```
invert({expr})
```

Bitwise complement (NOT) of {expr}.

isinf

```
isinf({expr})
```

1 if {expr} is +inf, -1 if -inf, else 0.

isnan

```
isnan({expr})
```

1 if {expr} is a NaN Float, else 0.

or

```
or({expr1}, {expr2})
```

Bitwise OR of {expr1} and {expr2}.

pow

```
pow({x}, {y})
```

{x} raised to the power {y} as a Float.

rand

```
rand([{expr}])
```

Pseudo-random 32-bit Number, optionally from seed-list {expr}.

srand

```
srand([{expr}])
```

Initialize and return a seed List for rand().

xor

```
xor({expr1}, {expr2})
```

Bitwise XOR of {expr1} and {expr2}.

Files, Buffers & Lines

77 entries

append

```
append({lnum}, {text})
```

Append {text} (String or List) below line {lnum}; 0 on success.

appendbufline

```
appendbufline({buf}, {lnum}, {text})
```

Append {text} below line {lnum} of buffer {buf}.

browse

```
browse({save}, {title}, {initdir}, {default})
```

Prompt for a file name via a dialog (GUI).

browsedir

```
browsedir({title}, {initdir})
```

Prompt for a directory via a dialog (GUI).

bufadd

```
bufadd({name})
```

Add a buffer for file {name} (without loading) and return its number (stub in standalone).

bufexists

```
bufexists({buf})
```

1 if buffer {buf} exists, else 0 (stub in standalone).

buflisted

```
buflisted({buf})
```

1 if buffer {buf} exists and is listed, else 0 (stub in standalone).

bufload

```
bufload({buf})
```

Ensure buffer {buf} is loaded (reading the file if needed) (stub in standalone).

bufloaded

```
bufloaded({buf})
```

1 if buffer {buf} exists and is loaded, else 0 (stub in standalone).

bufname

```
bufname([{buf}])
```

Name of buffer {buf} (default current) (stub in standalone).

bufnr

```
bufnr([{buf} [, {create}]])
```

Buffer number of {buf}; optionally create it (stub in standalone).

bufwinid

```
bufwinid({buf})
```

window-ID of the first window showing buffer {buf}, else -1 (stub in standalone).

bufwinnr

```
bufwinnr({buf})
```

Window number of the first window showing buffer {buf}, else -1 (stub in standalone).

byte2line

```
byte2line({byte})
```

Line number containing byte offset {byte}, else -1.

changenr

```
changenr()
```

Sequence number of the current entry in the buffer's change list (stub in standalone).

charcol

```
charcol({expr} [, {winid}])
```

Character column for position {expr}.

chdir

```
chdir({dir})
```

Change the working directory to {dir}; returns the previous directory.

cindent

```
cindent({lnum})
```

C-indent amount Vim would use for line {lnum}.

col

```
col({expr} [, {winid}])
```

Byte column for position {expr}.

delete

```
delete({fname} [, {flags}])
```

Delete file (or, with 'd/rf', directory) {fname}; 0 on success.

deletebufline

```
deletebufline({buf}, {first} [, {last}])
```

Delete lines {first}..{last} from buffer {buf}.

executable

```
executable({expr})
```

1 if {expr} is an executable found in \$PATH, else 0.

exepath

```
exepath({expr})
```

Full path of the executable {expr}, or empty if not found.

expand

```
expand({string} [, {nosuf} [, {list}]])
```

Expand wildcards and keywords ('%', '<cfile>', '~', ...) in {string}.

filecopy

```
filecopy({from}, {to})
```

Copy file {from} to {to}; v:true on success.

filereadable

```
filereadable({file})
```

1 if {file} exists and is readable, else 0.

filewritable

```
filewritable({file})
```

1 if {file} is writable, 2 if it is a writable directory, else 0.

finddir

```
finddir({name} [, {path} [, {count}]])
```

Find directory {name} in {path}; the {count}'th match (or List).

findfile

```
findfile({name} [, {path} [, {count}]])
```

Find file {name} in {path}; the {count}'th match (or List).

fnamemodify

```
fnamemodify({fname}, {mods})
```

Modify file name {fname} per the :p/:h/:t/:r/:e {mods}.

getbufinfo

```
getbufinfo([{buf}])
```

List of dicts with information about buffers.

getbufline

```
getbufline({buf}, {lnum} [, {end}])
```

List of lines {lnum}..{end} from buffer {buf}.

getbufoneline

```
getbufoneline({buf}, {lnum})
```

Single line {lnum} from buffer {buf} as a String.

getbufvar

```
getbufvar({buf}, {varname} [, {def}])
```

Buffer-local variable/option {varname} from buffer {buf}.

getchangelist

```
getchangelist([{buf}])
```

[changelist, index] for buffer {buf}.

getcwd

```
getcwd([ {winnr} [, {tabnr} ] ])
```

Current working directory (optionally of a window/tab).

getfontname

```
getfontname([ {name} ])
```

Name of the font currently in use (GUI) (stub in standalone).

getfperm

```
getfperm({fname})
```

Permissions of {fname} as a 9-character 'rwxrwxrwx' String.

getfsize

```
getfsize({fname})
```

Size of file {fname} in bytes (-1 if absent, -2 if too large).

getftime

```
getftime({fname})
```

Last modification time of {fname} as seconds since the epoch, else -1.

getftype

```
getftype({fname})
```

Type of file {fname}: 'file', 'dir', 'link', 'fifo', etc.

getline

```
getline({lnum} [, {end} ])
```

Text of line {lnum} (or List of lines {lnum}..{end}) in the current buffer.

glob

```
glob({expr} [, {nosuf} [, {list} [, {alllinks} ] ] ])
```

Expand file wildcards {expr}; String (or List) of matching paths.

glob2regpat

```
glob2regpat({string})
```

Vim regexp pattern equivalent to the file glob {string}.

globpath

```
globpath({path}, {expr} [, {nosuf} [, {list} [, {alllinks}]]])
```

Expand {expr} in every directory of {path}.

haslocaldir

```
haslocaldir([{winnr} [, {tabnr}]]])
```

1 if the window/tab has a local working directory.

indent

```
indent({lnum})
```

Indent (in spaces) of line {lnum} in the current buffer.

isabsolutepath

```
isabsolutepath({path})
```

1 if {path} is an absolute path, else 0.

isdirectory

```
isdirectory({directory})
```

1 if {directory} exists and is a directory, else 0.

last_buffer_nr

```
last_buffer_nr()
```

Number of the last (highest-numbered) buffer (stub in standalone).

line

```
line({expr} [, {winid}])
```

Line number for position {expr} (., '\$', mark, ...).

line2byte

```
line2byte({lnum})
```

Byte offset of the first byte of line {lnum} (1-based), else -1.

lispindent

```
lispindent({lnum})
```

Lisp indent amount Vim would use for line {lnum}.

mkdir

```
mkdir({name} [, {flags} [, {prot}]])
```

Create directory {name} ('p' makes parents); 1 on success.

nextnonblank

```
nextnonblank({lnum})
```

Line number of the first non-blank line at/after {lnum}, else 0.

pathshorten

```
pathshorten({path} [, {len}])
```

Shorten directory components of {path} to {len} characters.

prevnonblank

```
prevnonblank({lnum})
```

Line number of the first non-blank line at/before {lnum}, else 0.

readblob

```
readblob({fname} [, {offset} [, {size}]])
```

Blob of the (partial) contents of file {fname}.

readdir

```
readdir({directory} [, {expr}])
```

List of file names in {directory}, optionally filtered by {expr}.

readfile

```
readfile({fname} [, {type} [, {max}]])
```

List of lines read from file {fname}.

rename

```
rename({from}, {to})
```

Rename/move file {from} to {to}; 0 on success.

resolve

```
resolve({filename})
```

Resolve symbolic links in {filename} to its real path.

setbufline

```
setbufline({buf}, {lnum}, {text})
```

Set line {lnum} of buffer {buf} to {text}.

setbufvar

```
setbufvar({buf}, {varname}, {val})
```

Set buffer-local variable/option {varname} in buffer {buf} (stub in standalone).

setfperm

```
setfperm({fname}, {mode})
```

Set permissions of {fname} from a 9-character 'rwxrwxrwx' {mode}.

setline

```
setline({lnum}, {text})
```

Set line {lnum} to {text} (String or List of lines); 0 on success.

simplify

```
simplify({filename})
```

Simplify {filename} by resolving '.', '..' and doubled separators (no disk access).

swapfilelist

```
swapfilelist()
```

List of swap files found in the 'directory' directories.

swapinfo

```
swapinfo({fname})
```

Dict of information read from swap file {fname}.

swapname

```
swapname({buf})
```

Swap-file name of buffer {buf}, or empty if none (stub in standalone).

tempname

```
tempname()
```

Name of a unique, not-yet-existing temporary file.

undofile

```
undofile({name})
```

Undo-file path Vim would use for file {name}.

undotree

```
undotree([{buf}])
```

Dict describing the undo tree of the buffer.

virtcol

```
virtcol({expr} [, {list} [, {winid}]])
```

Screen (virtual) column of position {expr}.

virtcol2col

```
virtcol2col({winid}, {lnum}, {col})
```

Byte index in line {lnum} of screen column {col} in window {winid}.

winbufnr

```
winbufnr({nr})
```

Buffer number of window {nr}, else -1 (stub in standalone).

writefile

```
writefile({object}, {fname} [, {flags}])
```

Write List of lines or Blob {object} to file {fname}; 0 on success.

System & Environment

44 entries

chanclose

```
chanclose({id} [, {stream}])
```

Close channel {id} (or one of its streams) (stub in standalone).

chansend

```
chansend({id}, {data})
```

Send {data} to channel {id}; returns bytes written (stub in standalone).

environ

```
environ()
```

Dict of all environment variables and their values.

getenv

```
getenv({name})
```

Value of environment variable {name}, or v:null if unset.

getpid

```
getpid()
```

Process ID of the Vim process.

hostname

```
hostname()
```

Name of the host Vim is running on.

jobpid

```
jobpid({id})
```

Process ID of job {id} (stub in standalone).

jobresize

```
jobresize({id}, {width}, {height})
```

Resize the pseudo-terminal of job {id} (stub in standalone).

jobstart

```
jobstart({cmd} [, {opts}])
```

Start job running {cmd}; returns a job id (or <=0 on failure) (stub in standalone).

jobstop

```
jobstop({id})
```

Stop job {id} (stub in standalone).

jobwait

```
jobwait({ids} [, {timeout}])
```

Wait for the jobs {ids} to finish; List of exit codes.

json_decode

```
json_decode({string})
```

Vim value decoded from JSON text {string}.

json_encode

```
json_encode({expr})
```

JSON text encoding of {expr}.

libcall

```
libcall({lib}, {func}, {arg})
```

Call function {func} in dynamic library {lib} (String result) (stub in standalone).

libcallnr

```
libcallnr({lib}, {func}, {arg})
```

Call function {func} in dynamic library {lib} (Number result) (stub in standalone).

localtime

```
localtime()
```

Current time as seconds since the Unix epoch.

luaeval

```
luaeval({expr} [, {expr}])
```

Evaluate Lua expression {expr} and return the result.

msgpackdump

```
msgpackdump({list} [, {type}])
```

msgpack byte representation of the items in {list}.

msgpackparse

```
msgpackparse({data})
```

List of Vim values parsed from msgpack {data}.

perlval

```
perlval({expr})
```

Evaluate Perl expression {expr} and return the result.

py3eval

```
py3eval({expr})
```

Evaluate Python 3 expression {expr} and return the result.

pyeval

```
pyeval({expr})
```

Evaluate Python (2) expression {expr} and return the result.

pyxeval

```
pyxeval({expr})
```

Evaluate Python (pyx) expression {expr} and return the result.

reltime

```
reltime([{{start} [, {end}]]])
```

High-resolution time value, or an elapsed interval.

reltimefloat

```
reltimefloat({time})
```

reltime() value as a Float number of seconds.

reltimestr

```
reltimestr({time})
```

reltime() value formatted as a 'seconds.microseconds' String.

rpcnotify

```
rpcnotify({channel}, {event} [, {args} ...])
```

Send an RPC notification {event} to {channel} (stub in standalone).

rpcrequest

```
rpcrequest({channel}, {method} [, {args} ...])
```

Send a blocking RPC request {method} to {channel} and return the result (stub in standalone).

rpcstart

```
rpcstart({prog} [, {argv}])
```

Deprecated: start an RPC channel to {prog} (stub in standalone).

rpcstop

```
rpcstop({channel})
```

Deprecated: close RPC channel {channel} (stub in standalone).

rubyeval

```
rubyeval({expr})
```

Evaluate Ruby expression {expr} and return the result.

serverlist

```
serverlist()
```

Newline-separated list of server addresses Vim is listening on.

serverstart

```
serverstart([[{address}])
```

Start an RPC server, returning its listen address (stub in standalone).

serverstop

```
serverstop({address})
```

Stop the RPC server listening on {address} (stub in standalone).

setenv

```
setenv({name}, {val})
```

Set environment variable {name} to {val} (v:null unsets it).

sockconnect

```
sockconnect({mode}, {address} [, {opts}])
```

Connect a socket to {address} (tcp/pipe); returns a channel id (stub in standalone).

stdioopen

```
stdioopen({opts})
```

Open a channel on Vim's own stdin/stdout (stub in standalone).

stdpath

```
stdpath({what})
```

Standard config/data/cache/state path(s) for {what}.

strftime

```
strftime({format} [, {time}])
```

Format time {time} (default now) with strftime() {format}.

strptime

```
strptime({format}, {timestring})
```

Parse {timestring} per {format} into seconds since the epoch.

system

```
system({cmd} [, {input}])
```

Run shell {cmd}, returning its output as a String.

systemlist

```
systemlist({cmd} [, {input}])
```

Run shell {cmd}, returning its output as a List of lines.

termopen

```
termopen({cmd} [, {opts}])
```

Open a terminal running {cmd} in the current buffer (stub in standalone).

windowsversion

```
windowsversion()
```

Microsoft Windows version string (" on other systems) (stub in standalone).

Functional & Misc

210 entries

api_info

```
api_info()
```

Dict describing the Nvim API (version, functions, types).

argc

```
argc([winid])
```

Number of files in the argument list.

argidx

```
argidx()
```

Current index into the argument list.

arglistid

```
arglistid([winnr] [, {tabnr}])
```

Identifier of the argument list used by a window.

argv

```
argv([nr] [, {winid}])
```

Argument-list entry {nr} (or the whole List).

assert_equal

```
assert_equal({expected}, {actual} [, {msg}])
```

Add an error to v:errors unless {expected} == {actual}.

assert_equalfile

```
assert_equalfile({fname1}, {fname2} [, {msg}])
```

Add an error to v:errors unless the two files have equal contents.

assert_exception

```
assert_exception({error} [, {msg}])
```

Add an error to v:errors unless v:exception contains {error}.

assert_false

```
assert_false({actual} [, {msg}])
```

Add an error to v:errors unless {actual} is false.

assert_inrange

```
assert_inrange({lower}, {upper}, {actual} [, {msg}])
```

Add an error to v:errors unless {lower} <= {actual} <= {upper}.

assert_match

```
assert_match({pat}, {actual} [, {msg}])
```

Add an error to v:errors unless {pat} matches {actual}.

assert_notequal

```
assert_notequal({expected}, {actual} [, {msg}])
```

Add an error to v:errors unless {expected} != {actual}.

assert_notmatch

```
assert_notmatch({pat}, {actual} [, {msg}])
```

Add an error to v:errors unless {pat} does not match {actual}.

assert_report

```
assert_report({msg})
```

Add {msg} to v:errors unconditionally.

assert_true

```
assert_true({actual} [, {msg}])
```

Add an error to v:errors unless {actual} is true.

call

```
call({func}, {arglist} [, {dict}])
```

Call {func} with the List {arglist} as its arguments (stub in standalone).

clearmatches

```
clearmatches([win])
```

Clear all matches added with matchadd()/matchaddpos().

cmdcomplete_info

```
cmdcomplete_info([{what}])
```

Dict of information about the current command-line completion.

complete

```
complete({startcol}, {matches})
```

Set the Insert-mode completion list to {matches} starting at {startcol} (stub in standalone).

complete_add

```
complete_add({expr})
```

Add {expr} to the completion list during a 'completefunc'.

complete_check

```
complete_check()
```

1 if completion was aborted by typed input.

complete_info

```
complete_info([{what}])
```

Dict of information about the current Insert-mode completion.

confirm

```
confirm({msg} [, {choices} [, {default} [, {type}]]])
```

Show dialog {msg} with {choices}; return the chosen button number.

ctxget

```
ctxget([{index}])
```

Dict for the {index}'th entry on the context stack.

ctxpop

```
ctxpop()
```

Pop and restore the top editor context from the stack (stub in standalone).

ctxpush

```
ctxpush([{types}])
```

Push the editor context (of {types}) onto the context stack (stub in standalone).

ctxset

```
ctxset({context} [, {index}])
```

Set the {index}'th context-stack entry from {context} (stub in standalone).

ctxsize

```
ctxsize()
```

Number of entries on the context stack (stub in standalone).

cursor

```
cursor({lnum}, {col} [, {off}])
```

Move the cursor to line {lnum}, column {col}.

debugbreak

```
debugbreak({pid})
```

Interrupt process {pid} (MS-Windows debugging helper) (stub in standalone).

did_filetype

```
did_filetype()
```

1 if a FileType autocommand has run for the current buffer (stub in standalone).

diff_filler

```
diff_filler({lnum})
```

Number of filler lines above diff line {lnum}.

diff_hlID

```
diff_hlID({lnum}, {col})
```

Diff highlight ID at line {lnum}, column {col}.

eval

```
eval({string})
```

Evaluate {string} as a Vim expression (inverse of string()) (stub in standalone).

eventhandler

```
eventhandler()
```

1 if Vim is inside an event handler (e.g. processing a callback) (stub in standalone).

execute

```
execute({command} [, {silent}])
```

Execute Ex {command}(s) and return their captured output (stub in standalone).

feedkeys

```
feedkeys({string} [, {mode}])
```

Push {string} into the typeahead buffer as if typed (stub in standalone).

filter

```
filter({expr1}, {expr2})
```

Keep items of {expr1} for which {expr2} is non-zero; in place.

foldclosed

```
foldclosed({lnum})
```

First line of the closed fold at {lnum}, else -1.

foldclosedend

```
foldclosedend({lnum})
```

Last line of the closed fold at {lnum}, else -1.

foldlevel

```
foldlevel({lnum})
```

Fold nesting level of line {lnum}.

foldtext

```
foldtext()
```

Text Vim shows for the closed fold on the current line.

foldtextresult

```
foldtextresult({lnum})
```

The 'foldtext' string for the fold at {lnum}.

foreground

```
foreground()
```

Bring the Vim window to the foreground (GUI/clients) (stub in standalone).

fullcommand

```
fullcommand({name} [, {vim9}])
```

Full Ex-command name for the abbreviation {name}.

getcellwidths

```
getcellwidths()
```

List of [low, high, width] cell-width overrides set with setcellwidths().

getchar

```
getchar([{expr} [, {opts}])
```

Get one character of user input as a Number or special-key String.

getcharmod

```
getcharmod()
```

Bitmask of modifier keys held for the last getchar().

getcharpos

```
getcharpos({expr})
```

Like getpos() but the column is a character index.

getcharsearch

```
getcharsearch()
```

Dict describing the last character search (f/t/F/T).

getcharstr

```
getcharstr([{expr} [, {opts}])
```

Like getchar() but always returns the character as a String.

getcmlpat

```
getcmlpat()
```

Pattern used for completion of the current command line.

getcmltype

```
getcmltype()
```

Completion type of the current command line.

getcmdline

```
getcmdline()
```

Current command-line contents.

getcmdpos

```
getcmdpos()
```

1-based byte position of the cursor in the command line.

getcmdprompt

```
getcmdprompt()
```

Prompt string of the current input()/command line.

getcmdscreenpos

```
getcmdscreenpos()
```

Screen cursor position within the command line.

getcmdtype

```
getcmdtype()
```

Type of the current command line (':', '/', '?', '@', '-', '=').

getcmdwintype

```
getcmdwintype()
```

Type of the command-line window, or empty if none (stub in standalone).

getcompletion

```
getcompletion({pat}, {type} [, {filtered}])
```

List of command-line completion candidates for {pat} of {type}.

getcompletiontype

```
getcompletiontype({pat})
```

Completion type Vim would use for command line {pat}.

getcurpos

```
getcurpos([{winid}])
```

Cursor position of a window including curswant.

getcursorcharpos

```
getcursorcharpos([winid])
```

Like getcurpos() but the column is a character index.

getjumplist

```
getjumplist([winnr] [, {tabnr}])
```

[jumplist, index] for a window.

getloclist

```
getloclist({nr} [, {what}])
```

List of location-list entries for window {nr}.

getmarklist

```
getmarklist([buf])
```

List of marks (global, or local to buffer {buf}).

getmatches

```
getmatches([win])
```

List of matches added with matchadd()/setmatches().

getmousepos

```
getmousepos()
```

Dict with the last known mouse position.

getpos

```
getpos({expr})
```

Position [bufnum, lnum, col, off] of {expr}.

getqflist

```
getqflist([what])
```

List of quickfix entries (or info per {what}).

getreg

```
getreg([regname] [, {list} [, {opts}]]])
```

Contents of register {regname}.

getreginfo

```
getreginfo([ {regname} ])
```

Dict describing register {regname} (value, type, width).

getregion

```
getregion({pos1}, {pos2} [, {opts}])
```

List of text lines for the region between {pos1} and {pos2}.

getregionpos

```
getregionpos({pos1}, {pos2} [, {opts}])
```

List of [start, end] position pairs for each line of a region.

getregtype

```
getregtype([ {regname} ])
```

Type of register {regname}: 'v', 'V', or blockwise.

getscriptinfo

```
getscriptinfo([ {opts} ])
```

List of dicts describing the sourced Vim scripts.

getstacktrace

```
getstacktrace()
```

List describing the current Vimscript call stack.

gettabinfo

```
gettabinfo([ {tabnr} ])
```

List of dicts with information about tab pages.

gettabvar

```
gettabvar({tabnr}, {varname} [, {def}])
```

Tab-local variable {varname} of tab {tabnr}.

gettabwinvar

```
gettabwinvar({tabnr}, {winnr}, {varname} [, {def}])
```

Window-local variable in window {winnr} of tab {tabnr}.

gettagstack

```
gettagstack([{winnr}])
```

Dict describing the tag stack of window {winnr}.

getwininfo

```
getwininfo([{winid}])
```

List of dicts with information about windows.

getwinpos

```
getwinpos([{timeout}])
```

[x, y] pixel position of the Vim window.

getwinposx

```
getwinposx()
```

X pixel position of the left of the Vim window, else -1 (stub in standalone).

getwinposy

```
getwinposy()
```

Y pixel position of the top of the Vim window, else -1 (stub in standalone).

getwinvar

```
getwinvar({nr}, {varname} [, {def}])
```

Window-local variable/option {varname} of window {nr}.

has

```
has({feature} [, {check}])
```

1 if Vim supports {feature}, else 0.

hasmapto

```
hasmapto({what} [, {mode} [, {abbr}])
```

1 if a mapping exists whose rhs contains {what}.

highlight_exists

```
highlight_exists({name})
```

1 if highlight group {name} is defined (alias of hlexists()).

histadd

```
histadd({history}, {item})
```

Add {item} to the {history} list (cmd/search/expr/input).

histdel

```
histdel({history} [, {item}])
```

Delete entries from the {history} list.

histget

```
histget({history} [, {index}])
```

Entry {index} from the {history} list.

histnr

```
histnr({history})
```

Index of the most recent entry in the {history} list.

hlID

```
hlID({name})
```

Numeric ID of highlight group {name} (0 if undefined).

hlexists

```
hlexists({name})
```

1 if highlight group {name} is defined, else 0 (stub in standalone).

id

```
id({expr})
```

Unique String identifier for the container or value {expr}.

input

```
input({prompt} [, {text} [, {completion}]])
```

Prompt for and return a line of input from the user.

inputdialog

```
inputdialog({prompt} [, {text} [, {cancelreturn}]])
```

Like input() but using a GUI dialog when available.

inputlist

```
inputlist({textlist})
```

Prompt the user to pick a numbered entry from {textlist}.

inputrestore

```
inputrestore()
```

Restore typeahead previously saved with inputsave() (stub in standalone).

inputsave

```
inputsave()
```

Save and clear pending typeahead so input() can be used (stub in standalone).

inputsecret

```
inputsecret({prompt} [, {text}])
```

Like input() but the typed text is hidden.

interrupt

```
interrupt()
```

Interrupt script execution as if CTRL-C were pressed (stub in standalone).

map

```
map({expr1}, {expr2})
```

Replace each item of List/Dict/Blob/String {expr1} with {expr2}; in place.

maparg

```
maparg({name} [, {mode} [, {abbr} [, {dict}]]])
```

rhs (or Dict) of the mapping of {name} in {mode}.

mapcheck

```
mapcheck({name} [, {mode} [, {abbr}]]])
```

rhs of a mapping that {name} could match, else empty.

maplist

```
maplist([{abbr}])
```

List of dicts describing all mappings.

mapset

```
mapset({mode}, {abbr}, {dict})
```

Restore a mapping from a maparg() dict.

matchadd

```
matchadd({group}, {pattern} [, {priority} [, {id} [, {dict}]]])
```

Highlight {pattern} with {group}; returns the match id.

matchaddpos

```
matchaddpos({group}, {pos} [, {priority} [, {id} [, {dict}]]])
```

Highlight positions {pos} with {group}; returns the match id.

matcharg

```
matcharg({nr})
```

[{pattern', 'group'}] for the {nr}'th :match command.

matchdelete

```
matchdelete({id} [, {win}])
```

Delete the match with {id}.

menu_get

```
menu_get({path} [, {modes}])
```

List of dicts describing the menus under {path}.

menu_info

```
menu_info({name} [, {mode}])
```

Dict of information about menu {name}.

mode

```
mode([{expr}])
```

Current mode as a short String ('n', 'i', 'v', ...).

preinserted

```
preinserted()
```

Text inserted by the current 'completefunc'/preinsert, if any.

prompt_appendbuf

```
prompt_appendbuf({buf}, {expr})
```

Append {expr} to prompt-buffer {buf} above the prompt (stub in standalone).

prompt_getinput

```
prompt_getinput({buf})
```

Current input line in prompt-buffer {buf} (stub in standalone).

prompt_getprompt

```
prompt_getprompt({buf})
```

Prompt string of prompt-buffer {buf} (stub in standalone).

prompt_setcallback

```
prompt_setcallback({buf}, {expr})
```

Set the callback invoked on Enter in prompt-buffer {buf} (stub in standalone).

prompt_setinterrupt

```
prompt_setinterrupt({buf}, {expr})
```

Set the callback invoked on CTRL-C in prompt-buffer {buf} (stub in standalone).

prompt_setprompt

```
prompt_setprompt({buf}, {text})
```

Set the prompt of prompt-buffer {buf} to {text} (stub in standalone).

pum_getpos

```
pum_getpos()
```

Dict describing the popup menu position, or empty if hidden.

pumvisible

```
pumvisible()
```

1 if the Insert-mode popup menu is visible, else 0 (stub in standalone).

reg_executing

```
reg_executing()
```

Name of the register being executed (replayed), or empty (stub in standalone).

reg_recorded

```
reg_recorded()
```

Name of the register last recorded into, or empty (stub in standalone).

reg_recording

```
reg_recording()
```

Name of the register being recorded into, or empty (stub in standalone).

screenattr

```
screenattr({row}, {col})
```

Highlight attribute id of the screen cell at {row},{col} (stub in standalone).

screenchar

```
screenchar({row}, {col})
```

Codepoint of the character on the screen at {row},{col} (stub in standalone).

screenchars

```
screenchars({row}, {col})
```

List of codepoints (incl. composing) at screen cell {row},{col}.

screencol

```
screencol()
```

Current cursor screen column (stub in standalone).

screenpos

```
screenpos({winid}, {lnum}, {col})
```

Screen position of buffer position {lnum},{col}.

screenrow

```
screenrow()
```

Current cursor screen row (stub in standalone).

screenstring

```
screenstring({row}, {col})
```

String of the character(s) at screen cell {row},{col} (stub in standalone).

search

```
search({pattern} [, {flags} [, {stopline} [, {timeout} [, {skip}]]]])
```

Search for {pattern}; returns the matching line number, else 0.

searchcount

```
searchcount([{options}])
```

Dict of search match counts for the last/used pattern.

searchdecl

```
searchdecl({name} [, {global} [, {thisblock}]])
```

Move to the declaration of {name}; 0 if found (stub in standalone).

searchpair

```
searchpair({start}, {middle}, {end} [, {flags} ...])
```

Search for the matching {end} of a nested {start}/{end} pair.

searchpairpos

```
searchpairpos({start}, {middle}, {end} [, {flags} ...])
```

Like searchpair() but returns the [line, col] of the match.

searchpos

```
searchpos({pattern} [, {flags} [, {stopline} [, {timeout} [, {skip}]]]])
```

Like search() but returns the [line, col] of the match.

setcellwidths

```
setcellwidths({list})
```

Override the display cell width of character ranges from {list}.

setcharpos

```
setcharpos({expr}, {list})
```

Like setpos() but the column in {list} is a character index.

setcharsearch

```
setcharsearch({dict})
```

Set the last character-search state from {dict} (stub in standalone).

setcmdline

```
setcmdline({str} [, {pos}])
```

Set the command line to {str} with the cursor at {pos}.

setcmdpos

```
setcmdpos({pos})
```

Set the cursor position in the command line to {pos}.

setcursorcharpos

```
setcursorcharpos({lnum}, {col} [, {off}])
```

Move the cursor to character position {lnum},{col}.

setloclist

```
setloclist({nr}, {list} [, {action} [, {what}]])
```

Set the location list for window {nr}.

setmatches

```
setmatches({list} [, {win}])
```

Restore matches from a List produced by getmatches().

setpos

```
setpos({expr}, {list})
```

Set cursor/mark position {expr} from [bufnum, lnum, col, off].

setqflist

```
setqflist({list} [, {action} [, {what}]])
```

Set the quickfix list.

setreg

```
setreg({regname}, {value} [, {options}])
```

Set register {regname} to {value} with optional type {options}.

settabvar

```
settabvar({tabnr}, {varname}, {val})
```

Set tab-local variable {varname} of tab {tabnr} (stub in standalone).

settabwinvar

```
settabwinvar({tabnr}, {winnr}, {varname}, {val})
```

Set a window-local variable in window {winnr} of tab {tabnr} (stub in standalone).

settagstack

```
settagstack({winnr}, {dict} [, {action}])
```

Set the tag stack of window {winnr} (stub in standalone).

setwinvar

```
setwinvar({nr}, {varname}, {val})
```

Set window-local variable/option {varname} of window {nr} (stub in standalone).

shiftwidth

```
shiftwidth([{col}])
```

Effective 'shiftwidth' value (resolving 0 to 'tabstop').

sign_define

```
sign_define({name} [, {dict}])
```

Define sign {name} with attributes; 0 on success.

sign_getdefined

```
sign_getdefined([{name}])
```

List of defined signs (or just {name}).

sign_getplaced

```
sign_getplaced([{buf} [, {dict}])
```

List of signs placed in a buffer.

sign_jump

```
sign_jump({id}, {group}, {buf})
```

Jump to sign {id} of {group} in buffer {buf}.

sign_place

```
sign_place({id}, {group}, {name}, {buf} [, {dict}])
```

Place sign {name} in buffer {buf}; returns the sign id.

sign_placelist

```
sign_placelist({list})
```

Place a List of signs at once; List of ids.

sign_undefine

```
sign_undefine([{name}])
```

Undefine sign {name} (or all signs).

sign_unplace

```
sign_unplace({group} [, {dict}])
```

Remove placed sign(s) in {group}.

sign_unplacelist

```
sign_unplacelist({list})
```

Remove a List of placed signs.

spellbadword

```
spellbadword([{sentence}])
```

[badword, type] of the first misspelled word at/after the cursor.

spellsuggest

```
spellsuggest({word} [, {max} [, {capital}]])
```

List of spelling suggestions for {word}.

state

```
state([{what}])
```

String of characters describing Vim's current busy/blocking state (stub in standalone).

synID

```
synID({lnum}, {col}, {trans})
```

Syntax ID at line {lnum}, column {col} (stub in standalone).

synIDattr

```
synIDattr({synID}, {what} [, {mode}])
```

Attribute {what} of syntax ID {synID} (stub in standalone).

synIDtrans

```
synIDtrans({synID})
```

Translated (effective) syntax ID for {synID} (stub in standalone).

synconcealed

```
synconcealed({lnum}, {col})
```

Info about concealed text at line {lnum}, column {col}.

synstack

```
synstack({lnum}, {col})
```

List of syntax IDs stacked at line {lnum}, column {col}.

tabpagebuflist

```
tabpagebuflist([ {arg} ])
```

List of buffer numbers shown in a tab page (stub in standalone).

tabpagenr

```
tabpagenr([ {arg} ])
```

Number of the current (or last) tab page (stub in standalone).

tabpagewinnr

```
tabpagewinnr({tabnr} [, {arg}])
```

Number of the current window in tab {tabnr} (stub in standalone).

tagfiles

```
tagfiles()
```

List of tags files used by the current buffer.

taglist

```
taglist({expr} [, {filename}])
```

List of tags matching the regexp {expr}.

test_garbagecollect_now

```
test_garbagecollect_now()
```

Test helper: run the garbage collector immediately (stub in standalone).

test_write_list_log

```
test_write_list_log({fname})
```

Test helper: write the internal list-allocation log to {fname} (stub in standalone).

timer_info

```
timer_info([id])
```

List of dicts describing active timers.

timer_pause

```
timer_pause({timer}, {paused})
```

Pause or unpause timer {timer} (stub in standalone).

timer_start

```
timer_start({time}, {callback} [, {options}])
```

Start a timer firing {callback} after {time} ms; returns its id (stub in standalone).

timer_stop

```
timer_stop({timer})
```

Stop timer {timer} (stub in standalone).

timer_stopall

```
timer_stopall()
```

Stop all timers (stub in standalone).

visualmode

```
visualmode([expr])
```

Last Visual mode used ('v', 'V', or CTRL-V) (stub in standalone).

wait

```
wait({timeout}, {condition} [, {interval}])
```

Wait until {condition} is true or {timeout} ms elapse (stub in standalone).

wildmenumode

```
wildmenumode()
```

1 if the wildmenu command-line completion menu is active (stub in standalone).

wildtrigger

```
wildtrigger()
```

Trigger command-line ('wildchar') completion programmatically (stub in standalone).

win_execute

```
win_execute({id}, {command} [, {silent}])
```

Execute {command} as if in window {id}, returning its output (stub in standalone).

win_findbuf

```
win_findbuf({bufnr})
```

List of window-IDs that display buffer {bufnr}.

win_getid

```
win_getid([win] [, {tab}])
```

window-ID of window {win} in tab {tab} (stub in standalone).

win_gettype

```
win_gettype([nr])
```

Type of window {nr} ('popup', 'command', 'autocmd', ...).

win_gotoid

```
win_gotoid({id})
```

Go to the window with window-ID {id}; 1 on success (stub in standalone).

win_id2tabwin

```
win_id2tabwin({id})
```

[tabnr, winnr] of window-ID {id}.

win_id2win

```
win_id2win({id})
```

Window number of window-ID {id}, else 0 (stub in standalone).

win_move_separator

```
win_move_separator(nr, {offset})
```

Move the vertical separator of window {nr} by {offset} (stub in standalone).

win_move_statusline

```
win_move_statusline({nr}, {offset})
```

Move the status line of window {nr} by {offset} (stub in standalone).

win_screenpos

```
win_screenpos({nr})
```

[row, col] screen position of the top-left of window {nr}.

win_splitmove

```
win_splitmove({nr}, {target} [, {options}])
```

Move window {nr} to split alongside window {target} (stub in standalone).

wincol

```
wincol()
```

Cursor's screen column within its window (stub in standalone).

winheight

```
winheight({nr})
```

Height (in lines) of window {nr}, else -1 (stub in standalone).

winlayout

```
winlayout([{tabnr}])
```

Nested List describing the window layout of a tab page.

winline

```
winline()
```

Cursor's screen row within its window (stub in standalone).

winnr

```
winnr([{arg}])
```

Number of the current (or related) window (stub in standalone).

winrestcmd

```
winrestcmd()
```

Ex command string that restores the current window sizes (stub in standalone).

winrestview

```
winrestview({dict})
```

Restore the window view from a winsaveview() dict (stub in standalone).

winsaveview

```
winsaveview()
```

Dict capturing the current window view (cursor, scroll).

winwidth

```
winwidth({nr})
```

Width (in columns) of window {nr}, else -1 (stub in standalone).

wordcount

```
wordcount()
```

Dict of byte/char/word counts for the buffer and cursor.

Ex Commands

6 entries

echo

:echo {expr} — evaluate and display {expr} (space-separated).

echon

:echon {expr} — like :echo but without a trailing newline.

echomsg

:echomsg {expr} — display {expr} and save it in the message history.

let

:let {var} = {expr} — assign the value of {expr} to {var}.

call

:call {func}({args}) — call a function and discard its return value.

eval

:eval {expr} — evaluate {expr} for its side effects.

Options

15 entries

ignorecase

```
:set ignorecase (ic) - Bool, default 0
```

Ignore case in search patterns.

smartcase

```
:set smartcase (scs) - Bool, default 0
```

Override 'ignorecase' when the pattern has uppercase letters.

magic

```
:set magic (magic) - Bool, default 1
```

Use 'magic' regexp special-character meanings.

expandtab

```
:set expandtab (et) - Bool, default 0
```

Insert spaces instead of a <Tab>.

number

```
:set number (nu) - Bool, default 0
```

Show line numbers in the left margin.

relativenumber

```
:set relativenumber (rnu) - Bool, default 0
```

Show line numbers relative to the cursor.

wrap

```
:set wrap (wrap) - Bool, default 1
```

Wrap long lines to fit the window width.

hlsearch

```
:set hlsearch (hls) - Bool, default 0
```

Highlight all matches of the last search pattern.

incsearch

```
:set incsearch (is) - Bool, default 0
```

Show the match for the search pattern as it is typed.

autoindent

```
:set autoindent (ai) - Bool, default 0
```

Copy the indent of the current line to a new line.

tabstop

```
:set tabstop (ts) - Number, default 8
```

Number of spaces a <Tab> counts for.

shiftwidth

```
:set shiftwidth (sw) - Number, default 8
```

Number of spaces used for each step of (auto)indent.

softtabstop

```
:set softtabstop (sts) - Number, default 0
```

Number of spaces a <Tab> counts for while editing.

textwidth

```
:set textwidth (tw) - Number, default 0
```

Maximum text width; longer lines are broken (0 = off).

scrolloff

```
:set scrolloff (so) - Number, default 0
```

Minimum lines kept above and below the cursor.

Special v: Variables

3 entries

v:true

Boolean true; numeric value 1, string value "v:true".

v:false

Boolean false; numeric value 0, string value "v:false".

v:null

Null value; behaves like an empty string in most contexts.