

—— // AWKRS // ——

awkrs – Language Reference

v0.4.18

LANGUAGE REFERENCE

every builtin · function · variable · special file

2026-07-13

MenkeTechnologies

—— MENKETECHNOLOGIES ——

Contents

String Functions	2
Arithmetic Functions	4
I/O & General Functions	6
Time Functions (gawk)	7
Bitwise Functions (gawk)	8
Array & Type Functions (gawk)	9
Special Variables	10
Keywords & Control Flow	13

String Functions

11 topics

length

```
length([s])
```

Length of string `s` (or `$0`), or element count of an array.

substr

```
substr(s, m [, n])
```

`n`-char substring of `s` starting at position `m` (1-based).

index

```
index(s, t)
```

1-based position of `t` in `s`, or 0 if not found.

split

```
split(s, arr [, fs [, seps]])
```

Split `s` into `arr` on `fs`; returns the field count.

sub

```
sub(re, repl [, target])
```

Replace first match of `re` in `target` (`$0`); returns 1/0.

gsub

```
gsub(re, repl [, target])
```

Replace all matches of `re` in `target` (`$0`); returns count.

match

```
match(s, re [, arr])
```

Set RSTART/RLENGTH to the match of `re` in `s`; returns position or 0.

sprintf

```
sprintf(fmt, ...)
```

Format the arguments per `fmt` and return the string.

tolower

```
tolower(s)
```

Copy of `s` with uppercase letters lowercased.

toupper

```
toupper(s)
```

Copy of `s` with lowercase letters uppercased.

gensub

```
gensub(re, repl, how [, target])
```

Non-destructive global/Nth substitution returning the new string.

Arithmetic Functions

9 topics

`sin`

```
sin(x)
```

Sine of x (radians).

`cos`

```
cos(x)
```

Cosine of x (radians).

`atan2`

```
atan2(y, x)
```

Arctangent of y/x in radians.

`exp`

```
exp(x)
```

e raised to the power x .

`log`

```
log(x)
```

Natural logarithm of x .

`sqrt`

```
sqrt(x)
```

Square root of x .

`int`

```
int(x)
```

Integer part of x , truncated toward zero.

`rand`

```
rand()
```

Pseudo-random number in $[0, 1)$.

srand

```
srand([x])
```

Seed the RNG with `x` (or time); returns the previous seed.

I/O & General Functions

6 topics

print

`print` — keyword

Write its arguments to output, separated by `DFS` and terminated by `ORS`.

printf

```
printf(fmt, ...)
```

Format and print the arguments per `fmt`.

getline

`getline` — keyword

Read the next record into `$0` or a variable from input, a file, or a command.

close

```
close(file [, how])
```

Close an open file/pipe; returns its status.

system

```
system(cmd)
```

Run `cmd` via the shell; returns its exit status.

fflush

```
fflush([file])
```

Flush buffers for `file`, or all outputs if omitted.

Time Functions (gawk)

3 topics

sys`time`

```
systime()
```

Current time as seconds since the epoch (gawk).

str`ftime`

```
strftime([fmt [, ts [, utc]])
```

Format timestamp `ts` per `fmt` (gawk).

mk`time`

```
mktime(spec [, utc])
```

Convert a "YYYY MM DD HH MM SS [DST]" spec to a timestamp (gawk).

Bitwise Functions (gawk)

6 topics

and

```
and(v1, v2, ...)
```

Bitwise AND of the arguments (gawk).

or

```
or(v1, v2, ...)
```

Bitwise OR of the arguments (gawk).

xor

```
xor(v1, v2, ...)
```

Bitwise XOR of the arguments (gawk).

compl

```
compl(v)
```

Bitwise complement of `v` (gawk).

lshift

```
lshift(v, n)
```

`v` left-shifted by `n` bits (gawk).

rshift

```
rshift(v, n)
```

`v` right-shifted by `n` bits (gawk).

Array & Type Functions (gawk)

5 topics

typeof

```
typeof(x)
```

Type of **x**: "scalar", "array", "untyped", ... (gawk).

isarray

```
isarray(x)
```

1 if **x** is an array, else 0 (gawk).

atsplit

```
atsplit(s, arr [, fpat [, seps]])
```

Split **s** into **arr** by the pattern **fpat** (gawk).

asort

```
asort(src [, dst [, how]])
```

Sort array values; returns the element count (gawk).

asorti

```
asorti(src [, dst [, how]])
```

Sort array indices; returns the element count (gawk).

Special Variables

25 topics

NR

NR — special variable

Total number of input records read so far.

NF

NF — special variable

Number of fields in the current record.

FS

FS — special variable

Input field separator (default " ").

OFS

OFS — special variable

Output field separator (default " ").

ORS

ORS — special variable

Output record separator (default "\n").

RS

RS — special variable

Input record separator (default "\n").

FILENAME

FILENAME — special variable

Name of the current input file.

FNR

FNR — special variable

Record number within the current input file.

RSTART

RSTART — special variable

Start position of the last match() (1-based), or 0.

RLENGTH

RLENGTH — special variable

Length of the last match(), or -1.

SUBSEP

SUBSEP — special variable

Subscript separator for multi-dimensional array keys.

ARGC

ARGC — special variable

Count of command-line arguments in ARGV.

ARGV

ARGV — special variable

Array of command-line arguments.

ENVIRON

ENVIRON — special variable

Array of the process environment variables.

CONVFMT

CONVFMT — special variable

Conversion format for numbers used as strings (default "%.6g").

OFMT

OFMT — special variable

Output format for numbers in print (default "%.6g").

IGNORECASE

IGNORECASE — special variable

When non-zero, regex and string comparisons ignore case (gawk).

FIELDWIDTHS

FIELDWIDTHS — special variable

Space-separated fixed field widths for parsing (gawk).

FPAT

FPAT — special variable

Regex describing field contents, as an alternative to FS (gawk).

PROCINFO

PROCINFO — special variable

Array of process/runtime information (gawk).

RT

RT — special variable

Text matched by RS for the current record (gawk).

ERRNO

ERRNO — special variable

Description of the last getline/close/system error (gawk).

TEXTDOMAIN

TEXTDOMAIN — special variable

Text domain for string translation (gawk).

BINMODE

BINMODE — special variable

Binary I/O mode control (gawk).

LINT

LINT — special variable

Dynamic control of lint warnings (gawk).

Keywords & Control Flow

21 topics

BEGIN

BEGIN — keyword

Special pattern whose action runs once before any input is read.

END

END — keyword

Special pattern whose action runs once after all input is consumed.

BEGINFILE

BEGINFILE — keyword

Pattern whose action runs before each input file is read (gawk).

ENDFILE

ENDFILE — keyword

Pattern whose action runs after each input file is processed (gawk).

function

function — keyword

Define a user function: **function** *name(params)* { *body* }.

if

if — keyword

Conditional statement: **if** (*cond*) *stmt* with an optional **else** branch.

else

else — keyword

The alternative branch taken when an **if** condition is false.

while

while — keyword

Loop that repeats *stmt* while *cond* is true: **while** (*cond*) *stmt*.

for

for — keyword

Loop: **for** (*init*; *cond*; *incr*) *stmt*, or **for** (*key in array*) *stmt*.

do

do — keyword

Do-while loop: **do** *stmt* **while** (*cond*); the body runs at least once.

break

break — keyword

Exit the innermost **for**, **while**, or **do** loop immediately.

continue

continue — keyword

Skip to the next iteration of the innermost loop.

next

next — keyword

Stop processing the current record and read the next one.

nextfile

nextfile — keyword

Stop processing the current input file and advance to the next.

exit

exit — keyword

Stop reading input and run **END**; **exit** [*expr*] sets the exit status.

return

return — keyword

Return from a user function, optionally with a value: **return** [*expr*].

delete

delete — keyword

Remove an array element (**delete** *arr*[*k*]) or clear it (**delete** *arr*).

switch

switch — keyword

Multi-way branch on a value: **switch** (*expr*) { **case** ...: ... } (gawk).

case

case — keyword

A labeled branch inside a **switch** statement (gawk).

`default`

`default` — keyword

The fallback branch taken when no `case` matches in a `switch` (gawk).

`in`

`in` — keyword

Array membership test (`key in arr`) or iteration (`for (key in arr)`).