

—— // ZEMACS // ——

zemacs — Reference

v0.2.4

THE REFERENCE

every key · every command · every setting

2026-06-30

MenkeTechnologies

—— MENKETECHNOLOGIES ——

Contents

About This Reference	2
Keymap	3
Keymap	3
Normal mode	3
Insert mode	13
Select / extend mode	14
Picker.....	14
Prompt.....	14
Configuration and Settings	16
Editor	16
Typable Commands	33
Static Commands and Keybindings	45
Language Support	69

About This Reference

This is the zemacs reference: every keybinding, every configuration setting, and every command the editor ships, generated from the source. It is the companion to the narrative book — where the book explains *why*, this enumerates *what*.

The sections are: the **keymap** (organized by mode and prefix), the **configuration schema** ([\[editor\]](#) and its tables), the full list of **typable : commands**, the full list of **static commands with their default keybindings** by mode, and the **language-support** matrix.

Keymap

Keymap

- Normal mode
 - Movement
 - Changes
 - * Shell
 - Selection manipulation
 - Search
 - Minor modes
 - * View mode
 - * Goto mode
 - * Match mode
 - * Window mode
 - * Space mode
 - Popup
 - Completion Menu
 - Signature-help Popup
 - * Unimpaired
- Insert mode
- Select / extend mode
- Picker
- Prompt

□ Mappings marked (**LSP**) require an active language server for the file.

□ Mappings marked (**TS**) require a tree-sitter grammar for the file type.

⚠ Some terminals' default key mappings conflict with Helix's. If any of the mappings described on this page do not work as expected, check your terminal's mappings to ensure they do not conflict. See the [wiki](#) for known conflicts.

Normal mode

Normal mode is the default mode when you launch zemacs. You can return to it from other modes by pressing the **Escape** key.

Movement

NOTE: Unlike Vim, **f**, **F**, **t** and **T** are not confined to the current line.

Hereafter, **<n>** represents an integer by typing a sequence of digits.

Key	Description	Command
h , Left	Move left	<code>move_char_left</code>
j , Down	Move down	<code>move_visual_line_down</code>
k , Up	Move up	<code>move_visual_line_up</code>
l , Right	Move right	<code>move_char_right</code>
w	Move next word start	<code>move_next_word_start</code>
b	Move previous word start	<code>move_prev_word_start</code>
e	Move next word end	<code>move_next_word_end</code>

Key	Description	Command
W	Move next WORD start	<code>move_next_long_word_start</code>
B	Move previous WORD start	<code>move_prev_long_word_start</code>
E	Move next WORD end	<code>move_next_long_word_end</code>
t	Find till next char	<code>find_till_char</code>
f	Find next char	<code>find_next_char</code>
T	Find till previous char	<code>till_prev_char</code>
F	Find previous char	<code>find_prev_char</code>
<n>G, <n>gg	Go to line number <n>	<code>goto_line</code>
Alt-.	Repeat last motion (f, t, m, [or])	<code>repeat_last_motion</code>
Home	Move to the start of the line	<code>goto_line_start</code>
End	Move to the end of the line	<code>goto_line_end</code>
Ctrl-b, PageUp	Move page up	<code>page_up</code>
Ctrl-f, PageDown	Move page down	<code>page_down</code>
Ctrl-u	Move cursor and page half page up	<code>page_cursor_half_up</code>
Ctrl-d	Move cursor and page half page down	<code>page_cursor_half_down</code>
Ctrl-i	Jump forward on the jumplist	<code>jump_forward</code>
Ctrl-o	Jump backward on the jumplist	<code>jump_backward</code>
Ctrl-s	Save the current selection to the jumplist	<code>save_selection</code>

Changes

Key	Description	Command
r	Replace with a character	<code>replace</code>
R	Replace with yanked text	<code>replace_with_yanked</code>
~	Switch case of the selected text	<code>switch_case</code>
`	Set the selected text to lower case	<code>switch_to_lowercase</code>
Alt-`	Set the selected text to upper case	<code>switch_to_uppercase</code>
i	Insert before selection	<code>insert_mode</code>
a	Insert after selection (append)	<code>append_mode</code>
I	Insert at the start of the line	<code>insert_at_line_start</code>
A	Insert at the end of the line	<code>insert_at_line_end</code>
o	Open new line below selection	<code>open_below</code>
O	Open new line above selection	<code>open_above</code>
.	Repeat last insert	N/A
u	Undo change	<code>undo</code>

Key	Description	Command
<code>U</code>	Redo change	<code>redo</code>
<code>Alt-u</code>	Move backward in history	<code>earlier</code>
<code>Alt-U</code>	Move forward in history	<code>later</code>
<code>y</code>	Yank selection	<code>yank</code>
<code>P</code>	Paste after selection	<code>paste_after</code>
<code>p</code>	Paste before selection	<code>paste_before</code>
<code>" <reg></code>	Select a register to yank to or paste from	<code>select_register</code>
<code>></code>	Indent selection	<code>indent</code>
<code><</code>	Unindent selection	<code>unindent</code>
<code>=</code>	Format selection (LSP)	<code>format_selections</code>
<code>d</code>	Delete selection	<code>delete_selection</code>
<code>Alt-d</code>	Delete selection, without yanking	<code>delete_selection_noyank</code>
<code>c</code>	Change selection (delete and enter insert mode)	<code>change_selection</code>
<code>Alt-c</code>	Change selection (delete and enter insert mode, without yanking)	<code>change_selection_noyank</code>
<code>[ctrl-a</code>	Increment object (number) under cursor	<code>increment</code>
<code>[ctrl-x</code>	Decrement object (number) under cursor	<code>decrement</code>
<code>Q</code>	Start/stop macro recording to the selected register (experimental)	<code>record_macro</code>
<code>q</code>	Play back a recorded macro from the selected register (experimental)	<code>replay_macro</code>
<code>[ctrl-z</code>	Suspend Zemacs and return to the shell (resume with <code>fg</code>)	<code>suspend</code>

Shell

Key	Description	Command
<code> </code>	Pipe each selection through shell command, replacing with output	<code>shell_pipe</code>
<code>Alt- </code>	Pipe each selection into shell command, ignoring output	<code>shell_pipe_to</code>
<code>!</code>	Run shell command, inserting output before each selection	<code>shell_insert_output</code>
<code>Alt-!</code>	Run shell command, appending output after each selection	<code>shell_append_output</code>
<code>\$</code>	Pipe each selection into shell command, keep selections where command returned 0	<code>shell_keep_pipe</code>

Selection manipulation

Key	Description	Command
<code>s</code>	Select all regex matches inside selections	<code>select_regex</code>
<code>S</code>	Split selection into sub selections on regex matches	<code>split_selection</code>

Key	Description	Command
<code>Alt-s</code>	Split selection on newlines	<code>split_selection_on_newline</code>
<code>Alt-minus</code>	Merge selections	<code>merge_selections</code>
<code>Alt-_</code>	Merge consecutive selections	<code>merge_consecutive_selections</code>
<code>&</code>	Align selection in columns	<code>align_selections</code>
<code>-</code>	Trim whitespace from the selection	<code>trim_selections</code>
<code>;</code>	Collapse selection onto a single cursor	<code>collapse_selection</code>
<code>Alt-;</code>	Flip selection cursor and anchor	<code>flip_selections</code>
<code>Alt-:</code>	Ensures the selection is in forward direction	<code>ensure_selections_forward</code>
<code>,</code>	Keep only the primary selection	<code>keep_primary_selection</code>
<code>Alt-,</code>	Remove the primary selection	<code>remove_primary_selection</code>
<code>C</code>	Copy selection onto the next line (Add cursor below)	<code>copy_selection_on_next_line</code>
<code>Alt-C</code>	Copy selection onto the previous line (Add cursor above)	<code>copy_selection_on_prev_line</code>
<code>(</code>	Rotate main selection backward	<code>rotate_selections_backward</code>
<code>)</code>	Rotate main selection forward	<code>rotate_selections_forward</code>
<code>Alt-(</code>	Rotate selection contents backward	<code>rotate_selection_contents_backward</code>
<code>Alt-)</code>	Rotate selection contents forward	<code>rotate_selection_contents_forward</code>
<code>%</code>	Select entire file	<code>select_all</code>
<code>x</code>	Select current line, if already selected, extend to next line	<code>extend_line_below</code>
<code>X</code>	Extend selection to line bounds (line-wise selection)	<code>extend_to_line_bounds</code>
<code>Alt-x</code>	Shrink selection to line bounds (line-wise selection)	<code>shrink_to_line_bounds</code>
<code>J</code>	Join lines inside selection	<code>join_selections</code>
<code>Alt-J</code>	Join lines inside selection and select the inserted space	<code>join_selections_space</code>
<code>K</code>	Keep selections matching the regex	<code>keep_selections</code>
<code>Alt-K</code>	Remove selections matching the regex	<code>remove_selections</code>
<code>Ctrl-c</code>	Comment/uncomment the selections	<code>toggle_comments</code>
<code>Alt-o, Alt-up</code>	Expand selection to parent syntax node (TS)	<code>expand_selection</code>
<code>Alt-i, Alt-down</code>	Shrink syntax tree object selection (TS)	<code>shrink_selection</code>
<code>Alt-p, Alt-left</code>	Select previous sibling node in syntax tree (TS)	<code>select_prev_sibling</code>
<code>Alt-n, Alt-right</code>	Select next sibling node in syntax tree (TS)	<code>select_next_sibling</code>
<code>Alt-a</code>	Select all sibling nodes in syntax tree (TS)	<code>select_all_siblings</code>
<code>Alt-I, Alt-Shift-down</code>	Select all children nodes in syntax tree (TS)	<code>select_all_children</code>
<code>Alt-e</code>	Move to end of parent node in syntax tree (TS)	<code>move_parent_node_end</code>

Key	Description	Command
<code>Alt-b</code>	Move to start of parent node in syntax tree (TS)	<code>move_parent_node_start</code>

Search

Search commands all operate on the `/` register by default. To use a different register, use "`<char>`".

Key	Description	Command
<code>/</code>	Search for regex pattern	<code>search</code>
<code>?</code>	Search for previous pattern	<code>rsearch</code>
<code>n</code>	Select next search match	<code>search_next</code>
<code>N</code>	Select previous search match	<code>search_prev</code>
<code>*</code>	Use current selection as the search pattern, automatically wrapping with <code>\b</code> on word boundaries	<code>search_selection_detect_word_boundaries</code>
<code>Alt-*</code>	Use current selection as the search pattern	<code>search_selection</code>

Minor modes

These sub-modes are accessible from normal mode and typically switch back to normal mode after a command.

Key	Description	Command
<code>v</code>	Enter select (extend) mode	<code>select_mode</code>
<code>g</code>	Enter <code>goto mode</code>	N/A
<code>m</code>	Enter <code>match mode</code>	N/A
<code>:</code>	Enter command mode	<code>command_mode</code>
<code>z</code>	Enter <code>view mode</code>	N/A
<code>Z</code>	Enter sticky <code>view mode</code>	N/A
<code>[ctrl-w</code>	Enter <code>window mode</code>	N/A
<code>Space</code>	Enter <code>space mode</code>	N/A

These modes (except command mode) can be configured by [remapping keys](#).

View mode

Accessed by typing `z` in `normal mode`.

View mode is intended for scrolling and manipulating the view without changing the selection. The "sticky" variant of this mode (accessed by typing `Z` in normal mode) is persistent and can be exited using the escape key. This is useful when you're simply looking over text and not actively editing it.

Key	Description	Command
<code>z, c</code>	Vertically center the line	<code>align_view_center</code>
<code>t</code>	Align the line to the top of the screen	<code>align_view_top</code>
<code>b</code>	Align the line to the bottom of the screen	<code>align_view_bottom</code>

Key	Description	Command
<code>m</code>	Align the line to the middle of the screen (horizontally)	<code>align_view_middle</code>
<code>j</code> , <code>down</code>	Scroll the view downwards	<code>scroll_down</code>
<code>k</code> , <code>up</code>	Scroll the view upwards	<code>scroll_up</code>
<code>Ctrl-f</code> , <code>PageDown</code>	Move page down	<code>page_down</code>
<code>Ctrl-b</code> , <code>PageUp</code>	Move page up	<code>page_up</code>
<code>Ctrl-u</code>	Move cursor and page half page up	<code>page_cursor_half_up</code>
<code>Ctrl-d</code>	Move cursor and page half page down	<code>page_cursor_half_down</code>

Goto mode

Accessed by typing `g` in **normal mode**.

Jumps to various locations.

Key	Description	Command
<code><n>g</code>	Go to line number <code><n></code>	<code>goto_file_start</code>
<code>g</code>	Go to the start of the file	<code>goto_file_start</code>
<code><n> </code>	Go to column number <code><n></code>	<code>goto_column</code>
<code> </code>	Go to the start of line	<code>goto_column</code>
<code>e</code>	Go to the end of the file	<code>goto_last_line</code>
<code>f</code>	Go to files/URLs in selections	<code>goto_file</code>
<code>h</code>	Go to the start of the line	<code>goto_line_start</code>
<code>l</code>	Go to the end of the line	<code>goto_line_end</code>
<code>s</code>	Go to first non-whitespace character of the line	<code>goto_first_nonwhitespace</code>
<code>t</code>	Go to the top of the screen	<code>goto_window_top</code>
<code>c</code>	Go to the middle of the screen	<code>goto_window_center</code>
<code>b</code>	Go to the bottom of the screen	<code>goto_window_bottom</code>
<code>d</code>	Go to definition (LSP)	<code>goto_definition</code>
<code>D</code>	Go to declaration (LSP)	<code>goto_declaration</code>
<code>y</code>	Go to type definition (LSP)	<code>goto_type_definition</code>
<code>r</code>	Go to references (LSP)	<code>goto_reference</code>
<code>i</code>	Go to implementation (LSP)	<code>goto_implementation</code>
<code>a</code>	Go to the last accessed/alternate file	<code>goto_last_accessed_file</code>
<code>m</code>	Go to the last modified/alternate file	<code>goto_last_modified_file</code>
<code>n</code>	Go to next buffer	<code>goto_next_buffer</code>
<code>p</code>	Go to previous buffer	<code>goto_previous_buffer</code>
<code>.</code>	Go to last modification in current file	<code>goto_last_modification</code>
<code>j</code>	Move down textual (instead of visual) line	<code>move_line_down</code>

Key	Description	Command
k	Move up textual (instead of visual) line	<code>move_line_up</code>
w	Show labels at each word and select the word that belongs to the entered labels	<code>goto_word</code>

Match mode

Accessed by typing **m** in **normal mode**.

Please refer to the relevant sections for detailed explanations about **surround** and **textobjects**.

Key	Description	Command
m	Goto matching bracket (TS)	<code>match_brackets</code>
s <char>	Surround current selection with <char>	<code>surround_add</code>
r <from> <to>	Replace surround character <from> with <to>	<code>surround_replace</code>
d <char>	Delete surround character <char>	<code>surround_delete</code>
a <object>	Select around textobject	<code>select_textobject_around</code>
i <object>	Select inside textobject	<code>select_textobject_inner</code>

TODO: Mappings for selecting syntax nodes (a superset of **[]**).

Window mode

Accessed by typing **Ctrl-w** in **normal mode**.

This layer is similar to Vim keybindings as Kakoune does not support windows.

Key	Description	Command
w , Ctrl-w	Switch to next window	<code>rotate_view</code>
v , Ctrl-v	Vertical right split	<code>vsplit</code>
s , Ctrl-s	Horizontal bottom split	<code>hsplit</code>
t , Ctrl-t	Transpose the two adjacent splits	<code>transpose_view</code>
f	Go to files/URLs in selections in horizontal splits	<code>goto_file_hsplit</code>
F	Go to files/URLs in selections in vertical splits	<code>goto_file_vsplit</code>
h , Ctrl-h , Left	Move to left split	<code>jump_view_left</code>
j , Ctrl-j , Down	Move to split below	<code>jump_view_down</code>
k , Ctrl-k , Up	Move to split above	<code>jump_view_up</code>
l , Ctrl-l , Right	Move to right split	<code>jump_view_right</code>
q , Ctrl-q	Close current window	<code>wclose</code>
o , Ctrl-o	Only keep the current window, closing all the others	<code>wonly</code>
H	Swap window to the left	<code>swap_view_left</code>
J	Swap window downwards	<code>swap_view_down</code>
K	Swap window upwards	<code>swap_view_up</code>

Key	Description	Command
<code>L</code>	Swap window to the right	<code>swap_view_right</code>
<code>ns, nCtrl-s</code>	New horizontal split with a scratch buffer	<code>hsplit_new</code>
<code>nv, nCtrl-v</code>	New vertical split with a scratch buffer	<code>vsplit_new</code>

Space mode

Accessed by typing `Space` in `normal mode`.

This layer is a kludge of mappings, mostly pickers.

Key	Description	Command
<code>f</code>	Open file picker at LSP workspace root	<code>file_picker</code>
<code>F</code>	Open file picker at current working directory	<code>file_picker_in_current_directory</code>
<code>e</code>	Open file explorer at workspace root	<code>file_explorer</code>
<code>.</code>	Open file explorer at current buffer's directory	<code>file_explorer_in_current_buffer_directory</code>
<code>b</code>	Open buffer picker	<code>buffer_picker</code>
<code>j</code>	Open jumplist picker	<code>jumplist_picker</code>
<code>g</code>	Open changed file picker	<code>changed_file_picker</code>
<code>G</code>	Debug (experimental)	N/A
<code>k</code>	Show documentation for item under cursor in a <code>popup</code> (LSP)	<code>hover</code>
<code>s</code>	Open document symbol picker (LSP or TS)	<code>lsp_or_syntax_symbol_picker</code>
<code>S</code>	Open workspace symbol picker (LSP or TS)	<code>lsp_or_syntax_workspace_symbol_picker</code>
<code>d</code>	Open document diagnostics picker (LSP)	<code>diagnostics_picker</code>
<code>D</code>	Open workspace diagnostics picker (LSP)	<code>workspace_diagnostics_picker</code>
<code>r</code>	Rename symbol (LSP)	<code>rename_symbol</code>
<code>a</code>	Apply code action (LSP)	<code>code_action</code>
<code>h</code>	Select symbol references (LSP)	<code>select_references_to_symbol_under_cursor</code>
<code>,</code>	Open last fuzzy picker	<code>last_picker</code>
<code>w</code>	Enter <code>window mode</code>	N/A
<code>c</code>	Comment/uncomment selections	<code>toggle_comments</code>
<code>C</code>	Block comment/uncomment selections	<code>toggle_block_comments</code>
<code>Alt-c</code>	Line comment/uncomment selections	<code>toggle_line_comments</code>
<code>p</code>	Paste system clipboard after selections	<code>paste_clipboard_after</code>
<code>P</code>	Paste system clipboard before selections	<code>paste_clipboard_before</code>

Key	Description	Command
y	Yank selections to clipboard	yank_to_clipboard
Y	Yank main selection to clipboard	yank_main_selection_to_clipboard
R	Replace selections by clipboard contents	replace_selections_with_clipboard
/	Global search in workspace folder	global_search
?	Open command palette	command_palette

□ Global search displays results in a fuzzy picker, use **Space + '** to bring it back up after opening a file.

Popup Displays documentation for item under cursor. Remapping currently not supported.

Key	Description
Ctrl-u	Scroll up
Ctrl-d	Scroll down

Completion Menu Displays documentation for the selected completion item. Remapping currently not supported.

Key	Description
Shift-Tab, Ctrl-p, Up	Previous entry
Tab, Ctrl-n, Down	Next entry
Enter	Close menu and accept completion
Ctrl-c	Close menu and reject completion

Any other keypresses result in the completion being accepted.

Signature-help Popup Displays the signature of the selected completion item. Remapping currently not supported.

Key	Description
Alt-p	Previous signature
Alt-n	Next signature

Unimpaired

These mappings are in the style of **vim-unimpaired**.

Key	Description	Command
]d	Go to next diagnostic (LSP)	goto_next_diag
[d	Go to previous diagnostic (LSP)	goto_prev_diag
]D	Go to last diagnostic in document (LSP)	goto_last_diag
[D	Go to first diagnostic in document (LSP)	goto_first_diag
]f	Go to next function (TS)	goto_next_function
[f	Go to previous function (TS)	goto_prev_function
]t	Go to next type definition (TS)	goto_next_class

Key	Description	Command
[t	Go to previous type definition (TS)	goto_prev_class
]a	Go to next argument/parameter (TS)	goto_next_parameter
[a	Go to previous argument/parameter (TS)	goto_prev_parameter
]c	Go to next comment (TS)	goto_next_comment
[c	Go to previous comment (TS)	goto_prev_comment
]e	Go to next entry (TS)	goto_next_entry
[e	Go to previous entry (TS)	goto_prev_entry
]T	Go to next test (TS)	goto_next_test
[T	Go to previous test (TS)	goto_prev_test
]p	Go to next paragraph	goto_next_paragraph
[p	Go to previous paragraph	goto_prev_paragraph
]g	Go to next change	goto_next_change
[g	Go to previous change	goto_prev_change
]G	Go to last change	goto_last_change
[G	Go to first change	goto_first_change
]n	Go to next merge-conflict marker	goto_next_conflict
[n	Go to previous merge-conflict marker	goto_prev_conflict
]x	Go to next (X)HTML element	goto_next_xml_element
[x	Go to previous (X)HTML element	goto_prev_xml_element
]Space	Add newline below	add_newline_below
[Space	Add newline above	add_newline_above

Wildfire

In normal mode, expand or shrink the selection by syntax-aware text objects.

Key	Description	Command
<ret>	Select / grow to the closest enclosing text object	wildfire
<backspace>	Shrink to the previously selected text object	wildfire_shrink

Git conflicts and merge

These live under the space-**g** git menu (see [Space mode](#)) and the unpaired **]n**/**[n** motions above.

Key	Description	Command
SPC g m, SPC g c r	Open the 3-pane merge-conflict resolver (:merge)	resolve_conflicts
SPC g c O	Resolve all conflicts by keeping our side	conflict_take_all_ours
SPC g c T	Resolve all conflicts by keeping their side	conflict_take_all_theirs

Key	Description	Command
<code>SPC g =</code>	Side-by-side diff of the buffer vs. git HEAD (:diff)	<code>git_diff</code>

Insert mode

Accessed by typing `i` in `normal mode`.

Insert mode bindings are minimal by default. Emacs is designed to be a modal editor, and this is reflected in the user experience and internal mechanics. Changes to the text are only saved for undos when escaping from insert mode to normal mode.

- New users are strongly encouraged to learn the modal editing paradigm to get the smoothest experience.

Key	Description	Command
<code>Escape</code>	Switch to normal mode	<code>normal_mode</code>
<code>Ctrl-s</code>	Commit undo checkpoint	<code>commit_undo_checkpoint</code>
<code>Ctrl-x</code>	Autocomplete	<code>completion</code>
<code>Ctrl-r</code>	Insert a register content	<code>insert_register</code>
<code>Ctrl-w</code> , <code>Alt-Backspace</code>	Delete previous word	<code>delete_word_backward</code>
<code>Alt-d</code> , <code>Alt-Delete</code>	Delete next word	<code>delete_word_forward</code>
<code>Ctrl-u</code>	Delete to start of line	<code>kill_to_line_start</code>
<code>Ctrl-k</code>	Delete to end of line	<code>kill_to_line_end</code>
<code>Ctrl-h</code> , <code>Backspace</code> , <code>Shift-Backspace</code>	Delete previous char	<code>delete_char_backward</code>
<code>Ctrl-d</code> , <code>Delete</code>	Delete next char	<code>delete_char_forward</code>
<code>Ctrl-j</code> , <code>Enter</code>	Insert new line	<code>insert_newline</code>
<code>Tab</code>	Advance a snippet tab stop, else expand a snippet trigger or emmet abbreviation, else <code>smart tab</code>	<code>emmet_expand</code>
<code>Shift-Tab</code>	Insert tab	<code>insert_tab</code>

- `Tab` is overloaded in insert mode: if a snippet is active it jumps to the next tab stop; otherwise it tries to expand the word before the cursor as a `snippet` trigger or an emmet abbreviation; failing both, it behaves as a `smart tab`.

These keys are not recommended, but are included for new users less familiar with modal editors.

Key	Description	Command
<code>Up</code>	Move to previous line	<code>move_line_up</code>
<code>Down</code>	Move to next line	<code>move_line_down</code>
<code>Left</code>	Backward a char	<code>move_char_left</code>
<code>Right</code>	Forward a char	<code>move_char_right</code>
<code>PageUp</code>	Move one page up	<code>page_up</code>
<code>PageDown</code>	Move one page down	<code>page_down</code>
<code>Home</code>	Move to line start	<code>goto_line_start</code>

Key	Description	Command
End	Move to line end	<code>goto_line_end_newline</code>

As you become more comfortable with modal editing, you may want to disable some insert mode bindings. You can do this by editing your `config.toml` file.

```
[keys.insert]
up = "no_op"
down = "no_op"
left = "no_op"
right = "no_op"
pageup = "no_op"
pagedown = "no_op"
home = "no_op"
end = "no_op"
```

Select / extend mode

Accessed by typing `v` in [normal mode](#).

Select mode echoes Normal mode, but changes any movements to extend selections rather than replace them. Goto motions are also changed to extend, so that `vg1`, for example, extends the selection to the end of the line.

Search is also affected. By default, `n` and `N` will remove the current selection and select the next instance of the search term. Toggling this mode before pressing `n` or `N` makes it possible to keep the current selection. Toggling it on and off during your iterative searching allows you to selectively add search terms to your selections.

Picker

Keys to use within picker. Remapping currently not supported. See the documentation page on [pickers](#) for more info. [Prompt](#) keybinds also work in pickers, except where they conflict with picker keybinds.

Key	Description
<code>Shift-Tab</code> , <code>Up</code> , <code>Ctrl-p</code>	Previous entry
<code>Tab</code> , <code>Down</code> , <code>Ctrl-n</code>	Next entry
<code>PageUp</code> , <code>Ctrl-u</code>	Page up
<code>PageDown</code> , <code>Ctrl-d</code>	Page down
<code>Home</code>	Go to first entry
<code>End</code>	Go to last entry
<code>Enter</code>	Open selected
<code>Alt-Enter</code>	Open selected in the background without closing the picker
<code>Ctrl-s</code>	Open horizontally
<code>Ctrl-v</code>	Open vertically
<code>Ctrl-t</code>	Toggle preview
<code>Escape</code> , <code>Ctrl-c</code>	Close picker

Prompt

Keys to use within prompt, Remapping currently not supported.

Key	Description
Escape, Ctrl-c	Close prompt
Alt-b, Ctrl-Left	Backward a word
Ctrl-b, Left	Backward a char
Alt-f, Ctrl-Right	Forward a word
Ctrl-f, Right	Forward a char
Ctrl-e, End	Move prompt end
Ctrl-a, Home	Move prompt start
Ctrl-w, Alt-Backspace, Ctrl-Backspace	Delete previous word
Alt-d, Alt-Delete, Ctrl-Delete	Delete next word
Ctrl-u	Delete to start of line
Ctrl-k	Delete to end of line
Backspace, Ctrl-h, Shift-Backspace	Delete previous char
Delete, Ctrl-d	Delete next char
Ctrl-s	Insert a word under doc cursor, may be changed to Ctrl-r Ctrl-w later
Ctrl-p, Up	Select previous history
Ctrl-n, Down	Select next history
Ctrl-r	Insert the content of the register selected by following input char
Tab	Select next completion item
BackTab	Select previous completion item
Enter	Open selected

Configuration and Settings

Editor

- `[editor]` Section
- `[editor.clipboard-provider]` Section
- `[editor.statusline]` Section
- `[editor.lsp]` Section
- `[editor.cursor-shape]` Section
- `[editor.file-picker]` Section
- `[editor.file-explorer]` Section
- `[editor.buffer-picker]` Section
- `[editor.auto-pairs]` Section
- `[editor.auto-save]` Section
- `[editor.search]` Section
- `[editor.whitespace]` Section
- `[editor.indent-guides]` Section
- `[editor.gutters]` Section
 - `[editor.gutters.line-numbers]` Section
 - `[editor.gutters.diagnostics]` Section
 - `[editor.gutters.diff]` Section
 - `[editor.gutters.spacer]` Section
 - `[editor.gutters.code-action-hint]` Section
- `[editor.soft-wrap]` Section
- `[editor.smart-tab]` Section
- `[editor.inline-diagnostics]` Section
- `[editor.word-completion]` Section
- `[editor.workspace-trust]` Section

`[editor]` Section

Key	Description	Default
<code>scrolloff</code>	Number of lines of padding around the edge of the screen when scrolling	<code>5</code>
<code>mouse</code>	Enable mouse mode	<code>true</code>
<code>mouse-yank-register</code>	Which register to use for mouse yanks.	<code>*</code>
<code>middle-click-paste</code>	Middle click paste support	<code>true</code>
<code>default-yank-register</code>	Default register used for yank/paste	<code>''</code>
<code>scroll-lines</code>	Number of lines to scroll per scroll wheel step	<code>3</code>
<code>shell</code>	Shell to use when running external commands	Unix: <code>["sh", "-c"]</code> Windows: <code>["cmd", "/C"]</code>

Key	Description	Default
<code>line-number</code>	Line number display: <code>absolute</code> simply shows each line's number, while <code>relative</code> shows the distance from the current line. When unfocused or in insert mode, <code>relative</code> will still show absolute line numbers	<code>"absolute"</code>
<code>cursorline</code>	Highlight all lines with a cursor	<code>false</code>
<code>cursorcolumn</code>	Highlight all columns with a cursor	<code>false</code>
<code>continue-comments</code>	if zemacs should automatically add a line comment token if you create a new line inside a comment.	<code>true</code>
<code>gutters</code>	Gutters to display: Available are <code>diagnostics</code> and <code>diff</code> and <code>line-numbers</code> and <code>spacer</code> and <code>code-action-hint</code> , note that <code>diagnostics</code> also includes other features like breakpoints, 1-width padding will be inserted if gutters is non-empty	<code>["diagnostics", "spacer", "line-numbers", "spacer", "diff"]</code>
<code>auto-completion</code>	Enable automatic pop up of auto-completion	<code>true</code>
<code>path-completion</code>	Enable filepath completion. Show files and directories if an existing path at the cursor was recognized, either absolute or relative to the current opened document or current working directory (if the buffer is not yet saved). Defaults to true.	<code>true</code>

Key	Description	Default
<code>auto-format</code>	Enable automatic formatting on save ¹	<code>true</code>
<code>idle-timeout</code>	Time in milliseconds since last keypress before idle timers trigger.	<code>250</code>
<code>completion-timeout</code>	Time in milliseconds after typing a word character before completions are shown, set to 5 for instant.	<code>250</code>
<code>preview-completion-insert</code>	Whether to apply completion item instantly when selected	<code>true</code>
<code>completion-trigger-len</code>	The min-length of word under cursor to trigger autocompletion	<code>2</code>
<code>completion-replace</code>	Whether to make completions always replace the entire word and not just the part before the cursor	<code>false</code>
<code>auto-info</code>	Whether to display info boxes	<code>true</code>
<code>true-color</code>	Whether to override automatic detection of terminal truecolor support in the event of a false negative	<code>false</code>
<code>undercurl</code>	Whether to override automatic detection of terminal undercurl support in the event of a false negative	<code>false</code>
<code>rulers</code>	List of column positions at which to display the rulers. Can be overridden by language specific <code>rulers</code> in <code>languages.toml</code> file	<code>[]</code>

¹In most cases, you also need to enable the `auto-format` setting under `languages.toml`. You can find the reasoning [here](#).

Key	Description	Default
<code>bufferline</code>	Renders a line at the top of the editor displaying open buffers. Can be <code>always</code> , <code>never</code> or <code>multiple</code> (only shown if more than one buffer is in use)	<code>"never"</code>
<code>color-modes</code>	Whether to color the mode indicator with different colors depending on the mode itself	<code>false</code>
<code>text-width</code>	Maximum line length. Used for the <code>:reflow</code> command and soft-wrapping if <code>soft-wrap.wrap-at-text-width</code> is set	<code>80</code>
<code>workspace-lsp-roots</code>	Directories relative to the workspace root that are treated as LSP roots. Should only be set in <code>.zemacs/config.toml</code>	<code>[]</code>
<code>default-line-ending</code>	The line ending to use for new documents. Can be <code>native</code> , <code>lf</code> , <code>crlf</code> , <code>ff</code> , <code>cr</code> or <code>nel</code> . <code>native</code> uses the platform's native line ending (<code>crlf</code> on Windows, otherwise <code>lf</code>).	<code>"native"</code>
<code>insert-final-newline</code>	Whether to automatically insert a trailing line-ending on write if missing	<code>true</code>

Key	Description	Default
<code>atomic-save</code>	Whether to use atomic operations to write documents to disk. This prevents data loss if the editor is interrupted while writing the file, but may confuse some file watching/hot reloading programs.	<code>true</code>
<code>trim-final-newlines</code>	Whether to automatically remove line-endings after the final one on write	<code>false</code>
<code>trim-trailing-whitespace</code>	Whether to automatically remove whitespace preceding line endings on write	<code>false</code>
<code>popup-border</code>	Draw border around <code>popup</code> , <code>menu</code> , <code>all</code> , or <code>none</code>	<code>"none"</code>
<code>indent-heuristic</code>	How the indentation for a newly inserted line is computed: <code>simple</code> just copies the indentation level from the previous line, <code>tree-sitter</code> computes the indentation based on the syntax tree and <code>hybrid</code> combines both approaches. If the chosen heuristic is not available, a different one will be used as a fallback (the fallback order being <code>hybrid</code> -> <code>tree-sitter</code> -> <code>simple</code>).	<code>"hybrid"</code>

Key	Description	Default
<code>jump-label-alphabet</code>	The characters that are used to generate two character jump labels. Characters at the start of the alphabet are used first.	<code>"abcdefghijklmnopqrstuvwxyz"</code>
<code>end-of-line-diagnostics</code>	Minimum severity of diagnostics to render at the end of the line. Set to <code>disable</code> to disable entirely. Refer to the setting about <code>inline-diagnostics</code> for more details	<code>"hint"</code>
<code>clipboard-provider</code>	Which API to use for clipboard interaction. One of <code>pasteboard</code> (MacOS), <code>wayland</code> , <code>x-clip</code> , <code>x-sel</code> , <code>win32-yank</code> , <code>termux</code> , <code>tmux</code> , <code>windows</code> , <code>termcode</code> , <code>none</code> , or a custom command set.	Platform and environment specific.
<code>editor-config</code>	Whether to read settings from <code>EditorConfig</code> files	<code>true</code>
<code>rainbow-brackets</code>	Whether to render rainbow colors for matching brackets. Requires tree-sitter <code>rainbows.scm</code> queries for the language.	<code>false</code>
<code>kitty-keyboard-protocol</code>	Whether to enable Kitty Keyboard Protocol. Can be <code>enabled</code> , <code>disabled</code> or <code>auto</code>	<code>"auto"</code>

`[editor.clipboard-provider]` Section

Zemacs can be configured either to use a builtin clipboard configuration or to use a provided command.

For instance, setting it to use OSC 52 termcodes, the configuration would be:

```
[editor]
clipboard-provider = "termcode"
```

Alternatively, Zemacs can be configured to use arbitrary commands for clipboard integration:

```
[editor.clipboard-provider.custom]
yank = { command = "cat", args = ["test.txt"] }
paste = { command = "tee", args = ["test.txt"] }
primary-yank = { command = "cat", args = ["test-primary.txt"] } # optional
primary-paste = { command = "tee", args = ["test-primary.txt"] } # optional
```

For custom commands the contents of the yank/paste is communicated over stdin/stdout.

[editor.statusline] Section

Allows configuring the statusline at the bottom of the editor.

The configuration distinguishes between three areas of the status line:

```
[ ... .. LEFT ... .. | ... .. .. CENTER ... .. .. | ... .. RIGHT ... .. ]
```

Statusline elements can be defined as follows:

```
[editor.statusline]
left = ["mode", "spinner"]
center = ["file-name"]
right = ["diagnostics", "selections", "position", "file-encoding", "file-line-ending", "file-type"]
separator = "|"
mode.normal = "NORMAL"
mode.insert = "INSERT"
mode.select = "SELECT"
diagnostics = ["warning", "error"]
workspace-diagnostics = ["warning", "error"]
```

The [editor.statusline] key takes the following sub-keys:

Key	Description	Default
left	A list of elements aligned to the left of the statusline	["mode", "spinner", "file-name", "read-only-indicator", "file-modification-indicator"]
center	A list of elements aligned to the middle of the statusline	[]
right	A list of elements aligned to the right of the statusline	["diagnostics", "selections", "register", "position", "file-encoding"]
separator	The character used to separate elements in the statusline	" "
mode.normal	The text shown in the <code>mode</code> element for normal mode	"NOR"
mode.insert	The text shown in the <code>mode</code> element for insert mode	"INS"
mode.select	The text shown in the <code>mode</code> element for select mode	"SEL"
diagnostics	A list of severities which are displayed for the current buffer	["warning", "error"]
workspace-diagnostics	A list of severities which are displayed for the workspace	["warning", "error"]

The following statusline elements can be configured:

Key	Description
mode	The current editor mode (<code>mode.normal</code> / <code>mode.insert</code> / <code>mode.select</code>)
spinner	A progress spinner indicating LSP activity

Key	Description
<code>file-name</code>	The path/name of the opened file
<code>file-absolute-path</code>	The absolute path/name of the opened file
<code>file-base-name</code>	The basename of the opened file
<code>current-working-directory</code>	The current working directory
<code>file-modification-indicator</code>	The indicator to show whether the file is modified (a <code>[+]</code> appears when there are unsaved changes)
<code>file-encoding</code>	The encoding of the opened file if it differs from UTF-8
<code>file-line-ending</code>	The file line endings (CRLF or LF)
<code>file-indent-style</code>	The file indentation style
<code>read-only-indicator</code>	An indicator that shows <code>[readonly]</code> when a file cannot be written
<code>total-line-numbers</code>	The total line numbers of the opened file
<code>file-type</code>	The type of the opened file
<code>diagnostics</code>	The number of warnings and/or errors
<code>workspace-diagnostics</code>	The number of warnings and/or errors on workspace
<code>selections</code>	The primary selection index out of the number of active selections
<code>primary-selection-length</code>	The number of characters currently in primary selection
<code>position</code>	The cursor position
<code>position-percentage</code>	The cursor position as a percentage of the total number of lines
<code>separator</code>	The string defined in <code>editor.statusline.separator</code> (defaults to " ")
<code>spacer</code>	Inserts a space between elements (multiple/contiguous spacers may be specified)
<code>version-control</code>	The current branch name or detached commit hash of the opened workspace
<code>register</code>	The current selected register
<code>code-action-hint</code>	Indicator for when code actions are available

[`editor.lsp`] Section

Key	Description	Default
<code>enable</code>	Enables LSP integration. Setting to false will completely disable language servers regardless of language settings.	<code>true</code>
<code>display-messages</code>	Display LSP <code>window/showMessage</code> messages below statusline ²	<code>true</code>
<code>display-progress-messages</code>	Display LSP progress messages below statusline ³	<code>false</code>
<code>auto-signature-help</code>	Enable automatic popup of signature help (parameter hints)	<code>true</code>

²By default, a progress spinner is shown in the statusline beside the file path.

³By default, a progress spinner is shown in the statusline beside the file path.

Key	Description	Default
<code>auto-document-highlight</code>	Automatically highlight symbol references at the cursor	<code>false</code>
<code>display-inlay-hints</code>	Display inlay hints ⁴	<code>false</code>
<code>inlay-hints-length-limit</code>	Maximum displayed length (non-zero number) of inlay hints	Unset by default
<code>display-color-swatches</code>	Show color swatches next to colors	<code>true</code>
<code>display-signature-help-docs</code>	Display docs under signature help popup	<code>true</code>
<code>snippets</code>	Enables snippet completions. Requires a server restart (<code>:lsp-restart</code>) to take effect after <code>:config-reload/:set</code> . Include declaration in the goto references popup.	<code>true</code>
<code>goto-reference-include-declaration</code>		<code>true</code>

[`editor.cursor-shape`] Section

Defines the shape of cursor in each mode. Valid values for these options are `block`, `bar`, `underline`, or `hidden`.

- Due to limitations of the terminal environment, only the primary cursor can change shape.

Key	Description	Default
<code>normal</code>	Cursor shape in <code>normal mode</code>	<code>"block"</code>
<code>insert</code>	Cursor shape in <code>insert mode</code>	<code>"block"</code>
<code>select</code>	Cursor shape in <code>select mode</code>	<code>"block"</code>

[`editor.file-picker`] Section

Set options for file picker and global search. Ignoring a file means it is not visible in the Zemacs file picker and global search.

All git related options are only enabled in a git repository.

Key	Description	Default
<code>hidden</code>	Enables ignoring hidden files	<code>true</code>
<code>follow-symlinks</code>	Follow symlinks instead of ignoring them	<code>true</code>
<code>deduplicate-links</code>	Ignore symlinks that point at files already shown in the picker	<code>true</code>
<code>parents</code>	Enables reading ignore files from parent directories	<code>true</code>

⁴You may also have to activate them in the language server config for them to appear, not just in Zemacs. Inlay hints in Zemacs are still being improved on and may be a little bit laggy/janky under some circumstances. Please report any bugs you see so we can fix them!

Key	Description	Default
<code>ignore</code>	Enables reading <code>.ignore</code> files	<code>true</code>
<code>git-ignore</code>	Enables reading <code>.gitignore</code> files	<code>true</code>
<code>git-global</code>	Enables reading global <code>.gitignore</code> , whose path is specified in git's config: <code>core.excludesfile</code> option	<code>true</code>
<code>git-exclude</code>	Enables reading <code>.git/info/exclude</code> files	<code>true</code>
<code>max-depth</code>	Set with an integer value for maximum depth to recurse	Unset by default

Ignore files can be placed locally as `.ignore` or put in your home directory as `~/.ignore`. They support the usual ignore and negative ignore (unignore) rules used in `.gitignore` files.

Additionally, you can use Emacs-specific ignore files by creating a local `.emacs/ignore` file in the current workspace or a global `ignore` file located in your Emacs config directory: - Linux and Mac: `~/.emacs/ignore` - Windows: `%AppData%\emacs\ignore`

Example:

```
# unignore in file picker and global search
!.github/
!.gitignore
!.gitattributes
```

[`editor.file-explorer`] Section

In addition to the options for the file picker and global search, a similar set of options is presented to configure the file explorer separately. However, unlike the file picker, the defaults are set to avoid ignoring most files.

Note that the ignore files consulted by the file explorer when `ignore` is set to true are the same ones used by the file picker, including the aforementioned Emacs-specific ignore files.

Key	Description	Default
<code>hidden</code>	Enables ignoring hidden files	<code>false</code>
<code>follow-symlinks</code>	Follow symlinks instead of ignoring them	<code>false</code>
<code>parents</code>	Enables reading ignore files from parent directories	<code>false</code>
<code>ignore</code>	Enables reading <code>.ignore</code> files	<code>false</code>
<code>git-ignore</code>	Enables reading <code>.gitignore</code> files	<code>false</code>

Key	Description	Default
<code>git-global</code>	Enables reading global <code>.gitignore</code> , whose path is specified in git's config: <code>core.excludesfile</code> option	<code>false</code>
<code>git-exclude</code>	Enables reading <code>.git/info/exclude</code> files	<code>false</code>
<code>flatten-dirs</code>	Enables flattening single child directories	<code>true</code>

[editor.buffer-picker] Section

Set options for buffer picker.

Key	Description	Default
<code>start-position</code>	Controls behavior for which buffer is initially selected	<code>current</code>

Example

```
[editor.buffer-picker]
start-position = "previous"
```

[editor.auto-pairs] Section

Enables automatic insertion of pairs to parentheses, brackets, etc. Can be a simple boolean value, or a specific mapping of pairs of single characters.

To disable auto-pairs altogether, set `auto-pairs` to `false`:

```
[editor]
auto-pairs = false # defaults to `true`
```

The default pairs are `(){}""'''</code>`, but these can be customized by setting `auto-pairs` to a TOML table:

```
[editor.auto-pairs]
'(' = ')'
'{' = '}'
'[' = ']'
'"' = '"'
"'" = "'"
'<' = '>'
```

Additionally, this setting can be used in a language config. Unless the editor setting is `false`, this will override the editor config in documents with this language.

Example `languages.toml` that adds `<>` and removes `' '`

```
[[language]]
name = "rust"

[language.auto-pairs]
'(' = ')'
'{' = '}'
'[' = ']'
'"' = '"'
'\n' = '\n'
'<' = '>'
```

[editor.auto-save] Section

Control auto save behavior.

Key	Description	Default
<code>focus-lost</code>	Enable automatic saving on the focus moving away from Helix. Requires <code>focus event support</code> from your terminal	<code>false</code>
<code>after-delay.enable</code>	Enable automatic saving after <code>auto-save.after-delay.timeout</code> milliseconds have passed since last edit.	<code>false</code>
<code>after-delay.timeout</code>	Time in milliseconds since last edit before auto save timer triggers.	<code>3000</code>

[editor.search] Section

Search specific options.

Key	Description	Default
<code>smart-case</code>	Enable smart case regex searching (case-insensitive unless pattern contains upper case characters)	<code>true</code>
<code>wrap-around</code>	Whether the search should wrap after depleting the matches	<code>true</code>

[editor.whitespace] Section

Options for rendering whitespace with visible characters. Use `:set whitespace.render all` to temporarily enable visible whitespace.

Key	Description	Default
<code>render</code>	Whether to render whitespace. May either be <code>all</code> or <code>none</code> , or a table with sub-keys <code>space</code> , <code>nbspace</code> , <code>nnbspace</code> , <code>tab</code> , and <code>newline</code>	<code>"none"</code>
<code>characters</code>	Literal characters to use when rendering whitespace. Sub-keys may be any of <code>tab</code> , <code>space</code> , <code>nbspace</code> , <code>nnbspace</code> , <code>newline</code> or <code>tabpad</code>	See example below

Example

```
[editor.whitespace]
render = "all"
# or control each character
[editor.whitespace.render]
space = "all"
tab = "all"
nbspace = "none"
nnbspace = "none"
newline = "none"

[editor.whitespace.characters]
space = " "
nbspace = " "
nnbspace = "␣"
tab = "→"
newline = "↵"
tabpad = " " # Tabs will look like "→..." (depending on tab width)
```

[editor.indent-guides] Section

Options for rendering vertical indent guides.

Key	Description	Default
<code>render</code>	Whether to render indent guides	<code>false</code>
<code>character</code>	Literal character to use for rendering the indent guide	<code>" "</code>
<code>skip-levels</code>	Number of indent levels to skip	<code>0</code>

Example:

```
[editor.indent-guides]
render = true
character = "|" # Some characters that work well: "|", "⋈", "⋊", "⋉"
skip-levels = 1
```

[editor.gutters] Section

For simplicity, `editor.gutters` accepts an array of gutter types, which will use default settings for all gutter components.

```
[editor]
gutters = ["diff", "diagnostics", "line-numbers", "spacer"]
```

To customize the behavior of gutters, the `[editor.gutters]` section must be used. This section contains top level settings, as well as settings for specific gutter components as subsections.

Key	Description	Default
<code>layout</code>	A vector of gutters to display	<code>["diagnostics", "spacer", "line-numbers", "spacer", "diff"]</code>

Example:

```
[editor.gutters]
layout = ["diff", "diagnostics", "line-numbers", "spacer"]
```

[editor.gutters.line-numbers] Section

Options for the line number gutter

Key	Description	Default
min-width	The minimum number of characters to use	3

Example:

```
[editor.gutters.line-numbers]
min-width = 1
```

[editor.gutters.diagnostics] Section

Currently unused

[editor.gutters.diff] Section

The `diff` gutter option displays colored bars indicating whether a `git` diff represents that a line was added, removed or changed. These colors are controlled by the theme attributes `diff.plus`, `diff.minus` and `diff.delta`.

Other diff providers will eventually be supported by a future plugin system.

There are currently no options for this section.

[editor.gutters.spacer] Section

Currently unused

[editor.gutters.code-action-hint] Section

The `code-action-hint` gutter option displays an indicator for whether a code action is available at current selection.

There are currently no options for this section.

[editor.soft-wrap] Section

Options for soft wrapping lines that exceed the view width:

Key	Description	Default
enable	Whether soft wrapping is enabled.	false
max-wrap	Maximum free space left at the end of the line.	20
max-indent-retain	Maximum indentation to carry over when soft wrapping a line.	40
wrap-indicator	Text inserted before soft wrapped lines, highlighted with <code>ui.virtual.wrap</code>	"↪ "
wrap-at-text-width	Soft wrap at <code>text-width</code> instead of using the full viewport size.	false

Example:

```
[editor.soft-wrap]
enable = true
max-wrap = 25 # increase value to reduce forced mid-word wrapping
max-indent-retain = 0
wrap-indicator = "" # set wrap-indicator to "" to hide it
```

[editor.smart-tab] Section

Options for navigating and editing using tab key.

Key	Description	Default
<code>enable</code>	If set to true, then when the cursor is in a position with non-whitespace to its left, instead of inserting a tab, it will run <code>move_parent_node_end</code> . If there is only whitespace to the left, then it inserts a tab as normal. With the default bindings, to explicitly insert a tab character, press Shift-tab.	<code>true</code>
<code>supersede-menu</code>	Normally, when a menu is on screen, such as when auto complete is triggered, the tab key is bound to cycling through the items. This means when menus are on screen, one cannot use the tab key to trigger the <code>smart-tab</code> command. If this option is set to true, the <code>smart-tab</code> command always takes precedence, which means one cannot use the tab key to cycle through menu items. One of the other bindings must be used instead, such as arrow keys or <code>C-n/C-p</code> .	<code>false</code>

Due to lack of support for S-tab in some terminals, the default keybindings don't fully embrace smart-tab editing experience. If you enjoy smart-tab navigation and a terminal that supports the [Enhanced Keyboard protocol](#), consider setting extra keybindings:

```
[keys.normal]
tab = "move_parent_node_end"
S-tab = "move_parent_node_start"

[keys.insert]
S-tab = "move_parent_node_start"

[keys.select]
tab = "extend_parent_node_end"
S-tab = "extend_parent_node_start"
```

[editor.inline-diagnostics] Section

Options for rendering diagnostics inside the text like shown below

```
fn main() {
  let foo = bar;
           └ no such value in this scope
}
```

Key	Description	Default
<code>cursor-line</code>	The minimum severity that a diagnostic must have to be shown inline on the line that contains the primary cursor. Set to <code>disable</code> to not show any diagnostics inline. This option does not have any effect when in insert-mode and will only take effect 350ms after moving the cursor to a different line.	<code>"warning"</code>
<code>other-lines</code>	The minimum severity that a diagnostic must have to be shown inline on a line that does not contain the cursor-line. Set to <code>disable</code> to not show any diagnostics inline.	<code>"disable"</code>

Key	Description	Default
<code>prefix-len</code>	How many horizontal bars — are rendered before the diagnostic text.	<code>1</code>
<code>max-wrap</code>	Equivalent of the <code>editor.soft-wrap.max-wrap</code> option for diagnostics.	<code>20</code>
<code>max-diagnostics</code>	Maximum number of diagnostics to render inline for a given line	<code>10</code>

The allowed values for `cursor-line` and `other-lines` are: `error`, `warning`, `info`, `hint`.

The (first) diagnostic with the highest severity that is not shown inline is rendered at the end of the line (as long as its severity is higher than the `end-of-line-diagnostics` config option):

```
fn main() {
  let baz = 1;
  let foo = bar; a local variable with a similar name exists: baz
                    └ no such value in this scope
}
```

[`editor.word-completion`] Section

Options for controlling completion of words from open buffers.

Key	Description	Default
<code>enable</code>	Whether word completion is enabled	<code>true</code>
<code>trigger-length</code>	Number of word characters to type before triggering completion	<code>7</code>

Example:

```
[editor.word-completion]
enable = true
# Set the trigger length lower so that words are completed more often
trigger-length = 4
```

[`editor.workspace-trust`] Section

Controls implicit workspace trust. See the [workspace trust](#) chapter for the full feature.

Key	Description	Default
<code>level</code>	The default level of trust for every workspace.	<code>"servers"</code>
<code>prompt</code>	Whether to show a modal when opening a file in an untrusted workspace.	<code>true</code>
<code>trusted</code>	Glob patterns whose matching workspaces are trusted without a grant.	<code>[]</code>

Example:

Typable Commands

Commands run from the `:` command line, with their aliases.

Name	Description
<code>:terminal, :term</code>	Open an integrated terminal (PTY shell) running \$SHELL.
<code>:ide, :workbench</code>	Enter IDE mode (file-tree sidebar + panels, like <code>--ide</code> / F2).
<code>:diff, :gdiff</code>	Open a read-only side-by-side diff of the buffer vs. its git HEAD version.
<code>:merge, :resolve</code>	Resolve the buffer's git merge conflicts in a 3-pane (ours/result/theirs) view.
<code>:magit, :git, :gst</code>	Open the Magit-style git status (stage/unstage/discard/commit changes by section).
<code>:hex, :hexview, :hexedit</code>	Open a read-only xxd-style hex viewer of a file's raw bytes (optional path; defaults to the buffer's file).
<code>:snippets, :snip</code>	Open the user snippet library editor (create/edit/delete reusable snippets).
<code>:org-cycle, :org-fold</code>	Toggle a fold over the current org heading's subtree (TAB-style outline cycling).
<code>:org-todo</code>	Cycle the current org heading's TODO keyword: none -> TODO -> DONE -> none.
<code>:org-promote</code>	Promote the current org heading one level (remove a leading star).
<code>:org-demote</code>	Demote the current org heading one level (add a leading star).
<code>:org-next-heading</code>	Move the cursor to the next org heading line.
<code>:org-prev-heading</code>	Move the cursor to the previous org heading line.
<code>:org-fold-all</code>	Fold every org heading subtree in the buffer.
<code>:org-unfold-all</code>	Unfold every fold in the buffer.
<code>:org-agenda, :agenda</code>	Open the org agenda: TODO/DONE items across open .org buffers and *.org files under the working directory, grouped by scheduled/deadline date.
<code>:org-priority</code>	Cycle the current org heading's priority cookie: none -> [#A] -> [#B] -> [#C] -> none.
<code>:org-capture, :capture</code>	Prompt for a line of text and append it as a '* TODO ' entry to an inbox org file (default /inbox.org, or an explicit path argument).
<code>:exit, :x, :xit</code>	Write changes to disk if the buffer is modified and then quit. Accepts an optional path (:exit some/path.txt).
<code>:exit!, :x!, :xit!</code>	Force write changes to disk, creating necessary subdirectories, if the buffer is modified and then quit. Accepts an optional path (:exit! some/path.txt).
<code>:quit, :q</code>	Close the current view.
<code>:help, :h</code>	Open the inline Help browser (searchable: commands, keybindings, topics).
<code>:wc, :words, :count</code>	Show document line/word/char counts (and selection stats).
<code>:blame</code>	Show git blame for the current line in the status bar.
<code>:reopen, :reopen-closed</code>	Reopen the most recently closed file.

Name	Description
<code>:zen</code>	Toggle the IDE workbench (Zen / focus mode).
<code>:emmet, :zencode</code>	Expand the emmet/zen HTML abbreviation before the cursor.
<code>:quit!, :q!</code>	Force close the current view, ignoring unsaved changes.
<code>:open, :o, :edit, :e</code>	Open a file from disk into the current view.
<code>:buffer-close, :bc, :bclose</code>	Close the current buffer.
<code>:buffer-close!, :bc!, :bclose!</code>	Close the current buffer forcefully, ignoring unsaved changes.
<code>:buffer-close-others, :bco, :bcloseother</code>	Close all buffers but the currently focused one.
<code>:buffer-close-others!, :bco!, :bcloseother!</code>	Force close all buffers but the currently focused one.
<code>:buffer-close-all, :bca, :bcloseall</code>	Close all buffers without quitting.
<code>:buffer-close-all!, :bca!, :bcloseall!</code>	Force close all buffers ignoring unsaved changes without quitting.
<code>:buffer-next, :bn, :bnext</code>	Goto next buffer.
<code>:buffer-previous, :bp, :bprev</code>	Goto previous buffer.
<code>:write, :w</code>	Write changes to disk. Accepts an optional path (:write some/path.txt)
<code>:write!, :w!</code>	Force write changes to disk creating necessary subdirectories. Accepts an optional path (:write! some/path.txt)
<code>:write-buffer-close, :wbc</code>	Write changes to disk and closes the buffer. Accepts an optional path (:write-buffer-close some/path.txt)
<code>:write-buffer-close!, :wbc!</code>	Force write changes to disk creating necessary subdirectories and closes the buffer. Accepts an optional path (:write-buffer-close! some/path.txt)
<code>:new, :n</code>	Create a new scratch buffer.
<code>:format, :fmt</code>	Format the file using an external formatter or language server.
<code>:indent-style</code>	Set the indentation style for editing. ('t' for tabs or 1-16 for number of spaces.)
<code>:line-ending</code>	Set the document's default line ending. Options: crlf, lf.
<code>:earlier, :ear</code>	Jump back to an earlier point in edit history. Accepts a number of steps or a time span.
<code>:later, :lat</code>	Jump to a later point in edit history. Accepts a number of steps or a time span.
<code>:write-quit, :wq</code>	Write changes to disk and close the current view. Accepts an optional path (:wq some/path.txt)
<code>:write-quit!, :wq!</code>	Write changes to disk and close the current view forcefully. Accepts an optional path (:wq! some/path.txt)
<code>:write-all, :wa</code>	Write changes from all buffers to disk.
<code>:write-all!, :wa!</code>	Forcefully write changes from all buffers to disk creating necessary subdirectories.
<code>:write-quit-all, :wqa, :xa</code>	Write changes from all buffers to disk and close all views.
<code>:write-quit-all!, :wqa!, :xa!</code>	Forcefully write changes from all buffers to disk, creating necessary subdirectories, and close all views (ignoring unsaved changes).
<code>:quit-all, :qa</code>	Close all views.
<code>:quit-all!, :qa!</code>	Force close all views ignoring unsaved changes.
<code>:cquit, :cq</code>	Quit with exit code (default 1). Accepts an optional integer exit code (:cq 2).

Name	Description
<code>:cquit!, :cq!</code>	Force quit with exit code (default 1) ignoring unsaved changes. Accepts an optional integer exit code (<code>:cq! 2</code>).
<code>:theme</code>	Change the editor theme (show current theme if no name specified).
<code>:hunk-reset, :reset-hunk, :hunk-undo</code>	Undo the git hunk under the cursor, restoring it from HEAD (gitsigns <code>reset_hunk</code>).
<code>:hunk-next, :next-hunk</code>	Move the cursor to the next git hunk.
<code>:hunk-prev, :prev-hunk</code>	Move the cursor to the previous git hunk.
<code>:conflict-ours, :diffget-ours, :conflict-keep-ours</code>	Resolve the merge conflict at the cursor by keeping OUR side (HEAD).
<code>:conflict-theirs, :diffget-theirs, :conflict-keep-theirs</code>	Resolve the merge conflict at the cursor by keeping THEIR side (incoming).
<code>:conflict-both, :conflict-keep-both</code>	Resolve the merge conflict at the cursor by keeping BOTH sides.
<code>:conflict-next</code>	Jump to the next merge-conflict marker.
<code>:conflict-prev</code>	Jump to the previous merge-conflict marker.
<code>:theme-toggle, :toggle-theme, :light-dark</code>	Toggle between a dark and light theme (<code>:theme-toggle [dark] [light]</code>).
<code>:theme-next</code>	Switch to the next theme (alphabetical).
<code>:theme-prev</code>	Switch to the previous theme (alphabetical).
<code>:run, :r!</code>	Run a command in the IDE Run tool window (defaults to <code>cargo run</code>).
<code>:grep, :rg, :search-project</code>	Search the project (ripgrep) and show jumpable results in the Run console.
<code>:shell-quote, :sh-quote</code>	Wrap the selection in safe shell single-quotes.
<code>:wrap-tag, :tag</code>	Wrap each selection in
<code>:csv-column, :csv-col</code>	Replace the selected CSV/TSV with just its Nth column (1-based).
<code>:code-fence, :fence</code>	Wrap the selection in a fenced Markdown code block with optional language.
<code>:md-table, :table-fmt</code>	Align the selected Markdown pipe table (pad columns, rebuild separator row).
<code>:json-query, :json-get</code>	Replace the selected JSON with the value at a dot-path (e.g. <code>users.0.name</code>).
<code>:json-flatten, :json-paths</code>	Flatten the selected JSON into greppable <code>path = value</code> lines.
<code>:json-to-csv, :json-csv</code>	Convert the selected JSON array of objects to CSV (sorted header union).
<code>:json-unflatten, :json-unpaths</code>	Rebuild nested JSON from <code>path = value</code> lines (inverse of <code>:json-flatten</code>).
<code>:toml-to-json, :toml-json</code>	Convert the selected TOML to pretty-printed JSON.
<code>:json-to-toml, :json-toml</code>	Convert the selected JSON to pretty-printed TOML.
<code>:json-sort, :json-sort-array</code>	Sort the selected JSON array (optionally by an object field: <code>:json-sort name</code>).
<code>:json-pick, :json-select</code>	Keep only the named keys in the selected JSON object/array (e.g. <code>:json-pick name age</code>).
<code>:json-omit, :json-drop</code>	Drop the named keys from the selected JSON object/array (e.g. <code>:json-omit password</code>).
<code>:json-unique, :json-uniq</code>	Remove duplicate elements from the selected JSON array (optionally by a field).

Name	Description
<code>:json-group-by, :json-group</code>	Group the selected JSON array of objects by a field (e.g. <code>:json-group-by city</code>).
<code>:extract, :matches</code>	Replace the selection with every regex match, one per line (group 1 if present).
<code>:filter, :keep-lines</code>	Keep only the selected lines matching a regex (in-buffer <code>grep</code>).
<code>:reject, :remove-lines</code>	Drop the selected lines matching a regex (in-buffer <code>grep -v</code>).
<code>:count-matches, :count-regex</code>	Report how many regex matches (and matching lines) are in the selection.
<code>:uniq-count, :frequency</code>	Collapse the selected lines to <code>count line</code> , sorted by frequency (<code>uniq -c</code>).
<code>:stats, :describe</code>	Show count/sum/mean/min/max of the numbers in the selection (non-destructive).
<code>:seq, :sequence</code>	Insert an integer sequence, one per line: <code>:seq [step]</code> .
<code>:field, :cut</code>	Keep only the Nth whitespace field of each selected line (<code>awk '{print \$N}'</code>).
<code>:running-total, :cumsum</code>	Replace each numeric line with the cumulative total so far.
<code>:diff-lines, :deltas</code>	Replace each numeric line with its delta from the previous (inverse of <code>running-total</code>).
<code>:sum-column, :sumcol</code>	Sum the Nth whitespace field across the selected lines (non-destructive).
<code>:shuffle, :shuf</code>	Randomly reorder the selected lines (Fisher-Yates).
<code>:sample, :random-lines</code>	Keep N random lines from the selection, preserving order (<code>:sample 10</code>).
<code>:jsonl-to-json, :jsonl-json</code>	Convert the selected JSONL/NDJSON (one value per line) to a JSON array.
<code>:json-to-jsonl, :json-jsonl</code>	Convert the selected JSON array to JSONL (one compact value per line).
<code>:head, :first-lines</code>	Keep only the first N lines of the selection (<code>:head 10</code>).
<code>:tail, :last-lines</code>	Keep only the last N lines of the selection (<code>:tail 10</code>).
<code>:rev, :reverse-each-line</code>	Reverse the characters of each selected line independently (Unix <code>rev</code>).
<code>:json-table, :json-tbl</code>	Render the selected JSON array of objects as an aligned plain-text table.
<code>:hexdump, :xxd</code>	Render the selection as an xxd-style hex dump (offset, hex bytes, ASCII).
<code>:dedup, :unique-lines</code>	Remove all duplicate lines globally, keeping first occurrence and order.
<code>:caesar, :shift-letters</code>	Caesar-shift the selection's letters by N (e.g. <code>:caesar 13</code> = ROT13; N may be negative).
<code>:base32-encode, :base32</code>	Base32-encode the selection (RFC 4648).
<code>:base32-decode, :unbase32</code>	Base32-decode the selection (RFC 4648).
<code>:crc32, :checksum</code>	Show the CRC32 (IEEE) checksum of the selection in hex and decimal (non-destructive).
<code>:rot47, :rot-47</code>	Apply ROT47 to the selection (rotates all printable ASCII; self-inverse).
<code>:morse-encode, :morse</code>	Encode the selection (A-Z, 0-9) to Morse code (words separated by /).
<code>:morse-decode, :unmorse</code>	Decode Morse code in the selection back to text.
<code>:human-bytes, :humanize-size</code>	Convert each numeric line (a byte count) to a human-readable size like 1.5 KiB.
<code>:ordinal, :ordinalize</code>	Convert each numeric line to its ordinal (1 → 1st, 22 → 22nd).

Name	Description
<code>:to-snake, :snake-case</code>	Convert the selected identifier to snake_case.
<code>:to-kebab, :kebab-case</code>	Convert the selected identifier to kebab-case.
<code>:to-camel, :camel-case</code>	Convert the selected identifier to camelCase.
<code>:to-pascal, :pascal-case</code>	Convert the selected identifier to PascalCase.
<code>:to-constant, :screaming-snake, :upper-snake</code>	Convert the selected identifier to CONSTANT_CASE.
<code>:to-binary, :text-to-binary</code>	Convert the selection to space-separated 8-bit binary.
<code>:from-binary, :binary-to-text</code>	Convert space-separated binary in the selection back to text.
<code>:natural-sort, :sort-natural</code>	Sort the selected lines in natural order (file2 before file10).
<code>:pad-right, :ljust</code>	Left-justify each selected line, padding with spaces to a minimum width.
<code>:pad-left, :rjust</code>	Right-justify each selected line, padding with spaces to a minimum width.
<code>:json-keys, :json-fields</code>	List the keys of the selected JSON object (or union across an array of objects).
<code>:json-type, :json-describe</code>	Show the JSON type and size of the selection in the status line (non-destructive).
<code>:after, :cut-after</code>	Keep the text after the first on each selected line.
<code>:before, :cut-before</code>	Keep the text before the first on each selected line.
<code>:swapcase, :invert-case</code>	Invert the case of each character in the selection (Hello → hELLO).
<code>:strip-invisible, :strip-zero-width</code>	Remove zero-width / invisible Unicode characters from the selection.
<code>:lines-to-json, :lines-to-array</code>	Wrap the selected lines into a JSON array of strings.
<code>:json-to-lines, :array-to-lines</code>	Unwrap a JSON array in the selection into one line per element.
<code>:checkbox-list, :task-list</code>	Turn the selected lines into a Markdown task list (- [] item).
<code>:unwrap-paragraphs, :unhardwrap</code>	Join hard-wrapped lines within each paragraph into single lines.
<code>:sql-in, :sql-in-list</code>	Build a SQL IN-list ('a', 'b', 'c') from the selected lines.
<code>:dec-to-hex, :to-hex-num</code>	Convert each decimal number line to hexadecimal.
<code>:hex-to-dec, :from-hex-num</code>	Convert each hexadecimal number line to decimal.
<code>:unicode-escape, :u-escape</code>	Escape non-ASCII characters in the selection as \u{XXXX}.
<code>:unicode-unescape, :u-unescape</code>	Decode \u{XXXX} and \uXXXX escapes in the selection back to characters.
<code>:sort-by-length, :sortlen</code>	Sort the selected lines by length (shortest first).
<code>:count-unique, :distinct-count</code>	Report the number of distinct vs total selected lines (non-destructive).
<code>:rotate-lines, :rotate</code>	Cyclically rotate the selected lines by N (negative rotates the other way).
<code>:unquote-lines, :strip-quotes-lines</code>	Remove surrounding quotes from each selected line independently.
<code>:quote-lines, :quote-each</code>	Wrap each selected line in double quotes (escaping and ").
<code>:repeat, :repeat-text</code>	Repeat the selected text N times (:repeat 3).
<code>:capitalize-lines, :capitalize</code>	Uppercase the first letter of each selected line.
<code>:remove-blank-lines, :remove-empty</code>	Remove all blank (whitespace-only) lines from the selection.

Name	Description
<code>:trim-lines, :trim</code>	Trim leading and trailing whitespace from each selected line.
<code>:kv-to-json, :env-to-json</code>	Convert key=value / key: value lines in the selection to a JSON object.
<code>:json-to-kv, :json-to-env</code>	Convert the selected JSON object to key=value lines.
<code>:json-pluck, :json-values-of</code>	Extract one field's value from each object in a JSON array, one per line.
<code>:to-html-list, :html-list</code>	Convert the selected lines into an HTML
<code>:from-html-list, :html-list-to-lines</code>	Extract
<code>:csv-to-html-table, :csv-to-html</code>	Convert the selected CSV/TSV (first row = headers) to an HTML
<code>:slugify-lines, :slug-lines</code>	Slugify each selected line independently (URL-friendly).
<code>:lines-to-csv-row, :join-csv</code>	Join the selected lines into one CSV row (RFC-4180 quoting).
<code>:csv-row-to-lines, :split-csv</code>	Split a CSV row in the selection into one field per line (quote-aware).
<code>:deslugify, :unslugify</code>	Turn a slug back into a Title Cased phrase (hyphens/underscores to spaces).
<code>:csv-to-tsv, :csv-tsv</code>	Convert the selected CSV to tab-separated values (quote-aware).
<code>:tsv-to-csv, :tsv-csv</code>	Convert the selected TSV to CSV (RFC-4180 quoting).
<code>:strip-line-numbers, :unnumber</code>	Remove a leading line number (and separator) from each selected line.
<code>:markdown-link, :md-link</code>	Wrap the selected text as a Markdown link text .
<code>:extract-urls, :urls</code>	Replace the selection with the http(s) URLs found in it, one per line.
<code>:extract-emails, :emails</code>	Replace the selection with the email addresses found in it, one per line.
<code>:extract-ips, :ips</code>	Replace the selection with the IPv4 addresses found in it, one per line.
<code>:extract-quoted, :quoted-strings</code>	Replace the selection with the contents of double-quoted strings, one per line.
<code>:extract-between, :between</code>	Extract substrings between and delimiters, one per line.
<code>:wrap-with, :surround-with</code>	Wrap the selection with the given text on both sides (:wrap-with **).
<code>:extract-numbers, :numbers</code>	Replace the selection with the numbers found in it, one per line.
<code>:json-validate, :json-check</code>	Report whether the selection is valid JSON (with error location) — non-destructive.
<code>:csv-validate, :csv-check</code>	Check all CSV rows have the same field count (non-destructive).
<code>:ordered-list, :numbered-list</code>	Turn the selected lines into a Markdown ordered list (1. 2. 3.).
<code>:strip-list-markers, :unlist</code>	Strip leading bullet/number/checkbox list markers from each selected line.
<code>:sort-words, :sort-fields</code>	Sort the whitespace-separated words within each selected line.
<code>:unique-words, :dedup-words</code>	Remove duplicate words within each selected line (first occurrence kept).
<code>:sum-fields, :row-sum</code>	Replace each line with the sum of its numeric fields (row total).
<code>:avg-fields, :row-avg</code>	Replace each line with the mean of its numeric fields.
<code>:max-fields, :row-max</code>	Replace each line with the maximum of its numeric fields.

Name	Description
<code>:min-fields, :row-min</code>	Replace each line with the minimum of its numeric fields.
<code>:range-fields, :row-range</code>	Replace each line with the range (max - min) of its numeric fields.
<code>:to-env-export, :export-vars</code>	Prefix each KEY=value line with <code>export</code> (turn a .env into shell exports).
<code>:strip-export, :unexport</code>	Remove a leading <code>export</code> from each selected line.
<code>:dos2unix, :crlf-to-lf</code>	Convert CRLF/CR line endings in the selection to LF.
<code>:unix2dos, :lf-to-crlf</code>	Convert LF line endings in the selection to CRLF.
<code>:percent-of-total, :percentages</code>	Replace each numeric line with its percentage of the column total.
<code>:running-max, :cummax</code>	Replace each numeric line with the running maximum so far.
<code>:running-min, :cummin</code>	Replace each numeric line with the running minimum so far.
<code>:to-fixed, :round-to</code>	Format each numeric line to N decimal places (:to-fixed 2).
<code>:clamp, :clip</code>	Clamp each numeric line to the [min, max] range (:clamp 0 100).
<code>:scale, :multiply-by</code>	Multiply each numeric line by a factor (:scale 1.5).
<code>:offset, :add-to-each</code>	Add N to each numeric line (:offset 10; negative subtracts).
<code>:abs, :absolute-value</code>	Replace each numeric line with its absolute value.
<code>:linkify, :auto-link</code>	Wrap bare URLs in the selection with Markdown link syntax <code>url</code> .
<code>:strip-markdown-links, :unlink</code>	Replace <code>text</code> Markdown links with just their text.
<code>:strip-emphasis, :strip-md-emphasis</code>	Remove Markdown bold/italic/code emphasis markers from the selection.
<code>:strip-html-comments, :strip-comments-html</code>	Remove HTML/Markdown comments from the selection.
<code>:remove-trailing-commas, :fix-trailing-commas</code>	Remove trailing commas before } or] (JSON5/JS to strict JSON).
<code>:add-trailing-commas, :trailing-commas</code>	Add trailing commas before } or] (cleaner JS/JSON5 diffs).
<code>:smart-quotes, :curly-quotes</code>	Convert straight quotes to typographic curly quotes (context-aware).
<code>:typographic-dashes, :em-dash</code>	Convert — to em dash, – to en dash, ... to ellipsis.
<code>:de-typography, :ascii-punctuation</code>	Normalize curly quotes/dashes/ellipsis back to ASCII punctuation.
<code>:to-ascii, :transliterate</code>	Transliterate accented Latin characters to ASCII (café → cafe).
<code>:nato, :phonetic</code>	Spell the selection in the NATO phonetic alphabet (A → Alfa).
<code>:transpose-grid, :transpose-ws</code>	Transpose a whitespace-separated grid (rows become columns).
<code>:repeat-lines, :duplicate-each</code>	Repeat each selected line N times (:repeat-lines 3).
<code>:rename-word, :rename-local</code>	Rename every whole-word occurrence of the symbol under the cursor in this buffer.
<code>:grep-word, :gw, :find-references</code>	Search the project for the whole word under the cursor (jumpable in Run).
<code>:todos, :project-todos, :fixme</code>	Scan the whole project for TODO/FIXME/HACK/XXX/BUG/NOTE markers (jumpable in Run).
<code>:registers, :reg, :display</code>	Show the contents of all registers.
<code>:yank-join</code>	Yank joined selections. A separator can be provided as first argument. Default value is newline.

Name	Description
<code>:clipboard-yank</code>	Yank main selection into system clipboard.
<code>:clipboard-yank-join</code>	Yank joined selections into system clipboard. A separator can be provided as first argument. Default value is newline.
<code>:primary-clipboard-yank</code>	Yank main selection into system primary clipboard.
<code>:primary-clipboard-yank-join</code>	Yank joined selections into system primary clipboard. A separator can be provided as first argument. Default value is newline.
<code>:clipboard-paste-after</code>	Paste system clipboard after selections.
<code>:clipboard-paste-before</code>	Paste system clipboard before selections.
<code>:clipboard-paste-replace</code>	Replace selections with content of system clipboard.
<code>:primary-clipboard-paste-after</code>	Paste primary clipboard after selections.
<code>:primary-clipboard-paste-before</code>	Paste primary clipboard before selections.
<code>:primary-clipboard-paste-replace</code>	Replace selections with content of system primary clipboard.
<code>:show-clipboard-provider</code>	Show clipboard provider name in status bar.
<code>:change-current-directory, :cd</code>	Change the current working directory.
<code>:show-directory-stack</code>	Show the directory stack as a delimited string.
<code>:push-directory, :pushd</code>	Save and then change the current directory.
<code>:pop-directory, :popd</code>	Remove the top entry from the directory stack, and cd to the new top directory..
<code>:show-directory, :pwd</code>	Show the current working directory.
<code>:encoding</code>	Set encoding. Based on https://encoding.spec.whatwg.org .
<code>:character-info, :char</code>	Get info about the character under the primary cursor.
<code>:reload, :rl</code>	Discard changes and reload from the source file.
<code>:reload-all, :rla</code>	Discard changes and reload all documents from the source files.
<code>:git-stage, :stage, :git-add</code>	Stage the current buffer's file (git add).
<code>:git-unstage, :unstage</code>	Unstage the current buffer's file (git reset HEAD).
<code>:stash, :git-stash</code>	git stash the working-tree changes (then reload open buffers).
<code>:stash-pop, :git-stash-pop</code>	git stash pop the most recent stash (then reload open buffers).
<code>:update, :u</code>	Write changes only if the file has been modified.
<code>:lsp-workspace-command</code>	Open workspace command picker
<code>:lsp-restart</code>	Restarts the given language servers, or all language servers that are used by the current file if no arguments are supplied
<code>:set, :se</code>	Set options with vim syntax (:set nu, :set nowrap, :set tw=80, :set cursorline) or native :set key value.
<code>:lsp-stop</code>	Stops the given language servers, or all language servers that are used by the current file if no arguments are supplied
<code>:tree-sitter-scopes</code>	Display tree sitter scopes, primarily for theming and development.
<code>:tree-sitter-highlight-name</code>	Display name of tree-sitter highlight scope under the cursor.
<code>:tree-sitter-layers</code>	Display language names of tree-sitter injection layers under the cursor.

Name	Description
<code>:debug-start, :dbg</code>	Start a debug session from a given template with given parameters.
<code>:debug-remote, :dbg-tcp</code>	Connect to a debug adapter by TCP address and start a debugging session from a given template with given parameters.
<code>:debug-eval</code>	Evaluate expression in current debug context.
<code>:vsplit, :vs</code>	Open the file in a vertical split.
<code>:vsplit-new, :vnew</code>	Open a scratch buffer in a vertical split.
<code>:hsplit, :hs, :sp</code>	Open the file in a horizontal split.
<code>:hsplit-new, :hnew</code>	Open a scratch buffer in a horizontal split.
<code>:tutor</code>	Open the tutorial.
<code>:goto, :g</code>	Goto line number.
<code>:set-language, :lang</code>	Set the language of current buffer (show current language if no value specified).
<code>:set-option</code>	Set a config option at runtime. For example to disable smart case search, use <code>:set-option search.smart-case false</code> .
<code>:toggle-option, :toggle</code>	Toggle a config option at runtime. For example to toggle smart case search, use <code>:toggle search.smart-case</code> .
<code>:get-option, :get</code>	Get the current value of a config option.
<code>:move-line-down</code>	Move the current line down by one (drag down).
<code>:move-line-up</code>	Move the current line up by one (drag up).
<code>:cycle-case</code>	Cycle the case style of the symbol under the cursor.
<code>:change-case</code>	Change the symbol under the cursor to camel
<code>:left, :le</code>	Left-align line(s), setting leading indent to {n} (default 0) — vim :left.
<code>:right, :ri</code>	Right-align line(s) to width {n} (default 80) — vim :right.
<code>:center, :ce</code>	Center line(s) within width {n} (default 80) — vim :center.
<code>:undo</code>	Undo the last change (vim :undo).
<code>:redo, :red</code>	Redo the last undone change (vim :redo).
<code>:retab</code>	Replace tabs with spaces (tab-width per buffer) — vim :retab.
<code>:join, :j</code>	Join the current line(s) with the next, separated by a space (vim :j).
<code>:join!, :j!</code>	Join the current line(s) with the next, no separating space (vim :j!).
<code>:put, :pu</code>	Put (paste) a register's contents as new line(s) below the cursor (vim :put).
<code>:put!, :pu!</code>	Put (paste) a register's contents as new line(s) above the cursor (vim :put!).
<code>:delete-lines, :d, :del, :delete</code>	Delete the current line(s) into the unnamed register (vim :d).
<code>:yank-lines, :y, :ya, :yank</code>	Yank the current line(s) into the unnamed register (vim :y).
<code>:indent-lines</code>	Indent the current line(s) by one shiftwidth (vim :>).
<code>:dedent-lines</code>	Dedent the current line(s) by one shiftwidth (vim :<).
<code>:move-lines, :m</code>	Move the current line to after line {address}: :m{addr} (e.g. :m0, :m\$, :m.+2).

Name	Description
<code>:copy-lines, :t, :co, :copy</code>	Copy the current line to after line {address}: :t{addr} (e.g. :t0, :t\$).
<code>:global</code>	Run a command on matching lines: :g/pattern/d (delete).
<code>:vglobal</code>	Also :g!/pat/d. Run a command on non-matching lines: :v/pattern/d (delete).
<code>:substitute, :s</code>	Substitute: :s/pattern/replacement/[flags]. Also :%s/.../.../g for the whole file.
<code>:split-line</code>	Split the current line at the cursor, keeping the cursor in place.
<code>:just-one-space</code>	Collapse spaces and tabs around the cursor to a single space.
<code>:delete-blank-lines</code>	Collapse consecutive blank lines down to a single blank line.
<code>:uniquify-lines, :uniq</code>	Delete duplicate lines, keeping the first occurrence.
<code>:reverse, :reverse-lines, :tac</code>	Reverse the order of the selected lines (or the whole buffer).
<code>:uuid, :guid</code>	Insert a random UUID v4 at each cursor (replaces any selection).
<code>:goto-offset, :goto-char</code>	Move the cursor to an absolute character offset.
<code>:pad-numbers, :zero-pad</code>	Zero-pad every integer in the selection to digits.
<code>:increment-numbers, :incr-numbers</code>	Add N (default 1; negative to decrement) to every integer in the selection.
<code>:bases, :base-info</code>	Show the selected integer in decimal, hex, octal, and binary.
<code>:lorem, :lipsum</code>	Insert N words (default 30) of lorem-ipsum placeholder text.
<code>:date</code>	Insert the current UTC date (YYYY-MM-DD) at each cursor.
<code>:datetime, :now</code>	Insert the current UTC date and time (YYYY-MM-DD HH:MM:SS) at each cursor.
<code>:timestamp, :epoch</code>	Insert the current Unix epoch (seconds) at each cursor.
<code>:sum, :total</code>	Sum the numbers in the selection; reports sum/avg/min/max/count in the status line.
<code>:calc, :eval-math</code>	Evaluate an arithmetic expression (+ - * / % ^), or each selection in place.
<code>:join-with, :joinw</code>	Join the selected lines into one with a separator (default “,”).
<code>:split-on, :splito</code>	Split the selected line(s) on a separator (default “,”) into one item per line.
<code>:squeeze-blank-lines, :squeeze</code>	Collapse consecutive blank lines in the selection to one (cat -s).
<code>:dedup-adjacent, :uniq-adjacent</code>	Collapse consecutive duplicate lines in the selection (Unix uniq).
<code>:number-lines, :nl</code>	Prepend line numbers to the selected lines (optional start, default 1).
<code>:align, :tabularize</code>	Align the selected lines on a delimiter (default =) so it shares a column.
<code>:sort-by-field, :sortf</code>	Sort the selected lines by their Nth whitespace field (default 1).
<code>:sort-lines, :sortl</code>	Sort the selected lines (or the whole buffer) — vim-style line sort.
<code>:transpose-words</code>	Transpose the word before the cursor with the word after it.
<code>:transpose-chars</code>	Transpose the two characters around the cursor.
<code>:duplicate-line, :dup</code>	Duplicate the current line below.
<code>:delete-trailing-whitespace, :dtw</code>	Delete trailing whitespace from every line in the buffer.

Name	Description
<code>:sort</code>	Sort ranges in selection.
<code>:reflow</code>	Hard-wrap the current selection of lines to a given width.
<code>:tree-sitter-subtree, :ts-subtree</code>	Display the smallest tree-sitter subtree that spans the primary selection, primarily for debugging queries.
<code>:config-reload</code>	Refresh user config.
<code>:keymap</code>	Switch the active keymap preset: vim, helix, or emacs.
<code>:config-open</code>	Open the user config.toml file.
<code>:config-open-workspace</code>	Open the workspace config.toml file.
<code>:log-open</code>	Open the zemacs log file.
<code>:insert-output</code>	Run shell command, inserting output before each selection.
<code>:append-output</code>	Run shell command, appending output after each selection.
<code>:pipe, : </code>	Pipe each selection to the shell command.
<code>:pipe-to</code>	Pipe each selection to the shell command, ignoring output.
<code>:run-shell-command, :sh, :!</code>	Run a shell command
<code>:elisp, :eval-expression, :el</code>	Evaluate an Emacs Lisp expression against the editor (embedded elisprs).
<code>:vim, :viml, :vimscript</code>	Evaluate a Vimscript (VimL) expression via the embedded vimlrs interpreter.
<code>:awk, :awk-filter</code>	Filter the selection (or whole buffer) through an awk program (embedded awkrs).
<code>:zsh, :zshell</code>	Run a command in the embedded zsh shell (state persists); output shown in a popup.
<code>:stryke, :st</code>	Evaluate stryke (strykelang) source via the embedded interpreter (state persists).
<code>:repl</code>	Open the embedded-language REPL (elisp/viml/stryke/awk/zsh); optional starting language.
<code>:reset-diff-change, :diffget, :diffg</code>	Reset the diff change at the cursor position.
<code>:clear-register</code>	Clear given register. If no argument is provided, clear all registers.
<code>:set-register</code>	Set contents of the given register.
<code>:redraw</code>	Clear and re-render the whole UI
<code>:move, :mv</code>	Move the current buffer and its corresponding file to a different path
<code>:move!, :mv!</code>	Move the current buffer and its corresponding file to a different path creating necessary subdirectories
<code>:delete-file, :remove-file</code>	Delete the current buffer's file from disk and close the buffer (vim-eunuch :Delete).
<code>:chmod-x, :chmodx, :make-executable</code>	Make the current file executable (chmod a+x). Unix only.
<code>:mkdir</code>	Create a directory and any missing parents; with no arg, the current file's parent.
<code>:yank-diagnostic</code>	Yank diagnostic(s) under primary cursor to register, or clipboard by default
<code>:read, :r</code>	Load a file into buffer
<code>:echo</code>	Prints the given arguments to the statusline.
<code>:noop</code>	Does nothing.

Name	Description
<code>:workspace-trust</code>	Allow language servers and local config for the current workspace.
<code>:workspace-untrust</code>	Revoke the current workspace's trust grant or exclusion.
<code>:workspace-exclude</code>	Mark the current workspace as never-prompt. Never prompts for trust again.

Static Commands and Keybindings

Every static (bindable) command and the default keys bound to it, by mode.

Name	Description	Default keybinds
<code>no_op</code>	Do nothing	
<code>move_char_left</code>	Move left	normal: <code>h</code> , <code><[-h></code> , <code><left></code> , insert: <code><[-b></code> , <code><left></code>
<code>move_char_right</code>	Move right	normal: <code>l</code> , <code><right></code> , insert: <code><[-f></code> , <code><right></code>
<code>move_line_up</code>	Move up	normal: <code>gk</code> , <code>g<up></code>
<code>move_line_down</code>	Move down	normal: <code>gj</code> , <code>g<down></code>
<code>move_visual_line_up</code>	Move up	normal: <code>k</code> , <code><up></code> , <code><[-p></code> , insert: <code><up></code> , <code><[-g>k</code> , <code><[-g><up></code> , <code><[-g><[-k></code>
<code>move_visual_line_down</code>	Move down	normal: <code>j</code> , <code><[-j></code> , <code><[-n></code> , <code><down></code> , insert: <code><[-g>j</code> , <code><down></code> , <code><[-g><[-j></code> , <code><[-g><down></code>
<code>extend_char_left</code>	Extend left	select: <code>h</code> , <code><left></code>
<code>extend_char_right</code>	Extend right	select: <code>l</code> , <code><right></code>
<code>extend_line_up</code>	Extend up	
<code>extend_line_down</code>	Extend down	
<code>extend_visual_line_up</code>	Extend up	select: <code>k</code> , <code><up></code>
<code>extend_visual_line_down</code>	Extend down	select: <code>j</code> , <code><down></code>
<code>copy_selection_on_next_line</code>	Copy selection on next line	select: <code><[-v></code>
<code>copy_selection_on_prev_line</code>	Copy selection on previous line	
<code>move_next_word_start</code>	Move to start of next word	normal: <code><A-f></code> , <code><[-right></code> , <code><S-right></code> , insert: <code><A-f></code> , <code><[-right></code> , <code><S-right></code>
<code>move_prev_word_start</code>	Move to start of previous word	normal: <code><A-b></code> , <code><[-left></code> , <code><S-left></code> , insert: <code><A-b></code> , <code><[-left></code> , <code><S-left></code>
<code>move_next_word_end</code>	Move to end of next word	
<code>move_prev_word_end</code>	Move to end of previous word	
<code>move_next_long_word_start</code>	Move to start of next long word	
<code>move_prev_long_word_start</code>	Move to start of previous long word	
<code>move_next_long_word_end</code>	Move to end of next long word	
<code>move_prev_long_word_end</code>	Move to end of previous long word	
<code>move_next_sub_word_start</code>	Move to start of next sub word	
<code>move_prev_sub_word_start</code>	Move to start of previous sub word	
<code>move_next_sub_word_end</code>	Move to end of next sub word	
<code>move_prev_sub_word_end</code>	Move to end of previous sub word	

Name	Description	Default keybinds
<code>vim_move_next_word_start</code>	Move to start of next word (vim caret)	normal: <code>w</code>
<code>vim_move_prev_word_start</code>	Move to start of previous word (vim caret)	normal: <code>b</code>
<code>vim_move_next_word_end</code>	Move to end of next word (vim caret)	normal: <code>e</code>
<code>vim_move_prev_word_end</code>	Move to end of previous word (vim caret)	normal: <code>ge</code>
<code>vim_move_next_long_word_start</code>	Move to start of next long word (vim caret)	normal: <code>W</code>
<code>vim_move_prev_long_word_start</code>	Move to start of previous long word (vim caret)	normal: <code>B</code>
<code>vim_move_next_long_word_end</code>	Move to end of next long word (vim caret)	normal: <code>E</code>
<code>vim_move_prev_long_word_end</code>	Move to end of previous long word (vim caret)	normal: <code>gE</code>
<code>move_parent_node_end</code>	Move to end of the parent node	normal: <code><space>k\$</code> , select: <code><space>k\$</code>
<code>move_parent_node_start</code>	Move to beginning of the parent node	normal: <code><space>k0</code> , select: <code><space>k0</code>
<code>extend_next_word_start</code>	Extend to start of next word	select: <code>w</code>
<code>extend_prev_word_start</code>	Extend to start of previous word	select: <code>b</code>
<code>extend_next_word_end</code>	Extend to end of next word	select: <code>e</code>
<code>extend_prev_word_end</code>	Extend to end of previous word	
<code>extend_next_long_word_start</code>	Extend to start of next long word	select: <code>W</code>
<code>extend_prev_long_word_start</code>	Extend to start of previous long word	select: <code>B</code>
<code>extend_next_long_word_end</code>	Extend to end of next long word	select: <code>E</code>
<code>extend_prev_long_word_end</code>	Extend to end of prev long word	
<code>extend_next_sub_word_start</code>	Extend to start of next sub word	
<code>extend_prev_sub_word_start</code>	Extend to start of previous sub word	
<code>extend_next_sub_word_end</code>	Extend to end of next sub word	
<code>extend_prev_sub_word_end</code>	Extend to end of prev sub word	
<code>extend_parent_node_end</code>	Extend to end of the parent node	
<code>extend_parent_node_start</code>	Extend to beginning of the parent node	
<code>find_till_char</code>	Move till next occurrence of char	normal: <code>t</code>
<code>find_next_char</code>	Move to next occurrence of char	normal: <code>f</code>
<code>extend_till_char</code>	Extend till next occurrence of char	select: <code>t</code>
<code>extend_next_char</code>	Extend to next occurrence of char	select: <code>f</code>
<code>till_prev_char</code>	Move till previous occurrence of char	normal: <code>T</code>
<code>find_prev_char</code>	Move to previous occurrence of char	normal: <code>F</code>
<code>sneak_forward</code>	Sneak: jump forward to a two-character sequence	
<code>sneak_backward</code>	Sneak: jump backward to a two-character sequence	
<code>sneak_or_substitute_char</code>	Sneak forward, or substitute char when vim-sneak is off	normal: <code>s</code>

Name	Description	Default keybinds
<code>sneak_or_substitute_line</code>	Sneak backward, or substitute line when vim-sneak is off	normal: <code>S</code>
<code>extend_till_prev_char</code>	Extend till previous occurrence of char	select: <code>T</code>
<code>extend_prev_char</code>	Extend to previous occurrence of char	select: <code>F</code>
<code>repeat_last_motion</code>	Repeat last motion	normal: <code>;</code> , select: <code>;</code>
<code>repeat_find_char_reverse</code>	Repeat last find in opposite direction (,.)	normal: <code>,</code> , select: <code>,</code>
<code>replace</code>	Replace with new char	normal: <code>r</code> , select: <code>r</code>
<code>switch_case</code>	Switch (toggle) case	normal: <code>~</code> , select: <code>~</code>
<code>switch_to_uppercase</code>	Switch to uppercase	normal: <code><space>xU</code> , select: <code><space>xU</code>
<code>switch_to_lowercase</code>	Switch to lowercase	normal: <code><space>xu</code> , select: <code><space>xu</code>
<code>page_up</code>	Move page up	normal: <code>z^</code> , <code><A-v></code> , <code><C-b></code> , <code><S-up></code> , <code><pageup></code> , <code><S-minus></code> , insert: <code><A-v></code> , <code><S-up></code> , <code><pageup></code>
<code>page_down</code>	Move page down	normal: <code>z+</code> , <code><C-f></code> , <code><S-+></code> , <code><S-iet></code> , <code><S-down></code> , <code><pagedown></code> , insert: <code><S-down></code> , <code><pagedown></code>
<code>half_page_up</code>	Move half page up	
<code>half_page_down</code>	Move half page down	
<code>page_cursor_up</code>	Move page and cursor up	
<code>page_cursor_down</code>	Move page and cursor down	
<code>page_cursor_half_up</code>	Move page and cursor half up	normal: <code><C-u></code>
<code>page_cursor_half_down</code>	Move page and cursor half down	normal: <code><C-d></code>
<code>select_all</code>	Select whole document	
<code>select_regex</code>	Select all regex matches inside selections	
<code>select_all_instances</code>	Select all occurrences of the current selection in the buffer	
<code>split_selection</code>	Split selections on regex matches	
<code>split_selection_on_newline</code>	Split selection on newlines	
<code>merge_selections</code>	Merge selections	
<code>merge_consecutive_selections</code>	Merge consecutive selections	
<code>search</code>	Search for regex pattern	normal: <code>/</code> , <code><C-s></code>
<code>rsearch</code>	Reverse search for regex pattern	normal: <code>?</code>
<code>search_next</code>	Select next search match	normal: <code>n</code> , <code>gn</code> , <code><space>sH</code> , select: <code><space>sH</code>
<code>search_prev</code>	Select previous search match	normal: <code>N</code> , <code>gN</code>
<code>extend_search_next</code>	Add next search match to selection	
<code>extend_search_prev</code>	Add previous search match to selection	
<code>search_selection</code>	Use current selection as search pattern	

Name	Description	Default keybinds
<code>search_selection_detect_word_boundaries</code>	Use current selection as the search pattern, automatically wrapping with <code>\b</code> on word boundaries	
<code>make_search_word_bounded</code>	Modify current search to make it word bounded	
<code>global_search</code>	Global search in workspace folder	normal: <code><space>/, <space>po, <space>ps, <space>sB, <space>sD, <space>sF, <space>sP, <space>sb, <space>sd, <space>sf, <space>sp, <space>ss, <space>saA, <space>saB, <space>saD, <space>saF, <space>saP, <space>saa, <space>sab, <space>sad, <space>saf, <space>sap, <space>sgB, <space>sgF, <space>sgG, <space>sgb, <space>sgd, <space>sgf, <space>sgg, <space>sgp, <space>skB, <space>skD, <space>skF, <space>skP, <space>skb, <space>skd, <space>skf, <space>skp, <space>srB, <space>srD, <space>srF, <space>srP, <space>srR, <space>srb, <space>srD, <space>srF, <space>srP, <space>srR, select: <code><space>/, <space>po, <space>ps, <space>sB, <space>sD, <space>sF, <space>sP, <space>sb, <space>sd, <space>sf, <space>sp, <space>ss, <space>saA, <space>saB, <space>saD, <space>saF, <space>saP, <space>saa, <space>sab, <space>sad, <space>saf, <space>sap, <space>sgB, <space>sgF, <space>sgG, <space>sgb, <space>sgd, <space>sgf, <space>sgg, <space>sgp, <space>skB, <space>skD, <space>skF, <space>skP, <space>skb, <space>skd, <space>skf, <space>skp, <space>srB, <space>srD, <space>srF, <space>srP, <space>srR, <space>srb, <space>srD, <space>srF, <space>srP, <space>srR</code></code>
<code>extend_line</code>	Select current line, if already selected, extend to another line based on the anchor	normal: <code><space>kV</code> , select: <code><space>kV</code>
<code>extend_line_below</code>	Select current line, if already selected, extend to next line	
<code>extend_line_above</code>	Select current line, if already selected, extend to previous line	
<code>select_line_above</code>	Select current line, if already selected, extend or shrink line above based on the anchor	

Name	Description	Default keybinds
<code>select_line_below</code>	Select current line, if already selected, extend or shrink line below based on the anchor	
<code>extend_to_line_bounds</code>	Extend selection to line bounds	select: <code>V</code>
<code>shrink_to_line_bounds</code>	Shrink selection to line bounds	
<code>delete_selection</code>	Delete selection	normal: <code>x</code> , <code></code>
<code>delete_selection_noyank</code>	Delete selection without yanking	
<code>change_selection</code>	Change selection	select: <code>c</code> , <code>s</code>
<code>change_selection_noyank</code>	Change selection without yanking	
<code>collapse_selection</code>	Collapse selection into single cursor	normal: <code><esc></code>
<code>flip_selections</code>	Flip selection cursor and anchor	select: <code>O</code> , <code>o</code>
<code>ensure_selections_forward</code>	Ensure all selections face forward	
<code>insert_mode</code>	Insert before selection	normal: <code>i</code> , <code><ins></code> , <code><space>ki</code> , select: <code><space>ki</code>
<code>append_mode</code>	Append after selection	normal: <code>a</code> , select: <code>A</code>
<code>replace_mode</code>	Enter Replace mode (overtypе)	normal: <code>R</code> , <code>gR</code> , insert: <code><ins></code>
<code>command_mode</code>	Enter command mode	normal: <code>:</code> , <code>gQ</code> , <code><space>:</code> , <code><space>k:</code> , select: <code>:</code> , <code><space>:</code> , <code><space>k:</code>
<code>file_picker</code>	Open file picker	normal: <code><space>fA</code> , <code><space>fL</code> , <code><space>ff</code> , <code><space>fL</code> , <code><space>pf</code> , <code><space>ph</code> , <code><space>pp</code> , select: <code><space>fA</code> , <code><space>fL</code> , <code><space>ff</code> , <code><space>fL</code> , <code><space>pf</code> , <code><space>ph</code> , <code><space>pp</code>
<code>file_picker_in_current_buffer_directory</code>	Open file picker at current buffer's directory	
<code>file_picker_in_current_directory</code>	Open file picker at current working directory	
<code>file_explorer</code>	Open file explorer in workspace root	normal: <code><space>ad</code> , <code><space>af</code> , <code><space>ft</code> , <code><space>pd</code> , <code><space>pt</code> , <code><space>atrd</code> , <code><space>attr</code> , select: <code><space>ad</code> , <code><space>af</code> , <code><space>ft</code> , <code><space>pd</code> , <code><space>pt</code> , <code><space>atrd</code> , <code><space>attr</code>
<code>file_explorer_in_current_buffer_directory</code>	Open file explorer at current buffer's directory	normal: <code><space>fd</code> , <code><space>fj</code> , <code><space>jD</code> , <code><space>jd</code> , select: <code><space>fd</code> , <code><space>fj</code> , <code><space>jD</code> , <code><space>jd</code>
<code>file_explorer_in_current_directory</code>	Open file explorer at current working directory	
<code>code_action</code>	Perform code action	normal: <code><space>la</code> , select: <code><space>la</code>
<code>buffer_picker</code>	Open buffer picker	normal: <code><space>bW</code> , <code><space>bb</code> , <code><space>pb</code> , <code><space>b.b</code> , select: <code><space>bW</code> , <code><space>bb</code> , <code><space>pb</code> , <code><space>b.b</code>
<code>jumplist_picker</code>	Open jumplist picker	normal: <code><space>jj</code> , select: <code><space>jj</code>

Name	Description	Default keybinds
register_picker	Browse registers and paste the chosen one	normal: <code><space>re</code> , <code><space>rr</code> , <code><space>ry</code> , select: <code><space>re</code> , <code><space>rr</code> , <code><space>ry</code>
marks_picker	Fuzzy-pick a vim mark and jump to it (:Marks)	normal: <code><space>fb</code> , <code><space>rm</code> , select: <code><space>fb</code> , <code><space>rm</code>
buffer_line_picker	Fuzzy-search lines in the current buffer (:BLines)	normal: <code><space>sL</code> , select: <code><space>sL</code>
command_history_picker	Fuzzy-pick and run a past command line (:History:)	normal: <code><space>r:</code> , select: <code><space>r:</code>
search_history_picker	Fuzzy-pick and re-run a past search (:History/)	normal: <code><space>r/</code> , select: <code><space>r/</code>
unicode_picker	Fuzzy-pick a character/digraph and insert it (helm-unicode)	normal: <code><space>iu</code> , select: <code><space>iu</code>
git_file_log_picker	Commit log for the current file (:BCommits)	normal: <code><space>gt</code> , <code><space>gfl</code> , select: <code><space>gt</code> , <code><space>gfl</code>
git_repo_log_picker	Commit log for the whole repo (:Commits)	normal: <code><space>gL</code> , select: <code><space>gL</code>
theme_picker	Open fuzzy theme picker with live preview	normal: <code><space>Tc</code> , select: <code><space>Tc</code>
wrap_sexp	Wrap the selection in parentheses	normal: <code><space>kw</code> , select: <code><space>kw</code>
symbol_picker	Open symbol picker	normal: <code><space>ji</code> , <code><space>pg</code> , <code><space>s j</code> , select: <code><space>ji</code> , <code><space>pg</code> , <code><space>s j</code>
syntax_symbol_picker	Open symbol picker from syntax information	
lsp_or_syntax_symbol_picker	Open symbol picker from LSP or syntax information	
changed_file_picker	Open changed file picker	normal: <code><space>bm</code> , select: <code><space>bm</code>
frecent_file_picker	Open recent files ranked by frequency (z algorithm)	normal: <code><space>fr</code> , select: <code><space>fr</code>
reopen_last_closed	Reopen the most recently closed file	normal: <code><space>bu</code> , <code><space>fu</code> , select: <code><space>bu</code> , <code><space>fu</code>
harpoon_add	Pin the current file to the harpoon list	normal: <code><space>Ha</code> , select: <code><space>Ha</code>
harpoon_jump	Jump to the harpoon mark in slot [count]	normal: <code><space>Hj</code> , select: <code><space>Hj</code>
harpoon_1	Jump to harpoon mark 1	normal: <code><space>H1</code> , select: <code><space>H1</code>
harpoon_2	Jump to harpoon mark 2	normal: <code><space>H2</code> , select: <code><space>H2</code>
harpoon_3	Jump to harpoon mark 3	normal: <code><space>H3</code> , select: <code><space>H3</code>
harpoon_4	Jump to harpoon mark 4	normal: <code><space>H4</code> , select: <code><space>H4</code>
harpoon_next	Open the next harpoon mark	normal: <code><space>Hn</code> , select: <code><space>Hn</code>
harpoon_prev	Open the previous harpoon mark	normal: <code><space>Hp</code> , select: <code><space>Hp</code>
harpoon_menu	Open the harpoon marks menu	normal: <code><space>Hh</code> , <code><space>Hl</code> , select: <code><space>Hh</code> , <code><space>Hl</code>
harpoon_remove	Unpin the current file from harpoon	normal: <code><space>Hd</code> , select: <code><space>Hd</code>
select_references_to_symbol_under_cursor	Select symbol references	normal: <code><space>se</code> , <code><space>sh</code> , select: <code><space>se</code> , <code><space>sh</code>
workspace_symbol_picker	Open workspace symbol picker	normal: <code><space>jI</code> , <code><space>sS</code> , select: <code><space>jI</code> , <code><space>sS</code>

Name	Description	Default keybinds
<code>syntax_workspace_symbol_picker</code>	Open workspace symbol picker from syntax information	
<code>lsp_or_syntax_workspace_symbol_picker</code>	Open workspace symbol picker from LSP or syntax information	
<code>diagnostics_picker</code>	Open diagnostic picker	normal: <code><space>e</code> <code>l</code> , select: <code><space>e</code> <code>l</code>
<code>workspace_diagnostics_picker</code>	Open workspace diagnostic picker	normal: <code><space>e</code> <code>L</code> , select: <code><space>e</code> <code>L</code>
<code>last_picker</code>	Open last picker	normal: <code><space></code> <code>'</code> , <code><space></code> <code>r</code> <code>l</code> , <code><space></code> <code>s</code> <code>l</code> , select: <code><space></code> <code>'</code> , <code><space></code> <code>r</code> <code>l</code> , <code><space></code> <code>s</code> <code>l</code>
<code>insert_at_line_start</code>	Insert at start of line	normal: <code>I</code> , <code>g</code> <code>I</code>
<code>insert_at_line_end</code>	Insert at end of line	normal: <code>A</code>
<code>open_below</code>	Open new line below selection	normal: <code>o</code>
<code>open_above</code>	Open new line above selection	normal: <code>O</code>
<code>normal_mode</code>	Enter normal mode	normal: <code><[- c ></code> , <code><[- \ ></code> <code><[- g ></code> , <code><[- \ ></code> <code><[- n ></code>
<code>select_mode</code>	Enter selection extend mode	normal: <code>v</code> , <code>g</code> <code>h</code> , <code><[- v ></code> , <code>g</code> <code><[- h ></code> , <code><[- space ></code> , <code><space></code> <code>k</code> <code>v</code> , <code><space></code> <code>k</code> <code><[- v ></code> , select: <code><space></code> <code>k</code> <code>v</code> , <code><space></code> <code>k</code> <code><[- v ></code>
<code>exit_select_mode</code>	Exit selection mode	
<code>goto_definition</code>	Goto definition	normal: <code>g</code> <code>]</code> , <code>g</code> <code>d</code> , <code><[-] ></code> , <code><[- w ></code> <code>]</code> , <code><[- d ></code> , <code>g</code> <code><[-] ></code> , <code><[- w ></code> <code>g</code> <code>]</code> , <code><space></code> <code>g</code> <code>d</code> , <code><space></code> <code>j</code> <code>f</code> , <code><space></code> <code>j</code> <code>v</code> , <code><space></code> <code>w</code> <code>]</code> , <code><[- w ></code> <code><[-] ></code> , <code><space></code> <code>m</code> <code>g</code> <code>g</code> , <code><space></code> <code>w</code> <code>g</code> <code>]</code> , <code><[- w ></code> <code>g</code> <code><[-] ></code> , <code><space></code> <code>w</code> <code><[-] ></code> , <code><space></code> <code>w</code> <code>g</code> <code><[-] ></code> , select: <code><[-] ></code> , <code><space></code> <code>g</code> <code>d</code> , <code><space></code> <code>j</code> <code>f</code> , <code><space></code> <code>j</code> <code>v</code> , <code><space></code> <code>w</code> <code>]</code> , <code><space></code> <code>m</code> <code>g</code> <code>g</code> , <code><space></code> <code>w</code> <code>g</code> <code>]</code> , <code><space></code> <code>w</code> <code><[-] ></code> , <code><space></code> <code>w</code> <code>g</code> <code><[-] ></code>
<code>goto_declaration</code>	Goto declaration	normal: <code>g</code> <code>D</code> , <code><[- w ></code> <code>i</code> , <code>[<[- d ></code> , <code><space></code> <code>g</code> <code>D</code> , <code><space></code> <code>w</code> <code>i</code> , <code><[- w ></code> <code><[- i ></code> , <code><space></code> <code>w</code> <code><[- i ></code> , select: <code><space></code> <code>g</code> <code>D</code> , <code><space></code> <code>w</code> <code>i</code> , <code><space></code> <code>w</code> <code><[- i ></code>
<code>add_newline_above</code>	Add newline above	
<code>add_newline_below</code>	Add newline below	
<code>goto_type_definition</code>	Goto type definition	normal: <code>g</code> <code>y</code> , <code><space></code> <code>g</code> <code>y</code> , select: <code><space></code> <code>g</code> <code>y</code>
<code>goto_implementation</code>	Goto implementation	normal: <code><space></code> <code>g</code> <code>i</code> , select: <code><space></code> <code>g</code> <code>i</code>
<code>goto_file_start</code>	Goto line number <code><n></code> else file start	normal: <code>g</code> <code>g</code> , <code><A - l t ></code> , <code><[- h o m e ></code> , insert: <code><A - l t ></code> , <code><[- h o m e ></code>
<code>goto_file_end</code>	Goto file end	insert: <code><A - g t ></code> , <code><[- e n d ></code>
<code>extend_to_file_start</code>	Extend to line number <code><n></code> else file start	select: <code>g</code> <code>g</code>
<code>extend_to_file_end</code>	Extend to file end	

Name	Description	Default keybinds
<code>goto_file</code>	Goto files/URLs in selections	normal: <code>[f,]f, gf, gx, <C-w>gF, <C-w>gf, <space>fF, <space>fo, <space>jU, <space>ju, <space>xO, <space>wgF, <space>wgf, select: <space>fF, <space>fo, <space>jU, <space>ju, <space>xO, <space>wgF, <space>wgf</code>
<code>goto_file_hsplit</code>	Goto files in selections (hsplit)	normal: <code><C-w>f, <C-w>f, <space>wF, <space>wf, <C-w><C-f>, <space>w<C-f>, select: <space>wF, <space>wf, <space>w<C-f></code>
<code>goto_file_vsplit</code>	Goto files in selections (vsplit)	
<code>goto_reference</code>	Goto references	normal: <code>gr</code>
<code>goto_window_top</code>	Goto window top	normal: <code>H</code>
<code>goto_window_center</code>	Goto window center	normal: <code>M</code>
<code>goto_window_bottom</code>	Goto window bottom	normal: <code>L</code>
<code>goto_last_accessed_file</code>	Goto last accessed file	normal: <code><C-^>, <C-w>^, g<tab>, <C-tab>, <space>w^, <C-w><C-^>, <C-w>g<tab>, <space><tab>, <space>w<C-^>, <space>wg<tab>, select: <space>w^, <space><tab>, <space>w<C-^>, <space>wg<tab></code>
<code>goto_last_modified_file</code>	Goto last modified file	normal: <code><space>pr, select: <space>pr</code>
<code>goto_last_modification</code>	Goto last modification	normal: <code>g,, g., g;</code>
<code>goto_line</code>	Goto line	
<code>goto_last_line</code>	Goto last line	normal: <code>G, <A-gt>, <C-end></code>
<code>extend_to_last_line</code>	Extend to last line	select: <code>G, ge</code>
<code>goto_first_diag</code>	Goto first diagnostic	normal: <code><space>ef, select: <space>ef</code>
<code>copy_diagnostic</code>	Copy the diagnostic message(s) on the current line	
<code>goto_last_diag</code>	Goto last diagnostic	normal: <code><space>e., select: <space>e.</code>
<code>goto_next_diag</code>	Goto next diagnostic	normal: <code>]d, <space>en, select: <space>en</code>
<code>goto_prev_diag</code>	Goto previous diagnostic	normal: <code>[d, <space>ep, select: <space>ep</code>
<code>goto_next_change</code>	Goto next change	normal: <code>]g</code>
<code>goto_prev_change</code>	Goto previous change	normal: <code>[g</code>
<code>goto_next_conflict</code>	Goto next merge-conflict marker	normal: <code>]n</code>
<code>goto_prev_conflict</code>	Goto previous merge-conflict marker	normal: <code>[n</code>
<code>conflict_take_all_ours</code>	Resolve ALL conflicts: keep our side	normal: <code><space>gcO, select: <space>gcO</code>
<code>conflict_take_all_theirs</code>	Resolve ALL conflicts: keep their side	normal: <code><space>gcT, select: <space>gcT</code>
<code>git_diff</code>	Open side-by-side diff vs HEAD	normal: <code><space>g=, select: <space>g=</code>
<code>resolve_conflicts</code>	Resolve merge conflicts (3-way)	normal: <code><space>gm, <space>gcr, select: <space>gm, <space>gcr</code>

Name	Description	Default keybinds
<code>git_status</code>	Magit status	normal: <code><space>gs</code> , select: <code><space>gs</code>
<code>org_cycle</code>	Org: toggle subtree fold	normal: <code><space>mz</code> , <code><space>m<tab></code> , select: <code><space>mz</code> , <code><space>m<tab></code>
<code>org_todo</code>	Org: cycle TODO keyword	normal: <code><space>mt</code> , select: <code><space>mt</code>
<code>org_priority</code>	Org: cycle priority cookie	normal: <code><space>mp</code> , select: <code><space>mp</code>
<code>org_promote</code>	Org: promote heading	normal: <code><space>mH</code> , select: <code><space>mH</code>
<code>org_demote</code>	Org: demote heading	normal: <code><space>mL</code> , select: <code><space>mL</code>
<code>org_next_heading</code>	Org: next heading	normal: <code><space>mj</code> , select: <code><space>mj</code>
<code>org_prev_heading</code>	Org: previous heading	normal: <code><space>mk</code> , select: <code><space>mk</code>
<code>org_fold_all</code>	Org: fold all headings	normal: <code><space>ma</code> , select: <code><space>ma</code>
<code>org_unfold_all</code>	Org: unfold all	normal: <code><space>mA</code> , select: <code><space>mA</code>
<code>org_agenda</code>	Org: open agenda	normal: <code><space>aoa</code> , select: <code><space>aoa</code>
<code>org_capture</code>	Org: capture note	normal: <code><space>aoc</code> , select: <code><space>aoc</code>
<code>goto_first_change</code>	Goto first change	
<code>goto_last_change</code>	Goto last change	normal: <code><space>jc</code> , select: <code><space>jc</code>
<code>goto_line_start</code>	Goto line start	normal: <code>0</code> , <code>g0</code> , <code><home></code> , <code>g<home></code> , <code><space>j0</code> , select: <code><space>j0</code> , insert: <code><home></code>
<code>goto_line_end</code>	Goto line end	normal: <code>\$</code> , <code>g\$</code> , <code>gL</code> , <code><end></code> , <code>g<end></code> , <code><space>j\$</code> , select: <code><space>j\$</code>
<code>goto_column</code>	Goto column	normal: <code>\ </code>
<code>extend_to_column</code>	Extend to column	
<code>goto_next_buffer</code>	Goto next buffer	normal: <code>]b</code> , <code>gt</code> , <code><[-w>gt</code> , <code><space>bn</code> , <code><space>b.n</code> , <code><space>wgt</code> , select: <code><space>bn</code> , <code><space>b.n</code> , <code><space>wgt</code>
<code>goto_previous_buffer</code>	Goto previous buffer	normal: <code>[b</code> , <code>gT</code> , <code><[-w>gT</code> , <code><space>bp</code> , <code><space>b.N</code> , <code><space>b.p</code> , <code><space>wgT</code> , select: <code><space>bp</code> , <code><space>b.N</code> , <code><space>b.p</code> , <code><space>wgT</code> insert: <code><end></code>
<code>goto_line_end_newline</code>	Goto newline at line end	
<code>goto_first_nonwhitespace</code>	Goto first non-blank in line	normal: <code>^</code> , <code>_</code> , <code>g^</code> , <code><A-m></code>
<code>trim_selections</code>	Trim whitespace from selections	
<code>extend_to_line_start</code>	Extend to line start	select: <code>0</code> , <code><home></code>
<code>extend_to_first_nonwhitespace</code>	Extend to first non-blank in line	select: <code>^</code> , <code>gh</code>
<code>extend_to_line_end</code>	Extend to line end	select: <code>\$</code> , <code>g\$</code> , <code>gL</code> , <code><end></code>
<code>extend_to_line_end_newline</code>	Extend to line end	
<code>signature_help</code>	Show signature help	normal: <code><space>ls</code> , select: <code><space>ls</code>

Name	Description	Default keybinds
<code>smart_tab</code>	Insert tab if all cursors have all whitespace to their left; otherwise, run a separate command.	
<code>insert_tab</code>	Insert tab char	
<code>insert_newline</code>	Insert newline char	insert: <code><[-j></code> , <code><ret></code>
<code>insert_char_interactive</code>	Insert an interactively-chosen char	insert: <code><[-q></code> , <code><[-v></code>
<code>append_char_interactive</code>	Append an interactively-chosen char	
<code>delete_char_backward</code>	Delete previous char	normal: <code>X</code> , insert: <code><[-h></code> , <code><backspace></code>
<code>delete_char_forward</code>	Delete next char	insert: <code></code>
<code>delete_word_backward</code>	Delete previous word	insert: <code><[-w></code> , <code><A-backspace></code>
<code>delete_word_forward</code>	Delete next word	normal: <code><A-d></code> , insert: <code><A-d></code>
<code>kill_to_line_start</code>	Delete till start of line	insert: <code><[-u></code>
<code>kill_to_line_end</code>	Delete till end of line	
<code>undo</code>	Undo change	normal: <code>U</code> , <code>u</code> , <code><[-/>></code> , <code><[-_></code> , <code><space>ku</code> , select: <code><space>ku</code> , insert: <code><[-/>></code> , <code><[-_></code>
<code>redo</code>	Redo change	normal: <code><[-r></code> , <code><space>k<[-r></code> , select: <code><space>k<[-r></code>
<code>earlier</code>	Move backward in history	normal: <code>g<minus></code>
<code>later</code>	Move forward in history	normal: <code>g+</code>
<code>commit_undo_checkpoint</code>	Commit changes to new checkpoint	insert: <code><[-g>U</code> , <code><[-g>u</code>
<code>yank</code>	Yank selection	normal: <code><A-w></code>
<code>yank_to_clipboard</code>	Yank selections to clipboard	
<code>yank_to_primary_clipboard</code>	Yank selections to primary clipboard	
<code>yank_joined</code>	Join and yank selections	
<code>yank_joined_to_clipboard</code>	Join and yank selections to clipboard	
<code>yank_main_selection_to_clipboard</code>	Yank main selection to clipboard	
<code>yank_joined_to_primary_clipboard</code>	Join and yank selections to primary clipboard	
<code>yank_main_selection_to_primary_clipboard</code>	Yank main selection to primary clipboard	
<code>replace_with_yanked</code>	Replace with yanked text	select: <code>P</code> , <code>p</code>
<code>replace_selections_with_clipboard</code>	Replace selections by clipboard content	
<code>replace_selections_with_primary_clipboard</code>	Replace selections by primary clipboard	
<code>paste_after</code>	Paste after selection	normal: <code>p</code> , <code>]p</code> , <code>gp</code> , <code>zp</code> , <code><space>kp</code> , select: <code><space>kp</code>
<code>paste_before</code>	Paste before selection	normal: <code>P</code> , <code>[P</code> , <code>[p</code> , <code>]P</code> , <code>gP</code> , <code>zP</code> , <code><space>kP</code> , select: <code><space>kP</code>
<code>paste_clipboard_after</code>	Paste clipboard after selections	

Name	Description	Default keybinds
<code>paste_clipboard_before</code>	Paste clipboard before selections	
<code>paste_primary_clipboard_after</code>	Paste primary clipboard after selections	
<code>paste_primary_clipboard_before</code>	Paste primary clipboard before selections	
<code>indent</code>	Indent selection	normal: ==, <gt;<gt;, <space>x<tab>, select: <space>x<tab>, insert: <[-t> normal: <lt><lt>, insert: <[-d>
<code>unindent</code>	Unindent selection	
<code>format_selections</code>	Format selection	normal: <A-q>, <space>j+, <space>j=, <space>lf, <space>xjc, <space>xjf, <space>xjl, <space>xjn, <space>xjr, select: <space>j+, <space>j=, <space>lf, <space>xjc, <space>xjf, <space>xjl, <space>xjn, <space>xjr
<code>join_selections</code>	Join lines inside selection	normal: J, <A-^>, <space>kJ, select: <space>kJ
<code>join_selections_space</code>	Join lines inside selection and select spaces	
<code>keep_selections</code>	Keep selections matching regex	
<code>remove_selections</code>	Remove selections matching regex	
<code>align_selections</code>	Align selections in column	normal: <space>xaß, <space>xa(, <space>xa), <space>xa,, <space>xa., <space>xa:, <space>xa;, <space>xa=, <space>xal, <space>xal[, <space>xa], <space>xaa, <space>xac, <space>xal, <space>xam, <space>xar, <space>xa{, <space>xa}, select: <space>xaß, <space>xa(, <space>xa), <space>xa,, <space>xa., <space>xa:, <space>xa;, <space>xa=, <space>xal, <space>xal[, <space>xa], <space>xaa, <space>xac, <space>xal, <space>xam, <space>xar, <space>xa{, <space>xa}
<code>keep_primary_selection</code>	Keep primary selection	
<code>remove_primary_selection</code>	Remove primary selection	
<code>completion</code>	Invoke completion popup	insert: <A-/, <[-n>, <[-p>, <[-x>s, <[-x><[-]>, <[-x><[-d>, <[-x><[-f>, <[-x><[-i>, <[-x><[-k>, <[-x><[-l>, <[-x><[-n>, <[-x><[-o>, <[-x><[-p>, <[-x><[-r>, <[-x><[-s>, <[-x><[-t>, <[-x><[-u>, <[-x><[-v>
<code>hover</code>	Show docs for item under cursor	normal: K, <[-w>}, <[-w>g}, <space>lk, <space>w}, <space>hda, <space>mhh, <space>wg}, select: K, <space>lk, <space>w}, <space>hda, <space>mhh, <space>wg}

Name	Description	Default keybinds
<code>toggle_comments</code>	Comment/uncomment selections	normal: <code><A-;></code> , <code><space></code> ;; <code><space>cP</code> , <code><space>cT</code> , <code><space>cc</code> , <code><space>ch</code> , <code><space>cp</code> , <code><space>ct</code> , select: <code><space></code> ;;, <code><space>cP</code> , <code><space>cT</code> , <code><space>cc</code> , <code><space>ch</code> , <code><space>cp</code> , <code><space>ct</code>
<code>toggle_line_comments</code>	Line comment/uncomment selections	normal: <code><space>cL</code> , <code><space>cL</code> , select: <code><space>cL</code> , <code><space>cL</code>
<code>toggle_block_comments</code>	Block comment/uncomment selections	normal: <code><space>cb</code> , select: <code><space>cb</code>
<code>rotate_selections_forward</code>	Rotate selections forward	
<code>rotate_selections_backward</code>	Rotate selections backward	
<code>rotate_selection_contents_forward</code>	Rotate selection contents forward	
<code>rotate_selection_contents_backward</code>	Rotate selections contents backward	
<code>reverse_selection_contents</code>	Reverse selections contents	
<code>expand_selection</code>	Expand selection to parent syntax node	normal: <code><space>v</code> , <code><space>kU</code> , <code><space>kk</code> , select: <code><space>v</code> , <code><space>kU</code> , <code><space>kk</code>
<code>shrink_selection</code>	Shrink selection to previously expanded syntax node	normal: <code><space>kj</code> , select: <code><space>kj</code>
<code>wildfire</code>	Wildfire: select/expand to the closest text object	normal: <code><ret></code>
<code>wildfire_shrink</code>	Wildfire: shrink to the previously selected text object	normal: <code><backspace></code>
<code>select_next_sibling</code>	Select next sibling in the syntax tree	normal: <code><space>kL</code> , <code><space>kL</code> , select: <code><space>kL</code> , <code><space>kL</code>
<code>select_prev_sibling</code>	Select previous sibling the in syntax tree	normal: <code><space>kH</code> , <code><space>kh</code> , select: <code><space>kH</code> , <code><space>kh</code>
<code>select_all_siblings</code>	Select all siblings of the current node	
<code>select_all_children</code>	Select all children of the current node	
<code>jump_forward</code>	Jump forward on jumplist	normal: <code><[-i></code> , <code><tab></code>
<code>jump_backward</code>	Jump backward on jumplist	normal: <code><[-o></code> , <code><[-t></code> , <code><space>jb</code> , <code><space>s`</code> , select: <code><space>jb</code> , <code><space>s`</code>
<code>save_selection</code>	Save current selection to jumplist	
<code>jump_view_right</code>	Jump to right split	normal: <code><[-w>l</code> , <code><[-w>.l</code> , <code><space>wL</code> , <code><[-w><[-l></code> , <code><space>w.l</code> , <code><[-w><right></code> , <code><space>w<[-l></code> , <code><space>w<right></code> , select: <code><space>wL</code> , <code><space>w.l</code> , <code><space>w<[-l></code> , <code><space>w<right></code>
<code>jump_view_left</code>	Jump to left split	normal: <code><[-w>h</code> , <code><[-w>.h</code> , <code><space>wH</code> , <code><[-w><[-h></code> , <code><space>w.h</code> , <code><[-w><left></code> , <code><space>w<[-h></code> , <code><space>w<left></code> , select: <code><space>wH</code> , <code><space>w.h</code> , <code><space>w<[-h></code> , <code><space>w<left></code>

Name	Description	Default keybinds
<code>jump_view_up</code>	Jump to split above	normal: <code><C-w>k</code> , <code><C-w>t</code> , <code><C-w>.k</code> , <code><C-w><up></code> , <code><space>wk</code> , <code><space>wt</code> , <code><C-w><C-k></code> , <code><C-w><C-t></code> , <code><space>w.k</code> , <code><space>w<up></code> , <code><space>w<C-k></code> , <code><space>w<C-t></code> , select: <code><space>wk</code> , <code><space>wt</code> , <code><space>w.k</code> , <code><space>w<up></code> , <code><space>w<C-k></code> , <code><space>w<C-t></code>
<code>jump_view_down</code>	Jump to split below	normal: <code><C-w>b</code> , <code><C-w>j</code> , <code><C-w>.j</code> , <code><space>wb</code> , <code><space>wj</code> , <code><C-w><C-b></code> , <code><C-w><C-j></code> , <code><space>w.j</code> , <code><C-w><down></code> , <code><space>w<C-b></code> , <code><space>w<C-j></code> , <code><space>w<down></code> , select: <code><space>wb</code> , <code><space>wj</code> , <code><space>w.j</code> , <code><space>w<C-b></code> , <code><space>w<C-j></code> , <code><space>w<down></code>
<code>swap_view_right</code>	Swap with right split	normal: <code><C-w>L</code> , <code><C-w>.L</code> , <code><space>wL</code> , <code><space>w.L</code> , select: <code><space>wL</code> , <code><space>w.L</code>
<code>swap_view_left</code>	Swap with left split	normal: <code><C-w>H</code> , <code><C-w>.H</code> , <code><space>wH</code> , <code><space>w.H</code> , select: <code><space>wH</code> , <code><space>w.H</code>
<code>swap_view_up</code>	Swap with split above	normal: <code><C-w>K</code> , <code><C-w>.K</code> , <code><space>wK</code> , <code><space>w.K</code> , select: <code><space>wK</code> , <code><space>w.K</code>
<code>swap_view_down</code>	Swap with split below	normal: <code><C-w>J</code> , <code><C-w>.J</code> , <code><space>wJ</code> , <code><space>w.J</code> , select: <code><space>wJ</code> , <code><space>w.J</code>
<code>transpose_view</code>	Transpose splits	normal: <code><C-w>M</code> , <code><C-w>x</code> , <code><space>wM</code> , <code><space>wx</code> , <code><C-w><C-x></code> , <code><space>w<C-x></code> , select: <code><space>wM</code> , <code><space>wx</code> , <code><space>w<C-x></code>
<code>rotate_view</code>	Goto next window	normal: <code><C-w>p</code> , <code><C-w>r</code> , <code><C-w>w</code> , <code><C-w>.o</code> , <code><C-w>.r</code> , <code><C-w>.w</code> , <code><space>wp</code> , <code><space>wr</code> , <code><space>ww</code> , <code><C-w><C-p></code> , <code><C-w><C-r></code> , <code><C-w><C-w></code> , <code><C-w><tab></code> , <code><space>b.o</code> , <code><space>w.o</code> , <code><space>w.r</code> , <code><space>w.w</code> , <code><space>w<C-p></code> , <code><space>w<C-r></code> , <code><space>w<C-w></code> , <code><space>w<tab></code> , select: <code><space>wp</code> , <code><space>wr</code> , <code><space>ww</code> , <code><space>b.o</code> , <code><space>w.o</code> , <code><space>w.r</code> , <code><space>w.w</code> , <code><space>w<C-p></code> , <code><space>w<C-r></code> , <code><space>w<C-w></code> , <code><space>w<tab></code>
<code>rotate_view_reverse</code>	Goto previous window	normal: <code><C-w>R</code> , <code><C-w>W</code> , <code><C-w>.R</code> , <code><space>wR</code> , <code><space>wW</code> , <code><space>w.R</code> , select: <code><space>wR</code> , <code><space>wW</code> , <code><space>w.R</code>
<code>hsplit</code>	Horizontal bottom split	normal: <code><C-w>S</code> , <code><C-w>s</code> , <code><C-w>.S</code> , <code><C-w>.s</code> , <code><space>wS</code> , <code><space>ws</code> , <code><C-w><C-s></code> , <code><space>w.S</code> , <code><space>w.s</code> , <code><C-w>.<minus></code> , <code><space>w<C-s></code> , <code><space>w.<minus></code> , select: <code><space>wS</code> , <code><space>ws</code> , <code><space>w.S</code> , <code><space>w.s</code> , <code><space>w<C-s></code> , <code><space>w.<minus></code>

Name	Description	Default keybinds
hsplit_new	Horizontal bottom split scratch buffer	normal: <C-w>n, <space>Fn, <space>wn, <C-w><C-n>, <space>bNh, <space>bNj, <space>bNk, <space>bNl, <space>w<C-n>, select: <space>Fn, <space>wn, <space>bNh, <space>bNj, <space>bNk, <space>bNl, <space>w<C-n>
vsplit	Vertical right split	normal: <C-w>/, <C-w>2, <C-w>3, <C-w>4, <C-w>V, <C-w>v, <C-w>./, <C-w>.V, <C-w>.v, <space>w/, <space>w2, <space>w3, <space>w4, <space>wV, <space>wv, <C-w><C-v>, <space>w./, <space>w.V, <space>w.v, <space>w<C-v>, <space>u<space>w2, <space>u<space>w3, <space>u<space>w4, select: <space>w/, <space>w2, <space>w3, <space>w4, <space>wV, <space>wv, <space>w./, <space>w.V, <space>w.v, <space>w<C-v>, <space>u<space>w2, <space>u<space>w3, <space>u<space>w4
vsplit_new	Vertical right split scratch buffer	
wclose	Close window	normal: <C-w>D, <C-w>c, <C-w>d, <C-w>q, <C-w>.d, <space>cd, <space>wD, <space>wc, <space>wd, <space>wq, <C-w><C-d>, <C-w><C-q>, <space>w.d, <space>w<C-d>, <space>w<C-q>, <space>u<space>wd, select: <space>cd, <space>wD, <space>wc, <space>wd, <space>wq, <space>w.d, <space>w<C-d>, <space>w<C-q>, <space>u<space>wd
wonly	Close windows except current	normal: <C-w>1, <C-w>_, <C-w>m, <C-w>o, <C-w>.D, <C-w>._, <C-w>\ , <C-w>.\ , <space>w1, <space>w_, <space>wm, <space>wo, <C-w><C-o>, <space>w.D, <space>w._, <space>w\ , <space>w.\ , <space>w<C-o>, <space>u<space>w1, select: <space>w1, <space>w_, <space>wm, <space>wo, <space>w.D, <space>w._, <space>w\ , <space>w.\ , <space>w<C-o>, <space>u<space>w1
select_register	Select register	normal: "
insert_register	Insert register	insert: <C-r>
copy_between_registers	Copy between two registers	
align_view_middle	Align view middle	
align_view_top	Align view top	normal: zt

Name	Description	Default keybinds
<code>align_view_center</code>	Align view center	normal: <code>zz</code> , <code><[-l></code> , <code><[-w>.z</code> , <code><space>b.z</code> , <code><space>w.z</code> , select: <code><space>b.z</code> , <code><space>w.z</code>
<code>align_view_bottom</code>	Align view bottom	normal: <code>zb</code>
<code>scroll_up</code>	Scroll view up	normal: <code><[-y></code> , insert: <code><[-x><[-y></code>
<code>scroll_down</code>	Scroll view down	normal: <code><[-e></code> , insert: <code><[-x><[-e></code>
<code>scroll_column_left</code>	Scroll view left one column (zh)	normal: <code>zh</code> , <code>z<left></code>
<code>scroll_column_right</code>	Scroll view right one column (zl)	normal: <code>zl</code> , <code>z<right></code>
<code>scroll_half_column_left</code>	Scroll view left half a screen (zH)	normal: <code>zH</code> , <code>ze</code>
<code>scroll_half_column_right</code>	Scroll view right half a screen (zL)	normal: <code>zL</code> , <code>zs</code>
<code>resize_view_wider</code>	Make current window wider (CTRL-W >)	normal: <code><[-w>.</code>], <code><[-w><gt></code> , <code><space>w.</code>], <code><space>w<gt></code> , select: <code><space>w.</code>], <code><space>w<gt></code>
<code>resize_view_narrower</code>	Make current window narrower (CTRL-W <)	normal: <code><[-w>[</code> , <code><[-w>.</code> [, <code><[-w><lt></code> , <code><space>w[</code> , <code><space>w.</code> [, <code><space>w<lt></code> , select: <code><space>w[</code> , <code><space>w.</code> [, <code><space>w<lt></code>
<code>resize_view_taller</code>	Make current window taller (CTRL-W +)	normal: <code><[-w>+</code> , <code><[-w>.</code> } , <code><space>w+</code> , <code><space>w.</code> } , select: <code><space>w+</code> , <code><space>w.</code> }
<code>resize_view_shorter</code>	Make current window shorter (CTRL-W -)	normal: <code><[-w>{</code> , <code><[-w>.</code> { , <code><space>w{</code> , <code><space>w.</code> { , <code><[-w><minus></code> , <code><space>w<minus></code> , select: <code><space>w{</code> , <code><space>w.</code> { , <code><space>w<minus></code>
<code>resize_view_equalize</code>	Make all windows equal size (CTRL-W =)	normal: <code><[-w>=</code> , <code><space>w=</code> , select: <code><space>w=</code>
<code>rot13</code>	ROT13-encode the selection (g?)	
<code>url_encode</code>	Percent-encode (URL-encode) the selection	
<code>url_decode</code>	Percent-decode (URL-decode) the selection	
<code>parse_query_selection</code>	Expand a URL query string into decoded key=value lines	
<code>build_query_selection</code>	Build a URL query string from key=value lines	
<code>url_info_selection</code>	Break the selected URL into scheme/host/port/path/query lines	
<code>encode_base64</code>	Base64-encode the selection	
<code>decode_base64</code>	Base64-decode the selection	
<code>encode_base64url</code>	URL-safe base64-encode the selection (no padding)	
<code>decode_base64url</code>	URL-safe base64-decode the selection (JWT-friendly)	
<code>jwt_decode_selection</code>	Decode the selected JWT into pretty header + payload JSON	
<code>encode_html</code>	HTML-escape the selection (& < > " ')	
<code>decode_html</code>	Decode HTML entities in the selection	
<code>html_to_text_selection</code>	Strip HTML tags and decode entities to plain text	

Name	Description	Default keybinds
<code>title_case_selection</code>	Title-case the selection (capitalize each word)	
<code>sentence_case_selection</code>	Capitalize the first letter of each sentence in the selection	
<code>straighten_quotes_selection</code>	Convert smart quotes/dashes in the selection to plain ASCII	
<code>hex_to_rgb_selection</code>	Convert a #hex color in the selection to rgb(r, g, b)	
<code>rgb_to_hex_selection</code>	Convert an rgb(r, g, b) color in the selection to #hex	
<code>to_roman_selection</code>	Convert the selected integer to a Roman numeral	
<code>from_roman_selection</code>	Convert the selected Roman numeral to an integer	
<code>add_commas_selection</code>	Add thousands separators to numbers in the selection	
<code>strip_commas_selection</code>	Remove thousands separators from numbers in the selection	
<code>swap_quotes_selection</code>	Swap ' and " quote characters in the selection	
<code>strip_quotes_selection</code>	Remove surrounding quotes from the selection	
<code>reverse_words_selection</code>	Reverse the word order within each selected line	
<code>unwrap_tag_selection</code>	Strip the outermost ... wrapper from the selection	
<code>sort_paragraphs_selection</code>	Sort blank-line-separated paragraphs in the selection	
<code>lighten_selection</code>	Lighten the hex color in the selection by 10%	
<code>darken_selection</code>	Darken the hex color in the selection by 10%	
<code>contrast_text</code>	Recommend black/white text for the selected hex background color	
<code>toggle_value_selection</code>	Toggle the boolean/keyword in the selection (true<->false, ...)	
<code>normalize_whitespace_selection</code>	Collapse internal whitespace runs in the selection	
<code>insert_toc</code>	Insert a markdown table of contents from the buffer's headings	
<code>slugify_selection</code>	Slugify the selection (lowercase, hyphen-separated)	
<code>humanize_selection</code>	Humanize a slug/identifier into a Title-Cased label	
<code>transpose_csv_selection</code>	Transpose the selected CSV/TSV table (rows <-> columns)	
<code>csv_to_json_selection</code>	Convert the selected CSV/TSV to a JSON array of objects	
<code>regex_escape_selection</code>	Escape regex metacharacters in the selection	
<code>blockquote_selection</code>	Prefix each selected line with ">" (markdown blockquote)	
<code>unblockquote_selection</code>	Strip a leading ">" from each selected line	
<code>bullet_list_selection</code>	Make a markdown bullet list from the selected lines	
<code>unbullet_selection</code>	Strip a leading bullet (- * +) from each selected line	
<code>strip_ansi_selection</code>	Strip ANSI/VT escape codes from the selection	

Name	Description	Default keybinds
<code>html_escape_selection</code>	HTML-escape the selection (& < > " ' to entities)	
<code>html_unescape_selection</code>	HTML-unescape entities in the selection back to characters	
<code>reverse_chars_selection</code>	Reverse the characters in the selection	
<code>json_escape_selection</code>	JSON-escape the selection (for a string literal)	
<code>to_json_string_selection</code>	Wrap the selection in quotes as a JSON string literal	
<code>json_unescape_selection</code>	JSON-unescape the selection	
<code>to_hex_selection</code>	Encode the selection as hex bytes	
<code>from_hex_selection</code>	Decode hex bytes in the selection back to text	
<code>format_table_selection</code>	Align the selected markdown table's columns	
<code>csv_to_table_selection</code>	Convert the selected CSV/TSV to a markdown table	
<code>table_to_csv_selection</code>	Convert the selected markdown table to CSV	
<code>json_pretty_selection</code>	Pretty-print the selected JSON (preserves key order)	
<code>json_minify_selection</code>	Minify the selected JSON	
<code>xml_pretty_selection</code>	Pretty-print the selected XML/HTML	
<code>insert_digraph</code>	Insert a digraph by two-character mnemonic (CTRL-K)	insert: <[-k>
<code>insert_uuid_v4</code>	Insert a random UUIDv4 (SPC i U 4)	normal: <space>iU4, <space>iUU, select: <space>iU4, <space>iUU
<code>insert_uuid_v1</code>	Insert a time-based UUIDv1 (SPC i U 1)	normal: <space>iU1, select: <space>iU1
<code>insert_lorem_sentence</code>	Insert a lorem-ipsum sentence (SPC i l s)	normal: <space>ils, select: <space>ils
<code>insert_lorem_paragraph</code>	Insert a lorem-ipsum paragraph (SPC i l p)	normal: <space>ilp, select: <space>ilp
<code>insert_lorem_list</code>	Insert a lorem-ipsum list (SPC i l l)	normal: <space>ill, select: <space>ill
<code>insert_password_simple</code>	Insert a simple alphanumeric password (SPC i p 1)	normal: <space>ip1, select: <space>ip1
<code>insert_password_strong</code>	Insert a stronger password with symbols (SPC i p 2)	normal: <space>ip2, select: <space>ip2
<code>insert_password_paranoid</code>	Insert a long password for paranoids (SPC i p 3)	normal: <space>ip3, select: <space>ip3
<code>insert_password_numerical</code>	Insert a numeric password (SPC i p n)	normal: <space>ipn, select: <space>ipn
<code>insert_password_phonetic</code>	Insert a phonetically easy password (SPC i p p)	normal: <space>ipp, select: <space>ipp
<code>symbol_upper_camel</code>	Change symbol style to UpperCamelCase (SPC x i C)	normal: <space>xiC, select: <space>xiC
<code>symbol_up_case</code>	Change symbol style to UP_CASE (SPC x i U)	normal: <space>xiU, select: <space>xiU
<code>symbol_under_score</code>	Change symbol style to under_score (SPC x i _)	normal: <space>xi_, select: <space>xi_
<code>randomize_lines_in_region</code>	Randomize lines in the selection (SPC x l r)	normal: <space>xlr, select: <space>xlr
<code>randomize_words_in_region</code>	Randomize words in the selection (SPC x w r)	normal: <space>xwr, select: <space>xwr

Name	Description	Default keybinds
<code>copy_char_below</code>	Insert the character below the cursor (i_CTRL-E)	insert: <code><[-e></code>
<code>copy_char_above</code>	Insert the character above the cursor (i_CTRL-Y)	insert: <code><[-y></code>
<code>file_info</code>	Show file name and cursor position (CTRL-G)	normal: <code><[-g></code>
<code>document_stats</code>	Show document line/word/char counts (g_CTRL-G)	normal: <code>g<[-g></code> , select: <code>g<[-g></code>
<code>git_blame_line</code>	Show git blame for the current line (g_b)	normal: <code><space>gM</code> , <code><space>gb</code> , select: <code><space>gM</code> , <code><space>gb</code>
<code>git_branch_picker</code>	Pick a git branch and check it out	
<code>preferences</code>	Open the unified Preferences window	normal: <code><space></code> ,, select: <code><space></code> ,
<code>help</code>	Open the inline Help browser	normal: <code><space>bH</code> , <code><space>h?</code> , <code><space>hc</code> , <code><space>hh</code> , <code><space>hk</code> , select: <code><space>bH</code> , <code><space>h?</code> , <code><space>hc</code> , <code><space>hh</code> , <code><space>hk</code>
<code>dashboard</code>	Open the system-stats Dashboard (Preferences)	normal: <code><space>bh</code> , select: <code><space>bh</code>
<code>search_in_files</code>	Open the project-wide Find in Files panel	
<code>terminal</code>	Open an integrated terminal (PTY shell)	normal: <code><space>p'</code> , select: <code><space>p'</code>
<code>run_config_manager</code>	Manage run/debug configurations	normal: <code><space>Rc</code> , <code><space>Re</code> , <code><space>cm</code> , <code><space>pi</code> , select: <code><space>Rc</code> , <code><space>Re</code> , <code><space>cm</code> , <code><space>pi</code>
<code>run_active_config</code>	Run the active run configuration	normal: <code><F5></code> , <code><space>Rr</code> , <code><space>cC</code> , <code><space>pc</code> , <code><space>pu</code> , select: <code><space>Rr</code> , <code><space>cC</code> , <code><space>pc</code> , <code><space>pu</code>
<code>clear_run_output</code>	Clear the Run tool window output	normal: <code><space>Rl</code> , <code><space>Rx</code> , select: <code><space>Rl</code> , <code><space>Rx</code>
<code>rerun_last_run</code>	Re-run the last command in the Run console	normal: <code><space>RR</code> , <code><space>cr</code> , select: <code><space>RR</code> , <code><space>cr</code>
<code>run_next_error</code>	Jump to the next file:line in the run output	normal: <code><space>Rn</code> , select: <code><space>Rn</code>
<code>run_prev_error</code>	Jump to the previous file:line in the run output	normal: <code><space>Rp</code> , select: <code><space>Rp</code>
<code>reveal_in_tree</code>	Reveal the current file in the project tree	normal: <code><space>pV</code> , select: <code><space>pV</code>
<code>toggle_auto_reveal</code>	Toggle always-select-opened-file (autoscroll from source)	normal: <code><space>pV</code> , select: <code><space>pV</code>
<code>focus_file_tree</code>	Focus the project file tree panel	normal: <code><space>Wp</code> , <code><space>Wt</code> , select: <code><space>Wp</code> , <code><space>Wt</code>
<code>focus_structure</code>	Focus the structure/symbol outline panel	normal: <code><space>Wo</code> , <code><space>Ws</code> , select: <code><space>Wo</code> , <code><space>Ws</code>
<code>focus_problems</code>	Focus the problems/diagnostics panel	normal: <code><space>We</code> , select: <code><space>We</code>
<code>focus_run_console</code>	Focus the Run console (scroll output with j/k/PgUp/PgDn)	normal: <code><space>Wr</code> , select: <code><space>Wr</code>
<code>focus_git_panel</code>	Focus the Git changes panel (j/k select, Enter opens)	normal: <code><space>Wg</code> , <code><space>gG</code> , select: <code><space>Wg</code> , <code><space>gG</code>
<code>focus_ci_panel</code>	Focus the CI status panel (GitHub Actions runs; Enter opens in browser)	normal: <code><space>Wc</code> , select: <code><space>Wc</code>
<code>toggle_bottom_zoom</code>	Maximize / restore the bottom panel	normal: <code><space>Wm</code> , select: <code><space>Wm</code>
<code>toggle_drawer_mid</code>	Fold / unfold the middle column of the bottom drawer	normal: <code><space>Wf</code> , select: <code><space>Wf</code>

Name	Description	Default keybinds
<code>toggle_ide</code>	Toggle the IDE workbench (Zen / focus mode)	normal: <code><space>z</code> , select: <code><space>z</code>
<code>settings_page</code>	Open the settings page (config.toml editor)	normal: <code><space>S</code> , select: <code><space>S</code>
<code>goto_next_spell_error</code>	Move to the next misspelled word (Jj)	normal: <code>]s</code>
<code>goto_prev_spell_error</code>	Move to the previous misspelled word (Jj)	normal: <code>[s</code>
<code>spell_add_good</code>	Mark word under cursor as correctly spelled (zg)	normal: <code>zG</code> , <code>zg</code>
<code>spell_add_bad</code>	Mark word under cursor as misspelled (zw)	normal: <code>zW</code> , <code>zw</code>
<code>spell_undo</code>	Undo a zg/zw for the word under cursor (zug)	normal: <code>zuG</code> , <code>zuW</code> , <code>zug</code> , <code>zuw</code>
<code>spell_suggest</code>	Show spelling suggestions for the word under cursor (z=)	normal: <code>z=</code>
<code>fold_create</code>	Create a fold over the selection (zf)	
<code>fold_toggle</code>	Toggle fold under cursor (za)	normal: <code>zA</code> , <code>za</code> , <code>zi</code>
<code>fold_open</code>	Open fold under cursor (zo)	normal: <code>zO</code> , <code>zo</code> , <code>zv</code> , <code>zx</code>
<code>fold_close</code>	Close fold under cursor (zc)	normal: <code>zC</code> , <code>zc</code>
<code>fold_open_all</code>	Open all folds (zR)	normal: <code>zR</code> , <code>zX</code> , <code>zn</code> , <code>zr</code> , <code><space>nw</code> , select: <code><space>nw</code>
<code>fold_close_all</code>	Close all folds (zM)	normal: <code>zM</code> , <code>zN</code> , <code>zm</code>
<code>fold_delete</code>	Delete fold under cursor (zd)	normal: <code>zD</code> , <code>zd</code>
<code>fold_delete_all</code>	Delete all folds (zE)	normal: <code>zE</code>
<code>narrow_to_region</code>	Narrow the view to the selected region (SPC n r)	normal: <code><space>nr</code> , select: <code><space>nr</code>
<code>kmacro_add_counter</code>	Add [count] to the keyboard-macro counter (SPC K c a)	normal: <code><space>Kca</code> , select: <code><space>Kca</code>
<code>kmacro_insert_counter</code>	Insert the macro counter value, then increment (SPC K c c)	normal: <code><space>Kcc</code> , select: <code><space>Kcc</code>
<code>toggle_readonly</code>	Toggle the buffer's read-only (writable) state (SPC b w)	normal: <code><space>bw</code> , select: <code><space>bw</code>
<code>paredit_slurp_forward</code>	Paredit: slurp the next s-expression forward (SPC k s)	normal: <code><space>ks</code> , <code><space>k`s</code> , select: <code><space>ks</code> , <code><space>k`s</code>
<code>paredit_barf_forward</code>	Paredit: barf the last s-expression forward (SPC k b)	normal: <code><space>kb</code> , select: <code><space>kb</code>
<code>paredit_slurp_backward</code>	Paredit: slurp the previous s-expression backward (SPC k S)	normal: <code><space>kS</code> , select: <code><space>kS</code>
<code>paredit_barf_backward</code>	Paredit: barf the first s-expression backward (SPC k B)	normal: <code><space>kB</code> , select: <code><space>kB</code>
<code>paredit_splice</code>	Paredit: splice/unwrap the enclosing s-expression (SPC k W)	normal: <code><space>kW</code> , select: <code><space>kW</code>
<code>paredit_raise</code>	Paredit: raise the current s-expression (SPC k r)	normal: <code><space>kr</code> , select: <code><space>kr</code>
<code>paredit_transpose</code>	Paredit: transpose the s-expressions around point (SPC k t)	normal: <code><space>kt</code> , <code><space>k`p</code> , <code><space>k`t</code> , select: <code><space>kt</code> , <code><space>k`p</code> , <code><space>k`t</code>
<code>paredit_splice_kill_forward</code>	Paredit: splice, killing forward (SPC k e)	normal: <code><space>ke</code> , select: <code><space>ke</code>
<code>paredit_splice_kill_backward</code>	Paredit: splice, killing backward (SPC k E)	normal: <code><space>kE</code> , select: <code><space>kE</code>
<code>paredit_insert_sexp_after</code>	Paredit: insert a new () sexp after the current one (SPC k))	normal: <code><space>k)</code> , select: <code><space>k)</code>

Name	Description	Default keybinds
<code>paredit_insert_sexp_before</code>	Paredit: insert a new () sexp before the current one (SPC k ())	normal: <code><space>k()</code> , select: <code><space>k()</code>
<code>fold_next</code>	Move to next fold (zj)	normal: <code>]z, zj</code>
<code>fold_prev</code>	Move to previous fold (zk)	normal: <code>[z, zk</code>
<code>goto_line_last_nonblank</code>	Goto last non-blank on line (g_)	normal: <code>g_</code>
<code>goto_line_middle</code>	Goto middle of text line (gM)	normal: <code>gM, gm</code>
<code>goto_byte</code>	Goto byte {count} in buffer (go)	normal: <code>go</code>
<code>goto_prev_unmatched_paren</code>	Goto previous unmatched (([()	normal: <code>[(, <space>j()</code> , select: <code><space>j()</code>
<code>goto_prev_unmatched_brace</code>	Goto previous unmatched { ([{)	normal: <code>[{</code>
<code>goto_next_unmatched_paren</code>	Goto next unmatched) (])	normal: <code>])</code>
<code>goto_next_unmatched_brace</code>	Goto next unmatched } (])	normal: <code>] }</code>

Name	Description	Default keybinds
goto_prev_mark	Goto previous lowercase mark ([) normal: `` [     `goto_next_mark`   Goto next lowercase mark (])   normal: ]`` goto_prev_mark_line Goto previous lowercase mark, line start ([']) normal: `` [' `` goto_next_mark_line Goto next lowercase mark, line start (']) normal: `` ]' `` yank_file_path Yank current file path to clipboard normal: `` <space>fyC `` , `` <space>fyY `` , `` <space>fyy `` , select: `` <space>fyC `` , `` <space>fyY `` , `` <space>fyy `` yank_file_name Yank current file name to clipboard normal: `` <space>fyN `` , `` <space>fyn `` , select: `` <space>fyN `` , `` <space>fyn `` yank_file_path_with_line Yank current file path:line to clipboard normal: `` <space>fyl `` , `` <space>fyl `` , select: `` <space>fyl `` , `` <space>fyl `` yank_file_path_with_line_col Yank current file path:line:col to clipboard normal: `` <space>fyc `` , select: `` <space>fyc `` yank_file_dir Yank current file's directory to clipboard normal: `` <space>fyD `` , `` <space>fyd `` , select: `` <space>fyD `` , `` <space>fyd `` copy_remote_url Copy web permalink (host/blob/<sha>/path#Ln) for current line normal: `` <space>glC `` , `` <space>gll `` , `` <space>glP `` , select: `` <space>glC `` , `` <space>gll `` , `` <space>glP `` open_remote_url Open current line's web permalink in the browser normal: `` <space>glc `` , `` <space>gll `` , `` <space>glp `` , select: `` <space>glc `` , `` <space>gll `` , `` <space>glp `` open_url_under_cursor Open the URL under the cursor in the browser duplicate_selection_down Duplicate current line(s) downward duplicate_selection_up Duplicate current line(s) upward move_text_line_down Move current line(s)⁶⁵ down past the next line move_text_line_up Move current	normal: `, g`

Name	Description	Default keybinds
<code>goto_mark_line</code>	Goto mark line ('{a-z})	normal: <code>' , g</code>
<code>repeat_substitute</code>	Repeat last :substitute (&)	normal: <code>fr</code>
<code>repeat_substitute_global</code>	Repeat last :substitute on whole file (g&)	normal: <code>gr</code>
<code>vim_record_macro</code>	Record macro into register (q{reg})	normal: <code>q</code>
<code>vim_replay_macro</code>	Replay macro from register (@reg)	normal: <code>@</code>
<code>save_visual_selection</code>	Save the visual selection (for gv)	
<code>reselect_visual</code>	Reselect the last visual area (gv)	normal: <code>gv</code> , select: <code>gv</code>
<code>mark_insert_exit</code>	Record the insert-exit position (for gi)	
<code>insert_at_last_insert</code>	Insert at the last insert position (gi)	normal: <code>gi</code>
<code>goto_next_function</code>	Goto next function	normal: <code>][,]m</code>
<code>goto_prev_function</code>	Goto previous function	normal: <code>[] , [m</code>
<code>goto_next_class</code>	Goto next type definition	
<code>goto_prev_class</code>	Goto previous type definition	
<code>goto_next_parameter</code>	Goto next parameter	
<code>goto_prev_parameter</code>	Goto previous parameter	
<code>goto_next_comment</code>	Goto next comment	normal: <code>] * ,]/</code>
<code>goto_prev_comment</code>	Goto previous comment	normal: <code>[* , [/</code>
<code>goto_next_test</code>	Goto next test	normal: <code><space>pa</code> , select: <code><space>pa</code>
<code>goto_prev_test</code>	Goto previous test	
<code>goto_next_xml_element</code>	Goto next (X)HTML element	
<code>goto_prev_xml_element</code>	Goto previous (X)HTML element	
<code>goto_next_entry</code>	Goto next pairing	
<code>goto_prev_entry</code>	Goto previous pairing	
<code>goto_next_paragraph</code>	Goto next paragraph	normal: <code>} ,]]</code> , select: <code>}</code>
<code>goto_prev_paragraph</code>	Goto previous paragraph	normal: <code>{ , [[</code> , select: <code>{</code>
<code>move_sentence_forward</code>	Move to next sentence	normal: <code>)</code> , select: <code>)</code>
<code>move_sentence_backward</code>	Move to previous sentence	normal: <code>(</code> , select: <code>(</code>
<code>dap_launch</code>	Launch debug target	normal: <code><S-F5></code> , <code><space>dd</code> , select: <code><space>dd</code>
<code>dap_restart</code>	Restart debugging session	normal: <code><space>dr</code> , select: <code><space>dr</code>
<code>dap_toggle_breakpoint</code>	Toggle breakpoint	normal: <code><F9></code> , <code><space>db</code> , select: <code><space>db</code>
<code>dap_continue</code>	Continue program execution	normal: <code><space>dc</code> , select: <code><space>dc</code>
<code>dap_pause</code>	Pause program execution	normal: <code><space>dp</code> , select: <code><space>dp</code>
<code>dap_step_in</code>	Step in	normal: <code><F11></code> , <code><space>di</code> , select: <code><space>di</code>

Name	Description	Default keybinds
dap_step_out	Step out	normal: <S-F11>, <space>do, select: <space>do
dap_next	Step to next	normal: <F10>, <space>dn, select: <space>dn
dap_variables	List variables	normal: <space>dv, select: <space>dv
dap_terminate	End debug session	normal: <space>dq, select: <space>dq
dap_edit_condition	Edit breakpoint condition on current line	
dap_edit_log	Edit breakpoint log message on current line	
dap_switch_thread	Switch current thread	
dap_switch_stack_frame	Switch stack frame	
dap_enable_exceptions	Enable exception breakpoints	
dap_disable_exceptions	Disable exception breakpoints	
shell_pipe	Pipe selections through shell command	
shell_pipe_to	Pipe selections into shell command ignoring output	
shell_insert_output	Insert shell command output before selections	
shell_append_output	Append shell command output after selections	
shell_keep_pipe	Filter selections with shell predicate	
suspend	Suspend and return to shell	normal: <[-z>
rename_symbol	Rename symbol	normal: <space>lr, select: <space>lr
increment	Increment item under cursor	normal: <[-a>, <space>n+, <space>n=, select: <[-a>, g<[-a>, <space>n+, <space>n=
decrement	Decrement item under cursor	normal: <[-x>, <space>n_, <space>n<minus>, select: <[-x>, g<[-x>, <space>n_, <space>n<minus>
record_macro	Record macro	
replay_macro	Replay macro	normal: Q

Name	Description	Default keybinds
<code>command_palette</code>	Open command palette	normal: <F1>, <A-x>, <space>?, <space>eh, <space>ev, <space>h., <space>hf, <space>hi, <space>hl, <space>hm, <space>hn, <space>hp, <space>hr, <space>hdb, <space>hdf, <space>hdk, <space>hdl, <space>hdm, <space>hdp, <space>hds, <space>hdt, <space>hdv, <space>hdx, <space><space>, <space>h<space>, select: <space>?, <space>eh, <space>ev, <space>h., <space>hf, <space>hi, <space>hl, <space>hm, <space>hn, <space>hp, <space>hr, <space>hdb, <space>hdf, <space>hdk, <space>hdl, <space>hdm, <space>hdp, <space>hds, <space>hdt, <space>hdv, <space>hdx, <space><space>, <space>h<space>
<code>repl</code>	Open the embedded-language REPL (elisp/viml/stryke/awk/zsh)	normal: <space>ar, select: <space>ar
<code>goto_word</code>	Jump to a two-character label	normal: <space>jl, <space>jw, select: <space>jl, <space>jw
<code>extend_to_word</code>	Extend to a two-character label	
<code>goto_next_tabstop</code>	Goto next snippet placeholder	
<code>goto_prev_tabstop</code>	Goto next snippet placeholder	
<code>emmet_expand</code>	Expand emmet/zen HTML abbreviation (or Tab)	insert: <tab>
<code>snippet_expand</code>	Expand the user snippet whose trigger precedes the cursor	
<code>rotate_selections_first</code>	Make the first selection your primary one	
<code>rotate_selections_last</code>	Make the last selection your primary one	

Language Support

Language	Syntax Highlighting	Treesitter Textobjects	Auto Indent	Code Navigation Tags	Rainbow Brackets	Default language servers
ada	✓	✓				ada_language_server
adl	✓	✓	✓			
agda	✓					
alloy	✓					
amber	✓	✓	✓	✓	✓	amber-lsp
astro	✓					astro-ls
awk	✓	✓				awk-language-server
bash	✓	✓	✓	✓	✓	bash-language-server
basic	✓	✓	✓	✓		
bass	✓					bass
beancount	✓					beancount-language-server
bibtex	✓					texlab
bicep	✓					bicep-langserver
bitbake	✓					bitbake-language-server
blade	✓	✓			✓	
blueprint	✓					blueprint-compiler
bovex						
c	✓	✓	✓	✓	✓	clangd
c-sharp	✓	✓	✓	✓	✓	roslyn-language-server, OmniSharp, csharp-ls
c3	✓					c3-lsp

Language	Syntax Highlighting	Treesitter Textobjects	Auto Indent	Code Navigation Tags	Rainbow Brackets	Default language servers
cabal						haskell-language-server-wrapper
caddyfile	✓	✓	✓			
cairo	✓	✓	✓			cairo-language-server
capnp	✓		✓			
cel	✓					
chuck	✓					
circom	✓					circom-lsp
clarity	✓					clarinet
clojure	✓	✓	✓	✓	✓	clojure-lsp
cmake	✓	✓	✓		✓	neomake-lsp , cmake-language-server
codeql	✓	✓				codeql
comment	✓					
common-lisp	✓	✓		✓	✓	cl-lsp
concerto	✓	✓	✓			
cpon	✓		✓			
cpp	✓	✓	✓	✓	✓	clangd
cross-config	✓	✓			✓	taplo , tombi
crystal	✓	✓	✓	✓	✓	crystalline , ameba-ls
css	✓	✓	✓		✓	vscode-css-language-server
csv	✓					
cue	✓					cue
cylc	✓	✓	✓			
cython	✓		✓	✓		
d	✓	✓	✓			serve-d
dart	✓	✓	✓	✓	✓	dart
dbml	✓					
debian	✓					debian-lsp
devicetree	✓					dts-lsp
dhall	✓	✓				dhall-lsp-server
diff	✓					
djot	✓					

Language	Syntax Highlighting	Treesitter Textobjects	Auto Indent	Code Navigation Tags	Rainbow Brackets	Default language servers
docker-bake	✓	✓	✓	✓	✓	docker-language-server
docker-compose	✓	✓	✓			docker-compose-langserver , yaml-language-server , docker-language-server
dockerfile	✓	✓				docker-langserver , docker-language-server
dot	✓					dot-language-server
doxyfile drools	✓	✓	✓	✓		drools-lsp
dtd	✓					
dune	✓					
dunstrc	✓					
earthfile	✓	✓	✓			earthlyls
ebnf	✓					ebnfer
edoc	✓					
eex	✓					
eiffel	✓	✓	✓			eiffel-language-server
ejs	✓					
elisp	✓			✓		
elixir	✓	✓	✓	✓	✓	elixir-ls , expert
elm	✓	✓		✓	✓	elm-language-server
elvish	✓					elvish
embedded-perl	✓					
env	✓	✓				
erb	✓					
erlang	✓	✓	✓	✓	✓	erlang_ls , elp
esdl	✓					
fennel	✓				✓	fennel-ls
fga	✓	✓	✓			

Language	Syntax Highlighting	Treesitter Textobjects	Auto Indent	Code Navigation Tags	Rainbow Brackets	Default language servers
fidl	✓					
fish	✓	✓	✓			fish-lsp
flatbuffers	✓					
forth	✓					forth-lsp
fortran	✓		✓			fortls
freebasic	✓	✓	✓	✓		
fsharp	✓				✓	fsautocomplete
gas	✓	✓				asm-lsp
gdscrip	✓	✓	✓	✓	✓	
gemin	✓					
gherkin	✓					
ghostty	✓					
git-attributes	✓					
git-cliff-config	✓	✓			✓	taplo, tombi
git-commit	✓	✓				commit-lsp
git-config	✓	✓		✓		
git-ignore	✓					
git-notes	✓					
git-rebase	✓					
github-action	✓	✓	✓		✓	actions-language-server, yamllanguage-server, zizmor
gitlab-ci	✓	✓	✓	✓	✓	yamllanguage-server, gitlab-ci-ls
gjs	✓	✓	✓	✓		typescript-language-server, vscode-eslint-language-server, ember-language-server
gleam	✓	✓			✓	gleam
glimmer	✓					ember-language-server
gls	✓	✓	✓	✓	✓	gls_analyzer, glsld
gn	✓					

Language	Syntax Highlighting	Treesitter Textobjects	Auto Indent	Code Navigation Tags	Rainbow Brackets	Default language servers
gnuplot	✓					
go	✓	✓	✓	✓	✓	gopls, golangci-lint- langserver
go-format-string	✓				✓	
godot-resource	✓	✓		✓		
gomod	✓					
gotmpl	✓					gopls
gowork	✓					gopls
gpr	✓					gopls
						ada_ language_ server
graphql	✓	✓			✓	graphql-lsp
gren	✓	✓				
groovy	✓				✓	
gts	✓	✓	✓	✓		typescript- language- server, vscode- eslint- language- server, ember- language- server
hare	✓	✓				hare-lsp
haskell	✓	✓		✓	✓	haskell- language- server- wrapper
haskell-literate	✓					haskell- language- server- wrapper
haskell-persistent	✓					
haxe	✓			✓		
hcl	✓	✓	✓		✓	terraform- ls
hdl	✓					hdl
heex	✓	✓				elixir-ls, expert
helm	✓					helm_ls
hocon	✓	✓	✓			
hoon	✓					
hosts	✓					

Language	Syntax Highlighting	Treesitter Textobjects	Auto Indent	Code Navigation Tags	Rainbow Brackets	Default language servers
html	✓	✓	✓		✓	vscode-html-language-server , superhtml
htmldjango	✓					djllsp , vscode-html-language-server , superhtml
hurl	✓	✓	✓			
hy	✓					hyuga
hyprrlang	✓		✓	✓		hyprrls
idris						idris2-lsp
iex	✓					
ini	✓			✓		
ink	✓					
inko	✓	✓	✓	✓		
janet	✓		✓		✓	
java	✓	✓	✓	✓	✓	
javascript	✓	✓	✓	✓	✓	jdtls
						typescript-language-server
jinja	✓					
jjconfig	✓	✓	✓			taplo , tombi
jjdescription	✓					
jjrevset	✓					
jjtemplate	✓					
jq	✓	✓				jq-lsp
jsdoc	✓					
json	✓	✓	✓		✓	vscode-json-language-server
json-ld	✓	✓	✓		✓	vscode-json-language-server
json5	✓	✓	✓		✓	
jsonc	✓	✓	✓		✓	vscode-json-language-server
jsonnet	✓					jsonnet-language-server

Language	Syntax Highlighting	Treesitter Textobjects	Auto Indent	Code Navigation Tags	Rainbow Brackets	Default language servers
jsx	✓	✓	✓	✓	✓	typescript-language-server
julia	✓	✓	✓	✓	✓	julia
just	✓	✓	✓	✓		just-lsp
kcl	✓					kcl-language-server
kconfig	✓		✓			
kdl	✓	✓	✓	✓	✓	
klog	✓					
koka	✓		✓			koka
kotlin	✓	✓	✓	✓	✓	kotlin-language-server
koto	✓	✓	✓		✓	koto-ls
latex	✓	✓	✓			texlab
ld	✓		✓			
ldif	✓					
lean	✓					lake
ledger	✓					
less	✓		✓		✓	vscode-css-language-server
llvm	✓	✓	✓			
llvm-mir	✓	✓	✓			
llvm-mir-yaml	✓		✓			
log						
lpf	✓					
lua	✓	✓	✓	✓	✓	lua-language-server
lua-format-string	✓					
luap	✓					
luau	✓	✓	✓			luau-lsp
mail	✓	✓			✓	
make	✓		✓			
markdoc	✓					markdoc-ls
markdown	✓			✓		marksman , markdown-oxide , rumdl
markdown-rustdoc	✓					
markdown.inline	✓					
matlab	✓	✓	✓			
mermaid	✓					

Language	Syntax Highlighting	Treesitter Textobjects	Auto Indent	Code Navigation Tags	Rainbow Brackets	Default language servers
meson	✓		✓			mesonlsp
mint						mint
miseconfig	✓	✓	✓			taplo, tombi
mojo	✓	✓	✓			pixi
move	✓		✓			
msbuild	✓		✓			
nasm	✓	✓				asm-lsp
nearley	✓				✓	
nestedtext	✓	✓	✓			
nginx	✓					
nickel	✓		✓			nls
nim	✓	✓	✓		✓	nimlangserver
nix	✓	✓	✓	✓	✓	nil, nixd
nu	✓	✓	✓			nu, nu-lint
nunjucks	✓					
ocaml	✓	✓	✓		✓	ocaml lsp
ocaml-interface	✓					ocaml lsp
odin	✓	✓	✓			ols
ohm	✓	✓	✓			
opencl	✓	✓	✓			clangd
openscad	✓					openscad-lsp
org	✓					
pascal	✓	✓				pasls
passwd	✓					
pem	✓					
penrose	✓	✓				
perl	✓	✓	✓	✓	✓	perlnavigator
pest	✓	✓	✓			pest-language-server
php	✓	✓	✓	✓	✓	intelephense
php-only	✓			✓		
picat	✓	✓	✓	✓	✓	
pip-requirements	✓					
pkgbuild	✓	✓	✓			termux-language-server, bash-language-server
pkl	✓		✓			pkl-lsp

Language	Syntax Highlighting	Treesitter Textobjects	Auto Indent	Code Navigation Tags	Rainbow Brackets	Default language servers
po	✓	✓				
pod	✓					
ponylang	✓	✓	✓			pony-lsp
powershell	✓				✓	
prisma	✓	✓				prisma-language-server
prolog	✓		✓			swipl
properties	✓	✓				
protobuf	✓	✓	✓	✓		buf, pb, protols
proverif	✓					
prql	✓					
ptx	✓		✓			
pug	✓					
purescript	✓	✓				purescript-language-server
python	✓	✓	✓	✓	✓	ty, ruff, jedi-language-server, pylsp, zuban
qml	✓	✓	✓			qmls
qmv						
quarto	✓		✓			
quint	✓					quint-language-server
r	✓	✓	✓	✓	✓	R
racket	✓		✓		✓	racket
regex	✓				✓	
rego	✓					regols
rescript	✓	✓				rescript-language-server
ripple	✓			✓	✓	ripple-language-server
rmarkdown	✓		✓			R
robot	✓		✓			robotcode, robotframework_ls
robots.txt	✓	✓		✓		
ron	✓		✓	✓	✓	ron-lsp
rpmspec	✓					

Language	Syntax Highlighting	Treesitter Textobjects	Auto Indent	Code Navigation Tags	Rainbow Brackets	Default language servers
rshtml	✓	✓				rshtml-analyzer, vscode-html-language-server, superhtml
rst	✓			✓		
ruby	✓	✓	✓	✓	✓	ruby-lsp, solargraph
rust	✓	✓	✓	✓	✓	rust-analyzer
rust-format-args	✓					
rust-format-args-macro	✓	✓	✓		✓	
sage	✓	✓				
scala	✓	✓	✓	✓	✓	metals
scfg	✓					
scheme	✓	✓	✓	✓	✓	
scss	✓		✓		✓	vscode-css-language-server
shellcheckrc	✓	✓				
slang	✓	✓	✓			slangd
slint	✓	✓	✓			slint-lsp
slisp	✓			✓		
smali	✓		✓			smalisp
smithy	✓					cs
sml	✓					
snakemake	✓		✓			pylsp
solidity	✓	✓			✓	solc
sourcepawn	✓	✓				sourcepawn-studio
spade	✓		✓		✓	swim
spicedb	✓			✓		
sql	✓	✓			✓	
ssh_client_config	✓					
starlark	✓	✓	✓		✓	starpls, buck2
strace	✓					
strictdoc	✓			✓		
styx	✓	✓	✓		✓	styx
supercollider	✓					
svelte	✓	✓	✓	✓	✓	svelte-server

Language	Syntax Highlighting	Treesitter Textobjects	Auto Indent	Code Navigation Tags	Rainbow Brackets	Default language servers
sway	✓	✓	✓			<code>forc</code>
swift	✓	✓	✓	✓	✓	<code>sourcekit-lsp</code>
systemd	✓			✓		<code>systemd-lsp</code>
systemverilog	✓					<code>svlangserver,</code> <code>verible-verilog-ls</code>
t32	✓					
tablegen	✓	✓	✓			
tact	✓	✓	✓			
task	✓					
tcl	✓		✓			
teal	✓					<code>teal-language-server</code>
templ	✓					<code>templ</code>
tera	✓					
textproto	✓	✓	✓			
tfvars	✓		✓			<code>terraform-ls</code>
thrift	✓					
tilt	✓	✓	✓		✓	<code>tilt</code>
tlaplus	✓					
todotxt	✓					
tolk	✓		✓			
toml	✓	✓	✓	✓	✓	<code>taplo, tombi</code>
tql	✓		✓			
tsq	✓				✓	<code>ts_query_ls</code>
tsx	✓	✓	✓	✓	✓	<code>typescript-language-server</code>
twig	✓					
typescript	✓	✓	✓	✓	✓	<code>typescript-language-server</code>
typespec	✓	✓	✓			<code>tsp-server</code>
typst	✓	✓		✓		<code>tinymist</code>
ungrammar	✓					
unison	✓	✓	✓	✓	✓	
uxntal	✓					
v	✓	✓	✓			<code>v-analyzer</code>
vala	✓	✓				<code>vala-language-server</code>
vento	✓					

Language	Syntax Highlighting	Treesitter Textobjects	Auto Indent	Code Navigation Tags	Rainbow Brackets	Default language servers
verilog	✓	✓				verible-verilog-ls
vhdl	✓					vhdl_ls
vhs	✓					
vim	✓				✓	
vue	✓	✓	✓			vue-language-server
wast	✓					
wat	✓					wat_server
webc	✓					
werk	✓					
wesl	✓	✓				
wgsl	✓	✓	✓	✓	✓	wgsl-analyzer
wikitext	✓					wikitext-lsp
wit	✓		✓			
woodpecker-ci	✓	✓	✓	✓	✓	yaml-language-server
wren	✓	✓	✓			
xit	✓					
xml	✓	✓	✓		✓	
xtc	✓					
yaml	✓	✓	✓		✓	yaml-language-server, ansible-language-server
yara	✓					yls
yuck	✓		✓		✓	
zig	✓	✓	✓	✓	✓	zls