

# Sprint 1

## Dynamic Price Calculation



























































































with companyId, vehicleTypes, maxPassengers,  
enabled pricing rules, ordered by precedence, using  
distance and duration based pricing

Fake Data

# Faker

Random data is inserted in the database using data fixtures

```
1  [⊕] User: ...
9
10 [⊕] Company: ...
13
14 Product:
15   product{1..10}:
16   [⊕]   maxPassengers: "..."
20       type: "{{random.arrayElement([
21         \"saloon\",
22         \"estate\",
23         \"bus\",
24         \"minivan\",
25         \"limo\"
26       ])}}"
27       name: "{{commerce.productMaterial}} {{commerce.color}} car"
28
29       imagePath: "https://goo.gl/TA829X"
30       companyId: "@{company}"
31
32 PricingRule:
33   pricingRule{1..10}:
34     name: "{{commerce.productName}} Vehicle"
35     isEnabled: "{{random.boolean}}"
36     type: "{{random.arrayElement([
37       \"dynamic\",
38       \"fixed\"
39     ])}}"
40     precedence: "{{random.number}}"
41     companyId: "@{company}"
42
43 ProductPricing:
44   productPricing{1..100}:
45     isEnabled: "{{random.boolean}}"
46     minuteWaitingPrice: "0.25"
47     fixedPrice: "0"
48     dynamicStartPrice: "3.00"
49     dynamicMinimumPrice: "5.00"
50     dynamicMinutePrice: "0.32"
51     dynamicDistancePrice: "2.22"
52     pricingRuleId: "@{pricingRule.*}"
53     productId: "@{product.*}"
```

_id	name	maxPassengers	type	imagePath	companyId
 5aa00f3ddd433...	 Saloon	 3	 limo	 https://goo.gl/TA...	 5aa00f3ddd4337...
 5aa00f3ddd433...	 Estate	 4	 estate	 https://goo.gl/TA...	 5aa00f3ddd4337...
 5aa00f3ddd433...	 Bus	 6	 bus	 https://goo.gl/TA...	 5aa00f3ddd4337...
 5aa00f3ddd433...	 Minivan	 6	 minivan	 https://goo.gl/TA...	 5aa00f3ddd4337...
 5aa00f3ddd433...	 Limo	 20	 limo	 https://goo.gl/TA...	 5aa00f3ddd4337...
 5aa00f3ddd433...	 Granite purple car	 9	 limo	 https://goo.gl/TA...	 5aa00f3ddd4337...
 5aa00f3ddd433...	 Soft orange car	 1	 minivan	 https://goo.gl/TA...	 5aa00f3ddd4337...
 5aa00f3ddd433...	 Frozen violet car	 2	 saloon	 https://goo.gl/TA...	 5aa00f3ddd4337...
 5aa00f3ddd433...	 Plastic orchid car	 8	 minivan	 https://goo.gl/TA...	 5aa00f3ddd4337...
 5aa00f3ddd433...	 Plastic cyan car	 7	 limo	 https://goo.gl/TA...	 5aa00f3ddd4337...
 5aa00f3ddd433...	 Steel turquoise car	 10	 estate	 https://goo.gl/TA...	 5aa00f3ddd4337...
 5aa00f3ddd433...	 Soft azure car	 9	 estate	 https://goo.gl/TA...	 5aa00f3ddd4337...
 5aa00f3ddd433...	 Rubber silver car	 6	 estate	 https://goo.gl/TA...	 5aa00f3ddd4337...
 5aa00f3ddd433...	 Steel fuchsia car	 5	 bus	 https://goo.gl/TA...	 5aa00f3ddd4337...
 5aa00f3ddd433...	 Concrete white car	 3	 bus	 https://goo.gl/TA...	 5aa00f3ddd4337...

# Price Calculation

# Step 1 - PassengerApp sends request to TPS

The following slides show the process of sending the request to our TPS service, and the way that our server processes the request before returning a response with a price calculation for each requested vehicleType.

# Request

As the documentation of the old system suggests, the query format in the yellow box is expected, and used as an example.

Source:

<https://docs.dispatchapi.io/#get-prices-per-vehicle-type>

**Price** Show/Hide List Operations Expand Operations

**POST** /Prices/calculate Get Prices for route, for the multiple company's

**Response Class (Status 200)**  
Request was successful

**Model** Example Value

**Inline Model {}**

Response Content Type application/json

**Parameters**

Parameter	Value	Description	Parameter Type	Data Type
data	<pre>{   "companyId":     "5aa00f3ddd433723c832b566",   "vehicleTypes": "[\"limo\"]",   "checkAvailability": false,   "passengerCount": 2,   "requestedDate": "2017-18-01T12:30:00Z",   "departure": {     "city": "string",     "streetName": "string",     "postalCode": "string",     "houseNumber": "string",     "synonym": "string",     "internationalAlias": "string",     "gps": {       "lat": "52.373805",       "lng": "4.896701"     },     "gpsSpeed": 0,     "gpsBearing": 0,     "gpsAccuracy": 0,     "gpsTime": "2018-03-07T08:25:55.955Z",     "gpsOrigin": "string",   } }</pre>	Data required to calculate the price for a trip.	body	<b>Model</b> <span>Example Value</span> <pre>{   "companyId": "5a9e681228e140ae6d91668",   "vehicleTypes": "[\"saloon\", \"estate\", \"bus\"]",   "checkAvailability": false,   "passengerCount": 1,   "requestedDate": "2017-18-01T12:30:00Z",   "departure": {     "city": "string",     "streetName": "string",     "postalCode": "string",     "houseNumber": "string",   } }</pre>

```
{  
  companyId:  
  vehicleTypes:  
  passengerCount:  
  departure: {  
    gps: {  
      lat:  
      lng:  
    }  
  destination: {  
    gps: {  
      lat:  
      lng:  
    }  
  }  
}
```

# Data

The values on the left side of this slide are the only values that are being used currently.



## Step 2 - Obtaining ride distance and duration

The distance and duration of a trip are provided by the google directions API.

The next slide shows the request parameters sent to google directions API, and the desired response attributes.

# Request

Fields used in google directions:

1. departure (gps: lat, lng)
2. destination (gps: lat, lng)

# Response

Returned by google:

1. distance (in m)
2. duration (in s)

## Step 3 - Querying our database for matches

While location matching is not part of the system yet, we could theoretically pass all the information we have at this moment to our database query to get the best possible match while ignoring the locations and timeframes for now.

The query is performed for every vehicle type that the user wants to see, and returns exactly one best result for each.

The next slide shows the request that would be sent by the Passenger App to our TPS microservice.

# Query

Fields used in query:

1. companyId
2. vehicleTypes
3. passengerCount

Fields not used yet:

4. departure
5. destination
6. pickupTime

```
const aggregateQuery = () => {
  Product.dataSource.connector.db.collection("Product")
    .aggregate([
      {
        $match: {
          // for a given company
          companyId: ObjectId(body.companyId),
          // vehicles requested must match the product vehicle type
          type: { $in: JSON.parse(body.vehicleTypes) },
          // maxPassengers is bigger or equal to passengerCount
          maxPassengers: { $gte: body.passengerCount }
        }
      },
      {
        $lookup: {
          from: "ProductPricing",
          localField: "_id",
          foreignField: "productId",
          as: "productPricings"
        }
      },
      {
        $unwind: {
          path: "$productPricings",
          preserveNullAndEmptyArrays: false
        }
      },
      {
        $match: {
          // product for given rule is enabled
          "productPricings.isEnabled": true
        }
      },
      {
        $lookup: {
          from: "PricingRule",
          localField: "productPricings.pricingRuleId",
          foreignField: "_id",
          as: "pricingRules"
        }
      },
      {
        $unwind: {
          path: "$pricingRules",
          preserveNullAndEmptyArrays: true
        }
      },
      {
        $match: {
          // rule is enabled
          "pricingRules.isEnabled": true
        }
      },
      {
        $sort: {
          "pricingRules.precedence": -1,
          // should be -1 later, because fixed should go first
          "pricingRules.type": 1
        }
      },
      {
        $limit: 1
      }
    ])
    .toArray((err, data) => {
```

## Step 4 - Calculating the prices

After the query to the database has been made, the most complex work is done to calculate prices based on different rules provided and stored in our database by the group admins.

A group admin can choose whether he would like the price to be calculated using tiers. He can flip a switch after he's defined the thresholds and tier prices for every one of his products.

# Price formula

total =

metric \* metricPrice

or if tier pricing

each(threshold \* thresholdPrice)

final = max(  
total + startAmount,  
minAmount  
)

total: km \* kmPrice

or

km - thresholds \* kmPrice  
+ (threshold \* tierPrice)

Final: the price that is finally returned

E.g. \$0.5 dollar per km for the first 10 km, plus \$0.4 \* the next 10 km, plus \$0.35 for the rest 2.54 km.

total = 5 + 4 + 0.889

final = max(9.89 + 3, 5)

final = 9.89

(this example only used distance metric)

## Step 5 - Sending back the response

When all the prices have been calculated (for each vehicle type), the response is sent back to the PassengerApp.

# Response

each vehicle  
type has none  
or one result

```
[  
  {  
    "vehicleType": "saloon",  
    "maxPassengers": 8,  
    "fixedPrice": true,  
    "price": {  
      "currency": "EUR",  
      "total": 1165,  
      "breakdown": {  
        "route": 1099,  
        "tax": 66,  
        "toll": 0,  
        "parking": 0,  
        "waiting": 0,  
        "discount": 0  
      }  
    }  
  },  
  {  
    "vehicleType": "limo",  
    "maxPassengers": 5,  
    "fixedPrice": true,  
    "price": {  
      "currency": "EUR",  
      "total": 1165,  
      "breakdown": {  
        "route": 1099,  
        "tax": 66,  
        "toll": 0,  
        "parking": 0,  
        "waiting": 0,  
        "discount": 0  
      }  
    }  
  }  
],
```



# Project Structure

- .vscode
- common
- config
- coverage
- fixtures
- node\_modules
- server
- src
- test
- ⚙ .editorconfig
- ⚙ .env
- ≡ .env.example
- 💎 .gitignore
- {} .yo-rc.json
- {} deploy.json
- 🖼 icon.png
- {} package.json
- 📘 README.md
- {} tsconfig.json
- {} tslint.json

# File Structure

common	Loopback models & schemas
config	Loopback config files
coverage	Test reporting
fixtures	Data fixtures for generating test data in db
server	Loopback server files
src	Typescript project
test	Typescript tests
.editorconfig .env .tsconfig .tslint	Space, tabs, line-ending styles Environmental variables Typescript settings Typescript linting

Tests

# Tests: output

## 1. UNIT:

Aims to test small units of code.

## 2. INTEGRATION:

Tests whether different parts of the system work together.

## 3. Note:

Current tests assume that the environment in which it resides is operational. For example: a google directions api key is set, the system is connected to the network, et cetera.

These tests may be removed when it stands in the way of CI.

```
stefan@DESKTOP-M590E8U:/mnt/c/Projects/pricing-api$ yarn test
yarn run v1.5.1
$ tslint --fix src/**/*.ts{x} --config tslint.json --project tsconfig.json
$ yarn run test:coverage
$ TS_NODE_COMPILER_OPTIONS='{ "target": "es6" }' nyc --reporter=lcov yarn run test:unit
$ mocha -r ts-node/register "./test/**/*.spec.ts" --exit
```

```
INTEGRATION: The .env file and environmental variables
  ✓ should load without throwing an error
```

```
INTEGRATION: Server response status
  ✓ returns 200 on root page
  ✓ returns 404 everything else
```

```
UNIT: GoogleDirections Settings
  ✓ can be mutated
  ✓ can accept an API key
  ✓ should detect invalid API key
  ✓ has API key set
  ✓ has travelMode defined
```

```
INTEGRATION: Google API Service
  ✓ instantiation will succeed
  ✓ current environment has valid API key
  ✓ response to have { distance: 19.17, duration: 28.65 } (219ms)
```

```
UNIT: PriceCalculation Class
  ✓ should throw an error on duplicate thresholds
  ✓ should have readonly taxPerc property
  ✓ should throw an error invalid pricing
```

```
INTEGRATION: Price Calculation Different Cases
  ✓ should calculate a price without thresholds
  ✓ calculates price with distance threshold
  ✓ calculates price with duration threshold
  ✓ has a recursive function to calculate cascading thresholds
  ✓ calculates price with distance and duration thresholds
  ✓ should calculate a price with cascaded duration thresholds
```

```
20 passing (360ms)
```

```
Done in 9.98s.
```

```
stefan@DESKTOP-M590E8U:/mnt/c/Projects/pricing-api$
```

# Tests: debugging

## 1. Debug flag

Set debug flag to true to display errors and logs during the tests

```
import debug from '../..debug';

debug(true);

describe('UNIT: PriceCalculation Class', () => {

  it('should throw an error on duplicate...
```

4 passing (93ms)

5 failing

- 1) INTEGRATION: Price Calculation Different Cases  
should calculate a price without thresholds:

```
AssertionError: expected { Object (vehicleType,
maxPassengers, ...) } to deeply equal { Object (route, tax, ...)
}
```

+ expected - actual

```
{
- "fixedPrice": false
- "maxPassengers": 3
- "price": {
-   "breakdown": {
-     "discount": 0
-     "parking": 0
-     "route": 83
-     "tax": 5
-     "toll": 0
-     "waiting": 0
-   }
-   "currency": "EUR"
-   "total": 88
- }
- "vehicleType": "saloon"
+ "discount": 0
+ "parking": 0
+ "route": 83
+ "tax": 5
+ "toll": 0
+ "waiting": 0
```

# Tests: coverage reporting

## All files

84.88% Statements 146/172 72% Branches 36/50 87.18% Functions 34/39 85.37% Lines 140/164

File		Statements		Branches		Functions		Lines	
src	<div><div></div></div>	76.47%	26/34	44.44%	4/9	60%	3/5	80.65%	25/31
src/boot	<div><div></div></div>	100%	4/4	100%	0/0	100%	1/1	100%	4/4
src/services/directions	<div><div></div></div>	75.44%	43/57	69.57%	16/23	93.75%	15/16	74.55%	41/55
src/services/prices	<div><div></div></div>	94.81%	73/77	88.89%	16/18	88.24%	15/17	94.59%	70/74

Istanbul tests checks to see what lines of code were run. The report shows useful information to improve the test coverage of a project.

```
14  /**
15   * Start price calculations. The distance and duration metrics
16   * are fetched by the directionsService using an async function
17   * before calculate is used to calculate the trip price.
18   */
19   public async breakdown(pricing: pricing): Promise<object> {
20
21     if path not taken calculator.validPricingOrError(pricing);
22     metrics = await this.directionsService.directions();
23     if (!metrics) {
24       throw new HttpError('Metrics not provided for price calculation.');
```