

Elaborating F_i^+ to record calculus λ^{rec}

Snow

March 14, 2023

Changes in λ^{rec} 0) Simplify the system, drop polymorphism, and use simple labels

1) Type soundness proved

2) Use list for record types, so the time cost of concatenation can be moved to compilation.

1 Syntax of λ^{rec}

$ttyp, At, Bt, Ct$	$::=$	types
	\top	top type
	\perp	bottom type
	\mathbb{B}	base type
	$At \rightarrow Bt$	function types
	$\{ll : At, Bt\}$	record
txp, t, te, tp, tv, tu	$::=$	target term
	x	variable
	b	base value
	$\lambda x. t$	abstractions
	$\text{fix } x. t$	fixpoint
	$t_1 t_2$	applications
	$\{\}$	empty record
	$\{ll \Rightarrow t'_1, t_2\}$	
	$t_1.ll$	projection
	$t_1; t_2$	concatenation

Notes 0) Multi-field records are nullable. 1) The whole program evaluates to a record form. 3) l stands for a string.

value tv

(Values)

VALUE-UNIT
 $\frac{}{\text{value } \{\}}$

VALUE-LIT
 $\frac{}{\text{value } b}$

VALUE-ABS
 $\frac{}{\text{value } \lambda x. t}$

VALUE-MERGE
 $\frac{\text{value } tv_1 \quad \text{value } tv_2}{\text{value } \{ll \Rightarrow tv_1, tv_2\}}$

$t \rightarrow t'$

(Record Calculus Structural Reduction)

TS-PROJ1
 $\frac{t \rightarrow t'}{t.ll \rightarrow t'.ll}$

TS-APPL
 $\frac{t \rightarrow t'}{t t_2 \rightarrow t' t_2}$

TS-APPR
 $\frac{\text{value } tv \quad t \rightarrow t'}{tv t \rightarrow tv t'}$

TS-MERGE L
 $\frac{t \rightarrow t'}{t; t_2 \rightarrow t'; t_2}$

TS-MERGE R
 $\frac{\text{value } tv \quad t \rightarrow t'}{tv; t \rightarrow tv; t'}$

TS-RCDHEAD
 $\frac{t \rightarrow t'}{\{ll \Rightarrow t, t_2\} \rightarrow \{ll \Rightarrow t', t_2\}}$

TS-RCDTAIL
 $\frac{\text{value } tv \quad t \rightarrow t'}{\{ll \Rightarrow tv, t\} \rightarrow \{ll \Rightarrow tv, t'\}}$

TS-MERGEEMPTY
 $\frac{\text{value } tv}{\{\}; tv \rightarrow tv}$

TS-MERGERCD

$$\frac{\text{value } tv_1 \quad \text{value } tv_2 \quad \text{value } tv_3}{(\{ll \Rightarrow tv_1, tv_2\}); tv_3 \rightarrow \{ll \Rightarrow tv_1, (tv_2; tv_3)\}}$$

TS-PROJRCd

$$\frac{\text{value } tv \quad \text{lookup } ll \ tv \Rightarrow t}{tv.ll \rightarrow t}$$

TS-APPABS

$$\frac{}{(\lambda x.t) \ tv \rightarrow t[x \mapsto tv]}$$

TS-FIXPOINT

$$\frac{}{\text{fix } x.t \rightarrow t[x \mapsto \text{fix } x.t]}$$

$$\boxed{At \& Bt \Rightarrow Ct}$$

(Concatenate types)

CT-NIL

$$\frac{}{\top \& Bt \Rightarrow Bt}$$

CT-RCD

$$\frac{\text{lookup } ll \ Bt_2 \Rightarrow At \ \vee \ \text{lookup } ll \ Bt_2 = / > \quad Bt_1 \& Bt_2 \Rightarrow Ct}{(\{ll : At, Bt_1\}) \& Bt_2 \Rightarrow \{ll : At, Ct\}}$$

$$\boxed{\text{recTyp } At}$$

(Valid record types)

RT-NIL

$$\frac{}{\text{recTyp } \top}$$

RT-RCD

$$\frac{\text{recTyp } Bt}{\text{recTyp } \{ll : At, Bt\}}$$

$$\boxed{\vdash At}$$

(Type wellformedness)

WF-RCD

$$\frac{\vdash At \quad \vdash Bt \quad \text{recTyp } Bt \quad \text{lookup } ll \ Bt \Rightarrow At' \ \vee \ \text{lookup } ll \ Bt = / > \quad At \approx At'}{\vdash \{ll : At, Bt\}}$$

WF-NIL

$$\vdash \top$$

WF-BOT

$$\vdash \perp$$

WF-BASE

$$\vdash \mathbb{B}$$

WF-ARROW

$$\frac{\vdash At \quad \vdash Bt}{\vdash At \rightarrow Bt}$$

$$\boxed{At \& Bt \Rightarrow Ct}$$

(Concatenate types)

CT-NIL

$$\frac{}{\top \& Bt \Rightarrow Bt}$$

CT-RCD

$$\frac{\text{lookup } ll \ Bt_2 \Rightarrow At \ \vee \ \text{lookup } ll \ Bt_2 = / > \quad Bt_1 \& Bt_2 \Rightarrow Ct}{(\{ll : At, Bt_1\}) \& Bt_2 \Rightarrow \{ll : At, Ct\}}$$

$$\boxed{\Gamma \vdash t : At}$$

(Target typing)

TTYPING-BASE

$$\frac{\vdash \Gamma}{\Gamma \vdash b : \mathbb{B}}$$

TTYPING-VAR

$$\frac{\vdash \Gamma \quad x : At \in \Gamma}{\Gamma \vdash x : At}$$

TTYPING-ABS

$$\frac{\Gamma, x : At \vdash t : Bt}{\Gamma \vdash \lambda x.t : At \rightarrow Bt}$$

TTYPING-FIX

$$\frac{\Gamma, x : Bt \vdash t : At \quad At \approx Bt}{\Gamma \vdash \text{fix } x.t : At}$$

TTYPING-RCDCONS

$$\frac{\text{recTyp } Bt \quad \text{lookup } ll \ Bt \Rightarrow At' \ \vee \ \text{lookup } ll \ Bt = / > \quad At \approx At' \quad \Gamma \vdash t_1 : At \quad \Gamma \vdash t_2 : Bt}{\Gamma \vdash (\{ll \Rightarrow t_1, t_2\}) : (\{ll : At, Bt\})}$$

TTYPING-APP

$$\frac{\Gamma \vdash t_1 : At \rightarrow Bt \quad \Gamma \vdash t_2 : At' \quad At \approx At'}{\Gamma \vdash t_1 \ t_2 : Bt}$$

TTYPING-RCDNIL

$$\frac{\vdash \Gamma}{\Gamma \vdash \{\} : \top}$$

TTYPING-RCDPROJ

$$\frac{\Gamma \vdash t : At \quad \text{lookup } ll \ At \Rightarrow Bt}{\Gamma \vdash t.ll : Bt}$$

TTYPING-RCDMERGE

$$\frac{\text{recTyp } At \quad \text{recTyp } Bt \quad \Gamma \vdash t_1 : At \quad \Gamma \vdash t_2 : Bt \quad At \& Bt \Rightarrow Ct}{\Gamma \vdash t_1; t_2 : Ct}$$

$$\boxed{\Gamma \vdash t \Leftarrow At}$$

(Target flex typing)

$$\begin{array}{c} \text{TFTYPING-ORIG} \\ \Gamma \vdash t : At \\ \hline \Gamma \vdash t \Leftarrow At \end{array}$$

$$\begin{array}{c} \text{TFTYPING-TOP} \\ \Gamma \vdash t : At \\ \hline \Gamma \vdash t \Leftarrow \top \end{array}$$

$$\begin{array}{c} \text{TFTYPING-PART} \\ \Gamma \vdash t : At \\ \text{lookup } ll \text{ } At \Rightarrow Bt \\ \hline \Gamma \vdash t \Leftarrow \{ll : Bt\} \end{array}$$

$$\begin{array}{c} \text{TFTYPING-CONS} \\ \Gamma \vdash t \Leftarrow \{ll : At\} \\ \Gamma \vdash t \Leftarrow Bt \\ \hline \Gamma \vdash t \Leftarrow \{ll : At, Bt\} \end{array}$$

$$\begin{array}{c} \text{TFTYPING-SIM} \\ \Gamma \vdash t \Leftarrow At \quad At \approx Bt \\ \hline \Gamma \vdash t \Leftarrow Bt \end{array}$$

2 Syntax of F_i^+

typ, A, B, C	$::=$	types
	\top	top type
	\perp	bottom type
	\mathbb{B}	base type
	$A \rightarrow B$	function types
	$A \& B$	intersection
	$\{l : A\}$	record
exp, e	$::=$	expressions
	\top	top value
	b	base literal
	x	variables
	$\lambda x. e : A \rightarrow B$	abstractions
	$\text{fix } x. e : A$	fixpoint
	$e_1 e_2$	applications
	$e_1 , , e_2$	merge
	$e : A$	annotation
	$\{l = e\}$	record
	$e.l$	projection

Notes 0) Fixpoint typing rule updated.

1) Type translation (from source type to string) modeled.

2) Current focus: converting source type to target type.

$A \approx B$ (Types with the same index)				
$\frac{\text{EI-TRANS} \quad A \approx B \quad B \approx C}{A \approx C}$	$\frac{\text{EI-SYMM} \quad B \approx A}{A \approx B}$	$\frac{\text{EI-ARROW} \quad A_1 \approx A_2 \quad B_1 \approx B_2}{A_1 \rightarrow B_1 \approx A_2 \rightarrow B_2}$	$\frac{\text{EI-RCD} \quad A \approx B}{\{l : A\} \approx \{l : B\}}$	$\frac{\text{EI-AND} \quad A \approx A'}{A \& B \approx A' \& B}$
$\frac{\text{EI-COMM}}{A \& B \approx B \& A}$	$\frac{\text{EI-ASSOC}}{A \& (B \& C) \approx (A \& B) \& C}$	$\frac{\text{EI-TOP} \quad \top A \top}{A \& B \approx B}$	$\frac{\text{EI-DUP} \quad A_1 \approx A_2}{(A_1 \& A_2) \& B \approx A_1 \& B}$	

2.1 Elaboration rules

1) All top-like values are translated into empty lists.

$\frac{\text{ELA-TOP}}{\Gamma \vdash \top \Rightarrow \top \rightsquigarrow \{\}}$	$\frac{\text{ELA-TOPABS} \quad \top B \top}{\Gamma \vdash \lambda x. e : A \rightarrow B \Rightarrow A \rightarrow B \rightsquigarrow \{\}}$	$\frac{\text{ELA-TOPRCD} \quad \Gamma \vdash e \Rightarrow A \rightsquigarrow t \quad \top A \top}{\Gamma \vdash \{l = e\} \Rightarrow \{l : A\} \rightsquigarrow \{\}}$
--	--	--

2) All basic values (that are not merges) are translated into single-field records.

$\frac{\text{ELA-BASE}}{\Gamma \vdash b \Rightarrow \mathbb{B} \rightsquigarrow \{\top \mathbb{B} \top \Rightarrow b\}}$	$\frac{\text{ELA-ABS} \quad \Gamma, x : A \vdash e \Leftarrow B \rightsquigarrow t}{\Gamma \vdash \lambda x. e : A \rightarrow B \Rightarrow A \rightarrow B \rightsquigarrow \{\overrightarrow{\top B \top} \Rightarrow \lambda x. t\}}$
$\frac{\text{ELA-RCD} \quad \Gamma \vdash e \Rightarrow A \rightsquigarrow t}{\Gamma \vdash \{l = e\} \Rightarrow \{l : A\} \rightsquigarrow \{\{l : \top A \top \Rightarrow t\}\}}$	

3) Variables are directly used (unwrap the thunk) and merged terms are simply concatenated, with the expectation that $\cdot \vdash e \Rightarrow A \rightsquigarrow t$ implies $t \rightarrow^* \{|A| \Rightarrow t'\}$ (or a multi-field record) (i.e. the variable will be substituted by a term of this exact type).

$$\begin{array}{c} \text{ELA-VAR} \\ \frac{x : A \in \Gamma}{\Gamma \vdash x \Rightarrow A \rightsquigarrow x} \end{array} \qquad \begin{array}{c} \text{ELA-MERGE} \\ \frac{\Gamma \vdash e_1 \Rightarrow A \rightsquigarrow t_1 \quad \Gamma \vdash e_2 \Rightarrow B \rightsquigarrow t_2 \quad A * B}{\Gamma \vdash e_1, , e_2 \Rightarrow A \& B \rightsquigarrow t_1; t_2} \end{array}$$

4) Projection, application, and type application make use of the property that every translated subterms are records. Application is lazy.

$$\begin{array}{c} \text{ELA-PROJ} \\ \frac{\Gamma \vdash e \Rightarrow A \rightsquigarrow t_1 \quad t_1 : A; \{l\} \rightsquigarrow t_2 : B}{\Gamma \vdash e.l \Rightarrow B \rightsquigarrow t_2} \end{array} \qquad \begin{array}{c} \text{ELA-APP} \\ \frac{\Gamma \vdash e_1 \Rightarrow A \rightsquigarrow t_1 \quad \Gamma \vdash e_2 \Rightarrow B' \rightsquigarrow t_2 \quad t_1 : A; t_2 : B' \rightsquigarrow t_3 : C}{\Gamma \vdash e_1 e_2 \Rightarrow C \rightsquigarrow t_3} \end{array}$$

5) Annotated expressions, like fixpoints, rely on the subsumption rule to insert coercions. The coerced expression always evaluates to a record.

$$\begin{array}{c} \text{ELA-ANNO} \\ \frac{\Gamma \vdash e \Leftarrow A \rightsquigarrow t}{\Gamma \vdash e : A \Rightarrow A \rightsquigarrow t} \end{array} \qquad \begin{array}{c} \text{ELA-FIX} \\ \frac{\Gamma, x : A \vdash e \Leftarrow A \rightsquigarrow t}{\Gamma \vdash \text{fix } x. e : A \Rightarrow A \rightsquigarrow \text{fix } x. t} \end{array} \qquad \begin{array}{c} \text{ELA-SUB} \\ \frac{\Gamma \vdash e \Rightarrow A \rightsquigarrow t_1 \quad t_1 : A <: B \rightsquigarrow t_2}{\Gamma \vdash e \Leftarrow B \rightsquigarrow t_2} \end{array}$$

2.2 Coercions

$$\boxed{t_1 : A <: B \rightsquigarrow t_2} \qquad \text{(Coercive subtyping)}$$

$$\begin{array}{c} \text{S-TOP} \\ \frac{B \text{ Ordinary} \quad \lceil B \rceil}{t : A <: B \rightsquigarrow \{ \}} \end{array} \qquad \begin{array}{c} \text{S-BOT} \\ \frac{B \text{ Ordinary} \quad \neg \lceil B \rceil}{t : \perp <: B \rightsquigarrow \{|B| \Rightarrow \text{fix } x. x\}} \end{array} \qquad \begin{array}{c} \text{S-BASE} \\ \frac{}{t : \mathbb{B} <: \mathbb{B} \rightsquigarrow \{|\mathbb{B}| \Rightarrow t. |\mathbb{B}|\}} \end{array}$$

$$\begin{array}{c} \text{S-ARROW} \\ \frac{B_2 \text{ Ordinary} \quad \neg \lceil B_2 \rceil \quad x : B_1 <: A_1 \rightsquigarrow t_1 \wedge (t. |A_1 \rightarrow A_2|) t_1 : A_2 <: B_2 \rightsquigarrow t_2}{t : A_1 \rightarrow A_2 <: B_1 \rightarrow B_2 \rightsquigarrow \{|B_1 \rightarrow B_2| \Rightarrow \lambda x. t_2\}} \end{array} \qquad \begin{array}{c} \text{S-RCD} \\ \frac{B \text{ Ordinary} \quad \neg \lceil B \rceil \quad t. |\{l : A\}| : A <: B \rightsquigarrow t_2}{t : \{l : A\} <: \{l : B\} \rightsquigarrow \{|\{l : B\}| \Rightarrow t_2\}} \end{array}$$

$$\begin{array}{c} \text{S-ANDL} \\ \frac{C \text{ Ordinary} \quad t : A <: C \rightsquigarrow t'}{t : A \& B <: C \rightsquigarrow t'} \end{array} \qquad \begin{array}{c} \text{S-ANDR} \\ \frac{C \text{ Ordinary} \quad t : B <: C \rightsquigarrow t'}{t : A \& B <: C \rightsquigarrow t'} \end{array} \qquad \begin{array}{c} \text{S-SPLIT} \\ \frac{B_1 \triangleleft B \triangleright B_2 \quad t : A <: B_1 \rightsquigarrow t_1 \quad t : A <: B_2 \rightsquigarrow t_2 \quad t_1 : B_1 \triangleright B \triangleleft t_2 : B_2 \rightsquigarrow t_3}{t : A <: B \rightsquigarrow t_3} \end{array}$$

$$\boxed{t_1 : A \triangleright C \triangleleft t_2 : B \rightsquigarrow t} \qquad \text{(Coercive merging)}$$

$$\begin{array}{c} \text{M-AND} \\ \frac{}{t_1 : A \triangleright A \& B \triangleleft t_2 : B \rightsquigarrow t_1; t_2} \end{array} \qquad \begin{array}{c} \text{M-ARROW} \\ \frac{(t_1. |A \rightarrow B_1|) x : B_1 \triangleright B \triangleleft (t_2. |A \rightarrow B_2|) x : B_2 \rightsquigarrow t}{t_1 : A \rightarrow B_1 \triangleright A \rightarrow B \triangleleft t_2 : A \rightarrow B_2 \rightsquigarrow \{|A \rightarrow B| \Rightarrow \lambda x. t\}} \end{array}$$

$$\begin{array}{c} \text{M-RCD} \\ \frac{t_1. |\{l : A_1\}| : A_1 \triangleright A \triangleleft t_2. |\{l : A_2\}| : A_2 \rightsquigarrow t}{t_1 : \{l : A_1\} \triangleright \{l : A\} \triangleleft t_2 : \{l : A_2\} \rightsquigarrow \{|\{l : A\}| \Rightarrow t\}} \end{array}$$

$$\boxed{t_1 : A; t_2 : B \rightsquigarrow t_3 : C}$$

(Distributive application)

$$\text{A-TOP} \quad \frac{\boxed{\top}}{t_1 : A; t_2 : B \rightsquigarrow \{\} : \top}$$

$$\text{A-ARROW} \quad \frac{t_2 : C <: A \rightsquigarrow t_3}{t_1 : A \rightarrow B; t_2 : C \rightsquigarrow (t_1. \boxed{A \rightarrow B}) t_3 : B}$$

$$\text{A-AND} \quad \frac{t : A; t_2 : C \rightsquigarrow t_3 : A' \quad t : B; t_2 : C \rightsquigarrow t_4 : B'}{t_1 : A \& B; t_2 : C \rightsquigarrow t_3; t_4 : A' \& B'}$$

2.3 Auxiliary definitions

$$\frac{A_{k_1} < A_{k_2} < \dots < A_{k_m} \quad \neg \boxed{A_k}}{\boxed{|A_1 \& A_2 \& \dots \& A_n| = |A_{k_1}| \& |A_{k_2}| \& \dots \& |A_{k_m}|}}$$

$$\boxed{\boxed{A}}$$

(Top-like Types)

$$\text{TL-TOP} \quad \frac{}{\boxed{\top}}$$

$$\text{TL-AND} \quad \frac{\boxed{A} \quad \boxed{B}}{\boxed{A \& B}}$$

$$\text{TL-ARR} \quad \frac{\boxed{B}}{\boxed{A \rightarrow B}}$$

$$\text{TL-RCD} \quad \frac{\boxed{B}}{\boxed{\{l : B\}}}$$

$$\boxed{A \text{ Ordinary}}$$

(Ordinary Types)

$$\text{O-TOP} \quad \frac{}{\top \text{ Ordinary}}$$

$$\text{O-INT} \quad \frac{}{\mathbb{B} \text{ Ordinary}}$$

$$\text{O-ARROW} \quad \frac{B \text{ Ordinary}}{A \rightarrow B \text{ Ordinary}}$$

$$\text{O-RCD} \quad \frac{B \text{ Ordinary}}{\{l : B\} \text{ Ordinary}}$$

$$\boxed{A * B}$$

(Type Disjointness (Algorithmic))

$$\text{D-TOPL} \quad \frac{}{\top * A} \quad \text{D-TOPR} \quad \frac{}{A * \top}$$

$$\text{D-ANDL} \quad \frac{A_1 * B \quad A_2 * B}{A_1 \& A_2 * B}$$

$$\text{D-ANDR} \quad \frac{A * B_1 \quad A * B_2}{A * B_1 \& B_2}$$

$$\text{D-BASEARR} \quad \frac{}{\mathbb{B} * A_1 \rightarrow A_2}$$

$$\text{D-ARRBASE} \quad \frac{}{A_1 \rightarrow A_2 * \mathbb{B}}$$

$$\text{D-ARRARR} \quad \frac{A_2 * B_2}{A_1 \rightarrow A_2 * B_1 \rightarrow B_2}$$

$$\text{D-RCDEQ} \quad \frac{A * B}{\{l : A\} * \{l : B\}}$$

$$\text{D-RCDNEQ} \quad \frac{l_1 \neq l_2}{\{l_1 : A\} * \{l_2 : B\}}$$

$$\text{D-BASERCD} \quad \frac{}{\mathbb{B} * \{l : A\}}$$

$$\text{D-RCDBASE} \quad \frac{}{\{l : A\} * \mathbb{B}}$$

$$\text{D-ARRRCD} \quad \frac{}{A_1 \rightarrow A_2 * \{l : A\}}$$

$$\text{D-RCDARR} \quad \frac{}{\{l : A\} * A_1 \rightarrow A_2}$$

$$\boxed{B \triangleleft A \triangleright C}$$

(Split a Type into Two)

$$\text{SP-AND} \quad \frac{}{(A) \triangleleft (A \& B) \triangleright (B)}$$

$$\text{SP-ARROW} \quad \frac{B_1 \triangleleft B \triangleright B_2}{(A \rightarrow B_1) \triangleleft (A \rightarrow B) \triangleright (A \rightarrow B_2)}$$

$$\text{SP-RCD} \quad \frac{B_1 \triangleleft B \triangleright B_2}{\{l : B_1\} \triangleleft \{l : B\} \triangleright \{l : B_2\}}$$

$$\boxed{At <: Bt}$$

(Target Subtyping)

$$\text{TS-TOP} \quad \frac{}{At <: \top}$$

$$\text{TS-REFL} \quad \frac{}{At <: At}$$

$$\text{TS-ARROW} \quad \frac{At_1 <: At_2 \quad Bt_1 <: Bt_2}{At_1 \rightarrow Bt_1 <: At_2 \rightarrow Bt_2}$$

$$\text{TS-RCD} \quad \frac{\text{recTyp } Ct' \quad \text{lookup } ll \ Ct \Rightarrow Bt \quad Bt <: At \quad Ct <: Ct'}{Ct <: \{ll : At, Ct'\}}$$

$$\boxed{At \approx Bt}$$

(Types with the same index)

TEI-REFL	TEI-ARROW $\frac{At_1 \approx At_2 \quad Bt_1 \approx Bt_2}{At_1 \rightarrow Bt_1 \approx At_2 \rightarrow Bt_2}$	TEI-RCD $\frac{\text{recTyp } Ct \quad \text{lookup } ll \ Ct = / > \vee (\text{lookup } ll \ Ct \Rightarrow At' \wedge At' \approx At) \quad At \approx Bt \quad Ct \approx Ct'}{\{ll : At, Ct\} \approx \{ll : Bt, Ct'\}}$
TEI-COMM	$\frac{\begin{array}{l} \text{recTyp } Ct \\ \text{lookup } ll_1 \ Ct = / > \vee (\text{lookup } ll_1 \ Ct \Rightarrow At' \wedge At' \approx At) \\ \text{lookup } ll_2 \ Ct = / > \vee (\text{lookup } ll_2 \ Ct \Rightarrow Bt' \wedge Bt' \approx Bt) \\ ll_1 \neq ll_2 \\ \{ll_2 : Bt, (\{ll_1 : At, Ct\})\} \approx Ct' \end{array}}{\{ll_1 : At, (\{ll_2 : Bt, Ct\})\} \approx Ct'}$	TEI-DUP $\frac{\begin{array}{l} \text{recTyp } Ct \\ \text{lookup } ll \ Ct = / > \vee (\text{lookup } ll \ Ct \Rightarrow At' \wedge At' \approx At) \\ At \approx Bt \\ \{ll : Bt, (\{ll : At, Ct\})\} \approx Ct' \end{array}}{\{ll : At, (\{ll : Bt, Ct\})\} \approx Ct'}$

1) type soundness of the target calculus

2) connecting the source to the target

- type translation function (from source type to string):
intersection types are flattened, their
toplike parts are filtered, and all the conjuncts are sorted (but no deduplication).
- a relation that characterizes types that corresponds to the same
string.

3) I need a function that converts source types to target types, to prove that elaboration generates well-typed terms. There are 3 problems:

- Source types and target types are not one-to-one mapped. The typing rule for topline lambda functions does not split types but the subsumption rule does (via subtyping)

$\backslash x : \text{Int} . x : \text{Top\&Top} \rightsquigarrow \{ \}$

$(\backslash x : \text{Int} . x : \text{Int}) : \text{Int} \rightarrow \text{Top\&Top} \rightsquigarrow \{ \rightarrow | \text{Top\&Top} | \Rightarrow \backslash x . \dots \}$

Lemma eqIndTyp_sound_complete: $A \approx B$ iff $|A| = |B|$.

Lemma disjoint_type_no_eqInd: if $A \approx B$ and $A * B$ then there is a contradiction.

Lemma translation from source type to target type is a function

Lemma cosub_well_typed: if $t_1 : A <: B \rightsquigarrow t_2$ and $G || \vdash t_1 <= |[A]|$ then $G || \vdash t_2 : |[B]|$.

Theorem elaboration_well_typed: if $\Gamma \vdash e \text{ dirflag } A \rightsquigarrow t$ then $[[G]] || \vdash t : |[A]|$.