


# Web API Design with Spring Boot Week 4 Coding Assignment

**Points possible:** 70

Category	Criteria	% of Grade
Functionality	Does the code work?	25
Organization	Is the code clean and organized? Proper use of white space, syntax, and consistency are utilized. Names and comments are concise and clear.	25
Creativity	Student solved the problems presented in the assignment using creativity and out of the box thinking.	25
Completeness	All requirements of the assignment are complete.	25

**Instructions:** In Eclipse, or an IDE of your choice, write the code that accomplishes the objectives listed below. Ensure that the code compiles and runs as directed. Take screenshots of the code and of the running program (make sure to get screenshots of all required functionality) and paste them in this document where instructed below. Create a new repository on GitHub for this week's assignments and push this document, with your Java project code, to the repository. Add the URL for this week's repository to this document where instructed and submit this document to your instructor when complete.

**Here's a friendly tip:** as you watch the videos, code along with the videos. This will help you with the homework. When a screenshot is required, look for the icon:  You will keep adding to this project throughout this part of the course. When it comes time for the final project, use this project as a starter.

## Project Resources:

<https://github.com/promineotech/Spring-Boot-Course-Student-Resources>

## Coding Steps:

For this week's homework you need to copy source code from the supplied resources.


For this week's homework you need to copy source code from the Source folder in the supplied resources. Wait until the instructions tell you to copy the resources or you will get errors.

- 1) Select some options for a Jeep order:

- a) Use the `data.sql` file or the jeep database tables to select options for a Jeep order. Select any one of each of the following for the order:
    - i) color
    - ii) customer
    - iii) engine
    - iv) model
    - v) tire(s)
  - b) Select one or more options from the options table as well. Keep in mind that some options may work better than others – but if you want to put 37-inch tires on your Jeep Renegade, so be it!
- 2) Create a new integration test class to test a Jeep order named `CreateOrderTest.java`. Create this class in `src/test/java` in the `com.promineotech.jeep.controller` package.
- a) Add the Spring Boot Test annotations: `@SpringBootTest`, `@ActiveProfiles`, and `@Sql`. They should have the same parameters as the test created in weeks 1 and 2.
  - b) Create a test method (annotated with `@Test`) named `testCreateOrderReturnsSuccess201`.
  - c) In the test class, create a method named `createOrderBody`. This method returns a type of `String`. In this method, return a JSON object with the IDs that you picked in Step 1a and b. For example:

```
{
  "customer": "MORISON_LINA",
  "model": "WRANGLER",
  "trim": "Sport Altitude",
  "doors": 4,
  "color": "EXT_NACHO",
  "engine": "2_0_TURBO",
  "tire": "35_TOYO",
  "options": [
    "DOOR_QUAD_4",
    "EXT_AEV_LIFT",
    "EXT_WARN_WINCH",
    "EXT_WARN BUMPER_FRONT",
    "EXT_WARN BUMPER_REAR",
    "EXT_ARB_COMPRESSOR"
  ]
}
```

Make sure that the JSON is correct! If necessary, use a JSON formatter/validator like the one here: <https://jsonformatter.curiousconcept.com/>.

Produce a screenshot of the `createOrderBody()` method. 

In the test method, assign the return value of the `createOrderBody()` method to a variable named `body`.

d) In the test class, add an instance variable named `serverPort` to hold the port that Tomcat is listening on in the test. Annotate the variable with `@LocalServerPort`.

e) Add another instance variable for an injected `TestRestTemplate` named `restTemplate`.

f) In the test method, assign a value to a local variable named `uri` as follows:

```
String uri = String.format("http://localhost:%d/orders", serverPort);
```

g) In the test method, create an `HttpHeaders` object and set the content type to "application/json" like this:

```
HttpHeaders headers = new HttpHeaders();  
headers.setContentType(MediaType.APPLICATION_JSON);
```

Make sure to import the package `org.springframework.http.HttpHeaders`.

h) Create an `HttpEntity` object and set the request body and headers:


```
HttpEntity<String> bodyEntity = new HttpEntity<>(body, headers);
```

i) Send the request body and headers to the server. The `Order` class should have been copied earlier from the supplied resources. Ensure that you import `com.promineotech.jeep.entity.Order` and not some other `Order` class.

```
ResponseEntity<Order> response = restTemplate.exchange(uri,  
    HttpMethod.POST, bodyEntity, Order.class);
```



j) Add the AssertJ assertions to ensure that the response is correct. Replace the expected values to match the JSON in step 2c.

```
assertThat(response.getStatusCode()).isEqualTo(HttpStatus.CREATED);  
assertThat(response.getBody()).isNotNull();  
  
Order order = response.getBody();  
assertThat(order.getCustomer().getCustomerId()).isEqualTo("MORISON_LINA");  
assertThat(order.getModel().getModelId()).isEqualTo(JeepModel.WRANGLER);  
assertThat(order.getModel().getTrimLevel()).isEqualTo("Sport Altitude");  
assertThat(order.getModel().getNumDoors()).isEqualTo(4);  
assertThat(order.getColor().getColorId()).isEqualTo("EXT_NACHO");  
assertThat(order.getEngine().getEngineId()).isEqualTo("2_0_TURBO");  
assertThat(order.getTire().getTireId()).isEqualTo("35_TOYO");  
assertThat(order.getOptions()).hasSize(6);
```


k) Produce a screenshot of the test method. 

3) In the controller sub-package in `src/main/java`, create an interface named `JeepOrderController`. Add `@RequestMapping("/orders")` as a class-level annotation.

a) Create a method in the interface to create an order (`createOrder`). It should return an object of type `Order` (see below). It should accept a single parameter of type `OrderRequest` as described in the video. Make sure it accepts an HTTP POST request and returns a status code of 201 (created).


- b) Add the `@RequestBody` annotation to the `orderRequest` parameter. Make sure to add the `RequestBody` annotation from the `org.springframework.web.bind.annotation` package.
  - c) Produce a screenshot of the finished `JeepOrderController` interface showing no compile errors. 
- 4) Create a class that implements `JeepOrderController` named `DefaultJeepOrderController`.
- a) Add `@RestController` as a class-level annotation.
  - b) Add a log line to the implementing controller method showing the input request body (`orderRequest`)
  - c) Run the test to show a red status bar. Produce a screenshot that shows the test method, the log line, and the red JUnit status bar. 
- 5) Find the Maven dependency `spring-boot-starter-validation` by looking it up at <https://mvnrepository.com/>. Add this repository to the project POM file (`pom.xml`).
- 6) Add the class-level annotation `@Validated` to the `JeepOrderController` interface.
- 7) Add Bean Validation annotations to the `OrderRequest` class as shown in the video.
- a) Use these annotations for String types:
    - i) `@NotNull`
    - ii) `@Length(max = 30)`
    - iii) `@Pattern(regexp = "[\\w\\s]*")`
  - b) Use these annotations for integer types:
    - i) `@Positive`
    - ii) `@Min(2)`
    - iii) `@Max(4)`
  - c) Add `@NotNull` to the enum type.
  - d) Add validation to the list element (type String) by adding the validation annotations *inside* the generic definition. So, to add the String validation to the options, you would do this:

```
private List<@NotNull @Length(max = 30) @Pattern(regexp = "[\\w\\s]*") String> options;
```

Do not apply a `@NotNull` annotation to the `List` because if you have no options the `List` may be null.
  - e) Produce a screenshot of this class with the annotations. 
- 8) In the `jeep.service` sub-package, create the empty (no methods yet) order service interface (named `JeepOrderService`) and implementation (named `DefaultJeepOrderService`).

- a) Inject the interface into the order controller implementation class.
- b) Add the `@Service` annotation to the service implementation class.
- c) Create the `createOrder` method in the interface and implementing service. The method signature should look like this:

```
Order createOrder(OrderRequest orderRequest);
```

- d) Call the `createOrder` method from the controller and return the value returned by the service.
  - e) Add a log line in the `createOrder` method and log the `orderRequest` parameter.
  - f) Run the test `CreateOrderTest` again. Produce a screenshot showing that the service layer `createOrder` method correctly prints the log line in the console. (e.g. prints out the `OrderRequest` in the console from within the Service Layer). 
- 9) In the `jeep.dao` sub-package, create the empty (no methods yet) DAO interface (named `JeepOrderDao`) and implementation (named `DefaultJeepOrderDao`).
- a) Inject the DAO interface into the order service implementation class.
  - b) Add the `@Component` annotation to the DAO implementation class.
- 10) Replace the entire content of `JeepOrderDao.java` with the source found in `JeepOrderDao.source`. The source file is found in the Source folder of the supplied project resources.

**11) \*\*\* The next steps require you to copy source code from the Source directory in the supplied resources. Please follow the instructions EXACTLY. Some steps require you to replace ALL the source in a file. Some steps require you to ADD source to a file.**

- 12) Copy the *contents* of the file `DefaultJeepOrderDao.source` into `DefaultJeepOrderDao.java`. The source file is found in the Source folder of the supplied project resources.

In Eclipse, click the "Source" menu and select "Organize Imports". Pick packages from your project where applicable. Make sure you pick the import `java.util.Optional`, `java.util.List`, and `org.springframework.jdbc.core.RowMapper`.

- 13) Copy the *contents* of the file `DefaultJeepOrderService.source` into `DefaultJeepOrderService.java`. Add the source after the `createOrder()` method, but *inside* the class body. The source file is found in the Source folder of the supplied project resources.


In Eclipse, click the "Source" menu and select "Organize Imports". Pick packages from your project where applicable.

- 14) In `DefaultJeepOrderService.java`, work with the method `createOrder`.
- a) Add the `@Transactional` annotation to the `createOrder` method.

- b) In the createOrder method call the copied methods: getCustomer, getModel, getColor, getEngine, getTire and getOption, assigning the return values of these methods to variables of the appropriate types.
- c) Calculate the price, including all options.

15) In JeepOrderDao.java and DefaultJeepOrderDao.java, add the method:



```
Order saveOrder(Customer customer, Jeep jeep, Color color, Engine engine, Tire
    tire, BigDecimal price, List<Option> options);
```

- a) Call the jeepOrder.Dao.saveOrder method from the jeepOrderSalesService.createOrder service. Produce a screenshot of the jeepOrderSalesService.createOrder method. 
- b) Write the implementation of the saveOrder method in the DAO.
  - i) Call the supplied generateInsertSql method, passing in the customer, jeep, color, engine, tire and price. Assign the return value of the method to a SqlParameter object.
  - ii) Call the update method on the NamedParameterJdbcTemplate object, passing in a KeyHolder object as shown in the video. Create the KeyHolder like this:
 

```
KeyHolder keyHolder = new GeneratedKeyHolder();
```

Be sure to extract the order primary key from the KeyHolder object into a variable of type Long named orderPK.
  - iii) Write a method named saveOptions as shown in the video. This method should have the following method signature:
 

```
private void saveOptions(List<Option> options, Long orderPK)
```


For each option in the Options list, call the supplied generateInsertSql method passing the parameters option and order primary key (orderPK). Call the update method on the NamedParameterJdbcTemplate object.
  - iv) In the saveOrder method in the DAO implementation, return an Order object using the Order.builder. The Order should include orderPK, customer, jeep (model), color, engine, tire, options and price.
  - v) Produce a screenshot of the saveOrder method. 
- c) Run the integration test in CreateOrderTest. Produce a screenshot of the test method that shows the green JUnit status bar, the console output, and the test class. 

## Screenshots of Code:

2. k)

```
4
5- /**
6  *
7  * @return
8  */
9- protected String createOrderBody() {
10     // @formatter:off
11     return "{\n"
12         + "  \"customer\": \"IGNATOV_GISELLA\", \n"
13         + "  \"model\": \"CHEROKEE\", \n"
14         + "  \"trim\": \"Trailhawk\", \n"
15         + "  \"doors\": \"4\", \n"
16         + "  \"color\": \"EXT_VELVET_RED\", \n"
17         + "  \"engine\": \"3_6_HYBRID\", \n"
18         + "  \"tire\": \"265_BRIDGESTONE\", \n"
19         + "  \"options\": [\n"
20         + "    \"DOOR_WARRIOR_MIRROR\", \n"
21         + "    \"EXT_DUAL_UPPER_PREMIUM\", \n"
22         + "    \"INT_MOPAR_GRAB\", \n"
23         + "    \"INT_MOPAR_COLR\", \n"
24         + "    \"TOP_MOPAR_SKY\", \n"
25         + "    \"WHEEL_TACTIK_MATTE\", \n"
26         + "    \"EXT_MOPAR_CAMERA\" \n"
27         + "  ]\n"
28         + "}";
29     //formatter:on
30 }
31
32 }
```

### 3. c)



```
1 package com.promineotech.jeepp.controller;
2
3 import org.springframework.http.HttpStatus;
4
5
6
7
8
9
10
11
12
13
14
15
16
17
18
19 @RequestMapping("/orders")
20 @OpenAPIDefinition(info = @Info(title = "Jeep Order Service"),
21     servers = { @Server(url = "http://localhost:8080", description = "Local server.")})
22 public interface JeepOrderController {
23     //formatter:off
24     @Operation(
25         summary = "Create an order for a Jeep",
26         description = "Returns the created Order",
27         responses = {
28             @ApiResponse(
29                 responseCode = "201",
30                 description = "The created order is returned.",
31                 content = @Content(
32                     mediaType = "application/json",
33                     schema = @Schema(implementation = Order.class))),
34             @ApiResponse(
35                 responseCode = "400",
36                 description = "The request parameters are invalid.",
37                 content = @Content(
38                     mediaType = "application/json")),
39             @ApiResponse(
40                 responseCode = "404",
41                 description = "A Jeep component was not found with the input criteria.",
42                 content = @Content(
43                     mediaType = "application/json")),
44             @ApiResponse(
45                 responseCode = "500",
46                 description = "An unplanned error occurred.",
47                 content = @Content(
48                     mediaType = "application/json"))
49         },
50     parameters = {
51         @Parameter(
52             name = "order request",
53             required = true,
54             description = "The order as JSON")
55     }
56 }
```



### 3.c) continued

```
20 summary = "Create an order for a Jeep",
26 description = "Returns the created Order",
27 responses = {
28     @ApiResponse(
29         responseCode = "201",
30         description = "The created order is returned.",
31         content = @Content(
32             mediaType = "application/json",
33             schema = @Schema(implementation = Order.class))),
34     @ApiResponse(
35         responseCode = "400",
36         description = "The request parameters are invalid.",
37         content = @Content(
38             mediaType = "application/json")),
39     @ApiResponse(
40         responseCode = "404",
41         description = "A Jeep component was not found with the input criteria.",
42         content = @Content(
43             mediaType = "application/json")),
44     @ApiResponse(
45         responseCode = "500",
46         description = "An unplanned error occurred.",
47         content = @Content(
48             mediaType = "application/json"))
49 },
50 parameters = {
51     @Parameter(
52         name = "order request",
53         required = true,
54         description = "The order as JSON")
55 }
56 )
57
58
59 @PostMapping
60 @ResponseStatus(code = HttpStatus.CREATED)
61 Order createOrder(@RequestBody OrderRequest orderRequest);
62
63 //formatter:on
64 }
65
```

### 4.c)

The screenshot shows the Spring Tool Suite 4 IDE with the following components:

- Package Explorer:** Shows the project structure with the test class `CreateOrderTest` selected.
- JUnit Runner:** Shows the test results for `CreateOrderTest`. It indicates that the test `testCreateOrderReturnsSuccess201` failed. The failure trace shows an `AssertionFailedError` with the message "expected: 201 CREATED but was: 415 UNSUPPORTED\_MEDIA\_TYPE".
- Source Editor:** Displays the `BasicJeepOrderController` class. The `createOrder` method is highlighted, showing a `log.info` statement and a `return null;` statement.
- Console:** Shows the output of the test run. It includes logs from Spring Boot, the test runner, and the test class. The logs indicate that the test failed due to an `UnsupportedMediaTypeException` with status 415.

```
2022-08-20 05:08:05.175 INFO 7724 --- [main] c.p.jeepp.controller.CreateOrderTest : Starting CreateOrderTest using Java 17.0.3 on M...
2022-08-20 05:08:05.176 DEBUG 7724 --- [main] c.p.jeepp.controller.CreateOrderTest : Running with Spring Boot v2.7.2, Spring v5.3.22
2022-08-20 05:08:05.177 INFO 7724 --- [main] c.p.jeepp.controller.CreateOrderTest : The following 1 profile is active: "test"
2022-08-20 05:08:08.545 INFO 7724 --- [main] c.p.jeepp.controller.CreateOrderTest : Started CreateOrderTest in 3.801 seconds (JVM r...
2022-08-20 05:08:09.742 WARN 7724 --- [o-auto-l-exec-1] .w.s.m.s.DefaultHandlerExceptionResolver : Resolved [org.springframework.web.HttpMediaType...
```

7.e)

```
va/com/promineotech/jeep/entity/OrderRequest.java - Spring Tool Suite 4
File Search Project Run Window Help
JeepSales.java CreateOrder... CreateOrder... FetchJeepTe... OrderReques... *JeepOrderCo... Order.j

10
11 @Data
12 public class OrderRequest {
13
14     @NotNull
15     @Length(max = 30)
16     @Pattern(regexp = "[\\w\\s]*")
17     private String customer;
18
19     @NotNull
20     private JeepModel model;
21
22     @NotNull
23     @Length(max = 30)
24     @Pattern(regexp = "[\\w\\s]*")
25     private String trim;
26
27     @Positive
28     @Min(2)
29     @Min(4)
30     private int doors;
31
32     @NotNull
33     @Length(max = 30)
34     @Pattern(regexp = "[\\w\\s]*")
35     private String color;
36
37     @NotNull
38     @Length(max = 30)
39     @Pattern(regexp = "[\\w\\s]*")
40     private String engine;
41
42     @NotNull
43     @Length(max = 30)
44     @Pattern(regexp = "[\\w\\s]*")
45     private String tire;
46
47     private List<@NotNull @Length(max = 30) @Pattern(regexp = "[\\w\\s]*") String> options;
48 }
```

8.f)

```
1 package com.promineotech.jeep.service;
2
3 import org.springframework.beans.factory.annotation.Autowired;
4 import org.springframework.stereotype.Service;
5 import org.springframework.transaction.annotation.Transactional;
6 import com.promineotech.jeep.dao.JeepOrderDao;
7 import com.promineotech.jeep.entity.Order;
8 import com.promineotech.jeep.entity.OrderRequest;
9 import lombok.extern.slf4j.Slf4j;
10
11 @Service
12 @Slf4j
13 public class DefaultJeepOrderService implements JeepOrderService {
14
15     @Autowired
16     private JeepOrderDao jeepOrderDao;
17
18     @Transactional
19     @Override
20     public Order createOrder(OrderRequest orderRequest) {
21         log.info("service layer order = {} ", orderRequest);
22     }
23 }
```

Failure Trace

- java.lang.AssertionError: Expecting actual not to be null
- at com.promineotech.jeep.controller.CreateOrderTest.createOrderR...
- at java.base/java.util.ArrayList.forEach(ArrayList.java:1511)
- at java.base/java.util.ArrayList.forEach(ArrayList.java:1511)

Console

```
2022-08-20 06:36:44.088 INFO 23748 --- [main] c.p.jeep.controller.CreateOrderTest : Starting CreateOrderTest using Java
2022-08-20 06:36:44.088 DEBUG 23748 --- [main] c.p.jeep.controller.CreateOrderTest : Running with Spring Boot v2.7.2, Spr
2022-08-20 06:36:44.089 INFO 23748 --- [main] c.p.jeep.controller.CreateOrderTest : The following 1 profile is active: "
2022-08-20 06:36:47.469 INFO 23748 --- [main] c.p.jeep.controller.CreateOrderTest : Started CreateOrderTest in 3.832 sec
2022-08-20 06:36:48.657 INFO 23748 --- [o-auto-1-exec-1] c.p.j.c.BasicJeepOrderController : Order = OrderRequest(customer=IGNATO
2022-08-20 06:36:48.665 INFO 23748 --- [o-auto-1-exec-1] c.p.j.s.DefaultJeepOrderService : service layer order = OrderRequest(c
```

15.a)

```
25 private JeepOrderDao jeepOrderDao;
26
27 @Transactional
28 @Override
29 public Order createOrder(OrderRequest orderRequest) {
30     Customer customer = getCustomer(orderRequest);
31     Jeep model = getModel(orderRequest);
32     Color color = getColor(orderRequest);
33     Engine engine = getEngine(orderRequest);
34     Tire tire = getTire(orderRequest);
35     List<Option> options = getOption(orderRequest);
36     BigDecimal price = options
37         .stream()
38         .map(Option::getPrice)
39         .reduce(BigDecimal.ZERO, BigDecimal::add);
40     price.add(model.getBasePrice());
41     price.add(color.getPrice());
42     price.add(engine.getPrice());
43
44     return jeepOrderDao.saveOrder(customer, model, color, engine, tire, price, options);
45 }
```

## 15.b)v)

```

37
38
39 ● @Override
40 public Order saveOrder(Customer customer, Jeep jeep, Color color, Engine engine, Tire tire,
41     BigDecimal price, List<Option> options) {
42     SqlParams params = generateInsertSql(customer, jeep, color, engine, tire, price);
43     KeyHolder keyHolder = new GeneratedKeyHolder();
44     jdbcTemplate.update(params.sql, params.source, keyHolder);
45
46     Long orderPK = keyHolder.getKey().longValue();
47     saveOptions(options, orderPK);
48
49     return Order.builder()
50         .customer(customer)
51         .model(jeep)
52         .color(color)
53         .engine(engine)
54         .tire(tire)
55         .options(options)
56         .build();
57 }
58
59 ● private void saveOptions(List<Option> options, Long orderPK) {
60     for(Option option: options) {
61         SqlParams params = generateInsertSql(option, orderPK);
62         jdbcTemplate.update(params.sql, params.source);
63     }
64 }
65

```

## 15.c)

PromineWeek16 - jeep-sales/src/test/java/com/promineotech/jeep/controller/CreateOrderTest.java - Spring Tool Suite 4

File Edit Source Refactor Navigate Search Project Run Window Help

Package Explorer JUnit Order.java CreateOrderTest.java JeepSales.java CreateOrderService.java DefaultJeepOrderService.java FetchJeepTest.java DefaultJeepOrderDao.java

Finished after 6.909 seconds

Runs: 1/1 Errors: 0 Failures: 0

▼ CreateOrderTest (Runner: JUnit 5) (1.698 s)

TestCreateOrderReturnsSuccess2010 (1.698 s)

```

1 package com.promineotech.jeepp.controller;
2
3 import static org.assertj.core.api.Assertions.*;
4 import org.junit.jupiter.api.Test;
5 import org.springframework.boot.test.context.SpringBootTest;
6 import org.springframework.test.context.ActiveProfiles;
7 import org.springframework.test.context.jdbc.Sql;
8 import org.springframework.test.context.jdbc.SqlConfig;
9 import com.promineotech.jeepp.controller.support.CreateOrderTestSupport;
10 import com.promineotech.jeepp.entity.JeeppModel;
11 import com.promineotech.jeepp.entity.Order;
12 import org.springframework.boot.test.context.SpringBootTest.WebEnvironment;
13 import org.springframework.http.HttpEntity;
14 import org.springframework.http.HttpHeaders;
15 import org.springframework.http.HttpMethod;
16 import org.springframework.http.HttpStatus;
17 import org.springframework.http.MediaType;
18 import org.springframework.http.ResponseEntity;
19
20 @SpringBootTest(webEnvironment = WebEnvironment.RANDOM_PORT)
21 @ActiveProfiles("test")
22 @Sql(scripts = {
23     "classpath:flyway/migrations/V1.0_Jeepp.Schema.sql",
24     "classpath:flyway/migrations/V1.1_Jeepp.Data.sql"},
25     config = @SqlConfig(encoding = "utf-8"))
26 class CreateOrderTest extends CreateOrderTestSupport {
27
28     /*
29     */
30 }

```

Failure Trace


Console

```

2022-08-20 08:25:30.262 INFO 16564 --- [main] c.p.jeepp.controller.CreateOrderTest : Starting CreateOrderTest using Java 17.0.3 on
2022-08-20 08:25:30.263 DEBUG 16564 --- [main] c.p.jeepp.controller.CreateOrderTest : Running with Spring Boot v2.7.2, Spring v5.3.
2022-08-20 08:25:30.264 INFO 16564 --- [main] c.p.jeepp.controller.CreateOrderTest : The following 1 profile is active: "test"
2022-08-20 08:25:34.151 INFO 16564 --- [main] c.p.jeepp.controller.CreateOrderTest : Started CreateOrderTest in 4.453 seconds (JVM
2022-08-20 08:25:35.606 INFO 16564 --- [e-auto-1-exoc-1] c.p.j.c.hanicejeppOrderController : Order = OrderRequest(customer=IGNATYOV_GIBBILJA

```

## 15.c) continued

A screenshot of an IDE window showing a Java test file named 'CreateOrderTest.java'. The code is a JUnit test method 'TestCreateOrderReturnsSuccess201()' that simulates a POST request to create an order and asserts that a 201 status is returned with the correct order details. The IDE has a dark theme and shows several tabs at the top: 'JeepSales.java', 'CreateOrderTest.java' (active), 'JeepOrderService.java', 'DefaultJeepOrderService.java', 'FetchJeepTest.java', and 'DefaultJeepC...'.

```
31 @Test
32 void TestCreateOrderReturnsSuccess201() {
33     //Given: an order as JSON
34     String body = createOrderBody();
35     String uri = getBaseUriForOrders();
36
37     HttpHeaders headers = new HttpHeaders();
38     headers.setContentType(MediaType.APPLICATION_JSON);
39
40     HttpEntity<String> bodyEntity = new HttpEntity<>(body, headers);
41
42     //When: Order is sent
43     ResponseEntity<Order> response = getRestTemplate().exchange(uri, HttpMethod.POST,
44         bodyEntity, Order.class);
45
46     //Then: a 201 status is returned
47     assertThat(response.getStatusCode()).isEqualTo(HttpStatus.CREATED);
48
49     //And: the returned order is correct
50     assertThat(response.getBody()).isNotNull();
51     Order order = response.getBody();
52     assertThat(order.getCustomer().getCustomerId()).isEqualTo("IGNATOV_GISELLA");
53     assertThat(order.getModel().getModelId()).isEqualTo(JeepModel.CHEROKEE);
54     assertThat(order.getModel().getTrimLevel()).isEqualTo("Trailhawk");
55     assertThat(order.getModel().getNumDoors()).isEqualTo(4);
56     assertThat(order.getColor().getColorId()).isEqualTo("EXT_VELVET_RED");
57     assertThat(order.getEngine().getEngineId()).isEqualTo("3_6_HYBRID");
58     assertThat(order.getTire().getTireId()).isEqualTo("265_BRIDGESTONE");
59     assertThat(order.getOptions()).hasSize(7);
60 }
```

URL to GitHub Repository:

<https://github.com/MerelOhler/PromineoWeek16>