InterLink Protocol

A Zero-Knowledge Atomic Interoperability Framework

Trustless. Scalable. Unified.

MeridianAlgo Research Lab

Version 6.0 February 2026

Contents

Abstract **3**

1 Introduction **5**
1.1 The Blockchain Paradigm: A Detailed Overview . . . 5
1.1.1 Cryptographic Foundations . . . 5
1.1.2 Consensus Mechanisms . . . 5
1.1.3 Smart Contracts and Turing Completeness . . . 5
1.2 The Fragmentation Crisis: The Problems of Success . . . 6
1.2.1 The Siloed State Problem . . . 6
1.2.2 The Security Vulnerability of Bridges . . . 6
1.3 The Genesis of InterLink: A Proposal for Unification . . . 6
1.3.1 From Trust to Truth . . . 6
1.3.2 Unified Liquidity . . . 6
1.3.3 Sovereignty and Scalability . . . 7

2 Core Definitions **7**

3 Preliminaries **7**
3.1 The Concept of Zero-Knowledge . . . 8
3.1.1 Intuition: The Ali Baba Cave . . . 8
3.2 zk-SNARKs: A Technical Deep Dive . . . 8
3.3 Elliptic Curve Cryptography (ECC) . . . 8
3.3.1 BN254 (Alt-Bn128) . . . 9
3.3.2 Pallas and Vesta (The Pasta Curves) . . . 9
3.4 Polynomial Commitment Schemes (PCS) . . . 9
3.4.1 KZG (Kate-Zaverucha-Goldberg) . . . 9
3.4.2 IPA (Inner Product Argument) . . . 9
3.5 Solana Runtime (Sealevel) . . . 9

4 System Architecture **10**
4.1 The Hub-and-Spoke Topology . . . 10
4.1.1 Detailed Topology Description . . . 10
4.1.2 Topology Advantages and Trade-offs . . . 10
4.1.3 Example: Cross-Chain Message Routing . . . 11
4.2 Detailed Component Breakdown . . . 11
4.2.1 Source Chain Gateway (The Spoke) . . . 11
4.2.2 The Relayer Network (The Transport) . . . 12
4.2.3 The Solana Execution Hub (The Core) . . . 13
4.3 Cross-Chain Message Passing Lifecycle . . . 15
4.4 Consensus Verification in Circuits . . . 18

5 Rust Implementation & Engineering **18**
5.1 Circuit Engineering with Halo2 . . . 18
5.1.1 Circuit Configuration . . . 18
5.1.2 The Merkle Inclusion Chip . . . 19
5.2 Relayer Infrastructure . . . 21
5.2.1 Component Architecture . . . 21
5.2.2 Operational Workflow . . . 21
5.2.3 Incentive Structure . . . 21
5.2.4 Example: Relayer Processing a Deposit . . . 22

5.2.5 Concurrency Architecture . . . 22
5.3 Solana Anchor Development . . . 23
5.3.1 Instruction Context & CPIs . . . 23
5.3.2 Compute Budget Optimization . . . 24
5.4 Performance Optimization . . . 24
5.4.1 Parallel Proof Generation . . . 24
5.4.2 Batching . . . 25
5.4.3 Pipeline Architecture . . . 25

6 Tokenomics: The ILINK Standard **25**
6.1 Supply Dynamics . . . 25
6.1.1 Total Supply and Distribution . . . 25
6.1.2 Supply Schedule Mathematics . . . 26
6.2 Utility A: The Security Bond . . . 26
6.2.1 Staking Requirements . . . 26
6.2.2 Slashing Mechanism . . . 26
6.3 Utility B: Gas Abstraction & The Buy-Back-and-Burn . . . 26
6.3.1 Mechanism Overview . . . 26
6.3.2 Step-by-Step Process . . . 27
6.3.3 Economic Impact . . . 27
6.4 Mathematical Model of Deflation . . . 27
6.4.1 Burn Rate Calculation . . . 27
6.4.2 Supply Reduction Over Time . . . 27
6.4.3 Equilibrium Analysis . . . 27
6.4.4 Example Scenario . . . 27
6.5 Governance . . . 28
6.5.1 Quadratic Voting Mechanism . . . 28
6.5.2 Governance Parameters . . . 28
6.5.3 Proposal Lifecycle . . . 28
6.5.4 Example Governance Scenario . . . 28

7 Security Analysis **29**
7.1 Game Theoretic Analysis . . . 29
7.1.1 Protocol as an Extensive Game . . . 29
7.1.2 Payoff Matrix Analysis . . . 29
7.1.3 Mathematical Security Model . . . 29
7.2 Specific Attack Vectors & Mitigations . . . 30
7.2.1 Long-Range Attacks . . . 30
7.2.2 Data Availability (DA) Attacks . . . 31
7.2.3 Censorship Attacks . . . 31
7.2.4 51% Attacks on Source Chains . . . 31
7.3 Auditing & Formal Verification . . . 32
7.3.1 Multi-Layer Security Pipeline . . . 32
7.3.2 Example: Formal Verification of Merkle Proofs . . . 32
7.3.3 Continuous Security Monitoring . . . 32

8 Practical Workflows and Examples **32**
8.1 Example 1: Cross-Chain Token Swap (Ethereum → Solana) . . . 33
8.1.1 User Scenario and Requirements . . . 33
8.1.2 Step-by-Step Implementation . . . 33
8.1.3 Failure Scenarios and Recovery . . . 36
8.1.4 Performance Metrics . . . 37

8.2 Example 2: Cross-Chain Governance Vote . . . 37
8.2.1 Scenario: DAO Contract Upgrade . . . 37
8.2.2 Implementation Steps . . . 37
8.2.3 Advanced Example: Multi-Chain DeFi Strategy . . . 38
8.2.4 Developer Integration Guide . . . 38

9 Comparison with State of the Art **39**
9.1 InterLink vs. LayerZero . . . 40
9.1.1 Technical Architecture Comparison . . . 40
9.1.2 Economic Comparison . . . 40
9.1.3 Security Model Analysis . . . 40
9.2 InterLink vs. Axelar . . . 41
9.2.1 Consensus Mechanism Differences . . . 41
9.2.2 Scalability Analysis . . . 41
9.3 InterLink vs. Wormhole . . . 41
9.3.1 Guardian Model vs. Relayer Network . . . 41
9.3.2 Risk Analysis . . . 42
9.4 InterLink vs. Cosmos IBC . . . 42
9.4.1 Light Client Efficiency Comparison . . . 42
9.4.2 Technical Efficiency Gains . . . 42
9.5 Quantitative Performance Comparison . . . 43
9.5.1 Latency Analysis . . . 43
9.5.2 Cost Efficiency Analysis . . . 43
9.5.3 Security Quantification . . . 43
9.6 Unique InterLink Advantages . . . 43
9.6.1 Innovative Features . . . 43
9.6.2 Market Positioning . . . 44

10 Conclusion **44**
10.1 Future Work and Research Directions . . . 45
10.1.1 Cryptographic Enhancements . . . 45
10.1.2 Performance and Scalability Improvements . . . 45
10.1.3 Ecosystem Expansion . . . 46
10.1.4 Developer Experience and Tooling . . . 46
10.1.5 Long-Term Research Vision . . . 46
10.1.6 Implementation Timeline . . . 47
10.1.7 Research Collaboration Opportunities . . . 47
10.1.8 Risk Mitigation and Contingency Planning . . . 47

Abstract

Blockchain protocols have enabled trust-minimized value transfer and verifiable computation. Yet the rapid proliferation of Layer-1 (L1) and Layer-2 (L2) networks has produced a fragmented landscape in which users, liquidity, and application state remain isolated across heterogeneous execution environments. In practice, the popular "multi-chain" thesis has often devolved into a "siloed-chain" reality: liquidity is fractured, cross-chain workflows are high-latency, and composability is difficult to preserve. Many deployed interoperability systems rely on multisig federations or optimistic verification, introducing centralization risk and/or systemic delay. Historical bridge failures further demonstrate that trusted intermediaries frequently become the weakest link in the crypto-economic stack.

This paper presents **InterLink (ILINK)**, a protocol-level hyper-structure for cross-chain composability powered by **recursive zero-knowledge proofs (zk-SNARKs)**. Using the **halo2** proving system, InterLink enables atomic, trustless state transitions across heterogeneous ledgers without requiring honest-majority assumptions for message verification. The architecture combines a decentralized, stake-weighted **Relayer Network** with a high-throughput **Solana Execution Hub** responsible for proof verification, global message accounting, and cross-chain coordination.

We formalize the cryptographic primitives, circuit constraints, and incentive design that underpin the protocol. In particular, we show how recursive aggregation yields *amortized O(1)* on-chain verification costs for batched cross-chain intents while preserving sovereign security properties of connected chains. InterLink is therefore not merely a bridge: it is a verifiable substrate for a Unified Liquidity Layer that supports "omnichain" applications whose core logic is decoupled from any single execution environment.

Keywords: Zero-Knowledge Proofs, Recursive SNARKs, Atomic Composability, Rust Systems Engineering, Solana Anchor, Liquidity Unification, Hyper-Deflationary Tokenomics, Game-Theoretic Security, Blockchain Interoperability, Decentralized Finance (DeFi).

1 Introduction

The digital landscape is shifting from centralized, opaque databases toward decentralized, verifiable ledgers. Blockchains enable value transfer without trusted intermediaries and support smart contracts that execute deterministically. However, as the ecosystem matures, its progress is increasingly constrained by fragmentation across many execution environments. This paper motivates and specifies the **InterLink Protocol** as a response: a cross-chain interoperability layer designed to preserve security while restoring composability. We begin by reviewing the underlying primitives InterLink connects.

1.1 The Blockchain Paradigm: A Detailed Overview

At its core, a blockchain is a distributed, append-only ledger replicated across a network of computers. Unlike traditional databases controlled by a single operator (e.g., a bank, government, or cloud provider), a blockchain is maintained by a decentralized set of nodes that follow a consensus protocol. In effect, every participant can validate the same transaction history and resulting state, making unilateral manipulation both difficult to execute and easy to detect.

1.1.1 Cryptographic Foundations

The integrity of a blockchain rests on two primary cryptographic primitives: hashing and public-key cryptography.

- **Hashing:** A hash function maps an input of arbitrary length to a fixed-length digest. This mapping is deterministic and effectively one-way. In blockchains, each block typically commits to the previous block via its hash, forming a chain of commitments. If an adversary alters data in a prior block, the block hash changes and breaks all subsequent links, making tampering evident.
- **Public-Key Cryptography:** Users control accounts using keypairs: a public key (address/identifier) and a private key used to authorize actions. Transactions are signed with the private key, proving control without revealing the secret itself. This ensures that only the legitimate key holder can authorize transfers or contract interactions.

1.1.2 Consensus Mechanisms

To agree on the state of the ledger without a central authority, blockchains use consensus mechanisms.

- **Proof of Work (PoW):** Popularized by Bitcoin, PoW selects block producers by requiring participants to perform computational work. While energy-intensive, it is highly robust: attacking the network typically requires sustaining a large fraction of global hashpower.
- **Proof of Stake (PoS):** Used by networks such as Ethereum and Solana, PoS selects validators based on economic stake. Validators lock tokens as collateral, earn rewards for honest participation, and can be penalized (slashed) for provable misbehavior. PoS is more energy-efficient and can support higher throughput than PoW.

1.1.3 Smart Contracts and Turing Completeness

While Bitcoin introduced decentralized money, Ethereum extended the model to decentralized computation. Smart contracts are programs deployed on-chain that execute deterministically when invoked, enabling applications such as decentralized exchanges (DEXs), lending protocols,

and governance systems. This programmability (often described informally as "Turing completeness") is what enables rich on-chain financial and coordination systems, and it has driven the growth of Decentralized Finance (DeFi) and related ecosystems.

1.2 The Fragmentation Crisis: The Problems of Success

The success of blockchain technology has created a new bottleneck: fragmentation. As developers sought to overcome the scalability limits of early networks (such as Ethereum's low throughput and high fees), the ecosystem expanded into dozens of Layer-1 chains (Solana, Avalanche, Cosmos) and Layer-2 scaling systems (Optimism, Arbitrum, zkSync). These environments differ in execution, finality, and security, and they do not share a native, unified state.

1.2.1 The Siloed State Problem

Each blockchain behaves like a sovereign domain with its own consensus and state. As a result, an asset on Ethereum cannot natively exist on Solana. To move value, users depend on bridges that escrow assets on one chain and mint (or release) a representation on another. This design fragments liquidity into isolated pools, reducing capital efficiency and often increasing execution costs such as slippage.

1.2.2 The Security Vulnerability of Bridges

Traditional bridges have repeatedly proven to be among the highest-risk components in the ecosystem. Many rely on a trusted intermediary model: a small multisig or validator committee attests that a cross-chain event occurred. If that committee is compromised, coerced, or colludes, it can authorize fraudulent withdrawals and drain escrowed funds. This centralization risk contradicts the core ethos of blockchains and has been reinforced by repeated high-profile bridge exploits.

1.3 The Genesis of InterLink: A Proposal for Unification

We propose **InterLink** as a solution to the interoperability trilemma—scalability, security, and generality—without relying on weak trust assumptions. The trajectory is not simply "many chains," but a cross-chain-native environment in which value and application state can move and compose safely across heterogeneous runtimes. InterLink is being architected to serve as connective tissue for this environment.

1.3.1 From Trust to Truth

Existing solutions ask users to trust a third party. InterLink instead aims to reduce trust to verification. By leveraging **Zero-Knowledge Proofs (zk-SNARKs)**—specifically circuits built with the **Halo2** proving system—InterLink is designed to let one environment cryptographically validate key state-transition claims originating from another. In the intended flow, a relayer proves that a transaction occurred on a source chain, and the Solana Hub verifies the proof efficiently. This removes the need for trusted validators: if the proof is valid, the event is valid for cross-chain execution.

1.3.2 Unified Liquidity

InterLink is not envisioned solely as a message-passing protocol; it is being built as a liquidity unification layer. By using Solana as a high-performance execution hub, the protocol can coordinate cross-chain intents and route execution through a shared liquidity surface. The target UX is a single atomic action—for example, swapping a token on Ethereum for a token on Cosmos—with routing and settlement coordinated through the InterLink Hub.

1.3.3 Sovereignty and Scalability

We have chosen a modular architecture that respects the sovereignty of each chain while leveraging Solana's throughput for coordination. Proof generation happens off-chain via a decentralized network of relayers, while verification and state progression occur on-chain. This separation keeps the verification path succinct while pushing expensive computation to the edge, enabling high cross-chain throughput without congesting source or destination chains.

InterLink represents our vision for an "Internet of Blockchains"—a seamless, secure, and scalable network where value and data can flow as freely as information. We are actively developing the circuits and smart contracts described in this paper to turn this architecture into a concrete, auditable implementation.

2 Core Definitions

To ensure clarity throughout this technical compendium, we define the following core terms and actors used throughout the InterLink ecosystem.

The Hub (Solana): The global coordination layer and state manager. It is implemented on Solana and is responsible for verifying ZK proofs from connected chains and coordinating cross-chain state transitions.

The Spoke (External Chain): Any blockchain network connected to the InterLink Hub, such as Ethereum, Arbitrum, or the Cosmos Hub.

Gateway Contract: A set of smart contracts deployed on a Spoke chain that escrows assets, emits canonical events, and executes verified messages.

Relayer: An off-chain node that observes Gateway events on Spoke chains, generates zk-SNARK proofs about those events, and submits proofs and public inputs to the Hub.

zk-SNARK (Zero-Knowledge Succinct Non-Interactive Argument of Knowledge): A cryptographic proof that convinces a verifier that a statement is true without revealing the underlying private inputs beyond what is implied by correctness.

Recursive Proof: A proof that verifies another proof. In InterLink, many transaction proofs are aggregated ("folded") into a single recursive proof to reduce amortized on-chain verification costs.

Program Derived Address (PDA): A Solana-specific construct where an address is deterministically derived from a program ID and seed values. InterLink uses PDAs to represent accounts and vaults on Solana without requiring corresponding private keys.

Atomic Composability: The property that a multi-step, cross-chain operation either completes as a whole or fails as a whole, analogous to a single atomic transaction.

Liveness: The guarantee that the system continues to make progress (i.e., messages are eventually processed) even under partial faults or adversarial behavior.

Safety: The guarantee that the system never accepts an invalid state transition (e.g., minting assets without a corresponding, proven deposit).

3 Preliminaries

To provide a rigorous foundation for the InterLink Protocol, we first establish the mathematical and cryptographic primitives on which the system is built. This section summarizes the key

concepts and the concrete choices we make for curves, proving systems, and runtime environments.

3.1 The Concept of Zero-Knowledge

Before delving into the technicalities of SNARKs, it is helpful to build intuition for what a zero-knowledge proof guarantees and what it explicitly does not.

3.1.1 Intuition: The Ali Baba Cave

Consider a cave shaped like a loop with a locked door that blocks one of the paths. The door opens only if you know a secret password.

- **Prover (Peggy):** Wants to prove she knows the password without revealing it.
- **Verifier (Victor):** Wants to verify Peggy knows the password.

The Protocol: 1. Peggy enters the cave and randomly chooses path A or path B while Victor waits outside. 2. Victor then enters and requests that Peggy exit via path A (or path B). 3. If Peggy knows the password, she can always comply by opening the door if needed. 4. If Peggy does not know the password, she has a 50% chance of being on the wrong side and failing the challenge.

Repeating this test n times reduces the probability of cheating to 2^{-n}. For example, with $n = 40$, the cheating probability is negligible. Victor becomes convinced that Peggy knows the password, yet learns nothing about the password itself.

3.2 zk-SNARKs: A Technical Deep Dive

InterLink utilizes **zk-SNARKs** (Zero-Knowledge Succinct Non-Interactive Arguments of Knowledge). The acronym captures five key properties:

Zero-Knowledge: The verifier learns nothing about the prover's private inputs (the witness) beyond the fact that the statement is true. In InterLink, this means the Hub can learn that "Transaction X occurred on Ethereum" without ingesting Ethereum's full state or history.

Succinct: Proofs are compact and efficient to verify. In practice, proof sizes can be constant or logarithmic in the statement size, and verification can complete in milliseconds. This property is essential for on-chain verification, where storage and compute are constrained.

Non-Interactive: The prover produces a proof once, and anyone can verify it later without additional interaction. This is typically achieved via the Fiat–Shamir heuristic, which replaces the verifier's random challenges with hash-derived challenges.

Argument: The soundness guarantee holds against computationally bounded adversaries (i.e., those unable to break the underlying hardness assumptions within feasible resources). For blockchain settings, this is the relevant security model.

of Knowledge: The proof implies that the prover actually *knows* a valid witness, not merely that one exists in principle.

3.3 Elliptic Curve Cryptography (ECC)

InterLink selects specific elliptic curves to balance practical on-chain verification (especially on the EVM) with efficient recursive proof composition inside Halo2.

3.3.1 BN254 (Alt-Bn128)

For interoperability with the Ethereum Virtual Machine (EVM), we utilize the BN254 curve. BN254 is pairing-friendly and defined over a finite field $\mathbb{F}_q$, enabling efficient bilinear pairings $e : \mathbb{G}_1 \times \mathbb{G}_2 \to \mathbb{G}_T$. These pairings are a core primitive for verifying KZG commitments on-chain.

$$y^2 = x^3 + 3 \mod q$$

Ethereum includes dedicated precompiled contracts (0x06, 0x07, 0x08) for BN254 operations, which makes verification substantially more gas-efficient than generic elliptic-curve arithmetic.

3.3.2 Pallas and Vesta (The Pasta Curves)

For recursive proof generation inside the Relayer Network, we employ the Pallas and Vesta curves (the "Pasta" curves). They form a cycle: the scalar field of Pallas is the base field of Vesta, and vice versa.

- **Pallas:** $y^2 = x^3 + 5$
- **Vesta:** $y^2 = x^3 + 5$ (over a different field)

This cycle property allows a proof generated over one curve to be verified efficiently inside a circuit over the other, avoiding the heavy overhead of non-native ("wrong-field") arithmetic. This choice is central to InterLink's Halo2 recursion strategy.

3.4 Polynomial Commitment Schemes (PCS)

A polynomial commitment scheme (PCS) allows a prover to commit to a polynomial $P(X)$ and later prove evaluations of the form $P(z) = y$ without revealing the entire polynomial.

3.4.1 KZG (Kate-Zaverucha-Goldberg)

KZG is used for the final "outer" proof submitted to Ethereum.

- **Pros:** Constant size proofs (48 bytes), constant time verification.
- **Cons:** Requires a Trusted Setup (Structured Reference String).

3.4.2 IPA (Inner Product Argument)

IPA is used for internal "inner" proofs inside the recursive proving pipeline.

- **Pros:** Transparent (no trusted setup), relies only on discrete log hardness.
- **Cons:** $O(\log n)$ verification time (slower than KZG).

InterLink uses a hybrid approach: IPA for recursion/accumulation, then a final wrap (e.g., into KZG or Groth16) to minimize on-chain verification cost.

3.5 Solana Runtime (Sealevel)

Solana's runtime model (Sealevel) differs fundamentally from EVM-based chains.

- **Stateless Execution:** Programs (smart contracts) are stateless; state is stored in separate "Accounts."
- **Parallelism:** Transactions specify all accounts they will read or write upfront. This allows the runtime to schedule non-overlapping transactions in parallel.

- **PDAs (Program Derived Addresses):** Addresses deterministically derived from a program ID and seeds (e.g., `hash("user_vault", user_pubkey)`). This allows us to map a user's Ethereum address to a specific Solana account without needing a private key for that account.

4 System Architecture

4.1 The Hub-and-Spoke Topology

InterLink employs a hub-and-spoke network topology to minimize complexity and maximize scalability. This architectural pattern consists of a central coordination point (the hub) with multiple peripheral nodes (the spokes) that connect through the hub.

4.1.1 Detailed Topology Description

In the InterLink hub-and-spoke model:

- **The Hub (Solana):** Serves as the global clearinghouse and state manager, implemented on the Solana blockchain. All cross-chain messages are routed through this central hub, which verifies zk-SNARK proofs from connected chains and coordinates cross-chain state transitions.
- **The Spokes (External Chains):** Represent individual blockchain networks connected to the InterLink Hub, such as Ethereum, Arbitrum, Optimism, Cosmos Hub, and Sui. Each spoke maintains its own Gateway contract for interaction with the hub.

This design yields O(N) connection complexity, far superior to the $O(N^2)$ complexity of pairwise bridges. Adding a new chain requires only establishing a connection to the Solana Hub, rather than creating N-1 new bridge connections.

4.1.2 Topology Advantages and Trade-offs

Advantages:

- **Scalability:** New chains can be added without modifying existing spoke implementations, enabling rapid ecosystem expansion.
- **Consistency:** All cross-chain operations flow through a single verification layer, ensuring uniform security guarantees.
- **Efficiency:** Shared liquidity and routing logic reduce redundant implementations across chains.
- **Simplicity:** Centralized coordination simplifies protocol upgrades and governance decisions.

Trade-offs:

- **Single Point of Coordination:** While not a single point of failure (due to cryptographic verification), the hub becomes a critical coordination point.
- **Hub Performance Dependency:** Cross-chain throughput is limited by the hub's capacity, though Solana's high performance mitigates this concern.

4.1.3 Example: Cross-Chain Message Routing

Consider a message from Ethereum to Arbitrum: 1. Message originates at Ethereum Gateway → Relayers observe and prove → Proof submitted to Solana Hub 2. Solana Hub verifies proof → Routes message to Arbitrum Gateway → Arbitrum Gateway executes 3. If successful, no additional routing needed; if failed, refund message routes back through hub

This centralized routing enables sophisticated features like atomic multi-chain operations and unified liquidity management.

4.2 Detailed Component Breakdown

4.2.1 Source Chain Gateway (The Spoke)

The Gateway contract represents InterLink's presence on each connected blockchain. It serves as the secure interface between the external chain and the InterLink Hub, handling asset custody, event emission, and verified message execution.

Core Functions

Asset Custody: The Gateway maintains a secure vault for escrowed assets. When users initiate cross-chain transfers, their tokens are locked in this vault until the destination chain confirms successful execution.

Event Emission: The Gateway emits standardized events that Relayers monitor. These events contain all necessary information for proof generation, including:

- Transaction hash and block number
- Asset amount and recipient address
- Destination chain identifier
- Message payload hash

Message Ingestion: Upon receiving verified proofs from the Hub, the Gateway executes the intended operations, such as releasing escrowed assets or executing arbitrary logic.

Security Architecture

Safety Module: Each Gateway includes a Guardian role controlled by the InterLink DAO. In emergency situations, the Guardian can:

- Pause all Gateway operations
- Authorize emergency withdrawals
- Update contract parameters

Replay Protection: Gateways maintain sequence numbers and message hashes to prevent duplicate executions, ensuring each cross-chain message is processed exactly once.

Example: Ethereum Gateway Operation

Consider Alice depositing 1 ETH to bridge to Solana:

```
function deposit(
    address recipient,
    uint256 amount,
```

```
    uint16 destinationChain
) external payable {
    require(msg.value == amount, "Incorrect ETH amount");

    // Lock ETH in vault
    vault.deposit{value: amount}();

    // Emit canonical event for Relayers
    emit MessagePublished(
        sequenceNumber: ++seqNum,
        sender: msg.sender,
        recipient: recipient,
        amount: amount,
        destinationChain: destinationChain,
        payload: abi.encode(recipient, amount)
    );
}
```

Listing 1: Ethereum Gateway Deposit Function

When the Hub verifies the proof and sends confirmation, the Gateway on Solana (destination) mints wrapped ETH to Alice's address.

4.2.2 The Relayer Network (The Transport)

The Relayer Network forms the critical transport layer of InterLink, consisting of a decentralized set of off-chain nodes that observe, prove, and relay cross-chain messages. These nodes ensure censorship-resistant message passing while maintaining economic incentives for honest operation.

Component Architecture

Listener Component: Maintains persistent WebSocket connections to archive nodes of supported chains. The Listener:

- Subscribes to Gateway contract events using standardized filters
- Buffers events in memory for processing
- Handles connection failures and chain reorganizations
- Forwards events to the Prover component via internal channels

Prover Engine: The computational core that generates zk-SNARK proofs. Built with the Halo2 proving system, it:

- Fetches complete transaction data and Merkle proofs from archive nodes
- Constructs Halo2 circuits for transaction inclusion and consensus verification
- Generates succinct proofs that compress gigabytes of chain data into 100 bytes
- Aggregates multiple proofs into recursive structures for efficiency

Submitter Component: Handles interaction with the Solana Hub:

- Monitors mempool for optimal gas conditions
- Batches proofs for cost amortization
- Implements retry logic for failed submissions
- Tracks proof confirmations and collects rewards

Operational Workflow

A Relayer processes a cross-chain message through these stages:

1. **Event Detection:** Listener detects Gateway deposit event 2. **Finality Waiting:** Waits for source chain finality (12-15 minutes on Ethereum) 3. **Witness Collection:** Fetches Merkle proof and block headers from archive node 4. **Proof Generation:** Constructs and solves Halo2 circuits 5. **Submission:** Posts proof to Solana Hub with optimal timing 6. **Reward Collection:** Receives ILINK rewards for successful relay

Incentive Structure

Relayers earn ILINK tokens through a dual mechanism:

- **Base Rewards:** Fixed ILINK payment per successful message relay
- **Burn Participation:** Share of tokens burned from user fees
- **Staking Requirement:** Must stake 100,000 ILINK minimum to participate
- **Slashing:** Invalid proofs result in stake reduction and burns

Example: Relayer Processing a Deposit

Consider Bob's Relayer processing Alice's ETH deposit:

```
async fn process_deposit_event(event: DepositEvent) {
    // 1. Wait for finality
    wait_for_finality(event.block_number, Chain::Ethereum).await?;

    // 2. Fetch witness data
    let proof = eth_client.get_proof(event.tx_hash, event.slot).await?;
    let headers = eth_client.get_block_headers(event.block_number).await?;

    // 3. Generate proof
    let circuit = DepositCircuit::new(event, proof, headers);
    let (proof, public_inputs) = generate_proof(circuit)?;

    // 4. Submit to Solana
    let tx = solana_client.submit_proof(proof, public_inputs).await?;

    // 5. Monitor and claim rewards
    wait_for_confirmation(tx).await?;
    claim_relayer_rewards(event.sequence).await?;
}
```

Listing 2: Relayer Event Processing Flow

This decentralized network ensures no single entity can censor cross-chain messages, while economic incentives align Relayers with protocol success.

4.2.3 The Solana Execution Hub (The Core)

The Solana Execution Hub serves as InterLink's central nervous system, implemented as an Anchor program on Solana. It coordinates all cross-chain operations, verifies proofs, manages global state, and executes complex multi-chain logic.

Core Components

Verifier Contract: The cryptographic heart of the Hub, containing pre-deployed verification keys for all supported proof circuits. It performs:

- BN254 pairing checks for KZG proofs from EVM chains
- Custom verification logic for IPA-based recursive proofs
- Batch verification of multiple aggregated proofs

State Registry: A comprehensive mapping system that tracks cross-chain message state:

- `chain_id` → `sequence_number`: Tracks latest processed message per chain
- `message_hash` → `status`: Records execution status (pending, executed, failed)
- `user_address` → `vault_pda`: Maps user addresses to their Solana vault accounts

Liquidity Management Engine: Implements sophisticated AMM logic for cross-chain swaps:

- Concentrated liquidity pools with dynamic fee tiers
- Multi-hop routing across different token pairs
- Slippage protection and price impact calculations
- Integration with Jupiter aggregator for optimal execution

Message Dispatcher: Handles outbound cross-chain communications:

- Queues messages for destination chains
- Generates proofs for reverse-direction messages (refunds/failures)
- Coordinates with Relayer Network for message delivery

Verification Process

When a Relayer submits a proof to the Hub, the verification follows this sequence:

1. **Input Validation:** Check proof format and public inputs 2. **Circuit Verification:** Execute elliptic curve operations to validate the SNARK 3. **State Transition:** Update sequence numbers and message status 4. **Execution Trigger:** Invoke destination logic (minting, swapping, etc.)

Example: Hub Processing a Cross-Chain Swap

Consider Alice swapping 1 ETH on Ethereum for USDC on Solana:

```
#[derive(Accounts)]
pub struct ProcessCrossChainSwap<'info> {
    #[account(mut)]
    pub verifier: Account<'info, VerifierState>,
    #[account(mut)]
    pub user_vault: Account<'info, TokenAccount>,
    #[account(mut)]
    pub liquidity_pool: Account<'info, LiquidityPool>,
    pub token_program: Program<'info, Token>,
}

pub fn process_swap(
    ctx: Context<ProcessCrossChainSwap>,
    proof: Vec<u8>,
```

```
    public_inputs: PublicInputs,
    amount_in: u64,
    min_amount_out: u64
) -> Result<()> {
    // 1. Verify the zk-SNARK proof
    let is_valid = verifier::verify_proof(&proof, &public_inputs)?;
    require!(is_valid, ErrorCode::InvalidProof);

    // 2. Update sequence number for Ethereum
    let mut verifier = &mut ctx.accounts.verifier;
    require!(
        public_inputs.sequence > verifier.last_eth_sequence,
        ErrorCode::OutOfOrderMessage
    );
    verifier.last_eth_sequence = public_inputs.sequence;

    // 3. Mint wrapped ETH to temporary vault
    token::mint_to(
        ctx.accounts.mint_weth.clone(),
        ctx.accounts.temp_vault.to_account_info(),
        amount_in
    )?;

    // 4. Execute swap through liquidity pool
    let swap_result = execute_swap(
        &ctx.accounts.liquidity_pool,
        amount_in,
        min_amount_out,
        ctx.accounts.user_vault.to_account_info()
    )?;

    // 5. Emit success event
    emit!(SwapExecuted {
        user: ctx.accounts.user_vault.owner,
        amount_in,
        amount_out: swap_result.amount_out,
        source_chain: Chain::Ethereum,
    });

    Ok(())
}
```

Listing 3: Solana Hub Verification and Execution

This Hub architecture enables InterLink to function as a programmable, high-throughput coordination layer for the entire cross-chain ecosystem, supporting everything from simple token transfers to complex DeFi operations.

4.3 Cross-Chain Message Passing Lifecycle

To fully appreciate the system, we outline the end-to-end lifecycle of a cross-chain message.

Phase 1: Initiation and Event Emission

Inbound Trigger (User Action):

- User calls Gateway contract function (e.g., `deposit()` on Ethereum)
- Contract validates inputs and locks assets in vault
- Contract emits canonical `MessagePublished` event with:

  - Sequence number (for ordering)
  - Source/destination chain IDs
  - Sender/recipient addresses
  - Asset amount and type
  - Payload hash for integrity

Event Structure Example:

```
event MessagePublished(
    uint64 indexed sequenceNumber,
    address indexed sender,
    address recipient,
    uint256 amount,
    uint16 sourceChain,
    uint16 destinationChain,
    bytes32 payloadHash
);
```

Listing 4: Solidity Event Definition

Phase 2: Finality and Witness Collection

Block Finality (Safety Buffer):

- Relayers wait for economic finality before processing
- Ethereum L1: 12-15 minutes (finalized epoch)
- Ethereum L2s (Arbitrum/Optimism): Wait for batch posting to L1
- Cosmos chains: Wait for block commitment in light client

Witness Extraction (Data Gathering):

- Query archive node for complete transaction data
- Fetch Merkle proof from transaction receipt to block header
- Retrieve block header and consensus proof (validator signatures)
- Store all data as private inputs for circuit construction

Phase 3: Proof Generation and Submission

Proof Composition (Computation):

- *Circuit 1 (Transaction Inclusion):* Proves transaction exists in block
  - Verifies Merkle path from transaction to receipts root
  - Confirms transaction format and signature validity
- *Circuit 2 (Consensus Verification):* Proves block finality
  - Validates validator signatures (>2/3 for PoS, >50% for PoW)
  - Confirms block header integrity
- *Circuit 3 (Aggregation):* Combines proofs into single recursive structure

  - Uses Halo2 recursion for proof composition
  - Reduces verification cost from O(n) to O(1)

Solana Submission (Handover):

- Relayer submits proof + public inputs to Hub contract
- Transaction includes proof bytes, sequence number, block hash
- Solana validates proof and updates global state

Phase 4: Verification and Execution

On-Chain Verification (Check):

- Hub contract performs elliptic curve pairing operations
- Validates proof against pre-deployed verification key
- Confirms sequence number ordering (prevents replay)
- Updates state registry with message status

Execution (Result):

- If verification succeeds: Execute intended operation
  - Mint wrapped tokens on destination
  - Execute smart contract calls
  - Process liquidity pool swaps
- Emit success events for monitoring and analytics

Error Handling and Edge Cases

Proof Rejection Scenarios:

- Invalid cryptographic proof → Transaction reverts, Relayer slashed
- Out-of-order sequence number → Message queued for later processing
- Insufficient finality → Proof rejected until finality reached

Execution Failure Recovery:

- If destination execution fails (e.g., slippage too high):
  - Hub marks message as FAILED
  - Generates refund message for source chain
  - Relayers prove failure and unlock original assets

Performance Characteristics

Latency Breakdown:

- Source finality: 1-15 minutes (chain-dependent)
- Proof generation: 10-60 seconds (circuit complexity)

- Solana confirmation: 400ms (6-8 blocks)
- Total end-to-end: 2-16 minutes

Cost Amortization:

- Single proof verification: 300k gas on Solana
- Batch of 100 proofs: 3k gas per proof (99% reduction)
- Cross-chain fee: 0.01-0.1% of transaction value

This lifecycle ensures atomic, verifiable cross-chain operations with strong safety guarantees and economic incentives for honest participation.

4.4 Consensus Verification in Circuits

A distinctive InterLink feature is "Light Client in a Circuit," where we verify not just transaction signatures but the source chain's full consensus.

- **Ethereum (Sync Committee):** The circuit verifies BLS signatures from the current Sync Committee (512 validators) to confirm block header validity.
- **Cosmos (Tendermint):** The circuit verifies Ed25519 signatures from the validator set (voting power $> 2/3$).

This approach ensures InterLink inherits the complete security of the connected chain's consensus, rather than relying on a small multisig.

5 Rust Implementation & Engineering

The InterLink engineering approach emphasizes safety, performance, and maintainability. We use Rust throughout the stack—from off-chain Relayers to on-chain Solana programs—to guarantee memory safety and type correctness.

5.1 Circuit Engineering with Halo2

The core of InterLink lies in its zk-SNARK circuits. We adopt the **halo2-ce** (Community Edition) crate for its flexibility and native KZG commitment scheme support.

5.1.1 Circuit Configuration

A Plonk-ish circuit is structured as a matrix of columns and rows. We define a custom `InterlinkConfig` struct to manage these resources.

```rust
#[derive(Clone, Debug)]
pub struct InterlinkConfig {
    // Advice columns (Witnesses): Private inputs like secret keys or Merkle paths
    pub advice: [Column<Advice>; 5],
    // Instance columns (Public Inputs): Root hash, Nullifier, etc.
    pub instance: Column<Instance>,
    // Fixed columns (Constants): Selector bits, lookup tables
    pub fixed: [Column<Fixed>; 2],
    // Selectors to toggle gates
    pub s_hash: Selector,
    pub s_verify: Selector,
}

```

```rust
impl InterlinkConfig {
    pub fn configure(meta: &mut ConstraintSystem<F>) -> Self {
        let advice = [0; 5].map(|_| meta.advice_column());
        let instance = meta.instance_column();
        let fixed = [0; 2].map(|_| meta.fixed_column());
        let s_hash = meta.selector();

        meta.enable_equality(instance);
        for c in &advice { meta.enable_equality(*c); }

        // Define a Custom Gate: Poseidon Hash Round
        meta.create_gate("poseidon_round", |meta| {
            let s = meta.query_selector(s_hash);
            let a = meta.query_advice(advice[0], Rotation::cur());
            let b = meta.query_advice(advice[1], Rotation::cur());
            let out = meta.query_advice(advice[2], Rotation::cur());

            // Constraint: out = (a + b)^5 (simplified S-box)
            vec![s * (out - (a + b).pow([5]))]
        });

        Self { advice, instance, fixed, s_hash, s_verify: meta.selector() }
    }
}
```

Listing 5: Halo2 Circuit Configuration

5.1.2 The Merkle Inclusion Chip

We encapsulate logic into "Chips." The `MerkleChip` handles verification that a leaf exists in a tree, taking a `Path` (witness) and a `Root` (public input) to enforce the hashing path.

Merkle Tree Structure:

- Binary tree where each non-leaf node is hash of its children
- Leaf nodes contain transaction data or state commitments
- Root represents commitment to entire tree state
- Path from leaf to root proves inclusion without revealing other leaves

Chip Implementation Details: The MerkleChip processes the path iteratively, computing hash at each level:

1. Start with leaf value L
2. For each path level i:
    - If direction bit I = 0 (left): hash = H(L, P)
    - If direction bit I = 1 (right): hash = H(P, L)
3. Final hash equals root commitment

```rust
pub struct MerkleChip<F: Field> {
    config: MerkleConfig,
}

impl<F: Field> MerkleChip<F> {
    pub fn construct(config: MerkleConfig) -> Self {
        Self { config }
```

```rust
    }

    pub fn verify_inclusion(
        &self,
        mut layouter: impl Layouter<F>,
        path: &[Value<F>],  // Merkle path elements
        indices: &[Value<F>], // Left/right indicators
        leaf: Value<F>,     // Leaf to verify
        root: Value<F>,     // Expected root
    ) -> Result<(), Error> {
        layouter.assign_region(
            || "merkle inclusion proof",
            |mut region| {
                let mut current = leaf;

                for (i, (sibling, is_left)) in path.iter().zip(indices).enumerate() {
                    // Assign path element to advice column
                    region.assign_advice(
                        || format!("path element {}", i),
                        self.config.advice[0],
                        i,
                        || *sibling,
                    )?;

                    // Compute hash: if is_left { hash(current, sibling) } else { hash(sibling, current) }
                    let hash_result = self.poseidon_hash(
                        &mut region,
                        current,
                        *sibling,
                        *is_left,
                        i,
                    )?;

                    current = hash_result;
                }

                // Final constraint: computed root == expected root
                region.constrain_equal(current, root)?;

                Ok(())
            },
        )
    }

    fn poseidon_hash(
        &self,
        region: &mut Region<'_, F>,
        left: Value<F>,
        right: Value<F>,
        is_left: Value<F>,
        row: usize,
    ) -> Result<Value<F>, Error> {
        // Implementation of Poseidon hash constraints
        // This would include the full Poseidon permutation
        // with proper constraint enforcement
        unimplemented!("Poseidon hash implementation")
    }
}
```

Listing 6: Merkle Inclusion Chip Implementation

5.2 Relayer Infrastructure

The Relayer Network forms the critical transport layer of InterLink, consisting of a decentralized set of off-chain nodes that observe, prove, and relay cross-chain messages. These nodes ensure censorship-resistant message passing while maintaining economic incentives for honest operation.

5.2.1 Component Architecture

Listener Component: Maintains persistent WebSocket connections to archive nodes of supported chains. The Listener:

- Subscribes to Gateway contract events using standardized filters
- Buffers events in memory for processing
- Handles connection failures and chain reorganizations
- Forwards events to the Prover component via internal channels

Prover Engine: The computational core that generates zk-SNARK proofs. Built with the Halo2 proving system, it:

- Fetches complete transaction data and Merkle proofs from archive nodes
- Constructs Halo2 circuits for transaction inclusion and consensus verification
- Generates succinct proofs that compress gigabytes of chain data into 100 bytes
- Aggregates multiple proofs into recursive structures for efficiency

Submitter Component: Handles interaction with the Solana Hub:

- Monitors mempool for optimal gas conditions
- Batches proofs for cost amortization
- Implements retry logic for failed submissions
- Tracks proof confirmations and collects rewards

5.2.2 Operational Workflow

A Relayer processes a cross-chain message through these stages:

1. **Event Detection:** Listener detects Gateway deposit event 2. **Finality Waiting:** Waits for source chain finality (12-15 minutes on Ethereum) 3. **Witness Collection:** Fetches Merkle proof and block headers from archive node 4. **Proof Generation:** Constructs and solves Halo2 circuits 5. **Submission:** Posts proof to Solana Hub with optimal timing 6. **Reward Collection:** Receives ILINK rewards for successful relay

5.2.3 Incentive Structure

Relayers earn ILINK tokens through a dual mechanism:

- **Base Rewards:** Fixed ILINK payment per successful message relay
- **Burn Participation:** Share of tokens burned from user fees
- **Staking Requirement:** Must stake 100,000 ILINK minimum to participate
- **Slashing:** Invalid proofs result in stake reduction and burns

5.2.4 Example: Relayer Processing a Deposit

Consider Bob's Relayer processing Alice's ETH deposit:

```
async fn process_deposit_event(event: DepositEvent) {
    // 1. Wait for finality
    wait_for_finality(event.block_number, Chain::Ethereum).await?;

    // 2. Fetch witness data
    let proof = eth_client.get_proof(event.tx_hash, event.slot).await?;
    let headers = eth_client.get_block_headers(event.block_number).await?;

    // 3. Generate proof
    let circuit = DepositCircuit::new(event, proof, headers);
    let (proof, public_inputs) = generate_proof(circuit)?;

    // 4. Submit to Solana
    let tx = solana_client.submit_proof(proof, public_inputs).await?;

    // 5. Monitor and claim rewards
    wait_for_confirmation(tx).await?;
    claim_relayer_rewards(event.sequence).await?;
}
```

Listing 7: Relayer Event Processing Flow

5.2.5 Concurrency Architecture

We employ `tokio` for asynchronous runtime management. The design follows a producer-consumer pattern:

Architecture Overview:

- **Event Watcher (Producer):** Monitors Ethereum logs via WebSocket (`ethers-rs`), pushing events to a bounded `mpsc` channel.
- **Proof Generator (Consumer):** Processes events, retrieves witness data (Merkle proofs) from archive nodes, and executes the CPU-intensive proving algorithm. This operates in a separate `rayon` thread pool to prevent blocking the async runtime.
- **Transaction Manager:** Queues completed proofs and manages Solana transaction lifecycle, including retries and priority fees.

Why This Architecture?

- **Separation of Concerns:** Network I/O (async) vs. computation (blocking)
- **Resource Efficiency:** CPU-bound proving doesn't starve network operations
- **Fault Tolerance:** Channel-based communication with bounded buffers
- **Scalability:** Multiple proof generators can process events in parallel

```
#[derive(Clone)]
pub struct Relayer {
    event_rx: mpsc::Receiver<DepositEvent>,
    proof_tx: mpsc::Sender<ProofPackage>,
    solana_client: Arc<SolanaClient>,
}

impl Relayer {
    pub async fn run(self) -> Result<()> {
```

```rust
        // Spawn proof generation workers
        let mut workers = vec![];
        for i in 0..num_cpus::get() {
            let worker = ProofWorker::new(
                self.event_rx.clone(),
                self.proof_tx.clone(),
            );
            workers.push(tokio::spawn(async move {
                worker.run().await
            }));
        }

        // Main submission loop
        while let Some(proof_pkg) = self.proof_tx.recv().await {
            self.submit_proof(proof_pkg).await?;
        }

        Ok(())
    }

    async fn submit_proof(&self, pkg: ProofPackage) -> Result<()> {
        // Gas price monitoring
        let gas_price = self.solana_client.get_recent_prioritization_fees().
    await?;

        // Submit with optimal priority fee
        let tx = Transaction::new_with_payer(
            &[interlink_instruction::verify_and_execute(
                pkg.proof,
                pkg.public_inputs,
                pkg.amount,
            )],
            Some(&self.fee_payer.pubkey()),
        );

        self.solana_client.send_and_confirm_transaction(&tx).await?;
        Ok(())
    }
}
```

Listing 8: Relayer Concurrency Architecture

This decentralized network ensures no single entity can censor cross-chain messages, while economic incentives align Relayers with protocol success.

5.3 Solana Anchor Development

The verification layer is built using the Anchor framework, which provides safety checks and serialization for Solana programs.

5.3.1 Instruction Context & CPIs

When a proof is verified, the program must mint tokens, requiring a Cross-Program Invocation (CPI) to the SPL Token Program.

```rust
#[derive(Accounts)]
pub struct VerifyAndMint<'info> {
    #[account(mut)]
    pub payer: Signer<'info>,
    #[account(mut, seeds = [b"mint_authority"], bump)]
    pub mint_authority: SystemAccount<'info>,
```

```
    #[account(mut)]
    pub recipient: Account<'info, TokenAccount>,
    #[account(mut)]
    pub token_mint: Account<'info, Mint>,
    pub token_program: Program<'info, Token>,
}

pub fn handler(ctx: Context<VerifyAndMint>, amount: u64) -> Result<()> {
    // ... Verification Logic ...

    // Mint Tokens via CPI
    let seeds = &[b"mint_authority".as_ref(), &[ctx.bumps.mint_authority]];
    let signer = &[&seeds[..]];

    let cpi_ctx = CpiContext::new_with_signer(
        ctx.accounts.token_program.to_account_info(),
        token::MintTo {
            mint: ctx.accounts.token_mint.to_account_info(),
            to: ctx.accounts.recipient.to_account_info(),
            authority: ctx.accounts.mint_authority.to_account_info(),
        },
        signer,
    );
    token::mint_to(cpi_ctx, amount)?;
    Ok(())
}
```

Listing 9: Anchor CPI for Minting

5.3.2 Compute Budget Optimization

Solana enforces a strict compute unit (CU) limit (200k per instruction, 1.4M per transaction). Verifying a pairing check is computationally expensive.

- **Strategy:** We use the `ed25519_program` for signature verification where possible, alongside highly optimized BPF assembly for the pairing engine.
- **Address Lookup Tables (LUTs):** We employ LUTs to load more accounts in a single transaction, enabling verification to span multiple instructions if needed.

5.4 Performance Optimization

To achieve sub-second latency for high-frequency bridging, we deploy several optimization techniques.

5.4.1 Parallel Proof Generation

Zero-Knowledge Proof generation involves intensive mathematical computations, primarily Fast Fourier Transforms (FFTs) and Multi-Scalar Multiplications (MSMs). These are "embarrassingly parallel." We leverage the `rayon` crate to spawn a thread pool matching the number of physical CPU cores.

```
// Pseudo-code for parallel MSM
let scalars = ...;
let points = ...;
let result = rayon::join(
    || msm(&scalars[0..n/2], &points[0..n/2]),
    || msm(&scalars[n/2..n], &points[n/2..n])
);
```

Listing 10: Parallel MSM Example

This reduces proving time T from O(N) to O(N/C), where C is the core count.

5.4.2 Batching

Verifying a single proof on-chain incurs a fixed gas cost (e.g., 300k gas on EVM). By aggregating N transactions into one batch proof, we amortize this cost.

$$\text{Cost per Tx} = \frac{\text{Verification Cost}}{N} + \text{Marginal Data Cost}$$

For N=100 transactions, the per-user verification cost drops by 99%.

5.4.3 Pipeline Architecture

The Relayer node uses a staged pipeline for maximum throughput.

- **Stage 1 (Fetch):** Asynchronously retrieves witness data for Block i+2.
- **Stage 2 (Prove):** Generates the SNARK for Block i+1 using CPU resources.
- **Stage 3 (Submit):** Transmits the computed proof for Block i to Solana via RPC.

This ensures network I/O does not impede CPU-intensive tasks.

6 Tokenomics: The ILINK Standard

The ILINK token serves as the economic engine of the InterLink ecosystem. It captures value from cross-chain activity while securing the network through stake-weighted incentives.

6.1 Supply Dynamics

6.1.1 Total Supply and Distribution

- **Total Supply:** 1,000,000,000 (1 Billion) ILINK tokens
- **Emission Schedule:** Halving every 2 years, mirroring Bitcoin's approach to ensure long-term scarcity and predictable supply reduction
- **Initial Distribution:**
  - 20% Team & Advisors (4-year vesting, 1-year cliff) - Ensures long-term commitment
  - 15% Investors (3-year vesting) - Supports ecosystem development funding
  - 30% Ecosystem Growth (Grants, Liquidity Mining) - Incentivizes early adoption and development
  - 35% Community Treasury (DAO controlled) - Provides governance funds and protocol reserves

6.1.2 Supply Schedule Mathematics

The emission follows a geometric decay similar to Bitcoin's 4-year halving cycle:

$$S(t) = S_0 \times (1 - r)^{t/4}$$

Where:

- $S(t)$ = Supply emitted by year t
- S_0 = Initial annual emission
- r = Reduction factor (50% every 2 years)

This creates a predictable deflationary schedule that rewards early participation while maintaining long-term scarcity.

6.2 Utility A: The Security Bond

6.2.1 Staking Requirements

Relayers must stake ILINK to participate in the network, creating economic skin in the game:

$$\text{Stake}_{\text{min}} = 100,000 \text{ ILINK}$$

This minimum stake ensures Relayers have sufficient economic incentive to maintain honest operation.

6.2.2 Slashing Mechanism

If a Relayer submits an invalid proof (caught by the Verifier), their stake is slashed:

$$\text{SlashAmount} = \text{Stake} \times 50\%$$

Slashing Conditions:

- Invalid cryptographic proof
- Double-submission of the same message
- Submission after finality timeout
- Consensus violation (e.g., wrong validator signatures)

The slashed funds are permanently burned, instantly reducing total supply and creating a strong economic deterrent against malicious behavior.

6.3 Utility B: Gas Abstraction & The Buy-Back-and-Burn

6.3.1 Mechanism Overview

Users do not need to hold ILINK to use the bridge; they pay fees in the source chain's native token (e.g., ETH). The protocol automatically converts these fees into ILINK and burns a portion.

6.3.2 Step-by-Step Process

1. User pays 0.01 ETH fee for a cross-chain transaction
2. Protocol automatically swaps 0.01 ETH for ILINK on a DEX (e.g., Uniswap, Orca)
3. **40% of this ILINK is permanently burned**
4. 60% is distributed to Relayers as performance-based rewards

6.3.3 Economic Impact

This creates a self-reinforcing flywheel:

Increased Usage → Increased Buy Pressure → Increased Token Value → Reduced Effective Fees

As ILINK price increases, the same ETH fee buys fewer ILINK tokens to burn, effectively reducing the cost burden on users while increasing scarcity.

6.4 Mathematical Model of Deflation

6.4.1 Burn Rate Calculation

Let V be daily cross-chain transfer volume in USD. Let f be the fee rate (e.g., 0.1%). Let P be the ILINK price in USD. The daily tokens burned, B, equals:

$$B = \frac{V \times f \times 0.40}{P}$$

6.4.2 Supply Reduction Over Time

The total supply S(t) after time t follows:

$$S(t) = S_0 - \int_0^t B(\tau)d\tau$$

Where B(t) increases with transaction volume and decreases as P increases.

6.4.3 Equilibrium Analysis

In equilibrium, the burn rate balances new emissions:

$$\frac{dS}{dt} = E(t) - B(t)$$

Where E(t) is the emission rate (decaying geometrically) and B(t) is the burn rate (increasing with adoption).

When volume V grows and price P stabilizes, B(t) accelerates, creating deflationary pressure that may drive P upward, creating a self-stabilizing feedback loop.

6.4.4 Example Scenario

Assume:

- Daily volume V = $10M
- Fee rate f = 0.1% (=$10,000 daily fees)

- ILINK price P = \$1
- Burn percentage = 40% (=\$4,000 worth of ILINK)

Daily burn = \$4,000 / \$1 = 4,000 ILINK tokens burned per day.

If volume grows to \$100M with P = \$2: Daily burn = (\$100M × 0.001 × 0.4) / \$2 = \$20,000 / \$2 = 10,000 ILINK tokens burned per day.

The burn rate doubles despite the price increase, creating strong deflationary pressure.

6.5 Governance

6.5.1 Quadratic Voting Mechanism

ILINK holders govern the protocol via the InterLink DAO using quadratic voting to prevent plutocracy (whale dominance). The cost of votes follows:

$$\text{Cost} = (\text{Votes})^2$$

This ensures that:

- Small holders have disproportionate influence relative to large holders
- Proposal passage requires broad consensus
- Sybil attacks become economically prohibitive

6.5.2 Governance Parameters

- **Fee Rate Adjustment:** DAO can modify f (fee percentage) based on network utilization
- **Burn Percentage:** Can adjust the 40% burn rate to balance deflation vs. incentives
- **Chain Support:** Voting to deploy Gateways to new blockchains
- **Treasury Management:** Allocation of community funds for audits, bounties, and grants

6.5.3 Proposal Lifecycle

1. **Proposal Creation:** Any ILINK holder can submit proposals
2. **Discussion Period:** Community debate and refinement (1-2 weeks)
3. **Voting Period:** Quadratic voting with time-weighted participation
4. **Execution:** Successful proposals auto-execute via smart contracts

6.5.4 Example Governance Scenario

Suppose the network experiences high congestion with f = 0.1%. The DAO proposes increasing f to 0.15% to reduce load.

Voting Power Calculation:

- Alice holds 1,000 ILINK: Can cast 1,000 = 31.6 votes
- Bob holds 10,000 ILINK: Can cast 10,000 = 100 votes
- Charlie holds 100,000 ILINK: Can cast 100,000 = 316 votes

The quadratic mechanism ensures Alice's influence is 31.6/316 = 10% of Charlie's, rather than 1% under linear voting, creating more equitable governance.

This tokenomic design creates a sustainable economic model where network usage drives token scarcity, Relayer participation secures the network, and governance remains decentralized and fair.

7 Security Analysis

Security is the paramount requirement for any interoperability protocol. InterLink approaches security through a layered model, combining cryptographic hardness with game-theoretic incentives.

7.1 Game Theoretic Analysis

7.1.1 Protocol as an Extensive Game

We model InterLink as an extensive game between Relayers (R) and the Protocol (P), where Relayers can choose strategies of honest participation or malicious attack, and the Protocol responds through verification and slashing.

Strategy Space Definition:

- **Relayer Strategies:** {Honest, Malicious}
- **Protocol Responses:** {Accept Proof, Reject Proof}
- **Outcome Space:** {Valid Transfer, Invalid Transfer, Slashing Event}

7.1.2 Payoff Matrix Analysis

The strategic interaction between Relayers and Protocol creates the following payoff matrix:

	Valid Proof	**Invalid Proof**
Accept	R: +Fee +Reputation, P: +Trust +Volume	R: +Temporary Gain, P: -Security -Funds
Reject	R: -Fee -Gas, P: -Liveness	R: -Stake -Reputation, P: +Security

Table 1: Relayer-Protocol Payoff Matrix with Detailed Outcomes

Payoff Analysis:

- **Honest Equilibrium:** Relayers earn fees and reputation for correct proofs, Protocol gains user trust
- **Malicious Deterrence:** Invalid proofs trigger slashing, creating negative expected value for attacks
- **Nash Equilibrium:** Honest strategy dominates when stake costs exceed potential attack gains

7.1.3 Mathematical Security Model

Let S be the staked amount, G be potential attack gains, and P_{verif} be verification success probability.

The expected payoff for malicious behavior:

$$E[Malicious] = P_{verif} \times (-S) + (1 - P_{verif}) \times G$$

Since $P_{verif} \approx 1$ (cryptographic soundness), $E[Malicious] \approx -S$.

Rational Actor Assumption: Any rational actor will choose honest participation when the cost of generating valid proofs is lower than the stake penalty for invalid proofs.

7.2 Specific Attack Vectors & Mitigations

7.2.1 Long-Range Attacks

Attack Description: A long-range attack occurs when an attacker constructs a private fork of the source chain from a historical point. In PoS systems, old validator keys can be purchased from unstaked validators, allowing the attacker to build a competing chain that eventually overtakes the canonical chain.

Attack Flow:

1. Attacker acquires old validator private keys from past epochs
2. Builds alternative chain history from block N to current height
3. Submits proofs using the alternative chain's state
4. If accepted, attacker can withdraw assets that don't exist on canonical chain

InterLink Mitigation: Checkpointing InterLink implements Weak Subjectivity through checkpointing:

- Hub stores finalized block headers at regular intervals
- New proofs must extend from known checkpointed states
- Alternative histories contradicting checkpoints are rejected

```rust
fn verify_checkpoint(
    incoming_header: &BlockHeader,
    stored_checkpoints: &HashMap<u64, Hash>,
) -> Result<(), VerificationError> {
    // Find the nearest checkpoint before incoming header
    let checkpoint_height = (incoming_header.height / CHECKPOINT_INTERVAL) * CHECKPOINT_INTERVAL;

    if let Some(expected_hash) = stored_checkpoints.get(&checkpoint_height) {
        // Verify the header chain extends from this checkpoint
        let computed_hash = compute_header_hash_at_height(incoming_header, checkpoint_height)?;
        if computed_hash != *expected_hash {
            return Err(VerificationError::CheckpointMismatch);
        }
    }

    Ok(())
}
```

Listing 11: Checkpoint Verification Implementation

7.2.2 Data Availability (DA) Attacks

Attack Description: A DA attack occurs when a Relayer provides a valid proof of state transition but withholds the actual transaction data needed to reconstruct the new state. This creates "locked" assets where mathematical proofs exist but the underlying data is unavailable.

Attack Scenario:

1. Relayer submits proof: "Alice received 100 USDC on Solana"
2. Proof validates mathematically but transaction data is hidden
3. System cannot determine Alice's new balance or verify transfer legitimacy
4. Assets become permanently locked or attacker can claim them

InterLink Mitigation: DA Attestation InterLink requires explicit Data Availability commitments:

- ZK circuits include public input: hash of complete transaction data
- Proof verification checks DA layer (Ethereum, Celestia) for data posting
- Only proofs with confirmed data availability are accepted

7.2.3 Censorship Attacks

Attack Description: Censorship occurs when a coalition of Relayers systematically ignores messages from specific users, addresses, or applications. Unlike theft attacks, censorship doesn't steal funds but breaks the permissionless nature of cross-chain communication.

Censorship Mechanisms:

- **Selective Ignoring:** Relayers refuse to process messages from sanctioned addresses
- **Collusive Filtering:** Relayer network agrees to exclude certain transaction types
- **Front-Running Censorship:** Relayers delay legitimate messages to advantage themselves

InterLink Mitigation: Open Relayer Set InterLink employs a permissionless Relayer network:

- Anyone can become a Relayer by staking minimum ILINK
- Censorship creates arbitrage opportunities for honest Relayers
- Economic incentives favor processing all valid messages

7.2.4 51% Attacks on Source Chains

Attack Description: If a source chain suffers a 51% attack, the attacker could reorganize history and create conflicting proofs. InterLink must handle such scenarios without becoming a vector for double-spending.

Mitigation Strategy:

- **Finality Dependence:** Only accept proofs from finalized blocks
- **Reorg Monitoring:** Track chain reorganizations and invalidate affected proofs
- **Multi-Branch Handling:** Support proofs from multiple chain branches during uncertainty

7.3 Auditing & Formal Verification

7.3.1 Multi-Layer Security Pipeline

Static Analysis Phase:

- **Solidity Contracts:** Slither analysis for reentrancy, overflow, access control
- **Rust Programs:** Clippy and custom linting for memory safety and logic errors
- **ZK Circuits:** Halo2's built-in constraint validation

Fuzzing and Property Testing:

- **Contract Fuzzing:** Foundry's fuzzing engine tests millions of input combinations
- **Circuit Testing:** Proptest generates random circuit inputs to verify constraints
- **Integration Testing:** End-to-end test suites simulate complete cross-chain flows

Formal Verification Process: We collaborate with formal verification firms to prove:

- **Circuit Soundness:** ZK circuits correctly enforce intended constraints
- **Contract Correctness:** Smart contracts behave as specified under all conditions
- **System Invariants:** Properties like "total wrapped tokens = total locked assets" hold

7.3.2 Example: Formal Verification of Merkle Proofs

Consider verifying a Merkle inclusion proof. We formally prove:

$$\frac{\forall i \in [0, n] : H_{i+1} = \text{hash}(H_i, P_i) \vee H_{i+1} = \text{hash}(P_i, H_i)}{H_n = \text{root} \implies \text{leaf} \in \text{tree}}$$

This ensures the circuit cannot accept invalid Merkle proofs, even under adversarial input.

7.3.3 Continuous Security Monitoring

Post-Deployment Security:

- **Bug Bounty Program:** Incentivized disclosure of vulnerabilities
- **Real-time Monitoring:** Anomaly detection in proof validation patterns
- **Emergency Response:** Circuit breaker mechanisms for rapid shutdown

This comprehensive security approach ensures InterLink maintains cryptographic security guarantees while providing economic incentives for honest participation and robust mitigation strategies for identified attack vectors.

8 Practical Workflows and Examples

To illustrate the practical application of InterLink, we present detailed workflows for common cross-chain operations. This section bridges the gap between abstract architecture and concrete usage, providing developers with actionable implementation guidance.

8.1 Example 1: Cross-Chain Token Swap (Ethereum → Solana)

8.1.1 User Scenario and Requirements

Scenario: Alice wants to swap 10 ETH on Ethereum Mainnet for USDC on Solana with optimal execution.

Requirements:

- Atomic execution: Either complete swap or full refund
- Optimal routing: Best price across Solana DEXes
- Slippage protection: Minimum output guarantee
- Gas abstraction: No need to hold destination chain tokens

8.1.2 Step-by-Step Implementation

Step 1: User Interaction (Ethereum) Alice calls the InterLink Gateway contract with swap parameters:

```
// SPDX-License-Identifier: MIT
pragma solidity ^0.8.0;

interface IInterLinkGateway {
    function initiateSwap(
        address recipient,
        uint256 amountIn,
        address tokenIn,
        address tokenOut,
        uint256 minAmountOut,
        uint16 destinationChain,
        bytes calldata swapData
    ) external payable;
}

contract UserSwap {
    IInterLinkGateway public gateway;

    function swapETHForUSDC(uint256 minUSDC) external payable {
        // Encode Solana swap instructions
        bytes memory swapData = abi.encode(
            "JUPITER", // DEX aggregator
            "EPjFWdd5AufqSSqeM2qN1xzybapC8G4wEGGkZwyTDt1v", // USDC mint
            minUSDC
        );

        gateway.initiateSwap{value: msg.value}(
            msg.sender,            // recipient (Alice's Solana address)
            msg.value,             // amountIn (10 ETH)
            address(0),            // tokenIn (ETH)
            USDC_ADDRESS,          // tokenOut (USDC on Solana)
            minUSDC,               // minAmountOut
            1,                     // destinationChain (Solana)
            swapData               // encoded swap instructions
        );
    }
}
```

Listing 12: Solidity: User-Initiated Cross-Chain Swap

Step 2: Gateway Processing (Ethereum) The Gateway locks assets and emits structured event:

```
function initiateSwap(...) external payable {
    // 1. Validate inputs
    require(amountIn == msg.value, "Incorrect ETH amount");
    require(destinationChain == 1, "Only Solana swaps supported");

    // 2. Lock ETH in vault
    vault.deposit{value: amountIn}();

    // 3. Generate sequence number
    uint64 sequence = ++seqNum;

    // 4. Emit canonical event for Relayers
    emit SwapInitiated(
        sequence,
        msg.sender,
        recipient,
        amountIn,
        tokenIn,
        tokenOut,
        minAmountOut,
        destinationChain,
        swapData,
        keccak256(abi.encodePacked(sequence, msg.sender, recipient, amountIn))
    );
}
```

Listing 13: Solidity: Gateway Event Emission

Step 3: Relayer Observation and Proof Generation Bob's Relayer detects the event and generates proof:

```
#[derive(Debug, Deserialize)]
struct SwapInitiatedEvent {
    sequence: u64,
    sender: Address,
    recipient: String,
    amount_in: U256,
    token_in: Address,
    token_out: Address,
    min_amount_out: U256,
    destination_chain: u16,
    swap_data: Vec<u8>,
    payload_hash: [u8; 32],
}

async fn process_swap_event(event: SwapInitiatedEvent) -> Result<()> {
    // 1. Wait for Ethereum finality (12-15 minutes)
    wait_for_finality(event.block_number, Chain::Ethereum).await?;

    // 2. Fetch complete transaction data
    let tx = eth_client.get_transaction(event.tx_hash).await?;
    let receipt = eth_client.get_transaction_receipt(event.tx_hash).await?;
    let block = eth_client.get_block(event.block_number).await?;

    // 3. Generate Merkle proof for transaction inclusion
    let merkle_proof = generate_merkle_proof(&receipt, &block)?;

    // 4. Generate consensus proof (BLS signatures)
    let consensus_proof = generate_consensus_proof(&block)?;

```

```rust
    // 5. Construct ZK circuit inputs
    let circuit_inputs = SwapCircuitInputs {
        sequence: event.sequence,
        sender: event.sender,
        recipient: event.recipient.clone(),
        amount_in: event.amount_in,
        token_in: event.token_in,
        token_out: event.token_out,
        min_amount_out: event.min_amount_out,
        swap_data: event.swap_data,
        merkle_proof,
        consensus_proof,
    };

    // 6. Generate ZK proof
    let (proof, public_inputs) = generate_swap_proof(circuit_inputs).await?;

    // 7. Submit to Solana Hub
    submit_swap_to_solana(proof, public_inputs).await?;

    Ok(())
}
```

Listing 14: Rust: Relayer Swap Processing

Step 4: Solana Hub Verification and Execution The Hub verifies and executes the swap:

```rust
#[derive(Accounts)]
pub struct ExecuteSwap<'info> {
    #[account(mut)]
    pub hub_state: Account<'info, HubState>,

    #[account(mut)]
    pub user_token_account: Account<'info, TokenAccount>,

    #[account(mut)]
    pub wrapped_eth_vault: Account<'info, TokenAccount>,

    #[account(mut)]
    pub liquidity_pool: Account<'info, LiquidityPool>,

    pub jupiter_program: Program<'info, Jupiter>,
    pub token_program: Program<'info, Token>,
}

pub fn execute_swap(
    ctx: Context<ExecuteSwap>,
    proof: Vec<u8>,
    public_inputs: Vec<u8>,
    expected_sequence: u64,
) -> Result<()> {
    // 1. Verify ZK proof
    let is_valid = halo2_verifier::verify(&proof, &public_inputs)?;
    require!(is_valid, InterlinkError::InvalidProof);

    // 2. Verify sequence ordering
    let mut hub_state = &mut ctx.accounts.hub_state;
    require!(
        expected_sequence == hub_state.last_eth_sequence + 1,
        InterlinkError::InvalidSequence
    );
    hub_state.last_eth_sequence = expected_sequence;

```

```rust
    // 3. Mint wrapped ETH equivalent
    let amount_in = parse_amount_from_inputs(&public_inputs);
    token::mint_to(
        ctx.accounts.wrapped_eth_vault.clone(),
        ctx.accounts.temp_vault.to_account_info(),
        amount_in
    )?;

    // 4. Execute Jupiter swap via CPI
    let swap_ix = jupiter_instruction::swap(
        ctx.accounts.liquidity_pool.to_account_info(),
        ctx.accounts.temp_vault.to_account_info(),
        ctx.accounts.user_token_account.to_account_info(),
        amount_in,
        minimum_output_amount,
    )?;

    // Execute the swap
    invoke(&swap_ix, &[
        ctx.accounts.liquidity_pool.to_account_info(),
        ctx.accounts.temp_vault.to_account_info(),
        ctx.accounts.user_token_account.to_account_info(),
    ])?;

    // 5. Verify minimum output was received
    let actual_output = get_token_balance(ctx.accounts.user_token_account)?;
    require!(
        actual_output >= minimum_output_amount,
        InterlinkError::SlippageExceeded
    );

    // 6. Clean up temporary vault
    token::burn(
        ctx.accounts.temp_vault.to_account_info(),
        ctx.accounts.wrapped_eth_vault.to_account_info(),
        amount_in
    )?;

    // 7. Emit success event
    emit!(SwapExecuted {
        sequence: expected_sequence,
        user: ctx.accounts.user_token_account.owner,
        input_amount: amount_in,
        output_amount: actual_output,
        input_token: "ETH",
        output_token: "USDC",
    });

    Ok(())
}
```

Listing 15: Rust: Solana Hub Swap Execution

8.1.3 Failure Scenarios and Recovery

Scenario 1: Slippage Too High

1. Swap execution on Jupiter fails due to price impact
2. Hub marks transaction as FAILED in state registry
3. Generates refund message back to Ethereum

4. Relayer proves failure state and unlocks original ETH

Scenario 2: Proof Rejection

1. Invalid ZK proof submitted (malicious Relayer or bug)
2. Transaction reverts on Solana
3. Relayer stake slashed (50% burned)
4. User can retry with different Relayer

Scenario 3: Network Congestion

1. Solana network congestion delays proof submission
2. Proof submitted with higher priority fee
3. If timeout exceeded, refund initiated

8.1.4 Performance Metrics

- **Total Latency:** 12-20 minutes (Ethereum finality + proof generation + Solana confirmation)
- **Cost Breakdown:** 0.1% fee (protocol) + Solana gas + Relayer rewards
- **Success Rate:** >99.9% for properly formed transactions
- **Slippage Protection:** Guaranteed minimum output or full refund

8.2 Example 2: Cross-Chain Governance Vote

8.2.1 Scenario: DAO Contract Upgrade

A Cosmos-based DAO wants to upgrade a contract on Arbitrum through community voting.

8.2.2 Implementation Steps

Step 1: Cosmos DAO Vote Aggregation

```go
func (k Keeper) ProcessGovernanceVote(ctx sdk.Context, proposalID uint64) {
    // Aggregate votes from Cosmos validators/stakers
    proposal := k.GetProposal(ctx, proposalID)

    if proposal.Status == types.StatusPassed {
        // Generate cross-chain upgrade message
        upgradeMsg := types.CrossChainUpgrade{
            ContractAddress: "0x123...", // Arbitrum contract
            NewImplementation: "0x456...", // New logic
            ProposalID: proposalID,
            DaoAddress: k.daoAddress,
        }

        // Emit IBC event for InterLink processing
        k.emitCrossChainEvent(ctx, upgradeMsg)
    }
}
```

Listing 16: Cosmos SDK: DAO Vote Processing

Step 2: Relayer Consensus Verification For Cosmos Tendermint consensus, the Relayer verifies validator signatures:

```rust
fn verify_tendermint_consensus(
    block: &TendermintBlock,
    validator_set: &ValidatorSet,
) -> Result<(), VerificationError> {
    // 1. Verify commit signatures
    let mut signed_power = 0;
    for signature in &block.commit.signatures {
        let validator = validator_set.get(signature.validator_address)?;

        // Verify Ed25519 signature
        let message = block.header.hash();
        signature.verify(&message, &validator.public_key)?;

        signed_power += validator.voting_power;
    }

    // 2. Check 2/3 majority
    let total_power = validator_set.total_voting_power();
    require!(
        signed_power > (2 * total_power) / 3,
        VerificationError::InsufficientSignatures
    );

    Ok(())
}
```

Listing 17: Rust: Cosmos Consensus Verification

8.2.3 Advanced Example: Multi-Chain DeFi Strategy

Scenario: Alice implements a cross-chain yield farming strategy: 1. Deposit USDC on Ethereum → Borrow ETH on Compound 2. Bridge borrowed ETH to Solana → Provide liquidity in SOL-USDC pool 3. Stake LP tokens → Earn yields in multiple tokens 4. Periodically rebalance across chains

This demonstrates InterLink's capability for complex, multi-step cross-chain DeFi operations that were previously impossible due to atomicity and liquidity fragmentation issues.

8.2.4 Developer Integration Guide

Step 1: Contract Interface

```solidity
interface IInterLinkRouter {
    function sendMessage(
        uint16 destinationChain,
        bytes32 recipient,
        bytes calldata payload,
        address feeToken,
        uint256 feeAmount
    ) external payable;

    function estimateFee(
        uint16 destinationChain,
        bytes calldata payload
    ) external view returns (uint256);
}
```

Listing 18: Solidity: InterLink Integration Interface

Step 2: Payload Encoding Standardized payload format ensures compatibility across chains:

```rust
#[derive(Serialize, Deserialize)]
struct InterLinkPayload {
    version: u8,
    action: ActionType,
    sender: Address,
    recipient: Address,
    data: Vec<u8>,
    deadline: u64,
}

enum ActionType {
    Transfer,
    Swap,
    ContractCall,
    Governance,
}
```

Listing 19: Rust: Payload Encoding Standard

Step 3: Error Handling Implement robust error handling for cross-chain operations:

```solidity
contract CrossChainApp {
    mapping(uint64 => CrossChainTx) public pendingTxs;

    function handleExecution(uint64 sequence, bool success, bytes memory result
    ) external {
        CrossChainTx storage tx = pendingTxs[sequence];

        if (success) {
            // Process successful execution
            executeCallback(tx.callback, result);
        } else {
            // Handle failure - initiate refund or retry
            initiateRefund(tx);
        }

        delete pendingTxs[sequence];
    }
}
```

Listing 20: Solidity: Cross-Chain Error Handling

These examples demonstrate how InterLink enables previously impossible cross-chain operations, from simple token transfers to complex multi-chain DeFi strategies, all with strong guarantees of atomicity, security, and efficiency.

9 Comparison with State of the Art

InterLink competes in a crowded market. However, its architecture offers distinct advantages over incumbents.

Protocol	Trust Model	Latency	Gas Cost	Finality	Setup	Extensibility
InterLink	**ZK-Light Client**	**Medium**	**Low (O(1))**	**Src Finality**	**Trustless**	**High**
LayerZero v2	DVNs (Multi-sig)	Low	Low	Instant	Permissioned	High
Axelar	PoS Validators	Medium	Medium	1-2 mins	Trusted	Medium
Wormhole	Guardian Set (19/19)	Low	Low	Instant	Trusted	High
Cosmos IBC	Light Client	Low	Low	Instant	Trustless	Low

Table 2: Comprehensive Competitive Analysis

9.1 InterLink vs. LayerZero

9.1.1 Technical Architecture Comparison

LayerZero v2 Overview:

- **Ultra Light Nodes (ULNs):** Permissioned off-chain oracles that attest to cross-chain events
- **Decentralized Verifier Networks (DVNs):** External parties that validate message authenticity
- **Configurable Security:** Users choose which DVNs to trust for each message
- **Modular Design:** Separate oracle, relayer, and verification components

InterLink Advantages:

- **Cryptographic Security:** ZK proofs provide mathematical guarantees vs. social consensus
- **Unified Verification:** Single proof validates both event and consensus vs. multiple DVN attestations
- **Trust Minimization:** No reliance on external parties for security
- **Performance:** Amortized verification cost scales better with message volume

9.1.2 Economic Comparison

LayerZero Economics:

- Variable fees based on DVN selection and gas prices
- Permissioned relayers may extract MEV
- Governance controlled by LZ token holders

InterLink Economics:

- Predictable fees with buy-back-and-burn mechanism
- Censorship-resistant relayer network
- Quadratic voting ensures fair governance

9.1.3 Security Model Analysis

LayerZero v2 relies on a "security stack" where users select trusted DVNs. While flexible, this creates:

- **Trust Assumptions:** Users must research and trust multiple external parties
- **Coordination Risk:** All selected DVNs must remain honest simultaneously
- **Centralization Risk:** Popular DVNs become single points of failure

InterLink eliminates these assumptions through cryptographic verification, where security derives directly from the source chain's consensus rather than external attestations.

9.2 InterLink vs. Axelar

9.2.1 Consensus Mechanism Differences

Axelar Network Overview:

- **Dedicated Blockchain:** Axelar runs its own PoS network with 75 validators
- **Threshold Signatures:** Uses MPC-based threshold signatures for cross-chain messages
- **Gateway Contracts:** Deployed on supported chains to facilitate message passing
- **Validator Staking:** 75M AXL minimum stake requirement

InterLink's Hub-and-Spoke Approach:

- **Existing High-Performance Chain:** Leverages Solana's battle-tested infrastructure
- **ZK-Based Verification:** Cryptographic proofs replace signature-based consensus
- **Reduced Complexity:** No need to bootstrap and secure a new blockchain
- **Inherited Security:** Benefits from Solana's economic security without additional staking requirements

9.2.2 Scalability Analysis

Axelar's dedicated blockchain creates scalability challenges:

- **Validator Throughput:** Limited by 75 validator consensus
- **Cross-Chain Latency:** Additional consensus round for each message
- **Upgrade Complexity:** Coordinating validator set updates across chains

InterLink's architecture scales better:

- **Hub Throughput:** Inherits Solana's 50k+ TPS capacity
- **Verification Parallelism:** ZK proofs can be verified in parallel
- **Upgrade Flexibility:** Protocol upgrades don't require chain consensus

9.3 InterLink vs. Wormhole

9.3.1 Guardian Model vs. Relayer Network

Wormhole Guardian Overview:

- **Guardian Network:** 19 reputable entities that sign cross-chain messages
- **Multi-Signature Verification:** Requires 13/19 signatures for validity
- **Reputation-Based Security:** Guardians selected for track record and stake

- **Centralized Governance:** Guardian set controlled by Wormhole foundation

InterLink's Decentralized Approach:

- **Permissionless Relayers:** Anyone can participate by staking ILINK
- **Economic Incentives:** Slashing and rewards align relayer behavior
- **Censorship Resistance:** No central authority can prevent message relay
- **Scalable Security:** Security scales with economic stake, not fixed committee size

9.3.2 Risk Analysis

Wormhole's Guardian model introduces risks:

- **Coordinator Compromise:** If multiple Guardians collude or are coerced
- **Reputation Gaming:** Guardians might prioritize reputation over security
- **Governance Capture:** Foundation control over Guardian selection

InterLink mitigates these through:

- **Cryptographic Security:** Invalid proofs are mathematically impossible
- **Economic Alignment:** Relayers lose stake for dishonest behavior
- **Decentralized Governance:** Quadratic voting prevents plutocracy

9.4 InterLink vs. Cosmos IBC

9.4.1 Light Client Efficiency Comparison

IBC Light Client Overview:

- **Tendermint Light Client:** Verifies block headers through validator signatures
- **Relayer Model:** Permissionless relayers submit headers and proofs
- **Connection Handshake:** Requires initial connection establishment between chains
- **State Verification:** Verifies state proofs against verified headers

ZK-Enhanced Interoperability:

- **Compressed Verification:** ZK proofs reduce consensus verification from O(n) to O(1)
- **Universal Compatibility:** Works with any consensus mechanism (PoW, PoS, etc.)
- **Reduced On-Chain Cost:** Amortized verification enables cheaper cross-chain calls
- **Unified Interface:** Single protocol handles all chain types

9.4.2 Technical Efficiency Gains

IBC requires on-chain verification of:

- Block header validity (validator signatures)
- Merkle proof inclusion
- State transition correctness

InterLink compresses this into a single ZK proof that attests to all three simultaneously, providing:

- **Reduced Gas Costs:** 10-100x lower verification costs on destination chains
- **Faster Finality:** No need to wait for light client updates
- **Better Privacy:** Transaction details can be hidden while proving validity

9.5 Quantitative Performance Comparison

9.5.1 Latency Analysis

Metric	InterLink	LayerZero	Axelar	Wormhole
Source Finality	1-15 min	Instant	1-2 min	Instant
Proof Generation	10-60 sec	N/A	N/A	N/A
Verification	<1 sec	<1 sec	<1 sec	<1 sec
Total Latency	2-16 min	1-5 min	2-5 min	1-3 min

Table 3: Latency Comparison Across Protocols

9.5.2 Cost Efficiency Analysis

InterLink achieves superior cost efficiency through:

- **Batching:** 100-message batches reduce per-message costs by 99%
- **Recursive Proofs:** Aggregate proofs across multiple messages
- **Amortized Verification:** O(1) verification regardless of message complexity

9.5.3 Security Quantification

Security Property	InterLink	Competitors	Advantage
Cryptographic Security			Mathematical guarantees
Censorship Resistance			Permissionless relayers
Economic Alignment		Partial	Slashing + rewards
Scalable Security			Stake-based, not committee

Table 4: Security Feature Comparison

9.6 Unique InterLink Advantages

9.6.1 Innovative Features

Unified Liquidity Layer:

- Aggregates liquidity across all connected chains
- Enables atomic cross-chain swaps with optimal routing
- Provides unified price discovery and arbitrage opportunities

Recursive Proof Composition:

- Enables proof aggregation across multiple messages

- Supports complex multi-step cross-chain operations
- Maintains succinctness even for batched operations

Economic Sustainability:

- Buy-back-and-burn creates deflationary token dynamics
- Quadratic governance prevents plutocratic capture
- Stake-weighted security scales with adoption

9.6.2 Market Positioning

InterLink positions itself as the "ZK-native interoperability layer" that combines:

- **Trustless Security:** Cryptographic guarantees eliminate bridge risks
- **Developer Experience:** Simple APIs for complex cross-chain operations
- **Economic Efficiency:** Low costs and sustainable token economics
- **Future-Proofing:** Extensible architecture for emerging use cases

This comprehensive analysis demonstrates that InterLink offers a superior combination of security, efficiency, and extensibility compared to existing interoperability solutions, positioning it as the foundation for the next generation of cross-chain applications.

10 Conclusion

InterLink represents the maturity of the interoperability landscape. We have moved from the "Wild West" of multisig bridges, plagued by hacks and centralization, to the era of **Verifiable Interoperability**.

By combining the cryptographic guarantees of **halo2 zk-SNARKs** with the high-performance execution environment of **Solana**, InterLink solves the Trilemma. It offers the trustlessness of a light client with the cost-effectiveness of a multisig. The result is a Unified Liquidity Layer that empowers developers to build applications that transcend chain boundaries.

The future of blockchain is not about which chain wins. It is about how they all work together. InterLink is the common language that allows them to speak. We envision a future where users are unaware of which chain they are on; they simply interact with applications, and InterLink handles the complex routing of value and data in the background. This "Chain Abstraction" is the final frontier for mass adoption.

As we move forward, our development focus remains on three core pillars: cryptographic efficiency, economic sustainability, and developer experience. We are not just building a bridge; we are building the internet's value layer. By making cross-chain interaction as simple as a local function call, we unlock a new class of decentralized applications that were previously impossible.

The protocol we propose is more than just a technical specification; it is a foundational substrate for the next generation of decentralized finance and sovereign digital identity. By unifying the fragmented state of modern blockchains, InterLink enables a level of capital efficiency and user sovereignty that was hitherto theoretical. We believe that true decentralization requires a system where security is rooted in verifiable math rather than institutional reputation.

We invite the global research community, developers, and users to contribute to this open-source effort. Whether through formal security audits, circuit optimizations, or the creation of new

cross-chain primitives, your participation is vital to realizing the vision of a unified, trustless digital economy. Together, we can turn the fragmented multi-chain reality into a cohesive, interoperable ecosystem where innovation knows no borders.

10.1 Future Work and Research Directions

Our roadmap encompasses multiple research vectors that will enhance InterLink's capabilities and expand its applicability across the blockchain ecosystem.

10.1.1 Cryptographic Enhancements

Zero-Knowledge Virtual Machines (zkVMs):

- **Universal Circuit Templates:** Develop standardized circuit templates for common operations (ERC20 transfers, DEX swaps, NFT minting)
- **Recursive Proof Aggregation:** Implement advanced recursive structures for aggregating proofs across multiple chains simultaneously
- **Post-Quantum Security:** Research quantum-resistant proof systems to future-proof against cryptographic advances
- **Multi-Party Computation Integration:** Combine MPC with ZK proofs for enhanced privacy and scalability

Privacy-Preserving Interoperability:

- **Zero-Knowledge Token Transfers:** Enable cross-chain transfers where amount and recipient remain hidden
- **Confidential DEX Operations:** Private order matching and execution across chains
- **Anonymous Governance:** Quadratic voting with privacy preservation
- **Mixed ZK Protocols:** Integration with Aztec, Tornado Cash, and other privacy-focused systems

10.1.2 Performance and Scalability Improvements

Hardware Acceleration Research:

- **FPGA Implementation:** Custom FPGA designs optimized for Halo2 proving operations
- **ASIC Development:** Application-specific integrated circuits for high-throughput proof generation
- **GPU Optimization:** CUDA implementations for parallel proof computation
- **Distributed Proving Networks:** Decentralized proving pools for horizontal scaling

Network Layer Optimizations:

- **Proof Compression:** Advanced compression techniques to reduce proof sizes by 10-100x
- **Batching Algorithms:** Sophisticated batching strategies for optimal gas utilization
- **Layer 2 Integration:** Direct integration with rollups and sidechains for reduced latency
- **Cross-Chain State Channels:** Payment channel networks spanning multiple blockchains

10.1.3 Ecosystem Expansion

Multi-Chain Support Roadmap:

- **Layer 1 Integration:** Bitcoin, Ethereum, Solana, Cosmos, Polkadot, Avalanche, Near
- **Layer 2 Support:** Optimism, Arbitrum, Polygon, zkSync, StarkNet, Scroll
- **Altchain Compatibility:** Monero (privacy), Algorand (speed), Flow (NFTs)
- **Enterprise Chains:** Hyperledger, Quorum, Corda integration

DeFi and NFT Primitives:

- **Cross-Chain Lending:** Atomic borrowing and lending across protocols
- **Unified Liquidity Pools:** Aggregated liquidity from Uniswap, SushiSwap, PancakeSwap
- **NFT Fractionalization:** Cross-chain NFT ownership and trading
- **Derivatives Markets:** Cross-chain options, futures, and synthetic assets

10.1.4 Developer Experience and Tooling

SDK and Framework Development:

- **InterLink SDK:** Unified APIs for cross-chain application development
- **Smart Contract Libraries:** Pre-built contracts for common cross-chain patterns
- **Testing Frameworks:** Simulation environments for cross-chain application testing
- **Deployment Tools:** Automated deployment and configuration management

Integration and Interoperability Standards:

- **Cross-Chain Standards:** Standardized message formats and protocol interfaces
- **Oracle Networks:** Decentralized price feeds and data oracles across chains
- **Identity Systems:** Cross-chain digital identity and reputation
- **Governance Frameworks:** Interoperable DAO structures and voting mechanisms

10.1.5 Long-Term Research Vision

Fractal Scaling Architecture:

- **L3 Application Chains:** App-specific chains settling to InterLink as DA layer
- **Recursive Interoperability:** Chains that can themselves be InterLink hubs
- **Meta-Protocol Layer:** Higher-order protocols built on InterLink infrastructure
- **Quantum-Resistant Upgrades:** Migration paths for post-quantum cryptography

Societal Impact Research:

- **Global Financial Inclusion:** Cross-border payments for unbanked populations
- **Digital Sovereignty:** User-owned identity and assets across jurisdictions
- **Decentralized Governance:** Global decision-making without geographic boundaries
- **Economic Mobility:** Reduced friction in international trade and commerce

10.1.6 Implementation Timeline

Phase 1 (Q1-Q2 2024): Core Protocol

- Ethereum-Solana mainnet deployment
- Basic token transfer functionality
- Relayer network launch
- Security audits and formal verification

Phase 2 (Q3-Q4 2024): Ecosystem Expansion

- Multi-chain support (Arbitrum, Optimism, Cosmos)
- DEX integration and cross-chain swaps
- NFT and governance primitives
- Developer SDK release

Phase 3 (2025): Advanced Features

- Privacy-preserving transfers
- Hardware acceleration
- L3 fractal scaling
- Enterprise integrations

Phase 4 (2026+): Mass Adoption

- Global DeFi ecosystem
- Cross-chain identity systems
- Real-world asset tokenization
- Institutional adoption

10.1.7 Research Collaboration Opportunities

We actively seek partnerships with:

- **Academic Institutions:** Cryptography research, formal verification, distributed systems
- **Industry Partners:** Hardware manufacturers, DeFi protocols, Layer 1 platforms
- **Government Entities:** Regulatory compliance, cross-border payment frameworks
- **NGOs and Impact Organizations:** Financial inclusion and digital sovereignty initiatives

10.1.8 Risk Mitigation and Contingency Planning

Technical Risks:

- **Cryptographic Breaks:** Regular security audits and proof system upgrades
- **Scalability Limits:** Multi-layered optimization and hardware acceleration
- **Integration Complexity:** Modular architecture and extensive testing

Economic Risks:

- **Adoption Failure:** Comprehensive marketing and developer incentives
- **Competition:** Superior technology and network effects
- **Regulatory Changes:** Proactive compliance and legal frameworks

Operational Risks:

- **Team Sustainability:** Diverse funding sources and governance decentralization
- **Community Governance:** Gradual power transfer and education programs
- **Technical Debt:** Continuous refactoring and modernization

This comprehensive roadmap positions InterLink not just as a bridge protocol, but as the foundational infrastructure for a truly interconnected blockchain ecosystem. By addressing current limitations while anticipating future needs, InterLink aims to catalyze the next phase of blockchain adoption and innovation.

The journey ahead is ambitious, but the potential impact is transformative. We believe InterLink represents the convergence of cryptography, economics, and distributed systems into a unified framework that will redefine how value flows in the digital age. Through collaborative research, rigorous development, and community-driven governance, we will realize this vision together.

References

[1] Electric Coin Co. *The Halo2 Proving System*. 2024. https://zcash.github.io/halo2/

[2] Gabizon, A., Williamson, Z., Ciobotaru, O. *PLONK: Permutations over Lagrange-bases for Oecumenical Noninteractive arguments of Knowledge*. 2019.

[3] Yakovenko, A. *Solana: A new architecture for a high performance blockchain*. 2018.

[4] Zarick, R., et al. *LayerZero: Trustless Omnichain Interoperability Protocol*. 2021.

[5] Kate, A., Zaverucha, G.M., Goldberg, I. *Constant-Size Commitments to Polynomials and Their Applications*. 2010.

[6] Wormhole Team. *Wormhole: Generic Message Passing*. 2020.