

2. Implement Playwright with TypeScript

Use Ask Mode to analyze the existing project structure and identify all impacted files required for the Playwright with TypeScript implementation.

Once the analysis is complete, switch to Agent Mode to implement the required changes

```
import { test, expect } from '@playwright/test';

test.describe('Login Page', () => {
  test.beforeEach(async ({ page }) => {
    await page.goto('https://leaftaps.com/opentaps/control/main');
  });

  test('should display the username input', async ({ page }) => {
    const usernameInput = page.locator('#username');
    await expect(usernameInput).toBeVisible();
    await expect(usernameInput).toHaveAttribute('type', 'text');
  });

  test('should display the password input', async ({ page }) => {
    const passwordInput = page.locator('#password');
    await expect(passwordInput).toBeVisible();
    await expect(passwordInput).toHaveAttribute('type', 'password');
  });

  test('should display the login button', async ({ page }) => {
    const loginButton = page.locator('input[type="submit"][value="Login"]');
    await expect(loginButton).toBeVisible();
    await expect(loginButton).toBeEnabled();
  });

  test('should allow typing into username and password fields', async ({ page }) => {
    const usernameInput = page.locator('#username');
    const passwordInput = page.locator('#password');

    await usernameInput.fill('DemoUser');
    await expect(usernameInput).toHaveValue('DemoUser');

    await passwordInput.fill('DemoPass');
    await expect(passwordInput).toHaveValue('DemoPass');
  });
});
```