

= 260IV ECO THERMAL PRINTER =



iOS



Feature

- 200 mm/sec high speed printing
- Support 80mm large diameter roll
- Support Wall Mounting
- ESC/POS compatible
- Low-noise thermal printing
- Small size and low power consumption
- Easy paper jam clearance
- Built-in interface provides control capability for Cash Drawer
- Compatible with ESC/POS print instruction mode
- Support IAP online upgrade

Application



SUPERMARKET



MEDICAL CARE



STORAGE



POST



CATERING



STORE



TAX

Technical Specification



MODEL	260IV ECO
Printing method	Direct thermal
Printing speed	200mm/s
Paper width	79.5±0.5mm / ϕ 80 mm
Printable area	72 mm (adjustable by commands)
Maximum Paper diameter	83 mm
Paper thickness	0.06-0.08mm
Column capacity	42 / 48
Line space	3.75mm (Adjustable by commands)
Commands	Compatible with ESC/ POS
Interface type	USB / USB+LAN
Character size	ANK, Font A:1.5×3.0mm (12×24 dots) Font B:1.1×2.1mm (9×17 dots)
Bar code	UPC-A/UPC/JAN13, EAN13/JAN8, EAN8/CODE39/ITF/CODABAR/CODE93/CODE128
2-Dimension code	QR Code
Cutter	Partial Cutter life 100 Million
Print head life	100 km
Input buffer & NV Flash	256 k bytes
Input voltage	DC 24V/2.5A
Cash drawer output	DC 24V/1A
Work environment	Temperature (0~45℃) humidity (10~80%)
Storage environment	Temperature (-10~60℃) humidity (10~90%)
Operating system	Windows/ Linux/ SDK: Android/ IOS
Dimension	173(D)x128(W)x127(H)mm
Gross weight	1.3kg
Warranty	1 Year Carry in Warranty

