



POWERSTAR

trucks built to last

VX 1627 4x2

LWB Chassis Cab



Picture is for illustration purposes only

A brand of

EVERSTAR
industries

www.everstarindustries.com

Driven by Vision. Powered by Strength.

ENGINE	
Make	Weichai Euro 3 Turbo charged Intercooled
Model Configuration	WP 7.270 E30
Max Power—Kw @ r/min	199/2300
Max Torque—N.m @ r/min	1100/1200-1600
HP	270
Cylinder	6 Inline
Water Cooled	Yes
Direct Injection	Yes
Engine driven P.T.O	No
Displacement (l)	7.14
Compression Ratio	18:01

BRAKES	
Service	Dual circuit air brakes
Emergency / Parking	Spring potential brake
Auxiliary	ABS & EVB

STANDARD TYRE EQUIPMENT	
Size and ply rating	12 R22.5 incl spare wheel

FRONT AXLE	
Type	VR4/100-7.5(ABS) Drum Brake
Suspension	Non-free standing stabilization leaf spring, hydraulic shock absorber, transverse stabilizer

REAR AXLE	
Type	HL8/1020-10/4.11(ABS), Hypoid
Suspension	Stabilization suspension, hydraulic shock absorber, transverse stabilizer

ELECTRICAL EQUIPMENT	
Alternator	70Amp
Starter Motor	5.75kW
Batteries	2 x 12V -135AH

PERFORMANCE DATA	
Gradeability @ GVM	30% @ GVM
Max Geared Road Speed	110km/h (Limited to 80km/h)
Final Drive Ratio	4.11

CLUTCH	
Make / Type / Size	GFX 420mm single
Operation	Single dry frictional disc, diaphragm spring pushing type

WARRANTY	
New Vehicle	3 years / 300 000km (SA only)
T&C comply. Please refer to warranty booklet.	

TRANSMISSION	
Make/Model	JS118TB-B+CH50
No of Gears	8
Synchromesh or Constant Mesh	Synchromesh
P.T.O	Yes

RATIO			
Crawler		7th	1.39
1st	11.40	8th	1.00
2nd	7.94	9th	N/A
3rd	5.63	10th	N/A
4th	4.06	11th	N/A
5th	2.81	12th	N/A
6th	1.96	Reverse L	11.35

DIMENSIONS	
Overall Length (OL)	9 600
Overall Width (OW)	2 435
Overall Height (OH)	2 905
Front Overhang (FOH)	1 435
Rear Overhang (ROH)	2 550
Wheel Base (WB)	5 500
Bumper to Back of Cab (BBC)	1 880
Cab to rear axle / unit (CA)	5 055
Turning Radius (TR)	10 000
Fuel Tank Capacity	400 Litre Aluminium

MASS INFORMATION	
Manufacturers Gross Vehicle Mass (GVM)	16 000
Manufacturers Gross Combination Mass (GCM)	28 000
Manufacturers Front Axle mass (GA)	7 500
Manufacturers Rear Axle mass (GAR)	10 000
Permissible Maximum Vehicle Mass (V)	16 000
Permissible Maximum Front Axle Mass (AF)	7 100
Permissible Maximum Rear Axle Mass (AR)	9 000
Unladen Front Axle Mass (UF)	3 940
Unladen Rear Axle Mass (UR)	2 440
Total Unladen Mass (UT)	6 280
Permissible Max Drawing Vehicle Mass (D/T)	28 000

CAB (Day Cab)	
Hydraulic Tilttable Cab	



Comments: _____

Visit www.everstarindustries.com for dealer network

Please note: The manufacturer reserves the right to make changes to the design, form, colour and specifications of any Powerstar brochure without notice. The picture shown is for illustrated purposes only.

Product Number: 001/1027/15

 **POWERSTAR**
trucks built to last