



Miniature Inertial Measurement Unit

Overview

With more than three hundred miniature inertial measurement units (MIMUs) successfully launched combining for more than one million hours of on-orbit operation, the MIMU has quickly become the inertial measurement unit of choice for commercial and military satellite and space exploration programs.

Key Honeywell Advantages:

- 3 Axis Angular Measurement using proven GG1320 RLG
- Enhanced Built-in Test
- RS422 and MIL-STD-1553B
- Stimulus Ground Test Function
- Software Upload
- 28-100 Vdc Primary Power
- In-rush and Current Limiting
- On/Off Command



Click to enlarge



Feedback

[SAVE PAGE AS PDF](#)

[FIND A PARTNER](#)

[CONTACT US](#)

Specifications

Dimensions

Weight	< 4.7 kg (4.6 kg typical)
Size	< 233.7mm (D) X 169.9 mm (H) millimetre

Performance Data

Power Consumption (Typical)	< 32.0 Watts (25 W typical)
Operating Temperature	-30°C to 65°C

Environment	-30°C to 65°C (operating)
	Acceleration 25g
	EMI per MIL-STD-461c
	Pyrotechnic Shock 40,000g
	Radiation Hardened - 100 Krad Total Dose - SEU
	Tolerant - Latchup Immun
	Random Vibration 19.7 grms
	Space Vacuum

Resources

→	05 Feb 2025	2.15 MB