


# 6CCS3PRJ

# Designing for Consent Revocation in Online Platforms

Final Project Report

Author: Mert Ayranci

Supervisor: Kovila Coopamootoo

Student ID: 21175534

April 8, 2026

**Abstract**

The abstract is a very brief summary of the report's contents. It should be about half-a-page long. Somebody unfamiliar with your project should have a good idea of what your work is about by reading the abstract alone.

**Originality Avowal**

I verify that I am the sole author of this report, except where explicitly stated to the contrary. I grant the right to King's College London to make paper and electronic copies of the submitted work for purposes of marking, plagiarism detection and archival, and to upload a copy of the work to Turnitin or another trusted plagiarism detection service. I confirm this report does not exceed 25,000 words.

Mert Ayranci

April 8, 2026

**Acknowledgements**

It is usual to thank those individuals who have provided particularly useful assistance, technical or otherwise, during
your project. Your supervisor will obviously be pleased to be acknowledged as he or she will have invested quite a lot of time overseeing your progress.

# Contents


**1 Introduction** **3**

1.1 Motivations . . . . . 4
1.2 Scope . . . . . 4
1.3 Research Questions . . . . . 5
1.4 Aim and Objectives . . . . . 5
1.5 Contributions . . . . . 6
1.6 Key Takeaways . . . . . 7
1.7 Report Structure . . . . . 7

**2 Literature Review** **8**

2.1 Brief . . . . . 8
2.2 Digital Messaging and Photo Sharing . . . . . 8
2.3 Digital Privacy in Modern Communication . . . . . 9
2.4 The Concept of Consent . . . . . 12
2.5 Consent in Instant Messaging and Photo Sharing . . . . . 15
2.6 Human Computer Interaction (HCI) and Interface Design . . . . . 19
2.7 Empirical Usability Assessments of Current Platforms . . . . . 22
2.8 Research Gap and Summary . . . . . 23

**3 Requirements** **26**

3.1 Brief . . . . . 26
3.2 Stakeholders . . . . . 26
3.3 Use Case Scenarios . . . . . 27
3.4 Functional Requirements (FR) . . . . . 30
3.5 Non-Functional Requirements (NFR) . . . . . 35

**4 Design & Specification** **39**

4.1 Brief . . . . . 39
4.2 Design Rationale and Principles . . . . . 39
4.3 Conceptual System Model: Smart Photos (bu cok mu repetition) . . . . . 43
4.4 Functional Specification . . . . . 44
4.5 Non-Functional Specification . . . . . 49

**5 Implementation** **53**

5.1 Brief . . . 53
5.2 Technology Choices and Prototype Scope . . . 53
5.3 Development Process . . . 55
5.4 Components and State Management . . . 58
5.5 Translation to a Functional Prototype . . . 65
5.6 Prototype Boundaries and Limitations (does this belong to chapters: discussion, results/evaluation, conclusion/future work or this one?) . . . 76
5.7 Challenges and Solutions . . . 76
5.8 Software Testing . . . 76

**6 Legal, Social, Ethical and Professional Issues 77**
6.1 Legal Issues . . . 77
6.2 Social & Ethical Issues . . . 77
6.3 Professional Issues . . . 77

**7 Results/Evaluation 78**
7.1 Brief . . . 78
7.2 Interview-based Evaluation . . . 78
7.3 Thematic Analysis Findings . . . 84
7.4 Summary of Findings . . . 92

**8 Discussion 93**
8.1 Actionable Recommendations & Future Work . . . 93
8.2 Limitations . . . 93

**9 Conclusion and Future Work 94**
Bibliography . . . 101

**A Extra Information 102**
A.1 Tables, proofs, graphs, test cases, ... . . . 102
A.2 Survey Information Sheet . . . 102
A.3 Survey Questions . . . 102

**B User Guide 103**
B.1 Instructions . . . 103

**C Source Code 104**
C.1 Instructions . . . 104

# Chapter 1

# Introduction

The widespread use of digital messaging platforms has transformed how people share personal images, maintain relationships, and negotiate boundaries in everyday communication. Despite developments in security safeguards, users continue to face substantial difficulties in controlling shared content once it reaches another person's device. Current messaging platforms provide protection against external threats but offer limited tools for managing interpersonal risks such as regret, changing relationships, or misuse of personal photos (Trepte, 2020). These vulnerabilities are especially concerning given that consent in digital contexts is frequently dynamic rather than static, and users may seek to modify or withdraw access to shared material over time. Major messaging applications such as WhatsApp, with over 3 billion monthly active users (Statista, 2025), employ end-to-end encryption to secure message content. Yet this model does not extend to post-delivery control between users, leaving senders without meaningful mechanisms to revoke or modify consent once a photo has been delivered. While recent studies in privacy, digital safety, and interpersonal communication emphasise the significance of modifiable consent, practical design solutions for major messaging apps remain underdeveloped. Further work is needed to explore interaction models that support revocable consent without disrupting existing communication patterns. Although WhatsApp is used as the primary case study, the user needs and interaction principles explored in this project are intended to generalise to other messaging platforms that support private photo sharing and forwarding.

## 1.1 Motivations

Personal photos have become a common method of expression and interaction in digital communication, with users sharing them on a regular basis across WhatsApp. However, once an image is sent, users often lose the ability to influence how it will be used, stored, or redistributed. This lack of post-sharing control creates a disconnect between the technical protections offered by WhatsApp and the changing, context-dependent nature of interpersonal consent. While end-to-end encryption protects messages from external access, it does not address how users manage privacy between one another, nor does it accommodate situations where consent evolves over time.

There exists researches to some extent across digital privacy, human–computer interaction, and online safety, highlighting increasing concerns about image misuse and the loss of control users experience after sharing personal content. However, the practical design of mechanisms to prevent these issues, particularly in the context of dynamic consent, remains underexplored. Most existing work on consent revocation focuses on legal or conceptual frameworks rather than on usable, interface-level solutions within everyday messaging platforms such as WhatsApp. This project is motivated by the need to address this gap by examining how WhatsApp can better support ongoing, revocable consent when users share photos.

## 1.2 Scope

This project examines post-sharing consent revocation for personal photos in WhatsApp across multiple communication contexts, including one-to-one private chats, group messaging, and semi-public spaces such as communities. The primary focus is on how users can modify or withdraw consent after sharing photos, and how interface design can support this across different audience sizes and social dynamics. The scope is limited to image-based content; calls, video calls, videos, voice notes, documents, and status updates are excluded. The research is confined to user experience and interface design, investigating user-facing interaction patterns rather than underlying system architecture or encryption mechanisms. Large-scale user testing, behavioural studies, and technical feasibility assessments fall outside the project scope.

## 1.3 Research Questions

This project is guided by a set of research questions that aim to investigate how consent revocation can be effectively supported within WhatsApp's messaging environment. These questions address the limitations of current functionality, the expectations and concerns of users, and the design requirements for implementing revocable consent in a way that is understandable, usable, and trustworthy. Together, they shape the direction of the background research, design specification, prototype development, and evaluation.

The research questions are as follows (1 main question, 5 supporting questions):

**Main research question:** How can WhatsApp be designed to support clear, usable, and trustworthy mechanisms for revoking or modifying consent after users share photos in private conversations?

1. What limitations exist in WhatsApp's current design for managing photo sharing, and how do these limitations affect users' ability to control shared content?

2. What expectations, concerns, and behaviours do WhatsApp users have regarding post-sharing control of personal photos?

3. Which interface elements and interaction patterns best communicate photo permissions and make revocation options understandable within WhatsApp's existing UI?

4. How can the process of revoking or modifying consent be designed to be intuitive and fair for both the sender and the recipient?

5. How do the proposed revocation features affect the' perceived trust, safety, and sense of control of users when sharing photos on WhatsApp?

## 1.4 Aim and Objectives

The aim of this project is to develop and assess user interface mechanisms that facilitate revocable, ongoing consent within WhatsApp's photo-sharing environment, allowing users to maintain control over shared content in a transparent, intuitive, and reliable manner.

To achieve this aim, the project pursues the following objectives:

1. Analyze the limitations of the current WhatsApp design in relation to the control of photo-sharing.

2. Investigate user expectations, concerns, and behaviours with respect to post-sharing consent.

3. Define functional and non-functional requirements for effective consent revocation features.

4. Design a set of interface components and interaction flows that demonstrate how revocable consent can be integrated into the WhatsApp user interface.

5. Develop a high-fidelity prototype that illustrates the full permission and revocation workflow.

6. Evaluate the usability, clarity, trustworthiness, and perceived fairness of the proposed features through user testing.

7. Reflect on the broader implications for user safety, privacy, and ethical communication design.

## 1.5 Contributions

The project makes the following contributions:

1. A high-fidelity interactive Figma prototype demonstrating a redesigned consent revocation system for photo sharing in WhatsApp-like messaging environments.

2. A set of realistic interaction flows, UI states, and permission management behaviours modelling how revocable consent could function in practice.

3. A usability evaluation of the proposed design, assessing clarity, perceived trustworthiness, and fairness for both senders and recipients.

4. A human-centred design analysis of the practical implications of enabling revocable consent for photo sharing in messaging platforms.

## 1.6 Key Takeaways

## 1.7 Report Structure

# Chapter 2

# Literature Review

## 2.1 Brief

This chapter examines the literature on how the design of online messaging platforms shapes users' ability to understand, manage, and revoke consent, with a specific focus on photo sharing on WhatsApp. It begins with a brief overview of digital messaging and photo-based communication to situate the social and privacy-sensitive nature of image sharing. It then reviews relevant theoretical and consent-related perspectives to explain why consent revocation is not only a technical issue but also a contextual and interpersonal one. The chapter subsequently examines research on instant messaging, photo sharing, and interface design to assess how current platform features support or constrain meaningful user control. Finally, it synthesises the literature to identify research gaps that motivate the proposed user-centred revocation design.

## 2.2 Digital Messaging and Photo Sharing

Digital messaging has developed from earlier forms of computer-mediated communication into mobile, app-based, and increasingly multimodal communication environments, where text, images, and other media are integrated within the same platforms. Herring's historical overview highlights this shift from predominantly text-based CMC toward convergent and multimodal communication systems, providing a useful background for understanding contemporary messaging platforms [23]. Research on mobile messaging also shows how texting became embedded in everyday social contact, particularly in peer communication shaped by social norms and

situational constraints [27]. In parallel, early camera-phone studies show that images were used not only for personal capture but also for communication with absent others and remote tasks, helping establish photo messaging as a routine social practice [30]. This transition is important because it created communication settings in which image sharing carries social meaning and privacy expectations that may later complicate consent revocation.

## 2.3 Digital Privacy in Modern Communication

This section grounds the dissertation in theories that explain why consent revocation is not simply a delete button, but a socially negotiated and context-dependent action.

### 2.3.1 Communication Privacy Management (CPM)

Communication Privacy Management (CPM) theory explains privacy as an ongoing process of boundary management rather than a fixed state, making it useful for analysing disclosure in interpersonal and mediated communication [11, 46]. Petronio and Child (2020) describe CPM as a framework in which individuals treat private information as something they own and control, and they manage access to it through privacy rules shaped by context, relationship, perceived risk, and expectations about appropriate use after disclosure [46]. A key concept is co-ownership: once information is shared, recipients may become legitimate co-owners who develop their own assumptions about how that information can be retained, discussed, or circulated [46]. CPM therefore shifts attention from information itself to the negotiated rules and expectations that organise its flow.

This matters for consent revocation in messaging because consent revocation in messaging is not only a technical question of whether content can be deleted; it is also a social question about whether previously established privacy expectations can be changed after disclosure [11, 46]. CPM helps explain why post-sharing control is often contentious: a sender may understand revocation as a reassertion of personal control, while a recipient may interpret the same act as changing the rules after access has already been granted [46]. Hence, CPM provides a strong theoretical foundation for studying consent and control in messaging-based photo sharing, where interpersonal expectations are central to how users judge fairness, trust, and appropriateness.

Applied to revocable or dynamic consent in messaging, CPM suggests that revocation should be understood as an attempt to re-coordinate privacy boundaries rather than simply erasing data

[46]. The theory's concept of boundary turbulence is especially relevant here, as turbulence occurs when co-owners hold conflicting privacy rules or when expected information flows break down [46]. In messaging environments such as WhatsApp-style photo sharing, this framework helps explain why consent may need to be updated over time and why platform mechanisms for revocation must operate within the tension between social boundary expectations and the technical ease of retention, copying, or redistribution [11, 46].

### 2.3.2 Contextual Integrity (CI)

Contextual Integrity (CI) reframes privacy as appropriateness of information flows, not simply secrecy or access control [41]. Nissenbaum (2011) argues that information sharing is governed by contextual norms: who is involved (actors), what is shared (attributes), and how it moves (transmission principles) [41]. This is directly relevant to WhatsApp photo sharing because users ofMNten treat a private chat as a bounded context with an implied "right audience," even when the content is not technically protected from recipient-side redistribution. Under CI, harm occurs when a photo's flow changes context (e.g., from a one-to-one chat into a group, another platform, or offline circulation) because the transfer violates the original contextual expectations, even if the sender originally shared willingly [41].

CI is also useful for critiquing the limits of the notice-and-consent paradigm in everyday messaging. Nissenbaum (2011) critiques notice-and-consent as insufficient for online privacy governance, while Bourgeus and Vandercruysse (2024) argue that overreliance on consent often fails to produce meaningful privacy control in complex data ecosystems and motivate contextual and communal alternatives [5, 41]. This matters for photo sharing because images frequently involve group privacy: a photo can affect the sender, the recipient, and any depicted co-subjects, each with potentially different expectations about appropriate sharing [5]. Design implication: revocation mechanisms should be framed as restoring context-appropriate flow (limiting further redistribution and future access within WhatsApp), and the UI should represent that permissions apply to a social context (audience and transmission rules), not just to an individual recipient or a one-time send action.

### 2.3.3 Media Richness Theory (MRT) and Social Presence

Media Richness Theory (MRT) holds that communication media vary in their capacity to convey information in ways that support interpretation and mutual understanding, and that

richer media are generally better suited to tasks involving ambiguity (equivocality) [12]. In Daft and Lengel's account, rich media allow more immediate feedback and convey a greater variety of cues, which can help communicators clarify meaning and reduce misunderstanding when issues are socially sensitive or open to multiple interpretations [12]. WhatsApp-style messaging that includes photo sharing can therefore be treated as relatively rich in everyday practice because it combines rapid interaction with visual content that can communicate relational and emotional information. At the same time, empirical work has qualified strong deterministic readings of MRT: Dennis and Kinney (1998) report that while cue and feedback properties shape perceptions of media richness, matching media richness to task equivocality did not reliably improve performance outcomes in their study [14].

Social Presence Theory provides a complementary lens by emphasising the interpersonal qualities of mediated communication. Short, Williams, and Christie (1976) conceptualise social presence as the extent to which a medium conveys the salience of the interaction partner and the sense of interpersonal involvement, with higher social presence generally associated with greater warmth and immediacy in interaction [52]. In contemporary messaging contexts, this helps explain why users may prefer channels that support richer interpersonal signalling for relational communication, even when such channels also create additional privacy and control demands. Ishii et al. (2019) further argue that media richness should be revisited for modern technologies because users' experiences of richness are shaped not only by channel properties but also by evolving features and patterns of use, which is particularly relevant for mobile messaging environments [26].

Taken together, MRT and Social Presence Theory help explain why revocable or dynamic consent in messaging is not only a technical problem but also a socially consequential one. When users select richer media for intimate or socially sensitive exchange, the interaction may carry stronger interpersonal involvement and relational expectations about how shared content ought to be handled [12, 52]. In such contexts, withdrawing consent may be experienced as a delicate change in interpersonal boundaries rather than as a neutral technical action, because it can signal mistrust or create a sense of relational distance. Design implication: revocation mechanisms in WhatsApp-style photo sharing should be designed with attention to this social meaning, supporting face-saving and relationship maintenance while clearly communicating the practical limits of technical control in the presence of retention and recirculation practices [14, 26].

## 2.4 The Concept of Consent

This section examines consent in digital communication and argues that, in messaging contexts, it should be understood as an ongoing process rather than a one-time decision. While legal frameworks define the formal conditions under which consent is considered valid, consent in interpersonal messaging also functions as a relational and contextual expectation about what others may appropriately do with shared content.

### 2.4.1 The Legal Mandate (Bunu intro motivation kismina alabilirsin??)

Although the GDPR is not designed specifically for consent revocation in online messaging platforms, it provides a useful benchmark for how valid consent and withdrawal should be implemented in such environments. Under the GDPR, consent must be freely given, specific, informed, and unambiguous, and withdrawal must be as easy as giving consent; where consent is withdrawn and no other legal basis remains, the right to erasure may also be engaged [15, 47]. Chaurasiya (2025) shows that the Indian DPDP Act adopts a similar consent-centred approach by defining consent in affirmative terms and recognising mechanisms for managing and withdrawing it [9]. However, as Politou et al. (2018) note, revocation operates prospectively rather than retroactively, and erasure becomes technically difficult once data have been copied, shared, or replicated across systems [47]. In distributed communication contexts such as messaging, the legal mandate therefore establishes a right to revoke consent, but not a guarantee of complete practical forgetting.

### 2.4.2 Consent Fatigue, the Validity Gap, and Non-Use

Although legal and policy frameworks often treat consent as meaningful once it has been formally obtained, this assumption is difficult to sustain in contemporary digital environments. Baruh and Popescu argue that privacy self-management based on notice and choice places too much responsibility on individuals, even though data practices are often opaque, complex, and difficult to resist in practice [3]. In such settings, consent may be legally valid without being substantively meaningful, creating a validity gap between formal agreement and real user control. They further show that users may respond in two limited ways: through partial withdrawal or avoidance when privacy risks feel unmanageable, or through assimilation, where users accept reduced control and rely on market-provided protections [3].

Waldman extends this critique by showing that privacy is often operationalised narrowly within

organisations. In his account, lawyers tend to reduce privacy to notice and choice, while engineers often equate it with security or encryption, leaving limited space for more user-centred understandings of consent and control [56]. For the present topic, this suggests that effective revocation cannot depend only on formal consent or interface disclosure, but must be supported by designs that make control realistic and usable in practice.

### 2.4.3 Consent Models

Consent in everyday messaging cannot be understood adequately as a one-off, individualised act of permission, because interpersonal communication unfolds over time, across relationships, and under conditions of partial and often irreversible loss of control. Most of the revised consent models discussed below were developed in health, research, or broader data-governance settings rather than instant messaging; they are used here analytically, as conceptual tools for thinking about permission, revision, and withdrawal in WhatsApp-style communication. Traditional consent frameworks tend to assume that consent is static, singular, and transaction-like, yet this logic becomes unstable in ongoing interpersonal exchange, where the meaning of permission can shift after disclosure. As Burkhardt et al. suggest, meaningful consent depends not only on formal agreement but also on understanding and perceived control, while work on consent and revocation has also shown that decisions made at one moment cannot remain fully informed across the lifetime of data use [1, 8]. This is why dynamic consent has been positioned as a response to one-off authorisation models that ask people to agree to future uses they may neither anticipate nor revisit [51]. In messaging, these weaknesses are particularly visible because permission is shaped by repeated interaction, changing context, recipient interpretation, and what happens after content has already been sent.

Dynamic Consent offers the clearest correction to this temporal problem by treating permission as revisable rather than fixed. Across the literature, it is characterised by ongoing engagement, granular choice, and the possibility of adjusting preferences over time rather than accepting a single all-or-nothing decision [29, 31]. This broader orientation is reinforced by Wilbanks' argument that digital consent should be designed as the beginning of an ongoing ethical relationship rather than a one-time administrative step, and by later work that frames modifiable consent choices as central to user-centred data governance [39, 65]. However, what Dynamic Consent improves most clearly is temporality, not post-disclosure control. In everyday messaging, the ability to revise a preference does not necessarily translate into the ability to affect already-delivered content once it has moved beyond the sender's immediate control.

Revocable Consent is therefore closer to the central concern of this dissertation, because it foregrounds withdrawal after permission has already been granted. The literature usefully distinguishes between revocability as a normative requirement and revocation as a practically enforceable outcome. Consent and revocation have been framed as ongoing controls, with informed revocation emphasising that users should understand the forms of withdrawal available to them [1]. Related technical work similarly treats withdrawal as a change in the scope of authorised access: users should be able to specify who may access data, for what purposes, and for how long, while formal models of consent evolution represent revocation by closing a previously open interval of collection or access rather than undoing prior disclosure [35, 48]. This distinction is especially important for photo sharing, where a sender may be able to end future authorised access without being able to retract a photo that has already been viewed, saved, or copied by a recipient. Revocation in messaging is therefore best understood as limiting future legitimacy and platform-supported access, not as guaranteeing recovery of the original disclosure. This problem is reinforced by the broader notice-and-consent literature, which shows that even ostensibly reversible interfaces can fail to produce meaningful control when the design of choice itself is manipulative or unclear [42].

Other models address narrower weaknesses in static consent without resolving the broader problem. Retroactive consent is useful because it makes the timing of authorisation explicit, allowing consent and withdrawal to be analysed in terms of whether their effects apply to past or future data practices [48]. A related response is to reduce persistence prospectively by limiting the duration or openness of permission. Although Im et al. do not formalise ephemeral consent as a standalone governance model, their emphasis on consent as revertible and specific supports the idea that permission should be bounded and revisable rather than indefinite [24]. Yet these approaches remain partial. Once content has been copied, remembered, or redistributed by others, neither temporal expiry nor after-the-fact adjustment can fully restore sender control.

Seen comparatively, these models should not be treated as mutually exclusive competitors, but as attempts to repair different weaknesses in conventional consent. Dynamic Consent responds most clearly to temporality; Revocable Consent foregrounds withdrawal and reversibility; retroactive approaches sharpen how timing affects authorisation; and ephemeral approaches seek to limit persistence before problems arise. What unites them is a shared difficulty in accounting for messaging as a social practice in which the meaning and consequences of disclosure continue to evolve after the moment of sending [24, 29, 47, 48]. The central problem is therefore

not simply lack of choice, but the challenge of aligning revisability, revocability, relationality, and downstream loss of control within a single model.

For this reason, affirmative and ongoing consent offers the strongest conceptual direction for this dissertation. Im et al. describe affirmative consent as voluntary, informed, revertible, specific, and unburdensome, providing a framework that treats permission as active and revisable rather than presumed or exhausted at a single point in time [24]. These principles fit messaging more closely than one-off models because they better reflect how consent is negotiated in unfolding interaction. At the same time, they should not be overstated as a technical solution to screenshots, retention, or redistribution. Their value is conceptual and normative: they offer a clearer account of what responsible design should support, namely permission that can be revisited, clarified, limited, and renegotiated without assuming that post-sharing control can ever be complete.

This issue becomes even more complex in photo sharing, where consent may extend beyond a single sender-recipient relationship.

Taken together, the literature suggests that the main weakness of conventional consent models is not simply insufficient granularity, but their inability to account for the ongoing social life of shared content. Improved models repair important dimensions of this problem, but they still encounter hard limits once messages and photos enter interpersonal networks where recipients can retain, reinterpret, copy, or redistribute them. For everyday messaging, meaningful consent is therefore best understood not as a completed transaction but as an ongoing and socially situated process whose practical force depends on both relational norms and the technical limits of post-sharing control.

## 2.5 Consent in Instant Messaging and Photo Sharing

This section connects the consent concepts and theories to the specific realities of photo sharing in instant messaging, focusing on WhatsApp context.

### 2.5.1 Multi-Party Privacy Conflicts (MPCs)

Multi-party privacy conflicts arise when a single photo implicates several people whose privacy interests do not align, making individualised models of consent inadequate for photo sharing. In the photo-sharing literature, MPCs are generally understood as situations in which the person

who decides to share content is not the only person who bears the privacy consequences of that disclosure. One user's act of sharing can expose others depicted in the image, even where those others have had no meaningful opportunity to approve, refuse, or shape that disclosure. Cherubini et al. show that this problem is especially salient for co-owned content such as group photos, while Liu et al.'s survey of image privacy similarly suggests that privacy in online image sharing is shaped not only by image content itself but also by relationships, context, and multi-party interaction [10, 33]. Applied to instant messaging, this means that a shared photo may simultaneously involve the sender, the recipient, and any depicted co-subjects, each of whom may hold different expectations about whether the image should be sent, retained, forwarded, or later withdrawn. Consent in photo sharing is therefore not only ongoing, as argued in the previous subsection, but also distributed across multiple stakeholders from the outset, which makes sender-only models of permission normatively and practically incomplete [10, 33].

The literature proposes several responses to multi-party privacy conflicts, but these approaches often manage the problem more effectively than they resolve it. Cherubini et al. distinguish between precautionary mechanisms, which prevent or constrain sharing before disclosure, and dissuasion mechanisms, which seek to discourage risky sharing by prompting reflection on possible consequences [10]. They find that participants generally prefer precautionary mechanisms because these provide stronger protection for affected parties and reduce uncertainty for uploaders, although they also introduce friction and depend on identifying co-owners in advance [10]. This limitation is reflected in technical proposals. Xu et al. (2017) propose a system in which people appearing in a photo can be identified and involved in the sharing decision, but this depends on a privacy-preserving facial-recognition process to detect co-owners in the first place [66]. Again in another paper, Xu et al. (2019), similarly develop a trust-based privacy-preserving sharing model that allows selective protection of co-owned content, yet the approach still treats the problem largely through pre-sharing optimisation and does not fully incorporate direct negotiation among all affected parties [67]. Zhang et al. (2023) extend this critique by arguing that privacy-preserving frameworks often define ownership too narrowly and do not fully address the risks introduced by subsequent forwarding and cross-platform dissemination [68]. Taken together, these approaches are important because they show that co-ownership cannot be reduced to sender-side privacy settings alone, but they remain largely pre-sharing, system-centred, or prediction-based, and therefore struggle to reconcile competing interests once the image becomes socially and technically mobile [10, 66, 67, 68].

Multi-party privacy conflicts therefore show that consent revocation in messaging is not simply a matter of allowing one sender to change their mind, but a broader problem of shared stakes and weakening control once images begin to circulate [10, 68].

### 2.5.2 Persistence, Recipient Control, and the Limits of Revocation

Multi-party privacy conflicts show that control over a photo may already be shared before it is sent; the next limit is structural. In instant messaging, revocation does not operate as ongoing access control after delivery, because the system's basic function is to transmit content to a recipient-controlled device rather than to preserve sender authority over it indefinitely. For that reason, revocation is best understood as prospective and partial: once a photo has been delivered, a platform may still alter later in-app availability, but it cannot guarantee retrieval of the original disclosure. This is consistent with earlier work on revocation as a forward-looking rather than fully retroactive mechanism, and with Schnitzler et al.'s observation that deleting messages from a recipient's history is substantially harder than deleting them locally, even in closed messaging ecosystems [1, 47, 50].

WhatsApp provides a useful case because its privacy architecture and its revocation features point in different directions. On the one hand, WhatsApp emphasises end-to-end encryption and states in its UK Privacy Policy that messages are typically stored on users' devices rather than on its servers once delivery has occurred; on the other hand, this very model means that post-delivery control is necessarily limited [60, 64]. Deletion, disappearing messages, and view-once media should therefore be interpreted as bounded platform-level controls over later visibility, not as guarantees of erasure. WhatsApp's own help documentation states that recipients may see a message before deletion succeeds, that unsuccessful deletion may not be flagged to the sender, and that iOS recipients may still have media saved in Photos even after the message is deleted from the chat [62]. Likewise, disappearing messages only affect new messages and can be kept in the chat, while unopened view-once media can still be restored from backups; even newer protections such as Advanced Chat Privacy are described as helping prevent content from being taken outside WhatsApp by restricting export and auto-download, which reinforces that these features mitigate persistence routes rather than eliminate them [58, 59, 61, 63].

The weakness of revocation is not only technical but also interpretive. Schnitzler et al. show that users do not always correctly understand what a deletion action actually does, and that

clearer interface explanations improve their ability to assess deletion outcomes; in their study, participants in the WhatsApp condition understood message deletion more accurately than those in the Skype condition, partly because WhatsApp more clearly distinguishes local from broader deletion effects [50]. The same study also shows that deletion notices and other residual traces matter socially: participants were sometimes surprised not by whether deletion occurred, but by the notification that a message had been deleted, and some explicitly associated such traces with mistrust or ambiguity. In this sense, revocation in WhatsApp photo sharing is also an expectation-management problem. If interface cues suggest stronger control than the system can actually deliver, users may overestimate what deletion has achieved; if revocation is made too visibly traceable, it may also generate interpersonal friction rather than simply restore privacy [50].

If this subsection shows that revocation is already limited within the platform once a photo has been delivered, the next subsection shows that persistence becomes even harder to govern when recipients can capture and recirculate content through channels the platform cannot fully control.

### 2.5.3 The Screenshot Threat

The screenshot threat matters because it creates a form of persistence that no longer depends primarily on the platform's own retention settings. WhatsApp's privacy-oriented features, including disappearing messages, 'view once' media, and advanced chat privacy, can limit some later visibility or sharing within the app, but they do not fully govern what a recipient can do after viewing content [58, 59, 61, 64]. As Heath et al. note, even disappearing-message systems leave open preservation routes such as forwarding, screenshotting, copying, saving, or photographing content before it disappears [21]. As Ingber argues, screenshots turn part of a conversation into a new file on the recipient's device, making it easier to store, reuse, and circulate beyond the original exchange [25]. Screenshotting therefore creates a parallel persistence route that sits partly outside the logic of in-app revocation and ephemerality: even if the original message becomes less visible within WhatsApp, a copied representation may continue to exist elsewhere. More broadly, image-privacy scholarship identifies the recipient side as a continuing source of privacy risk once content is already in circulation, because recipients may retain or recirculate images beyond the sender's intended audience [33].

What makes screenshots especially important for this dissertation is that they are not only

technical workarounds but socially meaningful acts. Ingber distinguishes screenshot collection from screenshot sharing and shows that both can generate distinct privacy harms, because they move co-owned information into a new context without notice or consent [25]. This matters for consent because, as Im et al. note, affirmative consent must be specific: permission to share a photo with one recipient does not automatically extend to copying or recirculating it beyond the original interaction [24]. In WhatsApp photo sharing, screenshots therefore make revocation not only technically weak but normatively contested, as recipients may treat capture as harmless remembering, evidence, or legitimate reuse while senders may understand it as a breach of containment and trust.

For this reason, screenshot risk should be treated not as a marginal loophole but as a central challenge for any interface that presents revocation or ephemerality as meaningful user control [21, 25, 33].

## 2.6 Human Computer Interaction (HCI) and Interface Design

This section synthesises HCI research on why consent and revocation controls in digital platforms often fail in practice, and which interaction patterns can support meaningful, revisable user control in fast-paced messaging photo-sharing contexts [5, 65]. It focuses on the usability and integrity of control—whether users can locate, understand, and confidently act on privacy options without being nudged or steered toward platform-favoured outcomes [42].

### 2.6.1 Interface Failures and Manipulative Patterns

Even when platforms formally provide privacy and consent controls, HCI research shows these mechanisms often fail to produce meaningful user control at the interface level. This is an issue that becomes especially consequential in messaging-based photo sharing, where disclosures are often intimate, fast, and difficult to reverse once an image leaves the sender's device. Classic notice-and-choice approaches are frequently ineffective because notices are not usable or useful in practice, are often ignored, and are frequently treated as something bolted onto a system rather than integrated into its interaction design [49]. This breakdown is reinforced by broader critiques that modern data ecosystems create information asymmetries and complexity that make privacy self-management unrealistic: privacy policies are often too long and complex

to support real understanding, resulting in passive acceptance rather than informed decision-making [5, 65]. In messaging and social media settings, this becomes visible as concrete usability failures: expert evaluations using privacy-focused heuristics find that the ability to revoke consent is among the most problematic areas across popular apps, and that privacy information is inconsistently placed in menus in ways that undermine core usability principles such as consistency [2]. For photo sharing, the implication is straightforward: users cannot withdraw consent meaningfully if image-related controls (e.g., deletion, visibility, sharing restrictions) are hard to locate, hard to compare, and ambiguous about what they actually change—particularly when users are acting quickly in-chat and assume a "delete" action restores privacy.

This problem is intensified when interface designs do not merely confuse users but actively steer them toward platform-preferred outcomes. Empirical work on consent dialogs shows that "consent" interfaces commonly use design tactics that encourage acceptance of defaults (e.g., making "accept" more prominent, hiding configuration behind additional steps, or omitting an obvious decline path), so the banner functions more like a notification than a genuine control mechanism [4]. Analyses of GDPR-oriented consent pop-ups likewise argue that dark-pattern strategies can be used to circumvent the regulation's intent "by design," and that rights-protecting regulation is weakened if interface design is left unaddressed [53]. From a legal/HCI perspective, this steering is especially problematic because valid consent requires a meaningful choice and the ability to withdraw consent, and designs that make "accept" more salient than "reject" or that hide privacy-relevant options undermine that balance [18]. Experimental evidence also suggests that cookie-consent regimes often do not work as intended: participants frequently select privacy-unfriendly options and report low perceived control, raising concerns that interface-level nudges and defaults can hollow out the ideal of deliberative consent [19]. For WhatsApp-style photo sharing, the key implication is that revocation controls must not only exist but must be reachable, interpretable, and resistant to interface choices that overstate user agency or make withdrawal harder than acceptance.

Taken together, these failures motivate the next subsection's focus on what interaction patterns can actually support informed, revisable consent—for example, by treating notice timing and control presentation as explicit design dimensions [49] and by using interaction techniques that increase user attention to what they are disclosing [32].

### 2.6.2 Interactive Design for Meaningful and Revocable Consent

Constructive HCI work suggests that meaningful consent is best supported when it is designed as an explicit, understandable interaction rather than a frictionless checkbox event. In e-consent, Wilbanks argues that interface design shapes whether people actually attend to and understand what they are agreeing to, implying that consent should be treated as a designed experience that encourages comprehension rather than mere completion [65]. Relatedly, affirmative-consent work frames consent as requiring conditions such as being informed, specific, and revertible, which translates at the interface level into making actions intentional, consequences legible, and outcomes visible [24]. On mobile devices in particular, interaction techniques can be used to increase user engagement with the consent act itself: Lindegren et al. show that alternative smartphone consent designs intended to engage users (beyond a standard tap-through) can increase attention to what is being agreed to [32]. For messaging photo sharing, these insights imply that consent-relevant controls should be embedded into the moment of sending in a way users can notice under time pressure, and should provide clear feedback and states so users can tell what has changed after they act.

The same interactional logic extends from initial permission to later revision and withdrawal. Schaub et al. emphasise that the effectiveness of privacy notices depends on design dimensions such as timing and delivery context, supporting the use of just-in-time and contextually placed cues rather than relying on static policies [49]. For photo sharing, this points toward revocation controls that remain reachable after sending and are paired with explanations that honestly communicate scope. Where revocation is difficult to operationalise after disclosure, HCI work on multiparty privacy conflicts shows that design can intervene earlier through precautionary mechanisms (e.g., requiring collaboration/approval) or dissuasive mechanisms (e.g., friction or warnings that prompt reconsideration) [10]; these approaches are especially relevant to photo sharing because they can reduce avoidable disclosures before images become socially and technically mobile. Dynamic-consent literature strengthens this orientation by treating permissions as reviewable and updateable over time via interface-supported communication and preference management [29, 31, 51]. Technical proposals for dynamic consent management further highlight capabilities such as explicit expression of consent choices, access to consent history, and withdrawal support across a data lifecycle [35], while adoption-focused reviews emphasise that continuous communication and multiple modalities can facilitate use, but also note practical barriers such as consent fatigue and implementation complexity [31]. For WhatsApp-style

photo sharing, the design takeaway is not to promise perfect post-sharing control, but to build interactions that help users act deliberately at sharing time, understand the practical scope of revocation, and revisit decisions later through clear, contextual, and interpretable controls.

Overall, for messaging-based photo sharing the central HCI challenge is to design consent and revocation interactions that remain understandable and revisable over time, without implying that interface controls can fully overcome the limits of downstream retention and redistribution.

## 2.7 Empirical Usability Assessments of Current Platforms

Empirical evaluations suggest that revocation-related privacy controls are frequently available in principle but weak in usable effectiveness. In a STRAP-based expert heuristic evaluation of WhatsApp, Twitter, and Snapchat, Albesher and Alhussain identify the "ability to revoke consent" as the most notable problem area across all three apps, noting that none provides a clear way to revoke the underlying user agreement and that revocation (where offered) can be conditional or unreliable in its practical effect [2]. They also report that privacy information and settings are presented inconsistently across apps, undermining basic usability principles such as consistency and making control harder to locate and interpret [2]. Complementary legal-empirical evidence from the web consent ecosystem reinforces this availability–effectiveness gap: Kancherla et al. find that many popular sites make revocation interfaces absent or more complex than acceptance, and that revocation is often not correctly recorded or communicated to third parties, with tracking sometimes persisting even after users attempt to withdraw consent [28]. Taken together, these results support a general empirical takeaway: revocation tends to be a high-severity usability weakness, not simply a missing feature.

WhatsApp provides a concrete case of revocation-adjacent controls that remain bounded and context-dependent rather than fully reliable or granular consent management. Platform features such as message deletion, disappearing messages, view-once media, and chat-level protections can reduce some forms of persistence and re-sharing within the app, but they operate as mitigations rather than guaranteed erasure or downstream control [58, 59, 61, 62, 64]. Forensic analysis of ephemeral messaging further illustrates why these controls remain partial in practice: Heath et al. document how disappearing-message behaviour varies across platforms and storage locations, and they note WhatsApp's own acknowledgement that content can be preserved through actions such as replying (quoted content), forwarding into contexts where disappearing settings differ, or capturing content via screenshots/photography before expiry

[21]. Their results also show that message timers and residual artefacts can remain in application databases, reinforcing that ephemerality does not automatically eliminate persistence [21]. Overall, existing platforms provide controls that gesture toward revocation, but empirical and platform evidence suggests these controls remain partial, inconsistently interpretable, and weaker in practice than their presence implies.

## 2.8 Research Gap and Summary

Taken together, the literature reviewed in this chapter shows that consent revocation in messaging is neither a purely technical function nor a fully solved interface problem. Earlier sections establish that revocation is socially negotiated, only partially effective after delivery, vulnerable to forwarding and screenshots, and difficult to translate into interaction models that users can understand and act on in practice [21, 25, 42, 46, 47, 65]. The remaining research gaps therefore concern not whether revocation matters, but how it can be operationalised, scoped, and evaluated in WhatsApp-like photo-sharing contexts.

### 2.8.1 RG1: Translating dynamic/ongoing consent into usable messaging UI

The chapter has shown that dynamic, ongoing, and revocable consent are conceptually better suited to messaging than one-off authorisation, because they treat permission as revisable over time rather than exhausted at the moment of sending [24, 29, 31, 51]. However, the literature reviewed here provides much stronger conceptual and governance-level accounts than concrete guidance on how such models become low-friction, intelligible interaction flows within routine messaging. The unresolved issue is therefore one of translation: how ongoing consent can be expressed through usable controls, reviewable states, and in-context permission management for everyday photo sharing without overwhelming users or overstating what those controls can achieve [35, 65].

### 2.8.2 RG2: Post-delivery control is partial and easily misunderstood under real redistribution conditions

The chapter also shows that real platforms already offer deletion and ephemerality features, but that these operate only as bounded post-delivery mitigations rather than enforceable recall. In WhatsApp-like systems, revocation becomes structurally weaker once content reaches recipient-

controlled devices, and users do not always interpret deletion cues or feature scope accurately [47, 50, 59, 61, 62]. This problem intensifies under actual redistribution conditions, because forwarding, saving, screenshotting, and other capture practices create persistence routes beyond platform-scoped revocation [21, 25]. The remaining gap is therefore not simply that current controls are imperfect, but that there is still no robust model for post-delivery control that remains user-comprehensible once circulation extends beyond the original in-app exchange.

### 2.8.3 RG3: Multi-party privacy and fairness are under-supported in revocation interaction design

Across the chapter, privacy has been framed as relational, context-dependent, and frequently multi-party: once a photo is shared, senders, recipients, and depicted co-subjects can all have legitimate but competing stakes in how it is retained, circulated, or withdrawn [10, 33, 41, 46]. Yet current messaging tools largely encode revocation as a sender-centred action, offering little support for co-subject agency, negotiation, or explanations that make revocation intelligible to all affected parties. The unresolved issue is therefore one of fairness as well as control: the literature does not yet offer a clear interaction model for revocation that balances stakeholder visibility, minimises unnecessary interpersonal blame, and remains understandable in socially sensitive exchanges [10, 25].

### 2.8.4 RG4: Limited WhatsApp-specific empirical understanding of revocable photo-permission expectations

The reviewed literature gives a strong account of why WhatsApp is an important case: its controls are widely used, bounded in scope, and socially meaningful in ways that affect trust, interpretation, and downstream sharing [25, 50, 58, 62, 64]. It also provides platform documentation, heuristic usability evaluation, and evidence about screenshot or deletion effects [2, 21, 25, 50]. What remains under-evidenced, however, is what WhatsApp users themselves expect from revocable photo permissions in ordinary relational contexts: what forms of control they would understand, trust, accept, or regard as socially fair. The final gap is therefore empirical and context-specific, centring on user expectations rather than on the technical existence of platform features.

### 2.8.5 Summary

Together, these gaps show that the central problem is not simply whether revocation exists, but whether it can be translated into interaction models that are understandable, fair across stakeholders, realistic about post-delivery limits, and grounded in the expectations of WhatsApp users. They therefore motivate the need for a messaging-appropriate mechanism that supports usable, socially intelligible, and realistically scoped revocation of photo access in WhatsApp-like contexts.

# Chapter 3

# Requirements

## 3.1 Brief

This chapter defines the requirements for the WhatsApp-like prototype developed in this dissertation. Drawing on the literature review, it identifies the relevant stakeholders, use cases, functional requirements, and non-functional requirements for a prototype centred on photo permissions and revocation. The implemented scope includes pre-send and post-send permission configuration, recipient understanding of changing access states, constrained forwarding to a secondary recipient, and co-subject-related features within the current prototype. Together, these requirements translate the dissertation's broader privacy and consent concerns into a structured and implementable system specification. (buna da bak-») Broader issues that remain beyond the present prototype scope are identified separately as deferred concerns.

## 3.2 Stakeholders

1. **Photo Sender:** The sender shares the photo and configures its permissions. This stakeholder requires clear pre-send and post-send controls, visibility over the current state of a shared photo, and interaction patterns that allow revocation or permission change without unnecessary confusion.

2. **Primary Recipient:** The primary recipient receives the sender's photo in the original chat. This stakeholder requires clear feedback about whether a photo remains visible, or

whether any kind of revocation action has been taken.

3. **Secondary Recipient:** The secondary recipient appears only when the primary recipient forwards a photo. This stakeholder is necessary because the prototype examines whether sender-defined permissions continue to shape access after redistribution within the platform model.

4. **Co-Subject:** The co-subject is a person depicted in a photo. This stakeholder is necessary because the prototype examines whether co-subjects can request changes to the photo's permissions.

## 3.3 Use Case Scenarios

**(UC-S0): Sender Configures Permissions Before Sending**

1. The sender opens a chat and selects or uploads a photo.

2. The sender prepares the photo for sharing by configuring the following settings:

   - Forwaring permission
   - View once permission
   - Download permission
   - Expiry Permission
   - Co-subject declaration

3. The sender sends the photo into the chat.

4. The photo appears in the conversation with the chosen permission state applied.

**(UC-S1): Sender Revises Permissions After Sending**

1. The sender returns to a chat containing a previously shared photo.

2. The sender clicks the photo options button in the top-right corner of the photo message.

3. The sender selects 'Revocation permissions' from the in-chat action menu.

4. The system displays the available permission controls in the same in-chat menu.

5. The sender revises one or more permissions.
    - The sender revokes or restores photo access.
    - The sender allows or blocks forwarding.
    - The sender allows or blocks downloading.
    - The sender sets, changes, or removes a time limit.
6. The system updates the photo state in the chat.
7. The sender and other relevant participants see the revised access state.

**(UC-R1): Primary Recipient Encounters Active, Revoked, or View-Once Access**

1. The primary recipient opens the chat containing the sender's photo.
2. The recipient views the photo's current state in the chat interface.
3. The system presents the photo according to its current permission state, so that the recipient either sees the photo, opens it as view-once content, or is informed that access is no longer available.
4. The recipient may open the photo options menu from the button in the top-right corner of the photo message.
5. The recipient acts within the limits of the available permissions, such as replying, forwarding, downloading, or requesting access.

**(UC-R2): Primary Recipient Forwards an Allowed Photo**

1. The primary recipient opens a chat containing a received photo.
2. The recipient attempts to forward the photo.
3. The system checks whether forwarding is currently permitted by the sender's settings.
    - If forwarding is allowed, the forwarding option remains available.
    - If forwarding is not allowed, the forwarding path is blocked.

4. The photo is forwarded with the sender-defined constraints preserved in the prototype model.

**(UC-SR1): Secondary Recipient Receives Constrained Forwarded Content**

1. The secondary recipient receives the photo in a separate forwarded chat after the primary recipient forwards it.
2. The system displays the forwarded photo using the original sender's current permission state.
3. The secondary recipient views the forwarded content through the interface.
4. The secondary recipient can interact with the photo only within the inherited constraints.
5. If the sender later revokes access or the photo expires, the forwarded content also becomes unavailable in the secondary recipient's chat.

**(UC-C1): Co-Subject Requests Revocation of a Shared Photo**

1. The co-subject opens their view of the chat containing a photo in which they are depicted.
2. The system shows that the co-subject appears in the shared photo.
3. The co-subject opens the photo or views its current access state through the interface.
4. The co-subject opens the photo options menu from the button in the top-right corner of the photo message.
5. The co-subject selects 'Request revocation'.
6. The co-subject may add an optional message explaining the request.
7. The system sends the revocation request to the sender for review.

## 3.4 Functional Requirements (FR)

| ID | Requirement | Justification | Research Gap |
|---|---|---|---|
| **1. Pre-send consent configuration** | | | |
| FR1 | The prototype must allow the sender to select a photo and configure permissions before sending. | Supports contextual, pre-send consent by enabling the sender to define sharing conditions at the point of disclosure, including forwarding, view-once behaviour, expiry, co-subject declaration, and saving/export permissions. This is consistent with literature on dynamic and revisable consent, in-context privacy choices, and interface support for notice and control. [10, 21, 24, 29, 31, 48, 49, 51, 58, 59, 61, 65] | RG1 |
| FR2 | The prototype must explicitly address screenshot and download risk (e.g. warn before sharing, indicate that screenshots cannot be fully prevented). | Supports realistic privacy communication by treating screenshot and download risk as a central limitation of photo-sharing control rather than a marginal exception. Literature on privacy notice and platform-based media protection emphasises warning users before sharing and clearly communicating that some forms of capture cannot be fully prevented. [10, 21, 25, 49, 58, 59, 61, 64] | RG2 |
| **2. Post-send revocation and permission management** | | | |
| FR3 | The prototype must allow the sender to modify or revoke access to a previously shared photo via contextual in-chat, photo-level controls. | Supports post-send, revisable consent by allowing the sender to manage permissions for an already shared photo through contextual in-chat controls. Literature on privacy control and consent revocation emphasises that permissions should remain reachable after disclosure and be open to later withdrawal or adjustment. [1, 2, 35, 47, 49, 50] | RG1 RG2 |

| ID | Requirement | Justification | Research Gap |
|---|---|---|---|
| FR4 | The prototype must show all users clear states for active, revoked, view-once access and expiry duration. | Supports user understanding by making permission states and their consequences visible within the chat interface. Literature on revocation, privacy feedback, and usable consent emphasises that people do not always understand what access changes mean, so interfaces should present clear, legible outcomes for active, revoked, and time-limited content. [2, 24, 49, 50, 59, 61, 62, 65] | RG2 |
| FR5 | The prototype must maintain a live consent state per shared photo recording current permission status, expiry, active or revoked access, and applicable restrictions. | Supports reviewable and revisable consent by maintaining an updatable record of each photo's permission state over time. Literature emphasises that explicit consent choices must remain available for later review and change.[29, 35, 48, 65] | RG1 |
| FR6 | The prototype should provide clear feedback after key permission-related actions. | Supports user understanding by making the outcomes of permission changes visible and interpretable. Literature on privacy feedback and usable consent emphasises that clear post-action feedback reduces ambiguity about what has changed. [2, 49, 50, 65] | RG1<br>RG2 |
| **3. Redistribution and forwarding control** | | | |

| ID | Requirement | Justification | Research Gap |
|---|---|---|---|
| FR7 | The prototype must constrain forwarding according to the sender's current permission state. | Supports sender-defined control over redistribution by allowing forwarding only when it is explicitly permitted. Literature on contextual privacy and downstream sharing emphasises that forwarding changes information flow and should remain subject to the original sender's transmission constraints.[10, 21, 25, 33, 41, 58, 63, 68] | RG2 |
| FR8 | The prototype must propagate sender-defined permissions to forwarded content within the proof-of-concept model. | Supports continuity of privacy control across redistribution by ensuring that forwarded content inherits the original sender's permissions within the prototype model. Literature on contextual integrity and downstream sharing emphasises that transmission constraints should persist across forwarding to preserve context and reduce secondary privacy loss.[10, 21, 33, 41, 58, 63, 68] | RG2<br>RG3 |
| FR9 | The prototype should make the forwarded context and secondary-recipient view clearly interpretable. | Supports legibility of redistribution by making forwarded context and secondary-recipient status clear in the interface.Literature emphasises that forwarding changes audience and context, so interfaces should clearly indicate redistribution state and recipient position.<br>[2, 10, 33, 41, 49, 50, 65, 68] | RG2 |
| **4. Recipient Awareness and negotiated consent** | | | |

| ID | Requirement | Justification | Research Gap |
|---|---|---|---|
| FR10 | The prototype must provide recipients with a neutral inline indication when access is revoked or when permissions change. | Supports recipient awareness while minimising interpersonal friction by communicating access changes in neutral, face-saving language. Literature on privacy boundary negotiation and revocation emphasises that such notices should manage expectations without creating unnecessary blame, mistrust, or ambiguity. [10, 12, 25, 26, 46, 50, 52, 65] | RG3 |
| FR11 | The prototype must allow the recipient to request extended access, with the sender deciding whether to approve or reject that request. | Supports consent as an ongoing social process by allowing recipients to request continued access and senders to renegotiate permissions. Literature emphasises that privacy boundaries are not fixed at the point of sharing, but may be revisited, clarified, and renegotiated through interaction. [11, 24, 29, 31, 46, 51] | RG3 |
| **5. Co-subject and multi-party privacy control** | | | |
| FR12 | The prototype must support multi-party photos by allowing the sender to mark that a photo contains other people and allowing depicted co-subjects to request revocation of a shared photo, including an optional explanation for the request. | Supports multi-party privacy by recognising that shared photos may affect depicted co-subjects as well as senders. Literature emphasises that disclosure decisions in photo sharing involve shared privacy stakes, and that co-subjects should have some agency to contest or renegotiate disclosure. [5, 10, 33, 41, 46, 66, 67] | RG3 RG4 |

| ID | Requirement | Justification | Research Gap |
|---|---|---|---|
| FR13 | The prototype should allow a depicted co-subject to receive a notification that they appear in a shared photo when the sender has marked the image as multi-party content. | Supports co-subject awareness by making it visible when a privacy-relevant disclosure involves them. Literature emphasises that depicted others often lack opportunities to shape disclosure, and that awareness is a necessary precondition for agency. [5, 10, 33, 66] | RG3 |
| FR14 | The prototype should allow the sender to review and respond to a co-subject's request through a dedicated decision interface. | Supports multi-party privacy as a negotiated process by allowing the sender to explicitly review and respond to co-subject requests. Literature emphasises collaborative privacy mechanisms and treats consent as relational, revisable, and shaped through stakeholder negotiation. [10, 24, 46, 66, 67] | RG3 |
| FR15 | The prototype should provide neutral feedback when a co-subject request leads to changed permissions. | Supports clear communication of co-subject-related permission changes while minimising blame and interpersonal friction. Literature emphasises that revocation notices are socially meaningful and should be designed to support expectation management and face-saving. [25, 46, 50, 65] | RG3 |
| FR16 | The prototype should show that co-subject-related permission changes can affect forwarding and secondary-recipient access within the platform model. | Supports multi-party privacy beyond the original chat by showing that co-subject-related permission changes continue to affect redistribution and secondary-recipient access. Literature emphasises that forwarding changes audience and context, and that downstream dissemination can intensify multi-party privacy risk. [10, 33, 41, 68] | RG3 |

| ID | Requirement | Justification | Research Gap |
|---|---|---|---|
| FR17 | The prototype should allow the interface to explain the limits of co-subject protection, including that offline capture, screenshots, or prior viewing cannot be fully undone. | Supports realistic co-subject protection by clearly communicating the limits of platform-level control. Literature emphasises that revocation is partial and prospective, and that screenshots, offline capture, and prior viewing cannot be fully reversed.[21, 25, 47, 50] | RG2<br>RG3 |

**Table 3.1:** Functional Requirements

## 3.5 Non-Functional Requirements (NFR)

| ID | Requirement | Justification | Research Gap |
|---|---|---|---|
| **1. Usability and clarity** | | | |
| NFR1 | The prototype interface must be easy to understand for first-time users. | Helps users understand the permission model and core controls without prior training or repeated use. Literature on usable privacy and consent interfaces emphasises that controls should be legible, consistently presented, and not hidden or ambiguous. [2, 5, 24, 42, 49, 50, 65] | RG1<br>RG2 |

| ID | Requirement | Justification | Research Gap |
|---|---|---|---|
| NFR2 | The prototype should support quick routine sharing while adding only proportionate friction for privacy-sensitive actions. | Ensures that routine sharing stays quick while privacy-sensitive actions receive enough attention. Literature on usable consent and privacy interaction design emphasises that consent flows should remain low-friction in ordinary use, while more sensitive actions may justify prompts or warnings that encourage reflection without causing fatigue or avoidance. [3, 10, 24, 31, 32, 49, 65] | RG1 |
| NFR3 | Consent and privacy controls must present choices in a balanced, and non-manipulative way. | Ensures that users can understand and compare options and make freely made choices. Literature on meaningful consent and dark patterns emphasises that privacy choices should not rely on hidden options, unequal emphasis, unclear notices, or obstructed decline paths. [4, 18, 42, 49, 53, 65] | RG1<br>RG3 |
| NFR4 | The interface must provide readable and distinguishable permission states, labels, and controls. | Ensures that users can read, compare, and interpret permission-related information confidently. Literature on usable privacy and consent interfaces emphasises that permission states and controls should be visually legible and clearly distinguishable so users can understand status changes, locate actions, and interpret consequences without ambiguity. [2, 24, 49, 50, 65] | RG1<br>RG2 |
| **2. Performance** | | | |

| ID | Requirement | Justification | Research Gap |
|---|---|---|---|
| NFR5 | Permission-related actions and status changes should remain responsive enough for live demonstration in a local browser environment. | Ensures that permission changes appear quickly enough to support smooth interaction during use and evaluation of the prototype. Literature on usable consent and privacy interaction design emphasises that controls should remain responsive at the moment of action and not introduce disruptive delay. [2, 24, 31, 32, 49, 65] | RG1 |
| **3. Social impact** | | | |
| NFR6 | The interface must use neutral, non-blaming language to reduce unnecessary social tension when permissions change. | Ensures that permission changes are communicated in a socially careful and non-accusatory way. Literature on privacy boundary management and revocation emphasises that such changes are socially meaningful, so interface wording should minimise blame, ambiguity, and interpersonal friction while keeping changes intelligible. [11, 12, 26, 46, 49, 50, 52, 65] | RG3 |
| **4. Consistency** | | | |
| NFR7 | Permission menus, indicators, and states should remain consistent with familiar WhatsApp-like interaction patterns. | Ensures that new permission controls are easier to learn and less confusing by following interaction patterns users already recognise. Literature on usable privacy controls emphasises that consistency supports interpretability, and that settings should avoid inconsistent placement or presentation that makes actions harder to locate or understand. [2, 24, 49, 50, 59, 61, 62, 65] | RG1<br>RG4 |

| ID | Requirement | Justification | Research Gap |
|---|---|---|---|
| NFR8 | Permission management should assume continuity with WhatsApp's existing end-to-end encryption model, without requiring changes to the underlying encryption architecture. | Ensures that permission controls remain compatible with familiar secure messaging expectations. This assumption frames permission management as operating alongside, rather than replacing or weakening, WhatsApp's existing end-to-end encryption, and supports consistency by treating it as an additional layer of user control. | RG1<br>RG4 |
| **5. Transparency** | | | |
| NFR9 | The system must not over-promise. It should clearly indicate that revocation may not affect screenshots, saved copies, or prior viewing. | Ensures that users understand the practical limits of revocation clearly and honestly. Literature on revocation and media control emphasises that revocation is only partial and prospective, so interfaces should avoid implying complete erasure where screenshots, saved copies, exports, or prior viewing remain outside full platform control. [21, 25, 47, 49, 50, 58, 59, 61, 62, 64] | RG2 |

**Table 3.2:** Non-Functional Requirements

# Chapter 4

# Design & Specification

## 4.1 Brief

This chapter presents the design and specification of the proposed consent revocation system for photo sharing in WhatsApp. It translates the requirements, use cases, literature findings, and platform constraints established in earlier chapters into a justified interaction design and system specification. The chapter first introduces the Smart Photos concept and design rationale, before covering the specification in section4.4.

## 4.2 Design Rationale and Principles

The design of **Smart Photos** is grounded in the central argument of this dissertation: consent in messaging-based photo sharing should not be treated as a one-off permission granted at the moment of sending, but as an ongoing and revisable process shaped by context, relationships, and the practical limits of post-delivery control. In the proposed model, each shared photo is treated not simply as delivered content, but as a photo associated with a persistent permission state that can specify whether it may be forwarded, saved, viewed once, or accessed for a limited period. These permissions are not exhausted at disclosure, but remain reviewable and revisable through the interface after sending. The design principles set out below are informed by Communication Privacy Management, Contextual Integrity, revised consent models, and privacy-focused HCI research [11, 24, 41, 46, 49, 65]. They provide the conceptual basis for the structure of the model and the prioritisation of particular interaction choices.

### 4.2.1 Dynamic and Revocable Consent by Default

The first design principle is that consent should be treated as dynamic and revocable by default rather than as a fixed decision exhausted at the point of disclosure. This follows directly from the literature reviewed in Chapter 2, which shows that one-off consent models are poorly suited to interpersonal messaging, where disclosures unfold over time and may later feel inappropriate as contexts, relationships, or expectations change [24, 29, 31, 51]. In CPM terms, sharing a photo does not eliminate the need for later boundary management; rather, it creates a situation in which privacy rules may need to be revisited and renegotiated after disclosure [11, 46].

For that reason, the design does not treat photo sending as an irreversible transfer of control. Instead, it is structured around the idea that a photo can remain associated with a modifiable permission state, allowing the sender to determine conditions of access before sending and to revise those conditions afterwards. This principle underpins the decision to support both pre-send configuration and post-send permission management in the prototype, rather than limiting user control to a single moment of choice. It also supports the inclusion of time-bounded access, view-once behaviour, and later permission revision as core parts of the design rather than optional add-ons. That also means a photo keeps its original sharing conditions after it is sent, so later edits or allowed redistribution within the prototype do not change the original permissions. In this way, the prototype operationalises the dissertation's first research gap by translating the literature on dynamic and ongoing consent into a messaging-oriented interaction model that remains reviewable after disclosure.

### 4.2.2 Expectation Management over Absolute Control

The second principle is that the interface should communicate realistic and bounded forms of control rather than implying that revocation can fully undo disclosure. The literature reviewed in Chapter 2 shows consistently that revocation in messaging environments is prospective and partial: once content has been delivered, viewed, copied, downloaded, or captured through screenshots or external devices, no interface can guarantee complete retrieval or universal deletion [21, 25, 47, 50]. This limitation is especially important in WhatsApp-like systems, where platform-level controls can affect later in-app visibility but cannot fully govern what has already been retained on recipient-controlled devices [59, 61, 62, 64].

This principle therefore rejects any design framing that would overstate the application's power. Within the **Smart Photos** model, revocation is treated primarily as a mechanism for modifying

or withdrawing future platform-mediated access and redistribution, rather than as a guarantee of complete deletion after delivery. This makes expectation management a core design responsibility rather than a peripheral disclaimer. It justifies the inclusion of screenshot and capture warnings, state explanations, and wording that emphasises limited but meaningful control. In practical terms, the goal is to help users form a more accurate mental model of what permission changes can and cannot achieve.

### 4.2.3 (suna bi daha bak) Minimal Social Friction

A third design principle is that revocation and permission change should be communicated in a way that minimises unnecessary interpersonal tension. The literature reviewed earlier shows that revocation is not only a technical event but also a socially meaningful act. Under CPM, changing access after disclosure may be interpreted as a renegotiation of privacy boundaries, while work on social presence and media richness suggests that changes to communication permissions can carry relational signals such as mistrust, distancing, or suspicion [12, 26, 46, 52]. Empirical work on deletion cues further suggests that visible traces such as deletion notices may themselves become socially consequential, sometimes producing ambiguity or discomfort rather than simply clarifying what happened [50].

For that reason, the design aims to reduce friction without hiding the fact that a permission change has occurred. This means using neutral, system-mediated wording and avoiding interface patterns that imply blame. The aim is not to hide revocation, but to present it in a way that it limits the possibility of unnecessary tension. This principle is particularly important for recipient-facing notices and status changes, where the interface must remain clear about changing access while avoiding designs that frame revocation as punitive or suspicious.

### 4.2.4 Fairness Between Parties

Although the project prioritises sender-side control, the design rationale does not treat consent management as a purely sender-centred matter. Both CPM and Contextual Integrity suggest that once content has been shared, the expectations of other parties also matter, even where the sender retains a legitimate interest in revising access [41, 46]. A sender may view revocation as a reasonable attempt to reassert privacy boundaries, while a recipient may interpret the same action as a change to previously granted access. This tension does not mean the sender should lose the ability to revise permissions, but it does mean that recipient-facing states and notices

must be understandable. Although the immediate interaction in the prototype centres on the sender and both types of recipients, the same concern with fairness also extends to photos that involve depicted co-subjects whose interests may be affected by later access or redistribution.

The design therefore seeks to balance sender agency with recipient understanding. Recipients are not treated as passive endpoints who simply lose access without explanation. Instead, the system provides readable states, neutral notices, and clear indications of what remains available, what has changed, and what actions are no longer permitted. It also supports limited request-based interaction, allowing a recipient to ask for extended or renewed access while leaving the final decision with the sender. In this way, the design reflects the literature's view of consent as a socially negotiated process and responds to the need for revocation mechanisms that remain socially intelligible rather than merely technically enforceable.

### 4.2.5 (bu tamam) Consistency with WhatsApp's Existing Interaction Patterns

The final principle is that new revocation and permission features should remain consistent with the interaction patterns users already associate with WhatsApp-like messaging. HCI research reviewed in Chapter 2 shows that privacy controls often fail not only because they are absent, but because they are inconsistently presented, or difficult to interpret in fast-paced use [2, 49, 65]. In messaging contexts, where actions are often taken quickly and with limited deliberation, recognisable interaction patterns are especially important for first-use clarity and adoption.

For that reason, the design does not attempt to invent an entirely separate privacy-management environment detached from ordinary messaging behaviour. Instead, it follows familiar WhatsApp-like interaction conventions such as photo-level action menus, recognisable icons, in-chat state cues, and lightweight bottom-sheet style controls. This principle supports the non-functional requirements concerned with learnability, clarity, and consistency, and helps ensure that the proposed system feels like a plausible extension of an existing messaging platform rather than an unfamiliar parallel application. By embedding consent and revocation controls within established patterns of use, the design aims to support meaningful control without introducing so much novelty or friction that the feature becomes difficult to adopt in everyday communication.

## 4.3 Conceptual System Model: Smart Photos (bu cok mu repetition)

This section introduces the conceptual model that structures the prototype. The **Smart Photos** model treats each shared photo as an object associated with a persistent permission state, rather than as content whose control is fully transferred at the moment of delivery. Under this model, a photo is shared together with explicit permissions and constraints, such as whether it can be forwarded, saved, viewed once, or accessed for a limited period. These permissions are not fixed permanently at the point of sending. Instead, they remain attached to the photo as an ongoing state that can later be reviewed and revised through the interface.

This model is intended to support the dissertation's central view of consent as ongoing and revisable rather than exhausted at disclosure. It provides the conceptual basis for pre-send configuration, post-send permission management, recipient-facing state changes, constrained forwarding within the prototype, and cases where a shared photo may also involve co-subject interests. The model is intended to preserve the conditions under which a photo is originally shared, even if those conditions are later revised or the photo is redistributed within the platform. This means that permissions remain attached to the photo as it moves between users, rather than being reset each time it is shared.

A key position taken in this design is that consent revocation in WhatsApp photo sharing cannot be treated as a guarantee of complete deletion once a photo has been delivered to another user's device. Instead, the **Smart Photos** model conceptualises revocation primarily as a mechanism for modifying or withdrawing future platform-mediated access and redistribution. This framing follows directly from the constraints identified in Chapter 2, where messaging platforms such as WhatsApp were shown to operate within structural limits created by prior viewing, screenshots, local retention, and external capture. Treating revocation as equivalent to universal deletion would therefore risk producing misleading expectations and inaccurate mental models of control. The model instead aims to support meaningful but realistically bounded control by making permissions persistent, revisable, and visible, while remaining honest about the limits of what the system can enforce after disclosure.

## 4.4 Functional Specification

### 4.4.1 Pre-send Permission Configuration

To achieve **FR1** and **FR2**, the prototype places photo-permission controls directly within the sender's sharing flow rather than treating privacy as something that can only be addressed after a photo has already been sent. From the sender's chat interface, the user can open a photo picker, choose an image from preset media, device files, or camera input, and then either send it immediately with default settings or open a dedicated composer through 'Send with Revocable Permissions' for permission-based sharing. This keeps permission decisions close to the moment of disclosure while preserving a lightweight path for routine sharing.

When the sender chooses to send a photo with revocable permissions, the prototype opens a dedicated pre-send composer. Within this composer, the sender can define the photo's initial permission state before it enters the chat. The current implementation allows the sender to set whether forwarding is allowed, whether the photo should be limited to view-once access, whether downloading is allowed, whether the photo should be marked as containing a co-subject, and whether access should expire after a user-defined time interval. Time-limited access is configured through a duration selector for days, hours, minutes, and seconds, and the sender can also add a caption before sending. In this way, the act of sending does not function as a simple transfer of content, but as the creation of a photo message with an attached permission state from the outset.

The prototype also supports a lower-friction direct-send path from the same picker. In that case, the selected photo is sent immediately using default settings rather than through the full composer. This allows the design to distinguish between routine sharing and more privacy-sensitive sharing, while still making richer permission control available at the point of send when the sender chooses it.

To achieve **FR2**, the pre-send flow also includes an explicit risk cue that communicates the limits of later control before disclosure takes place. In the current prototype, the composer shows a short warning that screenshots and saved copies cannot be undone. This does not attempt to prevent screenshotting or local retention technically; instead, it frames such risks as structural limits of platform-level control and makes them visible before the photo is shared. As a result, the pre-send interaction supports more informed permission-setting by combining configurable restrictions with an explicit reminder that later revocation cannot fully reverse all

forms of recipient-side capture or retention.

### 4.4.2 Post-send Permission Management

To achieve **FR3**, the prototype keeps permission management reachable after a photo has already been delivered through contextual, photo-level controls within the chat. Each sent photo includes a small action button in the top-right corner of the message bubble. Selecting this control opens an in-chat menu from which the sender can access both general photo actions and a dedicated revocation-permissions view. Through these post-send controls, the sender can revoke or restore visibility, allow or block forwarding, allow or block downloading, and add or remove a time limit for an existing photo. In this way, post-send control is treated as an ongoing interaction tied to the individual photo message rather than as a one-off decision made only at the moment of sending.

To achieve **FR5**, these changes operate on a live consent state associated with each shared photo. In the current prototype, this state records whether access is active or revoked, whether forwarding is permitted, whether downloading is permitted, whether the photo is marked as view-once, whether a co-subject flag is present, and whether access expires at a specified time. Because these permissions remain attached to the same source photo after sending, the prototype can update the state of an existing message rather than replacing it with a new one. The adjacent permissions panel reinforces this model by showing the currently selected photo together with its current status, forwarding condition, view-once state, download condition, and time limit, allowing the sender to inspect the active state before making further changes.

To achieve **FR4**, the prototype also renders these permission states clearly within the chat interface for all relevant participants. Beneath each photo, the interface displays compact state labels indicating whether the photo is visible or revoked, whether forwarding is allowed, whether the content is view-once or reviewable later, whether downloading is allowed, and, where applicable, how long remains before expiry. When access is revoked, the recipient-facing interface replaces the visible photo with an inline placeholder indicating that the photo is no longer available in the current chat. When a photo is configured as view-once, recipients open it in a full-screen view that becomes unavailable after closing. These interface states make permission changes legible in the conversation rather than leaving them implicit or hidden.

To achieve **FR6**, key permission-related actions are accompanied by lightweight but persistent feedback within the same interface. After sending, the sender is shown a short summary of

the most recent send action, and forwarded activity is also summarised separately in the side panel. More generally, the outcome of permission changes is reflected immediately through updated state chips beneath the photo, the current-photo status shown in the permissions panel, and any visible change in recipient-facing presentation, such as revoked placeholders or expiry countdowns. Rather than relying on detached confirmation dialogs, the prototype makes the results of post-send actions understandable by updating the same chat and control surfaces through which the photo is already being managed.

### 4.4.3 Recipient Experience and Permission Changes

To achieve **FR10**, the prototype provides the recipient with neutral inline indications when access is no longer available or when the current permission state has changed. In the recipient view, each photo message is accompanied by visible state labels showing whether the photo is currently visible or revoked, whether forwarding is allowed, whether the content is view-once or reviewable later, whether downloading is allowed, and, where relevant, how long remains before expiry. If access is revoked, the visible photo is replaced by an inline placeholder stating that the photo is no longer visible in the current chat. The wording used in these states remains system-like and descriptive rather than accusatory, so that the recipient is informed of a change in access without the interface framing it as blame or misconduct.

In the current prototype, this neutral recipient-facing feedback is delivered primarily through updated in-chat state labels, revoked-state placeholders, and short explanatory text beneath the photo message, rather than through a separate system notice for every permission change. This keeps permission changes visible within the same conversational context in which the photo was shared, while supporting the dissertation's aim of making revocation legible without introducing unnecessarily confrontational deletion-style cues.

To achieve **FR11**, the prototype also allows the recipient to request renewed access when a previously shared photo is no longer available. In the current implementation, when the recipient opens the action menu for a revoked photo, a request-access option becomes available. Selecting this opens a small request flow in which the recipient can send an access request to the sender together with an optional explanatory message. The request does not automatically restore access; instead, it is routed to the sender side of the prototype as a pending request associated with the source photo.

The sender can then explicitly accept or reject that request. If the sender accepts, the prototype

restores the photo's access state for the corresponding source photo. If the sender rejects, the recipient is shown a short follow-up message indicating that the access request has been rejected. In this way, the prototype treats access renewal not as an automatic technical reversal, but as a negotiated interaction in which the recipient can ask for renewed access while the sender retains control over the final decision.

### 4.4.4 Forwarding and Redistribution Control

To achieve **FR7**, **FR8** and **FR9**, the prototype treats forwarding as a permission-dependent action rather than as an unrestricted continuation of ordinary message sharing. A photo can only be forwarded when the sender's current permission state allows redistribution and the photo remains active. In the chat interface, this is reflected through the photo-level action menu: when forwarding is blocked, the forwarding option is disabled; when it is permitted, the photo can be forwarded into the secondary-recipient chat. In this way, redistribution is constrained by the sender's current permission state rather than by recipient discretion alone.

To achieve **FR8**, forwarded content does not create a separate copy with an independent permission model. Instead, the forwarded message remains linked to the original photo through the same source-photo identifier and inherits the sender-defined permissions as represented in the interface. In the current prototype, this means that forwarded content continues to reflect the original photo's visibility status and other active restrictions, including forwarding availability, download permission, view-once behaviour, and any time-based expiry. If the sender later changes the permission state of the original photo, those changes are also reflected in the forwarded instance associated with that same source photo. The prototype therefore models forwarding as continued circulation under the original permission logic rather than as a break from the initial sharing conditions.

To achieve **FR9**, the prototype presents the forwarded flow as a distinct recipient context rather than leaving redistribution implicit. Forwarded content appears in a separate secondary-recipient chat, making the audience change visible during evaluation and helping distinguish the original recipient's conversation from the downstream one. Within that forwarded view, the interface also indicates that restrictions from the original chat still apply, reinforcing that redistribution remains governed by the sender-defined permission state. By separating the forwarded conversation while preserving inherited restrictions, the prototype makes downstream sharing legible as an extension of the original disclosure rather than as an unrelated or uncontrolled

disclosure event.

### 4.4.5 (why did i wrote 'this will be erased.')Co-Subject and Multi-Party Privacy Control

To achieve **FR12** and **FR13**, the prototype extends the permission model beyond the sender/recipient pair by allowing the sender to mark, at send time, that a photo contains a co-subject. In the current implementation, this is done through the pre-send composer, where the sender can enable a co-subject flag as part of the photo's initial permission state. Photos marked in this way then become visible within a dedicated co-subject view, where the depicted person is shown a clear indication that they appear in the photo. Rather than treating the image as sender-only content, the prototype therefore represents certain photos as multi-party disclosures whose privacy implications extend beyond the original sender and recipient.

To achieve **FR13** more specifically, the co-subject is not only shown the marked photo but is also given an explicit interface cue stating that they are depicted in it. In the current prototype, this appears as a dedicated co-subject card with a short notification message indicating that the person appears in the shared photo and may request revocation. This makes co-subject involvement visible in the interface and provides a basis for later action rather than leaving multi-party implications implicit or hidden.

To achieve **FR12** and **FR14**, the prototype also provides a co-subject request flow through which the depicted person can ask the sender to revoke the photo. This request is initiated from the co-subject's photo-level action menu and opens a small modal in which the co-subject can send a revocation request together with an optional explanatory message. The request is then routed to the sender side of the prototype as a pending item associated with the relevant source photo. Rather than applying revocation automatically, the sender is presented with an explicit accept-or-reject decision interface in the sender-only message area. This keeps co-subject privacy management within a negotiated interaction model rather than reducing it to hidden system behaviour.

To achieve **FR15**, the outcome of a co-subject request is communicated through clear but non-blaming feedback. On the sender side, accepted and rejected requests are shown with short outcome labels indicating whether the photo has been revoked or the co-subject has been notified of rejection. If the sender rejects the request, the co-subject receives a follow-up message

stating that the revocation request has been rejected. If the sender accepts, the photo's access state is updated without framing the change in accusatory terms. In this way, the prototype makes the outcome of co-subject intervention visible while still aiming to minimise unnecessary interpersonal friction.

To achieve **FR16**, co-subject-related permission changes continue to apply beyond the original chat. In the current prototype, accepting a co-subject revocation request changes the permission state of the original source photo itself. Because forwarded content remains linked to that same source photo and inherits its effective permission state, a co-subject-triggered revocation also affects the forwarded instance shown to the secondary recipient. The interface therefore models co-subject privacy as extending into downstream redistribution contexts rather than stopping at the original sender/recipient exchange.

To achieve **FR17**, the prototype also makes the limits of co-subject protection explicit. In the co-subject view, the interface states that protection is in-app only and that screenshots and prior viewing cannot be fully undone. The revocation-request flow similarly reminds the co-subject that offline copies may already exist. These cues ensure that co-subject controls are presented as meaningful but bounded forms of platform-level control, rather than as guarantees of complete erasure after disclosure.

## 4.5 Non-Functional Specification

### 4.5.1 Usability and Interaction Clarity

To achieve **NFR1**, the prototype presents permission-related controls within familiar chat and media-sharing interaction points rather than requiring users to learn a separate privacy-management environment before use. Core actions are embedded directly into the sender's chat interface through the photo picker, the pre-send composer, the in-chat photo menu, and the adjacent permissions panel. This is intended to make the permission model understandable from first use by keeping controls close to the photo they affect rather than hiding them in detached settings screens or abstract settings menus.

To achieve **NFR2**, the interface supports quick completion of routine sharing tasks while introducing additional interaction only where privacy-sensitive reflection is useful. In the current prototype, a selected photo can either be sent directly with default settings or opened in a dedicated composer for permission-based sharing. This preserves a lightweight path for ordinary

sharing, while still allowing the sender to configure forwarding, view-once behaviour, download permission, co-subject marking, and time-limited access before disclosure when more deliberate control is needed. In this way, the prototype aims to introduce proportionate friction rather than treating all sharing actions as equally sensitive.

To achieve **NFR3**, consent and privacy choices are presented as explicit, interpretable options rather than as hidden or one-sided defaults. In the pre-send composer, permission controls are shown as individually labelled buttons within the same visible panel, and the sender can either enable or leave each option disabled without navigating through obscured submenus or being forced toward a single preferred configuration. Similarly, post-send actions such as revoking access, blocking forwarding, blocking download, or adding a time limit are presented as explicit menu choices within the photo-level action flow. This keeps the interface relatively transparent about what options are available and avoids structuring privacy control as a hidden or manipulative interaction.

To achieve **NFR4**, permission states, labels, and controls are designed to remain visually distinguishable across the interface. The prototype uses clearly separated action menus, labelled permission buttons, compact state indicators beneath photo messages, and distinct placeholders for revoked content so that users can recognise the current state of a photo without having to infer it indirectly. This applies both to sender-side management and to recipient- and co-subject-facing views, where visible changes in access, forwarding, download permission, view-once status, and expiry need to remain legible after disclosure.

To achieve **NFR5**, permission-related actions remain responsive within the local browser-based prototype so that changes in state appear immediately during interaction and demonstration. In the current implementation, permission updates are applied directly to the active photo state and are reflected at once in the chat view, the permissions panel, forwarded content, and recipient-facing or co-subject-facing states where relevant. This helps preserve a credible and continuous messaging flow, particularly when the sender revises permissions after sending and the resulting changes need to remain immediately visible to other participants. Together, these choices specify usability and interaction clarity as core qualities of the prototype rather than as secondary presentation concerns.

### 4.5.2 Socially Careful Communication

To achieve **NFR6**, the prototype communicates permission changes through neutral, system-mediated wording that avoids unnecessary blame or accusation. This is especially important because revocation, restriction, and access renewal are not only technical actions but also socially meaningful changes in interpersonal access. In the current interface, permission changes are therefore phrased in descriptive terms such as a photo no longer being visible, access having changed in the current chat, or a request having been accepted or rejected, rather than in language that implies wrongdoing on the part of the recipient or frames the sender's action as punitive.

This principle is reflected in both photo-state presentation and request outcomes. When access is revoked, the recipient sees an in-chat placeholder stating that the photo is no longer visible, supported by short explanatory text and updated state labels. Similarly, request-based interactions are communicated through restrained feedback such as indicating that access has been restored, that a revocation request has been accepted, or that a request has been rejected and the affected party has been notified. These messages make the outcome of permission-related actions clear without relying on confrontational or suspicion-laden deletion-style cues.

In this way, socially careful communication is specified as a core non-functional quality of the prototype: permission changes must remain visible and understandable, but they should do so in language and interface forms that minimise avoidable interpersonal friction.

### 4.5.3 Consistency, and Honest Communication of Limits

To achieve **NFR7**, the prototype keeps permission menus, indicators, and message states consistent with familiar WhatsApp-like interaction patterns. Permission controls are embedded within recognisable chat elements, including the photo picker, the pre-send composer, the in-chat photo action menu, the sender-side permissions panel, and the state labels shown beneath shared images. This is intended to make the permission model feel like an extension of ordinary messaging behaviour rather than a separate or unfamiliar privacy-management environment. Consistency is therefore treated not only as a visual quality, but also as a way of reducing confusion when users encounter revocation, forwarding, view-once, time-limit, or co-subject controls for the first time.

To achieve **NFR8**, the prototype is specified as operating alongside familiar WhatsApp-style

secure messaging assumptions rather than replacing them. The design does not propose any change to the underlying end-to-end encryption model and does not attempt to solve revocation through cryptographic redesign. Instead, permission management is framed as an additional interface and state-management layer that governs how photos remain visible, reviewable, forwardable, or restricted within the platform context. This preserves conceptual continuity with users' expectations of secure WhatsApp-like communication while keeping the dissertation focused on interaction and consent management rather than on changes to the underlying encryption architecture.

To achieve **NFR9**, the prototype communicates the limits of revocation explicitly and avoids implying complete erasure after disclosure. In the current interface, this is expressed through pre-send warning text in the composer, explanatory notes beneath shared photos, revoked-state placeholders, and co-subject request flows that state that screenshots, saved copies, offline retention, and prior viewing cannot be fully undone. The permissions panel also reinforces this boundary by stating that the design is intentionally scoped as platform-level visibility control rather than a guarantee of universal deletion. In this way, the prototype remains honest about the partial and prospective nature of revocation and aims to calibrate user expectations about what its controls can and cannot enforce after a photo has been shared.

# Chapter 5

# Implementation

## 5.1 Brief

## 5.2 Technology Choices and Prototype Scope

### Next.js and React

React 19 was chosen for its component-based architecture, which supports modular development, reuse across the interface, and manageable UI state [36]. This suited the prototype particularly well, as the sender, recipient, forwarded recipient, and co-subject perspectives could be implemented as distinct interface regions while still sharing a common permission state. React's built-in state hooks allowed permission changes, such as revocation, forwarding restrictions, and time-limit expiry, to propagate immediately across the relevant views, supporting the responsiveness specified by **NFR5**. Because the prototype operates as a single-browser simulation rather than a networked multi-user system, this behaviour could be implemented without introducing an external state-management library.

Next.js 16 was used as the application framework, providing project scaffolding, routing, TypeScript integration, CSS processing, and an optimised production build pipeline [55]. Although the prototype is essentially a single-page application, Next.js streamlined development and supported rapid iteration across the two implementation rounds described in Section 5.3.

### TypeScript

TypeScript was used to define and enforce the core data structures of the prototype at compile time [37]. This was particularly important because the Smart Photos prototype relies on a structured permission model spanning message content, stakeholder roles, and photo-specific control. Several key types were used throughout the implementation:

- `PhotoPermissions` — encodes revocation status, forwarding, view-once, download, time-limit, and co-subject flags;
- `ChatMessage` — a discriminated union distinguishing text messages from photo messages, each carrying different metadata;
- `Participant` — a literal union (`"sender"`, `"recipient"`, `"forwardedRecipient"`, `"coOwner"`) that restricts handler functions to valid stakeholder roles.

Using explicit types helped keep these structures consistent across components and reduced the likelihood of development errors as the prototype evolved. This was especially valuable because the permission model is the central contribution of the prototype and any inconsistency in how permissions, messages, or stakeholder roles were represented would have weakened the credibility of the resulting user evaluation. Although TypeScript does not replace runtime permission logic, it improved maintainability and made the implementation safer to extend during iterative refinement.

### Tailwind CSS

Tailwind CSS 4 was chosen as the styling framework because its utility-first approach enabled rapid and consistent interface development without relying on large separate stylesheet files [54]. This suited the prototype well, as the interface needed to visually approximate familiar WhatsApp patterns such as chat bubbles, action menus, bottom sheets, and phone-frame layouts in order to support the familiarity and consistency specified by **NFR7**. Tailwind's utility classes made it straightforward to replicate these patterns while keeping styling close to the relevant component markup.

The framework was also useful during iterative refinement. Because visual adjustments could be made directly within the JSX, interface details could be revised quickly between implementation rounds without introducing substantial styling overhead. This was particularly valuable in a

prototype that underwent multiple rounds of refinement following participant feedback.

### Front-End Simulation and Prototype Scope

The prototype operates entirely as a front-end simulation with in-memory state. Conversation data, permission records, and photo metadata are managed through React state in the browser, with no server, database, or external API. This design was chosen to support the project's aim of evaluating the interaction design and user experience of consent revocation, rather than the engineering feasibility of a production messaging system. It also allowed multiple perspectives to be demonstrated in a single browser window and made permission changes immediately observable during evaluation.

As such, the prototype is an interactive proof-of-concept for the Smart Photos permission model. It demonstrates revocable consent, permission configuration, forwarding control, view-once behaviour, time-limited access, and co-subject involvement, but does not include production infrastructure such as encryption, authentication, persistent storage, real-time delivery, multi-device synchronisation, automated co-subject detection, or server-side access control.

### Technology Summary

| Technology | Version | Role in Prototype |
|---|---|---|
| React | 19.2 | Component-based UI library; manages the multi-view layout and reactive permission state via hooks. |
| Next.js | 16.1 | Application framework; provides the App Router, development server, and optimised production builds. |
| TypeScript | 5.x | Static type system; enforces the permission data model at compile time. |
| Tailwind CSS | 4.x | Utility-first CSS framework; enables rapid, consistent styling that approximates WhatsApp's visual patterns. |
| Vitest + RTL | 3.x | Test framework and React Testing Library; unit and component tests with code-coverage reporting. |

Table 5.1: Technology stack and component roles

## 5.3 Development Process




Figure 5.1: Development Process Diagram

### Phase 1: Initial Prototype

The first implementation round focused on realising the core interaction flows defined in the functional specification: pre-send permission configuration (FR1–FR2), post-send permission management including revocation and restoration (FR3, FR5, FR6), recipient-side state presentation (FR4, FR10), constrained forwarding to a secondary recipient (FR7–FR9), access-request and response flows (FR11), and co-subject notification and revocation-request mechanisms (FR12–FR17). Each flow was built as a self-contained interaction path within a single-page React application, with all four stakeholder views—sender, recipient, forwarded recipient, and co-subject—rendered side by side so that the consequences of any permission change could be observed across participants in real time.

At this stage the entire prototype resided in a single `page.tsx` file. This monolithic structure was a pragmatic choice for rapid prototyping: it avoided premature abstraction and kept all state and handlers visible in one place while the interaction model was still being tested and revised. That build was then used for the screenshot-driven interviews reported in Chapter 6.

### Evaluation and Rationale for a Second Round

A second implementation round was justified on methodological rather than evaluative grounds. As Gould and Lewis argue, usability-oriented design is inherently iterative, requiring a system to be modified and tested repeatedly as it develops from simulation to prototype and beyond [17]. The design in Chapter 4 was derived from literature and requirements engineering; once a runnable prototype existed, it became possible to observe how people interpreted unfamiliar permission states, warnings, and labels under realistic task conditions.

For this project, the interviews therefore functioned as a checkpoint between "specification-faithful" code and a version suitable for continued demonstration and assessment. This reflects the role of usability testing in helping designers uncover problems, discover opportunities for improvement, and learn how users actually engage with an interface [38]. A second round was therefore scoped deliberately to layout, styling, copy, and component structure, leaving the core types and permission logic aligned with Chapter 4 unless a change was strictly required for consistency. Chapter 6 documents what was learned from participants and how it was analysed.

## Phase 2: Post-Evaluation Refinements

Phase 2 implemented the interface adjustments motivated by that feedback and, in parallel, restructured the codebase from a single file into a multi-component architecture so that further changes and testing could proceed without entangling unrelated parts of the UI.

### Architectural Restructuring

During the second implementation round, the prototype was refactored from a single large `page.tsx` file into a modular structure. The top-level page retained responsibility for coordinating the overall multi-view simulation, while dedicated components under `components/photo-revocation-demo` handled specific interface elements such as composition, message rendering, previews, request panels, and modal interactions. Shared definitions and reusable logic were moved under `src/lib`, including the demo-specific modules in `photo-revocation-demo` (`types.ts`, `helpers.ts`, and `initialState.ts`) and the shared `photoModel.ts` file.

This restructuring improved maintainability and made later refinements more manageable. Interface changes could be applied to individual components without repeatedly modifying one monolithic file, while the underlying permission model remained separated from presentation concerns.

bu yanlisin duzeltimis hali (architectureda yanlislar var sanirim): During the second implementation round, the prototype was refactored from a single large page.tsx file into a modular structure. Following this refactoring, page.tsx became a thin wrapper responsible only for rendering the prototype entry component, while PhotoRevocationDemo.tsx took over responsibility for coordinating the overall multi-view simulation. Dedicated components under components/photo-revocation-demo then handled specific interface elements such as composition, message rendering, previews, request panels, and modal interactions. Shared definitions and reusable logic were moved under src/lib, including the demo-specific modules in photo-revocation-demo (types.ts, helpers.ts, and initialState.ts) and the shared photoModel.ts file.

### Interface Refinements

Phase 2 focused on improving clarity, presentation efficiency, and prototype fidelity without changing the underlying permission model. Permission information beneath photo messages was condensed into a compact summary with on-demand detail expansion, reducing visual clutter in the chat transcript. The pre-send limitation disclaimer was made more prominent,

and the revoked-state placeholder was simplified to reduce repeated explanation. In addition, the prototype was extended to support multi-photo messages with a shared permission set, together with collage and gallery views, bringing the interaction closer to familiar photo-sharing behaviour in mainstream messaging clients. Modal overlays were also scoped to individual handset frames so that each simulated participant view remained visually distinct. Further minor copy and layout adjustments were applied in the same spirit; they are not enumerated here. All these refinements are reflected in the final prototype described in the following sections.

## 5.4 Components and State Management

### Component Hierarchy

The final prototype comprises a thin entry page (`page.tsx`), a central orchestrator component (`PhotoRevocationDemo`), and seventeen leaf components organised into four functional groups. Figure 5.2 shows this hierarchy.





Figure 5.2: Component hierarchy of the prototype, showing the four functional groups.

`PhotoRevocationDemo` owns all shared application state and passes data and handler functions down to its children as props. Each simulated handset is wrapped in a `PhoneFrame`, which renders the device chrome and provides a `ChatPanelOverlayContext` so that modal overlays such as request panels and view-once confirmations can portal into the correct handset frame rather than covering the entire page. Beneath this shell, the components divide into four groups:

- **Conversation rendering.** `MessageList` iterates over a message array and dispatches each entry to `TextMessageBubble` or `PhotoMessageBubble`. Photo messages delegate further to `PhotoPreview` for single images, `PhotoStackGrid` for multi-photo collages, and `PhotoStackLightbox` for full-screen gallery viewing.

- **Composition and configuration.** `ComposerView` manages the pre-send interface, including caption input and permission toggles. `PickerSheet` handles photo selection, while `TimeLimitModal` and its child `ScrollWheelColumn` provide the time-limit picker.

- **Request and modal flows.** `RequestAccessPanel` and `RequestRevocationPanel` handle the access-request and co-subject revocation-request interfaces respectively. Furthermore, `ViewOnceInChatModal` manages the view-once confirmation overlay, with `ViewOnceSingleTick` rendering the single-view indicator on consumed messages.

- **Debug and demonstration.** `PrototypeStateSummary` surfaces the live permission state of the currently selected photo in a panel alongside the handset views, allowing evaluators to verify that permission changes propagate correctly across participants.

Each group corresponds to a distinct area of the interaction model defined in Chapter 4, so that changes to one concern—such as the composition interface—do not entangle another, such as request handling or message rendering.

## Shared Permission State

All application state that affects what participants see resides in `PhotoRevocationDemo` as React `useState` hooks. The most important of these are five message arrays (`mainMessages`, `forwardedMessages`, `senderOnlyMessages`, `recipientOnlyMessages`, `coSubjectOnlyMessages`) which together hold every message visible across the four simulated handsets.

The canonical permission record for a photo lives on its entry in `mainMessages`. Section 5.2 introduced the `PhotoPermissions` type in prose; Listing 5.1 shows the definition as it appears in the source:

Listing 5.1: The `PhotoPermissions` type (`types.ts`). Each field maps to a permission control in the sender's configuration panel.

```
export type PhotoPermissions = {
  status: PermissionStatus;
```

```
  canForward: boolean;
  viewOnce: boolean;
  expiresAt: number | null;
  canDownload: boolean;
  hasCoSubject: boolean;
};
```

Every photo message carries a `sourcePhotoId` that links it back to the canonical entry in `mainMessages`. This linking is encoded in the `ChatMessage` type, which uses a TypeScript discriminated union to distinguish text messages from photo messages:

Listing 5.2: Photo branch of the `ChatMessage` discriminated union (`types.ts`). The `sourcePhotoId` field links every copy (including forwarded ones) to the canonical permission record.

```
export type ChatMessage =
  | { id: number; sender: Participant; type: "text";
      text: string; time: string;
      /* ...request metadata fields... */ }
  | { id: number; sender: Participant; type: "photo";
      assets: PhotoAsset[];
      caption: string; time: string;
      permissions: PhotoPermissions;
      sourcePhotoId: number; };
```

When the sender revokes, restores, or otherwise modifies permissions, only the canonical entry in `mainMessages` is updated. Forwarded copies in `forwardedMessages` are never rewritten directly. Instead, every rendering component resolves the live permission state at render time by calling `getEffectivePermissions`, shown in Listing 5.3. This function looks up the canonical photo in `mainMessages` by matching `sourcePhotoId`, reads the stored permission fields, and applies time-limit expiry logic through `computeEffectiveStatus` before returning the result.

Listing 5.3: `getEffectivePermissions` (`helpers.ts`). Resolves the live permission state for any photo message by looking up the canonical record in `mainMessages` and applying expiry logic.

```
export function getEffectivePermissions(
```

```
  mainMessages: ChatMessage[],
  message: PhotoMessage,
): PhotoPermissions {
  const raw = mainMessages.find(
    (entry): entry is PhotoMessage =>
      entry.type === "photo"
      && entry.sourcePhotoId === message.sourcePhotoId,
  )?.permissions ?? message.permissions;

  const expiresAt = raw.expiresAt ?? null;
  const now = Date.now();
  return {
    ...raw,
    expiresAt,
    status: computeEffectiveStatus(raw.status, expiresAt, now),
  };
}
```

This derivation pattern means that a single state update to the canonical photo in `mainMessages` is sufficient for every participant view—sender, recipient, forwarded recipient, and co-subject—to reflect the change on the next render cycle. The prototype does not need to synchronise permission records across message arrays or maintain separate update logic for forwarded copies, because every component derives its view of permissions from the same canonical source.

## Local Interaction State

Alongside the shared permission state described above, `PhotoRevocationDemo` maintains a second category of state: transient values that control temporary interface behaviour rather than the canonical permission model. These include boolean flags that govern which overlay is currently visible (`pickerOpen`, `composerOpen`, `timeLimitModalOpen`), a structured value tracking which photo menu is active and in which mode (`openPhotoMenu`), and draft text fields that hold in-progress user input before it is committed (`draftCaption`, `accessRequestDraft`, `senderInput`, `recipientInput`). None of these values affect how permissions are stored or derived; they exist only to support the interactive surface of each handset view.

One notable piece of local state is the countdown tick. The prototype supports time-limited

photo access, and the remaining time must update visually every second. Rather than introducing a timer event system, the orchestrator increments a counter once per second via a `useEffect` hook:

Listing 5.4: Countdown tick effect in `PhotoRevocationDemo.tsx`. The tick value itself is never read; its sole purpose is to force React re-renders.

```
const [, setCountdownTick] = useState(0);


useEffect(() => {
  const id = setInterval(() => setCountdownTick((t) => t + 1), 1000);
  return () => clearInterval(id);
}, []);
```

The tick value is never read directly—the destructured state variable is deliberately discarded. Its only purpose is to trigger a React re-render every second so that `getEffectivePermissions` (Listing 5.3) and `formatExpiryCountdown` re-evaluate with a fresh `Date.now()`. This allows time-limited photos to expire visually in real time and countdown labels to update continuously, without requiring explicit expiry event handling or additional state-management infrastructure.

Separating these transient interaction values from the canonical permission state kept the implementation manageable: the permission model remained a clean, single-source-of-truth structure as described in the previous subsection, while the local state layer provided the flexibility needed to support rich interactions such as modal sequencing, draft composition, and live countdown display.

### State Transitions: Revocation and Forwarding

The two most consequential state transitions in the prototype are post-send revocation and constrained forwarding. Both operate on the canonical–copy architecture described in Section 5.4, but they update state in different directions: revocation modifies the canonical record so that all views change, while forwarding reads the canonical record to decide whether a new copy may be created.

### Post-Send Revocation

When the sender revokes access, the handler `updateSelectedPhotoPermissions` is called with a partial update—for example, { `status: "revoked"` }. This function maps over `mainMessages`, locates every entry whose `sourcePhotoId` matches the currently selected photo, and merges the update into its `permissions` object:

Listing 5.5: `updateSelectedPhotoPermissions` in `PhotoRevocationDemo.tsx`. The immutable map-and-merge pattern updates the canonical record without mutating existing state.

```
const updateSelectedPhotoPermissions =
  (updates: Partial<PhotoPermissions>) => {
    if (selectedPhotoId === null) return;
    setMainMessages((currentMessages) =>
      currentMessages.map((message) => {
        if (message.type !== "photo"
            || message.sourcePhotoId !== selectedPhotoId)
          return message;
        return {
          ...message,
          permissions: { ...message.permissions, ...updates },
        };
      }),
    );
  };
```

Because `forwardedMessages` is never rewritten, the revocation takes effect across all participant views through the derivation layer already shown in Listing 5.3: on the next render cycle, every `PhotoMessageBubble` calls `getEffectivePermissions`, which looks up the now-revoked canonical record and returns `"revoked"` as the effective status. The same handler is reused for restoring access, toggling the download flag, or enabling the co-subject flag—each is simply a different partial update passed to the same function.

### Constrained Forwarding

Forwarding introduces a new message into `forwardedMessages`, but only after checking the canonical permission state. Listing 5.6 shows the handler:

Listing 5.6: `forwardPhotoMessage` in `PhotoRevocationDemo.tsx`. The function guards on effective permissions before creating a linked copy.

```
const forwardPhotoMessage = (message: PhotoMessage) => {
  const effectivePermissions =
    getEffectivePermissions(mainMessages, message);

  if (effectivePermissions.status !== "active"
      || !effectivePermissions.canForward) {
    return;
  }

  const forwardedMessage: PhotoMessage = {
    id: getNextMessageId(mainMessages, forwardedMessages,
      senderOnlyMessages, coSubjectOnlyMessages,
      recipientOnlyMessages),
    sender: "recipient",
    type: "photo",
    assets: [...message.assets],
    caption: `Forwarded: ${message.caption}`,
    time: getTimeLabel(),
    permissions: effectivePermissions,
    sourcePhotoId: message.sourcePhotoId,
  };

  setForwardedMessages((prev) => [...prev, forwardedMessage]);
};
```

Two details are significant. First, the guard clause calls `getEffectivePermissions` to evaluate the canonical record at the moment of forwarding; if the photo has been revoked or its `canForward` flag is `false`, the function returns early and no copy is created. Second, the forwarded message carries the same `sourcePhotoId` as the original. This means that if the sender later revokes access, the derivation layer will resolve the forwarded copy against the updated canonical record, and the forwarded recipient's view will reflect the revocation without any additional update to `forwardedMessages`.

#### Time-Limit Expiry

Time-limited access follows the same derivation principle without requiring a dedicated state transition. When the sender configures a time limit before sending, the photo message is created with an `expiresAt` timestamp. No handler fires when the deadline passes; instead, `computeEffectiveStatus` (called within `getEffectivePermissions`) compares `expiresAt` against `Date.now()` on every render and returns `"revoked"` once the timestamp has elapsed:

Listing 5.7: `computeEffectiveStatus` in `photoModel.ts`. Expiry is treated as implicit revocation—no event or state write is needed.

```
export function computeEffectiveStatus(
  storedStatus: PermissionStatus,
  expiresAt: number | null,
  nowMs: number,
): PermissionStatus {
  if (storedStatus === "revoked") return "revoked";
  if (expiresAt != null && nowMs >= expiresAt) return "revoked";
  return "active";
}
```


Combined with the countdown tick described in the previous subsection, this ensures that a time-limited photo transitions smoothly from an active countdown display to a revoked placeholder at the moment of expiry, using the same rendering path as an explicit revocation. This uniformity—where manual revocation, forwarding constraints, and time-limit expiry all resolve through a single derivation function—operationalises the dissertation's treatment of consent as ongoing and revisable: a single state change at the source, whether made by the sender or by the passage of time, is sufficient to update every downstream presentation of the photo.

(should i also talk about the co-subject feature here?)

## 5.5 Translation to a Functional Prototype

This section shows how the mechanisms described in Section 5.4 appear in the finished prototype.

### Pre-Send Permission Configuration




(a) Photo picker with two images selected.

(b) Pre-send composer with configured permissions.

Figure 5.3: Pre-send permission configuration flow.

The sharing flow begins in the sender's chat view. Tapping the attachment icon opens a bottom-sheet photo picker (Figure 5.3a), which presents a grid of preset samples and any user-uploaded files. Multi-photo selection is reflected by numbered badges on each tile and a summary strip with thumbnails and a count—in the figure, two photos are selected. The sender may press **Send** to deliver immediately with permissive defaults, or **Send with revocable permissions** to open the pre-send composer. In code, this split is implemented in `PhotoRevocationDemo.tsx`: the overlay is the `PickerSheet` component, and the two buttons call `sendPhotoDirectly` (fixed default `PhotoPermissions`) versus `openComposerWithPhotos`,

which copies the selection into draft state and swaps the sender handset's body from the message list to the composer.


The pre-send composer (Figure 5.3b) is rendered by `ComposerView`. It shows the staged photos, five toggle chips for forwarding, view-once, download, co-subject, and time limit, and a caption field—in the figure, forwarding is on, a 30-second limit is set on the scroll-wheel picker, and the caption reads "Shared with revocable permissions." Those controls edit in-memory draft values (`draftPermissions`, `draftCaption`, `draftTimeLimit`) until the sender confirms; `sendConfiguredPhoto` then merges an optional expiry timestamp from the chosen duration and passes the result to `addPhotoMessage`, which appends the new photo to `mainMessages` and sets `sourcePhotoId` equal to the new message id, as described in Section 5.4.

At the top of the composer, a persistent warning reads: *"Screenshots and saved copies cannot be undone. Revocation only limits future access in this chat. Another device can still photograph the screen."* The sender always sees this copy before sending; it is fixed in the composer layout rather than shown as a dismissible notice. After a successful send, the composer closes, the picker selection is cleared, and the new message appears in the chat with permission summary chips beneath the bubble.


This two-step flow—picker then composer—separates routine photo sharing from permission-aware sharing, satisfying the pre-send configuration requirements (**FR1**) and the risk-cue disclosure (**FR2**) while keeping the lightweight direct-send path available for everyday use. The always-visible warning also addresses the learnability concern in **NFR3** and the expectation-management goal in **NFR9**, as the sender is never able to configure permissions without first seeing the system's limitations.

### Post-Send Permission Management

Once a photo has been delivered, the sender retains access to its permission state through contextual controls anchored to the message bubble. Tapping the small drop-down overlay on a sent photo opens an initial actions menu (Reply, Forward, Download, Revocation permissions); selecting *Revocation permissions* transitions the menu to a dedicated submenu shown in Figure 5.4a. In code, this two-level pattern corresponds to the `openPhotoMenu` state switching between `mode: "actions"` and `mode: "revoke"` within the `PhotoMessageBubble` component.




(a) Revocation submenu on a sent photo, showing the five post-send controls.




(b) Expanded permission summary beneath the message bubble, with a live expiry countdown.

Figure 5.4: Post-send permission management: the sender's revocation submenu (a) and the in-chat state feedback (b).


The submenu exposes five actions that map directly to `updateSelectedPhotoPermissions` (Listing 5.5): *Revoke / Restore photo access* toggles `status`, *Block / Allow forwarding* toggles `canForward`, *Block / Allow download* toggles `canDownload`, *Remove time limit* clears `expiresAt`, and *Set time limit* opens the `TimeLimitModal` to assign a new deadline. Each action is a single partial update to the canonical record in `mainMessages`; the menu labels reflect the current effective state so the sender always sees the available transition rather than the current value.

The result of any change is visible immediately in the chat thread. As shown in Figure 5.4b, each photo message carries a collapsible summary row beneath the bubble. In its compact form, colour-coded tick and cross indicators signal status, forwarding, review mode, and download at a glance; expanding the row reveals labelled chips—*Visible*, *Forwarding allowed*, *Reviewable later*, *Download blocked*, *Expires in 29m 40s*—together with the caption and disclaimer text. The expiry chip updates every second via the countdown tick mechanism described in Section 5.4. Because every participant view derives its display from the same canonical record through `getEffectivePermissions`, the recipient's and forwarded recipient's bubbles update on the same render cycle without the sender needing to take any additional action.


This post-send surface satisfies the ongoing permission-management requirement (**FR3**) and the live consent-state requirement (**FR5**), while the in-chat summary chips address the state-visibility requirement (**FR4**) and the feedback requirement (**FR6**).

## Recipient Experience and Revoked States

The recipient's view mirrors the sender's permission chips but does not expose any management controls. Figure 5.5a shows an active photo in the recipient handset: the two-photo collage is visible, and the expanded summary row displays *Visible*, *Forwarding allowed*, *Reviewable later*, *Download blocked*, and a live countdown (*Expires in 20m 49s*). These chips are derived from the same canonical record via `getEffectivePermissions`, so they always reflect the sender's most recent change. The recipient's action menu offers Reply, Forward (if permitted), Download (if permitted), and—when access has been revoked—*Request access*, but never exposes the revocation controls reserved for the sender.




(a) Active photo with expanded permission chips and live expiry countdown.





(b) Revoked state: photo replaced by a neutral placeholder.

Figure 5.5: Recipient experience: active photo (a) and after sender revocation (b).

When the sender revokes access, the recipient's bubble transitions to the state shown in Figure 5.5b. The photo is replaced by an *"Access changed — This photo is no longer visible."* placeholder with the note *"Screenshots, saved copies, or prior viewing may already exist."* The summary row updates to show all-cross indicators and chips reading *Revoked*, *No forwarding*, *Not reviewable*, and *Download blocked*. In the implementation, `PhotoMessageBubble` renders this placeholder whenever `getEffectivePermissions` returns a status of `"revoked"`, regardless of whether the revocation was manual or caused by time-limit expiry; no separate revocation event or message replacement is needed.

View-once photos follow a similar pattern. Before the recipient opens the content, the bubble shows a *"View once — Open"* prompt with permission chips including *View once* (Figure 5.6a). After the recipient taps *Open* and closes the full-screen viewer, the message id is added to the `consumedViewOnce` array and the bubble transitions to an *"Opened once — This photo can no longer be viewed."* notice; the *View once* chip gains a tick mark to confirm consumption (Figure 5.6b).




(a) View-once photo before opening.

(b) After opening: content consumed, tick indicator shown.

Figure 5.6: View-once lifecycle on the recipient handset: before (a) and after (b) consumption.

Across all three cases—active, revoked, and view-once consumed—the recipient sees neutral, system-mediated language rather than accusatory wording, satisfying the recipient-experience requirement (**FR10**). The consistent use of the same chip-based summary row across sender and recipient views ensures that both parties read permission state in an identical format, which supports the consistency requirement (**NFR7**).

## Forwarding and Access Requests

Forwarding is gated by the canonical permission state. When `canForward` is `true` and the photo is active, the recipient's action menu enables *Forward*; the handler `forwardPhotoMessage` (Listing 5.6) checks `getEffectivePermissions` at the moment of forwarding and, if permitted, appends a new message to `forwardedMessages` with the same `sourcePhotoId`. The forwarded copy therefore remains linked to the canonical record: any later revocation by the sender propagates to both the recipient and the secondary recipient without additional synchronisation, as described in Section 5.4.

Figure 5.7 shows the prototype after the sender has revoked access to a previously forwarded photo. All three handsets reflect the change simultaneously: the sender's view retains the photo but displays a revoked summary; the recipient's bubble is replaced by the "Access changed" placeholder with *Forward* and *Download* disabled in the action menu; the secondary recipient's forwarded copy shows the same revoked placeholder and chips (*Revoked*, *No forwarding*, *Not reviewable*, *Download blocked*). The recipient's menu now includes *Request access* as the only actionable option beyond *Reply*.





Figure 5.7: Three-view state after sender revocation of a forwarded photo. Left: sender with access-request notification (*Accept*/*Reject*). Centre: recipient with revoked placeholder and *Request access* in the action menu. Right: secondary recipient with propagated revocation.

When the recipient selects *Request access*, a `RequestAccessPanel` overlay opens inside the recipient's handset, allowing an optional message to accompany the request. The request is routed to the sender's thread as a text message carrying the photo reference and *Accept* / *Reject* buttons, visible in the sender panel of Figure 5.7. If the sender accepts, `updateSelectedPhotoPermissions` restores the canonical record to `status: "active"`; if they reject, a follow-up message confirms the decision to the recipient. Access renewal is therefore a negotiated interaction rather than an automatic reversal.

Figure 5.8 shows the prototype immediately after the sender has accepted the request. All three views have returned to an active state: the sender's thread now reads *"Accepted — access restored."*, the recipient's photo is visible again with active permission chips, and the secondary recipient's forwarded copy is likewise restored—all driven by the single canonical update propagating through `getEffectivePermissions`.






Figure 5.8: Three-view state after the sender accepts the access request. The photo is visible again across all participant views, with permission chips reflecting the restored state.

This flow satisfies the forwarding-control requirements (**FR7**–**FR9**) and the access-request requirement (**FR11**), while the three-way propagation visible in both figures demonstrates that downstream copies remain governed by the original sender's permission state throughout the revocation and renewal cycle.

## Co-Subject Notification and Revocation Request

When the sender marks a photo with the *Co-subject* toggle before sending, the prototype generates a notification in the co-subject's dedicated handset view. Figure 5.9a shows this notification: a prominent card reading *"You are depicted in this photo — Tap to view the photo."*,

followed by the explanatory text *"You have been notified that you appear in this photo. You can request the sender to revoke it."* and a limitation cue: *"Protection is in-app only; screenshots and prior viewing cannot be fully undone."* The same permission chips used throughout the prototype appear beneath the card, so the co-subject can inspect the photo's current state (in Figure 5.9a: *Visible*, *Forwarding allowed*, *Reviewable later*, *Download allowed*).




(a) Co-subject notification with depicted-person card and permission chips.

(b) Revocation request panel with optional message and limitation disclaimer.

Figure 5.9: Co-subject flow: notification (a) and revocation request (b).

If the co-subject wishes to act, selecting *Request revocation* from the photo's action menu opens the `RequestRevocationPanel` overlay (Figure 5.9b). The panel identifies the photo by label, provides an optional message field with placeholder text (*"e.g. I'd prefer this photo not to be shared."*), and repeats the platform-limitation warning: *"Revocation affects in-app access only;*

*offline copies may already exist."* Tapping *Send request* routes the revocation request to the sender's thread.





Figure 5.10: Sender's view after receiving the co-subject's revocation request, with *Accept* and *Reject* controls.

On the sender's side (Figure 5.10), the request appears as a text message reading *"Requested revocation of the photo: Cafe."* with *Accept* and *Reject* buttons. If the sender accepts, the canonical record is updated to `status: "revoked"` via `updateSelectedPhotoPermissions`, and the revocation propagates to all participant views through the same derivation path described in Section 5.4. If the sender rejects, a follow-up message confirms the decision. As with access requests, the co-subject flow is a negotiated interaction: the co-subject can express a preference, but the sender retains the final decision over the permission state.

This flow satisfies the co-subject notification and revocation-request requirements (**FR12**–**FR17**), while the consistent use of limitation warnings across both the notification card and the request panel reinforces the expectation-management principle introduced in the pre-send composer.

## 5.6 Prototype Boundaries and Limitations (does this belong to chapters: discussion, results/evaluation, conclusion/future work or this one?)

will talk about no face recognition, no end to end encryption or other kinds of security features added.

## 5.7 Challenges and Solutions

## 5.8 Software Testing

Changes were tested manually in the browser across the four stakeholder views after each modification. Version control was maintained with Git throughout both phases.

belki plywright testleri de eklersin.

co-subject ile alakali konususrken: If you keep co-subject, start with a lightweight version. For example: notify named people that the photo was shared, then let them request review or takedown. Do not start with a full complex rights system.

# Chapter 6

# Legal, Social, Ethical and Professional Issues

Your report should include a chapter with a reasoned discussion about legal, social ethical and professional issues within the context of your project problem. You should also demonstrate that you are aware of the regulations governing your project area and the Code of Conduct & Code of Good Practice issued by the British Computer Society, and that you have applied their principles, where appropriate, as you carried out your project.

## 6.1 Legal Issues

## 6.2 Social & Ethical Issues

## 6.3 Professional Issues

# Chapter 7

# Results/Evaluation

## 7.1 Brief

miro board linki koymayi unutma.

## 7.2 Interview-based Evaluation

### 7.2.1 Methodological Approach

A qualitative interview-based evaluation was used, with semi-structured interviews. This method was appropriate because the aim of the research was not only to gather feedback on the prototype, but also to investigate how participants made sense of new privacy controls, how they interpreted post-send revocation, and how they felt about the power balance between stakeholders. Weiss argues that qualitative interviewing is useful when the researcher needs more than brief or standardised answers, because it allows the interviewer to move beyond fixed questioning and obtain participants' fuller accounts through further explanation and discussion (Weiss, 1994, p. 3). It was therefore well suited to this study, where participants needed to explain their own reasoning, expectations, and concerns in response to novel interface states. Weiss also notes that qualitative interviewing enables researchers to access participants' "perceptions and reactions" that are only available through their own accounts (Weiss, 1994, p. 10).

Semi-structured interviews are well suited to this kind of exploratory HCI evaluation because

they combine consistency across participants with enough flexibility to probe misunderstandings, emotional reactions, and unanticipated concerns.This is also consistent with Weiss's view that, in qualitative interviewing, the interviewer should direct discussion toward the topics that matter to the study while also judging when a response requires elaboration (Weiss, 1994, pp. 8–9). In this study, the same scenario sequence was shown to all participants, while follow-up probes were used selectively depending on the participant's responses to explore their reasoning in more depth.

### 7.2.2 Participants and Sampling

The selection of participants were chosen using purposive sampling. This approach was appropriate because the study's goal was not to produce a statistically representative account of the general population. Instead, it seeks feedback from people whose daily experiences qualified them to evaluate a prototype for messaging-based photo sharing. Weiss1994 argues that, when a study is concerned with the experiences of people who share a common characteristic, the researcher needs "a sample of people who together can represent the population of concern," and that with small qualitative samples it is often preferable to select respondents purposively in order to capture important variation rather than rely on probability sampling [57].

The study specifically targeted adults aged 18-24, as this group is especially relevant to the context of the prototype and to contemporary messaging-based photo-sharing practices. In the UK, 18-24-year-olds remained the most active online in 2025, while 16-24-year-olds used the widest range of online communication platforms of any age group, indicating particularly high engagement with digital communication services [44, 45]. This is directly relevant to the current study because online communication platforms include services used for messaging and calling, and WhatsApp has been identified as both the most popular app for those activities and the highest-reaching messaging and calls service across age groups [43, 44]. Although some usage data is reported for the broader 16-24 category, the present study focuses on the adult subset of that group for practical and ethical reasons. Taken together, these findings support the use of an 18-24 sample for evaluating a prototype concerned with image-sharing permissions and consent revocation in messaging environments.

(SUNA BIR DAHA BAKICAZ YENI GENDER BACK UP KISMI BU)

Nine participants were recruited in total (8 male, 1 female), all of whom were university students aged between 20 and 23. The sample was not gender-balanced, which is acknowledged as a

limitation. However, the study did not aim to compare responses across demographic groups; its focus was on how participants interpreted and evaluated a specific interface design. In qualitative research of this kind, the analytical priority is depth of individual accounts rather than demographic representativeness [7, 34]. Malterud, Siersma and Guassora's concept of information power further supports this position: when the study aim is narrow and the sample is specific to the phenomenon under investigation, fewer and less diverse participants can still yield sufficient analytical insight [34]. Gender was recorded descriptively to contextualise the sample but was not used as an analytic category. All participants reported regular use of WhatsApp or similar messaging platforms, with a minimum of six years of experience, ensuring familiarity with the photo-sharing conventions and interface patterns that the prototype builds upon.

A target of 8-10 participants was set for this study. This number was considered appropriate for a focused qualitative evaluation with a relatively specific participant group and a narrow research aim. Rather than seeking statistical outcomes, the study aimed to identify the recurring patterns in how participants understood the prototype. This is supported by methodological literature suggesting that smaller interview samples can be sufficient in focused studies. Hennink, Kaiser and Marconi found that code saturation was reached at nine interviews, while Guest, Bunce and Johnson found that thematic saturation occured within the first twelwe interviws, with basic elements of higher-level themes were already present by six interviews [20, 22]. More broadly, Malterud, Siersma and Guassora argue that qualitative sample size should be guided by information power, such that studies with a narrow aim and specific sample may require fewer participants [34]. In this case, 8–10 participants was judged sufficient to generate meaningful evaluative insight while remaining feasible within the scope of the dissertation.

**Sonradan silmeyi unutma** ()

### 7.2.3 Inrerview Procedure

Each interview will be conducted individually using two main materials: a written moderator script and a set of screenshots taken from the prototype. The moderator script structures the session into a consent stage, a warm-up section, five scenarios,and a final wrap-up. This use of a written guide is consistent with Weiss's (1994) view that an interview guide should function as a prompt and checklist for the interviewer rather than as a script that is followed mechanically [57]. The visual materials consist of fictional example photos and screenshots illustrating the

main design states.

At the start of each session, participants will be read a standardised consent statement explaining the purpose of the study, the nature of the prototype evaluation, and the fact that the participant is not being tested. They will also be informed that they may skip any question, stop the interview at any time, and choose whether or not to be audio-recorded. This procedure is consistent with DeJonckheere and Vaughn's (2019) recommendation that participants should be informed when audio recording is used for data collection and that they should be able to refuse recording if they prefer. If consent is given, the interview will be audio-recorded so that responses can later be transcribed and analysed using the participant's exact wording, which DeJonckheere and Vaughn (2019) identify as an important advantage of verbatim transcription [13].

The interview begins with a short warm-up about participants' current photo-sharing behaviour on messaging apps such as WhatsApp. This order follows DeJonckheere and Vaughn's (2019) guidance that interviews should begin with easy, context-setting questions before moving into deeper discussion [13]. Participants are then shown a series of prototype scenarios in a fixed order using screenshots. These screenshots are based on the set scenarios which includes pre-send permissions screen, the post-send permission-change screen, the recipient-side view after access has changed, the forwarding/request-access-again flow, and co-subject related flow. For each screen participants asked to describe what they think happening. This is intentional, because participants' first interpretations are part of the evaluative data, especially in relation to clarity, trust, fairness, and perceived control. This reflects DeJonckheere and Vaughn's (2019) recommendation that interview questions should be open-ended, with follow-up questions used to explore responses in more detail [13]. Probes are used selectively rather than mechanically, so the interview remains conversational. This approach is consistent with Weiss (1994), who argues that rigidly covering every point in an interview guide can reduce the quality of qualitative data [57]. The interviews use fictional example photos rather than participants' own personal images. This keeps the scenarios realistic while avoiding unnecessary disclosure of private content, which is appropriate given the potentially sensitive nature of the topic [13]. At the end of the interview, participants are asked a short set of reflection questions about whether the design would increase their sense of control, affect their trust in the platform, and which elements felt most clear, useful, confusing, or uncomfortable. They are also invited to add anything else that stood out.

### 7.2.4 Data Analysis Method

Interview recordings were transcribed and analysed using reflexive thematic analysis [6, 7]. This approach was appropriate because the aim of the evaluation was not simply to count preferences or identify isolated usability issues, but to examine how participants interpreted the prototype, how they reasoned about post-send control, and how they judged the design in terms of clarity, trustworthiness, and fairness. Reflexive thematic analysis treats the researcher as an active participant in knowledge production rather than as a neutral coder, which suited the interpretive aims of this study [7].

The analysis used a hybrid deductive–inductive coding strategy. Initial coding was guided by concepts established in the literature review and research questions, including understandability of permission states, perceived control, trustworthiness, fairness between sender and recipient, forwarding comprehension, screenshot limitation awareness, and co-subject agency. At the same time, the analysis remained open to unanticipated issues raised by participants, such as discomfort, social tension, or concerns not anticipated by the prior literature. This combination of theory-driven and data-driven coding is methodologically supported in the thematic analysis literature, where the hybrid approach has been described as a legitimate means of honouring both the theoretical framework and the participants' accounts [16].

The analytic process followed a structured sequence from raw data to themes, as illustrated in Figure 7.1.





Figure 7.1: Overview of the thematic analysis process on the Miro board.

Transcripts were first read repeatedly to support familiarisation with the dataset as a whole. Key quotes capturing relevant perceptions, reactions, and experiences were then extracted and placed onto a Miro board as colour-coded sticky notes, with each colour representing the interview section from which the quote originated (warm-up, scenarios 1 through 5, and final reflections). This visual arrangement supported comparison across participants and helped codes and excerpts to be grouped spatially as patterns became more apparent. This process producedapproximately 500 quotes across all nine participants, which were further refined to around 250 analytically relevant quotes.

An initial codebook of 56 fine-grained codes was developed through the hybrid deductive–inductive process described above. These codes were informed in part by concepts identified in the literature review and research questions, while also being revised and expanded in response to recurring patterns in the interview data. To support efficient and consistent coding across the dataset, the 56 codes were consolidated into 20 working codes grouped into seven conceptual categories: Control and Agency, Understandability and Clarity, Trust and Transparency, Social and Emotional Impact, Forwarding and Redistribution, Co-Subject and Multi-Party Privacy, and UI and Design Feedback. Both the full and simplified codebooks are included in Appendix **??**.

Coding was conducted primarily at the semantic level, focusing on participants' explicit interpretations and stated reactions, while also attending to broader patterns of meaning where relevant. Each quote was tagged with the relevant code identifiers from the simplified codebook. Codes were then reviewed and grouped into broader candidate themes based on recurring patterns in how participants understood the prototype and evaluated its implications. Candidate themes were checked against the coded data and the wider dataset to ensure they captured meaningful patterns across multiple participants rather than reflecting isolated responses. Themes were refined iteratively until they provided a coherent and internally consistent structure for presenting the evaluation findings. The resulting five themes, their descriptions, contributing codes, and supporting quotes are summarised in Figure 7.2.








| Theme | Description | Codes | Example Interview Quotes |
|---|---|---|---|
| Theme 1: From Binary to Revocable Consent | This theme concerns participants' views on current photo-sharing controls as too limited or too extreme. It captures their preference for permission settings that can be adjusted both before and after sending, rather than fixed at the moment of disclosure. |  |  |
| Theme 2: Bounded Control and Honest Limitations | This theme concerns how participants responded to the system's communication of its own limits, particularly around screenshots and saved copies. It captures the tension between valuing transparency and questioning the usefulness of controls that cannot offer complete protection. |  |  |
| Theme 3: Revocation as Social Negotiation | This theme concerns how participants interpreted photo revocation as an interpersonal action rather than a purely technical one. It includes responses shaped by trust, fairness, awkwardness, and views on the request-access mechanism. |  |  |
| Theme 4: Co-Subject Privacy as a Multi-Consent Problem | This theme concerns participants' reactions to giving depicted individuals a role in post-send control. It includes both support for the underlying privacy principle and concerns about feasibility, power balance, and how such control should be governed. |  |  |
| Theme 5: Interface Legibility and Permission Understandibility | This theme concerns how clearly the interface communicated permission states, feature logic, and available actions. It includes participant responses to wording, repetition, layout, and the balance between visibility and message-space efficiency. |  |  |

Figure 7.2: Summary of the five themes with descriptions, associated codes, and example interview quotes.

To strengthen the credibility of the analysis, a peer review was conducted with a second reviewer from the same cohort. Through this process, the themes were checked for consistency with the original data and refined where necessary.

In line with reflexive thematic analysis, themes were not treated as if they simply emerged from the data, but were actively developed by the researcher through sustained engagement with the dataset and informed by the theoretical context established in Chapter 2 [7]. As a single-researcher project, the analysis did not incorporate formal inter-rater reliability checks. This is consistent with reflexive thematic analysis, which does not treat coding reliability or consensus between coders as markers of quality, but instead positions researcher subjectivity and reflexive engagement with the data as central to the analytic process [7]. The following section presents each theme in detail.

## 7.3 Thematic Analysis Findings

### 7.3.1 Theme 1: From Binary to Revocable Consent

The first theme captures how participants percieved current WhatsApp photo sharing controls as inadequate and how the prototype's revisable permissions model strengtens the consent re-

vocation. Participants consistently framed current WhatsApp photo sharing as too binary, typically reduced to either permenant availability or view-once, with no support for changing permissions later. The prototype's ability ot configure permissions before and after sending was recognised by all nine participants as an improvement and frequently connected to personal experiences. P1 described this need in explicitly relational terms: *"when I send some more private pictures to my close friends or my closest relationships... when my status of my relationship changes, I want to go back and undo what I send"* (P1, Warm-up). Furthermore P5 connected this to the risk of accidental disclosure: *"sometimes I can accidentally send pictures to the wrong people and it could have major consequences"* (P5, Warm-up). The shared underlying concern was not simply about deleting content, but about maintaining ongoing agency over shared material as the context evolves.

Several participants explicitly criticised the limited range of existing controls. As P1 put it, *"we have two options... no middle option because the two of them are both extremes"* (P1, Warm-up), while P4 summarised the broader issue by stating that *"in most apps, once the photo is sent, you do not really have much control anymore"* (P4, Warm-up). The prototype addressed this gap by allowing permissions to be configured at the point of sending and revised later.

For some participants, the increased sense of control extended beyond personal comfort to behavioural change. P5 suggested the feature would expand their use of the platform: *"This would definitely increase my use of this platform for photos. It could also make me consider using it more for business, maybe contracts"* (P5, Scenario 2). P2 similarly framed the co-subjectfeature in precautionary and regulatory terms, suggesting it could be useful in legal contexts because it provided a mechanism for showing that permission-related steps had been taken and for reducing future disputes over shared personal data. This indicates that revisable permissions may not only reduce anxiety for existing sharing behaviour but also enable new categories of photo sharing that users currently avoid.

These findings are consistent with the literature on dynamic and ongoing consent reviewed in Chapter2, which argues that one-off authorisation models are poorly suited to interpersonal messaging because the meaning of permission can shift after disclosure [24, 29, 65].

### 7.3.2 Theme 2: Bounded Honesty and System Limitations (screenshot limitasyonu, ya da ...)

This theme evaluates whether the prototype achieved the design goal set out in Section 4.2.2: communicating revocation as limited but meaningful control rather than implying complete erasure. In practice, the results only partially supported this expectation. For some participants, the screenshot warning and related explanations made the system feel more realistic and therefore more trustworthy, for others, the same honesty weakened the feature's perceived value by foregrounding how little control can be guaranteed after disclosure.

The most positive framing came from P4, who described the warning as making the design feel more credible: *"That may make the feature feel less powerful, but it also makes it more trustworthy and realistic"* (P4, Scenario 1). P7 similarly treated the disclaimer as a useful prompt for reflection before sending, although both P7 and P9 felt, it needed greater visual prominence to function effectively. This shows that the prototype generally succeeded in managing expectations for participants who had previously accepted revocation as prospective and partial, but that this was strongly dependent on the warning being properly placed and clearly visible.

At the other end of the spectrum, P3 interpreted the same information as undermining the feature's purpose: *"it does make you feel honest, but then at the same time it makes you think, what's the point of sending it using these revocable permissions in the first place?"* (P3, Scenario 1). This scepticism extended to P3's overall willingness to use the feature for sensitive content: *"if it was an image where I was on the border of sending it, I would probably send it with these features. But for extremely sensitive stuff, probably not"* (P3, Final Reflections). P9 did not notice the warning at all until it was pointed out: *"... the disclaimer is good but I didn't see it before until you pointed it out. So I think it'll be better if it was bigger"* (P9, Scenario 1).

The split in responses maps onto a tension identified in the design rationale (Section 4.2.2), where expectation management was positioned as a core design responsibility. The findings suggest that this principle is endorsed by participants who already hold a realistic mental model of digital persistence, but may discourage those who expect stronger guarantees. This is consistent with Schnitzler et al.'s observation that users do not always accurately understand what deletion or revocation actions achieve, and that clearer interface explanations can improve comprehension [50]. The practical implication is that the warning's value depends not only on its content but on its visual prominence and framing. Several participants suggested it should

be larger, more prominently placed, or accompanied by icons to ensure it is noticed before sending.

Platform trust responses further illuminate this theme. Participants who accepted the bounded nature of control tended to report increased trust in the platform (P1, P2, P4, P6, P8), reasoning that the feature demonstrated the platform's commitment to user privacy. P1 stated: *"it would make me trust the platform more, because it genuinely shows they want me to have control over my own privacy, which is something you cannot see everywhere in today's world"* (P1, Final Reflections). In contrast, participants who questioned the feature's effectiveness reported no change in platform trust (P3, P5, P7) or expressed broader scepticism about platform intentions (P9): *"it wouldn't change my trust in the platform, because most apps take sensitive information. I still don't trust them completely"* (P9, Final Reflections). P3 reframed the issue as interpersonal rather than institutional: *"the platform, no difference at all. It just makes a difference to the senders and how they interact"* (P3, Final Reflections).

Beyond the screenshot warning itself, participants identified a deeper technological limitation that the prototype cannot address: the possibility of capturing content using an external device. P7 noted that even with view-once protection, *"the photo is still displayed on the device. So you can always take another device and take a picture of the screen"* (P7, Warm-up). P5 echoed this: *"the only thing maybe you cannot get around is if the receiver takes a picture of the picture from another device"* (P5, Scenario 4). P8 similarly observed that *"of course there is always the option that another person might take a photo of the phone"* (P8, Scenario 1). This concern was raised by five participants in total and represents a structural limit of any platform-level revocation mechanism: once visual content is displayed on a screen, no software control can fully prevent physical capture. Notably, P5 suggested a partial technical mitigation where screenshots renders as a black screen and reports having seen this implemented elsewhere: *"if you take a screenshot of this picture, it could just look like a black screen. I've seen that"* (P5, Scenario 4). This suggests that while participants acknowledged the inherent limits of platform control, some also expected the design to push those limits further through available technical countermeasures. These observations are consistent with Heath et al.'s forensic analysis of ephemeral messaging, which documents multiple preservation routes including forwarding, screenshotting, and photographing content before it disappears [21].

### 7.3.3 Theme 3: Revocation as a Social Act

Participants did not treat revocation as a neutral technical action. Instead, they seen it as a socially meaningful act that could signal trust-mistrust, changing intentions or shifts in the relationship. The feedbacks ranged from acceptance to offence, with majority of participants suggesting that the social meaning of revocation depended on context, specifically the type of photo and the relationship involved.

Several participants expressed their acceptance by reasoning through reciprocity. So they stated that if they would want the same power as a sender, they should accept it as a recipient. P7 articulated this most clearly: *"there's no harsh feelings, no hard feelings. I'm totally happy with how it works... you don't play the role of just sender or just recipient. When you're using an app like this, you're actively being both"* (P7, Scenario 3).

However, other participants attached more negative meanings to the same action. P2 anticipated feeling *"a bit suspicious"* and *"annoyed"* (P2, Scenario 3), while P5 associated revocation with possible mistrust. The strongest reaction came from P8, who said: *"I would feel offended, like, why did you, at first you sent this and what happened that made you erase this photo?"* (P8, Scenario 3). These responses suggest that even when the interface uses neutral wording, revocation still carries an interpersonal signal that cannot be fully neutralised through design alone.

The request-access feature was designed to balane sender control with recipient-side agency. Again the responses were mixed. P5 reimagined the feature as a timed-access mechanism through a concrete scenario: *"one guy buys all the tickets... he could revoke access and then when friends are at the entrance, they could request access"* (P5, Scenario 3). However, P8 questioned the logic of requesting back something that was deliberately withdrawn: *"it makes things more weird. He revoked it for a reason. Why should I want it again?"* (P8, Scenario 3). P9 raised a practical concern about abuse: *"if the person keeps spamming the request access option, it might be bothersome. So a timer, so they can't request as frequently"* (P9, Scenario 3).

These findings connect to several theoretical perspectives from Chapter 2. The range of emotional reactions is consistent with CPM theory's concept of boundary turbulence, where changes to previously established privacy rules can produce conflict or discomfort [46]. The social meaning participants attached to revocation also supports the design rationale's third principle (Sec-

tion 4.2.3), which aimed to minimise social friction through neutral wording (a goal that the wording succesfully achieved, as 88% of the participants described it as neutral), but which does not completely eliminate the relational signal that exists there in the revocation process itself.

### 7.3.4 Theme 4: Co-Subject Privacy as a Multi-Consent Problem

This theme captures the participants' reactions to the co-subject feature which is the most complex and contradictory set of responses in the evaluation. This feature was simultaneously the most confusing and for several participants the most important feature in the prototype. At first each participant (9/9) couldn't understand the 'co-subject in photo' label and required explanation before they could engage with the concept. However, after the explanation, majority recognised the value of protecting the privacy of depicted individuals.

The terminological confusion was universal and immediate. P1 asked directly: *"co-subject in photo. Can you please explain what is co-subject in photo?"* (P1, Scenario 1). P9 attempted to interpret it through an existing mental model: *"the co-subject is a bit hard to understand, but I think it's like how tagging works on Instagram"* (P9, Scenario 1). The tagging comparison was made independently by four participants (P1, P8, P9, and implicitly P5), suggesting that tagging is the closest available reference point for users encountering multi-party photo permissions for the first time.

Furthermore, participants generally accepted the privacy concern the feature was trying to address. P3 expressed this most strongly: *"even if you're not the one who took the picture, if you're a subject, you should have the rights as to whether or not other people should have access"* (P3, Scenario 5). P9 similarly linked the feature to protection against harm, arguing that equal power between sender and co-subject would be preferable in cases where the depicted person might otherwise be exposed without consent. These responses suggest that participants saw depicted individuals as having a legitimate stake in downstream photo sharing, even when they were not the original sender.

At the same time, participants raised substantial concerns about feasibility. P8 questioned the fundamental premise: *"why would the sender at the first point bother to tag the co-subject?"* (P8, Scenario 5), highlighting that the feature depends entirely on voluntary sender action. P2 suggested automated identification as an alternative, but P5 immediately identified the accuracy risk: *"you could be on the street and another guy looked at the camera and if the app*

*detects that as a co-subject"* (P5, Scenario 5). This tension between manual tagging (which depends on sender willingness) and automated detection (which introduces accuracy and privacy risks) reflects a challenge also identified by Xu et al., who propose privacy-preserving facial recognition for co-owner detection but acknowledge the dependency on reliable identification [66]. P1 identified a further privacy tension: notifying a co-subject could reveal that the sender had shared their image in a private conversation, potentially harming the privacy of that conversation itself. To reduce friction, P5 proposed persistent consent preferences — *"always accept from this person, or never accept"* (P5, Scenario 5) — which would function as contact-level trust settings, reducing per-photo overhead. Together, these concerns suggest that while the co-subject concept is valued in principle, its implementation must navigate a trade-off between identification accuracy, user friction, and sender willingness to participate.

On the question of who should hold the strongest control, opinions differed into three different clusters. The majority (P1, P2, P4, P5, P9) favoured equal or balanced control between the sender and co-subject. P7 and P8 favoured giving the co-subject stronger control, with P7 arguing: *"I'd favour the co-subject to have the upper hand because they might not even been asked for permission. The sender might just be sending it to random people"* (P7, Scenario 5). A third group (P3, P5, P6) advocated a veto model in which any single objection would prevent sharing: P6 stated that *"if there's 5 or 6 people and only one says no, then it can't be sent, it has to be unanimous"* (P6, Scenario 5).

These findings are consistent with the multi-party privacy conflict literature, which argues that co-owned content creates situations where the person sharing is not the only person exposed to privacy consequences [10]. The divergence in participants' governance preferences reflects a broader problem identified in the literature: co-owned photos cannot be governed adequately through sender-only control. Existing approaches offer partial support for multi-party privacy, but still leave unresolved how conflicting stakeholder interests should be managed once an image begins to circulate [10, 66, 68]. Therefore, the prototype addresses this by giving the depicted person a role after disclosure through a co-subject revocation request, rather than leaving control entirely with the sender.Overall, the findings suggest that co-subject control was conceptually valued, but would require clearer terminology and more carefully engineered governance before it could function in practice.

### 7.3.5 Theme 5: Interface Legibility and Presentation Efficiency

This theme concerns how permission information was visually presented in the chat interface and how participants evaluated the trade-off between visibility and usability. Unlike earlier themes, which focused on the meaning and social implications of revocable sharing, this theme focuses specifically on interface density, readability, and the practical burden of displaying permissions inline within everyday messaging.

The most consistent concern was the space occupied by permission labels beneath photos. P6 noted: *"imagine there are quite a few photos and it's this long list with all these features. It can be annoying to scroll"* (P6, Scenario 2). P7 raised an accessibility dimension: *"it's quite wordy... it might take a while to process for a user with accessibility issues"* (P7, Scenario 3). P8 described the same issue from the sender's perspective, observing that sending multiple photos with individual permission displays would make the chat difficult to navigate (P8, Scenario 2). Participants suggested several alternatives: P6 proposed a long-press contextual menu following existing WhatsApp patterns, P5 suggested on/off toggle sliders instead of text-based labels, and P1 preferred permissions hidden behind a tap rather than displayed inline. These suggestions converge on a shared preference: permission information should be accessible but not persistently visible.

The concerns are consistent with established usability guidance. Nielsen's heuristics emphasise that interfaces should avoid displaying information that is irrelevant or rarely needed, since every additional unit of information competes with more important content and reduces its visibility. The same guidance also notes that users should not have to wonder whether different words, situations, or actions mean the same thing, which is relevant to participants' confusion over the distinction between view-once and time-limit controls [40].

Two further clarity issues also emerged. P8 and P9 both perceived view-once and time-limit as overlapping features, with P9 stating: *"viewing it once and putting a time limit, I think they are similar. Both accomplishes the same thing"* (P9, Scenario 1). This suggests the distinction between these two controls needs clearer differentiation in the interface. P8 also noted inconsistency in how revocation was communicated, observing that the revoked state used both passive and active voice and *"basically repeats it three times in different places"* (P8, Scenario 3).

At the same time, participants recognised that the prototype's visual consistency with What-

sApp's existing patterns supported learnability. P5 noted: *"it's integrated to the WhatsApp system and the WhatsApp user interface, it looks like I'm already familiar with this stuff"* (P5, Final Reflections). This suggests that the design principle of consistency with existing interaction patterns (Section 4.2.5) was effective, and that the challenge is not the permission model itself but the density of its always-visible presentation within the chat.

| **Theme** | **Research Questions** | **Research Gaps** |
|---|---|---|
| T1: From Binary to Revisable Control | RQ1, RQ2, RQ5 | RG1 |
| T2: Bounded Honesty and System Limitations | RQ1, RQ5 | RG2 |
| T3: Revocation as a Social Act | RQ4, RQ5 | RG3 |
| T4: Co-Subject Privacy as a Multi-Stakeholder Problem | RQ3, RQ4 | RG3, RG4 |
| T5: Interface Legibility and Permission Understandability | RQ3, RQ5 | RG1, RG4 |

Table 7.1: Mapping of themes to research questions and research gaps.

## 7.4 Summary of Findings

Taken together, the five themes indicate that the prototype's core permission model (pre-send and post-send control) was well understood and valued as increasing user control for shared photos compared to WhatsApp's current model. This positive overall assessment was also reflected in participants' clarity ratings, which ranged from 3 to 5 with a median of 4.However, responses also showed that this control was understood as partial, socially sensitive and dependent on clear presentation. Participants appreciated the ability to revise permissions after sending, particularly in situations involving sensitive content, accidental disclosure, or changing relationships, but they also recognised that revocation could not fully prevent screenshots or external capture. In addition, revocation was interpreted not only as a technical control but as a socially meaningful act, while the co-subject feature highlighted both the importance and complexity of multi-party consent. Taken together, these findings suggest that revocable photo sharing was well received in principle, but would require careful balancing of agency, realism, social acceptability, and interface simplicity in practice.

implementationun 2. fazinda cogu advicelar tiye alindi ve cozuldu (hangileri cozuldu ekle; hangi themelerdeki sikintilar cozuldu diye eklersen daha kisa olabilir.)

# Chapter 8

# Discussion

BELKI YENI FINDINGLERDEN SONRA IMPLEMENT EDILEN VE EDILMEYENLER OLARAK BIR TABLO YAPILABILIR. AMA GENEL OLARAK TUM THESISI DISCUSS ETMEYI UNUTMA, BURASI SADECE EVALUATION ILE ALAKALI DEGIL.

## 8.1 Actionable Recommendations & Future Work

## 8.2 Limitations

# Chapter 9

# Conclusion and Future Work

The project's conclusions should list the key things that have been learnt as a consequence of engaging in your project work. For example, "The use of overloading in C++ provides a very elegant mechanism for transparent parallelisation of sequential programs", or "The overheads of linear-time n-body algorithms makes them computationally less efficient than $O(n \log n)$ algorithms for systems with less than 100000 particles". Avoid tedious personal reflections like "I learned a lot about C++ programming...", or "Simulating colliding galaxies can be real fun...". It is common to finish the report by listing ways in which the project can be taken further. This might, for example, be a plan for turning a piece of software or hardware into a marketable product, or a set of ideas for possibly turning your project into an MPhil or PhD.

# References


[1] Ioannis Agrafiotis. Enhancing user's privacy : developing a model for managing and testing the lifecycle of consent and revocation. Unpublished, 2012.

[2] Abdulmohsen S. Albesher and Thamer Alhussain. Evaluating and Comparing the Usability of Privacy in WhatsApp, Twitter, and Snapchat. *International Journal of Advanced Computer Science and Applications*, 12(8), 2021.

[3] Lemi Baruh and Mihaela Popescu. Big data analytics and the limits of privacy self-management. *New Media & Society*, 19(4):579–596, April 2017.

[4] Carlos Bermejo Fernandez, Dimitris Chatzopoulos, Dimitrios Papadopoulos, and Pan Hui. This Website Uses Nudging: MTurk Workers' Behaviour on Cookie Consent Notices. *Proceedings of the ACM on Human-Computer Interaction*, 5(CSCW2):1–22, October 2021.

[5] August Bourgeus and Laurens Vandercruysse. Reinvigorating Consent: Exploring New Paradigms for Privacy and Data Sharing. 2024.

[6] Virginia Braun and Victoria Clarke. Using thematic analysis in psychology. *Qualitative Research in Psychology*, 3(2):77–101, 2006.

[7] Virginia Braun and Victoria Clarke. Reflecting on reflexive thematic analysis. *Qualitative Research in Sport, Exercise and Health*, 11(4):589–597, 2019.

[8] Gary Burkhardt, Frederic Boy, Daniele Doneddu, and Nick Hajli. Privacy Behaviour: A Model for Online Informed Consent. *Journal of Business Ethics*, 186(1):237–255, August 2023.

[9] Vedant Raj Chaurasiya. CONSENT MECHANISMS UNDER THE DIGITAL PERSONAL DATA PROTECTION ACT, 2023: A COMPARATIVE LEGAL ANALYSIS

WITH GDPR AND CCPA/CPRA. *LawFoyer International Journal of Doctrinal Legal Research*, 3(2):517–572, June 2025.

[10] Mauro Cherubini, Kavous Salehzadeh Niksirat, Marc-Olivier Boldi, Henri Keopraseuth, Jose M. Such, and Kévin Huguenin. When Forcing Collaboration is the Most Sensible Choice: Desirability of Precautionary and Dissuasive Mechanisms to Manage Multiparty Privacy Conflicts. *Proceedings of the ACM on Human-Computer Interaction*, 5(CSCW1):1–36, April 2021.

[11] Jeffrey T. Child and Sandra Petronio. Unpacking the paradoxes of privacy in cmc relationships: The challenges of blogging and relational communication on the internet. In Kevin B. Wright and Lynne M. Webb, editors, *Computer-Mediated Communication in Personal Relationships*, chapter 2, pages 21–39. Peter Lang US, January 2011.

[12] Richard L Daft and Robert H Lengel. ORGANIZATIONAL INFORMATION REQUIREMENTS, MEDIA RICHNESS AND STRUCTUR.

[13] Melissa DeJonckheere and Lisa M Vaughn. Semistructured interviewing in primary care research: a balance of relationship and rigour. *Family Medicine and Community Health*, 7(2):e000057, March 2019.

[14] Alan R. Dennis and Susan T. Kinney. Testing Media Richness Theory in the New Media: The Effects of Cues, Feedback, and Task Equivocality. *Information Systems Research*, 9(3):256–274, September 1998.

[15] European Union. Regulation (eu) 2016/679 of the european parliament and of the council of 27 april 2016 (general data protection regulation). Official Journal of the European Union, 2016. OJ L 119, 4 May 2016, pp. 1–88.

[16] Jennifer Fereday and Eimear Muir-Cochrane. Demonstrating rigor using thematic analysis: A hybrid approach of inductive and deductive coding and theme development. *International Journal of Qualitative Methods*, 5(1):80–92, 2006.

[17] John D. Gould and Clayton Lewis. Designing for usability: Key principles and what designers think. *Communications of the ACM*, 1985. Accessed: 2026-04-07.

[18] Colin M. Gray, Cristiana Santos, Nataliia Bielova, Michael Toth, and Damian Clifford. Dark Patterns and the Legal Requirements of Consent Banners: An Interaction Criticism

Perspective. In *Proceedings of the 2021 CHI Conference on Human Factors in Computing Systems*, pages 1–18, May 2021. arXiv:2009.10194 [cs].

[19] Paul Graßl, Hanna Schraffenberger, Frederik Zuiderveen Borgesius, and Moniek Buijzen. Dark and bright patterns in cookie consent requests. July 2020.

[20] Greg Guest, Arwen Bunce, and Laura Johnson. How many interviews are enough? *Field Methods - FIELD METHOD*, 18:59–82, 02 2006.

[21] Howard Heath, Áine MacDermott, and Alex Akinbi. Forensic analysis of ephemeral messaging applications: Disappearing messages or evidential data? *Forensic Science International: Digital Investigation*, 46:301585, September 2023.

[22] Monique M. Hennink, Bonnie N. Kaiser, and Vincent C. Marconi. Code saturation versus meaning saturation: How many interviews are enough? *Qualitative Health Research*, 27(4):591–608, 2017. PMID: 27670770.

[23] Susan C. Herring. The coevolution of computer-mediated communication and computer-mediated discourse analysis. In Patricia Bou-Franch and Pilar Garcés-Conejos Blitvich, editors, *Analyzing Digital Discourse*, pages 25–67. Springer International Publishing, Cham, 2019.

[24] Jane Im, Jill Dimond, Melody Berton, Una Lee, Katherine Mustelier, Mark S. Ackerman, and Eric Gilbert. Yes: Affirmative Consent as a Theoretical Framework for Understanding and Imagining Social Platforms. In *Proceedings of the 2021 CHI Conference on Human Factors in Computing Systems*, pages 1–18, Yokohama Japan, May 2021. ACM.

[25] Alexis Shore Ingber. Understanding screenshot collection and sharing on messaging platforms: a privacy perspective. *Journal of Computer-Mediated Communication*, 30(1):zmae023, January 2025.

[26] Kumi Ishii, Mary Madison Lyons, and Sabrina A. Carr. Revisiting media richness theory for today and future. *Human Behavior and Emerging Technologies*, 1(2):124–131, April 2019.

[27] Mizuko Ito. Mobile Phones, Japanese Youth, and the Re-placement of Social Contact. In *Mobile Communications*, pages 131–148. Springer-Verlag, London, 2005. Series Title: Computer Supported Cooperative Work.

[28] Gayatri Priyadarsini Kancherla, Nataliia Bielova, Cristiana Santos, and Abhishek Bichhawat. Measuring Compliance of Consent Revocation on the Web, May 2025. arXiv:2411.15414 [cs].

[29] Jane Kaye, Edgar A Whitley, David Lund, Michael Morrison, Harriet Teare, and Karen Melham. Dynamic consent: a patient interface for twenty-first century research networks. *European Journal of Human Genetics*, 23(2):141–146, February 2015.

[30] Tim Kindberg, Mirjana Spasojevic, Rowanne Fleck, and Abigail Sellen. I saw this and thought of you: some social uses of camera phones. In *CHI '05 Extended Abstracts on Human Factors in Computing Systems*, pages 1545–1548, Portland OR USA, April 2005. ACM.

[31] Ah Ra Lee, Dongjun Koo, Il Kon Kim, Eunjoo Lee, Hyun Ho Kim, Sooyoung Yoo, Jeong-Hyun Kim, Eun Kyung Choi, and Ho-Young Lee. Identifying facilitators of and barriers to the adoption of dynamic consent in digital health ecosystems: a scoping review. *BMC Medical Ethics*, 24(1):107, December 2023.

[32] Daniel Lindegren, Farzaneh Karegar, Bridget Kane, and John Sören Pettersson. An evaluation of three designs to engage users when providing their consent on smartphones. *Behaviour & Information Technology*, 40(4):398–414, March 2021.

[33] Chi Liu, Tianqing Zhu, Jun Zhang, and Wanlei Zhou. Privacy Intelligence: A Survey on Image Privacy in Online Social Networks. *ACM Computing Surveys*, 55(8):1–35, August 2023. arXiv:2008.12199 [cs].

[34] Kirsti Malterud, Volkert Dirk Siersma, and Ann Dorrit Guassora. Sample size in qualitative interview studies: Guided by information power. *Qualitative Health Research*, 26(13):1753–1760, 2016. PMID: 26613970.

[35] Mpyana Mwamba Merlec, Youn Kyu Lee, Seng-Phil Hong, and Hoh Peter In. A Smart Contract-Based Dynamic Consent Management System for Personal Data Usage under GDPR. *Sensors*, 21(23):7994, November 2021.

[36] Meta Platforms, Inc. React: The library for web and native user interfaces. `https://react.dev`, 2024. Accessed: 2025-04-01.

[37] Microsoft Corporation. Typescript: Javascript with syntax for types. `https://www.typescriptlang.org`, 2024. Accessed: 2025-04-01.

[38] Kate Moran. Usability (user) testing 101. https://www.nngroup.com/articles/usability-testing-101/, 2019. Accessed: 2026-04-07.

[39] Minal R. Narkhede, Nilesh I. Wankhede, and Akanksha M. Kamble. Enhancing patient autonomy in data ownership: privacy models and consent frameworks for healthcare. *Journal of Digital Health*, pages 1–23, March 2025.

[40] Nielsen Norman Group. 10 usability heuristics for user interface design. https://www.nngroup.com/articles/ten-usability-heuristics/, 2024. Accessed: 2026-04-07.

[41] Helen Nissenbaum. A Contextual Approach to Privacy Online. 2011.

[42] Midas Nouwens, Ilaria Liccardi, Michael Veale, David Karger, and Lalana Kagal. Dark Patterns after the GDPR: Scraping Consent Pop-ups and Demonstrating their Influence. In *Proceedings of the 2020 CHI Conference on Human Factors in Computing Systems*, pages 1–13, April 2020. arXiv:2001.02479 [cs].

[43] Ofcom. Online nation 2024 report. Report, Ofcom, November 2024. Published 28 November 2024.

[44] Ofcom. Adults' media use and attitudes report. Report, Ofcom, May 2025. Published 7 May 2025.

[45] Ofcom. Online nation report 2025. Report, Ofcom, December 2025. Published 10 December 2025.

[46] Sandra Petronio and Jeffrey T Child. Conceptualization and operationalization: utility of communication privacy management theory. *Current Opinion in Psychology*, 31:76–82, February 2020.

[47] Eugenia Politou, Efthimios Alepis, and Constantinos Patsakis. Forgetting personal data and revoking consent under the GDPR: Challenges and proposed solutions. *Journal of Cybersecurity*, 4(1), January 2018.

[48] Marco Robol, Travis D. Breaux, Elda Paja, and Paolo Giorgini. Consent Verification Monitoring. *ACM Transactions on Software Engineering and Methodology*, 32(1):1–33, January 2023.

[49] Florian Schaub, Rebecca Balebako, Adam Durity, and Lorrie Cranor. A design space for effective privacy notices. July 2015.

[50] Theodor Schnitzler, Christine Utz, Florian M Farke, Christina Pöpper, and Markus Dürmuth. Exploring user perceptions of deletion in mobile instant messaging applications. *Journal of Cybersecurity*, 6(1):tyz016, January 2020.

[51] Arianna Schuler Scott. *Dynamic Consent: a Mechanism for Engagement*. PhD thesis, University of Oxford, February 2022.

[52] John Short, Ederyn Williams, and Bruce Christie. *The Social Psychology of Telecommunications*. John Wiley & Sons, London, 1976.

[53] Than Htut Soe, Oda Elise Nordberg, Frode Guribye, and Marija Slavkovik. Circumvention by design – dark patterns in cookie consents for online news outlets, June 2020. arXiv:2006.13985 [cs].

[54] Tailwind Labs, Inc. Tailwind css: Rapidly build modern websites without ever leaving your html. `https://tailwindcss.com`, 2024. Accessed: 2025-04-01.

[55] Vercel, Inc. Next.js: The react framework. `https://nextjs.org/docs`, 2024. Accessed: 2025-04-01.

[56] Ari Ezra Waldman. Designing Without Privacy.

[57] Robert S. Weiss. *Learning from Strangers : The Art and Method of Qualitative Interview Studies.* Free Press, Riverside, 1995.

[58] WhatsApp. About advanced chat privacy. `https://faq.whatsapp.com/715385484388016`. WhatsApp Help Center. Retrieved December 16, 2025.

[59] WhatsApp. About disappearing messages. `https://faq.whatsapp.com/673193694148537`. WhatsApp Help Center. Retrieved December 16, 2025.

[60] WhatsApp. About end-to-end encryption. `https://faq.whatsapp.com/820124435853543`. WhatsApp Help Center. Retrieved December 16, 2025.

[61] WhatsApp. About view once. `https://faq.whatsapp.com/1077018839582332`. WhatsApp Help Center. Retrieved December 16, 2025.

[62] WhatsApp. How to delete messages. `https://faq.whatsapp.com/1370476507114859`. WhatsApp Help Center. Retrieved December 16, 2025.

[63] WhatsApp. Introducing advanced chat privacy: Enhanced protection for your most sensitive conversations. https://blog.whatsapp.com/introducing-advanced-chat-privacy?lang=en, April 2025. WhatsApp Blog.

[64] WhatsApp LLC. Privacy policy – uk. https://www.whatsapp.com/legal/privacy-policy-uk, March 2025.

[65] John Wilbanks. Design Issues in E-Consent. *Journal of Law, Medicine & Ethics*, 46(1):110–118, 2018.

[66] Kaihe Xu, Yuanxiong Guo, Linke Guo, Yuguang Fang, and Xiaolin Li. My Privacy My Decision: Control of Photo Sharing on Online Social Networks. *IEEE Transactions on Dependable and Secure Computing*, 14(2):199–210, March 2017.

[67] Lei Xu, Ting Bao, Liehuang Zhu, and Yan Zhang. Trust-Based Privacy-Preserving Photo Sharing in Online Social Networks. *IEEE Transactions on Multimedia*, 21(3):591–602, March 2019.

[68] Ming Zhang, Zhe Sun, Hui Li, Ben Niu, Fenghua Li, Zixu Zhang, Yuhang Xie, and Chunhao Zheng. Go-Sharing: A Blockchain-Based Privacy-Preserving Framework for Cross-Social Network Photo Sharing. *IEEE Transactions on Dependable and Secure Computing*, 20(5):3572–3587, September 2023.

# Appendix A

# Extra Information

## A.1 Tables, proofs, graphs, test cases, ...

The appendices contain information that is peripheral to the main body of the report. Information typically included in the Appendix are things like tables, proofs, graphs, test cases or any other material that would break up the theme of the text if it appeared in the body of the report. It is necessary to include your source code listings in an appendix that is separate from the body of your written report (see the information on Program Listings below).

## A.2 Survey Information Sheet

## A.3 Survey Questions

# Appendix B

# User Guide

## B.1 Instructions

You must provide an adequate user guide for your software. The guide should provide easily understood instructions on how to use your software. A particularly useful approach is to treat the user guide as a walk-through of a typical session, or set of sessions, which collectively display all of the features of your package. Technical details of how the package works are rarely required. Keep the guide concise and simple. The extensive use of diagrams, illustrating the package in action, can often be particularly helpful. The user guide is sometimes included as a chapter in the main body of the report, but is often better included in an appendix to the main report.

# Appendix C

# Source Code

## C.1 Instructions

Complete source code listings must be submitted as an appendix to the report. The project source codes are usually spread out over several files/units. You should try to help the reader to navigate through your source code by providing a "table of contents" (titles of these files/units and one line descriptions). The first page of the program listings folder must contain the following statement certifying the work as your own: "I verify that I am the sole author of the programs contained in this folder, except where explicitly stated to the contrary". Your (typed) signature and the date should follow this statement.

All work on programs must stop once the code is submitted to KEATS. You are required to keep safely several copies of this version of the program and you must use one of these copies in the project examination. Your examiners may ask to see the last-modified dates of your program files, and may ask you to demonstrate that the program files you use in the project examination are identical to the program files you have uploaded to KEATS. Any attempt to demonstrate code that is not included in your submitted source listings is an attempt to cheat; any such attempt will be reported to the KCL Misconduct Committee.

**You may find it easier to firstly generate a PDF of your source code using a text editor and then merge it to the end of your report. There are many free tools available that allow you to merge PDF files.**