

It contains the **communication goal** that the bot will try to achieve. This prompt may also include a description of **the way in which the bot is supposed to achieve the objective**. This can be used to **outline the entire process** that

## Applying constraints

**Moderate freedom** (partially predictable):

Greet the user, introduce yourself and ask how you can help.

Full freedom (completely unpredictable, **not recommended!**):

Start the conversation.

If you want to further **specify the format or tone** of the response, you can add this information to the message prompt.

These modifications are recommended only if you want to deviate from the bot persona that is specified in the **Bot persona** Component. For example, you can add Keep the answer very brief. or Use stricter tone .

In general, we recommend leaving the bot conversational freedom where there is no need to communicate precise information, i.e. use more general instructions in the prompt (of the **moderate freedom** degree) and let the bot work within its persona. By doing this, you can achieve a nice authentic conversation and a satisfying user experience.

Intent prompt

The intent prompt is located in the **LLM intent**, i.e. the element that can be embedded in the **Dialog node** Component.

The prompt that we specify in the Description parameter is **purely descriptive** in nature, i.e. it is not an instruction to the bot.

intent

Its basic form is **a description of a situation that must occur for the bot to detect the given intent**. It is usually based on the user's reaction, their behavior within the dialog, or the state they are currently in.

For example:

The user wants to terminate the conversation.

The user has stated that they are not interested in the service.

The user agrees.

Prompt specification

The state that is described in the prompt can be specified by providing examples of common ways of expressing the intent:

The user wants to end the conversation, for example said goodbye.

The user wants to reset their password, for example they stated that they forgot or lost their password.

Action prompt

The action prompt is located in the **LLM action**, i.e. in the element that is inserted into the **Dialog node** Component like the **LLM intent**.

The prompt, which we specify in the **Action description** parameter, is simply the **clear description of the action** to be performed by the bot, for example:

Submit the result.

Reset the password.

End the conversation.

Transfer to a live agent.

The bot is aware of what actions it is capable of performing and will trigger them the moment the conversation indicates that it is appropriate to execute them.

### Prompt specification

Even the action prompt can be refined by adding a situational context when it is appropriate to execute the action. For example:

Submit the result. Call this function only if all the questions have been answered by the user.

Reset the password. Use this function when the user explicitly stated that they need their password to be reset.

If you choose to provide a longer description of the action, make sure you clearly describe the functionality at beginning of the description, eg. `Submit the result` . Without that, the function may not be executed correctly.

We recommend using the terminology **use this function** or **call this function** in the specified prompt. Based on our research and testing with LLMs, this phrasing works best for the bot to accurately detect actions.

### Entity prompt

It is possible to extract entities before calling the function. The Description field includes a simple description of the extracted entity:

Full name of the client

Description of the incident

Age of the user

Address

### Prompt specification

It is possible to refine the entity prompt by specifying the format of the extracted data. For example:

Date of birth in format DD/MM/YYYY

Make sure that the entity prompt is **purely descriptive** and does not contain any instructions.

Next chapter: [General prompt engineering tips?atLf=PAGETREE](#)

Q

Search OmniAgent Academy

Attachments

image-20250215-120755...

image-20250215-120742...