tpg12bt.st2.incorrectMarkException

Class IncorrectMarkException

- java.lang.Object
  -
    - java.lang.Throwable
      -
        - java.lang.Exception
          -
            - tpg12bt.st2.incorrectMarkException.IncorrectMarkException

- **All Implemented Interfaces:**

      java.io.Serializable

---

    public class **IncorrectMarkException**
    extends java.lang.Exception

This exception class is used for mark value's that is incorrect.

See Also:

      Serialized Form

-

- *Constructor Summary*

<mark>Constructors</mark>
Constructor and Description
IncorrectMarkException(java.lang.String message) The constructor will initialize the inherited message data member of the class.

- *Method Summary*

- **Methods inherited from class java.lang.Throwable**

      addSuppressed, fillInStackTrace, getCause, getLocalizedMessage,
      getMessage, getStackTrace, getSuppressed, initCause, printStackTrace,
      printStackTrace, printStackTrace, setStackTrace, toString

- **Methods inherited from class java.lang.Object**

      clone, equals, finalize, getClass, hashCode, notify, notifyAll, wait,
      wait, wait

-

- *Constructor Detail*

- **IncorrectMarkException**

  ```
  public IncorrectMarkException(java.lang.String message)
  ```

  The constructor will initialize the inherited message data member of the class.

  Parameters:
  ```
  message - The message that should be associated with this
  exception.
  ```