


FORM ELEMENTS

Note1: use **<input>** element for textboxes, radio buttons, checkboxes, submit, reset.

Note2: To help you recall which attributes are needed for each element, I list the first initial of each in a **box** in the attributes column.

element	attributes abbrevs: t = type, i = id, n = name, v = value	sample code and how it renders
form use <form>	ni other: action, method	<form name="myForm" id="myForm" action="mailto:perel@ecc.edu" method="post"></form>
textbox (input box ⁴)	tni other: size, maxlength (= max # characters) n and i name the field v usually omitted; it is what the user types into the box; t omitted when type="text" is the default	Last Name: <input type="text"/> ex: Last Name: <input type="text" name="lastName" id="lastName" /> ex: Last Name: <input name="lastName" id="lastName" />
radio buttons	tniv other: checked="checked" ¹ n – names the field (name for the group of option buttons) i and v name each individual field value	year: <input type="radio"/> freshman <input type="radio"/> sophomore ex: <input type="radio" name="year" id="fresh" value="fresh" /> ex: <input type="radio" name="year" id="soph" value="soph" />
checkboxes	tni other: checked="checked" ¹ n and i name the field (where each checkbox is a field) v is usually omitted ²	pick a color: <input checked="" type="checkbox"/> red <input type="checkbox"/> blue ex: <input type="checkbox" name="red" id="red" /> (value="On" by default)
submit button reset button	tv v is text that appears on button	<input type="submit" value="Submit"/> <input type="submit" value="Submit" /> <input type="reset" value="Clear"/> <input type="reset" value="Clear" />
Selection list use: <select> w/ <option>'s	ni –in select tag: n and i – name the field (name for the list of options) other: size, multiple="multiple" ³ , selected="selected" ¹ (size is the # of list items showing) v - names each individual field value (each list option)	State: <input type="text" value="NY"/> <select name="states" id="states"> <option value="NY">NY</option> <option value="FL">FL</option> etc. </select>
textarea use <textarea>	ni other: rows, cols n and i name the field; rows =# of lines (default 3), cols =chars (default 20)	 <textarea name="comments" id="comments"></textarea>

Footnotes:

1. **checked="checked"** makes that button or option appear pre-checked. **selected="selected"** is similar.
- 2.. Suppose for a checkbox, name="red". (1) If value="yes" is included in the input tag, and red IS selected, then the pair red/yes is sent to server. If red is NOT selected, no pair is sent to server. If value is left off it will have default value of "On".
3. **multiple="multiple"** - allows user to select multiple items on the list using the CTRL key
4. input box also has type="value" where value can be email, tel, url or date
5. id is optional

The name and value attributes:

name – names the field

-- For **checkbox**, the **name** describes each individual checkbox and **value="On"** by default

-- For **radio buttons**, the **name** describes the group of buttons and **value** describes each individual button

value – names the value of the field

-- For **textbox**, and textarea value is what the user types into the box

-- For **buttons**, value is the text appearing on the button

element	Session	page number	section in e-text
textbox	7.1	510	7-5
radio buttons	7.2	537	7-13
checkboxes	7.2	540	7-14
select	7.2	531	7-12
textarea	7.2	542	7-15
submit & reset	7.3	556	7-20b

Carey 6 book.