

Ex.No.: 3	WRITING BASIC SQL SELECT STATEMENTS
Date: 2 / 8 / 2024	

OBJECTIVES

After the completion of this exercise, the students will be able to do the following:

- List the capabilities of SQL SELECT Statement
- Execute a basic SELECT statement

Capabilities of SQL SELECT statement

A SELECT statement retrieves information from the database. Using a select statement, we can perform

- ✓ Projection: To choose the columns in a table
- ✓ Selection: To choose the rows in a table
- ✓ Joining: To bring together the data that is stored in different tables

Basic SELECT Statement

Syntax

```
SELECT *|DISTINCT Column_name| alias
FROM table_name;
```

NOTE:

DISTINCT—Suppress the duplicates.

Alias—gives selected columns different headings.

Example: 1

```
SELECT * FROM departments;
```

Example: 2

```
SELECT location_id, department_id FROM departments;
```

Writing SQL Statements

- SQL statements are not case sensitive
- SQL statements can be on one or more lines.

- Keywords cannot be abbreviated or split across lines
- Clauses are usually placed on separate lines
- Indents are used to enhance readability

Using Arithmetic Expressions

Basic Arithmetic operators like *, /, +, - can be used

Example:1

```
SELECT last_name, salary, salary+300 FROM employees;
```

Example:2

```
SELECT last_name, salary, 12*salary+100 FROM employees;
```

The statement is not same as

```
SELECT last_name, salary, 12*(salary+100) FROM employees;
```

Example:3

```
SELECT last_name, job_id, salary, commission_pct FROM employees;
```

Example:4

```
SELECT last_name, job_id, salary, 12*salary*commission_pct FROM employees;
```

Using Column Alias

- To rename a column heading with or without AS keyword.

Example:1

```
SELECT last_name AS Name  
FROM employees;
```

Example: 2

```
SELECT last_name "Name" salary*12 "Annual Salary"  
FROM employees;
```

Concatenation Operator

- Concatenates columns or character strings to other columns
- Represented by two vertical bars (||)
- Creates a resultant column that is a character expression

Example:

```
SELECT last_name||job_id AS "EMPLOYEES JOB" FROM employees;
```

Using Literal Character String

- A literal is a character, a number, or a date included in the SELECT list.
- Date and character literal values must be enclosed within single quotation marks.

Example:

SELECT last_name||'is a'||job_id AS "EMPLOYEES JOB" FROM employees;

Eliminating Duplicate Rows:

- Using DISTINCT keyword.

Example:

SELECT DISTINCT department_id FROM employees;

Displaying Table Structure

- Using DESC keyword.

Syntax

DESC table_name;

Example:

DESC employees;

Find the Solution for the following:

True OR False

1. The following statement executes successfully.

Identify the Errors

SELECT employee_id, last_name
sal*12 ANNUAL SALARY
FROM employees;

SELECT employee_id, last_name sal *12 AS ANNUAL-SALARY FROM
employees;
Queries

2. Show the structure of departments table. Select all the data from it.

DESC Employees table;

select * from Employees table;

3. Create a query to display the last name, job code, hire date, and employee number for each employee, with employee number appearing first.

select Employee-id, last-name, job-id, hire-date from Employees-table;

4. Provide an alias STARTDATE for the hire date.

select hire-date as start-date from Employees-table;

5. Create a query to display unique job codes from the employee table.

select distinct job-id from Employees-table;

6. Display the last name concatenated with the job ID, separated by a comma and space, and name the column EMPLOYEE and TITLE.

select last-name || ', ' || job-id as "Employee-Title" from Employees-table;

7. Create a query to display all the data from the employees table. Separate each column by a comma. Name the column THE_OUTPUT.

SELECT employee id || ', ' || last-name || ', ' || salary AS THE-OUTPUT FROM employees;

Evaluation Procedure	Marks awarded
Query(5)	5
Execution (5)	5
Viva(5)	5
Total (15)	15
Faculty Signature	(K)