

Ex.No.: 12		WORKING WITH CURSOR, PROCEDURES AND FUNCTIONS
Date:	27/9/2024	

AIM:

Create PL/SQL Blocks to perform the Item Transaction Operations using CURSOR, FUNCTION and PROCEDURE.

ALGORITHM:

STEP-1: Start.

STEP-2: Create two tables Item Master and Item Trans.

itemmaster(itemid , itemname, stockonhand)

itemtrans(itemid ,itemname ,dateofpurchase ,quantity)

STEP-3: Create a PROCEDURE with id, name and quantity as parameters which make a call to the FUNCTION by passing id, name, dop, and quantity as parameters dop is set as sysdate.

STEP-4: Using FUNCTION fetch each record from the table Item Master using CURSOR inside a Loop statement,

If Item Master's ItemId is equal to the entered ID value then exit the loop otherwise fetch the next record.

loop

fetch master into masterrec

exit when master%notfound

if masterrec.itemid=id then

exit;

end if;

end loop;

STEP-5: If Itemmaster's itemid = id then,

Add the Itemmaster's stockonhand with the given quantity and update the ItemMaster table and insert the Item information into the ItemTrans table.

STEP-6: Else, if the inputted item is not present in the ItemMaster table then insert the

new Item in both the tables.

STEP-7: Call the Procedure by passing the Item informations which calls the Function.

STEP-8: Exit.

PROCEDURES – SYNTAX

```
create or replace procedure <procedure name> (argument {in, out, inout} datatype ) {is,as}
variable declaration;
constant declaration;
begin
PL/SQL subprogram body;
exception
exception PL/SQL block;
end;
```

FUNCTIONS – SYNTAX

```
create or replace function <function name> (argument in datatype,.....) return datatype {is,as}
variable declaration;
constant declaration;
begin
PL/SQL subprogram body;
exception
exception PL/SQL block;
end;
```

CREATING THE TABLE 'ITITEMS' AND DISPLAYING THE CONTENTS

```
SQL> create table ititems(itemid number(3), actualprice number(5), ordid number(4), prodid
number(4));
Table created.
```

```
SQL> insert into ititems values(101, 2000, 500, 201);
1 row created.
```

SQL> insert into ititems values(102, 3000, 1600, 202);
1 row created.

SQL> insert into ititems values(103, 4000, 600, 202);
1 row created.

SQL> select * from ititems;

ITEMID	ACTUALPRICE	ORDID	PRODID
101	2000	500	201
102	3000	1600	202
103	4000	600	202

PROGRAM FOR GENERAL PROCEDURE – SELECTED RECORD’S PRICE IS INCREMENTED BY 500 , EXECUTING THE PROCEDURE CREATED AND DISPLAYING THE UPDATED TABLE

SQL> create procedure itsum(identity number, total number) is price number;
2 null_price exception;
3 begin
4 select actualprice into price from ititems where itemid=identity;
5 if price is null then
6 raise null_price;
7 else
8 update ititems set actualprice=actualprice+total where itemid=identity;
9 end if;
10 exception
11 when null_price then
12 dbms_output.put_line('price is null');
13 end;
14 /
Procedure created.

SQL> exec itsum(101, 500);
PL/SQL procedure successfully completed.

SQL> select * from ititems;

ITEMID	ACTUALPRICE	ORDID	PRODID
101	2500	500	201
102	3000	1600	202
103	4000	600	202

PROCEDURE FOR ‘IN’ PARAMETER – CREATION, EXECUTION

SQL> set serveroutput on;


```

SQL> create procedure yyy (a IN number) is price number;
  2 begin
  3 select actualprice into price from ititems where itemid=a;
  4 dbms_output.put_line('Actual price is ' || price);
  5 if price is null then
  6 dbms_output.put_line('price is null');
  7 end if;
  8 end;
  9 /

```

Procedure created.

```

SQL> exec yyy(103);
Actual price is 4000
PL/SQL procedure successfully completed.

```

PROCEDURE FOR 'OUT' PARAMETER – CREATION, EXECUTION

```

SQL> set serveroutput on;

```

```

SQL> create procedure zzz (a in number, b out number) is identity number;
  2 begin
  3 select ordid into identity from ititems where itemid=a;
  4 if identity<1000 then
  5 b:=100;
  6 end if;
  7 end;
  8 /

```

Procedure created.

```

SQL> declare
  2 a number;
  3 b number;
  4 begin
  5 zzz(101,b);
  6 dbms_output.put_line('The value of b is ' || b);
  7 end;
  8 /

```

The value of b is 100

PL/SQL procedure successfully completed.

PROCEDURE FOR 'INOUT' PARAMETER – CREATION, EXECUTION

```

SQL> create procedure itit ( a in out number) is
  2 begin
  3 a:=a+1;

```

```
4 end;
5 /
Procedure created.
```

```
SQL> declare
2 a number:=7;
3 begin
4 itit(a);
5 dbms_output.put_line('The updated value is '||a);
6 end;
7 /
```

The updated value is 8
PL/SQL procedure successfully completed.

CREATE THE TABLE 'ITTRAIN' TO BE USED FOR FUNCTIONS

```
SQL>create table ittrain ( tno number(10), tfare number(10));
Table created.
```

```
SQL>insert into ittrain values (1001, 550);
1 row created.
```

```
SQL>insert into ittrain values (1002, 600);
1 row created.
```

```
SQL>select * from ittrain;
  TNO    TFARE
-----
 1001     550
 1002     600
```

PROGRAM FOR FUNCTION AND IT'S EXECUTION

```
SQL> create function aaa (trainnumber number) return number
2 trainfunction ittrain.tfare % type;
3 begin
4 select tfare into trainfunction from ittrain where tno=trainnum
5 return(trainfunction);
6 end;
7 /
```

Function created.

```
SQL> set serveroutput on;
```

```

SQL> declare
2 total number;
3 begin
4 total:=aaa (1001);
5 dbms_output.put_line('Train fare is Rs. '||total);
6 end;
7 /

```

Train fare is Rs.550

PL/SQL procedure successfully completed.

FACTORIAL OF A NUMBER USING FUNCTION — PROGRAM AND EXECUTION

```

SQL> create function itfact (a number) return number is
2 fact number:=1;
3 b number;
4 begin
5 b:=a;
6 while b>0
7 loop
8 fact:=fact*b;
9 b:=b-1;
10 end loop;
11 return(fact);
12 end;
13 /

```

Function created.

```
SQL> set serveroutput on;
```

```

SQL> declare
2 a number:=7;
3 f number(10);
4 begin
5 f:=itfact(a);
6 dbms_output.put_line('The factorial of the given number is'||f);
7 end;
8 /

```

The factorial of the given number is 5040
 PL/SQL procedure successfully completed.

Program 1

FACTORIAL OF A NUMBER USING FUNCTION

```
CREATE OR REPLACE FUNCTION Factorial (n IN number) RETURN number IS
    result number := 1;
BEGIN
    IF n < 0 THEN
        RETURN NULL;
    ELSEIF n = 0 OR n = 1 THEN
        RETURN 1;
    ELSE
        FOR i IN 2 .. n LOOP
            result := result * i;
        END LOOP;
    ENDIF;
    RETURN result;
EXCEPTION
    WHEN OTHERS THEN
        DBMS_OUTPUT.PUT_LINE('AN ERROR OCCURED' || SQLERRM);
        RETURN NULL;
END Factorial;

SET SERVER OUTPUT ON;
DECLARE
    num number := 5;
    fact number;
END;
```


Program 2

Write a PL/SQL program using Procedures IN,INOUT,OUT parameters to retrieve the corresponding book information in library

TO WRITE A PL/SQL BLOCK TO DISPLAY THE EMPLOYEE ID AND EMPLOYEE NAME WHERE DEPARTMENT NUMBER IS 11 USING EXPLICIT CURSORS

```
1 declare
2 cursor cen1 is select eid,sal from ssemp where dno=11;
3 ecode ssemp.eid%type;
4 esal empp.sal%type;
5 begin
6 open cen1;
7 loop
8 fetch cen1 into ecode,esal;
9 exit when cen1%notfound;
10 dbms_output.put_line(' Employee code and employee salary are' || ecode 'and' || esal);
```


Program 2;

```
CREATE TABLE BOOKS (
```

```
    book_id NUMBER(5) PRIMARY KEY,
```

```
    title VARCHAR2(100), author VARCHAR(100),
```

```
    Publications_Year NUMBER(4), available_copies NUMBER(5)
);
```

```
INSERT INTO BOOKS VALUES (1, '1984', 'Orwell', 1949, 4);
```

```
INSERT INTO BOOKS VALUES (2, 'Mocking bird', 'Lee', 1960, 2);
```

```
INSERT INTO BOOKS VALUES (3, 'Gatsby', 'Fitzbold', 1925, 5);
```

```
COMMIT;
```

```
CREATE OR REPLACE PROCEDURE GetBook Info By Id (P-book_id IN
NUMBER, P-title OUT VARCHAR2, P-author OUT VARCHAR2) IS
BEGIN
```

```
    SELECT title, author INTO P-title, P-author FROM BOOKS WHERE_id =
```

```
END;
```

```
SET SERVER OUTPUT ON;
```

```
DECLARE
```

```
    V-title VARCHAR(100), V-author VARCHAR2(100);
```

```
BEGIN
```

```
    Get book Info by Id(1, V-title, V-author);
```

```
DBMS-OUTPUT.PUT_LINE('Book: ' || V-title || ', Author: ' || V-author);
```

```
END;
```

```

11 end loop;
12 close cmt;
13* end;

```

SQL> /

Employee code and employee salary are 1 and 39000
Employee code and employee salary are 5 and 35000
Employee code and employee salary are 6 and 23000

PL/SQL procedure successfully completed.

TO WRITE A PL/SQL BLOCK TO UPDATE THE SALARY BY 5000 WHERE THE JOB IS LECTURER , TO CHECK IF UPDATES ARE MADE USING IMPLICIT CURSORS AND TO DISPLAY THE UPDATED TABLE

SQL> declare

```

2 county number;
3 begin
4 update ssempp set sal=sal+10000 where job='lecturer';
5 county:= sql%rowcount;
6 if county > 0 then
7 dbms_output.put_line('The number of rows are '|| county);
8 end if;
9 if sql %found then
10 dbms_output.put_line('Employee record modification successful');
11 else if sql%notfound then
12 dbms_output.put_line('Employee record is not found');
13 end if;
14 end if;
15 end;
16 /

```

The number of rows are 3

Employee record modification successful

PL/SQL procedure successfully completed.

SQL> select * from ssempp;

EID	ENAME	JOB	SAL	DNO
1	nala	lecturer	44000	11
2	kala	seniorlecturer	20000	12
5	ajay	lecturer	40000	11
6	vijay	lecturer	28000	11
3	nila	professor	60000	12

Evaluation Procedure	Marks awarded
PL/SQL Procedure(5)	5
Program/Execution (5)	5
Viva(5)	5
Total (15)	15
Faculty Signature	