Autonomous AI Navigation Beacon – Molten Core Powered (FTL Support Network)

Author: Mervyn Jagels

---

1. Concept Overview

The **Autonomous AI Navigation Beacon** is designed to create an **interstellar safety net** for BlinkDrive-powered spacecraft. These beacons provide:

- **Safe FTL Corridors** → Real-time data on gravitational fields, anomalies, and high-energy zones.
- **Autonomous AI** → Self-healing, adaptive mapping, and continuous network updates.
- **Energy Independence** → Powered by a **Molten Core Generator**, requiring no external fuel for centuries.

Goal:
Enable **safe, repeatable interstellar travel** through an **AI-coordinated beacon chain** between star systems.

---

2. Beacon Architecture

- **Core Power System**:
    - **Molten Magnetic Confinement Chamber** using high-density materials (tungsten + iridium lining).
    - Heat harvested by **granite matrix + copper lattice**, feeding **Stirling engine array** for electricity generation.

    - Self-sustaining via **laser thermal maintenance loop**, no fuel reload required for centuries.

- **AI System**:
    - **Mapping Functions**: Detects gravitational wells, high-energy particle regions, and hazards.
    - **Navigation Relay**: Stores and transmits FTL jump corridors.
    - **Autonomy**: Uses onboard diagnostics & redundancy for self-repair.
- **Lifetime**:
    - Estimated **500+ years** without manual intervention.

---

3. Deployment Strategy

- Beacons positioned every **1 AU to 50 AU** for local system mapping, then spaced across **1 Light-Year intervals** for interstellar routes.
- Initial deployment: **Earth** → **Proxima Centauri**.
- Each beacon forms part of an **Interstellar AI Mesh Network**, ensuring no blind FTL jumps.

---

4. Power Calculations

Molten Core System

- **Core Temperature**: 2,500 °C
- **Stirling Engines**: 12 units per beacon
- **Power Output**:

```
Per Engine: ~2.5 MW
Total: ~30 MW continuous
Capacitor Storage: 50 GJ for burst operations
```

Beacon Operational Load

- AI + Sensor Array: ~200 kW
- Communications & Quantum Uplink: ~1 MW peak
- Total Baseline Draw: <1.5 MW
- Surplus Power → stored in capacitors for emergencies or burst transmission.

---

5. Why It Matters

- Eliminates **jump-blindness risk** for interstellar ships.
- Enables **progressive exploration** without waiting for human missions to chart routes.
- Provides the backbone for **Interstellar Internet + AI Navigation Grid**.

---

6. Open Source Declaration

---

7. Credit

```
Lead Concept & Design: Mervyn Jagels
AI Assistance: Physics Modeling & Documentation
```