CSS Architecture Package

1. **Refactoring evidence:** before/after notes showing how you reduced duplication, lowered specificity, clarified naming, or replaced repeated values.

For this assignment, I started working on both the final capstone project and the CSS Architecture, mainly for the homepage of an event rental decor website. I started layer by layer, but first I did rough CSS styles. The first duplication I reduced was the header and footer properties; since they shared similar properties, I combined them into one group. Similar to the hover property.

Before

```
.site-header {
  display: flex;
  justify-content: space-between;
  align-items: center;
  padding: var(--space-md);
}

.site-footer {
  display: flex;
  justify-content: space-between;
  align-items: center;
  padding: var(--space-md);
}
```

After

```
.site-header,
.site-footer {
  display: flex;
  justify-content: space-between;
  align-items: center;
  padding: var(--space-md);
}
```

Before

```
.site-nav a: hover,
.site-footer a: hover {
  background-color: var(--color-main);
}

.button: hover {  background-color: var(--color-main);
}
```

After

```
.site-nav a:hover,
.site-footer a:hover,
.button:hover {
  background-color: var(--color-main);
}
```

I also reduced the repeated background colors for the header and footer and combined them.

For **Repeated Values,** like colors, spacing, font, and border radius, I used CSS custom properties. For example, instead of writing color codes for every element multiple times, I use (--color-custom property name); I do the same for spacing and other values. This makes my CSS easier to maintain and update whenever needed.

2. **Architecture notes:** a short explanation of your layer/order strategy, token decisions, naming approach, and browser checks.

I organized my CSS into six layers: reset, base, layout, components, utilities, and states; each layer serves a specific purpose.

I used custom properties for colors, spacing, and border radius, which is named by their purpose, like --color-bg for background color and --color-text for text. I also use champagne and surface colors on my website. Same for font as --font- body.

I used a simple naming approach for my CSS, which makes it easier to understand. Like .site-header, .site-footer, .gallery-grid, .button, and .card, these names are easy to understand and access.

I checked the website in Chrome on small, medium, and large screens. I also checked the hover effect on navigation and buttons. For accessibility, I used the Tab key, and it works properly. The website still needs modifications. It's just the architecture.

1. **AI disclosure:** if used, document the purpose, output considered, verification, and what changed.

I used AI to suggest token names and refactoring options for duplicate styles, like combining repeated hover styles. I made changes using the suggestions, and I tested and verified the output in the browser .