

**Your grade: 100%**Your latest: **100%** • Your highest: **100%** • To pass you need at least 75%. We keep your highest score.

Next item →

1. What two arguments commonly follow the **grep** command?

1 / 1 point

- ☒ The string to search for and the file to search through
- ☐ The file to move and the new file location
- ☐ The file to write to and the string to add to it
- ☐ The file name to search for and the directory to search through

✔ Correct

The **grep** command is commonly followed by the string to search for and the file to search through. It is used to search files for specified strings.2. In Linux, what does the piping command (**|**) do?

1 / 1 point

- ☐ It searches a specified file and returns all lines in the file containing a specified string.
- ☐ It moves a file or directory to a new location.
- ☒ It sends the standard output of one command as standard input to another command for further processing.



- ☐ It sends the standard input of one command as standard output to another command for further processing.

✔ Correct

The piping command (**|**) sends the standard output of one command as standard input to another command for further processing.3. A security professional enters **cp vulnerabilities.txt /home/analyst/projects** into the command line. What do they want the operating system to do?

1 / 1 point

- ☐ Create a new file named **vulnerabilities.txt** in the **projects** directory
- ☐ Remove the **vulnerabilities.txt** file from the **projects** directory
- ☒ Copy the **vulnerabilities.txt** file into the **projects** directory
- ☐ Search for the string **vulnerabilities.txt** in the **projects** directory

✔ Correct

They want the operating system to copy the **vulnerabilities.txt** file into the **projects** directory. The original version of the file or directory will also remain in its original location.4. What command creates a new file called **failed_logins.txt**?

1 / 1 point



- ☐ Remove the **vulnerabilities.txt** file from the **projects** directory
- ☒ Copy the **vulnerabilities.txt** file into the **projects** directory
- ☐ Search for the string **vulnerabilities.txt** in the **projects** directory

✔ Correct

They want the operating system to copy the **vulnerabilities.txt** file into the **projects** directory. The original version of the file or directory will also remain in its original location.4. What command creates a new file called **failed_logins.txt**?

1 / 1 point

- ☒ **touch failed_logins.txt**
- ☐ **find failed_logins.txt**
- ☐ **mkdir failed_logins.txt**
- ☐ **rm failed_logins.txt**

✔ Correct

The command **touch failed_logins.txt** creates a new file called **failed_logins.txt**. The **touch** command is used to create a new file.