

Your grade: 100%Your latest: **100%** • Your highest: **100%** • To pass you need at least 75%. We keep your highest score.[Next item →](#)

1. What is authorization?

1 / 1 point

- ☐ The concept of granting only the minimal access and authorization required to complete a task or function
- ☐ The process of temporarily granting elevated permissions to specific users
- ☒ The concept of granting access to specific resources in a system
- ☐ The process of a user proving that they are who they say they are in the system

Correct

Authorization is the concept of granting access to specific resources in a system.

2. Which of the following statements correctly describe the file permissions string `-rw-rw-rw-`? Select two answers.

1 / 1 point

- ☐ The user and group have execute permissions.
- ☒ The user has write permissions.

Correct

Correct

The 3rd character of the file permissions string `-rw-rw-rw-` indicates that the user has write permissions, and the 5th character of the file permissions string `-rw-rw-rw-` indicates that the group has read permissions.

- ☒ The group has read permissions.

Correct

The 3rd character of the file permissions string `-rw-rw-rw-` indicates that the user has write permissions, and the 5th character of the file permissions string `-rw-rw-rw-` indicates that the group has read permissions.

- ☐ The file type is a directory.

3. A security professional enters `chmod g+w access.txt` into the command line. What does this command tell the operating system to do?

1 / 1 point

- ☐ Remove write permissions from the group for the `access.txt` file
- ☒ Add write permissions to the group for the `access.txt` file
- ☐ Add write permissions to the user for the `access.txt` file
- ☐ Remove write permissions from the user for the `access.txt` file

Correct

Correct

The command `chmod g+w access.txt` tells the operating system to add write permissions to the group.4. Which of the following commands typically must be used with `sudo`? Select three answers.

1 / 1 point

- ☒ `useradd`

Correct

The `useradd`, `userdel`, and `chown` commands must typically be used with `sudo`. The `useradd` command adds a user to the system, `userdel` deletes a user from the system, and `chown` changes ownership of a file.

- ☐ `chmod`

- ☒ `userdel`

Correct

The `useradd`, `userdel`, and `chown` commands must typically be used with `sudo`. The `useradd` command adds a user to the system, `userdel` deletes a user from the system, and `chown` changes ownership of a file.

- ☒ `chown`

ownership of a file.

☒ `chown`

☒ Correct

The `useradd`, `userdel`, and `chown` commands must typically be used with `sudo`. The `useradd` command adds a user to the system, `userdel` deletes a user from the system, and `chown` changes ownership of a file.

5. A security analyst is updating permissions on a directory named `projects`. The current permissions are `drwxr-xr-x`. They want to add execute permissions for the group. What do they enter on the command line?

1 / 1 point

☐ `chmod u-x projects`

☐ `chmod x+x projects`

☒ `chmod g+x projects`

☐ `chmod g-x projects`

☒ Correct

They enter `chmod g+x projects`. This command adds execute permissions for the group.