

Your grade: 100%

Your latest: 100% • Your highest: 100% • To pass you need at least 75%. We keep your highest score.

[Next item →](#)

1. You want to open the file `"logs.txt"` and store it in the `file` variable for the purpose of reading it. You also want to ensure all resources are released and the file is closed after you read it. What is the correct line of code to do this?

1 / 1 point

- ☒ `with open("logs.txt", "r") as file:`
- ☐ `with file.open("logs.txt", "r"):`
- ☐ `with open("r", "logs.txt") as file:`
- ☐ `file = open("logs.txt", "r"):`

✓ Correct

The code `with open("logs.txt", "r") as file:` is the correct line of code to do this. The `with` keyword ensures all resources are released while opening and reading the file. This includes ensuring the file is closed after exiting the `with` statement. Then, calling the `open()` function with the file `"logs.txt"` and `"r"` as arguments indicates to read the `"logs.txt"` file. Finally, `as file` specifies to store the file object in the variable `file`.

2. After you've opened a log file as `login_file`, which line of code can you use to read the file and store it in a variable called `login_attempts`?

1 / 1 point

- ☐ `login_attempts = read(login_file)`
- ☒ `login_attempts = login_file.read()`
- ☐ `login_file.read() as login_attempts`
- ☐ `login_attempts = login_file.reader()`

✓ Correct

The code `login_attempts = login_file.read()` reads the log file and stores it in a variable called `login_attempts`. The `.read()` method converts files into strings. The code assigns the string it creates to another variable named `login_attempts`.

3. You just read a log file into a variable called `file`. The `file` variable contains a string of multiple IP addresses that are each separated by a whitespace. Which line of code separates each individual IP address and stores it as a list in a variable called `ip_addresses`?

1 / 1 point

- ☐ `split(file, ip_addresses)`
- ☐ `ip_addresses.split(file)`
- ☐ `ip_addresses = split(file)`
- ☒ `ip_addresses = file.split()`

✓ Correct

The code `ip_addresses = file.split()` separates the individual IP addresses in the `file`

variable and then stores this as a list in a variable called `ip_addresses`. The `.split()` method converts a string into a list. It separates the string based on a character passed into the function as an argument. If a character is not passed in, it will separate the string whenever it encounters a whitespace.

4. You need to check for unusual login activity. Specifically, you need to check a list of login timestamps to determine if any of the login times occurred at unusual hours. If you want to automate this through Python, what would be part of your code? Select two answers.

1 / 1 point

- ☒ A ~~for~~ loop that iterates through the list of timestamps

✓ Correct

The code should include a ~~for~~ loop that iterates through the list of timestamps and an `if` statement that checks if the login timestamp occurred at unusual hours.

- ☐ An `if` statement that checks if a specific user has multiple login timestamps during unusual hours
- ☒ An ~~if~~ statement that checks if the login timestamp occurred at unusual hours

✓ Correct

The code should include a ~~for~~ loop that iterates through the list of timestamps and an `if` statement that checks if the login timestamp occurred at unusual hours.

- ☐ A counter variable that keeps track of the number of failed login attempts