

Messyas

Lab-ex1



Folder is Empty

```
(base) messyas@messyas-B550-GAMER:~/Projetos/wecad$ git init
hint: Using 'master' as the name for the initial branch. This default branch name
hint: is subject to change. To configure the initial branch name to use in all
hint: of your new repositories, which will suppress this warning, call:
hint:
hint:   git config --global init.defaultBranch <name>
hint:
hint: Names commonly chosen instead of 'master' are 'main', 'trunk' and
hint: 'development'. The just-created branch can be renamed via this command:
hint:
hint:   git branch -m <name>
Initialized empty Git repository in /home/messyas/Projetos/wecad/.git/
(base) messyas@messyas-B550-GAMER:~/Projetos/wecad$
```

New repository

github.com/new

Wed Apr 91:05 PM

Create a new repository

A repository contains all project files, including the revision history. Already have a project repository elsewhere? [Import a repository.](#)

Required fields are marked with an asterisk (*).

Owner *

Repository name *

Messyas

/

wecab

wecab is available.

Great repository names are short and memorable. Need inspiration? How about [laughing-invention](#) ?

Description (optional)

teste git

☐ Public

Anyone on the Internet can see this repository. You choose who can commit.

☒ Private

You choose who can see and commit to this repository.

Initialize this repository with:

☐ Add a README file

This is where you can write a long description for your project. [Learn more about READMEs.](#)

Add .gitignore

.gitignore template: None

Choose which files not to track from a list of templates. [Learn more about ignoring files.](#)


Choose a license

License: None

A license tells others what they can and can't do with your code. [Learn more about licenses.](#)

You are creating a private repository in your personal account.

Create repository



```
(base) messyas@messyas-B550-GAMER:~/Projetos/wecad$ git remote add origin git@github.com:Messyas/wecab.git
(base) messyas@messyas-B550-GAMER:~/Projetos/wecad$
```

```
(base) messyas@messyas-B550-GAMER:~/Projetos/wecad$ echo "arquivo de teste" > teste1.txt
(base) messyas@messyas-B550-GAMER:~/Projetos/wecad$ echo "outro arquivo" > teste2.txt
(base) messyas@messyas-B550-GAMER:~/Projetos/wecad$ git add .
(base) messyas@messyas-B550-GAMER:~/Projetos/wecad$ git commit -m "Add arquivos de testes"
On branch master
nothing to commit, working tree clean
(base) messyas@messyas-B550-GAMER:~/Projetos/wecad$ git branch -m master main
(base) messyas@messyas-B550-GAMER:~/Projetos/wecad$ git push -u origin main
Enumerating objects: 4, done.
Counting objects: 100% (4/4), done.
Delta compression using up to 12 threads
Compressing objects: 100% (2/2), done.
Writing objects: 100% (4/4), 292 bytes | 292.00 KiB/s, done.
Total 4 (delta 0), reused 0 (delta 0), pack-reused 0
To github.com:Messyas/wecab.git
 * [new branch]    main -> main
branch 'main' set up to track 'origin/main'.
(base) messyas@messyas-B550-GAMER:~/Projetos/wecad$
```

New File at / - Messyas/v...x +

github.com/Messyas/wecab/new/main

Search Type [7] to search

Cancel changesCommit changes...

CodeIssuesPull requestsActionsProjectsSecurityInsightsSettings

wecab / teste3.txt in main

EditPreview

1 git teste 3

Commit changes

Commit message

Create teste3.txt

Extended description

passo 6

☒ Commit directly to the main branch

☐ Create a new branch for this commit and start a pull request

[Learn more about pull requests](#)

Cancel

Commit changes

Use **Control + Shift + m** to toggle the **tab** key moving focus. Alternatively, use **esc** then **tab** to move to the next interactive element on the page.

```
(base) messyas@messyas-B550-GAMER:~/Projetos/wecad$ git pull
remote: Enumerating objects: 4, done.
remote: Counting objects: 100% (4/4), done.
remote: Compressing objects: 100% (2/2), done.
remote: Total 3 (delta 0), reused 0 (delta 0), pack-reused 0 (from 0)
Unpacking objects: 100% (3/3), 963 bytes | 963.00 KiB/s, done.
From github.com:Messyas/wecad
   c079775..97c80b8  main       -> origin/main
Updating c079775..97c80b8
Fast-forward
 teste3.txt | 1 +
 1 file changed, 1 insertion(+)
 create mode 100644 teste3.txt
(base) messyas@messyas-B550-GAMER:~/Projetos/wecad$
```




```
(base) messyas@messyas-B550-GAMER:~/Projetos/wecad$ git branch novabranch  
(base) messyas@messyas-B550-GAMER:~/Projetos/wecad$
```

```
(base) messyas@messyas-B550-GAMER:~/Projetos/wecad$ git checkout novabranch
Switched to branch 'novabranch'
(base) messyas@messyas-B550-GAMER:~/Projetos/wecad$
```



```
(base) messyas@messyas-B550-GAMER:~/Projetos/wecad$ echo "arquivo de teste da branch nova" > testebranch.txt
(base) messyas@messyas-B550-GAMER:~/Projetos/wecad$
```

```
(base) messyas@messyas-B550-GAMER:~/Projetos/wecad$ echo "att nova branch" >> arquivo.txt
(base) messyas@messyas-B550-GAMER:~/Projetos/wecad$ git add .
(base) messyas@messyas-B550-GAMER:~/Projetos/wecad$ git commit -m "Atualiza recursos"
[novabranh d8cd9b3] Atualiza recursos
 2 files changed, 2 insertions(+)
 create mode 100644 arquivo.txt
 create mode 100644 testebranch.txt
(base) messyas@messyas-B550-GAMER:~/Projetos/wecad$ git push
Enumerating objects: 5, done.
Counting objects: 100% (5/5), done.
Delta compression using up to 12 threads
Compressing objects: 100% (2/2), done.
Writing objects: 100% (4/4), 429 bytes | 429.00 KiB/s, done.
Total 4 (delta 0), reused 0 (delta 0), pack-reused 0
To github.com:Messyas/wecab.git
   97c80b8..d8cd9b3  novabranh -> novabranh
(base) messyas@messyas-B550-GAMER:~/Projetos/wecad$
```



```
(base) messyas@messyas-B550-GAMER:~/Projetos/wecad$ git branch
* main
* novabranch
(base) messyas@messyas-B550-GAMER:~/Projetos/wecad$ git pull origin main
remote: Enumerating objects: 4, done.
remote: Counting objects: 100% (4/4), done.
remote: Compressing objects: 100% (2/2), done.
remote: Total 2 (delta 1), reused 0 (delta 0), pack-reused 0 (from 0)
Unpacking objects: 100% (2/2), 960 bytes | 960.00 KiB/s, done.
From github.com:Messyas/wecad
* branch      main      -> FETCH_HEAD
  a9e6467..399ae179  main    -> origin/main
Updating d8cd9b3..399ae179
Fast-forward
 teste3.txt | 2 +-
 1 file changed, 1 insertion(+), 1 deletion(-)
(base) messyas@messyas-B550-GAMER:~/Projetos/wecad$
```

```
(base) messyas@messyas-B550-GAMER:~/Projetos/wecad$ git branch
* main
* novabranh
(base) messyas@messyas-B550-GAMER:~/Projetos/wecad$ git checkout novabranh
Already on 'novabranh'
Your branch is ahead of 'origin/novabranh' by 2 commits.
  (use "git push" to publish your local commits)
(base) messyas@messyas-B550-GAMER:~/Projetos/wecad$ git add .
(base) messyas@messyas-B550-GAMER:~/Projetos/wecad$ git commit -m "mudancas"
[novabranh 90509af] mudancas
 1 file changed, 1 insertion(+), 1 deletion(-)
(base) messyas@messyas-B550-GAMER:~/Projetos/wecad$ git push
Enumerating objects: 5, done.
Counting objects: 100% (5/5), done.
Delta compression using up to 12 threads
Compressing objects: 100% (2/2), done.
Writing objects: 100% (3/3), 297 bytes | 297.00 KiB/s, done.
Total 3 (delta 1), reused 0 (delta 0), pack-reused 0
remote: Resolving deltas: 100% (1/1), completed with 1 local object.
To github.com:Messyas/wecab.git
   d8cd9b3..90509af  novabranh -> novabranh
(base) messyas@messyas-B550-GAMER:~/Projetos/wecad$
```

```
(base) messyas@messyas-B550-GAMER:~/Projetos/wecad$ git checkout main
Switched to branch 'main'
Your branch is behind 'origin/main' by 3 commits, and can be fast-forwarded.
(use "git pull" to update your local branch)
(base) messyas@messyas-B550-GAMER:~/Projetos/wecad$ git merge novabranh
Updating 97c80bb8..90509af
Fast-forward
 arquivo.txt      | 1 +
 teste3.txt       | 2 +-
 testebranch.txt  | 1 +
 3 files changed, 3 insertions(+), 1 deletion(-)
 create mode 100644 arquivo.txt
 create mode 100644 testebranch.txt
(base) messyas@messyas-B550-GAMER:~/Projetos/wecad$
```



```
(base) messyas@messyas-B550-GAMER:~/Projetos/wecad$ git push origin main
Total 0 (delta 0), reused 0 (delta 0), pack-reused 0
To github.com:Messyas/wecab.git
   399e179..90509af  main -> main
(base) messyas@messyas-B550-GAMER:~/Projetos/wecad$
```