

# WebFamSMS API Documentation

Version 1.0 | September 09, 2026

---

## 1. Overview

---

The WebFamSMS API allows you to send SMS messages programmatically, check your balance, and manage messages. All API requests must be authenticated using a valid API key.

**Base URL:**

<https://sms.webfam.co.ke/api/v1>

(Click to copy)

## 2. Authentication

All API requests require authentication using Bearer Token.

**Your Active API Key:**

WFK-0009\_wda4nx9nVGMxKdbfI7iVXfQPBd11IMtp

(Click to copy)

**Key Name:** Default API Key |

**Created:** 2026-08-11 20:27:38

| **Last Used:** 4 days ago

**Authorization Header:**

Authorization: Bearer

WFK-0009\_wda4nx9nVGMxKdbfI7iVXfQPBd11IMtp

(Click to copy)

**Note:** Your API key can be generated or regenerated from the Developer > API Keys section.

## 3. Rate Limits

| Plan       | Rate Limit              | Burst Limit            |
|------------|-------------------------|------------------------|
| Free       | 100 requests per minute | 10 requests per second |
| Pro        | 500 requests per minute | 50 requests per second |
| Enterprise | Unlimited               | Custom                 |

**Note:** Rate limits are applied per API key. Contact support for higher limits.

## 4. API Endpoints

### POST /sms/send

Send a single SMS to a recipient

URL: <https://sms.webfam.co.ke/api/v1/sms/send> (Click to copy)

#### Parameters:

| Name      | Type   | Required | Description                                 |
|-----------|--------|----------|---------------------------------------------|
| to        | string | Yes      | Recipient phone number (e.g., 254712345678) |
| message   | string | Yes      | SMS content (max 1600 characters)           |
| sender_id | string | No       | Sender ID (must be approved)                |

#### Example Request:

```
{
  "to": "254712345678",
  "message": "Hello from WebFamSMS API",
  "sender_id": "WebFamSMS"
}
```

 (Click to copy)

#### Example Response:

```
{
  "success": true,
  "data": {
    "message_id": 123,
    "status": "sent",
    "recipient": "254712345678",
    "cost": 1.5,
    "balance_remaining": 2000
  }
}
```

 (Click to copy)

#### Status Codes:

- 422** `VALIDATION_ERROR` - Invalid input parameters
- 400** `INSUFFICIENT_BALANCE` - Not enough SMS credits
- 400** `SEND_FAILED` - Failed to send SMS

### cURL Command:

```
curl -X POST https://sms.webfam.co.ke/api/v1/sms/send \
  -H "Authorization: Bearer WFK-0009_wda4nx9nVGMxKdbfI7iVXfQPbd1lIMtp" \
  -H "Content-Type: application/json" \
  -d '{"to":"254712345678","message":"Hello from WebFamSMS API","sender_id":"WebFamSMS"}' (Click to copy)
```

### POST /sms/bulk

Send bulk SMS to multiple recipients (max 100 per request)

URL: <https://sms.webfam.co.ke/api/v1/sms/bulk> (Click to copy)

#### Parameters:

| Name                    | Type   | Required | Description                       |
|-------------------------|--------|----------|-----------------------------------|
| <code>recipients</code> | array  | Yes      | List of phone numbers (max 100)   |
| <code>message</code>    | string | Yes      | SMS content (max 1600 characters) |
| <code>sender_id</code>  | string | No       | Sender ID (must be approved)      |

#### Example Request:

```
{
  "recipients": [
    "254712345678",
    "254798765432"
  ],
  "message": "Hello from WebFamSMS API",
  "sender_id": "WebFamSMS"
} (Click to copy)
```

### Example Response:

```
{
  "success": true,
  "data": {
    "total": 2,
    "sent": 2,
    "failed": 0,
    "failed_recipients": [],
    "total_cost": 3,
    "message_ids": [
      124,
      125
    ]
  }
}
```

(Click to copy)

### Status Codes:

422

VALIDATION\_ERROR - Invalid input parameters

400

INSUFFICIENT\_BALANCE - Not enough SMS credits

400

SEND\_FAILED - Failed to send SMS

### cURL Command:

```
curl -X POST https://sms.webfam.co.ke/api/v1/sms/bulk \
-H "Authorization: Bearer WFK-0009_wda4nx9nVGMxKdbfI7iVXfQPbd1lIMtp" \
-H "Content-Type: application/json" \
-d '{"recipients":["254712345678","254798765432"],"message":"Hello from WebFamSMS API","sender_id":"WebFamSMS"}'
```

(Click to copy)

POST

/sms/schedule

Schedule an SMS for future delivery

URL: <https://sms.webfam.co.ke/api/v1/sms/schedule> (Click to copy)

### Parameters:

| Name                      | Type     | Required | Description                                   |
|---------------------------|----------|----------|-----------------------------------------------|
| <code>to</code>           | string   | Yes      | Recipient phone number                        |
| <code>message</code>      | string   | Yes      | SMS content                                   |
| <code>scheduled_at</code> | datetime | Yes      | Scheduled delivery time (Format: Y-m-d H:i:s) |
| <code>timezone</code>     | string   | No       | Timezone (e.g., Africa/Nairobi, default: UTC) |
| <code>sender_id</code>    | string   | No       | Sender ID (must be approved)                  |

### Example Request:

```
{
  "to": "254712345678",
  "message": "Happy Birthday! \ud83c\udf82",
  "scheduled_at": "2026-08-10 09:00:00",
  "timezone": "Africa\Nairobi",
  "sender_id": "WebFamSMS"
} (Click to copy)
```

### Example Response:

```
{
  "success": true,
  "data": {
    "message_id": 124,
    "status": "scheduled",
    "recipient": "254712345678",
    "scheduled_at": "2026-08-10 09:00:00",
    "cost": 1.5
  }
} (Click to copy)
```

### Status Codes:

- 422** `VALIDATION_ERROR` - Invalid input parameters
- 400** `SCHEDULE_FAILED` - Failed to schedule SMS
- 400** `INSUFFICIENT_BALANCE` - Not enough SMS credits

#### cURL Command:

```
curl -X POST https://sms.webfam.co.ke/api/v1/sms/schedule \  
  -H "Authorization: Bearer WFK-0009_wda4nx9nVGMxKdbfI7iVXfQPBd1lIMtp" \  
  -H "Content-Type: application/json" \  
  -d '{"to":"254712345678","message":"Happy  
Birthday!","scheduled_at":"2026-08-10 09:00:00","timezone":"Africa/  
Nairobi","sender_id":"WebFamSMS"}' (Click to copy)
```

**DELETE****/sms/schedule/{id}**

Cancel a scheduled SMS message

URL: <https://sms.webfam.co.ke/api/v1/sms/schedule/{id}> (Click to copy)

Parameters:

| Name | Type    | Required | Description          |
|------|---------|----------|----------------------|
| id   | integer | Yes      | Scheduled message ID |

Example Response:

```
{
  "success": true,
  "message": "Scheduled message cancelled successfully",
  "data": {
    "message_id": 124,
    "status": "cancelled"
  }
}
```

 (Click to copy)

Status Codes:

**404**

NOT\_FOUND

- Scheduled message not found

**401**

UNAUTHORIZED

- Invalid or missing API key

**400**

CANCEL\_FAILED

- Failed to cancel scheduled message

cURL Command:

```
curl -X DELETE https://sms.webfam.co.ke/api/v1/sms/schedule/124 \
  -H "Authorization: Bearer WFK-0009_wda4nx9nVGMxKdbfI7iVXfQPBd1lIMtp" (Click
to copy)
```



**GET**

## /account/balance

Check your current SMS credit balance

URL: <https://sms.webfam.co.ke/api/v1/account/balance> (Click to copy)

### Example Response:

```
{
  "success": true,
  "data": {
    "balance": 1000,
    "currency": "SMS Credits",
    "low_balance_threshold": 100,
    "is_low": false
  }
}
```

 (Click to copy)

### Status Codes:

**401**

UNAUTHORIZED

- Invalid or missing API key

### cURL Command:

```
curl -X GET https://sms.webfam.co.ke/api/v1/account/balance \
-H "Authorization: Bearer WFK-0009_wda4nx9nVGMxKdbfI7iVXfQPBd11IMtp" (Click
to copy)
```

**GET**

## /messages

Get your SMS history with optional filters

URL: <https://sms.webfam.co.ke/api/v1/messages> (Click to copy)

#### Parameters:

| Name                    | Type    | Required | Description                                           |
|-------------------------|---------|----------|-------------------------------------------------------|
| <code>page</code>       | integer | No       | Page number (default: 1)                              |
| <code>limit</code>      | integer | No       | Records per page (default: 20, max: 100)              |
| <code>status</code>     | string  | No       | Filter by status (sent, delivered, failed, scheduled) |
| <code>start_date</code> | date    | No       | Filter from date (Y-m-d)                              |
| <code>end_date</code>   | date    | No       | Filter to date (Y-m-d)                                |

#### Example Response:

```
{
  "success": true,
  "data": {
    "current_page": 1,
    "per_page": 20,
    "total": 150,
    "last_page": 8,
    "messages": [
      {
        "id": 123,
        "recipients": [
          "254712345678"
        ],
        "message": "Hello from WebFamSMS API",
        "sender_id": "WebFamSMS",
        "status": "sent",
        "cost": 1.5,
        "created_at": "2026-08-09T14:30:00Z",
        "sent_at": "2026-08-09T14:30:05Z"
      }
    ]
  }
}
```

#### Status Codes:

**401**

UNAUTHORIZED

- Invalid or missing API key

#### cURL Command:

```
curl -X GET https://sms.webfam.co.ke/api/v1/messages?
page=1&limit=20&status=sent \
-H "Authorization: Bearer WFK-0009_wda4nx9nVGMxKdbfI7iVXfQPBd1lIMtp" (Click
to copy)
```

**GET****/messages/{id}**

Get details of a specific SMS message

URL: <https://sms.webfam.co.ke/api/v1/messages/{id}> (Click to copy)

Parameters:

| Name            | Type    | Required | Description |
|-----------------|---------|----------|-------------|
| <code>id</code> | integer | Yes      | Message ID  |

Example Response:

```
{
  "success": true,
  "data": {
    "id": 123,
    "recipients": [
      "254712345678"
    ],
    "recipient_count": 1,
    "message": "Hello from WebFamSMS API",
    "sender_id": "WebFamSMS",
    "status": "sent",
    "message_count": 1,
    "cost": 1.5,
    "created_at": "2026-08-09T14:30:00Z",
    "scheduled_for": null,
    "sent_at": "2026-08-09T14:30:05Z",
    "gateway_response": null
  }
}
```

(Click to copy)

Status Codes:

**404**

NOT\_FOUND

- Message not found

**401**

UNAUTHORIZED

- Invalid or missing API key

cURL Command:

```
curl -X GET https://sms.webfam.co.ke/api/v1/messages/123 \
  -H "Authorization: Bearer WFK-0009_wda4nx9nVGMxKdbfI7iVXfQPBd1lIMtp" (Click
to copy)
```

**GET****/messages/status/{id}**

Get the delivery status of a specific message

URL: <https://sms.webfam.co.ke/api/v1/messages/status/{id}> (Click to copy)

#### Parameters:

| Name            | Type    | Required | Description |
|-----------------|---------|----------|-------------|
| <code>id</code> | integer | Yes      | Message ID  |

#### Example Response:

```
{
  "success": true,
  "data": {
    "message_id": 123,
    "status": "delivered",
    "recipient": "254712345678",
    "sent_at": "2026-08-09T14:30:05Z",
    "delivered_at": "2026-08-09T14:30:10Z",
    "cost": 1.5,
    "delivery_report": {
      "network": "Safaricom",
      "dlr_code": "000",
      "dlr_description": "Delivered"
    }
  }
}
```

 (Click to copy)

#### Status Codes:

**404**

NOT\_FOUND

- Message not found

**401**

UNAUTHORIZED

- Invalid or missing API key

#### cURL Command:

```
curl -X GET https://sms.webfam.co.ke/api/v1/messages/status/123 \
-H "Authorization: Bearer WFK-0009_wda4nx9nVGMxKdbfI7iVXfQPBd1lIMtp" (Click
to copy)
```

**GET**

## /sender-ids

Get all approved Sender IDs for your account

URL: <https://sms.webfam.co.ke/api/v1/sender-ids> (Click to copy)

### Example Response:

```
{
  "success": true,
  "data": [
    {
      "id": 1,
      "sender_id": "WebFamSMS",
      "status": "approved",
      "is_default": true,
      "created_at": "2026-08-01T10:00:00Z"
    },
    {
      "id": 2,
      "sender_id": "MyBiz",
      "status": "approved",
      "is_default": false,
      "created_at": "2026-08-05T14:30:00Z"
    }
  ]
}
```

(Click to copy)

### Status Codes:

**401**

UNAUTHORIZED

- Invalid or missing API key

### cURL Command:

```
curl -X GET https://sms.webfam.co.ke/api/v1/sender-ids \
-H "Authorization: Bearer WFK-0009_wda4nx9nVGMxKdbfI7iVXfQPBd1lIMtp" (Click
to copy)
```

## 5. Error Codes

| Status Code | Error Code       | Description                | Example                                                       |
|-------------|------------------|----------------------------|---------------------------------------------------------------|
| 200         | —                | Success                    | <code>{"success": true}</code>                                |
| 400         | INVALID_REQUEST  | Invalid request parameters | <code>{"error": "Invalid phone number"}</code>                |
| 401         | UNAUTHORIZED     | Invalid or missing API key | <code>{"error": "Unauthorized"}</code>                        |
| 403         | FORBIDDEN        | Insufficient permissions   | <code>{"error": "Forbidden"}</code>                           |
| 404         | NOT_FOUND        | Resource not found         | <code>{"error": "Message not found"}</code>                   |
| 422         | VALIDATION_ERROR | Validation failed          | <code>{"errors": {"to": ["The to field is required"]}}</code> |
| 429         | RATE_LIMIT       | Rate limit exceeded        | <code>{"error": "Too many requests"}</code>                   |
| 500         | SERVER_ERROR     | Internal server error      | <code>{"error": "Internal server error"}</code>               |